

Client Command Guide

This guide shows the exact commands for using the system in a simple way.

1. Simple Workflow

Use the system in this order:

1. Check the service is alive with `/health`.
2. Create or list your sender hierarchy with `/cpanel-create`, `/subdomain-create`, and `/email-create`.
3. Create an SMTP account with `/smtp-create`.
4. Upload or send your email list into the system with `/ingest`.
5. Create a campaign with `/campaign-create`.
6. Send that campaign to one specific dataset with `/campaign-send`.
7. Use `/status`, `/queue`, `/metrics`, `/logs`, `/smtp-status`, and `/smtp-failures` to check results.

Important:

- Campaign sends are dataset-scoped. You must choose a `dataset_id` when sending.
- The system will not send a campaign to the whole recipient table.

2. Discord Commands

Service and monitoring

Command	What it does	Example
<code>/health</code>	Checks whether the service is running.	<code>/health</code>
<code>/status</code>	Shows the latest job summary, or one specific job if you provide a job id.	<code>/status</code> or <code>/status job_id: <job-id></code>
<code>/queue</code>	Shows queue counts for ingestion and sending.	<code>/queue</code>
<code>/metrics</code>	Shows total job counts and SMTP usage totals.	<code>/metrics</code>
<code>/logs</code>	Shows recent logs. You can choose how many lines to show.	<code>/logs limit:50</code>
<code>/pause</code>	Pauses ingestion and sending queues.	<code>/pause</code>
<code>/resume</code>	Resumes ingestion and sending queues.	<code>/resume</code>

Sending window

Command	What it does	Example
<code>/window-show</code>	Shows the current sending window settings.	<code>/window-show</code>

Command	What it does	Example
<code>/window-update</code>	Updates the sending window settings.	<code>/window-update hours:6 interval_hours:6 start_hour:0 start_minute:0 timezone:Asia/Karachi</code>

cPanel hierarchy

Command	What it does	Example
<code>/cpanel-create</code>	Creates a cPanel account group.	<code>/cpanel-create name:Main</code>
<code>/cpanel-list</code>	Lists all cPanel account groups.	<code>/cpanel-list</code>
<code>/subdomain-create</code>	Creates a subdomain under a cPanel group.	<code>/subdomain-create cpanel_id:<cpanel-id> name:mail</code>
<code>/subdomain-list</code>	Lists subdomains. You can filter by cPanel id.	<code>/subdomain-list</code> or <code>/subdomain-list cpanel_id:<cpanel-id></code>
<code>/email-create</code>	Creates an email account under a subdomain.	<code>/email-create subdomain_id:<subdomain-id> address:sender@example.com</code>
<code>/email-list</code>	Lists email accounts. You can filter by subdomain id.	<code>/email-list</code> or <code>/email-list subdomain_id:<subdomain-id></code>
<code>/accounts-status</code>	Shows account status overview.	<code>/accounts-status</code>

SMTP accounts

Command	What it does	Example
<code>/smtp-create</code>	Creates a new SMTP account.	<code>/smtp-create email_account_id:<email-account-id> host:smtp.gmail.com username:sender@gmail.com password:<app-password> port:587 use_tls:true max_per_window:50 max_concurrent:1</code>
<code>/smtp-update</code>	Updates an existing SMTP account.	<code>/smtp-update id:<smtp-id> host:smtp.gmail.com port:587 username:sender@gmail.com password:<new-password> use_tls:true max_per_window:50 max_concurrent:1</code>
<code>/smtp-status</code>	Shows active SMTP accounts.	<code>/smtp-status</code>
<code>/smtp-usage</code>	Shows SMTP usage for a specific window, or recent windows if no window id is provided.	<code>/smtp-usage</code> or <code>/smtp-usage window_id:<window-id></code>

Command	What it does	Example
<code>/smtp-failures</code>	Shows recent SMTP failures.	<code>/smtp-failures</code>
<code>/smtp-disable</code>	Disables one SMTP account.	<code>/smtp-disable id:<smtp-id></code>
<code>/smtp-enable</code>	Re-enables one SMTP account.	<code>/smtp-enable id:<smtp-id></code>

Ingestion

Command	What it does	Example
<code>/ingest</code>	Imports email data into the system.	<code>/ingest format:csv content:"name,email\nA,first@example.com"</code>

Accepted formats:

- `csv`
- `json`
- `txt`
- `raw`
- `bulk`

You can send data in these ways:

- `content` for pasted text
- `source_path` for a file path or URL
- `file` for an attached file

Example:

- `/ingest format:csv source_path:s3://bucket/file.csv`
- `/ingest format:txt content:"test1@example.com test2@example.com"`

Campaigns

Command	What it does	Example
<code>/campaign-create</code>	Creates a campaign.	<code>/campaign-create name:Promo subject:Hello body_html:<p>Hello</p> from_address:sender@example.com reply_to:reply@example.com</code>
<code>/campaign-update</code>	Updates an existing campaign.	<code>/campaign-update id:<campaign-id> subject:New Subject status:active</code>
<code>/campaign-list</code>	Lists campaigns.	<code>/campaign-list</code>

Command	What it does	Example
<code>/campaign-send</code>	Sends one campaign to one dataset only. <code>dataset_id</code> is required.	<code>/campaign-send id:<campaign-id> dataset_id:<dataset-id></code>

Important campaign rules:

- `from_address` is required when creating a campaign.
- `reply_to` is optional.
- When sending, you must provide `dataset_id`.
- The campaign will only send to recipients from that dataset.

3. What Each Command Is For

- Use `/health` when you want a quick yes/no check.
- Use `/ingest` when you have a new list of emails.
- Use `/campaign-create` when you want to prepare an email message.
- Use `/campaign-send` when you are ready to send to one dataset.
- Use `/smtp-create` when you want to connect an SMTP mailbox for sending.
- Use `/queue`, `/status`, `/metrics`, and `/logs` when you want to confirm the system is working.

4. Recommended Testing Order

1. Run `/health`.
2. Run `/cpanel-list`, `/subdomain-list`, and `/email-list` to confirm sender structure.
3. Run `/smtp-status` to confirm SMTP is active.
4. Run `/ingest` for your test email list.
5. Check `/status` until the ingest job is completed.
6. Run `/campaign-create`.
7. Run `/campaign-send` using the `dataset_id` from the ingest result.
8. Check `/queue`, `/metrics`, and `/logs`.
9. If mail does not arrive, check `/smtp-failures` and `/smtp-usage`.

5. Reference API Commands

If you prefer HTTP or need to integrate with another tool, these are the exact API endpoints.

Method	Endpoint	What it does
GET	<code>/health</code>	Service health
POST	<code>/ingest</code>	Start an ingest job
GET	<code>/status</code>	Job summary or one job
GET	<code>/queue</code>	Queue counts
GET	<code>/metrics</code>	Overall metrics

Method	Endpoint	What it does
GET	/logs	Recent logs
POST	/control/pause	Pause queues
POST	/control/resume	Resume queues
POST	/accounts/cpanel	Create cPanel group
GET	/accounts/cpanel	List cPanel groups
POST	/accounts/subdomain	Create subdomain
GET	/accounts/subdomain	List subdomains
POST	/accounts/email	Create email account
GET	/accounts/email	List email accounts
POST	/smtp/account	Create SMTP account
GET	/smtp/accounts	List SMTP accounts
PUT	/smtp/account/:id	Update SMTP account
POST	/smtp/account/:id/disable	Disable SMTP account
POST	/smtp/account/:id/enable	Enable SMTP account
GET	/smtp/status	Active SMTP accounts
GET	/smtp/usage	SMTP usage
GET	/smtp/failures	SMTP failures
POST	/campaigns	Create campaign
PUT	/campaigns/:id	Update campaign
GET	/campaigns	List campaigns
POST	/campaigns/:id/send	Send campaign to a dataset

API note:

- For `/campaigns/:id/send`, send `datasetId` in the request body.

6. Important Notes

- Do not use `smtp-list`; that command does not exist.
- Use `/smtp-status` instead.
- `campaign-send` needs a dataset id.
- If you want to test only one new file upload, use the dataset id from that upload.
- If you want help understanding a result, check `/status` first, then `/logs`.