

AngularJS to Angular Quick Reference

{@a top}

Angular is the name for the Angular of today and tomorrow. *AngularJS* is the name for all v1.x versions of Angular.

This guide helps you transition from AngularJS to Angular by mapping AngularJS syntax to the equivalent Angular syntax.

See the Angular syntax in this .

Template basics

Templates are the user-facing part of an Angular application and are written in HTML. The following table lists some of the key AngularJS template features with their equivalent Angular template syntax.

AngularJS	Angular
<p>### Bindings/interpolation Your favorite hero is: <code>{{vm.favoriteHero}}</code> In AngularJS, an expression in curly braces denotes one-way binding. This binds the value of the element to a property in the controller associated with this template. When using the <code>`controller as`</code> syntax, the binding is prefixed with the controller alias (<code>`vm`</code> or <code>`\$ctrl`</code>) because you have to be specific about the source of the binding.</p>	<p>### Bindings/interpolation In Angular, a template expression in curly braces still denotes one-way binding. This binds the value of the element to a property of the component. The context of the binding is implied and is always the associated component, so it needs no reference variable. For more information, see the [Interpolation](guide/template-syntax#interpolation) section of the [Template Syntax](guide/template-syntax) page.</p>
<p>### Filters <code><td>{{movie.title uppercase}}</td></code> To filter output in AngularJS templates, use the pipe character (<code> </code>) and one or more filters. This example filters the <code>`title`</code> property to uppercase.</p>	<p>### Pipes In Angular you use similar syntax with the pipe (<code> </code>) character to filter output, but now you call them pipes. Many (but not all) of the built-in filters from AngularJS are built-in pipes in Angular. For more information, see [Filters/pipes](guide/ajs-quick-reference#filters-pipes) below.</p>
<p>### Local variables <code><tr ng-repeat="movie in vm.movies"> <td>{{movie.title}}</td> </tr></code> Here, <code>`movie`</code> is a user-defined local variable.</p>	<p>### Input variables Angular has true template input variables that are explicitly defined using the <code>`let`</code> keyword. For more information, see the [ngFor micro-syntax](guide/template-syntax#microsyntax) section of the [Template Syntax](guide/template-syntax) page.</p>

Template directives

AngularJS provides more than seventy built-in directives for templates. Many of them aren't needed in Angular because of its more capable and expressive binding system. The following are some of the key AngularJS built-in directives and their equivalents in Angular.

AngularJS	Angular
<p>### ng-app <code><body ng-app="movieHunter"></code> The application startup process is called bootstrapping. Although you can bootstrap an AngularJS app in code, many applications bootstrap declaratively with the <code>`ng-app`</code> directive,</p>	<p>### Bootstrapping Angular doesn't have a bootstrap directive. To launch the app in code, explicitly bootstrap the application's root module (<code>`AppModule`</code>) in <code>`main.ts`</code> and</p>

<p>giving it the name of the application's module (`movieHunter`).</p>	<p>the application's root component (`AppComponent`) in `app.module.ts`.</p>
<p>### ng-class <div ng-class="{active: isActive}"> <div ng-class="{active: isActive, shazam: isImportant}"> In AngularJS, the `ng-class` directive includes/excludes CSS classes based on an expression. That expression is often a key-value control object with each key of the object defined as a CSS class name, and each value defined as a template expression that evaluates to a Boolean value. In the first example, the `active` class is applied to the element if `isActive` is true. You can specify multiple classes, as shown in the second example.</p>	<p>### ngClass In Angular, the `ngClass` directive works similarly. It includes/excludes CSS classes based on an expression. In the first example, the `active` class is applied to the element if `isActive` is true. You can specify multiple classes, as shown in the second example. Angular also has class binding, which is a good way to add or remove a single class, as shown in the third example. For more information see the [Attribute, class, and style bindings](guide/template-syntax#other-bindings) section of the [Template Syntax](guide/template-syntax) page.</p>
<p>### ng-click <button ng-click="vm.toggleImage()"> <button ng-click="vm.toggleImage(\$event)"> In AngularJS, the `ng-click` directive allows you to specify custom behavior when an element is clicked. In the first example, when the user clicks the button, the `toggleImage()` method in the</p>	<p>### Bind to the `click` event AngularJS event-based directives do not exist in Angular. Rather, define one-way binding from the template view to the component using event binding. For event binding, define the name of the target event within parenthesis and specify a template statement, in quotes, to the right of the equals. Angular then sets up an event handler for the target event. When the event is raised, the handler executes the template statement. In the first example, when a user clicks</p>

<p>controller referenced by the <code>`vm`</code> <code>`controller as`</code> alias is executed. The second example demonstrates passing in the <code>`\$event`</code> object, which provides details about the event to the controller.</p>	<p>the button, the <code>`toggleImage()`</code> method in the associated component is executed. The second example demonstrates passing in the <code>`\$event`</code> object, which provides details about the event to the component. For a list of DOM events, see: https://developer.mozilla.org/en-US/docs/Web/Events. For more information, see the [Event binding](guide/template-syntax#event-binding) section of the [Template Syntax](guide/template-syntax) page.</p>
<p>### ng-controller <code><div ng-controller="MovieListCtrl as vm"></code> In AngularJS, the <code>`ng-controller`</code> directive attaches a controller to the view. Using the <code>`ng-controller`</code> (or defining the controller as part of the routing) ties the view to the controller code associated with that view.</p>	<p>### Component decorator In Angular, the template no longer specifies its associated controller. Rather, the component specifies its associated template as part of the component class decorator. For more information, see [Architecture Overview](guide/architecture#components).</p>
<p>### ng-hide In AngularJS, the <code>`ng-hide`</code> directive shows or hides the associated HTML element based on an expression. For more information, see [ng-show](guide/ajs-quick-reference#ng-show).</p>	<p>### Bind to the <code>`hidden`</code> property In Angular, you use property binding; there is no built-in <code>*hide*</code> directive. For more information, see [ng-show](guide/ajs-quick-reference#ng-show).</p>
<p>### ng-href <code><a ng-href="{{ angularDocsUrl }}">Angular Docs</code> The <code>`ng-</code></p>	<p>### Bind to the <code>`href`</code> property Angular uses property binding; there is no built-in <code>*href*</code> directive. Place the element's <code>`href`</code> property in square brackets and set it to a quoted template expression. For more information see the [Property binding]</p>

`href` directive allows AngularJS to preprocess the `href` property so that it can replace the binding expression with the appropriate URL before the browser fetches from that URL. In AngularJS, the `ng-href` is often used to activate a route as part of navigation. <a ng-href="#{{ moviesHash }}">Movies Routing is handled differently in Angular.`

([guide/template-syntax#property-binding](#)) section of the [Template Syntax]([guide/template-syntax](#)) page. In Angular, ``href`` is no longer used for routing. Routing uses ``routerLink``, as shown in the following example. For more information on routing, see the [RouterLink binding]([guide/router#router-link](#)) section of the [Routing & Navigation]([guide/router](#)) page.

`ng-if`` `<table ng-if="movies.length">` In AngularJS, the ``ng-if`` directive removes or recreates a portion of the DOM, based on an expression. If the expression is false, the element is removed from the DOM. In this example, the ``` element is removed from the DOM unless the ``movies`` array has a length greater than zero.

`*ngIf`` The ``*ngIf`` directive in Angular works the same as the ``ng-if`` directive in AngularJS. It removes or recreates a portion of the DOM based on an expression. In this example, the ``` element is removed from the DOM unless the ``movies`` array has a length. The `(*)` before ``ngIf`` is required in this example. For more information, see [Structural Directives]([guide/structural-directives](#)). ``` element repeats for each movie object in the collection of movies. ``` in this example) and its contents into a template and uses that template to instantiate a view for each item in the list. Notice the other syntax differences: The `(*)` before ``ngFor`` is required; the ``let`` keyword identifies ``movie`` as an input variable; the list preposition is ``of``, not ``in``. For more information, see [Structural Directives]([guide/structural-directives](#)).

`ng-model`` `<input ng-`

`ngModel`` In Angular, `**two-way binding**` is denoted by ``[]``, descriptively referred to as a "banana in a box". This syntax is a shortcut for defining both property binding (from

`model="vm.favoriteHero"/>` In AngularJS, the ``ng-model`` directive binds a form control to a property in the controller associated with the template. This provides **two-way binding**, whereby any change made to the value in the view is synchronized with the model, and any change to the model is synchronized with the value in the view.

the component to the view) and event binding (from the view to the component), thereby providing two-way binding. For more information on two-way binding with ``ngModel``, see the [NgModel—Two-way binding to form elements with ``[(ngModel)]``]([../guide/template-syntax.html#ngModel](#)) section of the [Template Syntax]([guide/template-syntax](#)) page.

`ng-repeat` `<tr ng-repeat="movie in vm.movies">` In AngularJS, the ``ng-repeat`` directive repeats the associated DOM element for each item in the specified collection. In this example, the table row (```

`*ngFor` The ``*ngFor`` directive in Angular is similar to the ``ng-repeat`` directive in AngularJS. It repeats the associated DOM element for each item in the specified collection. More accurately, it turns the defined element (```

Bind to the ``hidden`` property Angular uses property binding; there is no built-in `*show*` directive. For hiding and showing elements, bind to the HTML ``hidden`` property. To

ng-show <h3 ng-show="vm.favoriteHero"> Your favorite hero is: {{vm.favoriteHero}} </h3> In AngularJS, the `ng-show` directive shows or hides the associated DOM element, based on an expression. In this example, the `element` is shown if the `favoriteHero` variable is truthy.

conditionally display an element, place the element's `hidden` property in square brackets and set it to a quoted template expression that evaluates to the *opposite* of *show*. In this example, the `element` is hidden if the `favoriteHero` variable is not truthy. For more information on property binding, see the [Property binding] (guide/template-syntax#property-binding) section of the [Template Syntax] (guide/template-syntax) page.

ng-src The `ng-src` directive allows AngularJS to preprocess the `src` property so that it can replace the binding expression with the appropriate URL before the browser fetches from that URL.

Bind to the `src` property Angular uses property binding; there is no built-in *src* directive. Place the `src` property in square brackets and set it to a quoted template expression. For more information on property binding, see the [Property binding] (guide/template-syntax#property-binding) section of the [Template Syntax] (guide/template-syntax) page.

page.

ng-style <div ng-style="{color: colorPreference}"> In AngularJS, the `ng-style` directive sets a CSS style on an HTML element based on an expression. That expression is often a key-value control object with each key of the object defined as a CSS property, and each value defined as an expression that evaluates to a value appropriate for the style. In the example, the `color` style is set to the current value of the `colorPreference` variable.

ngStyle In Angular, the `ngStyle` directive works similarly. It sets a CSS style on an HTML element based on an expression. In the first example, the `color` style is set to the current value of the `colorPreference` variable. Angular also has **style binding**, which is good way to set a single style. This is shown in the second example. For more information on style binding, see the [Style binding](guide/template-syntax#style-binding) section of the [Template Syntax](guide/template-syntax) page. For more information on the `ngStyle` directive, see [NgStyle](guide/template-syntax#ngStyle) section of the [Template Syntax](guide/template-syntax) page.

ngSwitch In Angular, the `ngSwitch` directive works similarly. It displays an element whose `*ngSwitchCase` matches the current `ngSwitch` expression


```
### ng-switch <div ng-switch="vm.favoriteHero && vm.checkMovieHero(vm.favoriteHero)">
<div ng-switch-when="true"> Excellent
choice! </div> <div ng-switch-when="false"> No movie, sorry! </div>
<div ng-switch-default> Please enter
your favorite hero. </div> </div>
```

In AngularJS, the `ng-switch` directive swaps the contents of an element by selecting one of the templates based on the current value of an expression. In this example, if `favoriteHero`` is not set, the template displays "Please enter ...". If `favoriteHero`` is set, it checks the movie hero by calling a controller method. If that method returns ``true``, the template displays "Excellent choice!". If that methods returns ``false``, the template displays "No movie, sorry!".

value. In this example, if `favoriteHero`` is not set, the `ngSwitch`` value is ``null`` and `*ngSwitchDefault`` displays, "Please enter ...". If `favoriteHero`` is set, the app checks the movie hero by calling a component method. If that method returns ``true``, the app selects `*ngSwitchCase="true"` and displays: "Excellent choice!" If that methods returns ``false``, the app selects `*ngSwitchCase="false"` and displays: "No movie, sorry!" The (*) before `ngSwitchCase`` and `ngSwitchDefault`` is required in this example. For more information, see [The NgSwitch directives](guide/template-syntax#ngSwitch) section of the [Template Syntax](guide/template-syntax) page.

{@a filters-pipes}

Filters/pipes

Angular **pipes** provide formatting and transformation for data in the template, similar to AngularJS **filters**. Many of the built-in filters in AngularJS have corresponding pipes in Angular. For more information on

pipes, see [Pipes](#).

AngularJS	Angular
### currency <code><td>{{movie.price currency}}</td></code> Formats a number as currency.	### currency The Angular <code>`currency`</code> pipe is similar although some of the parameters have changed.
### date <code><td>{{movie.releaseDate date}}</td></code> Formats a date to a string based on the requested format.	### date The Angular <code>`date`</code> pipe is similar.
### filter <code><tr ng-repeat="movie in movieList filter: {title: listFilter}"></code> Selects a subset of items from the defined collection, based on the filter criteria.	### none For performance reasons, no comparable pipe exists in Angular. Do all your filtering in the component. If you need the same filtering code in several templates, consider building a custom pipe.
### json <code><pre>{{movie json}}</pre></code> Converts a JavaScript object into a JSON string. This is useful for debugging.	### json The Angular <code>`json`</code> pipe does the same thing.
### limitTo <code><tr ng-repeat="movie in movieList limitTo:2:0"></code> Selects up to the first parameter (2) number of items from the collection starting (optionally) at the beginning index (0).	### slice The <code>`SlicePipe`</code> does the same thing but the <i>*order of the parameters is reversed*</i> , in keeping with the JavaScript <code>`Slice`</code> method. The first parameter is the starting index; the second is the limit. As in AngularJS, coding this operation within the component instead could improve performance.
### lowercase <code><div>{{movie.title lowercase}}</div></code> Converts the string to	### lowercase The Angular <code>`lowercase`</code> pipe does the same

lowercase.	thing.
<pre>### number <td> {{movie.starRating number}} </td> Formats a number as text.</pre>	<pre>### number The Angular `number` pipe is similar. It provides more functionality when defining the decimal places, as shown in the second example above. Angular also has a `percent` pipe, which formats a number as a local percentage as shown in the third example.</pre>
<pre>### orderBy <tr ng- repeat="movie in movieList orderBy : 'title'"> Displays the collection in the order specified by the expression. In this example, the movie title orders the `movieList`.</pre>	<pre>### none For performance reasons, no comparable pipe exists in Angular. Instead, use component code to order or sort results. If you need the same ordering or sorting code in several templates, consider building a custom pipe.</pre>

{@a controllers-components}

Modules/controllers/components

In both AngularJS and Angular, modules help you organize your application into cohesive blocks of functionality.

In AngularJS, you write the code that provides the model and the methods for the view in a **controller**. In Angular, you build a **component**.

Because much AngularJS code is in JavaScript, JavaScript code is shown in the AngularJS column. The Angular code is shown using TypeScript.

AngularJS	Angular
<pre>### IIFE (function () { ... })(); In</pre>	<pre>### none This is a nonissue in Angular because ES 2015</pre>

<p>AngularJS, an immediately invoked function expression (or IIFE) around controller code keeps it out of the global namespace.</p>	<p>modules handle the namespacing for you. For more information on modules, see the [Modules] (guide/architecture#modules) section of the [Architecture Overview](guide/architecture).</p>
<p>### Angular modules angular.module("movieHunter", ["ngRoute"]); In AngularJS, an Angular module keeps track of controllers, services, and other code. The second argument defines the list of other modules that this module depends upon.</p>	<p>### NgModules NgModules, defined with the `NgModule` decorator, serve the same purpose: * `imports`: specifies the list of other modules that this module depends upon * `declaration`: keeps track of your components, pipes, and directives. For more information on modules, see [NgModules] (guide/ngmodules).</p>
<p>### Controller registration angular .module("movieHunter") .controller("MovieListCtrl", ["movieService", MovieListCtrl]); AngularJS has code in each controller that looks up an appropriate Angular module and registers the controller with that module. The first argument is the controller name. The second argument defines the string names of all dependencies injected into this controller, and a reference to the controller function.</p>	<p>### Component decorator Angular adds a decorator to the component class to provide any required metadata. The `@Component` decorator declares that the class is a component and provides metadata about that component such as its selector (or tag) and its template. This is how you associate a template with logic, which is defined in the component class. For more information, see the [Components] (guide/architecture#components) section of the [Architecture Overview](guide/architecture) page.</p>
	<p>### Component class In</p>

Controller function function
MovieListCtrl(movieService) { }

In AngularJS, you write the code for the model and methods in a controller function.

Angular, you create a component class. NOTE: If you are using TypeScript with AngularJS, you must use the `export` keyword to export the component class. For more information, see the [Components](guide/architecture#components) section of the [Architecture Overview](guide/architecture) page.

Dependency injection
MovieListCtrl.\$inject = ['MovieService'];
function MovieListCtrl(movieService) { }

In AngularJS, you pass in any dependencies as controller function arguments. This example injects a `MovieService`. To guard against minification problems, tell Angular explicitly that it should inject an instance of the `MovieService` in the first parameter.

Dependency injection In Angular, you pass in dependencies as arguments to the component class constructor. This example injects a `MovieService`. The first parameter's TypeScript type tells Angular what to inject, even after minification. For more information, see the [Dependency injection](guide/architecture#dependency-injection) section of the [Architecture Overview](guide/architecture).

{@a style-sheets}

Style sheets

Style sheets give your application a nice look. In AngularJS, you specify the style sheets for your entire application. As the application grows over time, the styles for the many parts of the application merge, which can cause unexpected results. In Angular, you can still define style sheets for your entire application. But now you can also encapsulate a style sheet within a specific component.

AngularJS	Angular
<p>### Link tag <link href="styles.css" rel="stylesheet" /> AngularJS, uses a `link` tag in the head section of the `index.html` file to define the styles for the application.</p>	<p>### Styles configuration With the Angular CLI, you can configure your global styles in the `.angular-cli.json` file. You can rename the extension to `.scss` to use sass. ### StyleUrls In Angular, you can use the `styles` or `styleUrls` property of the `@Component` metadata to define a style sheet for a particular component. This allows you to set appropriate styles for individual components that won't leak into other parts of the application.</p>