FRL of not less than -/60/60.

(2) If an electrical wire or cable penetrates a *separating wall*—

(a) the service and building element at the penetration must—

(i) be identical with a prototype assembly that has been tested in accordance with AS 4072.1 and AS 1530.4 and achieve an FRL of not less than -/60/60; or

(ii) differ from a prototype assembly of the service and building element in accordance with AS 4072.1; or

(b) the service must be installed so that—

(i) the opening is neatly formed, cut or drilled and no closer than 50 mm to any other service; and

(ii) the opening is no larger in cross-section than—

(A) 2000 mm^2 if only a single cable is accommodated and the gap between the cable and the wall is no wider than 15 mm; or

(B) 500 mm^2 in any other case; and

(iii) any gap between the service and the wall is packed with mineral fibre or other suitable *fire-resisting* material.

(3) If an electrical switch, outlet, socket or the like is accommodated in a *separating wall*—

(a) the service and building element at the penetration must—

(i) be identical with a prototype assembly which has been tested in accordance with AS 4072.1 and AS 1530.4 and achieve an FRL of not less than -/60/60; or

(ii) differ from a prototype assembly of the service and building element in accordance with AS 4072.1; or

(b) the service must be installed so that—

(i) the opening or recess—

(A) is not located opposite any point within 300 mm horizontally or 600 mm vertically of any opening or recess on the opposite side of the wall; or

(B) does not extend beyond half the thickness of the wall; and

(ii) any gap between the service and the wall is packed with mineral fibre or other suitable *fire-resisting* material.

(4) Other than where a tested system is used in accordance with (3)(a), if an electrical switch, socket, outlet or the like is accommodated in a hollow *separating wall*, the *cavity* immediately behind the service must be framed and packed with mineral fibre or other suitable *fire-resisting* material (see Figure 9.3.2).