

Sectumsempra

For Manual/Intelligence

August 6, 2018

Sectumsempra模板——tbw部分

目录

1. 快速傅里叶变换
 2. 线性规划
 3. 对踵点对
 4. 平面区域
 5. 虚树
 6. 动态树
 7. KM算法(N^3)
 8. 最小树形图
 9. 可持久化线段树
 10. hint of pb_ds
-

快速傅里叶变换

```
#include <algorithm>
#include <complex>
#include <vector>
#include <cmath>
#define foreach(e,x) for(__typeof(x.begin()) e=x.begin();e!=x.end();++e)
using namespace std;

typedef complex<double> Comp;

const Comp I(0, 1);

const int MAX_N = 1 << 20;
Comp tmp[MAX_N];
void DFT(Comp*a, int n, int rev) {
    if (n == 1)
        return;
    for (int i = 0; i < n; ++i) {
        tmp[i] = a[i];
    }
    for (int i = 0; i < n; ++i) {
        if (i & 1)
            a[n / 2 + i / 2] = tmp[i];
        else
            a[i / 2] = tmp[i];
    }
    Comp*a0 = a, *a1 = a + n / 2;
    DFT(a0, n / 2, rev);
    DFT(a1, n / 2, rev);
    Comp cur(1, 0);
    double alpha = 2 * M_PI / n * rev;
    Comp step = exp(I * alpha);
    for (int k = 0; k < n / 2; ++k) {
        tmp[k] = a0[k] + cur * a1[k];
        tmp[k + n / 2] = a0[k] - cur * a1[k];
        cur *= step;
    }
    for (int i = 0; i < n; ++i) {
        a[i] = tmp[i];
    }
}

int main() {
```

```

static Comp a[1 << 20] = { }, b[1 << 20] = { };
int n = 1 << 20;
DFT(a, n, 1);
DFT(b, n, 1);
for (int i = 0; i < n; ++i) {
    a[i] *= b[i];
}
DFT(a, n, -1);
for (int i = 0; i < n; ++i) {
    a[i] /= n;
}
}

```

线性规划

```

// UVA10498 Happiness!
// Rujia Liu
#include<cstdio>
#include<cstring>
#include<algorithm>
#include<cassert>
using namespace std;

// 改进单纯性法的实现
// 参考: http://en.wikipedia.org/wiki/Simplex\_algorithm
// 输入矩阵a描述线性规划的标准形式。a为m+1行n+1列，其中行0~m-1为不等式，行m为目标函数（最大化）。列0~n-1为变量0~n-1的系数，列n为常数项
// 第i个约束为a[i][0]*x[0] + a[i][1]*x[1] + ... <= a[i][n]
// 目标为max(a[m][0]*x[0] + a[m][1]*x[1] + ... + a[m][n-1]*x[n-1] - a[m][n])
// 注意: 变量均有非负约束x[i] >= 0
const int maxm = 500; // 约束数目上限
const int maxn = 500; // 变量数目上限
const double INF = 1e100;
const double eps = 1e-10;

struct Simplex {
    int n; // 变量个数
    int m; // 约束个数
    double a[maxm][maxn]; // 输入矩阵
    int B[maxm], N[maxn]; // 算法辅助变量

    void pivot(int r, int c) {
        swap(N[c], B[r]);
        a[r][c] = 1 / a[r][c];
        for(int j = 0; j <= n; j++) if(j != c) a[r][j] *= a[r][c];
        for(int i = 0; i <= m; i++) if(i != r) {
            for(int j = 0; j <= n; j++) if(j != c) a[i][j] -= a[i][c] * a[r][j];
            a[i][c] = -a[i][c] * a[r][c];
        }
    }

    bool feasible() {
        for(;;) {
            int r, c;
            double p = INF;
            for(int i = 0; i < m; i++) if(a[i][n] < p) p = a[r = i][n];
            if(p > -eps) return true;
            p = 0;
            for(int i = 0; i < n; i++) if(a[r][i] < p) p = a[r][c = i];
            if(p > -eps) return false;
            p = a[r][n] / a[r][c];
            for(int i = r+1; i < m; i++) if(a[i][c] > eps) {
                double v = a[i][n] / a[i][c];
                if(v < p) { r = i; p = v; }
            }
            pivot(r, c);
        }
    }
}

```

```

    }
}

// 解有界返回1, 无解返回0, 无界返回-1. b[i]为x[i]的值, ret为目标函数的值
int simplex(int n, int m, double x[maxn], double& ret) {
    this->n = n;
    this->m = m;
    for(int i = 0; i < n; i++) N[i] = i;
    for(int i = 0; i < m; i++) B[i] = n+i;
    if(!feasible()) return 0;
    for(;;) {
        int r, c;
        double p = 0;
        for(int i = 0; i < n; i++) if(a[m][i] > p) p = a[m][c = i];
        if(p < eps) {
            for(int i = 0; i < n; i++) if(N[i] < n) x[N[i]] = 0;
            for(int i = 0; i < m; i++) if(B[i] < n) x[B[i]] = a[i][n];
            ret = -a[m][n];
            return 1;
        }
        p = INF;
        for(int i = 0; i < m; i++) if(a[i][c] > eps) {
            double v = a[i][n] / a[i][c];
            if(v < p) { r = i; p = v; }
        }
        if(p == INF) return -1;
        pivot(r, c);
    }
}
};

////////// 题目相关
#include<cmath>
Simplex solver;

int main() {
    int n, m;
    while(scanf("%d%d", &n, &m) == 2) {
        for(int i = 0; i < n; i++) scanf("%lf", &solver.a[m][i]); // 目标函数
        solver.a[m][n] = 0; // 目标函数常数项
        for(int i = 0; i < m; i++)
            for(int j = 0; j < n+1; j++)
                scanf("%lf", &solver.a[i][j]);
        double ans, x[maxn];
        assert(solver.simplex(n, m, x, ans) == 1);
        ans *= m;
        printf("Nasa can spend %d taka.\n", (int)floor(ans + 1 - eps));
    }
    return 0;
}
}

```

对踵点对

```

// LA4728/UVa1453 Square
// Rujia Liu
#include<cstdio>
#include<vector>
#include<cmath>
#include<algorithm>
using namespace std;

struct Point {
    int x, y;
    Point(int x=0, int y=0):x(x),y(y) { }
};

```

```

typedef Point Vector;

Vector operator - (const Point& A, const Point& B) {
    return Vector(A.x-B.x, A.y-B.y);
}

int Cross(const Vector& A, const Vector& B) {
    return A.x*B.y - A.y*B.x;
}

int Dot(const Vector& A, const Vector& B) {
    return A.x*B.x + A.y*B.y;
}

int Dist2(const Point& A, const Point& B) {
    return (A.x-B.x)*(A.x-B.x) + (A.y-B.y)*(A.y-B.y);
}

bool operator < (const Point& p1, const Point& p2) {
    return p1.x < p2.x || (p1.x == p2.x && p1.y < p2.y);
}

bool operator == (const Point& p1, const Point& p2) {
    return p1.x == p2.x && p1.y == p2.y;
}

// 点集凸包
// 如果不希望在凸包的边上有输入点, 把两个 <= 改成 <
// 注意: 输入点集会被修改
vector<Point> ConvexHull(vector<Point>& p) {
    // 预处理, 删除重复点
    sort(p.begin(), p.end());
    p.erase(unique(p.begin(), p.end()), p.end());

    int n = p.size();
    int m = 0;
    vector<Point> ch(n+1);
    for(int i = 0; i < n; i++) {
        while(m > 1 && Cross(ch[m-1]-ch[m-2], p[i]-ch[m-2]) <= 0) m--;
        ch[m++] = p[i];
    }
    int k = m;
    for(int i = n-2; i >= 0; i--) {
        while(m > k && Cross(ch[m-1]-ch[m-2], p[i]-ch[m-2]) <= 0) m--;
        ch[m++] = p[i];
    }
    if(n > 1) m--;
    ch.resize(m);
    return ch;
}

// 返回点集直径的平方
int diameter2(vector<Point>& points) {
    vector<Point> p = ConvexHull(points);
    int n = p.size();
    if(n == 1) return 0;
    if(n == 2) return Dist2(p[0], p[1]);
    p.push_back(p[0]); // 免得取模
    int ans = 0;
    for(int u = 0, v = 1; u < n; u++) {
        // 一条直线贴住边p[u]-p[u+1]
        for(;;) {
            // 当Area(p[u], p[u+1], p[v+1]) <= Area(p[u], p[u+1], p[v])时停止旋转
            // 即Cross(p[u+1]-p[u], p[v+1]-p[u]) - Cross(p[u+1]-p[u], p[v]-p[u]) <= 0
            // 根据Cross(A,B) - Cross(A,C) = Cross(A,B-C)
            // 化简得Cross(p[u+1]-p[u], p[v+1]-p[v]) <= 0

```

```

    int diff = Cross(p[u+1]-p[u], p[v+1]-p[v]);
    if(diff <= 0) {
        ans = max(ans, Dist2(p[u], p[v])); // u和v是对踵点
        if(diff == 0) ans = max(ans, Dist2(p[u], p[v+1])); // diff == 0时u和v+1也是对踵点
        break;
    }
    v = (v + 1) % n;
}
}
return ans;
}

int main() {
    int T;
    scanf("%d", &T);
    while(T--) {
        int n;
        scanf("%d", &n);
        vector<Point> points;
        for(int i = 0; i < n; i++) {
            int x, y, w;
            scanf("%d%d%d", &x, &y, &w);
            points.push_back(Point(x, y));
            points.push_back(Point(x+w, y));
            points.push_back(Point(x, y+w));
            points.push_back(Point(x+w, y+w));
        }
        printf("%d\n", diameter2(points));
    }
    return 0;
}

```

平面区域

```

// LA3218/UVa1340 Find the Border
// Rujia Liu
// 注意：本题可以直接使用“卷包裹”法求出外轮廓。本程序只是为了演示PSLG的实现
#include<cstdio>
#include<vector>
#include<cmath>
#include<algorithm>
#include<cstring>
#include<cassert>
using namespace std;

const double eps = 1e-8;
double dcmp(double x) {
    if(fabs(x) < eps) return 0; else return x < 0 ? -1 : 1;
}

struct Point {
    double x, y;
    Point(double x=0, double y=0):x(x),y(y) { }
};

typedef Point Vector;

Vector operator + (Vector A, Vector B) {
    return Vector(A.x+B.x, A.y+B.y);
}

Vector operator - (Point A, Point B) {
    return Vector(A.x-B.x, A.y-B.y);
}

```

```

Vector operator * (Vector A, double p) {
    return Vector(A.x*p, A.y*p);
}

// 理论上这个“小于”运算符是错的，因为可能有三个点a, b, c, a和b很接近（即a<b好b<a都不成立），b和c很接近，但a和c不接近
// 所以使用这种“小于”运算符的前提是能排除上述情况
bool operator < (const Point& a, const Point& b) {
    return dcmp(a.x - b.x) < 0 || (dcmp(a.x - b.x) == 0 && dcmp(a.y - b.y) < 0);
}

bool operator == (const Point& a, const Point &b) {
    return dcmp(a.x-b.x) == 0 && dcmp(a.y-b.y) == 0;
}

double Dot(Vector A, Vector B) { return A.x*B.x + A.y*B.y; }
double Cross(Vector A, Vector B) { return A.x*B.y - A.y*B.x; }
double Length(Vector A) { return sqrt(Dot(A, A)); }

typedef vector<Point> Polygon;

Point GetLineIntersection(const Point& P, const Vector& v, const Point& Q, const Vector& w) {
    Vector u = P-Q;
    double t = Cross(w, u) / Cross(v, w);
    return P+v*t;
}

bool SegmentProperIntersection(const Point& a1, const Point& a2, const Point& b1, const Point& b2) {
    double c1 = Cross(a2-a1,b1-a1), c2 = Cross(a2-a1,b2-a1),
    c3 = Cross(b2-b1,a1-b1), c4=Cross(b2-b1,a2-b1);
    return dcmp(c1)*dcmp(c2)<0 && dcmp(c3)*dcmp(c4)<0;
}

bool OnSegment(Point p, Point a1, Point a2) {
    return dcmp(Cross(a1-p, a2-p)) == 0 && dcmp(Dot(a1-p, a2-p)) < 0;
}

// 多边形的有向面积
double PolygonArea(Polygon poly) {
    double area = 0;
    int n = poly.size();
    for(int i = 1; i < n-1; i++)
        area += Cross(poly[i]-poly[0], poly[(i+1)%n]-poly[0]);
    return area/2;
}

struct Edge {
    int from, to; // 起点, 终点, 左边的面编号
    double ang;
};

const int maxn = 10000 + 10; // 最大边数

// 平面直线图 (PSGL) 实现
struct PSLG {
    int n, m, face_cnt;
    double x[maxn], y[maxn];
    vector<Edge> edges;
    vector<int> G[maxn];
    int vis[maxn*2]; // 每条边是否已经访问过
    int left[maxn*2]; // 左面的编号
    int prev[maxn*2]; // 相同起点的上一条边（即顺时针旋转碰到的下一条边）的编号

    vector<Polygon> faces;
    double area[maxn]; // 每个polygon的面积

    void init(int n) {
        this->n = n;
    }

```

```

    for(int i = 0; i < n; i++) G[i].clear();
    edges.clear();
    faces.clear();
}

// 有向线段from->to的极角
double getAngle(int from, int to) {
    return atan2(y[to]-y[from], x[to]-x[from]);
}

void AddEdge(int from, int to) {
    edges.push_back((Edge){from, to, getAngle(from, to)});
    edges.push_back((Edge){to, from, getAngle(to, from)});
    m = edges.size();
    G[from].push_back(m-2);
    G[to].push_back(m-1);
}

// 找出faces并计算面积
void Build() {
    for(int u = 0; u < n; u++) {
        // 给从u出发的各条边按极角排序
        int d = G[u].size();
        for(int i = 0; i < d; i++)
            for(int j = i+1; j < d; j++) // 这里偷个懒, 假设从每个点出发的线段不会太多
                if(edges[G[u][i]].ang > edges[G[u][j]].ang) swap(G[u][i], G[u][j]);
        for(int i = 0; i < d; i++)
            prev[G[u][(i+1)%d]] = G[u][i];
    }

    memset(vis, 0, sizeof(vis));
    face_cnt = 0;
    for(int u = 0; u < n; u++)
        for(int i = 0; i < G[u].size(); i++) {
            int e = G[u][i];
            if(!vis[e]) { // 逆时针找圈
                face_cnt++;
                Polygon poly;
                for(;;) {
                    vis[e] = 1; left[e] = face_cnt;
                    int from = edges[e].from;
                    poly.push_back(Point(x[from], y[from]));
                    e = prev[e^1];
                    if(e == G[u][i]) break;
                    assert(vis[e] == 0);
                }
                faces.push_back(poly);
            }
        }

    for(int i = 0; i < faces.size(); i++) {
        area[i] = PolygonArea(faces[i]);
    }
}

};

PSLG g;

const int maxp = 100 + 5;
int n, c;
Point P[maxp];

Point V[maxp*(maxp-1)/2+maxp];

// 在V数组里找到点p
int ID(Point p) {
    return lower_bound(V, V+c, p) - V;
}

```



```

}

// 假定poly没有相邻点重合的情况，只需要删除三点共线的情况
Polygon simplify(const Polygon& poly) {
    Polygon ans;
    int n = poly.size();
    for(int i = 0; i < n; i++) {
        Point a = poly[i];
        Point b = poly[(i+1)%n];
        Point c = poly[(i+2)%n];
        if(dcmp(Cross(a-b, c-b)) != 0) ans.push_back(b);
    }
    return ans;
}

void build_graph() {
    c = n;
    for(int i = 0; i < n; i++)
        V[i] = P[i];

    vector<double> dist[maxp]; // dist[i][j]是第i条线段上的第j个点离起点 (P[i]) 的距离
    for(int i = 0; i < n; i++)
        for(int j = i+1; j < n; j++)
            if(SegmentProperIntersection(P[i], P[(i+1)%n], P[j], P[(j+1)%n])) {
                Point p = GetLineIntersection(P[i], P[(i+1)%n]-P[i], P[j], P[(j+1)%n]-P[j]);
                V[c++] = p;
                dist[i].push_back(Length(p - P[i]));
                dist[j].push_back(Length(p - P[j]));
            }

    // 为了保证“很接近的点”被看作同一个，这里使用了sort+unique的方法
    // 必须使用前面提到的“理论上是错误”的小于运算符，否则不能保证“很接近的点”在排序后连续排列
    // 另一个常见的处理方式是把坐标扩大很多倍（比如100000倍），然后四舍五入变成整数（计算完毕后再还原），用少许的精度损失换来鲁棒性和速度。
    sort(V, V+c);
    c = unique(V, V+c) - V;

    g.init(c); // c是平面图的点数
    for(int i = 0; i < c; i++) {
        g.x[i] = V[i].x;
        g.y[i] = V[i].y;
    }
    for(int i = 0; i < n; i++) {
        Vector v = P[(i+1)%n] - P[i];
        double len = Length(v);
        dist[i].push_back(0);
        dist[i].push_back(len);
        sort(dist[i].begin(), dist[i].end());
        int sz = dist[i].size();
        for(int j = 1; j < sz; j++) {
            Point a = P[i] + v * (dist[i][j-1] / len);
            Point b = P[i] + v * (dist[i][j] / len);
            if(a == b) continue;
            g.AddEdge(ID(a), ID(b));
        }
    }

    g.Build();

    Polygon poly;
    for(int i = 0; i < g.faces.size(); i++)
        if(g.area[i] < 0) { // 对于连通图，惟一一个面积小于零的面是无限面
            poly = g.faces[i];
            reverse(poly.begin(), poly.end()); // 对于内部区域来说，无限面多边形的各个顶点是顺时针的
            poly = simplify(poly); // 无限面多边形上可能会有相邻共线点
            break;
        }
}

```

```

int m = poly.size();
printf("%d\n", m);

// 挑选坐标最小的点作为输出的起点
int start = 0;
for(int i = 0; i < m; i++)
    if(poly[i] < poly[start]) start = i;
for(int i = start; i < m; i++)
    printf("%.4lf %.4lf\n", poly[i].x, poly[i].y);
for(int i = 0; i < start; i++)
    printf("%.4lf %.4lf\n", poly[i].x, poly[i].y);
}

int main() {
    while(scanf("%d", &n) == 1 && n) {
        for(int i = 0; i < n; i++) {
            int x, y;
            scanf("%d%d", &x, &y);
            P[i] = Point(x, y);
        }
        build_graph();
    }
    return 0;
}

```

虚树

```

#include <iostream>
#include <sstream>
#include <algorithm>
#include <cstdio>
#include <cstdlib>
#include <cstring>
#include <cmath>
#include <vector>

const int N = 3e5 + 10;

int n;
std::vector<int> edge[N];
int father[N][21];
int size[N], deep[N];
int pos[N], tot;

void clear() {
    tot = 0;
    for (int i = 1; i <= n; i++) {
        edge[i].clear();
    }
}

void init() {
    std::cin >> n;
    clear();
    for (int i = 1; i <= n - 1; i++) {
        int u, v;
        scanf("%d%d", &u, &v);
        edge[u].push_back(v);
        edge[v].push_back(u);
    }
}

void dfs(int u) {
    size[u] = 1;
    pos[u] = ++tot;
}

```

```

    for (int i = 0; i < (int)edge[u].size(); i++) {
        int v = edge[u][i];
        if (v == father[u][0]) {
            continue;
        }
        father[v][0] = u;
        deep[v] = deep[u] + 1;
        dfs(v);
        size[u] += size[v];
    }
}

void prepare() {
    for (int j = 1; j <= 20; j++) {
        for (int i = 1; i <= n; i++) {
            father[i][j] = father[father[i][j - 1]][j - 1];
        }
    }
}

int least_common_ancestor(int u, int v) {
    if (deep[u] < deep[v]) {
        std::swap(u, v);
    }
    for (int i = 20; i >= 0; i--) {
        if (deep[father[u][i]] >= deep[v]) {
            u = father[u][i];
        }
    }
    if (u == v) {
        return u;
    }
    for (int i = 20; i >= 0; i--) {
        if (father[u][i] != father[v][i]) {
            u = father[u][i];
            v = father[v][i];
        }
    }
    return father[u][0];
}

bool cmp_pos(int x, int y) {
    return pos[x] < pos[y];
}

int get_ancestor(int u, int cnt) {
    for (int i = 20; i >= 0; i--) {
        if ((1 << i) <= cnt) {
            u = father[u][i];
            cnt -= (1 << i);
        }
    }
    return u;
}

int dist(int u, int v) {
    int t = least_common_ancestor(u, v);
    return deep[u] + deep[v] - 2 * deep[t];
}

void solve(std::vector<int> &query) {
    static int stack[N], fa[N];
    static std::vector<int> all;
    static std::pair<int, int> best[N];
    static int extra[N], ans[N];
    std::vector<int> rem = query;

```

```

int top = 0;
all.clear();

sort(query.begin(), query.end(), cmp_pos);

for (int i = 0; i < (int)query.size(); i++) {
    int u = query[i];
    if (top == 0) {
        stack[++top] = u;
        all.push_back(u);
        best[u] = std::make_pair(0, u);
    } else {
        int lca = least_common_ancestor(u, stack[top]);
        for (; deep[stack[top]] > deep[lca]; top--) {
            if (deep[stack[top - 1]] <= deep[lca]) {
                fa[stack[top]] = lca;
            }
        }
        if (stack[top] != lca) {
            fa[lca] = stack[top];
            stack[++top] = lca;
            best[lca] = std::make_pair(n + 10, -1);
            all.push_back(lca);
        }
        fa[u] = stack[top];
        stack[++top] = u;
        all.push_back(u);
        best[u] = std::make_pair(0, u);
    }
}

sort(all.begin(), all.end(), cmp_pos);

static int length[N];
for (int i = 0; i < (int)all.size(); i++) {
    int u = all[i];
    if (u != 1) {
        length[u] = deep[u] - deep[fa[u]];
    }
}

for (int i = (int)all.size() - 1; i > 0; i--) {
    int u = all[i];
    std::pair<int, int> tmp = best[u];
    tmp.first += length[u];
    best[fa[u]] = std::min(best[fa[u]], tmp);
}

for (int i = 1; i < (int)all.size(); i++) {
    int u = all[i];
    std::pair<int, int> tmp = best[fa[u]];
    tmp.first += length[u];
    best[u] = std::min(best[u], tmp);
}

/*
for (int i = 0; i < (int)all.size(); i++) {
    printf("best[%d] = {%d, %d}\n", all[i], best[all[i]].first, best[all[i]].second);
    printf("size[%d] = %d\n", all[i], size[all[i]]);
}
*/

for (int i = 0; i < (int)query.size(); i++) {
    ans[query[i]] = 0;
}

for (int i = 0; i < (int)all.size(); i++) {
    int u = all[i];
    if (i == 0) {
        ans[best[u].second] = n - size[u];
    }
}

```

```

    } else {
        int t = get_ancestor(u, length[u] - 1);
        if (best[u].second == best[fa[u]].second) {
            ans[best[u].second] += size[t] - size[u];
        } else {
            int step = u;
            for (int i = 20; i >= 0; i --) {
                int mid = father[step][i];
                if (deep[mid] <= deep[fa[u]]) {
                    continue;
                }
                std::pair<int, int> tmp1 = std::make_pair(dist(mid, best[u].second), best[u].second);
                std::pair<int, int> tmp2 = std::make_pair(dist(mid, best[fa[u]].second), best[fa[u]].second);
                if (tmp1 < tmp2) {
                    step = father[step][i];
                }
            }
            ans[best[u].second] += size[step] - size[u];
            ans[best[fa[u]].second] += size[t] - size[step];
        }
    }
}

for (int i = 0; i < (int)all.size(); i++) {
    int u = all[i];
    extra[u] = size[u];
}

for (int i = 0; i < (int)all.size(); i++) {
    int u = all[i];
    int t = get_ancestor(u, length[u] - 1);
    extra[fa[u]] -= size[t];
}

for (int i = 0; i < (int)all.size(); i++) {
    int u = all[i];
    ans[best[u].second] += extra[u];
}

for (int i = 0; i < (int)rem.size(); i++) {
    printf("%d ", ans[rem[i]]);
}

printf("\n");
}

void work() {
    deep[1] = 1;
    dfs(1);
    prepare();

    int q;
    std::cin >> q;
    while (q --) {
        int cnt;
        static std::vector<int> cur;

        cur.clear();

        scanf("%d", &cnt);
        for (int i = 1; i <= cnt; i++) {
            int t;
            scanf("%d", &t);
            cur.push_back(t);
        }

        solve(cur);
    }
}

int main() {

```

```
//freopen("input.txt", "r", stdin);

init();
work();

return 0;
}
```

动态树

```
#include <iostream>
#include <sstream>
#include <algorithm>
#include <cstdio>
#include <cstdlib>
#include <cstring>
#include <cmath>
#include <vector>

const int N = 3e5 + 10;

int n;

struct LinkCutTree {
    struct Node {
        int value, max, inc;
        bool rev;
        int father, child[2];

        Node() {
        }
    };
    Node node[N];
    const Node EMPTY;

    void clear() {
        std::fill(node + 1, node + n + 1, EMPTY);
    }

    void __inc(int x, int delta) {
        if (x == 0) {
            return ;
        }
        node[x].inc += delta;
        node[x].value += delta;
        node[x].max += delta;
    }

    void update(int x) {
        if (x == 0) {
            return ;
        }
        if (node[x].inc != 0) {
            __inc(node[x].child[0], node[x].inc);
            __inc(node[x].child[1], node[x].inc);
            node[x].inc = 0;
        }
        if (node[x].rev == true) {
            std::swap(node[x].child[0], node[x].child[1]);
            node[node[x].child[0]].rev ^= true;
            node[node[x].child[1]].rev ^= true;
            node[x].rev = false;
        }
    }
}
```

```

void renew(int x) {
    update(x);
    update(node[x].child[0]);
    update(node[x].child[1]);
    node[x].max = std::max(node[x].value, std::max(node[node[x].child[0]].max, node[node[x].child[1]].max));
}

void change_value(int x, int value) {
    splay(x);
    node[x].value = node[x].max = value;
    renew(x);
}

bool is_splay_father(int y, int x) {
    return (y != 0) && (node[y].child[0] == x || node[y].child[1] == x);
}

void rotate(int x, int c) {
    int y = node[x].father;
    node[y].child[c ^ 1] = node[x].child[c];
    if (node[x].child[c] != 0) {
        node[node[x].child[c]].father = y;
    }
    node[x].father = node[y].father;
    if (node[node[y].father].child[0] == y) {
        node[node[x].father].child[0] = x;
    } else if (node[node[y].father].child[1] == y) {
        node[node[x].father].child[1] = x;
    }
    node[x].child[c] = y;
    node[y].father = x;
    renew(y);
}

void splay(int x) {
    if (x == 0) {
        return ;
    }
    update(x);
    while (is_splay_father(node[x].father, x)) {
        int y = node[x].father;
        int z = node[y].father;
        if (is_splay_father(z, y)) {
            update(z);
            update(y);
            update(x);
            int c = (y == node[z].child[0]);
            if (x == node[y].child[c]) {
                rotate(x, c ^ 1);
                rotate(x, c);
            } else {
                rotate(y, c);
                rotate(x, c);
            }
        } else {
            update(y);
            update(x);
            rotate(x, x == node[y].child[0]);
            break;
        }
    }
    renew(x);
}

int access(int x) {
    int y = 0;
    for ( ; x != 0; x = node[x].father) {

```

```

        splay(x);
        node[x].child[1] = y;
        renew(y = x);
    }
    return y;
}

int get_root(int x) {
    x = access(x);
    while (true) {
        update(x);
        if (node[x].child[0] == 0) {
            break;
        }
        x = node[x].child[0];
    }
    return x;
}

void make_root(int x) {
    node[access(x)].rev ^= true;
    splay(x);
}

void link(int x, int y) {
    make_root(x);
    node[x].father = y;
    access(x);
}

void cut(int x, int y) {
    make_root(x);
    access(y);
    splay(y);
    node[node[y].child[0]].father = 0;
    node[y].child[0] = 0;
    renew(y);
}

void modify(int x, int y, int delta) {
    make_root(x);
    access(y);
    splay(y);
    __inc(y, delta);
}

int get_max(int x, int y) {
    make_root(x);
    access(y);
    splay(y);
    return node[y].max;
}
};
LinkCutTree lct;

void clear() {
    lct.clear();
}

void init() {
    for (int i = 1; i <= n - 1; i++) {
        int u, v;
        scanf("%d%d", &u, &v);
        lct.link(u, v);
    }
    for (int i = 1; i <= n; i++) {

```



```

        int t;
        scanf("%d", &t);
        lct.change_value(i, t);
    }
}

void work() {
    int q;
    std::cin >> q;

    while (q --) {
        int type;
        scanf("%d", &type);

        if (type == 1) {
            int u, v;
            scanf("%d%d", &u, &v);
            if (lct.get_root(u) == lct.get_root(v)) {
                puts("-1");
            } else {
                lct.link(u, v);
            }
        } else if (type == 2) {
            int u, v;
            scanf("%d%d", &u, &v);
            if (u == v || lct.get_root(u) != lct.get_root(v)) {
                puts("-1");
            } else {
                lct.cut(u, v);
            }
        } else if (type == 3) {
            int delta, u, v;
            scanf("%d%d%d", &delta, &u, &v);
            if (lct.get_root(u) != lct.get_root(v)) {
                puts("-1");
            } else {
                lct.modify(u, v, delta);
            }
        } else {
            int u, v;
            scanf("%d%d", &u, &v);
            if (lct.get_root(u) != lct.get_root(v)) {
                puts("-1");
            } else {
                printf("%d\n", lct.get_max(u, v));
            }
        }
    }
    printf("\n");
}

int main() {
    //freopen("input.txt", "r", stdin);
    //freopen("output.txt", "w", stdout);

    while (std::cin >> n) {
        clear();
        init();
        work();
    }

    return 0;
}

```

```

#include <iostream>
#include <sstream>
#include <algorithm>
#include <cstdio>
#include <cstdlib>
#include <cstring>
#include <cmath>
#include <vector>

const int N = 25;
const int INF = 1e8;

int n;
int profit[2][N][N];
int answer = -INF;

struct KM_State {
    int lx[N], ly[N];
    int match[N], way[N];

    KM_State() {
        for (int i = 1; i <= n; i++) {
            match[i] = 0;
            lx[i] = 0;
            ly[i] = 0;
            way[i] = 0;
        }
    }
};

struct KM_Solver {
    int w[N][N];
    KM_State state;
    int slack[N];
    bool used[N];

    KM_Solver() {
        for (int i = 1; i <= n; i++) {
            for (int j = 1; j <= n; j++) {
                w[i][j] = 0;
            }
        }
    }

    void hungary(int x) {
        state.match[0] = x;
        int j0 = 0;
        for (int j = 0; j <= n; j++) {
            slack[j] = INF;
            used[j] = false;
        }
        do {
            used[j0] = true;
            int i0 = state.match[j0], delta = INF, j1;
            for (int j = 1; j <= n; j++) {
                if (used[j] == false) {
                    int cur = w[i0][j] - state.lx[i0] - state.ly[j];
                    if (cur < slack[j]) {
                        slack[j] = cur;
                        state.way[j] = j0;
                    }
                    if (slack[j] < delta) {
                        delta = slack[j];
                        j1 = j;
                    }
                }
            }
        }
    }
};

```

```

    }
    for (int j = 0; j <= n; j++) {
        if (used[j]) {
            state.lx[state.match[j]] += delta;
            state.ly[j] -= delta;
        } else {
            slack[j] -= delta;
        }
    }
    j0 = j1;
} while (state.match[j0] != 0);

do {
    int j1 = state.way[j0];
    state.match[j0] = state.match[j1];
    j0 = j1;
} while (j0);
}

int get_ans() {
    int ret = 0;
    for (int i = 1; i <= n; i++) {
        if (state.match[i] > 0) {
            ret += w[state.match[i]][i];
        }
    }
    return state.ly[0];
}

};

void init() {
    std::cin >> n;
    for (int t = 0; t <= 1; t++) {
        for (int i = 1; i <= n; i++) {
            for (int j = 1; j <= n; j++) {
                scanf("%d", &profit[t][i][j]);
            }
        }
    }
}

void dfs(int x, int y, KM_Solver &solver) {
    if (x + y == n) {
        answer = std::max(answer, solver.get_ans());
        return ;
    }
    if (2 * x + 2 <= n) {
        KM_State tmp = solver.state;
        for (int i = 1; i <= n; i++) {
            solver.w[x + y + 1][i] = -profit[0][x + y + 1][i];
        }
        solver.hungary(x + y + 1);
        dfs(x + 1, y, solver);
        solver.state = tmp;
    }
    if (2 * y + 2 <= n) {
        KM_State tmp = solver.state;
        for (int i = 1; i <= n; i++) {
            solver.w[x + y + 1][i] = -profit[1][x + y + 1][i];
        }
        solver.hungary(x + y + 1);
        dfs(x, y + 1, solver);
        solver.state = tmp;
    }
}

void work() {

```

```

        static KM_Solver solver;
        dfs(0, 0, solver);
        std::cout << answer << std::endl;
    }

int main() {
    //freopen("C.in", "r", stdin);

    init();
    work();

    return 0;
}

```

最小树形图

```

// UVa11865 Stream My Contest
// Rujia Liu
#include<cstdio>
#include<cstring>
#include<vector>
#include<algorithm>
using namespace std;

const int INF = 1000000000;
const int maxn = 100 + 10;

// 固定根的最小树形图，邻接矩阵写法
struct MDST {
    int n;
    int w[maxn][maxn]; // 边权
    int vis[maxn];      // 访问标记，仅用来判断无解
    int ans;            // 计算答案
    int removed[maxn]; // 每个点是否被删除
    int cid[maxn];      // 所在圈编号
    int pre[maxn];      // 最小入边的起点
    int iw[maxn];       // 最小入边的权值
    int max_cid;        // 最大圈编号

    void init(int n) {
        this->n = n;
        for(int i = 0; i < n; i++)
            for(int j = 0; j < n; j++) w[i][j] = INF;
    }

    void AddEdge(int u, int v, int cost) {
        w[u][v] = min(w[u][v], cost); // 重边取权最小的
    }

    // 从s出发能到达多少个结点
    int dfs(int s) {
        vis[s] = 1;
        int ans = 1;
        for(int i = 0; i < n; i++)
            if(!vis[i] && w[s][i] < INF) ans += dfs(i);
        return ans;
    }

    // 从u出发沿着pre指针找圈
    bool cycle(int u) {
        max_cid++;
        int v = u;
        while(cid[v] != max_cid) { cid[v] = max_cid; v = pre[v]; }
        return v == u;
    }
}

```

```

// 计算u的最小入弧，入弧起点不得在圈c中
void update(int u) {
    iw[u] = INF;
    for(int i = 0; i < n; i++)
        if(!removed[i] && w[i][u] < iw[u]) {
            iw[u] = w[i][u];
            pre[u] = i;
        }
}

// 根结点为s，如果失败则返回false
bool solve(int s) {
    memset(vis, 0, sizeof(vis));
    if(dfs(s) != n) return false;

    memset(removed, 0, sizeof(removed));
    memset(cid, 0, sizeof(cid));
    for(int u = 0; u < n; u++) update(u);
    pre[s] = s; iw[s] = 0; // 根结点特殊处理
    ans = max_cid = 0;
    for(;;) {
        bool have_cycle = false;
        for(int u = 0; u < n; u++) if(u != s && !removed[u] && cycle(u)){
            have_cycle = true;
            // 以下代码缩圈，圈上除了u之外的结点均删除
            int v = u;
            do {
                if(v != u) removed[v] = 1;
                ans += iw[v];
                // 对于圈外点i，把边i->v改成i->u（并调整权值）；v->i改为u->i
                // 注意圈上可能还有一个v'使得i->v'或者v'->i存在，因此只保留权值最小的i->u和u->i
                for(int i = 0; i < n; i++) if(cid[i] != cid[u] && !removed[i]) {
                    if(w[i][v] < INF) w[i][u] = min(w[i][u], w[i][v]-iw[v]);
                    w[u][i] = min(w[u][i], w[v][i]);
                    if(pre[i] == v) pre[i] = u;
                }
                v = pre[v];
            } while(v != u);
            update(u);
            break;
        }
        if(!have_cycle) break;
    }
    for(int i = 0; i < n; i++)
        if(!removed[i]) ans += iw[i];
    return true;
}

};

//////// 题目相关
MDST solver;

struct Edge {
    int u, v, b, c;
    bool operator < (const Edge& rhs) const {
        return b > rhs.b;
    }
};

const int maxm = 10000 + 10;
int n, m, C;
Edge edges[maxm];

// 取b前cnt大的边构造网络，判断最小树型图的边权和是否小于C
bool check(int cnt) {
    solver.init(n);

```

```

for(int i = 0; i < cnt; i++)
    solver.AddEdge(edges[i].u, edges[i].v, edges[i].c);
if(!solver.solve(0)) return false;
return solver.ans <= C;
}

int main() {
    int T;
    scanf("%d", &T);
    while(T--) {
        scanf("%d%d%d", &n, &m, &C);
        for(int i = 0; i < m; i++) {
            scanf("%d%d%d%d", &edges[i].u, &edges[i].v, &edges[i].b, &edges[i].c);
        }
        sort(edges, edges+m);
        int L = 1, R = m, ans = -1;
        while(L <= R) {
            int M = L + (R-L)/2;
            if(check(M)) { ans = edges[M-1].b; R = M-1; }
            else L = M+1;
        }
        if(ans < 0) printf("streaming not possible.\n");
        else printf("%d kbps\n", ans);
    }
    return 0;
}

```

可持久化线段树

```

#include <iostream>
#include <algorithm>
#include <cstdio>
#include <cstdlib>
#include <cstring>
#include <cmath>
#include <vector>
using namespace std;

const int N = 100005;

struct Node
{
    int best[3], son[2];
};

struct Segment_Tree
{
    Node tree[N * 19];
    int __root[N], tot;
    void merge(Node &ret, int left, int right, Node t1, Node t2)
    {
        ret.best[0] = max(t1.best[2] + t2.best[1], max(t1.best[0], t2.best[0]));
        int mid = (left + right) >> 1;
        ret.best[1] = t1.best[1] + (t1.best[1] == mid - left + 1) * t2.best[1];
        ret.best[2] = t2.best[2] + (t2.best[2] == right - mid) * t1.best[2];
    }
    void add(int &root, int root1, int left, int right, int x)
    {
        root = ++tot;
        if(left == x && right == x)
        {
            tree[root].best[0] = tree[root].best[1] = tree[root].best[2] = 1;
            return ;
        }
        int mid = (left + right) >> 1;
    }

```

```

    if(x <= mid)
    {
        add(tree[root].son[0], tree[root1].son[0], left, mid, x);
        tree[root].son[1] = tree[root1].son[1];
    }
    else
    {
        tree[root].son[0] = tree[root1].son[0];
        add(tree[root].son[1], tree[root1].son[1], mid + 1, right, x);
    }
    merge(tree[root], left, right, tree[tree[root].son[0]], tree[tree[root].son[1]]);
}
Node search(int root, int left, int right, int L,int R)
{
    if(root == 0) return tree[0];
    if(left == L && right == R) return tree[root];
    int mid = (left + right) >> 1;
    if(R <= mid) return search(tree[root].son[0], left, mid, L, R);
    if(L > mid) return search(tree[root].son[1], mid + 1, right, L, R);
    Node t1 = search(tree[root].son[0], left, mid, L, mid);
    Node t2 = search(tree[root].son[1], mid + 1, right, mid + 1, R);
    Node ret;
    merge(ret, left, right, t1, t2);
    return ret;
}
};
Segment_Tree T;

int n, q;
pair<int, int> g[N];

void insert(int x, int pos)
{
    T.add(T.__root[x], T.__root[x - 1], 1, n, pos);
}
void init()
{
    cin >> n;
    for(int i = 1; i <= n; i++)
        scanf("%d", &g[i].first), g[i].first *= -1, g[i].second = i;
}
bool check(int mid, int L, int R, int length)
{
    Node step = T.search(T.__root[mid], 1, n, L, R);
    return (step.best[0] >= length);
}
int Solve(int L, int R, int length)
{
    int low = 1, high = n, ret = n + 1;
    while(low <= high)
    {
        int mid = (low + high) >> 1;
        if(check(mid, L, R, length)) ret = min(ret, mid), high = mid - 1;
        else low = mid + 1;
    }
    return ret;
}
void work()
{
    sort(g + 1, g + n + 1);
    for(int i = 1; i <= n; i++)
        insert(i, g[i].second);
    cin >> q;
    while(q --)
    {
        int c, d, e;
        scanf("%d%d%d", &c, &d, &e);
    }
}

```

```
        printf("%d\n", -g[Solve(c, d, e)].first);
    }
}

int main()
{
    //freopen("input.txt", "r", stdin);
    //freopen("output.txt", "w", stdout);
    init(), work();
    return 0;
}
```

Hint of pb_ds

priority_queue:

```
#include <ext/pb_ds/priority_queue.hpp>

__gnu_pbds::priority_queue<int> heap;

* point iterator push(const reference)
* void modify(point iterator, const reference)
* void erase(point iterator)

* void join(priority queue &other)
* 注意: other会被清空
```

tree

```
#include <ext/pb_ds/assoc_container.hpp>
#include <ext/pb_ds/tree_policy.hpp>

tree<int, int, less<int>, rb_tree_tag, tree_order_statistics_node_update>

* find_by_order(size type order)
* size_type order of key(const key reference r key)

void join(tree &other)
void split(const key reference r key, tree &other)
```


Sectumsempra模板——xzj部分

树链剖分

```
#include<iostream>
#include<cstdio>
#include<algorithm>
#include<cstring>
using namespace std;
typedef long long LL;
const LL INF=2e9;
const LL N=2e5 + 100;
struct ones
{
    LL max_l,max_r,max_sum,sum,tag;
    ones(){}
    ones(LL max_l,LL max_r,LL max_sum,LL sum,LL tag):max_l(max_l),max_r(max_r),max_sum(max_sum),sum(sum),tag(tag){}
}tree[N*4];
struct Edge
{
    LL v,next;
    Edge(){}
    Edge(LL v,LL next):v(v),next(next){}
}edge[N*2];
LL edn,p[N],dep[N],fa[N],son[N],size[N],place[N],n,m,value[N],now,top[N],which[N];
LL MAX(LL a,LL b,LL c){
    return max(a,max(b,c));
}
ones operator + (const ones &a,const ones &b){
    return ones(max(a.max_l,a.sum + b.max_l),max(b.max_r,b.sum + a.max_r),MAX(a.max_sum,b.max_sum,a.max_r + b.max_l),a.sum + b.sum);
}
void dfs1(LL x){
    dep[x]=dep[fa[x]] + 1;
    size[x]=1;
    for(LL i=p[x];~i;i=edge[i].next)
    {
        LL y=edge[i].v;
        if(y!=fa[x])
        {
            fa[y]=x;
            dfs1(y);
            size[x]+=size[y];
            if(size[y]>size[son[x]]) son[x]=y;
        }
    }
}
void dfs2(LL x){
    place[x]=++now;
    which[now]=x;
    if(son[x]==0) return;
    top[son[x]]=top[x];
    dfs2(son[x]);
    for(LL i=p[x];~i;i=edge[i].next)
    {
        LL y=edge[i].v;
        if(y!=fa[x] && y!=son[x])
        {
            top[y]=y;
            dfs2(y);
        }
    }
}
void modify(LL x,LL len,LL c)
{
}
```

```

    if(c>=0) tree[x]=ones(len * c,len * c,len * c,len * c,c);
    else tree[x]=ones(c,c,c,len * c,c);
}
void build (LL x,LL l,LL r){
    if(l+1==r) modify(x,1,value[which[l]]);else
    {
        LL mid=(l+r)/2;
        build(x*2,l,mid);
        build(x*2+1,mid,r);
        tree[x]=tree[x*2]+tree[x*2+1];
    }
}
void dwnntag(LL x,LL len)
{
    if(tree[x].tag==INF) return;
    modify(x * 2,len/2,tree[x].tag);
    modify(x*2+1,len-len/2,tree[x].tag);
    tree[x].tag=INF;
}
void change(LL x,LL l,LL r,LL ll,LL rr,LL c)
{
    if(l>=ll && r<=rr) modify(x,r-l,c);
    else
    {
        dwnntag(x,r-l);
        LL mid=(l+r)/2;
        if(ll<mid) change(x*2,l,mid,ll,rr,c);
        if(rr>mid) change(x*2+1,mid,r,ll,rr,c);
        tree[x]=tree[x*2]+tree[x*2+1];
    }
}
ones get(LL x,LL l,LL r,LL ll,LL rr)
{
    if(l>=ll && r<=rr) return tree[x];
    dwnntag(x,r-l);
    LL mid=(l+r)/2;
    ones tmp=ones(-INF,-INF,-INF,0,INF);
    if(ll<mid) tmp=get(x*2,l,mid,ll,rr) + tmp;
    if(rr>mid) tmp=tmp + get(x*2+1,mid,r,ll,rr);
    return tmp;
}
int main()
{
    cin>>n>>m;
    for(LL i=1;i<=n;i++)
        scanf("%lld",&value[i]);
    edn=0;memset(p,-1,sizeof(p));
    for(LL i=1;i<n;i++)
    {
        LL u,v;
        scanf("%lld%lld",&u,&v);
        edge[edn]=Edge(v,p[u]);p[u]=edn++;
        edge[edn]=Edge(u,p[v]);p[v]=edn++;
    }
    dfs1(1);
    top[1]=1;
    dfs2(1);
    build(1,1,n+1);
    while (m--)
    {
        LL type,u,v,c;
        scanf("%lld%lld%lld%lld",&type,&u,&v,&c);
        if(type==2)
        {
            ones ans1=ones(-INF,-INF,-INF,0,INF),ansr=ones(-INF,-INF,-INF,0,INF);
            while(true)
            {

```


Sectumsempra补充模板——zfg部分

目录

1. CRT(非互质)
 2. CRT
 3. lct
 4. lucas定理
 5. manacher
 6. palindromic_tree
 7. treap
 8. VirtualTree
 9. 后缀数组
 10. 后缀自动机（非字典树）
 11. 后缀自动机（含字典树）
 12. 可持久化并查集
 13. 扩展kmp
 14. 全局最小割
 15. 最小表示法
 16. 左偏树 & 斜堆
-

CRT(非互质)

```
#include<iostream>
#include<cstdio>
#include<cstring>
#include<vector>
#define rep(i, l, r) for(int i = l; i <= r; ++i)
using namespace std;
typedef long long ll;
void ExGcd(ll a, ll b, ll &d, ll &x, ll &y){
    if(!b){d = a; x = 1; y = 0;}
    else {
        ExGcd(b, a % b, d, y, x);
        y -= a/b * x;
    }
}
struct ModularEquation{
    ll m, r;
    ModularEquation(){}
    ModularEquation(ll m, ll r):m(m), r(r){}
    pair<bool, ModularEquation> operator + (const ModularEquation &t) const{
        ll c = t.r - r;
        ll d, x, y;
        ExGcd(m, t.m, d, x, y);
        if(c % d) return make_pair(0, ModularEquation(0, 0));
        c /= d;
        ll NewM = m / d * t.m, NewR = r + m * x * c;
        NewR %= NewM;
        if(NewR <= 0) NewR += NewM;
        return make_pair(1, ModularEquation(NewM, NewR));
    }
};
vector<ModularEquation> t;
int main(){
    int cas;
    cin >> cas;
    while(cas--){
        ll N;
```

```

int m;
cin >> N >> m;
t.clear();
rep(i, 1, m) t.push_back(ModularEquation(0, 0));
for(int i = 0; i < m; ++i) scanf("%I64d", &t[i].m);
for(int i = 0; i < m; ++i) scanf("%I64d", &t[i].r);
bool flag = 1;
for(int i = 1; i < m; ++i){
    pair<bool, ModularEquation> bm = t[i - 1] + t[i];
    if(!bm.first){
        flag = 0;
        break;
    }
    t[i] = bm.second;
}
if(!flag){
    printf("0\n");
    continue;
}
ModularEquation ans = t[m - 1];
ans.r %= ans.m;
if(ans.r <= 0) ans.r += ans.m;
if(N < ans.r) printf("0\n");
else cout << 1 + (N - ans.r) / ans.m << "\n";
}
return 0;
}

```

CRT

```

#include<iostream>
#include<cstdio>
#include<cstring>
#define rep(i, l, r) for(int i = l; i <= r; ++i)
using namespace std;
typedef long long ll;
const int maxn = 1e5 + 10;
class CRT{
private:
    int p[maxn], v[maxn], m;
    ll M, n;
public:
    void ExGcd(ll a, ll b, ll &x, ll &y){
        if(!b){x = 1; y = 0;}
        else {
            ExGcd(b, a % b, y, x);
            y -= x*(a/b);
        }
    }
    void work(){
        cin >> n >> m;
        rep(i, 1, m) scanf("%d", &p[i]);
        rep(i, 1, m) scanf("%d", &v[i]);
        M = 1;
        rep(i, 1, m) M*= p[i];
        ll t = 0;
        printf("M = %lld\n", M);
        rep(i, 1, m){
            int k = M / p[i];
            ll AnsX, AnsY;
            ExGcd(k, p[i], AnsX, AnsY);
            printf("k = %d p[%d] = %d AnsX = %d\n", k, i, p[i], AnsX);
            t += v[i] * AnsX * k;
        }
        printf("t = %lld M = %lld\n", t, M);
    }
}

```

```

        if(t <= 0)
            t = (t % M) + M;
        cout << (n - t) / M + 1 << "\n";
    }
}
solver;
int main(){
    int cas;
    cin >> cas;
    while(cas--){
        solver.work();
    }
    return 0;
}

```

lct

```

// hdu 4010
#include<iostream>
#include<cstdio>
#include<cstring>
#include<algorithm>
#include<cmath>
#define maxn 300101
using namespace std;
int ch[maxn][2], fa[maxn], w[maxn], val[maxn], flag[maxn], n, m, last, sign[maxn];
bool root(int x){
    return ch[fa[x]][0] != x && ch[fa[x]][1] != x;
}
void maintain(int x){
    if(!x) return ;
    w[x] = val[x];
    if(ch[x][0] && w[ch[x][0]] > w[x]) w[x] = w[ch[x][0]];
    if(ch[x][1] && w[ch[x][1]] > w[x]) w[x] = w[ch[x][1]];
}
void pushdown(int x){
    if(!x) return ;
    if(flag[x]){
        flag[ch[x][0]] ^= 1;
        flag[ch[x][1]] ^= 1;
        swap(ch[x][0], ch[x][1]);
        flag[x] = 0;
    }
    if(sign[x]){
        sign[ch[x][0]] += sign[x]; w[ch[x][0]] += sign[x]; val[ch[x][0]] += sign[x];
        sign[ch[x][1]] += sign[x]; w[ch[x][1]] += sign[x]; val[ch[x][1]] += sign[x];
        sign[x] = 0;
    }
}
void rotate(int x, bool d){
    int k = ch[x][d ^ 1];
    fa[ch[x][d ^ 1] = ch[k][d]] = x;
    ch[k][d] = x;
    fa[k] = fa[x];
    if(ch[fa[x]][0] == x) ch[fa[x]][0] = k;
    else if(ch[fa[x]][1] == x) ch[fa[x]][1] = k;
    fa[x] = k ;
    maintain(x);
    maintain(k);
}
void splay(int x){
    pushdown(x);
    while(!root(x)){
        int y = fa[x], z = fa[y]; pushdown(z); pushdown(y); pushdown(x);
        bool d1 = x == ch[y][0], d2 = y == ch[z][0];
        if(root(y)) rotate(y, d1);
        else if(d1 == d2) rotate(z, d2), rotate(y, d1);
    }
}

```

```

        else rotate(y, d1 ), rotate(z, d2);
    }
}
void access(int x){
    for(last = 0; x; last = x, x = fa[x] ){
        splay(x);
        ch[x][1] = last;
        maintain(x);
    }
}
void makeroot(int x){
    access(x);
    splay(x);
    flag[x] ^= 1;
}
void link(int x, int y){
    makeroot(x);
    fa[x] = y;
    access(x);
}
void cut(int x){
    access(x);
    splay(x);
    fa[ch[x][0]] = 0;
    ch[x][0] = 0;
    maintain(x);
}
int getroot(int x){
    access(x);
    splay(x);
    int p = x;
    for(; ch[p][0]; p = ch[p][0] ) pushdown(p);
    return p;
}
int lca(int x, int y){
    access(x);
    access(y);
    return last;
}
}
struct edge
{
    int l,r;
}e[maxn];
void work(int x,int v)
{
    val[x]+=v;
    w[ch[x][1]]+=v;val[ch[x][1]]+=v;sign[ch[x][1]]+=v;
    maintain(x);
}
void illegal()
{
    printf("-1\n");
}
int main()
{
    while(cin>>n){
        memset(fa,0,sizeof(fa));memset(ch,0,sizeof(ch));memset(flag,0,sizeof(flag));memset(sign,0,sizeof(sign));
        for(int i=1;i<n;i++)scanf("%d%d",&e[i].l,&e[i].r);
        for(int i=1;i<=n;i++)scanf("%d",&val[i]);
        for(int i=1;i<n;i++)link(e[i].l,e[i].r);
        cin>>m;
        for(int i=1;i<=m;i++){
            int opt,v1,v2,v3;scanf("%d%d%d",&opt,&v1,&v2);
            if(opt==1){
                if(getroot(v1)==getroot(v2))illegal();
                else link(v1,v2);
            }else

```

```

        if(opt==2){
            if(v1==v2||getroot(v1)!=getroot(v2))illegal();
            else {makeroot(v1);cut(v2);}
        }else
        if(opt==3){
            scanf("%d",&v3);
            if(getroot(v2)!=getroot(v3)){
                illegal();
                continue;
            }
            int k=lca(v2,v3);
            access(v2);splay(k);
            work(k,v1);
            access(v3);splay(k);
            work(k,v1);
            val[k]-=v1;maintain(k);
        }
        else {
            if(getroot(v1)!=getroot(v2)){
                illegal();
                continue;
            }
            int k=lca(v1,v2),ans=0;
            access(v1);splay(k);
            if(ch[k][1])ans=max(ans,max(val[k],w[ch[k][1]]));
            else ans=val[k];
            access(v2);splay(k);
            if(ch[k][1])ans=max(ans,max(val[k],w[ch[k][1]]));
            printf("%d\n",ans);
        }
    }
    printf("\n");
}
return 0;
}

```

lucas定理

```

#include<iostream>
#include<cstdio>
#include<cstring>
#include<vector>
#define rep(i, l, r) for(int i = l; i <= r; ++i)
using namespace std;
typedef long long ll;
struct data{
    vector<int>v;
    int & operator [](const int x){
        while(x >= v.size())v.push_back(0);
        return v[x];
    }
}fac;
int n, m, p;
void prepare(){
    fac[0] = 1;
    rep(i, 1, p)fac[i] = (ll)fac[i - 1] * i % p;
}
int qp(int a, int b){
    int ret = 1, tmp = a;
    for(; b; b >>= 1){
        if(b & 1)ret = (ll) ret * tmp % p;
        tmp = (ll)tmp * tmp % p;
    }
    return ret;
}

```



```

int C(int a, int b){
    if(a < b)return 0;
    return (11)fac[a] * qp((11)fac[b] * fac[a - b] % p, p - 2) % p;
}
int lucas(int a, int b){
    return b == 0 ? 1 : (11) C(a % p, b % p) * lucas(a / p, b / p) % p;
}
int main(){
    int cas;
    cin >> cas;
    while(cas--){
        cin >> n >> m >> p;
        prepare();
        printf("%d\n", lucas(n + m, n));
    }
    return 0;
}

```

manacher

```

#include<iostream>
#include<cstdio>
#include<cstring>
#include<algorithm>
#define rep(i, l, r) for(int i = l; i <= r; ++i)
using namespace std;
const int maxn = 240101;
class manacher{
    // hdu 3068
private:
    char s[maxn];
    int len, n, cnt[maxn], f[maxn];
public:
    int solve(char *str){
        n = strlen(str + 1);
        cnt[0] = cnt[1] = 0;
        s[len = 1] = -1;
        rep(i, 1, n){
            s[++len] = 0;
            s[++len] = str[i];
        }
        s[++len] = -2;
        memset(f, 0, sizeof(int) * (len + 2));
        int p = 0;
        f[1] = f[len] = 1;
        for(int i = 2; i < len; ++i){
            cnt[i] = cnt[i - 1] + (s[i] > 0);
            if(p + f[p] - 1 < i)
                for(p = i; s[p - f[p]] == s[p + f[p]]; ) ++f[p];
            else {
                int k = 2 * p - i;
                f[i] = min(f[k], k - (p - f[p]));
                for(; s[i - f[i]] == s[i + f[i]]; ) ++f[i];
                if(i + f[i] > p + f[p]) p = i;
            }
        }
        int ret = 0;
        for(int i = 2; i < len; ++i)
            ret = max(ret, cnt[i + f[i] - 1] - cnt[i - f[i]]);
        return ret;
    }
} solver;
char s[maxn];
int main(){
    while(scanf("%s", s + 1) != EOF)

```

```

        printf("%d\n", solver.solve(s));
    return 0;
}

```

palindromic_tree

```

#include<iostream>
#include<cstdio>
#include<cstring>
#include<string>
#include<cstdlib>
#define rep(i,l,r) for(int i=l;i<=r;++i)
using namespace std;
const int maxn=10001;
struct palindromic_tree{
    int ch[maxn][26],len[maxn],pre[maxn],tot,last,s[maxn],maxlen,cnt[maxn];
    palindromic_tree(){
        tot=1;
        len[0]=0;
        len[1]=-1;
        pre[0]=1;
        s[0]=-1;
        //±0Ðë 0²Ã%Úµãî²³¤¥Êî²0µÃ%ÚµãÊ-1²Ã%Úµãî²³¤¥Êî²-1µÃ%ÚµãÊ-Êô0²%»»»£-Ôô±0Ðë,øch[0][i].³Öµî²1
    }
    int match(int pos){
        while(s[maxlen-len[pos]-1]!=s[maxlen])pos=pre[pos];
        return pos;
    }
    void add(int c){
        s[++maxlen]=c;
        int now=match(last);
        if(!ch[now][c]){
            ++tot;
            pre[tot]=ch[match(pre[now])][c];
            //pre²îch,³Öµóî%ä²»¿É%»»»£¬ñÔô»á¹ò
            ch[now][c]=tot;
            len[tot]=len[now]+2;
        }
        last=ch[now][c];
        //printf("last=%d len=%d now=%d pre=%d\n",last,len[last],now,pre[tot]);
        cnt[last]++;
    }
    void out(){
        rep(i,0,tot)printf("i=%d len=%d pre=%d cnt=%d\n",i,len[i],pre[i],cnt[i]);
    }
    void count(){
        for(int i=tot;i>1;i--)cnt[pre[i]]+=cnt[i];
    }
}t;
string s;
int main(){
    cin>>s;
    rep(i,0,s.size()-1)t.add(s[i]-'a');
    t.out();
    return 0;
}

```

treap

```

#include<iostream>
#include<cstdio>
#include<cstring>

```

```

#include<algorithm>
class Treap{
    int w[maxn], ln[maxn], rn[maxn], size[maxn];
    void maintain(int x){
        size[x] = size[ln[x]] + size[rn[x]] + 1;
    }
    int merge(int x, int y){
        if(!x || !y) return x | y;
        if(rank() % (size[x] + size[y]) < size[x] ){
            rn[x] = merge(rn[x], y);
            maintain(x);
        }
        else {
            ln[y] = merge(x, ln[y]);
            maintain(y);
        }
    }
    pair<int, int> split(int x, int rank) {
        if(!x || !rank) return make_pair(0, x);
        pair<int, int> p;
        if(rank <= size[ln[x]]){
            p = split(ln[x], rank);
            ln[x] = p.second;
            p = make_pair(p.first, x);
            maintain(x);
        }
        else {
            p = split(rn[x], rank - size[ln[x]] - 1);
            rn[x] = p.first;
            p = make_pair(x, p.second);
            maintain(x);
        }
        return p;
    }
};

```

VirtulTree

```

/*
bzoj 3572
*/
#include<iostream>
#include<cstdio>
#include<cstring>
#include<algorithm>
#include<vector>
#define rep(i, l, r) for(int i = l; i <= r; ++i)
using namespace std;
namespace VirtulTree{
    const int logn = 18;
    const int maxn = 3e5 + 10;
    int n, m, fa[maxn][logn + 1], deep[maxn], times, dfn[maxn], stk[maxn], top, rdn[maxn];
    int rt[maxn], d[maxn], size[maxn], ans[maxn];
    bool mark[maxn];
    vector<int> g[maxn], mp, vt[maxn], OutOrder;
    inline void add(int x, int y){
        g[x].push_back(y);
    }
    void dfs(int x){
        dfn[x] = ++times;
        size[x] = 1;
        for(int i = 0; i < g[x].size(); ++i)
            if(fa[x][0] != g[x][i]){
                fa[g[x][i]][0] = x;
                deep[g[x][i]] = deep[x] + 1;
            }
    }
}

```

```

        dfs(g[x][i]);
        size[x] += size[g[x][i]];
    }
    rdfn[x] = times;
}

void init(){
    cin >> n;
    rep(i, 2, n){
        int x, y;
        scanf("%d%d", &x, &y);
        add(x, y);
        add(y, x);
    }
    dfs(1);
    rep(i, 1, logn)
        rep(j, 1, n)
            fa[j][i] = fa[fa[j][i - 1]][i - 1];
    cin >> m;
}

bool cmp(int a, int b){
    return dfn[a] < dfn[b];
}

int lca(int x, int y){
    if(deep[x] < deep[y]) swap(x, y);
    int delta = deep[x] - deep[y];
    for(int i = logn; i >= 0; --i)
        if((delta >> i) & 1) x = fa[x][i];
    if(x == y) return x;
    for(int i = logn; i >= 0; --i)
        if(fa[x][i] != fa[y][i]) x = fa[x][i], y = fa[y][i];
    return fa[x][0];
}

void clear(){
    for(int i = 0; i < mp.size(); ++i){
        mark[mp[i]] = 0;
        d[mp[i]] = n + 1;
        vt[mp[i]].clear();
    }
    for(int i = 0; i < OutOrder.size(); ++i)
        ans[OutOrder[i]] = 0;
    OutOrder.clear();
    mp.clear();
    top = 0;
}

int getpos(int x, int step){
    for(int i = logn; i >= 0; --i)
        if((step >> i) & 1) x = fa[x][i];
    return x;
}

void dfs2(int x){
    ans[rt[x]] += size[x];
    for(int i = 0; i < vt[x].size(); ++i){
        int k = vt[x][i];
        dfs2(k);
        if(rt[k] != rt[x]){
            int len = (deep[k] - deep[x] - 1) - (d[k] - d[x]);
            int p1, p2;
            if(len & 1) {
                if(rt[k] < rt[x])
                    p1 = getpos(k, (len >> 1) + 1);
                else
                    p1 = getpos(k, (len >> 1));
            }
            else
                p1 = getpos(k, len >> 1);
            ans[rt[k]] += size[p1] - size[k];
        }
    }
}

```

```

        ans[rt[x]] -= size[p1];
    }
    else ans[rt[x]] -= size[k];
}
}

void getdist(int x){
    for(int i = 0; i < vt[x].size(); ++i){
        int k = vt[x][i];
        if(d[k] > d[x] + deep[k] - deep[x] || (d[k] == d[x] + deep[k] - deep[x] && rt[x] < rt[k])){
            d[k] = d[x] + deep[k] - deep[x];
            rt[k] = rt[x];
        }
        getdist(k);
        if(d[x] > d[k] + deep[k] - deep[x] || (d[x] == d[k] + deep[k] - deep[x] && rt[k] < rt[x])){
            d[x] = d[k] + deep[k] - deep[x];
            rt[x] = rt[k];
        }
    }
}

void DFS(){
    int root;
    for(int i = 0; i < mp.size(); ++i){
        int now = mp[i];
        if(!top) stk[++top] = root = mp[i], root = now;
        else {
            while(!(dfn[stk[top]] <= dfn[now] && dfn[now] <= rdfs[stk[top]])) --top;
            int last = stk[top], delta = deep[now] - deep[last];
            vt[last].push_back(now);
            stk[++top] = now;
        }
    }
    getdist(root);
    getdist(root);
    dfs2(root);
    if(root != 1) ans[rt[root]] += size[1] - size[root];
}

void solve(){
    rep(i, 1, m){
        int k, x;
        scanf("%d", &k);
        clear();
        rep(j, 1, k){
            scanf("%d", &x);
            mp.push_back(x);
            OutOrder.push_back(x);
            mark[rt[x] = x] = 1;
            d[x] = 0;
        }
        sort(mp.begin(), mp.end(), cmp);
        int tmp = mp.size();
        for(int i = 1; i < tmp; ++i){
            int last = mp[i - 1], now = mp[i];
            int LCA = lca(last, now);
            if(!mark[LCA]){
                mark[LCA] = 1;
                d[LCA] = n + 1;
                mp.push_back(LCA);
            }
        }
        sort(mp.begin(), mp.end(), cmp);
        DFS();
        for(int i = 0; i < OutOrder.size(); ++i)
            printf("%d ", ans[OutOrder[i]]);
        printf("\n");
    }
}

void work(){

```

```

        clear();
        init();
        solve();
    }
}

int main(){
    VirtulTree::work();
    return 0;
}

```

后缀数组

```

#include<iostream>
#include<cstdio>
#include<cstring>
#define rep(i, l, r) for(int i = l; i <= r; ++i)
using namespace std;
const int maxn = 1e5 + 10;
class solver{
private:
    char s[maxn], MaxChar, MinChar;
    int sa[maxn], rank[maxn], n, assist[maxn], cnt[maxn], height[maxn];
public:
    void GetSa(int m){
        int *x = rank, *y = assist;
        rep(i, 1, m) cnt[i] = 0;
        rep(i, 1, n) cnt[x[i] = s[i] - MinChar + 1]++;
        rep(i, 1, m) cnt[i] += cnt[i - 1];
        for(int i = n; i >= 1; --i) sa[cnt[x[i]]--] = i;
        for(int k = 1; k <= n; k <= 1){
            int p = 0;
            rep(i, n - k + 1, n) y[++p] = i;
            rep(i, 1, n) if(sa[i] - k >= 1) y[++p] = sa[i] - k;
            rep(i, 1, m) cnt[i] = 0;
            rep(i, 1, n) cnt[x[i]]++;
            rep(i, 1, m) cnt[i] += cnt[i - 1];
            for(int i = n; i >= 1; --i) sa[cnt[x[y[i]]]--] = y[i];
            p = 1;
            swap(x, y);
            x[sa[1]] = 1;
            rep(i, 2, n)
                x[sa[i]] = y[sa[i]] == y[sa[i - 1]] && y[sa[i] + k] == y[sa[i - 1] + k] ? p : ++p;
            if(p >= n)break;
            m = p;
        }
        rep(i, 1, n) rank[sa[i]] = i;
    }
    void GetHeight(){
        int p = 0;
        rep(i, 1, n){
            if(p) --p;
            if(rank[i] != 1) while(s[i + p] == s[sa[rank[i] - 1] + p]) ++p;
            height[rank[i]] = p;
        }
    }
    void init(){
        scanf("%s", s + 1);
        n = strlen(s + 1);
    }
    void solve(){
        MaxChar = s[1], MinChar = s[1];
        rep(i, 1, n)
            MaxChar = max(MaxChar, s[i]),
            MinChar = min(MinChar, s[i]);
        GetSa(MaxChar - MinChar + 1);
    }
}

```

```
    }  
}Solver;
```

后缀自动机（非字典树）

```
#include<iostream>  
#include<cstdio>  
#include<cstring>  
#define rep(i, l, r) for(int i = l; i <= r; ++i)  
using namespace std;  
int MinLen;  
const int maxn = 2e5 + 20;  
char s[maxn];  
int pre[maxn], step[maxn], ch[maxn][52], last, cnt[maxn], g[maxn], cnt2[maxn], tot;  
int order[maxn];  
/* xÖµäË÷  
void insert(int k){  
    int p=last;  
    if(ch[p][k]){  
        if(step[p]+1==step[ch[p][k]])last=ch[p][k];  
        else {  
            int q=ch[p][k],nq=++tot;  
            memcpy(ch[nq],ch[q],sizeof(ch[nq]));  
            step[nq]=step[p]+1;  
            pre[nq]=pre[q];  
            pre[q]=nq;  
            last=nq;  
            for(;p&&ch[p][k]==q;p=pre[p])ch[p][k]=nq;  
            if(!p&&ch[p][k]==q)ch[p][k]=nq;  
        }  
        return ;  
    }  
    int np=++tot;  
    last=np;  
    step[np]=step[p]+1;  
    for(;p&&!ch[p][k];p=pre[p])ch[p][k]=np;  
    if(!p&&!ch[p][k])ch[p][k]=np,pre[np]=p;  
    else if(step[p]+1==step[ch[p][k]])pre[np]=ch[p][k];  
    else {  
        int q=ch[p][k],nq=++tot;  
        memcpy(ch[nq],ch[q],sizeof(ch[nq]));  
        step[nq]=step[p]+1;  
        pre[nq]=pre[q];  
        pre[q]=pre[np]=nq;  
        for(;p&&ch[p][k]==q;p=pre[p])ch[p][k]=nq;  
        if(!p&&ch[p][k]==q)ch[p][k]=nq;  
    }  
}  
*/  
void add(int k){  
    int p = last, np = ++tot;  
    step[np] = step[p] + 1;  
    last = np;  
    for(; p && !ch[p][k]; p = pre[p]) ch[p][k] = np;  
    if(!p && !ch[p][k]) ch[p][k] = np, pre[np] = p;  
    else if(step[ch[p][k]] == step[p] + 1) pre[np] = ch[p][k];  
    else {  
        int q = ch[p][k], nq = ++tot;  
        memcpy(ch[nq], ch[q], sizeof(ch[q]));  
        step[nq] = step[p] + 1;  
        pre[nq] = pre[q];  
        pre[q] = pre[np] = nq;  
        for(; p && ch[p][k] == q; p = pre[p]) ch[p][k] = nq;  
        if(!p && ch[p][k] == q) ch[p][k] = nq;  
    }  
}
```

```

        ++cnt[np];
    }
    void clear(){
        rep(i, 0, tot) memset(ch[i], 0, sizeof(ch[i]));
        rep(i, 0, tot) step[i] = pre[i] = cnt[i] = g[i] = cnt2[i] = 0;
        last = tot = 0;
    }
    void RadixSort(){
        rep(i, 1, tot) g[step[i]]++;
        rep(i, 1, n) g[i] += g[i - 1];
        rep(i, 1, tot) order[g[step[i]]--] = i;
    }
    int main(){
        while(cin >> MinLen && MinLen){
            scanf("%s", s + 1);
            int n = strlen(s + 1);
            clear();
            rep(i, 1, n)
                add( s[i] <= 'z' && s[i] >= 'a' ? s[i] - 'a' : s[i] - 'A' + 26);
        }
        return 0;
    }
}

```

后缀自动机（含字典树）

```

#include<iostream>
#include<cstdio>
#include<cstring>
#define rep(i, l, r) for(int i = l; i <= r; ++i)
using namespace std;
int MinLen;
const int maxn = 2e5 + 20;
char s[maxn];
int pre[maxn], step[maxn], ch[maxn][52], last, cnt[maxn], g[maxn], cnt2[maxn], tot;
int order[maxn];
/* ×ÖµäË÷
void insert(int k){
    int p=last;
    if(ch[p][k]){
        if(step[p]+1==step[ch[p][k]])last=ch[p][k];
        else {
            int q=ch[p][k],nq=++tot;
            memcpy(ch[nq],ch[q],sizeof(ch[nq]));
            step[nq]=step[p]+1;
            pre[nq]=pre[q];
            pre[q]=nq;
            last=nq;
            for(;p&&ch[p][k]==q;p=pre[p])ch[p][k]=nq;
            if(!p&&ch[p][k]==q)ch[p][k]=nq;
        }
    }
    return ;
}
int np=++tot;
last=np;
step[np]=step[p]+1;
for(;p&&!ch[p][k];p=pre[p])ch[p][k]=np;
if(!p&&!ch[p][k])ch[p][k]=np,pre[np]=p;
else if(step[p]+1==step[ch[p][k]])pre[np]=ch[p][k];
else {
    int q=ch[p][k],nq=++tot;
    memcpy(ch[nq],ch[q],sizeof(ch[nq]));
    step[nq]=step[p]+1;
    pre[nq]=pre[q];
    pre[q]=pre[np]=nq;
    for(;p&&ch[p][k]==q;p=pre[p])ch[p][k]=nq;
}
}

```



```

        if(!p&&ch[p][k]==q)ch[p][k]=nq;
    }
}
*/
void add(int k){
    int p = last, np = ++tot;
    step[np] = step[p] + 1;
    last = np;
    for(; p && !ch[p][k]; p = pre[p]) ch[p][k] = np;
    if(!p && !ch[p][k]) ch[p][k] = np, pre[np] = p;
    else if(step[ch[p][k]] == step[p] + 1) pre[np] = ch[p][k];
    else {
        int q = ch[p][k], nq = ++tot;
        memcpy(ch[nq], ch[q], sizeof(ch[q]));
        step[nq] = step[p] + 1;
        pre[nq] = pre[q];
        pre[q] = pre[np] = nq;
        for(; p && ch[p][k] == q; p = pre[p]) ch[p][k] = nq;
        if(!p && ch[p][k] == q) ch[p][k] = nq;
    }
    ++cnt[np];
}
void clear(){
    rep(i, 0, tot) memset(ch[i], 0, sizeof(ch[i]));
    rep(i, 0, tot) step[i] = pre[i] = cnt[i] = g[i] = cnt2[i] = 0;
    last = tot = 0;
}
void RadixSort(){
    rep(i, 1, tot) g[step[i]]++;
    rep(i, 1, n) g[i] += g[i - 1];
    rep(i, 1, tot) order[g[step[i]]--] = i;
}
int main(){
    while(cin >> MinLen && MinLen){
        scanf("%s", s + 1);
        int n = strlen(s + 1);
        clear();
        rep(i, 1, n)
            add( s[i] <= 'z' && s[i] >= 'a' ? s[i] - 'a' : s[i] - 'A' + 26);
    }
    return 0;
}

```

可持久化并查集

```

#include<iostream>
#include<cstdio>
#include<cstring>
#define rep(i, l, r) for(int i = l; i <= r; ++i)
using namespace std;
const int maxn = 2e5 + 10;
const int logn = 40;
int root[maxn], tot, n, m;
int ln[maxn * logn], rn[maxn * logn], rank[maxn * logn], fa[maxn * logn];
void build(int &x, int l, int r){
    x = ++tot;
    if(l == r) fa[x] = l;
    else {
        int mid = (l + r) >> 1;
        build(ln[x], l, mid);
        build(rn[x], mid + 1, r);
    }
}
void modify(int &x, int last, int l, int r, int p1, int p2){
    x = ++tot;

```

```

    if(l == r){
        fa[x] = p2;
        return ;
    }
    ln[x] = ln[last]; rn[x] = rn[last];
    int mid = (l + r) >> 1;
    if(p1 <= mid) modify(ln[x], ln[last], l, mid, p1, p2);
    else modify(rn[x], rn[last], mid + 1, r, p1, p2);
}
int query(int x, int l, int r, int pos){
    if(l == r) return x;
    int mid = (l + r) >> 1;
    if(pos <= mid) return query(ln[x], l, mid, pos);
    else return query(rn[x], mid + 1, r, pos);
}
int get(int rt, int x){
    int k = query(rt, 1, n, x);
    if(fa[k] == x) return k;
    return get(rt, fa[k]);
}
void add(int &x, int last , int l, int r, int pos){
    x = ++tot;
    if(l == r)
        rank[x] = rank[last] + 1, fa[x] = fa[last];
    else {
        ln[x] = ln[last];
        rn[x] = rn[last];
        int mid = (l + r) >> 1;
        if(pos <= mid) add(ln[x], ln[last] ,l, mid, pos);
        else add(rn[x], rn[last] ,mid + 1, r, pos);
    }
}
int main(){
    cin >> n >> m;
    build(root[0], 1, n);
    rep(i, 1, m){
        int opt;
        scanf("%d", &opt);
        if(opt == 1){
            int x, y;
            scanf("%d%d", &x, &y);
            root[i] = root[i - 1];
            int r1 = get
            (root[i - 1], x), r2 = get(root[i - 1], y);
            if(fa[r1] == fa[r2]) continue;
            if(rank[r1] > rank[r2]) swap(r1, r2);
            modify(root[i], root[i - 1], 1, n, fa[r1], fa[r2]);
            if(rank[r1] == rank[r2]);
                add(root[i], root[i], 1, n, fa[r2]);
        }
        else if(opt == 2){
            int k;
            scanf("%d", &k);
            root[i] = root[k];
        }
        else {
            int x, y;
            scanf("%d%d", &x, &y);
            root[i] = root[i - 1];
            int r1 = get(root[i], x), r2 = get(root[i], y);
            printf("%d\n", fa[r1] == fa[r2]);
        }
    }
    return 0;
}

```

扩展kmp

```
#include<iostream>
#include<cstdio>
#include<cstring>
#include<algorithm>
#define rep(i, l, r) for(int i = l; i <= r; ++i)
using namespace std;
const int maxn = 2e5 + 10;
int n, len, f[maxn];
char s[maxn];
// hdu 43333
void exkmp(){
    int p = 1;
    f[p] = 0;
    rep(i, 2, n){
        f[i] = 0;
        if(p + f[p] - 1 < i)
            while(s[i + f[i]] == s[1 + f[i]]) ++f[i];
        else {
            f[i] = min(f[i - p + 1], p + f[p] - i);
            while(s[i + f[i]] == s[1 + f[i]]) ++f[i];
        }
        if(i + f[i] > p + f[p]) p = i;
    }
}
int main(){
    int cas, cnt1, cnt2, cnt3, val;
    cin >> cas;
    rep(num, 1, cas){
        cnt1 = cnt2 = cnt3 = 0;
        val = 1;
        scanf("%s", s + 1);
        n = strlen(s + 1);
        len = n << 1;
        rep(i, 1, n) s[n + i] = s[i];
        exkmp();
        f[1] = len;
        rep(i, 1, n)
            if(f[i] >= n)
                cnt2++;
            else if(s[f[i] + 1] > s[i + f[i]]) cnt1++;
            else cnt3++;
        cnt1/=cnt2;
        cnt3/=cnt2;
        cnt2 = 1;
        printf("Case %d: %d %d %d\n", num, cnt1, cnt2, cnt3);
    }
    return 0;
}
```

全局最小割

```
#include<iostream>
#include<cstdio>
#include<cstring>
#define maxn 510
#define rep(i,l,r) for(int i=l;i<=r;++i)
using namespace std;
const int INF=1<<29;
struct programmer{
    int n,m,d[maxn];
    int w[maxn][maxn],cut,ans;
    bool use[maxn],vis[maxn];
```

```

void init(){
    cin>>n>>m;
    rep(i,1,m){
        int l,r,v;scanf("%d%d%d",&l,&r,&v);
        w[l][r]+=v;
        w[r][l]+=v;
    }
}

int prim(){
    memset(d,0,sizeof(d));
    memset(vis,0,sizeof(vis));
    int s,t;
    cut=0;
    while(1){
        int maxv=-INF,pos;
        rep(i,1,n)if(!use[i]&&!vis[i]&&d[i]>maxv){
            maxv=d[i];
            pos=i;
        }
        if(maxv== -INF){
            rep(i,1,n)if(!use[i]){
                w[i][s]+=w[i][t];
                w[s][i]+=w[i][t];
            }
            return t;
        }
        cut=maxv;
        vis[pos]=1;
        s=t; t=pos;
        rep(i,1,n)
            if(!use[i]&&!vis[i])d[i]+=w[pos][i];
    }
}

void work(){
    ans=INF;
    rep(i,2,n){
        int k=prim();
        use[k]=1;
        if(cut<ans)ans=cut;
    }
    printf("%d\n",ans);
}

}program;

int main(){
    program.init();
    program.work();
    return 0;
}

```

最小表示法

```

#include<iostream>
#include<cstdio>
#include<cstring>
#define rep(i, l, r) for(int i = l; i <= r; ++i)
using namespace std;
// zju 2006
int solve(char *s){
    int i = 1, j = 2, len = strlen(s + 1), k = 0;
    while(i <= len && j <= len){
        if(k == len) return min(i, j);
        int p1 = i + k > len ? i + k - len : i + k,
            p2 = j + k > len ? j + k - len : j + k;
        if(s[p1] == s[p2]) ++k;
        else if(s[p1] > s[p2]){

```

```

        i += k + 1;
        if(i == j) ++i;
        k = 0;
    }
    else {
        j += k + 1;
        if(i == j) ++j;
        k = 0;
    }
}
return min(i, j);
}
char s[1001];
int main(){
    int n;
    cin >> n;
    rep(i, 1, n){
        scanf("%s", s + 1);
        printf("%d\n", solve(s));
    }
    return 0;
}

```

左偏树 & 斜堆

```

#include<cstdio>
#include<algorithm>
using namespace std;
#define N 1000100
int n,m,w[N],l[N],r[N],d[N],fa[N];bool died[N];char str[9];
int find(int x){return x==fa[x]?x:fa[x]=find(fa[x]);}
int merge(int x,int y){
    if(!x)return y;
    if(!y)return x;
    if(w[x] > w[y]) swap(x,y);
    r[x] = merge(r[x],y);
    /* if(d[r[x]] > d[l[x]]) swap(r[x],l[x]); */
    d[x] = d[r[x]] + 1;
    swap(l[x], r[x]);
    return x;
}

```