

Assignment 2

April 9, 2021

*You are currently looking at **version 1.5** of this notebook. To download notebooks and datafiles, as well as get help on Jupyter notebooks in the Coursera platform, visit the [Jupyter Notebook FAQ](#) course resource.*

1 Assignment 2

In this assignment you'll explore the relationship between model complexity and generalization performance, by adjusting key parameters of various supervised learning models. Part 1 of this assignment will look at regression and Part 2 will look at classification.

1.1 Part 1 - Regression

First, run the following block to set up the variables needed for later sections.

```
In [110]: import numpy as np
import pandas as pd
from sklearn.model_selection import train_test_split

np.random.seed(0)
n = 15
x = np.linspace(0,10,n) + np.random.randn(n)/5
y = np.sin(x)+x/6 + np.random.randn(n)/10

#print(x)
#print(y)
X_train, X_test, y_train, y_test = train_test_split(x, y, random_state=0)

# You can use this function to help you visualize the dataset by
# plotting a scatterplot of the data points
# in the training and test sets.
def part1_scatter():
    import matplotlib.pyplot as plt
    %matplotlib notebook
```

```

plt.figure()
plt.scatter(X_train, y_train, label='training data')
plt.scatter(X_test, y_test, label='test data')
plt.legend(loc=4);

# NOTE: Uncomment the function below to visualize the data, but be sure
# to **re-comment it before submitting this assignment to the autograder
#part1_scatter()
#print(x.shape)
#print(X_train.shape)

```

1.1.1 Question 1

Write a function that fits a polynomial LinearRegression model on the *training data* `X_train` for degrees 1, 3, 6, and 9. (Use `PolynomialFeatures` in `sklearn.preprocessing` to create the polynomial features and then fit a linear regression model) For each model, find 100 predicted values over the interval $x = 0$ to 10 (e.g. `np.linspace(0, 10, 100)`) and store this in a numpy array. The first row of this array should correspond to the output from the model trained on degree 1, the second row degree 3, the third row degree 6, and the fourth row degree 9.

The figure above shows the fitted models plotted on top of the original data (using `plot_one()`).

This function should return a numpy array with shape (4, 100)

```

In [111]: from sklearn.linear_model import LinearRegression
          from sklearn.preprocessing import PolynomialFeatures
          X_train, X_test, y_train, y_test = train_test_split(x, y, random_state = 0)

          np.random.seed(0)
          n = 15
          x = np.linspace(0, 10, n) + np.random.randn(n)/5
          y = np.sin(x) + x/6 + np.random.randn(n)/10

          def answer_one():
              from sklearn.linear_model import LinearRegression
              from sklearn.preprocessing import PolynomialFeatures

              # Your code here
              X_train, X_test, y_train, y_test = train_test_split(x, y, random_state=0)
              poly_1 = PolynomialFeatures(degree=1)
              poly_3 = PolynomialFeatures(degree=3)
              poly_6 = PolynomialFeatures(degree=6)
              poly_9 = PolynomialFeatures(degree=9)
              X_train = X_train.reshape(-1, 1)
              x_poly_1 = poly_1.fit_transform(X_train)
              x_poly_3 = poly_3.fit_transform(X_train)
              x_poly_6 = poly_6.fit_transform(X_train)

```

```

x_poly_9 = poly_9.fit_transform(X_train)

x_predict = np.linspace(0,10,100).reshape(-1,1)
x_predict_1 = poly_1.fit_transform(x_predict)
x_predict_3 = poly_3.fit_transform(x_predict)
x_predict_6 = poly_6.fit_transform(x_predict)
x_predict_9 = poly_9.fit_transform(x_predict)
#x_polys = [x_poly_1,x_poly_3,x_poly_6,x_poly_9]
modell1 = LinearRegression()
model3 = LinearRegression()
model6 = LinearRegression()
model9 = LinearRegression()
modell1.fit(x_poly_1, y_train)
model3.fit(x_poly_3, y_train)
model6.fit(x_poly_6, y_train)
model9.fit(x_poly_9, y_train)
prediction1 = None
prediction3 = None
prediction6 = None
prediction9 = None
predictions = [prediction1,prediction3,prediction6,prediction9]
degrees = [1,3,6,9]

X_train_1, X_test_1, y_train_1, y_test_1 = train_test_split(x_poly_1,
X_train_3, X_test_3, y_train_3, y_test_3 = train_test_split(x_poly_3,
X_train_6, X_test_6, y_train_6, y_test_6 = train_test_split(x_poly_6,
X_train_9, X_test_9, y_train_9, y_test_9 = train_test_split(x_poly_9,

#x_predict_poly_1 = modell1.transform(x_predict)
#x_predict_poly_3 = model3.transform(x_predict)
#x_predict_poly_6 = model6.transform(x_predict)
#x_predict_poly_9 = model9.transform(x_predict)
#linreg1 = LinearRegression().fit(X_train_1, y_train_1)
#linreg3 = LinearRegression().fit(X_train_3, y_train_3)
#linreg6 = LinearRegression().fit(X_train_6, y_train_6)
#linreg9 = LinearRegression().fit(X_train_9, y_train_9)
prediction1 = modell1.predict(x_predict_1)
prediction3 = model3.predict(x_predict_3)
prediction6 = model6.predict(x_predict_6)
prediction9 = model9.predict(x_predict_9)
predictions = np.array([prediction1, prediction3, prediction6, prediction9])
return predictions

#answer_one()

```

```

In [112]: # feel free to use the function plot_one() to replicate the figure
# from the prompt once you have completed question one
#def plot_one(degree_predictions):

```

```

import matplotlib.pyplot as plt
%matplotlib notebook
plt.figure(figsize=(10,5))
plt.plot(X_train, y_train, 'o', label='training data', markersize=10)
plt.plot(X_test, y_test, 'o', label='test data', markersize=10)
for i, degree in enumerate([1,3,6,9]):
    plt.plot(np.linspace(0,10,100), degree_predictions[i], alpha=0.8)
plt.ylim(-1,2.5)
plt.legend(loc=4)

plot_one(answer_one())

```

1.1.2 Question 2

Write a function that fits a polynomial LinearRegression model on the training data `X_train` for degrees 0 through 9. For each model compute the R^2 (coefficient of determination) regression score on the training data as well as the the test data, and return both of these arrays in a tuple.

This function should return one tuple of numpy arrays (`r2_train`, `r2_test`). Both arrays should have shape `(10,)`

```

In [113]: from sklearn.linear_model import LinearRegression
          from sklearn.preprocessing import PolynomialFeatures
          X_train, X_test, y_train, y_test = train_test_split(x, y, random_state = 0)

          np.random.seed(0)
          n = 15
          x = np.linspace(0,10,n) + np.random.randn(n)/5
          y = np.sin(x)+x/6 + np.random.randn(n)/10
          def answer_two():

              from sklearn.linear_model import LinearRegression
              from sklearn.preprocessing import PolynomialFeatures
              from sklearn.metrics.regression import r2_score
              X_train, X_test, y_train, y_test = train_test_split(x, y, random_state = 0)
              poly_0 = PolynomialFeatures(degree=0)
              poly_1 = PolynomialFeatures(degree=1)
              poly_2 = PolynomialFeatures(degree=2)
              poly_3 = PolynomialFeatures(degree=3)
              poly_4 = PolynomialFeatures(degree=4)
              poly_5 = PolynomialFeatures(degree=5)
              poly_6 = PolynomialFeatures(degree=6)
              poly_7 = PolynomialFeatures(degree=7)
              poly_8 = PolynomialFeatures(degree=8)
              poly_9 = PolynomialFeatures(degree=9)
              X_train = X_train.reshape(-1,1)
              x_poly_0 = poly_0.fit_transform(X_train)
              x_poly_1 = poly_1.fit_transform(X_train)
              x_poly_2 = poly_2.fit_transform(X_train)

```

```

x_poly_3 = poly_3.fit_transform(X_train)
x_poly_4 = poly_4.fit_transform(X_train)
x_poly_5 = poly_5.fit_transform(X_train)
x_poly_6 = poly_6.fit_transform(X_train)
x_poly_7 = poly_7.fit_transform(X_train)
x_poly_8 = poly_8.fit_transform(X_train)
x_poly_9 = poly_9.fit_transform(X_train)

X_test = X_test.reshape(-1,1)
x_test_0 = poly_0.fit_transform(X_test)
x_test_1 = poly_1.fit_transform(X_test)
x_test_2 = poly_2.fit_transform(X_test)
x_test_3 = poly_3.fit_transform(X_test)
x_test_4 = poly_4.fit_transform(X_test)
x_test_5 = poly_5.fit_transform(X_test)
x_test_6 = poly_6.fit_transform(X_test)
x_test_7 = poly_7.fit_transform(X_test)
x_test_8 = poly_8.fit_transform(X_test)
x_test_9 = poly_9.fit_transform(X_test)

model0 = LinearRegression()
model1 = LinearRegression()
model2 = LinearRegression()
model3 = LinearRegression()
model4 = LinearRegression()
model5 = LinearRegression()
model6 = LinearRegression()
model7 = LinearRegression()
model8 = LinearRegression()
model9 = LinearRegression()

degrees = [0,1,2,3,4,5,6,7,8,9]

model0.fit(x_poly_0, y_train)
model1.fit(x_poly_1, y_train)
model2.fit(x_poly_2, y_train)
model3.fit(x_poly_3, y_train)
model4.fit(x_poly_4, y_train)
model5.fit(x_poly_5, y_train)
model6.fit(x_poly_6, y_train)
model7.fit(x_poly_7, y_train)
model8.fit(x_poly_8, y_train)
model9.fit(x_poly_9, y_train)

#print(X_train_0.shape)
#print(y_train_0.shape)

```

```

prediction_train0 = model0.predict(x_poly_0)
prediction_train1 = model1.predict(x_poly_1)
prediction_train2 = model2.predict(x_poly_2)
prediction_train3 = model3.predict(x_poly_3)
prediction_train4 = model4.predict(x_poly_4)
prediction_train5 = model5.predict(x_poly_5)
prediction_train6 = model6.predict(x_poly_6)
prediction_train7 = model7.predict(x_poly_7)
prediction_train8 = model8.predict(x_poly_8)
prediction_train9 = model9.predict(x_poly_9)

```

```

prediction_test0 = model0.predict(x_test_0)
prediction_test1 = model1.predict(x_test_1)
prediction_test2 = model2.predict(x_test_2)
prediction_test3 = model3.predict(x_test_3)
prediction_test4 = model4.predict(x_test_4)
prediction_test5 = model5.predict(x_test_5)
prediction_test6 = model6.predict(x_test_6)
prediction_test7 = model7.predict(x_test_7)
prediction_test8 = model8.predict(x_test_8)
prediction_test9 = model9.predict(x_test_9)
#print(X_train_0, prediction_train0)

```

```

r2_train_0 = r2_score(y_train, prediction_train0)
r2_train_1 = r2_score(y_train, prediction_train1)
r2_train_2 = r2_score(y_train, prediction_train2)
r2_train_3 = r2_score(y_train, prediction_train3)
r2_train_4 = r2_score(y_train, prediction_train4)
r2_train_5 = r2_score(y_train, prediction_train5)
r2_train_6 = r2_score(y_train, prediction_train6)
r2_train_7 = r2_score(y_train, prediction_train7)
r2_train_8 = r2_score(y_train, prediction_train8)
r2_train_9 = r2_score(y_train, prediction_train9)
#print(X_test_0, prediction_test0)

```

```

r2_test_0 = r2_score(y_test, prediction_test0)
r2_test_1 = r2_score(y_test, prediction_test1)
r2_test_2 = r2_score(y_test, prediction_test2)
r2_test_3 = r2_score(y_test, prediction_test3)
r2_test_4 = r2_score(y_test, prediction_test4)
r2_test_5 = r2_score(y_test, prediction_test5)
r2_test_6 = r2_score(y_test, prediction_test6)
r2_test_7 = r2_score(y_test, prediction_test7)
r2_test_8 = r2_score(y_test, prediction_test8)
r2_test_9 = r2_score(y_test, prediction_test9)

```

```

#r2_train = [r2_train_0,r2_train_1,r2_train_2,r2_train_3,r2_train_4,r2_train_5,
             #r2_train_6,r2_train_7,r2_train_8,r2_train_9]
#r2_test = [r2_test_0,r2_test_1,r2_test_2,r2_test_3,r2_test_4,r2_test_5,r2_test_6,
            #r2_test_7,r2_test_8,r2_test_9]
r2_train = np.array([r2_train_0, r2_train_1, r2_train_2, r2_train_3, r2_train_4,
                    r2_train_5, r2_train_6, r2_train_7, r2_train_8, r2_train_9])
r2_test = np.array([r2_test_0, r2_test_1, r2_test_2, r2_test_3, r2_test_4,
                    r2_test_5, r2_test_6, r2_test_7, r2_test_8, r2_test_9])
return (r2_train, r2_test)

#answer_two()

def plot(degree_predictions):
    import matplotlib.pyplot as plt
    %matplotlib notebook
    plt.figure(figsize=(10,5))
    degrees = np.arange(0,10,1)
    plt.plot(degrees, r2_train, '-o',label='training data', markersize=10)
    plt.plot(degrees, r2_test, '-o', label='test data', markersize=10)
    degrees = np.arange(0,11,1)
    for i,degree in enumerate([0,1,2,3,4,5,6,7,8,9]):
        plt.plot(np.arange(0,11,1), degree_predictions[i], alpha=0.8, lw=2)
    plt.xlim(0,10)
    plt.ylim(-0.9,1.2)
    plt.legend(loc=4)

plot(answer_two())
print(answer_two())

```

1.1.3 Question 3

Based on the R^2 scores from question 2 (degree levels 0 through 9), what degree level corresponds to a model that is underfitting? What degree level corresponds to a model that is overfitting? What choice of degree level would provide a model with good generalization performance on this dataset?

Hint: Try plotting the R^2 scores from question 2 to visualize the relationship between degree level and R^2 . Remember to comment out the import matplotlib line before submission.

This function should return one tuple with the degree values in this order: (Underfitting, Overfitting, Good_Generalization). There might be multiple correct solutions, however, you only need to return one possible solution, for example, (1,2,3).

```

In [114]: def answer_three():

    # Your code here
    degree_range = [0,1,2,3,4,5,6,7,8,9]
    r2_train, r2_test = answer_two()

    r2_train_sorted = np.sort(r2_train)

```

```

r2_test_sorted = np.sort(r2_test)

# Initialize the values
Underfitting = 0
Overfitting = 0
Good_Generalization = 0
min_r2_train = np.min(r2_train)
max_r2_train = np.max(r2_train)
mean_r2_train = np.mean(r2_train)
min_r2_test = np.min(r2_test)
max_r2_test = np.max(r2_test)
mean_r2_test = np.mean(r2_test)

for degree, data in zip(degree_range, zip(r2_train, r2_test)):
    if data[0] == min_r2_train and data[1] == min_r2_test:
        Underfitting = degree
    if data[0] > r2_train_sorted[1] and data[1] <= r2_test_sorted[1]:
        Overfitting = degree
    if data[0] < max_r2_train and data[1] == max_r2_test:
        Good_Generalization = degree

return Underfitting, Overfitting, Good_Generalization

#return #(0,9,7) # Return your answer
#r2_train, r2_test = answer_two()

# Sort the scores
#r2_train_sorted = np.sort(r2_train)
#r2_test_sorted = np.sort(r2_test)

# Initialize the values
#Underfitting = 0
#Overfitting = 0
#Good_Generalization = 0
#min_r2_train = np.min(r2_train)
#max_r2_train = np.max(r2_train)
#mean_r2_train = np.mean(r2_train)
#min_r2_test = np.min(r2_test)
#max_r2_test = np.max(r2_test)
#mean_r2_test = np.mean(r2_test)
#print(min_r2_train, min_r2_test)
#print(max_r2_train, max_r2_test)
#print(mean_r2_train, mean_r2_test)

#answer_three()
#answer_two()

```


1.1.4 Question 4

Training models on high degree polynomial features can result in overly complex models that overfit, so we often use regularized versions of the model to constrain model complexity, as we saw with Ridge and Lasso linear regression.

For this question, train two models: a non-regularized LinearRegression model (default parameters) and a regularized Lasso Regression model (with parameters $\alpha=0.01$, $\text{max_iter}=10000$) both on polynomial features of degree 12. Return the R^2 score for both the LinearRegression and Lasso model's test sets.

This function should return one tuple (LinearRegression_R2_test_score, Lasso_R2_test_score)

```
In [115]: def answer_four():
    from sklearn.preprocessing import PolynomialFeatures
    from sklearn.linear_model import Lasso, LinearRegression
    from sklearn.metrics.regression import r2_score
    from sklearn.preprocessing import MinMaxScaler
    scaler = MinMaxScaler()

    # Your code here
    X_train, X_test, y_train, y_test = train_test_split(x, y, random_state=42)
    X_train = X_train.reshape(-1,1)
    X_test = X_test.reshape(-1,1)
    #X_train_scaled = scaler.fit_transform(X_train)
    #X_test_scaled = scaler.transform(X_test)
    poly = PolynomialFeatures(degree=12)
    model1 = LinearRegression()
    model2 = Lasso(alpha=0.01, max_iter = 10000)
    x_poly_train = poly.fit_transform(X_train)
    x_poly_test = poly.fit_transform(X_test)
    model1.fit(x_poly_train, y_train)
    model2.fit(x_poly_train, y_train)
    linear_prediction_test = model1.predict(x_poly_test)
    lasso_prediction_test = model2.predict(x_poly_test)
    r2_test_linear = r2_score(y_test, linear_prediction_test)
    r2_test_lasso = r2_score(y_test, lasso_prediction_test)

    return (r2_test_linear, r2_test_lasso) # Your answer here
#answer_four()
```

1.2 Part 2 - Classification

Here's an application of machine learning that could save your life! For this section of the assignment we will be working with the [UCI Mushroom Data Set](#) stored in `readonly/mushrooms.csv`. The data will be used to train a model to predict whether or not a mushroom is poisonous. The following attributes are provided:

Attribute Information:

1. cap-shape: bell=b, conical=c, convex=x, flat=f, knobbed=k, sunken=s
2. cap-surface: fibrous=f, grooves=g, scaly=y, smooth=s
3. cap-color: brown=n, buff=b, cinnamon=c, gray=g, green=r, pink=p, purple=u, red=e, white=w, yellow=y
4. bruises?: bruises=t, no=f
5. odor: almond=a, anise=l, creosote=c, fishy=y, foul=f, musty=m, none=n, pungent=p, spicy=s
6. gill-attachment: attached=a, descending=d, free=f, notched=n
7. gill-spacing: close=c, crowded=w, distant=d
8. gill-size: broad=b, narrow=n
9. gill-color: black=k, brown=n, buff=b, chocolate=h, gray=g, green=r, orange=o, pink=p, purple=u, red=e, white=w, yellow=y
10. stalk-shape: enlarging=e, tapering=t
11. stalk-root: bulbous=b, club=c, cup=u, equal=e, rhizomorphs=z, rooted=r, missing=?
12. stalk-surface-above-ring: fibrous=f, scaly=y, silky=k, smooth=s
13. stalk-surface-below-ring: fibrous=f, scaly=y, silky=k, smooth=s
14. stalk-color-above-ring: brown=n, buff=b, cinnamon=c, gray=g, orange=o, pink=p, red=e, white=w, yellow=y
15. stalk-color-below-ring: brown=n, buff=b, cinnamon=c, gray=g, orange=o, pink=p, red=e, white=w, yellow=y
16. veil-type: partial=p, universal=u
17. veil-color: brown=n, orange=o, white=w, yellow=y
18. ring-number: none=n, one=o, two=t
19. ring-type: cobwebby=c, evanescent=e, flaring=f, large=l, none=n, pendant=p, sheathing=s, zone=z
20. spore-print-color: black=k, brown=n, buff=b, chocolate=h, green=r, orange=o, purple=u, white=w, yellow=y
21. population: abundant=a, clustered=c, numerous=n, scattered=s, several=v, solitary=y
22. habitat: grasses=g, leaves=l, meadows=m, paths=p, urban=u, waste=w, woods=d

The data in the mushrooms dataset is currently encoded with strings. These values will need to be encoded to numeric to work with sklearn. We'll use `pd.get_dummies` to convert the categorical variables into indicator variables.

```
In [116]: import pandas as pd
import numpy as np
from sklearn.model_selection import train_test_split

mush_df = pd.read_csv('mushrooms.csv')
mush_df2 = pd.get_dummies(mush_df)

X_mush = mush_df2.iloc[:,2:]
y_mush = mush_df2.iloc[:,1]

# use the variables X_train2, y_train2 for Question 5
X_train2, X_test2, y_train2, y_test2 = train_test_split(X_mush, y_mush, r
```

```

# For performance reasons in Questions 6 and 7, we will create a smaller
# entire mushroom dataset for use in those questions. For simplicity we
# the 25% test split created above as the representative subset.
#
# Use the variables X_subset, y_subset for Questions 6 and 7.
X_subset = X_test2
y_subset = y_test2

```

1.2.1 Question 5

Using `X_train2` and `y_train2` from the preceeding cell, train a `DecisionTreeClassifier` with default parameters and `random_state=0`. What are the 5 most important features found by the decision tree?

As a reminder, the feature names are available in the `X_train2.columns` property, and the order of the features in `X_train2.columns` matches the order of the feature importance values in the classifier's `feature_importances_` property.

This function should return a list of length 5 containing the feature names in descending order of importance.

Note: remember that you also need to set `random_state` in the `DecisionTreeClassifier`.

```

In [117]: def answer_five():
            from sklearn.tree import DecisionTreeClassifier

            # Your code here
            clf = DecisionTreeClassifier(random_state=0).fit(X_train2, y_train2)
            top_five = clf.feature_importances_.argsort()[::-1][:5]
            result = list(X_train2.columns[top_five])

            return result# Your answer here

```

1.2.2 Question 6

For this question, we're going to use the `validation_curve` function in `sklearn.model_selection` to determine training and test scores for a Support Vector Classifier (SVC) with varying parameter values. Recall that the `validation_curve` function, in addition to taking an initialized unfitted classifier object, takes a dataset as input and does its own internal train-test splits to compute results.

Because creating a validation curve requires fitting multiple models, for performance reasons this question will use just a subset of the original mushroom dataset: please use the variables `X_subset` and `y_subset` as input to the validation curve function (instead of `X_mush` and `y_mush`) to reduce computation time.

The initialized unfitted classifier object we'll be using is a Support Vector Classifier with radial basis kernel. So your first step is to create an SVC object with default parameters (i.e. `kernel='rbf'`, `C=1`) and `random_state=0`. Recall that the kernel width of the RBF kernel is controlled using the `gamma` parameter.

With this classifier, and the dataset in `X_subset`, `y_subset`, explore the effect of `gamma` on classifier accuracy by using the `validation_curve` function to find the training and test scores for 6 values of `gamma` from `0.0001` to `10` (i.e. `np.logspace(-4, 1, 6)`). Recall that you can specify

what scoring metric you want `validation_curve` to use by setting the “scoring” parameter. In this case, we want to use “accuracy” as the scoring metric.

For each level of `gamma`, `validation_curve` will fit 3 models on different subsets of the data, returning two 6x3 (6 levels of `gamma` x 3 fits per level) arrays of the scores for the training and test sets.

Find the mean score across the three models for each level of `gamma` for both arrays, creating two arrays of length 6, and return a tuple with the two arrays.

e.g.

if one of your array of scores is

```
array([[ 0.5,  0.4,  0.6],
       [ 0.7,  0.8,  0.7],
       [ 0.9,  0.8,  0.8],
       [ 0.8,  0.7,  0.8],
       [ 0.7,  0.6,  0.6],
       [ 0.4,  0.6,  0.5]])
```

it should then become

```
array([ 0.5,  0.73333333,  0.83333333,  0.76666667,  0.63333333,  0.5])
```

This function should return one tuple of numpy arrays (`training_scores`, `test_scores`) where each array in the tuple has shape (6,).

```
In [121]: def answer_six():
            from sklearn.svm import SVC
            from sklearn.model_selection import validation_curve
            # Your code here
            param_range = np.logspace(-4,1,6)
            clf = SVC(kernel='rbf', C=1, random_state=0)
            train_scores, test_scores = validation_curve(SVC(), X_subset, y_subset,
                                                         param_name='gamma',
                                                         param_range=param_range, cv=3)

            train_scores_mean = np.mean(train_scores, axis=1)
            test_scores_mean = np.mean(test_scores, axis=1)
            return (train_scores_mean, test_scores_mean)
            #answer_six()

Out[121]: (array([ 0.56647847,  0.93155951,  0.99039881,  1.          ,  1.          ,
                  0.56768547,  0.92959558,  0.98965952,  1.          ,  0.99507994,
                  0.52240279]))
```

1.2.3 Question 7

Based on the scores from question 6, what `gamma` value corresponds to a model that is underfitting (and has the worst test set accuracy)? What `gamma` value corresponds to a model that is overfitting (and has the worst test set accuracy)? What choice of `gamma` would be the best choice

for a model with good generalization performance on this dataset (high accuracy on both training and test set)?

Hint: Try plotting the scores from question 6 to visualize the relationship between gamma and accuracy. Remember to comment out the import matplotlib line before submission.

This function should return one tuple with the degree values in this order: (Underfitting, Overfitting, Good_Generalization) Please note there is only one correct solution.

```
In [124]: def answer_seven():
```

```
    training_scores, test_scores = answer_six()
    param_range = np.logspace(-4, 1, 6)
```

```
    train_scores_sorted = np.sort(training_scores)
    test_scores_sorted = np.sort(test_scores)
```

```
    Underfitting = 0
```

```
    Overfitting = 0
```

```
    Good_Generalization = 0
```

```
    min_train_scores = np.min(training_scores)
```

```
    max_train_scores = np.max(training_scores)
```

```
    min_test_scores = np.min(test_scores)
```

```
    max_test_scores = np.max(test_scores)
```

```
    for gamma, data in zip(param_range, zip(training_scores, test_scores)):
```

```
        if data[0] <= min_train_scores and data[1] <= min_test_scores:
```

```
            Underfitting = gamma
```

```
        if data[0] > max_train_scores and data[1] <= min_test_scores:
```

```
            Overfitting = gamma
```

```
        if data[0] == max_train_scores and data[1] == max_test_scores:
```

```
            Good_Generalization = gamma
```

```
    return (Underfitting, Overfitting, Good_Generalization)
```

```
    #answer_seven()
```

```
Out[124]: (0.0001, 10.0, 0.10000000000000001)
```

```
In [ ]:
```