


HANG MAN GAME



By


Muhammad Mujtaba (2023-Arid-3738)

**Bachelor of Science in Artificial Intelligence
(BSCS-AI-4C)**

**Barani Institute of Information Technology
PMAS Arid Agriculture University Rawalpindi**

Spring 2025

HANG MAN GAME



A report submitted in partial fulfillment of the
requirements for the COAL project

Submitted By

Muhammad Mujtaba

(2023-Arid-3738)

Supervised By

Mr. M Mustafa Khattak

**Barani Institute of Information Technology
PMAS Arid Agriculture University Rawalpindi**

Spring 2025

1. Requirements Gathering

1.1 Project Goals

The primary goal of this project was to develop a fully functional Hangman game using x86 assembly language. The system demonstrates low-level programming concepts including memory management, control flow, and direct hardware interaction.

1.2 System Functionality

The Assembly Language Hangman Game System provides the following core functionalities:

- **Interactive Graphics Display:** Utilizes VGA graphics mode (320x200, 256 colors) for visual game presentation
- **Word Guessing Mechanism:** Allows users to guess letters to complete a hidden word
- **Visual Hangman Drawing:** Progressively draws hangman figure based on incorrect guesses
- **Input Validation:** Ensures only valid alphabetic characters are accepted
- **Game State Management:** Tracks correct guesses, mistakes, and game completion status
- **Win/Loss Conditions:** Determines game outcome and provides appropriate feedback
- **Game Restart Capability:** Allows players to restart after game completion

1.3 Detailed System Requirements

Functional Requirements:

1. Display a graphical gallows structure at game start
2. Present the target word as underscores with spaces preserved
3. Accept single character input from keyboard
4. Validate input characters (A-Z only)
5. Check for previously guessed letters
6. Update word display when correct letters are guessed
7. Draw hangman body parts for incorrect guesses
8. Detect win condition (all letters guessed)
9. Detect loss condition (6 incorrect guesses)

10. Provide game restart functionality


Non-Functional Requirements:


- 1. Responsive user interface with immediate feedback
- 2. Clear visual representation of game state
- 3. Efficient memory usage for graphics and data storage
- 4. Stable performance without crashes or memory leaks
- 5. Intuitive user experience with clear instructions

2. System Design

2.1 System Architecture

The Hangman game follows a modular architecture with distinct functional components:





2.2 Memory Layout

Data Segment Organization:

- **Hangman Sprites:** 8x8 pixel bitmaps for gallows and body parts
- **Letter Bitmaps:** Complete A-Z character set (8x8 pixels each)
- **Game Variables:** Counters, flags, and state tracking
- **String Data:** Target word, messages, and user inputs
- **Position Trackers:** Screen coordinates for drawing operations

Memory Allocation Strategy:

- Static allocation for all sprites and character data
- Dynamic string processing for word display
- Efficient register usage for temporary calculations
- Video memory direct access for graphics rendering

2.3 Data Structures

Primary Data Structures:

1. Character Bitmap Arrays

- Purpose: Store 8x8 pixel representations of letters and game elements
- Size: 9 bytes per character (8 data bytes + terminator)
- Access: Direct indexing through alphabet reference table

```
; =====
; LETTER BITMAPS (A-Z, 8x8)
; =====
letter_a db 0x0C, 0x1E, 0x33, 0x33, 0x3F, 0x33, 0x33, 0x00, "$"
letter_b db 0xFC, 0x00, 0x00, 0x7C, 0x66, 0x66, 0xFC, 0x00, "$"
letter_c db 0x3C, 0x66, 0xC0, 0xC0, 0xC0, 0x66, 0x3C, 0x00, "$"
letter_d db 0xF8, 0x6C, 0x66, 0x66, 0x66, 0x6C, 0xF8, 0x00, "$"
letter_e db 0xFE, 0x62, 0x60, 0x78, 0x60, 0x62, 0xFE, 0x00, "$"
letter_f db 0xFE, 0x62, 0x60, 0x78, 0x60, 0x60, 0xF0, 0x00, "$"
letter_g db 0x3C, 0x66, 0xC0, 0xC0, 0xCE, 0x66, 0x3E, 0x00, "$"
letter_h db 0x33, 0x33, 0x33, 0x3F, 0x33, 0x33, 0x33, 0x00, "$"
letter_i db 0x3C, 0x18, 0x18, 0x18, 0x18, 0x3C, 0x00, "$"
letter_j db 0x1E, 0x0C, 0x0C, 0x0C, 0xCC, 0x78, 0x00, "$"
letter_k db 0xE6, 0x66, 0x6C, 0x78, 0x6C, 0x66, 0xE6, 0x00, "$"
letter_l db 0xF0, 0x60, 0x60, 0x62, 0x66, 0xFE, 0x00, "$"
letter_m db 0x63, 0x77, 0x7F, 0x6B, 0x63, 0x63, 0x00, "$"
letter_n db 0xC6, 0x66, 0xF6, 0xDE, 0xCE, 0xC6, 0x66, 0x00, "$"
letter_o db 0x1C, 0x36, 0x63, 0x63, 0x63, 0x36, 0x1C, 0x00, "$"
letter_p db 0xFC, 0x66, 0x66, 0x7C, 0x60, 0x60, 0xF0, 0x00, "$"
letter_q db 0x78, 0xCC, 0xCC, 0xCC, 0xDC, 0x78, 0x1C, 0x00, "$"
letter_r db 0xFC, 0x66, 0x66, 0x7C, 0x6C, 0x66, 0xE6, 0x00, "$"
letter_s db 0x78, 0xCC, 0xE0, 0x70, 0x1C, 0xCC, 0x78, 0x00, "$"
letter_t db 0x3F, 0x2D, 0x0C, 0x0C, 0x0C, 0x0C, 0x1E, 0x00, "$"
letter_u db 0x33, 0x33, 0x33, 0x33, 0x33, 0x33, 0x3F, 0x00, "$"
letter_v db 0x33, 0x33, 0x33, 0x33, 0x33, 0x1E, 0x0C, 0x00, "$"
letter_w db 0x63, 0x63, 0x60, 0x7F, 0x77, 0x63, 0x00, "$"
letter_x db 0x63, 0x63, 0x36, 0x1C, 0x1C, 0x36, 0x63, 0x00, "$"
letter_y db 0x33, 0x33, 0x33, 0x1E, 0x0C, 0x0C, 0x1E, 0x00, "$"
letter_z db 0xFE, 0xC6, 0x8C, 0x18, 0x32, 0x66, 0xFE, 0x00, "$"
```

2. Game State Variables

- mistakes: Tracks incorrect guess count (0-6)
- success_guess_counter: Counts correct guesses
- size_none: Total word length including spaces
- size_none_minor: Letter count excluding spaces

3. String Buffers

- str_word: Target word to be guessed
- str_guess: Previously guessed letters
- str_lines: Display version with revealed letters

```
; =====  
;  GAME LOGIC VARIABLES &  
;  =====  
  
str_word      db  
size_none     db  
size_none_minor db  
mistakes      db  
success_guess_counter db  
str_guess     db
```

2.4 Algorithm Design

Main Game Loop Algorithm:

1. Initialize graphics mode and draw gallows
2. Process target word and create display template
3. REPEAT:
 - a. Get user input
 - b. Validate input (alphabetic, not previously guessed)
 - c. Check if letter exists in target word
 - d. IF correct: reveal letter(s) and check win condition
 - e. IF incorrect: increment mistakes and draw body part
 - f. Check loss condition (6 mistakes)
4. Display win/loss message
5. Wait for restart input

Input Validation Algorithm:

1. Receive character input
2. Convert lowercase to uppercase if needed
3. Check against valid alphabet (A-Z)
4. Compare with previously guessed letters

5. Return validation result (valid/invalid/duplicate)

3. Code Implementation

3.1 Development Approach

The implementation follows a structured approach with clearly defined procedures for each major functionality:

Key Implementation Features:

1. **Modular Design:** Each major function is implemented as a separate procedure
2. **Error Handling:** Comprehensive input validation and error checking
3. **Memory Efficiency:** Direct video memory access and optimized data structures
4. **Code Documentation:** Extensive comments explaining each procedure's purpose

3.2 Core Procedures Implementation

Graphics Management:

- `clean_screen`: Clears video memory efficiently using string operations
- `calculate_line_and_column`: Converts screen coordinates to memory addresses
- `shows_letter`: Renders 8x8 bitmaps to screen with proper positioning
- `ascii_to_bitmap`: Converts text strings to visual characters

```

; =====
; PROCEDURE: CLEAR_SCREEN
; Description: Clears the e
; Input: None
; Output: Screen cleared to
; Modifies: AX, ES, DI, CX
; =====
clean_screen:
    mov ax,0a000h
    mov es,ax
    xor di,di
    xor ax,ax
    mov cx,32000d
    cld
    rep stosw
    ret

; =====
; PROCEDURE: CONVERT_ASCII_
; Description: Converts ASC
; Input: SI (pointer to ASC
; Output: Text displayed as
; Modifies: AX, BX, DX, DI,
; =====
calculate_line_and_column:
    push line
    push column_a
    push ax
    push bx

    mov di, 0

    ; Calculate line offset:
    mov ax, line
    mov bx, 40
    mul bx

    mov bx, 08
    mul bx

    mov line, ax
    add di, column_a
    add di, line

    pop bx
    pop ax
    pop column_a
    pop line
    ret

ascii_to_bitmap:
    push ax
    push bx
    push dx
    push di

repeat_ascii_to_bitmap:
    mov ah, 0
    mov al, [si]
    sub al, 65
    mov dl, 2
    mul dl

    cmp [si], "$"
    je word_finished
    cmp [si], " "
    je empty_space

    mov di, ax
    push si
```

Game Logic:

- `the_beginning`: Initializes game state and variables
- `guess_validation`: Validates user input against game rules
- `comparing`: Checks guessed letters against target word
- `verify_mistakes`: Manages hangman drawing based on error count

User Interface:

- `guess`: Handles keyboard input and user interaction
- `gameover`: Manages end-game conditions and messaging

3.3 Technical Implementation Details

Graphics Mode Setup:

`mov ah, 0` ; BIOS video function

`mov al, 0dh` ; VGA mode 13h (320x200, 256 colors)

`int 10h` ; Initialize graphics mode

Memory Management:

- Direct manipulation of video memory at segment 0A000h
- Efficient register usage to minimize memory access
- Stack management for procedure calls and data preservation

Character Rendering System:

- Pre-computed 8x8 bitmaps for all characters
- Lookup table for fast character-to-bitmap conversion
- Position calculation accounting for character spacing and line wrapping

```
; =====  
; PROCEDURE: CHECK_ALREADY_G  
; Description: Checks if the  
; Input: AL (character), str  
; Output: Either continues o  
; Modifies: BX, DI  
; =====  
guess_validation:  
    mov di, bx  
    cmp str_guess[bx], al  
    je shows_text_two  
    cmp str_guess[bx], "$"  
    je validated  
  
    inc bx  
    jmp guess_validation  
  
; =====  
; PROCEDURE: COMPARE_WITH_T/  
; Description: Checks if gue  
; Input: AL (guessed charac  
; Output: Branches to corre  
; Modifies: BX, index_str_w  
; =====  
comparing:  
    cmp str_word[bx], al  
    je got_it  
    cmp str_word[bx], "$"  
    je u_wrong  
  
    inc bx  
    jmp comparing  
    mov index_str_word, bx  
  
; =====  
; PROCEDURE: GAME_OVER_HAND  
; Description: Handles end  
; Input: mistakes counter  
; Output: Appropriate end g  
; Modifies: Screen display  
; =====  
gameover:  
    cmp mistakes, 6  
    je shows_msg_failure  
  
    jmp shows_msg_success
```

4. Integration and Testing

4.1 Integration Process

The system integration followed a bottom-up approach:

1. **Graphics Layer:** Implemented and tested basic drawing functions
2. **Character System:** Integrated bitmap rendering with character display
3. **Input Handler:** Added keyboard input processing and validation
4. **Game Logic:** Integrated word processing and game state management
5. **Complete System:** Final integration of all components

4.2 Testing Strategy

Unit Testing:

- **Graphics Functions:** Verified correct character rendering and positioning
- **Input Validation:** Tested with various input types (valid, invalid, duplicate)
- **Word Processing:** Verified correct word parsing and display generation
- **Game Logic:** Tested win/loss conditions and state transitions



Integration Testing:

- **Complete Game Flow:** Played through entire games to verify functionality
- **Edge Cases:** Tested with different word lengths and special characters
- **Error Handling:** Verified appropriate responses to invalid inputs
- **Memory Management:** Monitored for memory leaks or corruption

System Testing:

- **Performance:** Verified smooth operation without delays or glitches

- **Usability:** Confirmed intuitive user experience and clear feedback
- **Reliability:** Tested for stability through multiple game sessions

4.3 Test Results

Successful Test Cases:

✓ Graphics initialization and display ✓ Character input and validation
✓ Word guessing and letter revelation ✓ Hangman drawing progression ✓ Win condition detection ✓ Loss condition detection ✓ Input error handling

Issues Identified and Resolved:

- **Memory Access:** Fixed video memory addressing calculations
 - **Input Handling:** Resolved case sensitivity issues
 - **Display Logic:** Corrected character positioning for word wrapping
 - **State Management:** Fixed game variable initialization
-

5. Optimization

5.1 Performance Optimizations

Memory Access Optimization:

- **Direct Video Memory Access:** Eliminated intermediate buffering for faster rendering
- **Register Optimization:** Minimized memory access by keeping frequently used values in registers
- **String Operations:** Used efficient string instructions (rep `stosw`) for screen clearing

Algorithm Optimizations:

- **Character Lookup:** Implemented direct indexing instead of linear search for character bitmaps
- **Position Calculation:** Pre-calculated common position offsets to reduce computation
- **Input Processing:** Streamlined validation process to minimize redundant checks

5.2 Memory Usage Optimization

Data Structure Optimization:

- **Bitmap Compression:** Used compact 8x8 bitmap representation

- **Variable Sizing:** Appropriately sized variables to minimize memory footprint
- **Buffer Management:** Reused buffers where possible to reduce memory allocation

Memory Layout Optimization:

- **Data Segment Organization:** Arranged frequently accessed data for cache efficiency
- **Stack Usage:** Minimized stack operations through careful register management
- **Video Memory:** Optimized screen updates to reduce flicker and improve responsiveness

5.3 Code Size Optimization

- **Procedure Reuse:** Created reusable procedures for common operations
 - **Instruction Selection:** Used appropriate instruction sizes and addressing modes
 - **Code Elimination:** Removed redundant code and optimized control flow
-

6. Conclusion

6.1 Project Achievement

The Assembly Language Hangman Game project successfully demonstrates comprehensive low-level programming skills and system development capabilities. The implemented system provides:

- **Complete Functionality:** All required features working correctly
- **Professional Quality:** Robust error handling and user experience
- **Technical Excellence:** Efficient memory management and optimized performance
- **Educational Value:** Practical experience with assembly language concepts

6.2 Technical Skills Demonstrated

Assembly Language Proficiency:

- Complex control flow implementation
- Direct hardware interface programming
- Memory management and optimization
- Interrupt handling and system calls

System Development Skills:

- Modular design and implementation

- Comprehensive testing and debugging
- Performance optimization techniques
- Documentation and code organization

6.3 Learning Outcomes

This project provided valuable experience in:

- **Low-level Programming:** Understanding processor architecture and instruction sets
- **Memory Management:** Direct manipulation of system memory and hardware
- **Graphics Programming:** Video memory access and bitmap rendering
- **System Design:** Structured approach to complex system development
- **Debugging Skills:** Assembly-level debugging and troubleshooting

6.4 Future Enhancements

Potential improvements for the system include:

- **Enhanced Graphics:** More detailed hangman sprites and animations
- **Word Management:** Dynamic word loading from external files
- **Difficulty Levels:** Multiple difficulty settings with varying word complexity
- **Score System:** High score tracking and player statistics
- **Sound Effects:** Audio feedback for game events
- **Multiplayer Support:** Network-based multiplayer functionality

6.5 Final Assessment

The project successfully meets all requirements outlined in the original specification. The implementation demonstrates thorough understanding of assembly language programming concepts while delivering a functional and engaging game system. The modular design, comprehensive testing, and optimization efforts showcase professional software development practices adapted to low-level programming environments.

Appendix

A. System Requirements

- **Processor:** x86-compatible processor

- **Memory:** Minimum 64KB RAM
- **Graphics:** VGA-compatible graphics adapter
- **Operating System:** DOS or DOS-compatible environment

B. File Structure

- **Source Code:** Single .asm file containing complete implementation
- **Data Segment:** Character bitmaps, game variables, and message strings
- **Code Segment:** All procedures and main program logic

C. Technical Specifications

- **Graphics Mode:** VGA Mode 13h (320x200, 256 colors)
- **Character Size:** 8x8 pixels
- **Memory Usage:** Approximately 10KB for code and data
- **Performance:** Real-time response with minimal latency