

**Question 1** Correct Mark 1.00 out of 1.00 [Flag question](#)

Given two numbers, write a C program to swap the given numbers.

For example:

Input	Result
10 20	20 10

Answer: (penalty regime: 0 %)

```
1 #include <stdio.h>
2 int main()
3 {
4     int a,b,temp;
5     scanf("%d",&a);
6     scanf("%d",&b);
7     temp = a;
8     a = b;
9     b = temp;
10    printf("Kd %d",a,b);
11    return 0;
12 }
```

	Input	Expected	Got	
✓	10 20	20 10	20 10	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

**Question 2** | Correct | Mark 1.00 out of 1.00 | [Flag question](#)

Write a C program to find the eligibility of admission for a professional course based on the following criteria:

Marks in Maths  $\geq 65$

Marks in Physics  $\geq 55$

Marks in Chemistry  $\geq 50$

Or

Total in all three subjects  $\geq 180$

**Sample Test Cases****Test Case 1****Input**

70 60 80

**Output**

The candidate is eligible

**Test Case 2****Input**

50 80 80

← → ↺ ↻

## Output

The candidate is eligible

## Test Case 3

## Input

50 60 40

## Output

The candidate is not eligible

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a, b, c, d;
5     scanf("%d %d %d", &a, &b, &c);
6     d=a+b+c;
7     if(a >= 65 && b >= 55 && c >= 50){
8         printf("The candidate is eligible \n");
9     }
10    else if(d==180){
11        printf("The candidate is eligible \n");
12    }
13    else{
14        printf("The candidate is not eligible \n");
15    }
16    return 0;
17 }
```

file:///C:/Users/.../.../...

```
1 #include<stdio.h>
2 int main()
3 {
4     int a, b, c, d;
5     scanf("%d %d %d", &a, &b, &c);
6     d=a+b+c;
7     if(a >= 65 && b >= 55 && c >= 50){
8         printf("The candidate is eligible \n");
9     }
10    else if(d>=180){
11        printf("The candidate is eligible \n");
12    }
13    else{
14        printf("The candidate is not eligible \n");
15    }
16    return 0;
17 }
```

Input	Expected	Got
✓ 70 60 80	The candidate is eligible	The candidate is eligible ✓
✓ 50 80 80	The candidate is eligible	The candidate is eligible ✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

**Question 3** Correct Mark 1.00 out of 1.00 Flag question

Malini goes to BestSave hyper market to buy grocery items. BestSave hyper market provides 10% discount on the bill amount B when ever the bill amou

The bill amount B is passed as the input to the program. The program must print the final amount A payable by Malini.

Input Format:

The first line denotes the value of B.

Output Format:

The first line contains the value of the final payable amount A.

Example input/Output 1:

Input:

1900

Output:

1900

Example input/Output 2:

Input:

3000

Output:

3000

Output:

2700

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main()
3 {
4     int a, b, c;
5     scanf("%d",&a);
6     b = a/10;
7     c=a-b;
8     if(a>2000 ){
9         printf("%d",c);
10    }
11    else{
12        printf("%d",a);
13    }
14    return 0;
15 }
```

	Input	Expected	Got	
✓	1900	1900	1900	✓
✓	3000	2700	2700	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.

**Question 4** Correct Mark 1.00 out of 1.00 Flag question

Baba is very kind to beggars and every day Baba donates half of the amount he has when ever a beggar requests him, The money M left in Baba's hand is received the alms are passed as the input, The program must print the money Baba had in the beginning of the day.

**Input Format:**

The first line denotes the value of M.  
The second line denotes the value of B.

**Output Format:**

The first line denotes the value of money with Baba in the beginning of the day.

**Example Input/Output:**

Input:

100  
2

Output:

400

Explanation:

Baba donated to two beggars. So when he encountered second beggar he had  $100 \times 2 = \text{Rs.}200$  and when he encountered 1st he had  $200 \times 2 = \text{Rs.}400$ .

**Answer:** (penalty regime: 0 %)

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main(){
3     int a,b;
4     scanf("%d%d",&a,&b);
5
6     for(int i=0;i<b;i++){
7         a=a*2;
8     }
9     printf("%d\n",a);
10    return 0;
11 }
```

	Input	Expected	Got	
✓	100	400	400	✓
	2			

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.



**Question 5** Correct Mark 1.00 out of 1.00 Flag question

The CEO of company ABC Inc wanted to encourage the employees coming on time to the office. So he announced that for every consecutive day an employee came on time consecutively starting from Monday is also passed as the input. The program must calculate and print the "Punctuality Incentive"

**Input Format:**

The first line denotes the value of I.  
The second line denotes the value of N.

**Output Format:**

The first line denotes the value of P.

**Example Input/Output:**

Input:

500  
3

Output:

2100

Explanation:

On Monday the employee receives Rs.500, on Tuesday Rs.700, on Wednesday Rs.900

On Monday the employee receives Rs.500, on Tuesday Rs.700, on Wednesday Rs.900

So total = Rs.2100

Answer: (penalty regime: 0 %)

```
1 #include<stdio.h>
2 int main(){
3     int x,n;
4     scanf("%d",&x,&n);
5     int total =0;
6     for(int i=0;i < n;i++){
7         total+=x*(i*200);
8     }
9     printf("%d\n",total);
10    return 0;
11 }
```

	Input	Expected	Got	
✓	500 3	2100	2100	✓
✓	100 3	900	900	✓

Passed all tests! ✓

Correct

Marks for this submission: 1.00/1.00.