

API Test Cases – Event Update & Delete

UpdateEventTests.java

1. successfulUpdateEventTest

Positive Test - 201

Precondition:

- A valid event exists in the database and its {id} is known. A valid Authorization Token is generated.

Steps:

- Set HTTP Method to PUT.
- Set Endpoint URL to /events/{id} (replace {id} with the actual event ID).
- Add Header: Authorization: Bearer <valid_token>.
- Add Header: Content-Type: application/json.
- Add JSON Body with updated, completely valid values for all required fields.
- Send Request.

Expected Result:

- Status Code must be 201 Created (or 200 OK, depending on specific API documentation).
- Response Body must contain the updated event details, perfectly matching the submitted JSON payload.

2. updateEventMissingTokenTest

Negative Test - 401

Precondition:

- A valid event exists in the database and its {id} is known.

Steps:

- Set HTTP Method to PUT.
- Set Endpoint URL to /events/{id}.
- Omit the Authorization header.
- Add Header: Content-Type: application/json.
- Add JSON Body with updated, valid values.
- Send Request.

Expected Result:

- Status Code must be 401 Unauthorized.
- Response Body must contain an authorization error message. The event must remain completely unchanged in the database.

3. updateEventEmptyTitleTest

Negative Test - 422

Precondition:

- A valid event exists. A valid Authorization Token is generated.

Steps:

- Set HTTP Method to PUT.
- Set Endpoint URL to /events/{id}.
- Add Header: Authorization: Bearer <valid_token>.
- Add JSON Body containing an empty title string, while keeping all other fields valid.
- Send Request.

Expected Result:

- Status Code must be 422 Unprocessable Entity.
- Response Body must contain a specific validation error indicating that the title field cannot be empty.

4. updateEventInvalidImageTest

Negative Test - 422

Precondition:

- A valid event exists. A valid Authorization Token is generated.

Steps:

- Set HTTP Method to PUT.
- Set Endpoint URL to /events/{id}.
- Add Header: Authorization: Bearer <valid_token>.
- Add JSON Body containing an invalid image URL format (e.g., missing "http://"), while keeping all other fields valid.
- Send Request.

Expected Result:

- Status Code must be 422 Unprocessable Entity.
- Response Body must contain a validation error for the incorrect image format.

5. updateEventEmptyLocationTest

Negative Test - 422

Precondition:

- A valid event exists. A valid Authorization Token is generated.

Steps:

- Set HTTP Method to PUT.
- Set Endpoint URL to /events/{id}.
- Add Header: Authorization: Bearer <valid_token>.
- Add JSON Body containing an empty location string, while keeping all other fields valid.
- Send Request.

Expected Result:

- Status Code must be 422 Unprocessable Entity.
- Response Body must contain a validation error indicating that the location field cannot be empty.

DeleteEventTests.java

1. successfulDeleteEventTest

Positive Test - 200

Precondition:

- A valid event exists in the database and its {id} is known. A valid Authorization Token is generated.

Steps:

- Set HTTP Method to DELETE.
- Set Endpoint URL to /events/{id}.
- Add Header: Authorization: Bearer <valid_token>.
- Send Request.

Expected Result:

- Status Code must be 200 OK (or 204 No Content, depending on API specs).
- Database Verification: A subsequent GET request to /events/{id} must return a 404 Not Found status code, confirming the event no longer exists.

2. deleteEventMissingTokenTest

Negative Test - 401

Precondition:

- A valid event exists in the database and its {id} is known.

Steps:

- Set HTTP Method to DELETE.
- Set Endpoint URL to /events/{id}.
- Omit the Authorization header.
- Send Request.

Expected Result:

- Status Code must be 401 Unauthorized.
- Response Body must contain an authorization error message.
- Database Verification: The event must not be deleted (a subsequent GET request to /events/{id} must successfully return 200 OK).