

API Test Cases – Event Creation (POST)

CreateEventTests.java

1. successfulCreateEventTest

Positive Test - 201

Precondition:

- A valid Authorization Token is generated. No prior event data is required.

Steps:

- Set HTTP Method to POST.
- Set Endpoint URL to /events.
- Add Header: Authorization: Bearer <valid_token>.
- Add Header: Content-Type: application/json.
- Add JSON Body with completely valid values for all required fields (title, location, image, etc.).
- Send Request.

Expected Result:

- Status Code must be 201 Created.
- Response Body must contain the newly created event, including a generated id, and all fields must match the submitted JSON payload.
- Database Verification: A subsequent GET request to /events/{id} must return the same event with 200 OK.

2. createEventMissingTokenTest

Negative Test - 401

Precondition:

- No Authorization Token is provided.

Steps:

- Set HTTP Method to POST.
- Set Endpoint URL to /events.
- Omit the Authorization header.
- Add Header: Content-Type: application/json.
- Add JSON Body with valid values for all required fields.
- Send Request.

Expected Result:

- Status Code must be 401 Unauthorized.
- Response Body must contain an authorization error message. No event must be created in the database.

3. createEventEmptyTitleTest

Negative Test - 422

Precondition:

- A valid Authorization Token is generated.

Steps:

- Set HTTP Method to POST.
- Set Endpoint URL to /events.
- Add Header: Authorization: Bearer <valid_token>.
- Add JSON Body containing an empty title string, while keeping all other fields valid.
- Send Request.

Expected Result:

- Status Code must be 422 Unprocessable Entity.
- Response Body must contain a specific validation error indicating that the title field cannot be empty.
- Database Verification: No event must be created in the database.

4. createEventInvalidImageTest

Negative Test - 422

Precondition:

- A valid Authorization Token is generated.

Steps:

- Set HTTP Method to POST.
- Set Endpoint URL to /events.
- Add Header: Authorization: Bearer <valid_token>.
- Add JSON Body containing an invalid image URL format (e.g., missing "http://"), while keeping all other fields valid.
- Send Request.

Expected Result:

- Status Code must be 422 Unprocessable Entity.
- Response Body must contain a validation error for the incorrect image format.
- Database Verification: No event must be created in the database.

5. createEventEmptyLocationTest

Negative Test - 422

Precondition:

- A valid Authorization Token is generated.

Steps:

- Set HTTP Method to POST.
- Set Endpoint URL to /events.
- Add Header: Authorization: Bearer <valid_token>.
- Add JSON Body containing an empty location string, while keeping all other fields valid.
- Send Request.

Expected Result:

- Status Code must be 422 Unprocessable Entity.
- Response Body must contain a validation error indicating that the location field cannot be empty.

- Database Verification: No event must be created in the database.