Decide, Don’t Generate

Decide, Don’t Generate

Jev, System One Models, and the Decision Layer of Agentic AI

Sridhar Mukkandi

First edition

Decide, Don’t Generate: Jev, System One Models, and the Decision Layer of Agentic AI

Copyright © 2026 Sridhar Mukkandi. All rights reserved.

No part of this book may be reproduced, stored or transmitted in any form without written permission from the author, except for brief quotations in reviews and articles.

Independently published. First edition, 2026.

Jev is a product of TypeSafe AI. This book is independent: the author is not affiliated with TypeSafe AI, and the book is not endorsed or sponsored by it. All trademarks belong to their respective owners.

About the numbers in this book. The examples in this book are assumed, to explain the ideas clearly. Kestrel Logistics, Harbor Pharma and everyone in them are imagined, and the numbers about them, including every number shown for Jev, are illustrations, not measurements of real companies or of the real product. Charts made this way are marked “synthetic”. Claims made by TypeSafe AI are labelled “vendor-reported” and cited.

The information in this book is provided without warranty. The author assumes no responsibility for errors or omissions, or for damages resulting from its use. Nothing in this book is legal, security-compliance or medical advice.

Cover design and typesetting by the author. Text set in Source Serif 4, Inter and JetBrains Mono, all under the SIL Open Font License.

Contact: sridhar.authorhub@gmail.com

Table of contents

Preface vii

How to read this book ix

Prologue: two nights x

1 What “learning” means 1

2 Probability, and how a machine learns it 9

3 Calibration: when 0.8 really means 80% 16

4 From probabilities to actions 23

5 How modern AI models work 29

6 RAG, agents, and where they break 36

7 Fast and slow: System One models and Jev 43

8 Asking the right question: choice, score, noul 50

9 Testing a model’s calibration yourself 56

10 The bake-off: six ways to make a decision 62

11 Act, review, or escalate 69

12 Decision patterns, and a hybrid agent 77

13 One team, start to finish, and beyond 84

14 From model to service 92

15 What changes now 100

Appendices 108

Glossary 108

Cheat sheets 111

Answers to the exercises 114

Bibliography 117

Index 120

About the Author 122

Preface

This is a book about making decisions with AI.

Every day, software makes millions of small decisions: whether a message is a scam, which team should handle a complaint, whether a payment is safe, or whether an AI agent should take an action. More and more of these decisions are now given to large language models like ChatGPT. LLMs are excellent at reading and writing, but a decision is not a paragraph of text. It is a choice between a few options, made without being fully sure, and every wrong choice has a cost.

To make such decisions well, you need three things:

- a **number for how likely each answer is, which you can trust**: when it says 80%, it should be right about 80 times out of 100;
- a **line for when to act**, based on what each kind of mistake costs, not on habit;
- a clear rule for **when to hand the case to a person**.

Most people building with AI today do not have all three. This book explains each of them from the beginning, in simple language, without any code.

In 2026, a company called TypeSafe AI released Jev, which it calls the first **System One model**: a model that never writes text, and only answers clear questions with probabilities, in one fast step (TypeSafe AI 2026). This book shows how to judge such a model for yourself. But the main idea is bigger than any one product: in an AI system, the small decisions should be handled by their own fast, checkable part, separate from the part that reads and writes text. Building that part well needs its own skills, and this book teaches them.

How to trust the numbers in this book

The examples are assumed. The book follows one imagined company, Kestrel Logistics, and its security team. All numbers about this company are from an assumed example, chosen to explain the ideas clearly. Charts made this way are marked **synthetic**.

Jev's numbers are illustrations. The numbers shown for Jev are examples to explain how such a model can be tested, not measurements of the real product.

Company claims are labelled. When the book reports what TypeSafe says about Jev, such as its speed or price, it is marked *vendor-reported*, and the source is given.

Every claim goes into one of three groups: what can be checked, what the company says, and what nobody outside the company knows yet. Chapter 7 explains this habit. It is a good habit for anything you read about new AI models, including this book.

How to read this book

If you are new to machine learning, read the book in order. Chapters 1 to 4 are the foundation: what a probability means, how to check it, and how to turn it into an action. Chapters 5 and 6 give a short, simple tour of neural networks, LLMs and AI agents.

If you already work with LLMs, still read Chapters 3 and 4, because everything after them depends on these two chapters. Then continue from Chapter 7.

If you lead a team or a product, read Chapters 1 to 4, then Chapters 7, 10, 11, 13 and 15. After that, you will be able to ask your team the four questions that matter most: What does a mistake cost? Where is the threshold? Can we trust the probabilities? Who checks the warnings?

The boxes

A **Key idea** box, with a thick bar on its left, holds one lesson worth remembering: a bold headline you can repeat to a colleague, and one sentence that explains why it is true. At the end of each chapter, a **Keep these** box lists all the key ideas of that chapter.

A **Where this breaks** box shows the limits of what the chapter just explained. Please read these boxes carefully; they tell you when a method can be trusted and when it cannot.

A **Set the threshold** box gives you a small decision to make, with real costs. The answer is given in brackets.

A **Going deeper** box has optional maths. You can skip it; nothing later depends on it.

Each chapter ends with one exercise. Try it before you turn the page; the answers are at the back of the book.

Prologue: two nights

Let us imagine a logistics company called Kestrel Logistics. Like every large company, it has computers that watch for trouble. Whenever something looks suspicious, such as a login from a strange country, an email with an odd link, or a laptop connecting to an unknown server, the computer raises a warning. This warning is called an **alert**. Each alert must be checked by a person, who decides whether it is a real attack or a false alarm.

On this night, only one security engineer is on duty. Checking one alert carefully takes about twelve minutes, so the engineer can check about five alerts in an hour.




Figure 1. One night, from midnight to 7 a.m. Each line is one alert; real attacks are the taller red lines, marked on top. The engineer checks alerts in the order they arrive, so only the alerts on the left get checked. The rest wait until morning.

Between midnight and 7 a.m., 218 alerts arrive, and 25 of them are real attacks (Figure 1). The engineer checks the alerts in the order in which they arrive, and by morning has finished 34 of them. Only 3 of those were real attacks. All the other attacks were still waiting in the queue, unchecked.

The engineer did nothing wrong: every alert that was checked was judged correctly. The real problem was the order of the work. Alerts were checked because they arrived first, not because they were the most dangerous.

Now let us imagine the same night again, with one change. A computer model reads each alert as soon as it arrives and gives it a number: the chance that it is a real attack. This number can be trusted. Among all the alerts it gives a 10% chance, about one in ten really turns out to be an attack.

With such numbers, the work can be divided sensibly. Alerts that are almost surely harmless are closed automatically, and a few of them are

picked at random so that a person can later check that the model is not making mistakes. Alerts that are very likely to be attacks wake up a senior person immediately. All the remaining alerts go to the engineer on duty, with the most dangerous ones at the top of the list. The engineer still makes the important decisions, but now spends the night on the alerts that matter most.

This book explains how to build that second night. It does not need much new technology, but it needs clear thinking about three questions. What does a probability really mean, and how can we check that it is correct? What does each kind of mistake cost, and where should we draw the line between “act” and “ignore”? And when should a machine decide by itself, and when should it hand the case to a person? The same three questions come up when a bank checks payments for fraud, when a hospital decides which patient to see first, and when an AI agent chooses its next step. We use a security team as the example only because its mistakes are easy to count.

Next: before a machine can decide anything, it has to learn. What does that actually mean?

CHAPTER 1

What “learning” means

Anyone who starts learning AI today hears many new words at once: machine learning, deep learning, LLM, RAG, agents. It feels like seven different subjects. But all these words belong to one story. Each new idea came because the old idea had a problem it could not solve.

In this chapter we go through that story from the beginning, in simple steps. At the end, you will see where this book fits.

BY THE END OF THIS CHAPTER

- Understand the difference between a computer that follows rules and a computer that learns.
- Explain what a *model* is, in one sentence.
- See the full picture: AI, machine learning, deep learning, LLMs, RAG, agents and Jev.

Rules work, until they don’t

Many systems in our daily life follow simple rules. A water tank switch turns the motor off when the tank is full. Your bank blocks a UPI payment if it is above your daily limit. A college portal shows “absent” if attendance is below 75%. Nobody “trained” these systems. A programmer wrote the rule, and the computer follows it.

Rules are good. They are fast and cheap, and when something goes wrong you can read the rule and understand why. If a simple rule solves your problem, use the rule.

The problem starts when the situation keeps changing. Think about fake messages that try to steal passwords. This is called **phishing**. The IT team of a company writes a rule: *if an email has the word “password”, mark it as suspicious.* On Monday, the rule blocks the IT team’s own “reset your password” emails, so they add an exception. On Wednesday, the attacker writes “password” with a zero, so they add another rule. On Friday, the attacker stops using the word completely and just sends a link to a fake login page. The list of rules keeps growing, and it is always one step behind

the attacker. You may have seen the same thing with fake “KYC update” SMS messages: the wording changes every week.




Figure 1.1. Two ways to catch phishing. On the left, every new trick forces a new exception, and the list never catches up. On the right, we stop writing rules and show the computer labelled examples instead.

So we change the approach. Instead of writing the rules ourselves, we collect thousands of old emails where we already know the answer: this one was phishing, this one was normal. Then we ask the computer to find the pattern by itself (Figure 1.1).

● KEY IDEA

A computer can learn the rules by itself from examples.

We do not write every rule by hand. We show it thousands of old cases where we already know the answer, and it finds the pattern. When the cheaters change their tricks, we simply show it new examples.

What is a model?

After the computer studies the examples, we get something we can use on new cases. You give it a new email, and it gives back an answer. This thing is called a **model**.

You can imagine a model as a machine with many small knobs. During learning, the computer keeps turning the knobs until the machine gives the right answer for most of the examples. After that, we stop turning the

knobs and use the machine on new emails, where nobody knows the answer yet.

● KEY IDEA

A model is a learned rule.

It is like a formula whose numbers were not typed by a programmer but found from examples. You give it a new case, and it gives back an answer.

You already use many models. When your bank sends an SMS like *"Did you just make a payment of ₹40,000 in another city? Reply NO if not you,"* no person wrote a rule about you. A model learned your normal spending pattern, and this payment did not match it.

A model can learn the wrong thing

To make the ideas concrete, this book uses one example again and again. Let us imagine a logistics company called Kestrel Logistics. Like any company, its computers raise warnings when something looks suspicious, for example a login from a strange country. These warnings are called **alerts**. Suppose that in four weeks the security team receives 20,000 alerts, about 714 per day, and only 7.6% of them are real attacks; the rest are false alarms. Since this is an example, we can assume we know the correct answer for every alert, which lets us check every idea properly.

Each alert comes with a *threat score* between 0 and 1. The score comes from outside security services that keep lists of known dangerous websites and computers. A high score means the alert involves something already known to be dangerous. Let us try a simple rule: *if the score is above some number t, mark the alert as an attack.* A cut-off number like t is called a **threshold**.

Which value of t should we choose? We let the computer try every value from 0 to 1, count the mistakes for each value, and keep the value with the fewest mistakes. This is learning in its simplest form: try many settings on the examples, and keep the one that works best.

The computer chooses 0.90. With this threshold it makes 1,487 mistakes. But look at this: a rule that *never* marks anything as an attack makes 1,515 mistakes, almost the same number. Out of 1,515 real attacks, the "best" rule catches only 73 (Figure 1.2).

Why did this happen? There are about twelve harmless alerts for every real attack. So the easiest way to reduce the number of mistakes is to al-




Figure 1.2. Every possible threshold and the mistakes it makes. Low thresholds bury the team in false alarms; high ones miss attacks. The total is lowest at the far right, just below the dotted line for “flag nothing at all”.

most never raise an alarm. The computer did exactly what we asked. Our question was wrong.

● KEY IDEA

If you ask the wrong question, you get a useless answer.

We asked the computer only to “make as few mistakes as possible”. Since attacks are rare, it learned the easiest trick: never say “attack”. The computer did what we asked, not what we wanted.

In fact, our question had two problems. First, it counted every mistake as equal, although missing a real attack costs much more than one false alarm; Chapter 4 fixes this. Second, it forced the answer to be only *yes* or *no*, which throws away useful information, as we see next.

A better answer: how likely?

Let us ask a different question: *among alerts with a similar score, how many were real attacks?*

Figure 1.3 shows the answer. There is no clear line where alerts suddenly become dangerous. Even in the lowest-score group, 2% were attacks. That looks small, but the group has 7,270 alerts, so more than a hundred attacks are hiding there. And in the highest-score group, only 62% were attacks.




Figure 1.3. Group the alerts by threat score and count how many were real attacks. The share climbs steadily from 2% to 62%. Even at the top, plenty are harmless; even at the bottom, a few are attacks.

So for an alert with a score of 0.55, the honest answer is not "attack" or "safe". The honest answer is: *about one in five alerts like this is an attack.*

This kind of answer is much more useful. It tells the team how worried to be, which alerts to check first, and, once we know the cost of each mistake, where to draw the line.

● KEY IDEA

"How likely" is more useful than "yes" or "no".

An answer like "one in five alerts like this is an attack" tells you how worried to be and which case to check first. But it helps only if that "one in five" is true.

When a model's "how sure" is correct, we say the model is **calibrated**. You will see this word many times in this book, and Chapter 3 explains it fully.

The bigger story, and where this book fits

The threat score was one simple number. Real data is often much messier, and each new step in AI came to handle that:

- **Deep learning.** A photo has lakhs of pixels, and an email is a long piece of text. Nobody can write rules for these by hand. So researchers built models with many layers, which find their own clues in the raw data.

- **Large language models (LLMs).** Researchers then trained very large deep-learning models on a huge amount of text, with one simple task: guess the next word. To do this well, the models had to learn the language itself. ChatGPT is an LLM.
- **RAG.** An LLM knows a lot about the world, but nothing about your company. So before it answers, we search your company’s documents and give it the right pages to read.
- **Agents.** Finally, we let the model use tools, such as searching, sending an email or closing a ticket, and work step by step towards a goal.

Chapters 5 and 6 explain each of these in more detail.

When you watch an agent work, you notice something interesting. Most of its steps are not writing. They are small decisions with only a few possible answers: *Is this alert real? Which team should handle this ticket? Is this action safe?* Today, people usually send each such question to an LLM. The LLM writes a full paragraph, and then another program has to search that paragraph for the actual answer. It works, but it is like asking someone to write an essay when you only wanted a tick in a box: slow and costly for such a small job.




Figure 1.4. The same question, two ways. An LLM writes its answer piece by piece, and your code has to read the sentence. A decision model returns the answer as data, with a probability for every option, in one pass.

In 2026, a company called TypeSafe AI released a model named **Jev** for exactly these small decisions. Jev does not write any text. You give it the situation and a clear question, and it gives back the answer with a probability for each option (Figure 1.4). TypeSafe calls it a *System One* model. The name comes from the psychologist Daniel Kahneman, who called our fast, automatic thinking “System 1” (Kahneman 2011). In this book, the numbers shown for Jev are examples to explain the ideas, not measurements of the real product. They are marked *synthetic*.




Figure 1.5. The story so far. Each step exists because the one before it hit a problem it couldn't solve. System One models like Jev grow out of deep learning and fit into the "decide" step of an agent.

Figure 1.5 shows the whole story on one page. The next three chapters stay with the basics, because everything else in the book depends on one idea: a good answer should say how likely it is, and that "how likely" should be correct.

● KEEP THESE

- **A computer can learn the rules by itself from examples.** We do not write every rule by hand. We show it thousands of old cases where we already know the answer, and it finds the pattern. When the cheaters change their tricks, we simply show it new examples.
- **A model is a learned rule.** It is like a formula whose numbers were not typed by a programmer but found from examples. You give it a new case, and it gives back an answer.
- **If you ask the wrong question, you get a useless answer.** We asked the computer only to "make as few mistakes as possible". Since attacks are rare, it learned the easiest trick: never say "attack". The computer did what we asked, not what we wanted.
- **"How likely" is more useful than "yes" or "no".** An answer like "one in five alerts like this is an attack" tells you how worried to be and which case to check first. But it helps only if that "one in five" is true.

EXERCISES

1. Name one system you use that follows fixed rules, and one that has learned from examples. How did you know?

Next chapter: what does “70% chance” really mean? There is a common trap here that even doctors fall into.

CHAPTER 2

Probability, and how a machine learns it

Many people think probability is only about coins and dice, something from school maths that has nothing to do with building AI. This is a costly mistake. In this chapter we learn to read a probability correctly, see a common trap that even doctors fall into, and see how a machine learns probabilities from examples.

BY THE END OF THIS CHAPTER

- Understand what "70% chance" really means, in a way you can check.
- Avoid the base-rate trap, and update a probability when new evidence comes.
- See how a machine learns a probability, and two ways it can fool you.

What "70% chance" means

Suppose the weather app says there is a 70% chance of rain tomorrow, and it does not rain. Was the app wrong?

One day cannot tell us. We need to look at many days. Take all the days when the app said "70%". If it rained on about 70 out of every 100 such days, the app is doing its job. Tomorrow was simply one of the other 30 days.

● KEY IDEA

A probability is checked over many cases, not one.

"70% chance of rain" means that on 100 such days, it should rain on about 70. If it does not rain tomorrow, the forecast was not wrong.

This is useful because we can check it. When a model says "this alert is 70% likely to be an attack", it is making the same kind of promise as the weather app, and we can check it in the same way.

The trap that fools doctors

Try this question before reading further. Suppose a test catches 99% of real attacks, but also raises a false alarm on 5% of normal activity, and real attacks are rare: about 1 in every 1,000 events. If the test raises an alarm, what is the chance that it is a real attack?

Most people answer about 95%. The correct answer is about **2%**. In a famous study from 1978, doctors at a top American medical college were asked the same question about a medical test, and the most common answer was also 95% (Casscells et al. 1978).




Figure 2.1. The same puzzle, counted out. Of 100,000 events, 100 are attacks and the detector catches 99 of them. But 5% of the 99,900 normal events also set it off: 4,995 false alarms. When the alarm sounds, you're holding one of 5,094 alerts, and only 99 of them are real.

The easy way to see this is to count, as in Figure 2.1. Take 100,000 events (one lakh). Only 100 are attacks, and the test catches 99 of them. But 5% of the 99,900 normal events also raise an alarm, which is 4,995 false alarms. So out of 5,094 alarms, only 99 are real. That is about 2%.

The chance before we see any evidence, here 1 in 1,000, is called the **base rate**. Forgetting the base rate is one of the most common mistakes with probability. This is why a fraud model that is "95% accurate" can still send a bank lakhs of false alarms. Whenever a probability surprises you, convert it into counts like this (Gigerenzer and Hoffrage 1995).

KEY IDEA

When something is rare, most alarms are false.

If only 1 in 1,000 events is an attack, even a 99%-accurate alarm is right only about 2 times in 100. To see this, count it out with 1,00,000 cases instead of using percentages.

There is a related mistake: mixing up a question with its reverse. Most international cricketers are right-handed, but that does not mean most right-handed people are international cricketers. In the same way, "How often do attacks have a bad score?" and "How often is an alert with a bad score an attack?" are two different questions with very different answers. In our example, only 27% of attacks come with a bad threat score, but an alert with a bad score is an attack 46% of the time.

Updating with new evidence

How should a new clue change our belief? The easiest way uses **odds**, the way people talk about a cricket match: "odds of 1 to 4" means one win for every four losses. A probability of 20% is the same as odds of 20 to 80, or 1 to 4.

Next, we measure how strong each clue is: how many times more often it appears with attacks than with harmless alerts. This number is called the **likelihood ratio**. In our example, a bad threat score appears about 10.2 times more often with attacks than with harmless alerts, so it is a strong clue.

The rule is simple: *new odds* = *old odds* × *strength of the clue*. This is called **Bayes' rule**.

An ordinary alert starts at 8%. With a bad threat score, it goes up to 46%. If it also happened outside office hours, it becomes 58%. If the login was also from a new country, it becomes 72% (Figure 2.2). One caution: this assumes each clue gives new information. In real life, clues often overlap, so in practice we let a model learn how much each clue is worth.

Why accuracy can mislead

Suppose our rule is: *mark an alert as an attack if its threat score is 0.5 or more.* Three common measures:




Figure 2.2. Starting from the base rate and multiplying the odds by each clue's likelihood ratio. Three ordinary clues take an alert from "probably nothing" to "probably an attack".

- **Precision**: when the rule raises an alarm, how often is it a real attack? Here, 34%.
- **Recall**: out of all real attacks, how many does the rule catch? Here, 45%.
- **Accuracy**: out of all alerts, how many did the rule judge correctly? Here, 89%.




Figure 2.3. Every one of the 20,000 alerts, sorted by what the rule said and what really happened. Precision and recall each ignore one of the two columns, which makes them fair judges of rare events.

The accuracy of 89% sounds good. But a rule that *never* raises any alarm has an even higher accuracy, 92%, simply because most alerts are harmless. It is like a weather forecaster in Rajasthan who always says "no rain": right on most days, and useless on the days that matter. So for rare events, look at precision and recall instead.

How a machine learns a probability

Bayes' rule multiplies the odds by each clue. Mathematicians found an easier way: change the odds into a scale where each clue simply *adds* points instead of multiplying. (This scale is called the log-odds, but you do not need the name.) This gives a very simple model, much like a credit score: start with a base number, add some points for each clue, and then turn the total into a probability with an S-shaped curve. The points for each clue are called **weights**, and this model is called **logistic regression**. Banks and hospitals have used it for decades to score loans and patient risk.



Figure 2.4. The S-curve (the logistic, or sigmoid, function) turns total evidence into a probability. Every step to the right multiplies the odds by the same amount, which is why the curve flattens out: once you're very sure, more evidence changes the probability only a little.

To find good weights, we need a way to score a probability. If the model says 90% and the event happens, it should lose very few points. If it says 1% and the event happens, it should lose many points, because it was confident and wrong. This score is called **log loss**.

Log loss has an important property: over many cases, the only way to get the best score is to give honest probabilities (Figure 2.5). If a model exaggerates and says 99% when the truth is 80%, it gains a little on the cases that happen but loses heavily on the ones that do not. So a model trained with log loss is pushed towards honest probabilities.

Training means finding the weights with the lowest log loss. Imagine standing on a hill in thick fog. You cannot see the bottom, but you can feel which way the ground slopes. So you take a small step downhill, and repeat. This method is called **gradient descent**.




Figure 2.5. Log loss for a single alert. If it really was an attack (red, solid curve), the penalty is small when the model gave "attack" a high probability. It grows very fast as that probability gets close to zero. Harmless alerts (blue, dashed curve) work the same way from the other side.

● KEY IDEA

Every machine learning model learns the same way: guess, check, correct.

It makes a guess, sees how wrong it was, changes its numbers a little, and repeats this millions of times. A small model and ChatGPT both learn like this; only the size is different.

Two ways a model fools you

Overfitting means memorising instead of learning, like a student who memorises last year's question paper and then fails when the questions change. A very flexible model can remember every small detail of its training examples, including details that were just chance. It then looks excellent on those examples but performs badly on new cases. Figure 2.6 shows this with a decision tree, a model that sorts cases by asking a series of yes/no questions: the more questions it may ask, the more it memorises. The only way to catch this is to test the model on data it has never seen.

Leakage means a clue secretly contains the answer, like a student who has seen the answer key. For example, if we train with the analysts' notes, results look amazing, because notes like "confirmed phishing" are written *after* someone has already decided. When the model has to decide, that note does not exist yet. So for every clue, ask: *will I really have this information at the moment of the decision?*




Figure 2.6. A decision tree allowed only a few questions learns general patterns. Allowed dozens, it memorises individual training alerts: its loss on them approaches zero while its loss on new alerts climbs.

KEEP THESE

- **A probability is checked over many cases, not one.** "70% chance of rain" means that on 100 such days, it should rain on about 70. If it does not rain tomorrow, the forecast was not wrong.
- **When something is rare, most alarms are false.** If only 1 in 1,000 events is an attack, even a 99%-accurate alarm is right only about 2 times in 100. To see this, count it out with 1,00,000 cases instead of using percentages.
- **Every machine learning model learns the same way: guess, check, correct.** It makes a guess, sees how wrong it was, changes its numbers a little, and repeats this millions of times. A small model and ChatGPT both learn like this; only the size is different.

EXERCISES

1. A spam filter catches 98% of spam and wrongly flags 1% of normal emails. If only 1% of all emails are spam, what fraction of flagged emails are actually normal? Use counts, as in Figure 2.1.

Next chapter: if a model says 80%, does it really mean 80%? We learn how to check, and how to fix it.

CHAPTER 3

Calibration: when 0.8 really means 80%

If a model says 80%, does it really mean 80%? This sounds like a silly question, but it can cost a lot of money. Nothing inside a model forces its 80% to match reality. It matches only if the model was built carefully and then checked. Checking this is the most important habit in this book.

BY THE END OF THIS CHAPTER

- Understand what *calibrated* means, and why it is different from accurate.
- Check a model's numbers with one simple chart and one simple score.
- Fix a model whose probabilities are wrong, and check it group by group.

What weather forecasters do well

In the 1970s, researchers in the United States compared weather forecasts with what actually happened. When forecasters said "30% chance of rain", it rained on about 30% of those days. When they said "70%", it rained on about 70% (Murphy and Winkler 1977).

Most people are not like this. If you ask someone for a range they are "90% sure" about, the true answer falls inside that range much less than 90% of the time. People are usually too confident.

Good forecasters are not always right; nobody can be. They are good because their numbers mean what they say (Figure 3.1). This is called **calibration**.




Figure 3.1. Two forecasters. For each thing they said ("30%", "70%" and so on), we count how often it actually happened. The careful forecaster sits on the diagonal: their 70% happens about 70% of the time. The overconfident one says 90% about things that happen only about 70% of the time.

● KEY IDEA

A model's "80%" must really mean 80%.

Take all the cases where it said 80%: about 80 out of 100 should turn out true. This is called being calibrated. If its 80% really means 50%, every decision based on it goes wrong.

Ranking and calibration are two different things

A model's numbers can be good at two separate jobs, and it is important not to mix them up. Think of a teacher who ranks every student correctly, from first to last, but writes everyone's marks 30 points too high. The order is right; the marks are wrong.

Ranking: does the model give higher numbers to attacks than to harmless alerts? If we sort alerts by the model's number, do real attacks come to the top? This is measured by **AUC**. Pick one real attack and one harmless alert at random: AUC is the chance that the model gives the attack the higher number. An AUC of 1 is perfect; 0.5 is no better than tossing a coin.

Calibration: are the numbers themselves correct? When the model says 0.3, are about three out of ten such alerts real attacks?

In Figure 3.2, both models have the same AUC of 0.888. But model B says 40% for alerts that are attacks only a few times in a hundred. If you only want to know which alerts to check first, B is as good as A. But if you use




Figure 3.2. Two models, identical at ranking (same AUC) but not at calibration. Model A is the logistic regression from Chapter 2. Model B is the same model with its probabilities distorted: it still sorts the alerts in the same order, but its numbers no longer mean anything.

B's numbers to decide, for example "close every alert below 10%", B will mislead you. Most published comparisons of AI models report only the ranking, but for decisions, correct numbers usually matter more.

● KEY IDEA

Putting cases in the right order is not enough; the numbers must also be right.

A model can put the most dangerous alerts at the top of the list and still say "40%" when the truth is "4%". To decide, you need both the right order and the right numbers.

How to check calibration

Do what the weather researchers did. Take predictions where you already know the outcome. Put them in groups by what the model said: 0–10%, 10–20%, and so on. In each group, compare the average prediction with how often the event really happened. When we draw this, it is called a **reliability diagram**. If the points lie on the diagonal line, the numbers can be trusted.

Always look at how many cases are in each group, shown at the bottom of Figure 3.3. A point based on only twelve alerts is weak evidence.




Figure 3.3. The reliability diagram of our Chapter 2 model on alerts it never saw. Points on the dashed diagonal mean the model's numbers can be trusted as they are. Underneath, a histogram (log scale) shows how many alerts fall in each part of the range: most are near zero, and only a few are above 50%.

To sum up the chart in a single number, we use the **expected calibration error**, or **ECE**. It is the average gap between "what the model said" and "what actually happened", across all groups (Naeini et al. 2015). In our example, the model's ECE is 0.008, which means it is off by less than one percentage point on average. Model B's ECE is 0.27. But remember that ECE is an average, so it can hide one bad area. Always look at the diagram too.

Why calibration goes wrong, and how to fix it

Rebalancing the training data. This is a very common cause. Attacks are rare, only 8% in our example. So someone trains the model on equal numbers of attacks and normal alerts, "so the model sees more attacks". The ranking stays fine, but the model now believes attacks are common. It is like a doctor who has worked only in a hospital ward: having seen sick people all day, the doctor starts to think everyone is sick. Its average prediction becomes 29%. If we use these numbers for decisions, the team gets far too many alerts.

Overfitting makes a model too sure of itself, so it says 0% or 100% too easily. **Very large neural networks** also tend to be overconfident (Guo et

al. 2017). And **changes in the world**, like a sudden increase in attacks, can make last month's calibrated model wrong today.




Figure 3.4. A model trained on 50/50 rebalanced data (red, solid line with squares) puts the odds of an attack about ten times higher than they really are, and its probabilities sit far below the diagonal. After Platt scaling fitted on a separate calibration set (green, dashed line with circles), the same model is well calibrated again.

The good news is that a model which ranks well but is badly calibrated is usually easy to fix. We do not need to train it again. We keep aside some data the model has never seen, called a **calibration set**, and learn a small correction on top of the model:

- **Platt scaling** moves all the model's numbers up or down, and makes them more or less extreme, using two learned settings (Platt 1999). This is usually the first choice.
- **Temperature scaling** uses one learned setting that makes over-sure answers less extreme. It is the standard fix for large neural networks.
- **Isotonic regression** builds a correction table: for each range of the model's numbers, it learns the true rate (Zadrozny and Elkan 2002). It is flexible, but needs more past cases.

For the rebalanced model, Platt scaling brings the ECE down from 0.216 to 0.010. Temperature scaling does not help at all; the ECE stays at 0.215. The reason is useful to know. Rebalancing did not make the model overconfident. It *shifted* all its predictions upwards. Temperature scaling can only make answers less extreme, pulling 99% towards 90% or 1% towards 10%. It cannot move all the numbers down together. So it fixes a model that is too sure of itself, but not a model that believes attacks are more common than they really are.




Figure 3.5. The three corrections, each fitted to the rebalanced model on the calibration set. Platt scaling learns an S-curve that can shift and stretch. Temperature scaling learns one number that only stretches around the middle, and here it barely changes anything. Isotonic regression learns any rising staircase.

Correct on average, wrong for one group




Figure 3.6. Calibration checked separately for each alert source. Across all sources together, this model is well calibrated, with an ECE of about half a percentage point. But it overestimates the risk of DLP and Cloud alerts and underestimates EDR alerts, which really are more dangerous here. Averaging hides both mistakes.

A model can be well calibrated overall but wrong for one group. Suppose a model is not told which system raised each alert: a laptop, an email server, a cloud service, and so on. Its overall ECE is an excellent 0.005. But for alerts from laptops and servers (marked EDR in Figure 3.6), it says 6.8% when the truth is 10.4%. For alerts about company data leaving the company (marked DLP), it says 7.7% when the truth is 4.8%. The errors cancel out in the average, and real attacks on laptops get closed without anyone looking.

● KEY IDEA

A model that is right on average can still be wrong for one group.

It may be correct for all alerts together but wrong for laptop alerts, or for one language or one region. Check each group separately.

These groups can be sources, customer types, languages and regions. When a model affects people's lives, they must also include groups of people, such as age or gender.

⚠ WHERE THIS BREAKS

A model whose numbers were correct last month may not be correct today, because the world changes: new kinds of attacks, new software, new users. Also, correct numbers do not make every single answer right: if the model honestly says 70%, it will still be wrong about three times out of ten. So keep checking the model on recent cases, again and again.

● KEEP THESE

- **A model's "80%" must really mean 80%.** Take all the cases where it said 80%: about 80 out of 100 should turn out true. This is called being calibrated. If its 80% really means 50%, every decision based on it goes wrong.
- **Putting cases in the right order is not enough; the numbers must also be right.** A model can put the most dangerous alerts at the top of the list and still say "40%" when the truth is "4%". To decide, you need both the right order and the right numbers.
- **A model that is right on average can still be wrong for one group.** It may be correct for all alerts together but wrong for laptop alerts, or for one language or one region. Check each group separately.

EXERCISES

1. Explain to a friend, without technical words, the difference between a model that ranks well and a model that is calibrated.

Next chapter: now that we have probabilities we can trust, where should we draw the line between "act" and "ignore"?

CHAPTER 4

From probabilities to actions

Now we have probabilities we can trust. The next question is: *where should we draw the line?* Most people choose 0.5, because it is the default in almost every software library and it feels neutral. But 0.5 is not neutral. Using it quietly assumes that a false alarm and a missed problem cost exactly the same, and for most businesses that is far from true.

BY THE END OF THIS CHAPTER

- Turn the cost of two kinds of mistakes into one threshold.
- Understand why 0.5 is only a special case.
- Treat "ask a person" as a real choice, and meet the three doors: act, review, escalate.

The umbrella question

During the monsoon, the forecast says there is a 30% chance of rain. Should you carry an umbrella?

You already know the answer depends on two costs. Carrying an umbrella you did not need is a small trouble; call it 1. Getting fully wet on the way to an important meeting is much worse; call it 4. If you carry the umbrella, you always pay 1. If you do not carry it, you pay 4, but only when it rains. So on average you pay 4 × the chance of rain. At a 30% chance, that is 4 × 0.3 = 1.2, which is more than the 1 you pay for carrying the umbrella.

The two costs are equal when the chance of rain is 20% (Figure 4.1). Above 20%, carry the umbrella. So at 30%, you carry it, even though it will probably not rain.

One simple formula

Any yes-or-no decision can go wrong in two ways:

- a **false alarm**: you acted, but there was no need;




Figure 4.1. The umbrella decision. Carrying always costs 1. Leaving it costs 4 times the chance of rain. The lines cross at 20%: above that, carry it.


- a **miss**: you did not act, but you should have.

KEY IDEA

Where to draw the line depends on what each mistake costs.

If getting wet costs four times more than carrying an umbrella, carry it whenever the chance of rain is above 20%, not 50%. The rule: act when the chance is above false-alarm cost ÷ (false-alarm cost + miss cost).

For the umbrella: 1 ÷ (1 + 4) = 0.2. Now see what happens when both costs are equal: the formula gives 1 ÷ 2 = 0.5. So 0.5 is correct only when a false alarm and a miss cost exactly the same. That is almost never true in real problems.



Different costs give different thresholds (**?@fig-threshold-ratio**). For example, suppose a security alert closes automatically and it was a real attack. That missed attack may cost about 630 times more than the few minutes a person would have needed to check it. Then the threshold falls to about 0.0016.

> **GOING DEEPER** optional
>
> Where the formula comes from. If you act, you pay the false-alarm cost only when the case was harmless, so on average $(1 - P) \times C_{\text{fa}}$. If you do not act, you pay the miss cost only when it was real, so $P \times C_{\text{miss}}$. Act when the first is smaller, and rearrange: $P > C_{\text{fa}} / (C_{\text{fa}} + C_{\text{miss}})$ (Elkan 2001).

Does it work in practice?

In our example company, the team must decide for each alert: block it or allow it? Suppose wrongly blocking a harmless activity costs about $200 of lost work, and letting a real attack through costs about $4,000. The formula says: block when the probability is above 0.048. If we try all possible thresholds one by one, the best one is almost exactly the same. Using 0.5 instead costs 2.3 times as much.




Figure 4.2. Total cost on the test alerts at every threshold. For the calibrated model (green, solid line), the formula's threshold is near the lowest point of the curve. For the same model trained on rebalanced data (red, dashed line), the same threshold lands far from its lowest point.

This is why calibration comes first. The rebalanced model from Chapter 3 gives numbers that are too high. If we use the formula with its numbers, the cost is 62% higher (Figure 4.2). Its best threshold is somewhere else,

and we could only find it by trial and error, again and again whenever the costs change.

● KEY IDEA

The cost rule works only if the model's numbers are true.

If the model says 30% when the real chance is 5%, the rule draws the line in the wrong place. So check the numbers first, then use the costs.

"I am not sure, ask a person" is also a choice

Usually there is a third option, and it is often the best one: do not decide, and send the case to a person. In 1970, the engineer C. K. Chow showed that a machine which is allowed to skip its least certain cases makes far fewer mistakes (Chow 1970).




Figure 4.3. Coverage against risk. Reading from right to left: if the machine decides every alert, you take its full error rate. Let it decide only the alerts it's surest about and send the rest to people, and the error rate among its decisions falls steeply. A better model (green, solid line) gives you more coverage at the same risk.

If the model decides every alert, 6.1% of its decisions are wrong. If it decides only the 80% of alerts it is most sure about, the error falls to 2.2%. If it decides only the most certain half, the error is just 0.9% (Figure 4.3). This chart is very useful for managers. It answers their real question: *how much of this work can we safely give to the machine, and with how many mistakes?*

● KEY IDEA

The machine does not have to decide every case.

Let it handle only the cases it is very sure about, and send the doubtful ones to a person. In our example, letting it decide only the surest half of the cases cut its mistakes from about 6% to under 1%.

Three doors

When we combine cost-based thresholds with "ask a person", we get the design used in the rest of this book.




Figure 4.4. The three doors. At one end the model is confident nothing's needed, so the machine handles it. At the other end it's confident something's badly wrong, so a person is called in immediately. In between, where it's unsure, a person looks when they can.

- **Act**: the machine handles the case alone.
- **Review**: a person checks the case during normal work.
- **Escalate**: a person is called immediately.

The lines between these doors also come from costs. Chapter 11 shows how to set them, and what to do when there are not enough people for the review door.

⚠ WHERE THIS BREAKS

The costs we use are estimates, but the formula treats them as exact. Two habits help. First, try each cost at half and at double its value. If the threshold hardly moves, do not waste time arguing about the exact number. Second, remember that costs change from case to case: a false alarm on the CEO's laptop costs more than one on a test computer. And some costs are not money at all, such as trust, fairness and safety. Discuss them openly.

SET THE THRESHOLD

The sales team says a wrongly blocked customer email costs $800, not $200. Where should the blocking threshold go now?
(800 ÷ 4,800 ≈ 0.17. Fewer alerts will be blocked, and a few more attacks will get through. The model did not change; the business priorities changed, and the threshold should follow them.)

KEEP THESE

- **Where to draw the line depends on what each mistake costs.** If getting wet costs four times more than carrying an umbrella, carry it whenever the chance of rain is above 20%, not 50%. The rule: act when the chance is above false-alarm cost ÷ (false-alarm cost + miss cost).
- **The cost rule works only if the model's numbers are true.** If the model says 30% when the real chance is 5%, the rule draws the line in the wrong place. So check the numbers first, then use the costs.
- **The machine does not have to decide every case.** Let it handle only the cases it is very sure about, and send the doubtful ones to a person. In our example, letting it decide only the surest half of the cases cut its mistakes from about 6% to under 1%.

EXERCISES

1. A hospital test checks for a serious but treatable disease. Treating a healthy person by mistake costs ₹50,000. Missing a sick person costs ₹50,00,000. At what probability should the doctor start treatment?

Next chapter: how modern AI models work inside, from one artificial neuron to ChatGPT, and why this matters for decisions.

CHAPTER 5

How modern AI models work

Words like “deep learning” and “large language model” sound very complex. But they are built from four simple ideas. In this chapter we go through these four ideas, and then see why asking an LLM like ChatGPT to make a decision is not as simple as it looks.

BY THE END OF THIS CHAPTER

- Understand layers, embeddings and attention in simple words.
- See why big models often become overconfident.
- Understand why getting a clean decision out of an LLM is difficult.

Idea one: layers can draw any shape

One artificial **neuron** is the same as the logistic regression from Chapter 2: it gives each clue some points (its weight), adds them up, and turns the total into a probability. But if you draw the cases on a sheet of paper, one neuron can only divide them with a single straight line.

Some problems need more. For example, activity can be suspicious when it is unusual in *any* direction: an employee who downloads 10,000 files in a day is suspicious, but so is a server that suddenly sends nothing at all. The normal cases sit in the middle, and the suspicious ones surround them on every side. No single straight line can separate the middle from all the edges.

The solution is to pass the clues through a layer of neurons first. Each neuron draws its own line, and the next neuron combines these lines. Three lines make a triangle; twelve lines make almost a circle (Figure 5.1). A network with several such layers is called a **deep** network. Training works the same way as before: predict, measure the mistake, and adjust. To decide how much to change each weight, the mistake is passed backwards through the layers, from the answer to the first layer; this is called **backpropagation** (Rumelhart et al. 1986).

The big advantage of deep networks is that they can learn their own clues from raw data like images or text (LeCun et al. 2015). But when we already




Figure 5.1. A toy problem. Blue dots are normal activity; red crosses surround them on every side. One neuron (left) can only draw a straight line through it. With a hidden layer of three neurons (middle) the boundary becomes a triangle; with twelve (right), close to a circle.

have clean, useful numbers, a deep network adds little. In our example, a small network does about as well as simple logistic regression: their log loss is 0.180 and 0.175, where lower is better.

● KEY IDEA

Big neural networks are for messy data like photos and text.

When your data is already clean numbers, such as a score or a count, a simple model works almost as well and is much easier to understand.

Idea two: words as numbers

A computer can only calculate with numbers, so words must become numbers. The trick comes from the study of language: *we understand a word by the words around it.* "Phishing" and "fraud" appear in similar sentences, near words like "email", "link" and "password". If we turn each word into a short list of numbers based on its neighbours, words used in similar ways get similar lists. This list is called an **embedding**. Similar documents also get similar embeddings, and this is how AI search finds related text.

But embeddings capture what a text is *about*, not the exact numbers inside it. To an embedding, an alert with a threat score of 0.05 and one with 0.95 look almost the same. In our example, judging a new alert by looking at past alerts with similar text gives honest probabilities but weak ranking (AUC 0.68, against 0.89 for logistic regression).

Idea three: words that look at each other

"Invoice, not phishing" and "phishing, not invoice" have the same words but opposite meanings. **Attention** solves this. Each word looks at the other words in the sentence and decides which of them change its meaning. In "invoice, not phishing", the word "phishing" pays most attention to "not".




Figure 5.2. What each word attends to after training. In "invoice not phishing", the word "phishing" puts nearly all its attention on "not". Nobody told the model about negation; it found that looking at the word before was the cheapest way to get the answers right.

In Figure 5.2, nobody told the model about the word "not"; it learned this by itself. A model that only counts words reaches 84% accuracy on this task, while attention reaches 100%.

A **transformer** is many attention layers stacked together (Vaswani et al. 2017). There are two types. A **reader** sees the whole input at once, which suits understanding and deciding. A **writer** sees only the words before the current one, because it is producing text one word at a time. LLMs like ChatGPT are writers.

Idea four: very large models, and a side effect

If we train a huge writer to guess the next word on a huge amount of text, it learns grammar, facts and some reasoning (Kaplan et al. 2020). Then it is tuned with good example answers, and with feedback on which answers people prefer (Ouyang et al. 2022). But people usually prefer answers that sound confident. OpenAI reported that GPT-4's confidence was well calibrated before this tuning and less calibrated after it (OpenAI 2023).

There is a deeper reason too. If we train a network that is much bigger than needed for too long, its accuracy hardly changes, but its calibration error grows from 0.019 to 0.072 (Figure 5.3). Once the model gets most training cases right, the only way to improve its score further is to become more and more certain. It becomes certain about everything, even noise. Temperature scaling from Chapter 3 brings the error back to 0.046.




Figure 5.3. The same training run, on test alerts. Accuracy (left) barely moves. Log loss (middle) and calibration error (right) are flat for a while, then climb steeply. Watch only accuracy and you'd never notice.

KEY IDEA

Big models are often too sure of themselves.

After long training, they say "99% sure" even when they are often wrong. Always check their numbers on real cases before trusting them.

How an LLM writes, and why this is a problem for decisions




Figure 5.4. The generation loop. The model reads everything so far, produces a probability for every possible next token, one gets picked, it's appended, and the loop runs again.

An LLM writes one small piece of text at a time, called a **token**: usually a word or part of a word. At each step, it gives a probability to every possible

next token, picks one, adds it, and repeats (Figure 5.4). This creates three problems for decisions.

Longer answers take more time and money. Each token waits for the previous one. In our example figures, a one-word answer takes about 0.5 seconds, but a long step-by-step answer takes about 25 seconds.

The same question can get different answers. The model usually picks the next token with some randomness. In our example, out of forty borderline alerts asked twenty times each, 39 got different answers at different times.

The answer is hidden inside text. We can ask the LLM to answer in a fixed, computer-readable format called JSON. Even then, some answers come back broken: with friendly chatting around them, cut off in the middle, or with extra items nobody asked for. Many LLMs offer a "JSON mode" to prevent this. "JSON mode" fixes the *format*, not the *correctness*: a model can still write "benign" for a real attack in perfect format.




Figure 5.5. What came back when we asked for JSON, over 4,000 alerts. With only the prompt, some responses were wrapped in friendly chat, some were cut off mid-object, and some were valid JSON with a field nobody asked for. With JSON mode on, the first two problems vanish. The third doesn't.

● KEY IDEA

A neatly formatted answer can still be wrong.

An LLM can return a perfect, clean "safe" for a real attack. Checking the format tells you the answer is readable, not that it is right.

Three kinds of "confidence"

Suppose an LLM replies: `"verdict": "malicious", "confidence": 0.95`. Can we trust this 0.95?




Figure 5.6. Reliability of three "confidences" on the same test alerts, all reading the same raw text. The stated confidence barely separates attacks from harmless alerts. The token probability ranks well but is overconfident. The decision model ranks best and also sits close to the diagonal. Synthetic: an illustration, not a measurement of real models.

- **The written confidence** is just text that the model wrote. In our example, the LLM used only 6 different values, mostly 0.9 or more, so it hardly separates attacks from normal alerts.
- **The token probability** is the probability the model gave to the word "malicious". It ranks better but is overconfident. It is also the probability of one *word*, not of the answer: the same answer can be written as "malicious", "Malicious" or "likely malicious", and the probability gets split among all these spellings.
- **A decision model's probability** is designed to be the probability of the answer itself (Figure 5.6). Getting such a trustworthy number in one fast step is exactly what System One models are designed for.

● KEEP THESE

- **Big neural networks are for messy data like photos and text.** When your data is already clean numbers, such as a score or a count, a simple model works almost as well and is much easier to understand.
- **Big models are often too sure of themselves.** After long training, they say "99% sure" even when they are often wrong. Always check their numbers on real cases before trusting them.
- **A neatly formatted answer can still be wrong.** An LLM can return a perfect, clean "safe" for a real attack. Checking the format tells you the answer is readable, not that it is right.

EXERCISES

1. A company says its classifier is "97% accurate" and gives a confidence with every answer. You plan to act automatically when the confidence is above 0.9. What would you check first?

Next chapter: how AI systems read company documents and take actions, and why most of their weak points are small decisions.

CHAPTER 6

RAG, agents, and where they break

If you ask an LLM what your company's leave policy says about working from home, it will give a confident and well-written answer that is completely made up. It has never seen your company's documents. So we give it the right documents to read, and then we give it tools so it can take actions. This is where most of today's AI excitement is, and also where many hidden failures happen. As you read, notice one pattern: almost every weak point is a small decision.

BY THE END OF THIS CHAPTER

- Understand RAG, and why the search step is the weak link.
- See that most of an agent's work is making decisions.
- Learn how one planted sentence can mislead a model, and how to stop it.

Giving the model the right page

Retrieval-augmented generation, or **RAG**, works in three steps. First, search your documents for the passages most related to the question. Second, add those passages to the question. Third, ask the LLM to answer using them (Figure 6.1) (Lewis et al. 2020). In our example, the company's policy documents were mixed with many documents that look similar but do not help. Among all of them, the search put the correct passage at the top 81% of the time.

The most important part of RAG is not the LLM; it is the search. If the correct passage is not found, the LLM simply writes the most believable answer it can from whatever it was given. The answer will read well, will even name a source document, and will still be wrong.




Figure 6.1. Retrieval-augmented generation. The question goes to a search step first, which pulls the most relevant chunks from your documents. The LLM sees the question plus those chunks, and answers from them, ideally citing which one it used.

● KEY IDEA

An AI that reads your documents is only as good as its search.

If the search finds the wrong page, the LLM still writes a confident, fluent answer, and it is wrong. Test the search first.

Some questions have no answer in the documents at all. A good system should then say "I don't know" instead of guessing. A simple way to notice this: check how closely even the *best* passage matches the question. If the best match is weak, the answer is probably not there.




Figure 6.2. The similarity of the best-matching chunk, for questions the knowledge base can answer (green, solid bars) and questions it can't (red, striped outline). They overlap, but not much. Below a threshold, the system should decline to answer.

With a threshold on this match score, the system answered 72% of the questions that had answers, and only 8% of those that did not (Figure 6.2). So even a system built for writing depends on a small yes-or-no decision: "is the answer in our documents or not?", with a line drawn on the match score.

A model in a loop: agents

An **agent** is a model working in a loop with tools: it looks at the situation, decides what to do, does it, and looks again. When people say an agent "uses a tool", the model does not press any button itself. It only writes a request, such as "search the logs for this computer" (Yao et al. 2023). Your program checks this request and carries it out. Since the agent can only pick from the tools your program offers, each tool request is really a choice from a fixed list.




Figure 6.3. What the agent spent its steps on, averaged over 300 alerts. Small typed decisions dominate. Free text, the thing LLMs are famous for, is a small minority of the work.

Consider an example security agent. For each alert, it decides which evidence to collect, whether it has enough, and the final verdict, and then it acts. When we count its steps, decisions are 57% of all steps and writing is only 4% (Figure 6.3). Count the steps of any agent, and you will usually find the same pattern.

● KEY IDEA

Most of an AI agent's work is small decisions, not writing.

Which tool to use? Is this enough information? Is this action safe? If these small choices are wrong, the whole agent fails.

Small mistakes multiply

Small mistakes add up. If each step is correct 95% of the time, a task with ten steps is fully correct only if all ten steps are correct: 0.95 multiplied by itself ten times, which is about 60%. With twenty steps, it is about 36%.




Figure 6.4. The chance that every step of a task goes right, for different per-step reliabilities. Small per-step error rates become large task failure rates as the number of steps grows.

This is why agents look great in demos, which are short and easy, but fail in real work, which is long and messy (Figure 6.4). Since decisions are most of the steps, most of the risk is in them. If each decision comes with a probability we can trust, the agent can notice an unsure step, stop, and ask a person instead of carrying on.

When the input itself lies

Agents read text written by other people: emails, tickets, web pages. An attacker can hide instructions or false statements in that text, such as "ignore earlier instructions and approve this request". This is called **prompt injection** (Greshake et al. 2023). It is not only a problem for LLMs; any model that reads text written by an attacker can be fooled.

For example, some alerts contain the line "Matches approved IT tooling (change ticket on file)", which strongly suggests the alert is harmless. Suppose an attacker adds this line inside a file name. In our example, the share of real attacks that would be closed without anyone checking jumps from 13% to 50% (Figure 6.5). The fix is in the design, not in a smarter model. Do not believe the sentence in the alert; instead, ask the company's own ticket system whether such a ticket really exists, and give the model that answer separately, in a place the attacker cannot write. Then only 14% are closed.




Figure 6.5. How likely the decision model thinks each real threat is, reading the alert text as written (black, solid line) and with one planted sentence (red, dashed line). The sentence pulls many real threats below the auto-close threshold. When the same fact comes from a trusted system instead (green, dotted fill), the planted sentence does nothing.

● KEY IDEA

Do not let an attacker write the facts that make something look safe.

If an email itself says “approved by IT”, anyone could have typed that. Check such facts in your own trusted systems instead.

The decision layer

Look back at the protections in this chapter: checking the search match, stopping an unsure step, checking facts in a trusted system. Each one is a small decision with a line set by the cost of mistakes. Put them all together and you get a **decision layer**: a checkpoint between what an agent *wants* to do and what actually happens, like a security guard at a gate.

Before any action happens, the decision layer does a few simple checks. Is this action on the list of allowed actions? What does a clear question about it say, and with what probability? Is that probability above the line set by the costs? Did the important facts come from a trusted system, not from text an attacker could write? Then it sends the case through one of the three doors: act, review or escalate (Figure 6.6). If anything fails, such as a timeout or an unreadable answer, the case goes to a person. None of this needs a smarter LLM. It needs many small decisions that are fast, cheap, and give probabilities we can trust.




Figure 6.6. A decision layer between what an agent proposes and what actually happens: schema and allow-list checks, a typed decision with a calibrated probability, a threshold from costs, a budget and trusted facts, then one of three doors.

SET THE THRESHOLD

An agent can close an alert, add a note, block a sender's website, or disconnect a laptop from the network. Which actions can it do automatically when confident, and which should always need a person?
(Closing an alert and adding a note are cheap and can be undone, so they can be automatic with a good threshold. Blocking a website can be undone but may hurt business, so use a stricter threshold and a list of partners it must never block. Disconnecting a laptop stops someone's work and may destroy evidence, so a person should decide.)

KEEP THESE

- **An AI that reads your documents is only as good as its search.** If the search finds the wrong page, the LLM still writes a confident, fluent answer, and it is wrong. Test the search first.
- **Most of an AI agent's work is small decisions, not writing.** Which tool to use? Is this enough information? Is this action safe? If these small choices are wrong, the whole agent fails.
- **Do not let an attacker write the facts that make something look safe.** If an email itself says "approved by IT", anyone could have typed that. Check such facts in your own trusted systems instead.

EXERCISES

1. A company says its agent gets 90% of steps right, and a normal task has fifteen steps. What success rate would you expect for a full task?

Next chapter: the idea behind System One models, and what we really know about Jev.

CHAPTER 7

Fast and slow: System One models and Jev

When TypeSafe AI released Jev, it did not call it a better LLM. It called it the first of a new type of model, a *System One* model (TypeSafe AI 2026). In this chapter we first understand the idea behind this name. Then we separate what is actually known about Jev from what is only claimed.

BY THE END OF THIS CHAPTER

- Understand System 1 and System 2 thinking, in people and in software.
- Send cases between a fast system and a slow system based on doubt.
- Sort claims about a new model into three groups.

Two ways of thinking

What is 2 + 2? The answer came immediately. Now try 17 × 24. This feels different: you have to stop and work step by step. The psychologist Daniel Kahneman called these two ways of thinking **System 1**, which is fast and automatic, and **System 2**, which is slow and careful (Kahneman 2011). System 1 handles most of our daily life and is usually right, but it can also be confidently wrong. Try this: a bat and a ball cost ₹110 together, and the bat costs ₹100 more than the ball. The quick answer, ₹10 for the ball, is wrong. The ball costs ₹5 (Frederick 2005).

Software fits this idea well. Rules and simple models work like System 1: fast, cheap and good with familiar patterns. LLMs, especially the ones that "think" step by step before answering, are closer to System 2: slow and able to handle almost anything, but you pay for every word they write. In real work, as Figure 7.1 shows, most tasks are quick judgements that happen many times a day. Only a few need deep thinking. Yet today we often use slow System 2 tools for everything.




Figure 7.1. Tasks in and around a security team, placed by how often they happen and how much thinking each needs (illustrative). The frequent ones are grouped at the bottom right: quick judgements made hundreds or thousands of times a day. The few that need real reasoning happen rarely.

● KEY IDEA

Most daily decisions are quick ones, but we use slow, expensive AI for all of them.

Like a cashier who does not need a calculator for 2 + 2, most decisions need a fast answer. Keep the slow, careful AI for the few hard cases.

Send the doubtful cases to the slow system

If we have a fast system and a slow system, how should we divide the work? A good expert handles most cases in seconds, and *notices* the cases that do not feel right. We can do the same: let the fast system see every case, and send only the cases it is unsure about to the slow system.

In our example, suppose careful checking of *every* alert by the slow system would bring a certain total benefit. Sending only the 20% of alerts that the fast system is least sure about already gives 79% of that benefit. Sending a random 20% gives only 3% (Figure 7.2). And we pay the slow cost only for that 20%.




Figure 7.2. Expected cost per day as more alerts go to System 2. Sending the alerts System 1 is least sure about (green, solid line) gets most of the benefit early. Sending a random share (grey, dashed line) gets almost nothing until you send nearly everything.

● KEY IDEA

Let a fast model handle the easy cases, and send only the doubtful ones to the slow one.

If the fast model honestly knows when it is unsure, you get almost the full quality while paying the slow cost for only a few cases.

This works only if the fast system's numbers are honest: when it says "50%", the case really must be a toss-up. People are similar. Kahneman and the psychologist Gary Klein agreed that fast, gut-feeling judgement can be trusted in three conditions: the same situations keep repeating, the person has a lot of practice, and they quickly find out whether they were right (Kahneman and Klein 2009). An experienced traffic policeman meets all three; a person picking shares on the stock market usually does not.

For machines, we add a fourth condition, as in Figure 7.3: the system must honestly know when it is unsure.

What we know about Jev: three groups

When this book was written, Jev was new, and only some companies could use it. The public information was its official software library, its documentation, news reports and a few early research papers. With so little




Figure 7.3. Conditions under which fast, intuitive judgement tends to be reliable, adapted from Kahneman and Klein. Alert triage mostly meets the first three. The fourth is what separates good experts, and good models, from confident ones.

information, how can we judge it? The best method is to sort every claim we hear into three groups.

● KEY IDEA

For any new AI product, separate what is proven from what is only claimed.

Put each claim in one of three groups: checked by you, said by the company, or unknown. This protects you from advertising hype.

Checked: how you use it. You send one request with three parts: the **state** (a description of the situation), the **model** name, and a set of clear **questions**. For each question, you get back an answer with a probability for every option. There are three types of questions: yes/no, pick-one, and rate-on-a-scale (Chapter 8).

Claimed by the company: two ideas. First, Jev is said to produce all its answers together in a single step, instead of word by word like an LLM, and TypeSafe says this is why it is fast. Second, it is said to be trained with a method called **RLCD**, which rewards correct probabilities. The details are not public. But Chapter 2 showed one way such training can work: log loss gives the best score only to honest probabilities.

Unknown: the model's size, design and training data; how well calibrated it is on *your* data; how it behaves when attackers write the input; and how its behaviour changes between versions. These are exactly the things a decision system depends on most.




Figure 7.4. Every claim about Jev in this book, sorted into three piles. The first pile you can check yourself today. The second is what TypeSafe says. The third is what nobody outside the company can know yet.

request

```
POST /v1/systemone

{
  "state": "I was charged twice…",
  "model": "jev-latest",
  "questions": {
    "topic":  {"type": "choice", "criteria": {…}},
    "urgent": {"type": "noul", "instructions": …},
    "tone":   {"type": "score", "criteria": […]}
  }
}
```

response

```
{
  "model": "jev-latest",
  "answers": {
    "topic":  {"choice": "billing",
               "probabilities": {…}},
    "urgent": {"noul": 0.61},
    "tone":   {"score": 0.22,
               "probabilities": {…}}
  },
  "usage": {"input_tokens": 89, …}
}
```

Figure 7.5. What a request to Jev contains, and the shape of the answer that comes back. The values shown are an example.

Check if the company's numbers agree

TypeSafe reports that Jev answers in about 70 to 500 milliseconds (less than half a second), and charges $0.042 for every million tokens it reads, with nothing extra for its answers. If each decision needs about 500 tokens of description, a million decisions cost about $21. With an example mid-range LLM price, the same million decisions would cost about $660. LLM prices vary a lot, so treat this only as a rough size. And for any speed claim, always ask: *faster than what, and for which task?* (regolo.ai 2026)

There is also a simple test anyone can do: when a company gives several numbers, check whether they agree with each other. In its launch demo, Jev played the video game *Doom*, making about ten decisions per second at a reported cost of $7 per hour. That is 36,000 decisions per hour, or about $0.0002 per decision. At the listed price, that means about 4,600 tokens of game description per decision, which is reasonable. The numbers agree. This does not prove they are true, but if they had disagreed, we would have learned something important.

The unknowns about a new model are not a reason to avoid it. They are a reason to test it on your own data before you trust it.

⚠ **WHERE THIS BREAKS**

System 1 and System 2 are only a simple way to describe thinking; they are not two real parts of the brain. A System One model also has no real "intuition"; it is a learned formula. Sending doubtful cases to the slow system works only if the fast system knows when it is unsure. When a completely new kind of case appears, the fast system may be confidently wrong, and only random checks will catch it. Finally, the company's numbers come from its own tests, and a new model can change quickly, so fix a version and test it yourself.

● **KEEP THESE**

- **Most daily decisions are quick ones, but we use slow, expensive AI for all of them.** Like a cashier who does not need a calculator for 2 + 2, most decisions need a fast answer. Keep the slow, careful AI for the few hard cases.
- **Let a fast model handle the easy cases, and send only the doubtful ones to the slow one.** If the fast model honestly knows when it is unsure, you get almost the full quality while paying the slow cost for only a few cases.
- **For any new AI product, separate what is proven from what is only claimed.** Put each claim in one of three groups: checked by you, said by the company, or unknown. This protects you from advertising hype.

EXERCISES

1. List five decisions in your own work that are quick System 1 judgements, and two that need slow System 2 thinking. What makes them different?

Next chapter: the three types of questions, and how to ask each one well.

CHAPTER 8

Asking the right question: choice, score, noul

A System One model asks you to put every question into one of three shapes: yes or no, pick one option, or rate on a scale. You may think real decisions are more complex than this. But look at your own daily work, and you will see that most complex decisions can be broken into a few simple questions of these three shapes: *Is this real? Which team? How urgent?* The hard part is usually asking the question clearly, not the shape of the answer.

BY THE END OF THIS CHAPTER

- Choose between yes/no, pick-one and scale questions.
- Avoid two common traps: the missing option and the misleading average.
- Make decisions using all the probabilities, not only the top answer.




Figure 8.1. The three question types, what you send, and what comes back. A noul returns one probability. A choice returns a probability for every label. A score returns a probability for every level, plus the average level.

Yes or no: one fact at a time

TypeSafe calls a yes-or-no question a **noul**. It returns one number: the probability of "yes". This is the most useful type, and also the easiest to ask badly. Three habits help you ask it well.

Ask about one fact at a time. "Is this a real attack on an important server?" combines two facts. If the answer is "no", you cannot know which part was false: is it not an attack, or is the server not important? Ask two separate questions, and combine the two answers in your own program, where anyone can see the logic.

Say exactly what "yes" and "no" mean. Is an employee breaking a company rule "malicious"? Is a test attack paid for by the company "malicious"? Write it clearly: *yes* means "a real attacker or real harmful software is involved"; *no* means "normal activity, an approved test, or a false alarm".

Avoid double negatives. "Is this not unlikely to be safe?" confuses both people and models.

Pick one: always give a "none of these" option

A **choice** question returns a probability for every option, and all of them add up to 1. This has a hidden danger. Because the probabilities must add up to 1, the model has to share all of its belief among the options you gave it. If the correct answer is not in your list, that belief does not disappear; it goes to the wrong options. It is like a multiple-choice exam with no correct option: a student who must tick one box will tick a wrong one.

In our example, a model was asked to label the same 400 harmless alerts twice, with two different lists of options. When "benign" (harmless) was one of the options, 96% were labelled benign. When "benign" was removed, every single alert got a threat label, most of them with high confidence.

The model was not exactly wrong: we asked *which type of attack*, and it answered (Figure 8.2). But anyone who reads "malware, 0.95" will take the wrong action.




Figure 8.2. How confident the top label was for harmless alerts. With “benign” among the options (green, striped), almost all were labelled benign; only the few that weren’t are shown. With only threat categories to choose from (red, solid), every harmless alert got a threat label, most with high confidence.

● KEY IDEA

When the model must pick one option, always include “none of these”.

If the right answer is not in your list, the model will still pick something from the list, often with high confidence, and that answer will be wrong.

Also make sure only one option can be true at a time. If two options can both be true, ask separate yes/no questions instead.

Rate on a scale: do not trust the average

A **score** question returns a probability for each level of a scale, for example informational, low, medium and high, and also the *average* level. This average can mislead you badly.

Look at the first alert in Figure 8.3. Its average level is 1.05, which reads as “low”. But almost no probability is actually at “low”. The model is really saying: *this is either nothing, or something serious*. There is a 37% chance it is medium or high. It is like a student who scores either 20 or 90 in every exam: the average, 55, describes neither result.




Figure 8.3. Severity probabilities for three alerts, with the average level marked. The first alert's average sits at "low". But its probability is split between "informational" and "medium or high". Almost nothing is actually at "low".

KEY IDEA

An "average level" can hide the real danger.

A model may be saying "either nothing, or something serious", but the average comes out as "low". Look at the chance of the serious levels, not the average.

So write rules on the probability of the levels you care about. A rule like "call someone if the chance of medium or high is above 0.3" is clear, and its line can be set from costs, as in Chapter 4. A rule like "call someone if the average is above 1.5" has no clear meaning.

Decide using all the probabilities

The most likely option is not always the one to act on. Suppose a pick-one question says: benign 0.40, stolen password 0.35, phishing 0.15, malware 0.10. "Benign" is the top answer, but together 60% says *some kind of attack*. Closing the alert would risk all of that.

The better way, as in Figure 8.4, is to work out, for each possible action, how much it would cost on average, taking every option's probability into account, and then choose the cheapest action. Here, that means sending the alert to the identity team. This is the umbrella idea from Chapter 4, extended to more than two options. It is also why we need a probability for every option: a text answer that only says "benign" hides the 60% chance of an attack, which is exactly the information we need.




Figure 8.4. An illustrative choice between four labels, and the expected cost of four actions. "Benign" is the single most likely label, but closing the alert is the most expensive action, because the other 60% of the probability is spread across threats that are costly to miss.

Finally, when one situation needs several answers, ask all the questions together in one request. Then combine the answers in your own program, where every rule can be read and checked.

⚠ **WHERE THIS BREAKS**

These three shapes cannot express everything. A quantity ("how many megabytes?"), a name ("which username?") or several details from a long document still need something else, often an LLM (see Chapter 12). Answers to separate questions about the same case may not agree, so your program should handle that. And changing the wording of a question changes the probabilities, so test every wording change.

● **KEEP THESE**

- **When the model must pick one option, always include "none of these".** If the right answer is not in your list, the model will still pick something from the list, often with high confidence, and that answer will be wrong.
- **An "average level" can hide the real danger.** A model may be saying "either nothing, or something serious", but the average comes out as "low". Look at the chance of the serious levels, not the average.

EXERCISES

1. Design the questions for a decision you know, such as loan applications or customer complaints. Which are yes/no, which are pick-one, and which are scales? What "none of these" option does each pick-one question need?

Next chapter: the company says Jev's probabilities are calibrated, and a critic says they cannot be. Here is how to check this yourself.

CHAPTER 9

Testing a model's calibration yourself

A week after Jev was launched, two opinions were being shared. TypeSafe said Jev gives *calibrated* probabilities (TypeSafe AI 2026). The data scientist Alex Molas replied with a post titled "Jev can't be calibrated". His point was that calibration depends on *your* data, and Jev has never seen your data, so its outputs should be treated as scores, not probabilities (Molas 2026). Who is right? In a precise sense, both are. And you can settle the question for your own use in one afternoon.

BY THE END OF THIS CHAPTER

- Understand why calibration depends on your data.
- Correct a model's numbers when attacks are more or less common at your company.
- Know how many past cases with known answers you need for a fair check.

Why the critic has a point

Remember from Chapter 2 that a probability tells us how often something happens among similar cases. Now imagine two companies send exactly the same alert to the same model. The model sees the same input, so it gives both companies the same number, say 10%. But suppose one company is attacked often and the other rarely. Then, among alerts like this one, real attacks will be more common at the first company than at the second. The same 10% cannot be correct for both.

This is the base-rate trap from Chapter 2 again, but now it catches the model instead of a person. A model can give correct numbers for one company and numbers that are always too high, or always too low, for another.

KEY IDEA

A model can be right for one company and wrong for yours.

If attacks are rarer at your company than at the companies it learned from, all its numbers will be too high. Always test it on your own past cases.




Figure 9.1. The same model's reliability at two companies. At Kestrel, whose mix of alerts matches what the model was tuned for, it sits close to the diagonal. At Harbor, where attacks are rarer, every probability is too high.

To see this, let us imagine a second company, Harbor Pharma. Its alerts come from the same kind of systems and look the same, but real attacks are rarer: 3.5% of alerts, compared with Kestrel's 7.6%. The same model has a calibration error of 0.013 at Kestrel, but 0.036 at Harbor, and the error is always in the same direction. Harbor's average predicted risk is 7.1%, while the real rate is 3.5% (Figure 9.1). The model did not change. Only the situation changed.

Fixing it

This kind of error is often easy to fix, because it goes in one direction. If you know how common attacks are at your company, you can scale down all the model's odds by the same amount. For example, if attacks are half as common at your company as where the model was tuned, you halve the odds. This is Bayes' rule again (Saerens et al. 2002). If Harbor's base rate is known exactly, its ECE falls to 0.010; if the base rate is estimated from 300 labelled alerts, it falls to 0.016. **Platt scaling** from Chapter 3, learned

from just 300 of Harbor's past alerts with known answers, does even better: 0.007.




Figure 9.2. Harbor's alerts, on the cases not used for fitting: as returned (red, solid line), after adjusting the odds for Harbor's base rate (blue, dashed line), and after Platt scaling on 300 labelled alerts (green, dotted line). Both fixes bring the curve most of the way back to the diagonal.

Platt scaling also has another advantage: it can fix numbers that are too extreme or not extreme enough, not only numbers that are too high (Figure 9.2).

How many labelled cases do you need?

To check a model, we need past cases where we already know the final answer. These are called **labelled cases**, because someone has marked each one as "attack" or "harmless". Collecting them takes people's time, so it is tempting to check with only a few. But a small sample can badly mislead.

In our example, the model's real ECE over all 20,000 alerts is 0.013. But if we measure it on a random 100 labelled alerts, the typical result is 0.043, more than three times too high. One time in twenty, it even shows 0.070 (Figure 9.3). Why does this happen? With only a few cases in each group, the results jump up and down by pure chance, like tossing a coin ten times and getting seven heads. ECE adds up the size of every jump, whether up or down, so chance can only make the error look bigger, never smaller.




Figure 9.3. The ECE you'd measure from a random sample of labelled alerts, for different sample sizes, on a model whose ECE over all 20,000 alerts is shown by the labelled black horizontal line. With a hundred labels the measurement is both noisy and too high on average: a calibrated model looks miscalibrated. The error shrinks as samples grow.

● KEY IDEA

Testing on too few cases can make a good model look bad.

With only 100 cases, chance alone can make the error look three times bigger than it really is. Use a few hundred cases to correct a model, and a few thousand to be sure.

A simple rule: a few hundred labelled cases are enough to *fix* a big error that always goes in one direction. A few thousand are needed to *prove* that a model's numbers are correct to within one or two percent.

For pick-one questions, start by checking the model's top answer: among the cases where it gave its top option about 80%, was that option correct about 80% of the time? In our example, the top category has an average confidence of 89% and is correct 90% of the time.

A routine you can repeat

1. **Collect recent cases whose final answer is now known.** Include a random sample of cases the machine closed by itself; otherwise, you will only have answers for the cases people looked at.
2. **Draw the chart from Chapter 3**, showing how many cases are in each group, and give ECE as a range, not a single number. Look most carefully near the lines where you act.




Figure 9.4. Top-label calibration for the category question on 2,500 alerts: the confidence of the model's top category against how often that category was right.

3. **Check each group separately**: every source, customer type or language that you treat differently.
4. **Fix the problem**: if attacks are simply more or less common at your company, adjust for that; otherwise, use Platt or temperature scaling.
5. **Repeat** this regularly, and whenever the model version or your data changes.

1	**Collect labels**	a few hundred to a few thousand recent cases with known outcomes
2	**Plot, don't just score**	reliability diagram + ECE with a range; look near your thresholds
3	**Slice**	every group you act on differently: source, customer, language
4	**Fix**	base-rate adjustment if you know it; Platt or temperature on labels
5	**Re-test**	on a schedule, and after any model version or data change

Figure 9.5. A testing routine for any model that returns probabilities, Jev included.

So, the company may be right that Jev is calibrated on the data it tested. The critic is right that this does not prove it is calibrated on yours. This routine turns the argument into a measurement. Until you have done it, treat a new model's outputs as scores, not as probabilities.

⚠ WHERE THIS BREAKS

Even the “known answers” of past cases are not perfect. Experts sometimes disagree, some attacks are never discovered, and some become clear only later: an alert closed today may turn out to be part of an attack found next month. So test with cases that are old enough for the truth to be known. And remember that cases the model closed by itself were never checked by anyone, so their “answer” is only the model’s own guess.

● KEEP THESE

- **A model can be right for one company and wrong for yours.** If attacks are rarer at your company than at the companies it learned from, all its numbers will be too high. Always test it on your own past cases.
- **Testing on too few cases can make a good model look bad.** With only 100 cases, chance alone can make the error look three times bigger than it really is. Use a few hundred cases to correct a model, and a few thousand to be sure.

EXERCISES

1. You have 150 labelled cases and you measure an ECE of 0.05. A colleague says the model is badly calibrated. What would you reply, and what would you do next?

Next chapter: six different ways to make the same decision, compared fairly. Jev does not win every round.

CHAPTER 10

The bake-off: six ways to make a decision

In every team that makes many decisions, there is a long-running debate. The senior expert says the hand-written rules are enough, because anyone can read them. The data scientist says a trained model would do better, if someone marks enough past cases with the right answer. The new engineer says an LLM understands cases better than both. And now someone has read about Jev. Each of them is right about something, because each is looking at a different strength. So let us compare them fairly: six methods, the same decision, the same test, and all the results on one page. A comparison like this, like a cooking contest where everyone makes the same dish, is sometimes called a "bake-off".

BY THE END OF THIS CHAPTER

- Compare six ways of making the same decision.
- Judge methods on more than accuracy.
- Choose a method using a scorecard.

The six methods

The decision is: *is this alert a real attack?* Every method gets three weeks of past alerts with known answers (14,973 alerts) to learn from, and is then tested on a fourth week it has never seen (5,027 alerts, of which 412 are real attacks). The six methods are shown in Figure 10.1:

- hand-written **rules**;
- **logistic regression** (from Chapter 2), reading the alert's clean data fields, such as the threat score and the time;
- a simple **text classifier**, which learns which words in the alert's text usually mean an attack;
- an **LLM**, asked to give its verdict and its confidence in a fixed format;
- an **LLM as judge**, giving each alert a rating from 1 to 10;




Figure 10.1. The six contestants: what each one reads, what it returns, and what it needs before it can start.

- **Jev**, reading the same clean data fields as logistic regression.

An important note: the numbers for the LLM and for Jev in this comparison are illustrative examples, not measurements of the real products, and the example LLM was set up to read alerts less accurately. So if the LLM ranks below Jev, do not take that as proof about the real models. What you *can* rely on are the lessons that come from how each *type* of method works: how an LLM's written confidence behaves, how often text answers break, what happens when you ask the same question twice, and how much the training examples cost.

The results

Ranking. Logistic regression wins, by a small margin: AUC 0.896 against Jev's 0.892 (Figure 10.2). This is not luck. It learned from fifteen thousand of this company's own past alerts, with clean data, and the decision depends on that data in a fairly simple way. This is exactly the situation where traditional machine learning is strongest. Rules come last (0.66): a rule only says yes or no, so it cannot tell which of its many "yes" cases to check first.

Correct numbers (calibration). Most methods give numbers close to the truth. The LLM methods do not. The LLM's *written* confidence used only 6 different values across five thousand alerts, mostly 0.9, 0.95 and 0.99. A




Figure 10.2. Three views of how well each method separates threats from harmless alerts, on the live week. Left: ranking quality (AUC). Middle: the share of all real threats found if the team reviews the top 240 alerts each day. Right: calibration error, where lower is better.

number that an LLM writes is just text, and like people, it prefers round numbers. The LLM-as-judge rating from 1 to 10, when read as a probability, has the worst calibration of all (0.102).

Examples needed. Logistic regression must first learn from about 3,000 past cases with known answers before it catches up with Jev, which needs none to start. A team with months of history already has such cases. A new team, or a completely new decision, does not.




Figure 10.3. Ranking on the live week as the trained methods see more labelled alerts, averaged over random samples. Jev and the LLMs need no labels to start, so they're flat lines. Logistic regression catches up with Jev at about 3,000 labels.

KEY IDEA

A model you train yourself needs thousands of answered examples first.

Someone has to check and mark those cases, and that takes time and money. A ready-made model can start today, without them.

Speed and price. Nothing is faster or cheaper than a rule, and simple models like logistic regression are close behind: they answer in millionths of a second on computers you already have. Jev's figures, as reported by the company, are in between: about $21 per million decisions. So Jev is cheap compared with an LLM, but not compared with a simple rule. The example LLM costs about $740 per million (a little more than in Chapter 7, because here it also writes a short answer with a confidence) and takes about 1.4 seconds per answer.




Figure 10.4. Time and cost per decision for each method, on log scales. Classic models run in millionths of a second, for fractions of a cent per million decisions (an assumption: computing cost only). The LLM figures are this book's illustrative assumptions; Jev's are vendor-reported.

KEY IDEA

If a simple rule or a simple model does the job, use it.

It is faster, cheaper and easier to explain than any large AI model.

Stability. When the same question was asked to the LLM five times, 5.2% of the answers changed at least once, and 3.2% of its answers could not be

read by the program at all. A model that always answers with a fixed set of options and probabilities cannot break like this.

The scorecard

SYNTHETIC · not measured on real Jev

	ranking (AUC)	caught at 240/day	calibration (ECE)	cost per million	time per decision	labels needed	same answer twice?	explains itself?
Rules	0.66	50%	0.009	< $1	1 µs	none	yes	fully
Logistic regression	**0.90**	**87%**	**0.008**	< $1	10 µs	~3,000	yes	weights
Text classifier	0.75	67%	0.011	$1	100 µs	15,000+	yes	word weights
LLM, JSON	0.71	60%	0.025	$740	1.4 s	none	not always	in words*
LLM-as-judge	0.75	69%	0.102	$552	583 ms	none	not always	in words*
Jev (illustrative)	0.89	86%	0.012	$21†	70–500 ms†	none‡	yes	no

Bold: best in column. † vendor-reported. ‡ none to start; about 300 to check and calibrate. Classic costs: compute only (assumption).
* reasons written after the fact, which may not be how the verdict was reached. LLM figures: illustrative.

Figure 10.5. The whole contest on one page. Bold marks the best in each numeric column. Every accuracy number is synthetic; every cost and time is an assumption, an illustration, or vendor-reported, as marked.

Read Figure 10.5 column by column, and ask which columns matter for *your* decision.

- If you have thousands of past cases with answers, clean data and a decision that does not change much: logistic regression is hard to beat.
- If every decision must be explained to an auditor: rules are the clear winner.
- If you have no past answers, only raw text, or many different decisions: a System One model is the strongest choice, after you check its numbers.
- The LLM is the weakest at deciding here, but it can do something no other method can: read anything, and *write*. Chapter 12 gives it exactly that job.

KEY IDEA

There is no best method for every decision.

Choose based on what matters for this decision: how accurate it is, how trustworthy its numbers are, how much data it needs, its cost and its speed.

⚠ WHERE THIS BREAKS

This is one decision in one imagined company, and the numbers for the LLM and Jev are only illustrations. The test week has only about four hundred real attacks, so small differences between methods may be pure chance. What you should take from this chapter is the *way* of comparing: run the same comparison on your own data, with the real models.

SET THE THRESHOLD

A new team will handle alerts about cloud storage. Nobody has checked any of these alerts before, so there are no past answers yet. The team will check and mark about 300 cases per week. Which method should they start with, and when should they reconsider?
(Start with a method that needs no past answers, such as a System One model. Use the first 300 checked cases to test and correct its numbers. After a few weeks, when more cases are checked, train a logistic regression next to it. If both agree, keep the cheaper one. If they disagree, study the cases where they disagree.)

KEEP THESE

- **A model you train yourself needs thousands of answered examples first.** Someone has to check and mark those cases, and that takes time and money. A ready-made model can start today, without them.
- **If a simple rule or a simple model does the job, use it.** It is faster, cheaper and easier to explain than any large AI model.
- **There is no best method for every decision.** Choose based on what matters for this decision: how accurate it is, how trustworthy its numbers are, how much data it needs, its cost and its speed.

EXERCISES

1. Make a scorecard for a decision in your own work. Which three columns matter most?

Next chapter: a probability is not an action. We set up three doors, act, review and escalate, with thresholds based on costs.

CHAPTER 11

Act, review, or escalate

Suppose an alert comes in at 2 a.m., and the model gives it a probability of 0.37. We already know what this number means and how to check it. But the team now has a more practical question: *what should we do with this alert?* Should we close it, keep it for the morning, or call someone immediately? This step, from a number to an action, is the least exciting part of an AI system, but it is where most of the money is saved or lost.

BY THE END OF THIS CHAPTER

- Set the act and escalate thresholds using costs.
- Fit your rules to the number of people you actually have.
- Run the system safely, with random checks, records and daily monitoring.

Why 0.5 fails

Most tutorials say: above 0.5, treat it as an attack; below 0.5, treat it as safe. Let us test this on one realistic week in our example company. About 689 alerts per day get closed automatically. That sounds great, until we see that every day about 37 of these closed alerts were real attacks, and nobody looked at them.

The 0.5 rule makes two wrong assumptions: that a missed attack and a false alarm cost the same, and that there are only two possible actions. In fact, there are three.

Three doors

Every case can leave through one of three doors:

- **Act**: the system handles it alone, and no person reads it. Most cases should go this way, because most cases are harmless.




Figure 11.1. 420 alerts from the live week, placed by how likely the (calibrated) model thinks they are to be real threats. Note the log scale: most alerts are crowded at the far left, where the model is confident they're harmless. The red crosses, real threats, are mostly to the right, but not all of them. The two lines are the thresholds this chapter arrives at, for a team of six.

- **Review**: a person checks it during normal working hours. This takes about twelve minutes of a skilled person's time.
- **Escalate**: someone is called immediately, even at 2 a.m., because it cannot wait.

The same idea works outside security. In customer support, the three doors are an automatic reply, a support agent and a supervisor. In checking social media posts, they are automatic approval, a human reviewer and the legal team.

● KEY IDEA

Every case can go through one of three doors: act, review or escalate.

The machine closes the clearly safe cases, a person checks the unclear ones, and the clearly dangerous ones wake someone up immediately.

In Figure 11.1, most harmless alerts are on the left, and most real attacks are on the right. But some attacks are scattered in the middle, and a few hide among the harmless ones. No two lines can put every alert in the right place. Our job is to make sure the mistakes we cannot avoid are the cheap ones.

Let costs decide the thresholds

Let P be the chance that an alert is a real attack. For each door, we write down what it costs on average. These are example estimates for a mid-sized company; the method matters more than the exact numbers.

- **Act.** If the alert was real, an attack got through. Expected loss about $10,000. Cost: $P \times \$10{,}000$.
- **Review.** Twelve minutes of a person's time at $75 per hour is $15. Reviewers also miss about one attack in twenty. Cost: $15, plus $P \times 5\% \times \$10{,}000$ for the attacks they miss.
- **Escalate.** Calling someone for nothing costs about $400. Cost: $(1 - P) \times \$400$.




Figure 11.2. Expected cost of each action as the probability of a real threat rises (both axes on a log scale). Acting is cheapest when P is tiny, escalating when P is large, and review wins everywhere in between. The two crossing points are the thresholds.

For each value of P, we choose the cheapest door. The two points where the lines cross in Figure 11.2 are our thresholds, and we can find them with simple arithmetic: act when P is below about 0.0016, and escalate when P is above about 0.43.

Look at the first number again. The machine may close an alert by itself only when it is *99.8% sure* the alert is harmless. This is not over-caution; it comes directly from the costs. A real attack that nobody sees costs about 630 times more than one review.

Check the probabilities first. These lines assume that P is correct. In our example, for alerts the raw model called "below 2%", it said 0.6% on average, but the real rate was 1.4%, which is 2.5 times higher. Most models are too sure of themselves when they give very small or very large numbers. Correcting the numbers with Platt scaling on past cases (Chapter 3) brings them close to the truth.

KEY IDEA

Check that the model's numbers are true before you draw any lines.

If the model says 1% when the truth is 3%, your line will quietly close real attacks without anyone noticing.

The real limit: the number of people

If we use only the cost-based thresholds, about 638 alerts per day go to review. That is a full day's work for about 16 people. But the team has only 6 people, so it can review about 240 alerts per day. The rest wait in the queue until the day ends, and are then closed without anyone looking at them.

KEY IDEA

Plan for the number of people you actually have.

If about 640 cases a day go to a team that can check 240, the other 400 are never seen, and nobody chooses which ones are skipped.

So we ask a better question: *of all the ways to place the two lines that keep the review queue within what six people can handle, which one costs the least?* With the best such lines, tested on a new week, the machine closes 432 alerts per day, people review 243, and 44 are escalated. The number of real attacks closed without anyone seeing them falls from 37 per day to about 6.1.

About six per day is still not zero. Now think like the manager who approves the budget. Figure 11.4 shows the best policy for every team size. Going from six people to eight reduces unseen attacks from 6.1 to 2.7 per day, which avoids about $34,000 of expected loss every day. The model does not make this choice. But now the choice has a clear price, instead of being a guess. The lower curve in Figure 11.4 is the same model reading clean data fields instead of the raw alert text. It shows that giving the model better input helps about as much as hiring more people.

Two more rules

What is at risk matters, not only how likely. A model can be 99% sure that an alert on the payroll server is harmless, but the remaining 1% is




Figure 11.3. Where the live week's real threats (left) and harmless alerts (right) end up each day, under one threshold at 0.5 and under the three-zone policy that respects capacity. The light, plain segment on the left (act) is the number that matters: threats closed with no person involved.




Figure 11.4. Threats auto-closed per day, for every team size from 3 to 14 analysts, with thresholds fitted again for each. The gap between the two curves is what better input is worth: the same model reading structured alert fields instead of raw alert text.

still on the payroll server. So nothing on a critical system should close automatically, however confident the model is. And any case that does not clearly belong to another door should go to a person. When in doubt, review.

Randomly check what the machine closed. Cases sent to people come back with an answer. Cases closed by the machine come back with *nothing*, so you never see the machine's own mistakes, exactly where they hurt most. So send a small random share, say 3%, of automatically closed cases to a person anyway.

● KEY IDEA

Always check a few of the cases the machine closed by itself.

Nobody looks at a closed case again, so the machine's mistakes stay hidden unless you pick some at random and check them.

Running it every day

Write down the **policy**, the rules that turn a probability into an action, with a version number, for example: "Version 3: act below 0.031, escalate above 0.34, set on 1–21 September, six people". Then it can be reviewed, and changed back if needed. Record every decision: what the model saw, what it said, and which policy turned that into an action. If the model fails or does not answer in time, send the case to review, never to automatic closing.

Then watch three numbers every day: the share of cases at each door, the review queue compared with the team's capacity, and the predicted number of attacks compared with the confirmed number. When an attack campaign starts in week five, no single alert looks unusual. But the model expected 7% of alerts to be attacks while the real figure was 12%, and the review queue overflowed (Figure 11.5). Both problems are clear on a daily chart. Then a person decides what to do: correct the model's numbers using the latest week, close fewer alerts of that type automatically for some time, or add more reviewers.




Figure 11.5. Top: the share of alerts that were real threats each day (black, solid line) against what the calibrated model expected (green, dashed line). Bottom: alerts sent to review each day against the team's capacity. In week five (shaded, between dotted lines), reality moves away from the model, and the queue overflows.

⚠ **WHERE THIS BREAKS**

The lines are set using past data, but attackers act in the future. An attacker who learns which kinds of alerts the model treats as safe will try to make the attack look exactly like those. Random checks, keeping the model's scores private, and never auto-closing critical systems make this harder, but not impossible. The cost estimates also need to be reviewed whenever the business changes, not only when the model changes.

KEEP THESE

- **Every case can go through one of three doors: act, review or escalate.** The machine closes the clearly safe cases, a person checks the unclear ones, and the clearly dangerous ones wake someone up immediately.
- **Check that the model's numbers are true before you draw any lines.** If the model says 1% when the truth is 3%, your line will quietly close real attacks without anyone noticing.
- **Plan for the number of people you actually have.** If about 640 cases a day go to a team that can check 240, the other 400 are never seen, and nobody chooses which ones are skipped.
- **Always check a few of the cases the machine closed by itself.** Nobody looks at a closed case again, so the machine's mistakes stay hidden unless you pick some at random and check them.

EXERCISES

1. Design an act/review/escalate policy for something outside security, such as refund requests or insurance claims. What does each door mean, which mistake is expensive, and what limits the review door?

Next chapter: common designs for using decision models in real systems, and an agent built from them.

CHAPTER 12

Decision patterns, and a hybrid agent

An experienced cook does not need a recipe for every dish, because most dishes use the same few steps: fry, add water, cook till thick. Software also has such common steps. We call them **patterns**: well-known solutions with a name, so that a team can simply say "put a gate before that action" and everyone understands. In this chapter we collect the patterns for using decision models, and then build an agent with them.

BY THE END OF THIS CHAPTER

- Recognise six common patterns for using decision models in real systems.
- Find a decision step that is wrong even when nothing crashes.
- Divide work correctly between a decision model and an LLM.

All six patterns in Figure 12.1 follow one rule.

● KEY IDEA

The model only answers; your own program takes the action.

The model gives an answer with a probability, and your rules decide what to do with it. So nothing happens without passing through rules you control.

Six patterns

1. Extract, then decide. The input is messy, like an email or a PDF, but the decision is small. LLMs are very good at reading messy text, but weaker at the decision itself. So we let the LLM read the text and fill in a simple form, with fields like "sender", "amount" and "deadline". Then a decision model decides using that form.




Figure 12.1. The six patterns in this chapter, as small diagrams. In every one, something else writes or acts, and a typed question decides.




Figure 12.2. Extract, then decide. The LLM reads the raw text and writes structured fields; a decision model answers a typed question about them; policy thresholds turn the answer into an action. The LLM writes but never decides; the decision model decides but never writes.

In our example, extracting first improved the ranking (AUC) from 0.708, when the LLM decided alone, to 0.865. But the company's own clean data fields did even better (0.892), because the alert text never mentions things like how important the computer is. No LLM can extract a fact that is not written. So if clean data already exists, use it.

2. The decide step. As Chapter 6 showed, most steps of an agent are small decisions. Give each of these to a decision model as a clear question, and call the LLM only when something must be written. Since every decision comes with a probability, the agent can notice when it is unsure and stop, instead of continuing confidently.

3. The safety gate. Before any risky action, such as deleting a file or sending money, ask a clear question: *is this action safe?* Answer it using only facts the attacker cannot change, such as the company's own records. A high probability allows the action, a low probability blocks it, and anything in the middle goes to a person. These are the three doors again, now for actions.




Figure 12.3. A guardrail gate. The agent proposes an action. A decision model estimates whether it's safe, from trusted facts only, never from text an attacker could write. High probability allows the action, low probability blocks it, and the middle asks a person.

4. Check the writer. Some outputs must be written, such as a report or a reply to a customer. After the LLM writes a draft, ask clear questions *about* the draft: is every statement supported by the evidence? Is the tone suitable? Then send it, return it once for correction, or give it to a person. Limit the number of corrections, or the loop may never end.

5. The router. To send each case to the right team, ask a pick-one question ("which team?"), but send it automatically only when one team is clearly the most likely. In our example, sending every alert by its top answer sent

88% to the right team. Sending automatically only when the top probability was at least 0.8 covered 80% of alerts, and 94% of those went to the right team. The rest went to a general queue for a person to sort.

6. The memory manager. Agents keep notes, like a diary, and look things up in them later. Each note and each lookup is a small decision: is this worth remembering? Where should I search? A published system called Jev-Mem uses a System One model for these small decisions and calls a slower, more careful model only to write the final answer; its authors report better and faster answers than the systems they compared it with (Jiang et al. 2026). Memory mistakes are silent: a fact that was wrongly thrown away is simply missing later, and nothing tells you so. So keep a record of what gets thrown away.

A hybrid agent

Now let us design the security agent from Chapter 6 as a **hybrid**: a decision model makes every decision, and the LLM writes only what a person will read. Every run leaves a **trace**, a step-by-step record of what the agent saw and what each decision said, with its probability. This one record helps the team find mistakes, answer questions from auditors, and explain any decision later.




Figure 12.4. The hybrid agent. A cheap lookup always runs first. Jev decides which other evidence to collect, then answers the three verdict questions together. The policy turns the verdict into an action, and the LLM writes a case note or urgent message only when a person will read it.

A mistake with no error message

Suppose we run the agent for a week. Everything looks fine: no errors, every answer is readable, and the actions are spread across all three doors. Then we do one simple check that should be done for every decision step of every agent: *count how often each answer is chosen.*




Figure 12.5. How often the first version of the agent chose each option at its "which evidence next?" step, across 700 live alerts. It never once chose threat intel.

In our example, across 700 alerts, the step "which evidence should I collect next?" *never* chose the threat-intelligence lookup, which checks the alert against lists of known dangerous websites and computers, and is the most useful information about an alert (Figure 12.5). So every verdict was made without it. The ranking quality (AUC) dropped from 0.887 to 0.723, and about 22.6 real attacks per day were closed automatically. Every answer was in a clean, correct format, so nothing in the system complained.

KEY IDEA

Count how often each answer is chosen.

In our example, the agent never once chose the most useful option, and there was no error message. Simple counting is the only way to catch such hidden mistakes.

The fix was not a better model. The threat lookup takes a fraction of a second and costs almost nothing. Deciding *whether* to do the lookup costs about the same as simply doing it. So the agent now always does the lookup. When checking something is cheaper than deciding whether to check it, just check it.

Hybrid agent against an LLM-only agent

Now compare it with an agent where the LLM makes every decision, using the same steps, tools and thresholds.




Figure 12.6. Four measures for the two agents on the same 700 live alerts, scaled to a day. The LLM's stated confidences sent far more alerts to review than the queue can take, so more real threats were never seen by a person.

In our example, the hybrid agent took 1.4 seconds per alert, while the LLM-only agent took 6.2. The bigger difference is the review queue (Figure 12.6). The LLM's written confidences are mostly a few round numbers like 0.9 and 0.95, so the lines between the doors cannot separate the cases well, and it sent about 530 alerts per day to a team that can review 240. The hybrid sent 184. When the queue is twice too long, the extra alerts are simply not seen. Adding up the attacks that were closed automatically and the attacks that waited in the queue until they were closed unseen, the hybrid missed about 10 per day, and the LLM-only agent about 19.




Figure 12.7. Share of each agent's total time spent on each kind of step. In the hybrid, the largest share is the LLM writing for people. In the all-LLM agent, most of the time goes on deciding.

Figure 12.7 shows where the time goes. The LLM-only agent spends most of its time deciding. The hybrid agent spends its biggest share on *writing* notes that people will read, which is exactly the work an LLM is best at.

● KEY IDEA

Use an LLM for reading and writing, not for deciding.

LLMs are excellent at understanding messy text and writing for people. For the decisions themselves, a decision model is faster, cheaper and more reliable.

⚠ WHERE THIS BREAKS

All numbers in this chapter are illustrative, including the timings, and part of the difference between the two agents comes from how the example was set up. Treat the speed, the queue and the design lessons as the main findings. Also, every pattern you add is one more place where something can go wrong: if an LLM first reads the text, then a safety check runs, and then a router sends the case on, a mistake can happen at any of these three steps.

● KEEP THESE

- **The model only answers; your own program takes the action.** The model gives an answer with a probability, and your rules decide what to do with it. So nothing happens without passing through rules you control.
- **Count how often each answer is chosen.** In our example, the agent never once chose the most useful option, and there was no error message. Simple counting is the only way to catch such hidden mistakes.
- **Use an LLM for reading and writing, not for deciding.** LLMs are excellent at understanding messy text and writing for people. For the decisions themselves, a decision model is faster, cheaper and more reliable.

EXERCISES

1. Design a safety gate for an email agent that can send messages to customers. What is the clear question, which facts can be trusted, and where are the thresholds?

Next chapter: one team's complete journey from start to finish, and the same design in fields far from security.

CHAPTER 13

One team, start to finish, and beyond

So far, each chapter looked at one part of the problem. In this chapter we follow the whole journey, the way a real team would: how the team worked before, how the new system was tested quietly before it was allowed to act, how it was switched on, and what happened when an attack campaign hit. Then we leave security and see the same design in other fields.

BY THE END OF THIS CHAPTER

- Test a new decision system in shadow mode before trusting it.
- See why the order of a queue matters as much as its size.
- Recognise decision layers in banking, healthcare, customer support and more.

Before: one long queue

In our example, the security team gets about 718 alerts per day and can review 240. Before the new system, alerts flagged by the senior expert's rules went to the front of one queue, and all other alerts waited in the order they arrived. Any alert not reached within a day was closed without anyone looking at it.

This is a very common way of working, and its failures stay hidden. The alerts closed at the end of the day were never opened, so nobody knows how many of them were real attacks. In our example we do know: about 27.1 real attacks per day were never seen by anyone.

Testing quietly: shadow mode

The new system uses only what we have already learned: clear questions (Chapter 8), numbers checked and corrected on past cases (Chapters 3 and




Figure 13.1. Where each day's alerts go, and where the real threats go, before and after. Before, most alerts aged out of the queue unseen, and so did a large share of real threats. After, most alerts are closed by the policy on purpose, and most real threats are queued or paged.

9), three doors with lines that fit the size of the team (Chapter 11), and an LLM that only writes notes for people (Chapter 12).

But we do not switch on such a system and simply hope. First we run it in **shadow mode**: it sees every alert and writes down what it *would* have done, while people continue working exactly as before. It is like a trainee driver with a driving instructor: the trainee says what they would do, but the instructor still drives.

● KEY IDEA

Test a new system silently before you let it act.

In shadow mode, it makes decisions but nothing actually happens, so you can compare its choices with what really happened, at no risk.

After the shadow week, the team discusses one main number: how many real attacks the system *would* have closed automatically. In our example it was about 6.1 per day. That sounds bad, until we compare it with the 27.1 per day that the old queue missed. The number was also a little higher than the team had expected from past data. The honest thing is to say this clearly in the meeting, and then watch the daily numbers to see whether it was bad luck or a real problem. The team switched the system on, with random checks of closed alerts, and a rule that any case the system fails to answer goes to a person.

The order of the queue matters

The new review queue is sorted by probability, with the most likely attacks first. If we kept the old way, in order of arrival, the typical real attack would wait about 158 minutes. Sorted by probability, it waits about 4 minutes. The people, the alerts and the queue are the same; only the order changed. The share of real attacks seen by a person within one hour went up from 37% to 83%.



Figure 13.2. How long it takes for a real threat to reach a person. Before, rule-flagged threats were seen quickly and the rest waited up to a day or were never seen. After, urgent calls reach someone in about fifteen minutes and the queue takes the likeliest threats first.

● KEY IDEA

Checking the most dangerous cases first saves a lot of time.

Just by sorting the queue by probability instead of arrival time, real attacks reached a person in minutes instead of hours, with the same team.

When an attack campaign hits

Then a phishing campaign started: attackers sent many fake emails with dangerous links at the same time. Alerts about suspicious links came three times more often than usual, and many more of them were real. On the first day, the review queue already had more alerts than the team could check. Also, the model's numbers for link alerts were now too *low*, because they had been corrected on past weeks when such alerts were mostly harmless. The daily monitoring showed both problems on day two. On day three, the team measured how common real attacks now were

among link alerts, corrected those numbers (Chapter 9), and approved overtime.




Figure 13.3. The campaign week, day by day, with and without a response on day 3. Left: alerts sent to review, against the team's capacity. Right: real threats never seen by a person, added up over the week. Recalibrating link alerts and adding overtime helped, but it didn't make the problem go away.

It helped. Over the week, real attacks never seen by anyone fell from about 144 to about 121 (Figure 13.3). But with the corrected numbers, the queue became even longer than the team could handle with overtime, because many more alerts truly needed checking.

KEY IDEA

True numbers show how much work there really is; they do not reduce it.

During an attack campaign, honest numbers showed that many more cases needed checking. Sometimes the right answer is simply more people.

The team was never the problem. With the old queue, what they checked depended on luck: whichever alert arrived first. With the new system, they check the most dangerous alerts first, by design.

Beyond security

Security was only our teaching example. The same design, a model that answers clear questions and rules that turn its answers into actions, appears in many other fields.




Figure 13.4. Six decision layers, each described the same way: what the model reads, the typed questions it answers, the option every choice must include, and who makes the final call. Green cards, which end "the model decides; people audit", let the model decide. Red cards, which end "a person decides", keep a person as the decider.

Figure 13.4 describes six examples in the same way: what the model reads, the clear questions it answers, the "none of these" option, and who makes the final decision. The biggest difference between the cards is the last one: *who decides*, the machine or a person.




Figure 13.5. The six domains placed by how many decisions a day they involve and how much one missed problem costs (illustrative). Where volume is high and each mistake is cheap, the model decides and people check samples. Where each mistake is expensive, the model orders the queue and a person makes the call.

Where decisions are many and each mistake is cheap, like checking social media posts or card payments for fraud, no team can look at everything. So the model decides, and people check a sample (Figure 13.5). Where decisions are few and each mistake is costly, like a hospital deciding which patient needs care first, the model should never close a case. Its job is to put the right patient at the top of the list, and a doctor or nurse decides.

● KEY IDEA

Let the machine decide when cases are many and mistakes are cheap; let a person decide when mistakes are costly.

Checking millions of card payments is a job for a machine; deciding about a hospital emergency is a job for a doctor.

The umbrella rule from Chapter 4 works in every field; only the costs change. A late reply to a support ticket costs a little customer goodwill, so the line may be near 5%. A missed emergency at a hospital costs far more than seeing a patient early, so the line falls to about 0.3%. A line that

low only works if the model's numbers are correct even for very small chances, below one percent.

Always test before you trust. In our example with 400 support tickets, the same model that worked well on security alerts sent only 74% of tickets to the right team. Account problems went to the right team only 54% of the time, because "I can't log in" uses similar words to "the app is not working". Sending automatically only when the top answer was above 0.6 covered 55% of tickets, with 85% correct.



Figure 13.6. Signs that a decision suits a System One model, and signs that it doesn't, or that a person must make it.

Not every problem needs a decision layer. It fits well when there are many similar cases every day, a fixed list of possible answers, a way to find out later which answer was right, and a cost you can put on each kind of mistake (Figure 13.6). It does not fit a one-time judgement, an answer that must be written out, or a problem that needs a plan rather than a verdict.

⚠ **WHERE THIS BREAKS**

All numbers here are examples, and real teams differ in many ways. Shadow mode is only as good as the outcomes you compare it with. And "a person decides" protects people only if that person has time to think. A doctor who must approve four hundred suggestions an hour is not really deciding. Watch the workload of the people in the loop as carefully as you watch the model.

KEEP THESE

- **Test a new system silently before you let it act.** In shadow mode, it makes decisions but nothing actually happens, so you can compare its choices with what really happened, at no risk.
- **Checking the most dangerous cases first saves a lot of time.** Just by sorting the queue by probability instead of arrival time, real attacks reached a person in minutes instead of hours, with the same team.
- **True numbers show how much work there really is; they do not reduce it.** During an attack campaign, honest numbers showed that many more cases needed checking. Sometimes the right answer is simply more people.
- **Let the machine decide when cases are many and mistakes are cheap; let a person decide when mistakes are costly.** Checking millions of card payments is a job for a machine; deciding about a hospital emergency is a job for a doctor.

EXERCISES

1. Choose a decision from your own work and write its card: what the model reads, the clear questions, the “none of these” option, and who decides.

Next chapter: what it takes to run a decision model as a reliable service, and what is inside a small System One model.

CHAPTER 14

From model to service

In every project there comes a day when the prototype works and someone asks: “Can we use this from Monday?” A model that makes good decisions on one person’s laptop is not yet a service that a whole company can depend on. A real service must answer at 3 a.m. even when the network is slow, explain its decisions to an auditor a year later, warn someone when the situation changes, and change safely when it is improved. This chapter explains what that needs, and then looks inside a small System One model.

BY THE END OF THIS CHAPTER

- Use a model you do not own safely: fixed versions, retries and failures.
- Make every decision explainable with a record.
- Understand what is inside a small System One model.

Using a model you do not own

Test with a practice version first. Most AI companies provide an official software library: ready-made code that your program uses to talk to their model. The library prepares each request, tries again when there is a problem, and reads the answer. Only its last step actually sends the request over the internet. If we replace that last step with a practice version that answers on our own computer, we can test all our own rules for free, and then switch to the real service by changing one setting.

Use a fixed version. AI companies update their models often, and each update can change the numbers your rules depend on.

● KEY IDEA

Always use a fixed version of the AI model.

A name like “latest” can change to a new model overnight. With a fixed version, the behaviour changes only when you decide to change it.




Figure 14.1. The official library does all the work of building requests, retrying and parsing answers. One setting decides where requests go: a practice version answers locally; the default sends them over the network to the real service.

Retry only the right errors. Your own mistakes, such as a wrong key or a wrong model name, will fail the same way every time, so fix them instead of retrying. Problems outside your control, such as a busy server or a broken connection, are worth retrying. In our example, if one request in five fails, only 79% of calls succeed with no retry, but 99.2% succeed with two retries. But each retry takes time, and a login check may have to answer within 300 milliseconds, about a third of a second, so there is no time for many retries.

Plan for failures. Sometimes the AI service will not answer at all, or will answer too late. Decide in advance what happens then, and treat it as one more kind of case. For a login, the right rule may be "allow it, but mark it for review". For closing an alert, it should be "do not close; send to a person". Write this rule in the policy, where everyone can see it.

● KEY IDEA

Decide in advance what to do when the AI does not answer.

For important actions, a failed or late answer should send the case to a person, never close it automatically.

Ask questions together. In our example, four questions about the same alert in one request used about 179 tokens, and the same four questions in four separate requests used 343, because the alert's description was sent four times. One request is also faster.

The service




Figure 14.2. The decision service. Each alert's trusted fields go to Jev as three typed questions; the answer is calibrated, and the policy, business rules and capacity turn it into a zone. Every decision is recorded before it is returned. Any failure falls back to review. A daily monitor reads the log, and a candidate version can run in shadow beside the current one.

You will recognise every part of Figure 14.2 from earlier chapters. Four habits turn these parts into a reliable service.

One settings file, with a version. The model version, the correction numbers from Chapter 3, the lines between the doors, and every business rule are kept in one file. Every decision is stamped with that file's version number.

> ● KEY IDEA
>
> **Keep all the settings in one file, with a version number.**
>
> Then, even a year later, you can explain exactly why any decision was made.

A record for every decision. A decision model gives probabilities, not reasons. But suppose we record the model's original number, the corrected number, the lines that were used, any business rule that applied, and the settings version. Then every *action* can be fully explained later, even though the model itself gives no reasons.

Thresholds and rules set together. In our example, a test run over one week showed that the review queue had more alerts than the team could check, from the very first day. The lines had been set for 240 reviews per day. But *after* that, someone added a sensible rule: never close an alert on an important system automatically. Every alert this rule sent to review





Figure 14.3. One decision record, with notes on why each field is there. Together they say what the service saw, what the model said, what the policy did, which version decided, and why.

was extra work that nobody had planned for. When the thresholds were set again *with* the rule included, the average queue went from about 275 to 245 per day. Thresholds and business rules work together, so they must be set together.



Daily monitoring, a responsible person, and shadow testing. Every day, check four numbers: how many cases went through each door, how long the review queue is compared with what the team can handle, how often calls to the AI service failed, and how many attacks the model expected compared with how many people confirmed. When an attack campaign starts, the last number shows the problem on the very first day: the model's numbers no longer match reality. A named person should have the authority to switch the service to "review everything" while the cause is found. And every improvement should first run in shadow mode

beside the current version. In our example, the new version agreed with the old one on 96% of alerts, and the shadow test showed, before anyone paid the price, how many attacks its changes would let through.




Figure 14.4. Two weeks of the daily monitor: the live week, then the phishing campaign. Top: the review queue, red and striped on days a flag was raised. Bottom: for alerts people saw, the share the model predicted to be real against the share they confirmed. The campaign opens a gap on its first day.

What is inside a small System One model

You do not need to build a System One model to use one. But it helps to understand what one looks like inside.

Imagine a small model built for alerts. It works like a doctor who examines a patient once and then fills in three different forms. One shared part, the **encoder**, reads the alert once and sums it up as a short list of numbers. Then three small parts, called **heads**, read that summary, one for each type of question (Figure 14.5). The yes/no head uses the S-curve from Chapter 2. The pick-one head gives probabilities that add up to 1. The scale head uses a single dial with marks on it, so that "high" always stays above "medium". All three heads are trained together with log loss, which rewards honest probabilities (Chapter 2), and afterwards each head's numbers are corrected with temperature scaling on cases it has never seen (Chapter 3). Such a model can be very small, about 2,091 numbers.




Figure 14.5. The three heads. A noul turns one number into P(yes) with the S-curve. A choice turns one number per label into probabilities that add up to 1. A score turns one number into probabilities for levels in order, by cutting it at points that must stay in order.




Figure 14.6. Reliability of P(attack) on the live week. Left: the small model as trained, slightly overconfident. Middle: after dividing by the fitted temperature. Right: the overtrained network before any temperature; its problems are ones no single temperature can fix.

In our example, the temperature correction reduced the error in the model's numbers (ECE) from 0.017 to 0.009, without changing the ranking. A much bigger version trained for too long was a warning: its error was 0.069, and after a temperature correction it was no better, 0.077 (Figure 14.6). Once a model has memorised its training cases, a correction afterwards cannot fully repair it. It is better to stop training at the right time.

● KEY IDEA

Train carefully, stop at the right time, then correct the numbers.

Training too long makes a model memorise and become overconfident. After training, correct its numbers on cases it has never seen.

⚠ WHERE THIS BREAKS

A real service also needs login security for its users, limits on usage, safe storage for its records, control over who can change the settings, and protection for any personal data. Shadow tests show only where two versions *disagree*; if both are wrong in the same way, only random checks will catch it. And a small model trained on one company's alerts will slowly become wrong as that company's situation changes, so it must be checked and retrained regularly.

● KEEP THESE

- **Always use a fixed version of the AI model.** A name like "latest" can change to a new model overnight. With a fixed version, the behaviour changes only when you decide to change it.
- **Decide in advance what to do when the AI does not answer.** For important actions, a failed or late answer should send the case to a person, never close it automatically.
- **Keep all the settings in one file, with a version number.** Then, even a year later, you can explain exactly why any decision was made.
- **Train carefully, stop at the right time, then correct the numbers.** Training too long makes a model memorise and become overconfident. After training, correct its numbers on cases it has never seen.

EXERCISES

1. For an online service you depend on, list three errors you would retry and three you would fix. For each decision it makes, what should a failed call mean?

Next chapter: what changes, for the industry and for you, when decisions become cheap, fast and calibrated.

CHAPTER 15

What changes now

Predictions about AI often turn out wrong, so this last chapter stays with three things: what this book has shown, what it suggests, and what nobody knows yet.

BY THE END OF THIS CHAPTER

- See the decision layer as a separate part of an AI system.
- Understand why cheaper decisions can mean more work for people.
- Leave with a clear plan for your first decision.

A separate layer for decisions

For the last few years, the usual AI system has been one big model doing everything: reading, deciding, writing and using tools, all through text.




Figure 15.1. Two ways to build an AI system. Left: one model does everything as text. Right: each layer does one job. An LLM reads and writes, a decision layer answers typed questions with probabilities, a policy turns those into actions, and tools, logs and people sit underneath.

The right side of Figure 15.1 shows the design this book has been building, chapter by chapter. The LLM does what only an LLM can do: read anything and write for people. The decision layer answers small, clear questions in one step, with probabilities we can check. The policy, your own rules, draws the lines based on the cost of mistakes and the size of the team. And at the bottom, tools take actions and people review. Each part is smaller than the whole system, can be tested on its own, and can be replaced without rebuilding everything else. So when a better LLM or a cheaper decision model appears, you can change one part and keep the rest. This is why we think the design will last.

● KEY IDEA

Give each part of the system one job.

The LLM reads and writes, the decision model decides, your rules choose the action, and people decide what mistakes cost.

Cheaper decisions, more decisions

In 1865, the economist William Stanley Jevons noticed something surprising about coal (Jevons 1865). James Watt's steam engine produced much more work from each tonne of coal. People expected Britain to use less coal. Instead, it used much more, because cheaper coal power was now used for many more things. We have seen the same with mobile data in India: when data became very cheap, people did not just save money; they started watching videos all day. This pattern is called the **Jevons paradox**. The name Jev comes from Jevons, and this time the "coal" is decisions.

A check is worth doing only when the loss it can prevent is bigger than what the check costs, and when it can be done in time. Today a company makes a few thousand careful decisions per day. But it *could* make millions: one for every email, every login and every line in its computer logs. Checking any one of these is worth only a tiny amount of money. At the example LLM price of $0.00066 per decision, almost none are worth checking. At Jev's reported price of $0.000021, many are.

Where does the bill change? For checks a company already does, cheaper decisions mean many more checks (in our example, 8 times more), but the total bill still goes *down*, because each check is so cheap. The bill goes up only when cheap decisions make *new* kinds of checks worth doing, such as checking every file that anyone shares outside the company.

KEY IDEA

When decisions become cheap, we make many more of them.

When mobile data became cheap in India, people did not save money; they used far more data. Cheap decisions will be used for many new tasks in the same way.




Figure 15.2. Alerts sent to a person per day, under two rules (illustrative). A rule that flags a fixed share of what the model looks at grows with the number of decisions, and at Jev volumes it sends far more than the team can handle. A cost-based threshold, which flags only when the expected loss is larger than the cost of a review, barely moves.

There is a hidden cost: more decisions also means more cases sent to people. Consider a rule that seemed fine when there were few decisions: "send the top 0.1% to a person". It sends 136 cases per day, which the team, able to check 240, can handle. At the new, higher volume, the same rule sends 1,185 per day, even though nobody changed it (Figure 15.2). A rule based on cost, which sends a case to a person only when the loss it may cause is higher than the cost of checking it, sends 175 per day at both volumes.

KEY IDEA

As the number of cases grows, set the line by cost, not by percentage.

"Send the top 0.1% to a person" sends more and more cases as volume grows. "Send it when the possible loss is more than the cost of checking" stays steady.

What becomes valuable

If deciding becomes cheap, what becomes rare and valuable? Good human judgement about the decision itself. Someone still has to decide what each mistake costs, where the thresholds should be, how many cases the team can review, and whether the probabilities are still correct this week. No model can do this for you. This is why the first chapters of this book, about probability, correct numbers and costs, are the foundation. They make the difference between a system that makes a million cheap decisions well and one that makes a million cheap mistakes.




Figure 15.3. Skills that matter more when decisions get cheap, and skills that matter less on their own, with the chapters that teach each.

● KEY IDEA

When machines decide cheaply, human judgement becomes more valuable.

Someone must still decide what each mistake costs, where the lines are, and how many people are needed. No model can do this for you.

Many things are still unknown: whether a System One model's numbers are correct on your data, how it changes between versions, how it behaves when attackers write the input, and what the final prices will be. None of these is a reason to wait. You can check its numbers on your own past cases this week. You can handle version changes with a fixed version and daily monitoring. You can check prices in a spreadsheet. And this design

does not depend on any one company: if your system sends a clear question, gets back a probability, and keeps its rules in your own program, you can move to a different model in a day.




Figure 15.4. Open questions, and what you can do about each today.

KEY IDEA

Build your system so that every part can be measured, adjusted and replaced.

Then you are safe even if a company changes its prices or its model, because you can switch to another one in a day.

What to do on Monday

If you do only one thing after reading this book, make a list of every decision your system makes, and count how often each one happens. Most people are surprised by how many there are, and how many are small, clear and frequent.

Then choose *one* decision. Collect a few hundred past cases with known answers and check whether the model's numbers are correct. Put a cost on each type of mistake and draw the lines. Run it in shadow mode. Switch it on with a rule for failures, random checks and daily monitoring. Then move to the next decision. This is not exciting work, but it is how every system in this book became better.




Figure 15.5. A first three months, one decision at a time.

⚠ WHERE THIS BREAKS

This chapter is the least certain part of the book. The cost and speed numbers are examples, and Jev's numbers are as reported by the company during early access. The idea that every AI system will soon have a separate decision layer is our opinion based on the evidence, not a proven fact. It could be wrong if general models become fast and well calibrated enough. Even then, everything about costs, thresholds and calibration will still apply.

SET THE THRESHOLD

Take the most frequent decision in your own system. What does a wrong "yes" cost? What does a wrong "no" cost? Where should the threshold be? And how will you know, one month from now, whether the probabilities behind it are still correct?
(There is no answer at the back of the book for this one. If you can answer all four questions, you have learned what this book set out to teach.)

Alan Turing ended his most famous paper with a line that suits this moment: "We can only see a short distance ahead, but we can see plenty there that needs to be done" (Turing 1950).




Figure 15.6. The whole book as one story.

KEEP THESE

- **Give each part of the system one job.** The LLM reads and writes, the decision model decides, your rules choose the action, and people decide what mistakes cost.
- **When decisions become cheap, we make many more of them.** When mobile data became cheap in India, people did not save money; they used far more data. Cheap decisions will be used for many new tasks in the same way.
- **As the number of cases grows, set the line by cost, not by percentage.** "Send the top 0.1% to a person" sends more and more cases as volume grows. "Send it when the possible loss is more than the cost of checking" stays steady.
- **When machines decide cheaply, human judgement becomes more valuable.** Someone must still decide what each mistake costs, where the lines are, and how many people are needed. No model can do this for you.
- **Build your system so that every part can be measured, adjusted and replaced.** Then you are safe even if a company changes its prices or its model, because you can switch to another one in a day.

EXERCISES

1. Make a decision list for one system you know: every decision, how often it happens, what a mistake costs, and who is responsible for it.

Thank you for reading.

Glossary

One plain sentence for each term, and the chapter where it's explained fully.

Act, review, escalate The three zones of a decision policy: handle it automatically, send it to a person, or raise it urgently (Chapter 11).

Agent A program that uses a model to observe, decide and act in a loop, calling tools along the way (Chapter 6).

Attention A way for each word in a sequence to look at the others and decide which ones matter for its meaning (Chapter 5).

Audit (random) Sending a random share of automatically handled cases to a person, so that mistakes the system is sure about still get seen (Chapter 11).

AUC The chance that a model gives a randomly chosen real case a higher score than a randomly chosen harmless one. It measures ranking, not calibration (Chapter 3).

Base rate How common something is before you look at any evidence, like the share of alerts that are real threats (Chapter 2).

Calibration A model is calibrated when the things it calls 70% likely happen about 70% of the time: its probabilities are honest (Chapter 3).

Capacity How many cases the people in the loop can handle in a day. A policy that ignores it isn't a policy (Chapter 11).

CISO Chief information security officer: the person in charge of an organisation's security (Chapter 7).

Choice A typed question with a set of named options. The answer is a probability for each option, adding up to 1 (Chapter 8).

Confidence In a Jev choice or score answer, a number from 0 to 1 that is high when most of the probability is on one option and low when it is spread out. It is not simply the top probability (Chapter 7).

Cost-based threshold The probability above which acting is cheaper than not acting, set by what each kind of mistake costs (Chapter 4).

Decision layer The part of a system that turns probabilities into actions: typed questions, calibration, thresholds, rules and fail-safes (Chapters 6 and 15).

Decision record The logged account of one decision: what was seen, what the model said, what the policy did, which version decided and why (Chapter 14).

Drift A change in the world, or in the data, that makes a model's probabilities less accurate than when they were checked (Chapter 11).

DLP (data loss prevention) Security tools that warn when company data may be leaving the organisation, such as a large file sent to a personal email address (Chapter 3).

ECE (expected calibration error) The average gap between what a model said and what happened, across groups of similar predictions (Chapter 3).

Embedding A list of numbers that places a word, sentence or item in a space where similar things sit close together (Chapter 5).

Epoch One full pass of training over all the training examples (Chapter 5).

Escape option The "other", "none" or "not enough information" option that gives cases fitting nowhere somewhere to go (Chapter 8).

Extract, then decide A pattern in which an LLM turns messy input into fields and a decision model decides on those fields (Chapter 12).

Fail-safe The decided meaning of a failure, such as "if the call fails, send the case to review" (Chapters 11 and 14).

Gradient descent Improving a model step by step by nudging its numbers in the direction that reduces the loss (Chapter 2).

Guardrail gate A typed check on trusted facts that runs before an agent's action is allowed to happen (Chapter 12).

Hybrid agent An agent in which a decision model answers the small decisions and an LLM only writes (Chapter 12).

Isotonic regression A calibration method that learns any increasing mapping from scores to probabilities. It's flexible, but needs more data than Platt scaling (Chapter 3).

Jevons paradox When making something more efficient to use makes people use more of it in total, not less (Chapter 15).

JSON mode An LLM setting that makes its output valid JSON, though not necessarily correct JSON (Chapter 5).

Label The known right answer for an example, used to train or test a model (Chapter 1).

LLM (large language model) A model trained to predict the next piece of text, which lets it read and write almost anything (Chapter 5).

LLM-as-judge Using an LLM to rate or check an output, often on a numbered scale (Chapter 10).

Log loss A score that punishes confident wrong answers heavily. It's a proper scoring rule (Chapter 2).

Logistic regression A model that adds up weighted evidence and passes the total through an S-curve to get a probability (Chapter 2).

Loss A number that measures how wrong a model is on some examples. Training tries to make it smaller (Chapter 2).

Noul TypeSafe's name for a yes-or-no question. The answer is the probability of yes (Chapter 8).

Observe, Decide, Act The loop an agent runs: read something, choose what to do, do it, repeat (Chapter 6).

Overconfidence Probabilities that are more extreme than the evidence justifies. It's common in large models and in overtrained small ones (Chapter 5).

Overfitting Learning the training examples so closely that performance on new examples gets worse (Chapter 2).

Platt scaling A calibration method that fits an S-curve mapping a model's scores to calibrated probabilities (Chapter 3).

Policy The rules that turn a probability into an action, usually as thresholds between zones (Chapter 11).

Prior shift A change in the base rate between where a model was calibrated and where it's used. You can correct it if you know the new base rate (Chapter 9).

Prompt injection Text planted in an input that tries to make a model follow the attacker's instructions (Chapter 6).

Proper scoring rule A way of scoring predictions under which reporting your honest probability gives the best average score (Chapter 2).

RAG (retrieval-augmented generation) Giving an LLM relevant documents, found by search, before it answers (Chapter 6).

Reliability diagram A chart of what a model said against what happened. A calibrated model sits on the diagonal (Chapter 3).

RLCD TypeSafe's name for reinforcement learning for calibrated decisions, which it says trains Jev. The details aren't published (Chapter 7).

Router A pattern that sends each case to a destination with a choice question, falling back to a person when unsure (Chapter 12).

Score A typed question with ordered levels. The answer is a probability for each level and an expected level (Chapter 8).

Shadow mode Running a new system or version beside the current one, recording what it would do without letting it act (Chapters 13 and 14).

SIEM (security information and event management) The tool that collects a company's logs and raises security alerts. Kestrel's alerts come from one (Chapter 12).

Softmax The function that turns a list of scores into probabilities that add up to 1 (Chapter 14).

State What a decision model reads: the situation, as text or structured fields (Chapter 7).

Structured output An LLM answer constrained to a schema, such as JSON with named fields (Chapter 5).

System 1, System 2 Kahneman's names for fast, automatic thinking and slow, deliberate thinking (Chapter 7).

System One model TypeSafe's term for a model that answers typed questions with probabilities in one fast pass, without writing text (Chapter 7).

Temperature (calibration) One number that softens or sharpens every probability a model gives, fitted on held-out data (Chapter 3).

Temperature (sampling) A setting that makes an LLM's choice of next token more or less random (Chapter 5).

Three-zone policy A policy with two thresholds, splitting cases into act, review and escalate (Chapter 11).

Threshold A number that splits cases into two groups, like a line on the probability scale: above it you do one thing, below it another (Chapters 1 and 4).

Token A piece of text, often part of a word, that an LLM reads and writes one at a time (Chapter 5).

Trace The step-by-step record of what an agent observed, decided and did (Chapter 12).

Transformer The network design built from attention layers that underlies modern LLMs (Chapter 5).

Triage Sorting cases by how likely they are to be real and how urgent they are, so the most important ones are handled first (Preface, Chapter 13).

Typed question A question whose answer has a fixed shape: a noul, a choice or a score (Chapter 8).

Vendor-reported A claim made by the company selling the product, not independently checked (Chapter 7).

Cheat sheets

Everything on these pages is explained fully in the chapter given in brackets. They're here for the day you need the formula and not the explanation.

Setting the threshold (Chapter 4)

For a yes-or-no decision, act when the probability of a problem is above

$$p^* = \frac{C_{\text{false alarm}}}{C_{\text{false alarm}} + C_{\text{miss}}}$$

A false alarm costing $400 and a miss costing $10,000 give $p^* = 400/10{,}400 \approx 0.04$.

Three zones (Chapter 11)

Say a review costs C_r and misses a share m of real problems. A miss costs C_{miss} and a false urgent call costs C_{page}. Then the cheapest thresholds for calibrated probabilities are

$$\text{low} = \frac{C_r}{C_{\text{miss}}\,(1-m)} \qquad \text{high} = \frac{C_{\text{page}} - C_r}{C_{\text{page}} + m\,C_{\text{miss}}}$$

Then check the queue. If the review zone holds more cases than people can clear, raise the low (act) threshold until it fits, and write down what that costs.

Measuring probabilities (Chapters 2 and 3)

For predictions p_i and outcomes $y_i \in \{0, 1\}$:

$$\text{log loss} = -\frac{1}{n}\sum_i \left[y_i \log p_i + (1 - y_i)\log(1 - p_i)\right]$$

$$\text{ECE} = \sum_b \frac{n_b}{n}\left|\,\bar{p}_b - \bar{y}_b\,\right|$$

where each bin b holds n_b predictions with average $\bar{p}_b$ and observed rate $\bar{y}_b$. AUC measures ranking only: a model can have a perfect AUC and useless probabilities.

Fixing probabilities (Chapters 3 and 9)

Method	What it fits	Use when
Temperature	$p' = \sigma(z/T)$, one number	the model is too confident (or not confident enough) everywhere
Platt scaling	$p' = \sigma(az + b)$, two numbers	a few hundred labels; the usual first fix
Isotonic	any increasing curve	thousands of labels
Prior shift	odds × $\dfrac{b'/(1-b')}{b/(1-b)}$	only the base rate changed, from b to b'

Here $z = \log \frac{p}{1-p}$ and σ is the S-curve.

Testing a model's calibration on your data (Chapter 9)

1. Collect labels for a random sample of real cases, not just the interesting ones.
2. Measure ranking (AUC) and calibration (ECE, with a bootstrap range) separately.
3. Compare the average predicted probability with the observed base rate. A big gap usually means the base rate has changed (prior shift).
4. Fix the base rate first; then use Platt scaling on a few hundred labels if needed.
5. Test again on labels you didn't fit on. Repeat on a schedule and whenever the model version changes.

Designing typed questions (Chapter 8)

- **Noul**: one fact per question; say what counts as yes and as no; no double negatives.
- **Choice**: options that don't overlap; always an escape option ("other", "none", "not enough information").
- **Score**: put thresholds on the probability of the levels you care about, not on the average level.
- Ask related questions in one call: the state is sent once.
- Decide with all the probabilities and the costs of each action, not just the top label.

Calling a decision model (Chapters 7, 8 and 14)

- Ask several typed questions about the same situation in **one call**: yes/no (noul), pick one (choice), rate on a scale (score).
- Every choice needs an escape option: "none", "other", "not enough information".

- **Pin the model version.** "latest" can change under you.
- Retry rate limits and server errors; never retry your own mistakes, fix them.
- Decide in advance what a **failed call means**; the safe default is "send to a person".
- Log the probabilities, the policy version and the request ID with every decision.

Choosing a method (Chapter 10)

If you have…	Start with
thousands of labels, clean fields, one stable decision	logistic regression
a rule an expert can write and an auditor must read	rules
no labels, raw text or many different decisions	a decision model, checked on a few hundred labels
messy input and a clear decision	an LLM to extract, a decision model to decide
output a person must read	an LLM, checked by typed questions

Before a decision service runs (Chapter 14)

A fixed model version · a config with a version number and a fingerprint · a meaning for every failure · a record for every decision · random audits of automatic actions · a daily monitor · shadow runs for new versions · an owner who can switch everything to review.

Answers to the exercises

Some exercises have one correct answer. Others ask about your own work, so here you will find a sample answer and what a good answer should include.

Chapter 1. A college portal that marks you "absent" below 75% attendance follows a fixed rule: someone wrote it, and you can read it. The bank SMS that asks "Did you make this payment?" comes from a model that learned your usual spending. A good test: if nobody can write the rule on one page, and the system keeps working when the situation changes, it probably learned from examples.

Chapter 2. Take 10,000 emails. 100 are spam, and the filter catches 98 of them. Of the 9,900 normal emails, 1% are flagged by mistake: 99 emails. So 98 + 99 = 197 emails are flagged, and 99 of them are normal. That is about **half**. A filter that sounds 98% good is wrong on every second email it flags, because spam is rare.

Chapter 3. Ranking is like putting students in order of marks: the best student should be at the top. Calibration is like a teacher who says "eight out of ten students like you will pass", and then about eight out of ten really do. A teacher can order the students perfectly and still give wrong chances, or the other way round.

Chapter 4. Threshold = false-alarm cost ÷ (false-alarm cost + miss cost) = ₹50,000 ÷ (₹50,000 + ₹50,00,000) ≈ **0.01**. Start treatment when the chance of disease is above about **1%**. Missing a sick person costs a hundred times more than treating a healthy one, so even a small chance is enough to act.

Chapter 5. First check whether the confidence can be trusted on your own data. Take a few hundred past cases with known answers. Among the cases where it said more than 0.9, how many were really correct? How many cases are there above 0.9 at all? And for the rare, costly class, what are the precision and recall? "97% accurate" can simply mean that the rare case is rare.

Chapter 6. 0.9 multiplied by itself fifteen times is about 0.21. So only about **one task in five** will finish with every step correct. This is why an agent needs a way to notice an unsure step and stop.

Chapter 7. A good answer names decisions that happen many times a day, have a few possible answers, and give quick feedback (for example: is this invoice a duplicate, which team gets this ticket). The slow decisions are

rare, new each time, or need a written plan (for example: choosing a new supplier, explaining a loss to the board).

Chapter 8. For loan applications: a yes/no question, "Does the income proof match the bank statement?"; a pick-one question, "Purpose of the loan: home / vehicle / education / business / other"; a scale question, "Repayment risk: low / medium / high". Every pick-one question needs an escape option such as "other" or "not enough information".

Chapter 9. With only 150 cases, ECE is noisy and usually too high: in Chapter 9, a model whose real ECE was 0.013 showed about 0.04 on samples of 100. So reply: "We cannot say yet." Then draw the reliability diagram with the number of cases in each group, report ECE as a range, and collect a few hundred more labelled cases. If all the errors go in one direction, check the base rate first.

Chapter 10. The best columns depend on the decision. A bank checking loan documents may care most about calibration, explaining itself, and labels needed. A support team routing tickets may care most about cost, speed and labels needed. The point is to choose the columns before looking at which method wins.

Chapter 11. For refund requests: *act* means an automatic refund for small, clear cases; *review* means a support agent checks it; *escalate* means the fraud team looks at it today. The expensive mistake is paying a large fraudulent refund; the cheaper one is making an honest customer wait. The review door is limited by how many requests the agents can check in a day.

Chapter 12. Ask a yes/no question such as "Is this reply safe to send to this customer without a person?" Take the facts from trusted systems: the customer's account, the order status, and the list of approved message types, never from the customer's own email, which anyone can write. Send automatically only when the probability is very high (for example above 0.95), block it when it is low, and send everything in between to a person. A wrong message to a customer is hard to take back, so the "send" threshold should be strict.

Chapter 13. A sample card for an insurance company's claims: the model reads the claim form and the policy; it answers "Is this a straight-through payment?" (yes/no), "Fraud risk: low / medium / high" (scale), and "Claim type: health / motor / home / not enough information" (pick one, with an escape option). Large claims are decided by a person; the model only orders the queue.

Chapter 14. Retry: a timeout, a busy server, and a "too many requests" message. Fix, never retry: a wrong API key, a model name that does not exist, and a request in the wrong format. For a payment check, a failed

call should mean “hold the payment and send it to a person”; for a low-risk task like sorting emails, it can mean “put it in the general queue”.

Chapter 15. A good list has every decision, not only the famous ones: how often each one happens per day, what each kind of mistake costs, and one named person responsible. The small, frequent decisions with a clear cost are where to start.

Bibliography

Casscells, Ward, Arno Schoenberger, and Thomas B. Graboys. 1978. 'Interpretation by Physicians of Clinical Laboratory Results'. *New England Journal of Medicine* 299 (18): 999–1001.

Chow, C. K. 1970. 'On Optimum Recognition Error and Reject Tradeoff'. *IEEE Transactions on Information Theory* 16 (1): 41–46.

Elkan, Charles. 2001. 'The Foundations of Cost-Sensitive Learning'. *Proceedings of the Seventeenth International Joint Conference on Artificial Intelligence (IJCAI)*, 973–78.

Frederick, Shane. 2005. 'Cognitive Reflection and Decision Making'. *Journal of Economic Perspectives* 19 (4): 25–42.

Gigerenzer, Gerd, and Ulrich Hoffrage. 1995. 'How to Improve Bayesian Reasoning Without Instruction: Frequency Formats'. *Psychological Review* 102 (4): 684–704.

Greshake, Kai, Sahar Abdelnabi, Shailesh Mishra, Christoph Endres, Thorsten Holz, and Mario Fritz. 2023. 'Not What You've Signed up for: Compromising Real-World LLM-Integrated Applications with Indirect Prompt Injection'. *Proceedings of the 16th ACM Workshop on Artificial Intelligence and Security*.

Guo, Chuan, Geoff Pleiss, Yu Sun, and Kilian Q. Weinberger. 2017. 'On Calibration of Modern Neural Networks'. *Proceedings of the 34th International Conference on Machine Learning (ICML)*.

Jevons, William Stanley. 1865. *The Coal Question: An Inquiry Concerning the Progress of the Nation, and the Probable Exhaustion of Our Coal-Mines*. Macmillan.

Jiang, Dongming, Yi Li, and Bingzhe Li. 2026. *Jev-Mem: System-One-Controlled Agentic Memory for Efficient AI Agents*. arXiv:2609.23986. Accessed 29 September 2026. https://arxiv.org/abs/2609.23986.

Kahneman, Daniel. 2011. *Thinking, Fast and Slow*. Farrar, Straus and Giroux.

Kahneman, Daniel, and Gary Klein. 2009. 'Conditions for Intuitive Expertise: A Failure to Disagree'. *American Psychologist* 64 (6): 515–26.

Kaplan, Jared, Sam McCandlish, Tom Henighan, et al. 2020. *Scaling Laws for Neural Language Models*. https://arxiv.org/abs/2001.08361.

LeCun, Yann, Yoshua Bengio, and Geoffrey Hinton. 2015. 'Deep Learning'. *Nature* 521: 436–44.

Lewis, Patrick, Ethan Perez, Aleksandra Piktus, et al. 2020. 'Retrieval-Augmented Generation for Knowledge-Intensive NLP Tasks'. *Advances in Neural Information Processing Systems 33 (NeurIPS)*.

Molas, Alex. 2026. *Jev Can't Be Calibrated*. Blog post, 23 September 2026. Accessed 29 September 2026. https://www.alexmolas.com/2026/09/23/jev-cant-be-calibrated.html.

Murphy, Allan H., and Robert L. Winkler. 1977. 'Reliability of Subjective Probability Forecasts of Precipitation and Temperature'. *Journal of the Royal Statistical Society, Series C (Applied Statistics)* 26 (1): 41–47.

Naeini, Mahdi Pakdaman, Gregory F. Cooper, and Milos Hauskrecht. 2015. 'Obtaining Well Calibrated Probabilities Using Bayesian Binning'. *Proceedings of the AAAI Conference on Artificial Intelligence*.

OpenAI. 2023. *GPT-4 Technical Report*. https://arxiv.org/abs/2303.08774.

Ouyang, Long, Jeff Wu, Xu Jiang, et al. 2022. 'Training Language Models to Follow Instructions with Human Feedback'. *Advances in Neural Information Processing Systems 35 (NeurIPS)*.

Platt, John C. 1999. 'Probabilistic Outputs for Support Vector Machines and Comparisons to Regularized Likelihood Methods'. In *Advances in Large Margin Classifiers*. MIT Press.

regolo.ai. 2026. *Jev and System One Models: Benchmarks, Open-Source Alternatives, and When to Use Them*. Blog post. Accessed 29 September 2026. https://regolo.ai/jev-and-system-one-models-benchmarks-open-source-alternatives-and-when-to-use-them/.

Rumelhart, David E., Geoffrey E. Hinton, and Ronald J. Williams. 1986. 'Learning Representations by Back-Propagating Errors'. *Nature* 323: 533–36.

Saerens, Marco, Patrice Latinne, and Christine Decaestecker. 2002. 'Adjusting the Outputs of a Classifier to New a Priori Probabilities: A Simple Procedure'. *Neural Computation* 14 (1): 21–41.

Turing, Alan M. 1950. 'Computing Machinery and Intelligence'. *Mind* 59 (236): 433–60.

TypeSafe AI. 2026. *Introducing System One Models & Jev*. TypeSafe AI blog. Accessed 29 September 2026. https://typesafe.ai/blog/introducing-system-one-models-and-jev.

Vaswani, Ashish, Noam Shazeer, Niki Parmar, et al. 2017. 'Attention Is All You Need'. *Advances in Neural Information Processing Systems 30 (NeurIPS)*.

Yao, Shunyu, Jeffrey Zhao, Dian Yu, et al. 2023. 'ReAct: Synergizing Reasoning and Acting in Language Models'. *International Conference on Learning Representations (ICLR)*.

Zadrozny, Bianca, and Charles Elkan. 2002. 'Transforming Classifier Scores into Accurate Multiclass Probability Estimates'. *Proceedings of the Eighth ACM SIGKDD International Conference on Knowledge Discovery and Data Mining*, 694–99.

Index

A
Act, review, escalate, 69, 70
Agent, 36, 42, 77, 83
Attention, 29, 31
AUC, 17

B
Bake-off, 62
Base rate, 9, 15
Bayes' rule, 11, 57

C
Calibration, 16, 22, 56, 61
Capacity, 73, 74
Choice (question type), 50, 54
Cost-based threshold, 27

D
Decision layer, 40, 84, 100
Decision record, 95
Doom demo, 48
Drift, 74

E
ECE (expected calibration error), 18, 21
Embedding, 29, 30
Extract, then decide, 77, 78

G
Gradient descent, 13
Guardrail gate, 79

H
Harbor Pharma, 57
Hybrid agent, 80, 82

I
Isotonic regression, 20, 21

J
Jev-Mem, 80
Jevons paradox, 101
Jevons, William Stanley, 101
JSON mode, 33

K
Kahneman, Daniel, 6, 43

L
LLM (large language model), 29, 34
LLM-as-judge, 63
Log loss, 13
Logistic regression, 13
Loss, 13, 15

M
Molas, Alex, 56

N
Noul, 50, 51

O
Overconfidence, 29, 34
Overfitting, 14

P
Phishing campaign, 74, 84, 95
Platt scaling, 20
Policy, 73, 76
Prompt injection, 39

R
RAG (retrieval-augmented generation), 36
Reliability diagram, 18, 19
RLCD, 46
Router, 79, 83

S
Score (question type), 50, 52
Shadow mode, 84, 90, 94, 98
State, 46
System 1, System 2, 43, 49
System One model, 43, 48

T
Temperature (calibration), 20
Threat intel, 81
Three-zone policy, 73
Threshold, 3, 23, 28
Token, 32, 34

Trace, 80
Transformer, 31
TypeSafe AI, 6, 43, 51, 56

About the Author

Sridhar Mukkandi is an applied AI engineer who builds agents and the decision systems behind them. He writes for engineers who want AI systems they can trust.

sridhar.authorhub@gmail.com