

[mock] 2023-03-28 Final Exam

5072DASC6Y Data Science 23/24 (2.1) · 7 exercises · 25.0 points

General Data Science Questions

2.0 points · 2 questions

1 Which of the following is a commonly used loss function for regression?

1.0 point · Multiple choice · 4 alternatives

- | | |
|---|-----|
| <input checked="" type="radio"/> Squared error loss | 1.0 |
| <input type="radio"/> Logistic loss | 0.0 |
| <input type="radio"/> Perceptron loss | 0.0 |
| <input type="radio"/> Cross-entropy loss | 0.0 |

Feedback

Feedback when the question is answered correctly

Feedback when the question is answered partially correctly

Feedback when the question is answered incorrectly

2 Which of the following best describes the purpose of data augmentation?

1.0 point · Multiple choice · 4 alternatives

- | | |
|--|-----|
| <input type="radio"/> To reduce the model training time | 0.0 |
| <input checked="" type="radio"/> To combat overfitting by increasing dataset diversity | 1.0 |
| <input type="radio"/> To reduce the size of input (e.g., images) | 0.0 |
| <input type="radio"/> To perform feature selection | 0.0 |

Feedback

Feedback when the question is answered correctly

Feedback when the question is answered partially correctly

Feedback when the question is answered incorrectly

Structured Data Processing Questions

4.0 points · 4 questions

3 Suppose we flipped a coin 100 times, and we got 50 heads and 50 tails. What is the entropy of the result in this coin-flipping experiment?

1.0 point · Multiple choice · 4 alternatives

- | | |
|------------------------------------|-----|
| <input checked="" type="radio"/> 1 | 1.0 |
| <input type="radio"/> 0 | 0.0 |
| <input type="radio"/> 0.5 | 0.0 |
| <input type="radio"/> 0.25 | 0.0 |

Feedback

Feedback when the question is answered correctly

Feedback when the question is answered partially correctly

Feedback when the question is answered incorrectly

4 Which of the following statements about the Decision Tree model is **TRUE**? Notice that we refer to the general Decision Tree, not a specific implementation.

1.0 point · Multiple choice · 4 alternatives

- | | |
|--|-----|
| <input type="radio"/> Decision Tree can be trained well without problems using the misclassification error as the node-splitting strategy. | 0.0 |
| <input type="radio"/> Decision Tree cannot handle continuous features. | 0.0 |
| <input checked="" type="radio"/> When splitting nodes, Decision Tree can use the same feature multiple times. | 1.0 |
| <input type="radio"/> Decision Tree can only be used for the classification task. | 0.0 |

Feedback

Feedback when the question is answered correctly

Feedback when the question is answered partially correctly

Feedback when the question is answered incorrectly

5 Suppose that we fit a binary classification model in identifying spam and ham (i.e., non-spam). Spam is the positive label, and ham is the negative label. The following shows the evaluation result of the model. What is the f-score of the model based on the evaluation result?

- 30 samples are predicted as spam, and they are indeed spam in reality
- 20 samples are predicted as spam, but it turns out that they are not spam in reality
- 70 samples are predicted as ham, but it turns out that they are spam in reality
- 80 samples are predicted as ham, and they are indeed ham in reality

1.0 point · Multiple choice · 4 alternatives

- | | |
|--------------------------------------|-----|
| <input type="radio"/> 0.55 | 0.0 |
| <input type="radio"/> 0.3 | 0.0 |
| <input type="radio"/> 0.6 | 0.0 |
| <input checked="" type="radio"/> 0.4 | 1.0 |

Feedback

Feedback when the question is answered correctly

Feedback when the question is answered partially correctly

Feedback when the question is answered incorrectly

6 Suppose that we are performing a prediction task using artificial neurons. Which of the following statements about artificial neurons is **TRUE**?

1.0 point · Multiple choice · 4 alternatives

- | | |
|--|-----|
| <input type="radio"/> The perceptron classifier uses the identity activation function with the hinge loss function. | 0.0 |
| <input type="radio"/> Support Vector Machine uses the sigmoid activation function with the perceptron loss function. | 0.0 |
| <input checked="" type="radio"/> Linear regression uses the identity activation function with the squared error loss function. | 1.0 |
| <input type="radio"/> Logistic regression uses the identity activation function with the binary cross entropy loss function. | 0.0 |

Feedback

Feedback when the question is answered correctly

Feedback when the question is answered partially correctly

Feedback when the question is answered incorrectly

Text Data Processing Questions

5.0 points · 5 questions

7 Which of the following about word embeddings in natural language processing is **TRUE**?

1.0 point · Multiple choice · 4 alternatives

- ☐ Word embeddings can only be learned using supervised methods, which means we need labels for the sentences in the training data. 0.0
- ☐ Word embeddings require manual feature engineering to capture the meaning of words effectively. 0.0
- ☐ Word embeddings typically represent each word as one integer value to capture semantic relationships between words. 0.0
- ☒ Word embeddings can be trained by iteratively using one word in a sentence to predict nearby words as accurately as possible. 1.0

Feedback

Feedback when the question is answered correctly

Feedback when the question is answered partially correctly

Feedback when the question is answered incorrectly

8 Which of the following about text processing is **TRUE**?

1.0 point · Multiple choice · 4 alternatives

- ☒ POS tagging labels the role of each word in a particular part of speech, such as verb. 1.0
- ☐ Stemming can correctly identify the original form of each word. 0.0
- ☐ Lemmatization simply chops word tails to obtain the word's base form. 0.0
- ☐ Tokenization represents each word as a data point in a high-dimensional space. 0.0

Feedback

Feedback when the question is answered correctly

Feedback when the question is answered partially correctly

Feedback when the question is answered incorrectly

9 What is the primary goal of using dot product in the context of word embeddings?

1.0 point · Multiple choice · 4 alternatives

- ☒ To measure the similarity between two words. 1.0
- ☐ To predict the probability of a word belonging to a certain topic. 0.0
- ☐ To normalize word vectors so that the output is a probability distribution. 0.0
- ☐ To find the frequency of words in a text document. 0.0

Feedback

Feedback when the question is answered correctly

Feedback when the question is answered partially correctly

Feedback when the question is answered incorrectly

10 What is the output of topic modeling using Latent Dirichlet Allocation?

1.0 point · Multiple choice · 4 alternatives

- ☐ A set of word vectors, where each word is represented as a data point in a high-dimensional space. 0.0
- ☐ A set of document vectors, where each document is represented as a bag-of-words vector. 0.0
- ☒ A set of topic vectors, where each vector is represented as a probability distribution over the words in the text corpus. 1.0
- ☐ A set of clusters, where each cluster represents a group of similar documents. 0.0

Feedback

Feedback when the question is answered correctly

Feedback when the question is answered partially correctly

Feedback when the question is answered incorrectly

11 Which of the following about TF-IDF (term frequency-inverse document frequency) is **TRUE**?

1.0 point · Multiple choice · 4 alternatives

- ☐ IDF weights each word by considering how frequently it shows in different documents. IDF is lower when the word appears in fewer documents. 0.0
- ☒ TF-IDF can be seen as a weighted Bag of Words approach, which means TF-IDF weights the term frequency based on the inverse document frequency. 1.0
- ☐ The goal of using TF-IDF is to transform each word into a vector so that we can use the vector for further tasks, such as classification. 0.0
- ☐ If a word appears in only a few documents (and frequently in these documents), TF-IDF can show that the word contains less information and should be less important. 0.0

Feedback

Feedback when the question is answered correctly

Feedback when the question is answered partially correctly

Feedback when the question is answered incorrectly

Image Data Processing Questions

5.0 points · 5 questions

12 Given an image, which of the following kernels will blur the image after performing the typical convolution operation (no padding, stride 1) using the kernel? Assume that numpy is imported.

1.0 point · Multiple choice · 4 alternatives

- ☐ `numpy.array([[0, 0, 0],[0, 2, 0],[0, 0, 0]])` 0.0
- ☐ `numpy.array([[1, 0, -1],[2, 0, -2],[1, 0, -1]])` 0.0
- ☒ `numpy.array([[0.11, 0.11, 0.11],[0.11, 0.11, 0.11],[0.11, 0.11, 0.11]])` 1.0
- ☐ `numpy.array([[0, 0, 0],[1, 0, 0],[0, 0, 0]])` 0.0

Feedback

Feedback when the question is answered correctly

Feedback when the question is answered partially correctly

Feedback when the question is answered incorrectly

13 Which of the following about Convolutional Neural Network (CNNs) is **TRUE**?

1.0 point · Multiple choice · 4 alternatives

- ☐ The number of trainable parameters in the convolution layers is roughly the same as the parameters in the fully connected layers. 0.0
- ☐ The activation functions in CNNs are used to reduce the dimensions of the features. 0.0
- ☐ The max pooling layer is used to help the network pay attention to the most important information, and there are trainable parameters. 0.0
- ☒ The normalization layer acts as regularization during training and can make deep neural networks much easier to train. 1.0

Feedback

Feedback when the question is answered correctly

Feedback when the question is answered partially correctly

Feedback when the question is answered incorrectly

14 You are training a deep neural network for image classification. Which of the following is likely to happen if you initialize all the weights (i.e., the model parameters) in the network to zero? And what is the most likely reason for this to happen?

1.0 point · Multiple choice · 4 alternatives

- ☐ The loss and model performance metrics converge quickly, as the weights are not too far from their optimal values. 0.0
- ☒ The loss and model performance metrics almost do not change. This is because the neurons learn the same features, and the network cannot tell the difference between different inputs. 1.0
- ☐ The loss and model performance metrics are good in both the training and validation set. This is because weights are initialized to the same value and do not have any biases during model training. 0.0
- ☐ The loss and model performance metrics are decreasing slowly. This is because initializing the weights to a constant number makes the gradient smaller. 0.0

Feedback

Feedback when the question is answered correctly

Feedback when the question is answered partially correctly

Feedback when the question is answered incorrectly

15 You are training a deep feedforward neural network for classifying images with clothes using a dataset with 10 classes. Your network structure has four hidden layers with sizes 512, 256, 256, and 128, respectively. The outputs from every hidden layer are passed to sigmoid activation functions. You use a learning rate 0.01 with the stochastic gradient descent optimizer. After trying hard to get the best possible performance, you found that the network can achieve only about 10% accuracy on the training and test set. Which of the following best describes what happened in this situation, and also what action to take?

1.0 point · Multiple choice · 4 alternatives

- ☐ The network is too shallow to capture the complexity of the image classification task. Increasing the depth of the network would likely lead to better performance. 0.0
- ☒ The sigmoid activation function saturates when the input is large or small, causing the gradients to vanish. We can change the activation function to leaky ReLU. 1.0
- ☐ The network underfits the training data. Use regularization techniques such as dropout or data augmentation will improve generalization performance. 0.0
- ☐ The learning rate is too high, causing the network training process to be unstable. Decreasing the learning rate after some epochs may fix the problem. 0.0

Feedback

Feedback when the question is answered correctly

Feedback when the question is answered partially correctly

Feedback when the question is answered incorrectly

16 Given an input RGB image (3 channels) of size 33 by 33, a convolutional layer with 6 image filters (each filter has size 5 by 5), a stride of 2, and padding of 1. What is the dimensionality of the output of the layer? The following options are in the format of width x height x channel.

1.0 point · Multiple choice · 4 alternatives

- ☒ 16 x 16 x 6 1.0
- ☐ 16 x 16 x 3 0.0
- ☐ 32 x 32 x 6 0.0
- ☐ 32 x 32 x 3 0.0

Feedback

Feedback when the question is answered correctly

Feedback when the question is answered partially correctly

Feedback when the question is answered incorrectly

Deep Learning Questions

5.0 points · 5 questions

17 Which of the following about Recurrent Neural Networks (RNNs) is **TRUE**?

1.0 point · Multiple choice · 4 alternatives

- ☐ RNNs are mainly designed to handle image data. 0.0
- ☐ We can create an encoder-decoder structure using RNNs, and using the final encoder output is easy for the model to remember information from a long time ago. 0.0
- ☐ RNNs cannot handle sequences longer than a fixed number of time steps. 0.0
- ☒ RNNs contain hidden layers that can capture information from previous time steps. 1.0

Feedback

Feedback when the question is answered correctly

Feedback when the question is answered partially correctly

Feedback when the question is answered incorrectly

18 Which of the following about the PyTorch deep learning framework is **TRUE**?

1.0 point · Multiple choice · 4 alternatives

- ☐ PyTorch sets the gradients of all parameters to zero after each backpropagation step, which prevents the new gradients from being added to the previous ones. Users do not need to handle this by themselves. 0.0
- ☒ PyTorch can automatically compute gradients for tensors, which enables users to easily implement backpropagation and other optimization algorithms. 1.0
- ☐ PyTorch automatically uses GPU (Graphics Processing Unit) by default if the machine has GPUs, which means that users do not need to specify the device to use. 0.0
- ☐ PyTorch has no objects or functions to support automatic batching, data shuffling, or multi-process data loading. Users need to handle these by themselves. 0.0

Feedback

Feedback when the question is answered correctly

Feedback when the question is answered partially correctly

Feedback when the question is answered incorrectly

19 Suppose we have a deep feedforward neural network with two layers. The first layer has four artificial neurons, and the second layer has one neuron. We want to use the network to perform binary classification on the data that is not linearly separable. This means that the dataset cannot be separated with a reasonable performance by just using a linear classifier. Which of the following settings can help us achieve our task well?

1.0 point · Multiple choice · 4 alternatives

- ☐ Use the identity activation function for all neurons and use the cross-entropy loss 0.0
- ☐ Use the tanh activation function for all neurons and use the squared error loss 0.0
- ☒ Use the tanh activation function for all neurons and use the cross-entropy loss 1.0
- ☐ Use the identity activation function for all neurons and use the squared error loss 0.0

Feedback

Feedback when the question is answered correctly

Feedback when the question is answered partially correctly

Feedback when the question is answered incorrectly

20 Which of the following best describes the goal of using a softmax activation function?

1.0 point · Multiple choice · 4 alternatives

- ☐ To ensure that the output is always between -1 and 1. 0.0
- ☐ To produce a binary output. 0.0
- ☐ To ensure that the gradients cannot be negative and the model converges faster. 0.0
- ☒ To map arbitrary input values to a probability distribution output. 1.0

Feedback

Feedback when the question is answered correctly

Feedback when the question is answered partially correctly

Feedback when the question is answered incorrectly

21 Which of the following is the order that best describes the attention mechanism?

- A: Compute the attention distribution using softmax
- B: Compute attention-weighted sum of encoder output
- C: Get the encoder output values (from the RNN)
- D: Compute attention scores (dot product similarity)
- E: Transform encoder outputs (dimension reduction)

1.0 point · Multiple choice · 4 alternatives

- | | |
|--|-----|
| <input checked="" type="radio"/> CEDAB | 1.0 |
| <input type="radio"/> ECDBA | 0.0 |
| <input type="radio"/> CABDE | 0.0 |
| <input type="radio"/> CBDAE | 0.0 |

Feedback

Feedback when the question is answered correctly

Feedback when the question is answered partially correctly

Feedback when the question is answered incorrectly

Coding Questions

4.0 points · 4 questions

22 Given a 2-dimensional numpy array A with integers or floats. All values in the array are different. Assume that numpy is imported. What is the following code doing?

■ `numpy.argmax(A, axis=1)`

1.0 point · Multiple choice · 4 alternatives

- ☐ Return an array containing the indices of the minimum value in each row of array A. 0.0
- ☐ Return an array containing the minimum value in each column of array A. 0.0
- ☐ Return an array containing the maximum value in each column of array A. 0.0
- ☒ Return an array containing the indices of the maximum value in each row of array A. 1.0

Feedback

Feedback when the question is answered correctly

Feedback when the question is answered partially correctly

Feedback when the question is answered incorrectly

23 Given a pandas series object *S* with integers or floats. The index of each row means the time steps. What is the following code doing?

■ `S.rolling(3, min_periods=1, closed="right").sum()`

1.0 point · Multiple choice · 4 alternatives

- ☐ For each row in series *S*, compute the difference between each value and the average of the previous two values from the two preceding time steps. 0.0
- ☒ For each row in series *S*, compute the sum of the current value and the previous two values from the two preceding time steps. Then, store the sum in the current row. 1.0
- ☐ Compute the cumulative sum of series *S*, where the value in each row is the sum of all values up to and including that value. 0.0
- ☐ Replace each value in series *S* with the sum of the current value and the maximum value in a window of size 3. The window is moved one position ahead at a time. 0.0

Feedback

Feedback when the question is answered correctly

Feedback when the question is answered partially correctly

Feedback when the question is answered incorrectly

24 You are preprocessing text data for a document classification task. Given a pandas dataframe object D with two columns “c” and “t”. Each row means a document. The “c” column contains information about the class that the document belongs to, such as “Business”. The “t” column contains a list of tokens, such as ['Wall, St.', 'Bears', 'Claw', 'Back', 'Into']. What is the following code doing?

- `D.explode("t").groupby(["c", "t"]).size().reset_index(name="n").sort_values(["c", "n"], ascending=[True, False]).groupby("c").head(5)`

1.0 point · Multiple choice · 4 alternatives

- ☒ Return a new dataframe with a new column that shows the 5 most used words per class, and their frequency. 1.0
- ☐ Return a new dataframe with a new column that shows the 5 least used words per class, and their frequency. 0.0
- ☐ Remove rows with duplicate tokens in the “t” column. Return a new dataframe with a new column that counts the frequency of each token among all documents per class. 0.0
- ☐ Compute the average frequency of each token in each document per class. Return a new dataframe with a new column that shows the 5 tokens with the highest average frequency. 0.0

Feedback

Feedback when the question is answered correctly

Feedback when the question is answered partially correctly

Feedback when the question is answered incorrectly

25 Given a pandas dataframe object D, where column “w” in each row contains a list of words, such as ['Wall, St.', 'Bears', 'Claw', 'Back', 'Into']. What is the following code doing? Variable “S” in the code below contains a list of words, such as ['the', 'of', 'a', 'on'].

■ `D["w"].apply(lambda x: [word for word in x if word.lower() not in S])`

1.0 point · Multiple choice · 4 alternatives

- ☐ Select only the rows in the dataframe where the word list in the “w” column contains any word in list S. 0.0
- ☐ For each word list in each row in the “w” column of the dataframe, add words that are in list S. 0.0
- ☒ For each word list in each row in the “w” column of the dataframe, remove words that are in list S. 1.0
- ☐ Count the frequency of each word in the “w” column of the dataframe, and then return the words that occur less frequently than a threshold defined in list S. 0.0

Feedback

Feedback when the question is answered correctly

Feedback when the question is answered partially correctly

Feedback when the question is answered incorrectly