

A general approach to backtracking questions in Java (Subsets, Permutations, Combination Sum, Palin



This structure might apply to many other backtracking questions, but here I am just going to demonstrate Subsets, Permutations, and Combination Sum.

Subsets: https://leetcode.com/problems/subsets/ (https://leetcode.com/problems/subsets/)

```
public List<List<Integer>> subsets(int[] nums) {
    List<List<Integer>> list = new ArrayList<>();
    Arrays.sort(nums);
    backtrack(list, new ArrayList<>(), nums, 0);
    return list;
}

private void backtrack(List<List<Integer>> list , List<Integer> tempList, int [] nums, int start){
    list.add(new ArrayList<>(tempList));
    for(int i = start; i < nums.length; i++){
        tempList.add(nums[i]);
        backtrack(list, tempList, nums, i + 1);
        tempList.remove(tempList.size() - 1);
    }
}</pre>
```

```
Subscribe
                                                                                                   ▲ Report
public List<List<Integer>> subsetsWithDup(int[] nums) {
    List<List<Integer>> list = new ArrayList<>();
    Arrays.sort(nums);
    backtrack(list, new ArrayList<>(), nums, 0);
    return list;
}
private void backtrack(List<List<Integer>> list, List<Integer> templist, int [] nums, int start){
    list.add(new ArrayList<>(tempList));
    for(int i = start; i < nums.length; i++){</pre>
        if(i > start && nums[i] == nums[i-1]) continue; // skip duplicates
        tempList.add(nums[i]);
        backtrack(list, tempList, nums, i + 1);
        tempList.remove(tempList.size() - 1);
    }
}
```

```
public List<List<Integer>> permute(int[] nums) {
    List<List<Integer>> list = new ArrayList<>();
    // Arrays.sort(nums); // not necessary
    backtrack(list, new ArrayList<>(), nums);
    return list;
 }
 private void backtrack(List<List<Integer>> list, List<Integer> tempList, int [] nums){
    if(tempList.size() == nums.length){
       list.add(new ArrayList<>(tempList));
    } else{
       for(int i = 0; i < nums.length; i++){</pre>
          if(tempList.contains(nums[i])) continue; // element already exists, skip
          tempList.add(nums[i]);
          backtrack(list, tempList, nums);
          tempList.remove(tempList.size() - 1);
       }
    }
 }
Permutations II (contains duplicates): https://leetcode.com/problems/permutations-ii/ (https://leetcode.com/problems/permutations-ii/)
 public List<List<Integer>> permuteUnique(int[] nums) {
     List<List<Integer>> list = new ArrayList<>();
     Arrays.sort(nums);
     backtrack(list, new ArrayList<>(), nums, new boolean[nums.length]);
     return list;
 }
 private void backtrack(List<Integer>> list, List<Integer> tempList, int [] nums, boolean [] used){
     if(tempList.size() == nums.length){
         list.add(new ArrayList<>(tempList));
     } else{
         for(int i = 0; i < nums.length; i++){</pre>
             if(used[i] || i > 0 && nums[i] == nums[i-1] && !used[i - 1]) continue;
             used[i] = true;
             tempList.add(nums[i]);
             backtrack(list, tempList, nums, used);
             used[i] = false;
             tempList.remove(tempList.size() - 1);
         }
     }
 }
Combination Sum: https://leetcode.com/problems/combination-sum/ (https://leetcode.com/problems/combination-sum/)
 public List<List<Integer>> combinationSum(int[] nums, int target) {
```

```
List<List<Integer>> list = new ArrayList<>();
    Arrays.sort(nums);
    backtrack(list, new ArrayList<>(), nums, target, 0);
    return list;
}
private void backtrack(List<List<Integer>> list, List<Integer> tempList, int [] nums, int remain, int start){
    if(remain < 0) return;</pre>
    else if(remain == 0) list.add(new ArrayList<>(tempList));
    else{
        for(int i = start; i < nums.length; i++){</pre>
            tempList.add(nums[i]);
            backtrack(list, tempList, nums, remain - nums[i], i); // not i + 1 because we can reuse same elements
            tempList.remove(tempList.size() - 1);
        }
   }
}
```

Combination Sum II (can't reuse same element): https://leetcode.com/problems/combination-sum-ii/ (https://leetcode.com/problems/combination-sum-ii/)

```
public List<List<Integer>> combinationSum2(int[] nums, int target) {
    List<List<Integer>> list = new ArrayList<>();
    Arrays.sort(nums);
    backtrack(list, new ArrayList<>(), nums, target, 0);
    return list;
}
private void backtrack(List<List<Integer>> list, List<Integer> tempList, int [] nums, int remain, int start){
    if(remain < 0) return;</pre>
    else if(remain == 0) list.add(new ArrayList<>(tempList));
    else{
        for(int i = start; i < nums.length; i++){</pre>
            if(i > start && nums[i] == nums[i-1]) continue; // skip duplicates
            tempList.add(nums[i]);
            backtrack(list, tempList, nums, remain - nums[i], i + 1);
            tempList.remove(tempList.size() - 1);
        }
    }
}
```

Palindrome Partitioning: https://leetcode.com/problems/palindrome-partitioning/ (https://leetcode.com/problems/palindrome-partitioning/)

```
public List<List<String>> partition(String s) {
   List<List<String>> list = new ArrayList<>();
   backtrack(list, new ArrayList<>(), s, 0);
   return list;
}
public void backtrack(List<List<String>> list, List<String> tempList, String s, int start){
   if(start == s.length())
      list.add(new ArrayList<>(tempList));
   else{
      for(int i = start; i < s.length(); i++){</pre>
         if(isPalindrome(s, start, i)){
            tempList.add(s.substring(start, i + 1));
            backtrack(list, tempList, s, i + 1);
            tempList.remove(tempList.size() - 1);
         }
      }
   }
}
public boolean isPalindrome(String s, int low, int high){
   while(low < high)</pre>
      if(s.charAt(low++) != s.charAt(high--)) return false;
   return true;
}
```