MJCET

Project: Take-Out Robot

Assembly No: TR-SA3

Assembly: Y-AXIS

Lastest Update on: 25-03-2022

Item No	Part Name	Order Code/Drawing Number	Description	Material Standard	Size	Weight (kg)	Qty/Set	Manufacturer/ Vendor	Manufacturer Part No	Notes
3.1	3.1_Y Beam Channel		Y- Axis Beam	Aluminium Alloy(AL 6063 T6)	1750mm	19	1	Sica	PG 80160 H	
3.2	2.18 X Stopper	TR-SA2-010	Stopper	MS	As per Drawing	0.04	4			
3.3	3.16 Y-Proximity Sensor Holder	TR-SA3-09	Y PS Holder	SS 304	As per Drawing	0.13	2			
3.4	E2A_M18KS08_WP_BASE		Proximity sensor				2			
3.5	E2A_M18KS08_WP_NUT		Proximity Sensor Nuts				4	Omron	E2A-M18KS08-WP-B1-2M	
3.6	2.3_X-Guide Block		Guide Block			2.4	2	Hiwin	RGH20CAZ0H	
3.7	3.3_Y-Guide Rail_RGR20R1750H		Guide Rail		Length: 2700	28	2	Hiwin	RGR20R2700H	
3.8	ISO 4762 M5 x 20 - 20N		Allen Nuts & Bolts	SS 302	M5 20mm		52			
3.9	ISO 4762 M5 x 35 - 22N		Allen Nuts & Bolts	SS 302	M5 35mm		8			
3.1O	ISO 10669-5.4-N		Washers	SS 302			4			
3.11	ISO 4762 M5 x 12 - 12N		Allen Nuts & Bolts	SS 302	M5 12mm		4			
3.12	TR-SA3-01	TR-SA3-01	Y-Spacer-L-Type	MS	As per Drawing	1.5	1			
3.13	TR-SA3-07	TR-SA3-07	Spacer 30mm	MS	As per Drawing	1.22	1			
3.14	ISO 4762 M5 x 30 - 22N		Allen Nuts & Bolts	SS 302	M5 30mm		12			
3.15	_TBCK_S5M150_10		Clamp Plate for Timing belt				1			
3.16	_TBCK_S5M150_12			Clear Ionized-A6N01-T5	Width- 15mm	0.07	1	Misumi	TBCK-S5M150	
3.17	ISO 4762 M4 x 20 - 20N		Allen Nuts & Bolts	SS 302	M4 20mm		6			
3.18	3.12_Y-beam Side Plate	TR-SA3-05	Beam Side Plate	Aluminium (Al 6063)	As per Drawing	0.17	2			
3.19	hg-kn73j		AC Servo Motor			12	1	Mitsubishi	HG-KN 73(B) J	
3.2O	3.17 Y-Motor Clamp	TR-SA3-10		SS 304	As per Drawing	0.37	1			
3.21	3.13_Y-motor plate	TR-SA3-06	Motor Plate	SS 304	As per Drawing	0.15	1			
3.22	ISO 4762 M8 x 16 - 16N		Allen Bolts	SS 302			4			
3.23	ISO 4762 M6 x 16 - 16N		Allen Bolts	SS 302			8			
3.24	ISO 10511-M6-N		Nylon Lock Nut	SS 302			4			
3.25	3.10_Y-idler Pulley Holding Plate	TR-SA3-03	Plate Idler Pulley	MS	As per Drawing	0.1	1			
3.26	3.9_Y-Cantilever Shaft		Cantilever Shafts - Shouldered - Lock Nut	Steel	Dia-10mm	0.1	1			
3.27	socket head cap screw_iso		Allen Nuts & Bolts	SS 302	M4 20mm		8			
3.28	C_AHTFW26_S5M150_10_3		Idler Pulley	[Aluminum] 2000 Series Aluminum Alloy	10mm ID Width- 15mm	0.07	2	Misumi	C-AHTFW26-S5M150-10	
3.29	C_AHTFW26_S5M150_10_6						1			
3.3O	C-HTPA26S5M150-A-N19		Y- Timing Pulley	[Steel] S45C Equivalent	19mm ID Width- 15mm	0.07	1	Misumi	C-HTPA26S5M150-A-N19	

3.31	Belt1-8^TR-SA-3		Y- Timing Belt	Rubber Belt	Length- 3588mm Width- 15mm	0.17	1	Misumi	HTBOGS5M150-725	
3.32	T-NUTS		M4 T-Nuts				6			
3.33	T-NUTS		M5 T-Nuts				76			
3.34	T-NUTS		M6 T-Nuts				8			
3.35	T-NUTS		M8 T-Nuts				4			