

Objects

Part 2

Outline

- Function as Class (Constructor Function)
- Property Descriptor
- Property Attributes (data property)
- Define / Modify Property
- Getters and Setters

Define a Class

- JavaScript ECMAScript 5, does not have class type.
- So it does not support full object oriented programming concept as other languages like Java or C#.
- However, you can create a function in such a way so that it will act as a class.

Define a Class : Example

```
function Person() {  
    this.firstName = "unknown";  
    this.lastName = "unknown";  
}
```

```
var person1 = new Person();  
person1.firstName = "Steve";  
person1.lastName = "Jobs";
```

```
console.log(person1.firstName + " " + person1.lastName);
```

```
var person2 = new Person();  
person2.firstName = "Bill";  
person2.lastName = "Gates";
```

```
console.log(person2.firstName + " " + person2.lastName);
```

Add Methods in a Class

```
function Person() {  
    this.firstName = "unknown";  
    this.lastName = "unknown";  
    this.getFullName = function() {  
        return this.firstName + " " + this.lastName;  
    }  
};
```

```
var person1 = new Person();  
person1.firstName = "Steve";  
person1.lastName = "Jobs";
```

```
console.log(person1.getFullName());
```

```
var person2 = new Person();  
person2.firstName = "Bill";  
person2.lastName = "Gates";
```

```
console.log(person2.getFullName());
```

Constructor

```
function Person(FirstName, LastName, Age) {  
    this.firstName = FirstName || "unknown";  
    this.lastName = LastName || "unknown";  
    this.age = Age || 25;  
    this.getFullName = function() {  
        return this.firstName + " " + this.lastName;  
    }  
};
```

```
var person1 = new Person("James", "Bond", 50);  
console.log(person1.getFullName());
```

```
var person2 = new Person("Tom", "Paul");  
console.log(person2.getFullName());
```

Read-only Property

```
function Person(firstName) {  
    var _firstName = firstName || "unknown";  
  
    Object.defineProperty(this, {  
        "FirstName": {  
            get: function() {  
                return _firstName;  
            }  
        }  
    });  
};  
  
var person1 = new Person("Steve");  
//person1.FirstName = "Steve"; -- will not work  
console.log(person1.FirstName);  
  
var person2 = new Person("Bill");  
//person2.FirstName = "Bill"; -- will not work  
console.log(person2.FirstName);
```

Multiple Properties

```
function Person(firstName, lastName, age) {
  var _firstName = firstName || "unknown";
  var _lastName = lastName || "unknown";
  var _age = age || 25;

  Object.defineProperty(this, {
    "FirstName": {
      get: function() { return _firstName },
      set: function(value) { _firstName = value }
    },
    "LastName": {
      get: function() { return _lastName },
      set: function(value) { _lastName = value }
    },
    "Age": {
      get: function() { return _age },
      set: function(value) { _age = value }
    }
  });

  this.getFullName = function() {
    return this.FirstName + " " + this.LastName;
  }
};

var person1 = new Person();
person1.FirstName = "John";
person1.LastName = "Bond";

console.log(person1.getFullName());
```


Property Descriptor

- Each property of an object has property descriptor which describes the nature of a property.
- Property descriptor for a particular object's property can be retrieved using `Object.getOwnPropertyDescriptor()` method.

- **Syntax:**

`Object.getOwnPropertyDescriptor(object, 'property name')`

- The `getOwnPropertyDescriptor` method returns a property descriptor for a property that directly defined in the specified object but not inherited from object's prototype.

Property Descriptor : Example

```
var person = {
  firstName: 'Steve',
  lastName: 'Jobs'
};

function Student() {
  this.name = "John";
  this.gender = "Male";
  this.sayHi = function() {
    alert('Hi');
  }
}

var student1 = new Student();

console.log(Object.getOwnPropertyDescriptor(person, 'firstName'));
console.log(Object.getOwnPropertyDescriptor(student1, 'name'));
console.log(Object.getOwnPropertyDescriptor(student1, 'sayHi'));
```

Output:

Object {value: "Steve", writable: true, enumerable: true, configurable: true}
Object {value: "John", writable: true, enumerable: true, configurable: true}
Object {value: function, writable: true, enumerable: true, configurable: true}

Property Attributes

Attribute	Description
value	Contains an actual value of a property.
writable	Indicates that whether a property is writable or read-only. If true then value can be changed and if false then value cannot be changed and will throw an exception in strict mode
enumerable	Indicates whether a property would show up during the enumeration using for-in loop or Object.keys() method.
configurable	Indicates whether a property descriptor for the specified property can be changed or not. If true then any of this 4 attribute of a property can be changed using Object.defineProperty() method.

- The **three attributes** (writable, enumerable, and configurable) are all **optional** and all **default to true**.
- These will be **false by default** when we use **Object.defineProperty()** method

Define Property

- This method allows you to **define** a **new property** on an object
- It can also be used to **change the descriptor** of an existing property
- Syntax:

`Object.defineProperty(object, 'property name', descriptor)`

```
function Student(){  
    this.name = "Steve";  
    this.gender = "Male";  
  
}
```

```
var student1 = new Student();
```

```
Object.defineProperty(student1, 'name', { writable:false } );
```

Object.defineProperty() (Ex.1.0)

```
user = { };
Object.defineProperty(user, 'name', {
  value: 'John',
  writable: false,
  enumerable: true,
  configurable: true
})
console.log(user.name);      // 'John'
user.name = 'Jack';         // Exception if in
                             // 'strict' mode
console.log(user.name);      // 'John'
```

Object.defineProperty() (Ex.1.1)

```
Object.defineProperty(user, 'name', {  
    writable: true,  
    configurable: false  
});
```

```
user.name = 'Jack'
```

```
console.log(user.name); // "Jack"
```

```
delete user.name // Won't work
```

Object.defineProperty()

```
user = {}  
Object.defineProperty(user, {  
  "name" :    { value: "John" },  
  "gender" : { value: "male" }  
})
```

```
>> Object.getOwnPropertyDescriptor(user, 'name')
```

```
← ► Object { value: "John", writable: false, enumerable: false, configurable: false }
```

```
console.log(name); // "John"  
user.name = "Jack"; // Won't work  
console.log(name); // "John"
```

Defining Getters and Setters

- A **getter** is a method that **gets the value** of a specific property
- A **setter** is a method that **sets the value** of a specific property
- You can **define** getters and setters on any predefined **core object** or **user-defined object** that supports the addition of new properties.
- Getters and setters can be either
 - **defined** using **object initializers**, or
 - **added later** to any object at any time using **a getter or setter adding method**

Defining Getters and Setters

```
var user = {  
  firstName: 'John',  
  get fName() {  
    return this.firstName;  
  },  
  set fName(fName) {  
    this.firstName = fName.toUpperCase();  
  }  
}  
  
user.fName = 'jack';  
user.fName;    // JACK
```

Defining Getters and Setters

```
let user = {  
  name: "John",  
  surname: "Smith",  
  
  get fullName() {  
    return `${this.name} ${this.surname}`;  
  },  
  
  set fullName(value) {  
    [this.name, this.surname] = value.split(" ");  
  }  
};  
  
// set fullName is executed with the given value.  
user.fullName = "Alice Cooper";  
  
alert(user.name); // Alice  
alert(user.surname); // Cooper
```

Object.defineProperty()

```
var obj = { counter: 0 };
```

```
Object.defineProperty(obj, "reset", {  
  get: function () { this.counter = 0; }  
});
```

```
Object.defineProperty(obj, "increment", {  
  get: function () { this.counter++; }  
});
```

```
Object.defineProperty(obj, "decrement", {  
  get: function () { this.counter--; }  
});
```

Object.defineProperty()

```
Object.defineProperty(obj, "add", {  
  set: function (value) { this.counter += value;  
  }  
});
```

```
Object.defineProperty(obj, "subtract", {  
  set: function (value) { this.counter -  
= value; }  
});
```

```
obj.reset;      // counter = 0  
obj.add = 10;    // counter = 10  
obj.subtract = 3; // counter = 7  
obj.increment;   // counter = 8  
obj.decrement;   // counter = 7
```

Properties with Getters and Setters

```
function Person() {  
    var _firstName = "unknown";  
  
    Object.defineProperty(this, {  
        "FirstName": {  
            get: function () {  
                return _firstName;  
            },  
            set: function (value) {  
                _firstName = value;  
            }  
        }  
    });  
};
```

```
var person1 = new Person();  
person1.FirstName = "Steve";  
alert(person1.FirstName );  
  
var person2 = new Person();  
person2.FirstName = "Bill";  
alert(person2.FirstName );
```

Object.defineProperty() (Ex.2)

```
user = { name: 'John' };
```

```
var age = 30;
```

```
Object.defineProperty(user, 'age', {  
  get: () => age,  
  set: value => { age = value }  
});
```

```
>> user
```

```
← { ... }
```

```
  age: 30
```

```
  name: "John"
```

```
  ▶ <get age(): function get()
```

```
  ▶ <set age(): function set(value)
```

```
  ▶ <prototype>: Object { ... }
```

References

- <https://www.tutorialsteacher.com/javascript>