


# 703308 VO High-Performance Computing MPI - Message Passing Interface

Philipp Gschwandtner

#### Overview

- general concepts about MPI
  - characteristics
  - programming model
  - startup
- point-to-point communication
- collective communication
- practical example

# Motivation for using MPI: data distribution



# Message Passing Interface (MPI)

- message passing library for distributed memory parallelism
- de-facto standard for C (C++) and Fortran
- maintained by the MPI Forum
  - initial release in 1994 (version 1.0)
  - updates in 1997 (2.0), 2012 (3.0), 2015 (3.1), 2021 (4.0), 202x (4.1), 202x (5.0)
  - specification updates slow, aim at stability and high TRL
    - ▶ "On June 30 2020, the MPI forum voted for version 3.3 of these voting rules (effective June 30th, 2020)."

# MPI implementations

#### OpenMPI

- open source
- merge of multiple previous MPI implementations
- default on many systems

#### MPICH

- also open source
- basis for many vendor implementations such as Intel, IBM, Cray, Microsoft, ...
  - default on many systems
- Do not confuse implementation versions with specification versions!
- Do not confuse implementation adherence with specification adherence!
- https://www.mpi-forum.org/implementation-status/

#### Main characteristics

- offers specific tools for
  - sending and receiving messages
  - waiting and synchronization
  - identification of individual processes
  - ...


- additional convenience tools for
  - partitioning and distributing data
  - organizing processes in structures
  - large-scale I/O operations
  - ...

#### Main characteristics cont'd


- a lot of user responsibility
  - explicit parallelism and communication
  - program correctness
  - performance optimization
    - ► (non-)blocking
    - ► (a)synchronous

- a lot of advantages
  - available everywhere
  - several implementations
  - portable to many architectures
  - very high performance

# Recap: MIMD: MPMD



# Recap: MIMD: SPMD



# MPMD through SPMD

- many MPI implementations support only SPMD
- SPMD can emulate MPMD

```
int main() {
    // get id information
    int cpuID = ...;
    if(cpuID==0) {
        ... // program A
    } else {
        ... // program B
```

# Parallelism requires two mechanisms

- a mechanism for spawning processes
  - multiple ways of achieving this
  - we won't look at this in too much detail
  - simply rely on mpiexec to do the work for you
- a mechanism for sending and receiving messages
  - many, many ways of exchanging messages
  - we will definitely look at this in a lot of detail
  - tons of functionality to choose from, as we'll see in a bit

# Compiler and execution wrappers

- mpicc/mpic++ for compiling
  - OpenMPI: --showme prints compiler flags
  - passes all additional compiler flags to backend compiler (e.g. mpicc -g)
- mpiexec for running
  - formerly mpirun, but mpiexec is standardized
  - alternatively srun or whatever the platform documentation recommends

# Startup procedure of an MPI application

# SLURM job submission

- allocates resources
- setsenvironment
- calls mpiexec

#### mpiexec

- reads SLURM environment
- connects to nodes
- spawns processes

# MPI function calls

- identify processes
- exchange messages
- synchronize

#### Hello world in MPI

```
#include <mpi.h>
#include <stdio.h>
int main(int argc, char** argv) {
   MPI_Init(&argc, &argv); // initialize the MPI environment
    int size;
   MPI Comm size(MPI COMM WORLD, &size); // get the number of ranks
    int rank;
   MPI_Comm_rank(MPI_COMM_WORLD, &rank); // get the rank of the caller
    printf("Hello world from rank %d of %d\n", rank, size);
    MPI_Finalize(); // cleanup
```

# Setup and teardown

- int MPI\_Init( int\* argc, char\*\*\* argv )
  - must be called by every process before calling any other MPI function
  - initializes the MPI library
- int MPI\_Finalize( void )
  - must be the last MPI function called by every process
  - user must ensure completion of all locally (!) pending communication
  - performs library cleanup

# Who am I talking to?


- in MPI-speak, processes are known as "ranks"
  - numbered from 0 to N-1
  - own rank can be queried with
    int MPI\_Comm\_rank( MPI\_Comm
    comm, int\* rank )

- almost all MPI semantics are relative to a "communicator" or "group"
  - identifies a set of ranks
  - always available: MPI\_COMM\_WORLD
    (=everyone)
  - new communicators and groups that hold subsets of ranks can be created
  - when developing a library, always create your own communicator!
    - frequent MPI programming pattern

# Point-to-Point Communication

# Point-to-point communication

- ▶ MPI\_Send(...)/MPI\_Recv(...)
  - single sender, single receiver ("point-to-point")
- simplest form of communication available
  - not necessarily the best
- multiple different types
  - ▶ (a)synchronous
  - (non-)blocking



## MPI Send

- - buf: source buffer to send data from
  - count: number of data elements to send
  - datatype: type of data to send
  - dest: destination rank
  - tag: user-defined message type or category
  - comm: communicator

MPI\_Send(&number, 1, MPI\_INT, 1, 42, MPI\_COMM\_WORLD);

#### MPI Recv

- int MPI\_Recv(void\* buf, int count, MPI\_Datatype datatype, int source, int tag, MPI\_Comm comm, MPI\_Status\* status)
  - buf: destination buffer to save data to
  - count: number of data elements to receive
  - datatype: type of data to receive
  - source: source rank
  - tag: user-defined message type or category
  - comm: communicator
  - status: holds additional information (e.g. rank of sender or tag of message)
- MPI\_Recv(&number, 1, MPI\_INT, 0, 42, MPI\_COMM\_WORLD,
  MPI STATUS IGNORE);

# Basic send/receive example

```
int number;
if (rank == 0) {
    number = -1;
    MPI_Send(&number, 1, MPI_INT, 1, 42, MPI_COMM_WORLD);
} else if (rank == 1) {
    MPI_Recv(&number, 1, MPI_INT, 0, 42, MPI_COMM_WORLD, MPI_STATUS_IGNORE);
    printf("Rank 1: Received %d from rank 0\n", number);
}
```

# Side note: MPI data type conversion

#### "representation conversion"

- changes the binary representation of some data
- allowed in MPI, required by supporting heterogeneous architectures
  - e.g. sender is ARM, receiver is x86, ...
  - e.g. big-endian vs. little-endian, ASCII vs. EBCDIC, ...

#### "type conversion"

- converts the actual data type, e.g. from float to integer
- c.f. C++ numeric casts
- not allowed in MPI

#### Predefined MPI constants

- datatypes
  - MPI\_INT, MPI\_FLOAT, MPI\_DOUBLE, MPI\_BYTE, MPI\_CHAR, ...
- wildcards & misc
  - MPI\_ANY\_SOURCE
  - MPI\_ANY\_TAG
  - MPI\_COMM\_WORLD
  - MPI\_STATUS\_IGNORE
  - ...


# (Non-)Blocking and (a)synchronous communication

#### distinguish two important properties

- When does the MPI function call return?
  - Can I overwrite the send buffer?
  - When is all the data in the receive buffer?
- When does the corresponding message transfer happen?
  - Do I need to wait for the receiver to get the entire message?
  - Do I need to wait for the receiver to begin receiving?

```
if (rank == 0) {
    MPI_Send(&number, ...);
} else if (rank == 1) {
    MPI_Recv(&number, ...);
}
```

# (Non-)Blocking and (a)synchronous communication cont'd



# Blocking vs. non-blocking communication

- blocking point-to-point:
   MPI\_Send() and MPI\_Recv()
  - allows to re-use send buffer after send call returns
  - allows to read receive buffer after receive call returns

```
if (rank == 0) {
    MPI_Send(&number, ...);
    // re-use number here
} else if (rank == 1) {
    MPI_Recv(&number, ...);
    // use number here
}
```

# Blocking vs. non-blocking communication cont'd

- non-blocking point-to-point:
  MPI\_Isend() and MPI\_Irecv()
  - send and receive return (almost)Immediately
  - MPI\_Wait() call blocks until buffer can be read/re-used


```
MPI_Request request;
if (rank == 0) {
  MPI_Isend(&number, ..., &request);
  MPI_Wait(&request, MPI_STATUS_IGNORE);
  // re-use number here
} else if (rank == 1) {
  MPI_Irecv(&number, ..., &request);
  MPI Wait(&request, MPI STATUS IGNORE);
  // re-use number here
```

# (A)Synchronous send modes

- ▶ MPI\_Ssend() synchronous mode
  - will wait for matching receive
- ▶ MPI\_Bsend() buffered mode
  - will buffer, won't wait for a matching receive
- ▶ MPI\_Rsend() ready mode
  - requires an already posted, matching receive (dangerous, developer responsibility!)
- MPI\_Send() standard mode
  - may buffer (depends on message size)
  - may or may not wait for matching receive
- ▶ and there are also non-blocking variants for ALL of them...

# Message order preservation

- messages do NOT overtake each other if
  - same communicator
  - same source rank
  - same destination rank
- regardless of blocking or synchronization mode
- mandated by MPI specification




# Collective Communication

#### Collective communication

- convenience function for frequently-used programming patterns (e.g. distributing data)
  - can involve several ranks at the same time, not just 2
  - must be called by ALL ranks in the communicator
  - must be called in-order by all ranks (no interleaving of multiple collective communication calls!)
  - is locally finished when local operation has finished
  - is globally finished when all participating ranks are finished
  - available as blocking and non-blocking variants (but cannot be mixed!)

# MPI\_Scatter/MPI\_Scatterv

- sends chunks of data to multiple ranks, including root itself
- simple way of partitioning and distributing data
- MPI\_Scatterv() allows varying counts of elements to be distributed to each rank



## MPI Scatter


- - sendbuf: source buffer to send data from
  - sendcount: number of data elements to send to each rank
  - sendtype: type of data to send
  - recvbuf: destination buffer to save data to
  - recvcount: number of data elements to receive at each rank
  - recvtype: type of data to receive
  - root: rank of the sender
  - comm: communicator

## Scatter example

```
int globaldata[4];
if(rank==0) {
    for(int i = 0; i < 4; i++) {
        globaldata[i] = ...
int localdata;
MPI_Scatter(globaldata, 1, MPI_INT, &localdata, 1, MPI_INT, 0,
  MPI COMM WORLD);
```


# MPI\_Gather/MPI\_Gatherv

- sends chunks of data from multiple ranks, including root itself, to root
- simple way of collecting data
- MPI\_Gatherv() allows varying counts of elements to be collected from each rank



# MPI\_Bcast

- broadcast operation
- sends copies of data to multiple ranks




# Q: emulating broadcast with point-to-point?


```
MPI_Bcast(&buf, 1, MPI_INT, 0, MPI_COMM_WORLD);
  if (rank == 0) {
   for (int i = 0; i < size; i++) {
      if (i != rank) {
          MPI_Send(&buf, 1, MPI_INT, i, 0, MPI_COMM_WORLD);
 else {
   MPI_Recv(&buf, 1, MPI_INT, 0, 0, MPI_COMM_WORLD, MPI_STATUS_IGNORE);
```

# Collective communication patterns


- chosen automatically at runtime by MPI implementation
- may depend on multiple parameters, including
  - type of operation (e.g. broadcast)
  - number and location of ranks
  - size and structure of data
  - hardware capabilities



sequential algorithm O(num ranks)



tree-based algorithm e.g. O(log<sub>2</sub>(num\_ranks))



hardware operation O(1)

#### Barrier


- int MPI\_Barrier(MPI\_Comm comm)
  - comm: communicator
- causes all ranks to wait until everyone reached the barrier
  - normally not needed: explicit data communication usually also inherently synchronizes
  - often used for debugging and profiling
    - Don't forget to remove in production/release!

# MPI\_Reduce

- aggregate data from multiple ranks, including root itself, to root
  - e.g. MPI\_SUM
  - may use optimized collective communication patterns
- assumes associative reduction operation • such that e.g.

$$(x_0 \circ x_1) \circ (x_2 \circ x_3) = ((x_0 \circ x_1) \circ x_2) \circ x_3$$

be careful with floating point types!



# MPI\_Reduce cont'd

- int MPI\_Reduce(const void\* sendbuf, void\* recvbuf, int count, MPI\_Datatype datatype, MPI\_Op op, int root, MPI\_Comm comm)
  - sendbuf: source buffer to reduce data from
  - recybuf: destination buffer to reduce data into
  - count: number of data elements in source and destination buffers
  - datatype: type of data to reduce
  - op: reduction operation
  - root: rank of the destination of aggregated result
  - comm: communicator

# Available reduction operations


- several pre-defined
  - MPI\_MAX, MPI\_MIN
  - MPI\_SUM, MPI\_PROD
  - MPI\_LAND, MPI\_LOR, MPI\_LXOR
  - ▶ MPI BAND, MPI BOR, MPI BXOR
  - MPI\_MAXLOC, MPI\_MINLOC
- All pre-defined operations are associative and commutative

- also user-defined ops are possible
  - must be associative
  - may be commutative
  - requires a specific function signature
  - needs to be registered as an MPI handle

### Additional MPI functions

- ▶ MPI\_Wtime
  - returns time in seconds since an arbitrary time in the past (<u>W</u>all clock time)
- MPI\_Sendrecv
  - convenience wrapper for blocking send and receive
- ▶ MPI\_Allreduce/MPI\_Allgather/...
  - same as non-all versions, but result is available everywhere (performance impact!)
- ▶ MPI Scan/MPI Exscan
  - inclusive and exclusive prefix reductions
- MPI\_Wait/MPI\_Test
  - blocking/non-blocking check whether pending operation completed
- ▶ MPI\_Probe/MPI\_Iprobe
  - blocking/non-blocking check for new message without actually receiving it

### Example code: naïve matrix multiplication



```
#include <mpi.h>
#include <stdio.h>
#include <stdlib.h>
#define SIZE 4
int A[SIZE][SIZE];
int B[SIZE][SIZE];
int C[SIZE][SIZE];
void fill_matrix(int m[SIZE][SIZE]);
void print_matrix(int m[SIZE][SIZE]);
```

# Example code: naïve matrix multiplication cont'd

```
int myRank, numProcs;
MPI_Init(&argc, &argv);
MPI Comm rank(MPI COMM WORLD, &myRank);
MPI Comm size(MPI COMM WORLD, &numProcs);
// if matrix size not divisible
if(SIZE % numProcs != 0) {
    MPI Finalize();
    return EXIT FAILURE;
  root generates input data
if(myRank == 0) {
    fill matrix(A);
    fill_matrix(B);
```

```
// compute boundaries of local computation
int start = myRank*SIZE/numProcs;
int end = (myRank+1)*SIZE/numProcs;
// distribute rows of A to everyone
MPI_Scatter(A, SIZE*SIZE/numProcs, MPI_INT,
  A[start], SIZE*SIZE/numProcs, MPI INT, 0,
  MPI COMM WORLD);
// send entire matrix B to everyone
MPI Bcast(B, SIZE*SIZE, MPI INT, 0,
  MPI COMM WORLD);
```

# Example code: naïve matrix multiplication cont'd

```
// local computation of every rank
for(int i = start; i < end; i++) {</pre>
   for(int j = 0; j < SIZE; j++) {
       C[i][j] = 0;
        for(int k = 0; k < SIZE; k++) {
            C[i][j] += A[i][k] * B[k][j];
```

```
// gather result rows back to root
MPI_Gather(C[start], SIZE*SIZE/numProcs,
  MPI INT, C, SIZE*SIZE/numProcs, MPI INT, 0,
  MPI COMM WORLD);
if(myRank == 0) { print matrix(C); }
MPI Finalize();
return EXIT_SUCCESS;
```

# Submitting to a cluster (SLURM & SGE)

```
#!/bin/bash
# submission partition
#SBATCH --partition std.q
# name of the job
#SBATCH --job-name my_test_job
# redirect output stream to this file
#SBATCH --output output.dat
# specify parallel environment
#SBATCH --ntasks 8
#SBATCH --ntasks-per-node 2
srun /path/to/application
# or
mpiexec -n $SLURM NTASKS /path/to/application
```

```
#!/bin/bash
# submission queue
#$ -q std.q
# change to current directory
#$ -cwd
# name of the job
#$ -N my test job
# redirect output stream to this file
#$ -o output.dat
# join the output and error stream
#$ -j yes
# specify parallel environment
#$ -pe openmpi-2perhost 8
mpiexec -n 8 /path/to/application
```

# Tales from the proseminar: osu\_latency on LCC3 (WIP!)

	mpiexec								mpirun						srun					
	intel-				openmpi	openmpi	intel-				openmpi	openmpi	intel-				openmpi	openmpi		
	mpi_2019	openmpi (	openmpi	openmpi	_4.1.4-	_4.1.4-	mpi_2019	openmpi	openmpi	openmpi	_4.1.4-	_4.1.4-	mpi_2019	9 openmpi	openmpi	openmpi	_4.1.4-	_4.1.4-		
	.10.317-	_3.1.6-	_4.1.4-	_4.1.4-	intel-	oneapi-	.10.317-	_3.1.6-	_4.1.4-	_4.1.4-	intel-	oneapi-	.10.317-	_3.1.6-	_4.1.4-	_4.1.4-	intel-	oneapi-		
	gcc-8.5.0	gcc-12.2.0	gcc-12.2.0	gcc-8.5.0	2021.7.1	2022.2.1	gcc-8.5.0	gcc-12.2.0	gcc-12.2.0	gcc-8.5.0	2021.7.1	2022.2.1	gcc-8.5.0	gcc-12.2.0	gcc-12.2.0	gcc-8.5.0	2021.7.1	2022.2.1		
	1,80	1,66	95,88	69,47	28,93	85,42	1,81	. 1,66	79,14	56,00	97,42	80,42	2	1,67	71,90	78,34	66,89	92,06		
1	1,76	5 1,63	95,62	70,13	40,54	86,30	1,78	1,63	28,03	86,42	82,59	85,00	)	1,63	71,16	76,03	83,24	87,43		
2	1,78		94,80		75,30	86,50	1,77	1,64						1,63	71,98					
4	1,74	4 1,61	95,21	40,60	95,26	83,93	1,76	1,62	31,36	66,64	93,13	28,45	5	1,62	73,02	78,09	86,48			
8	1,75	5 1,62	91,95	34,66	95,93	64,33	1,77	1,62	26,62	2 25,96	97,88	84,32	2	1,63	69,35			,		
16	1,75	5 1,62	94,23	51,73	93,17	86,81	1,76	1,62	27,07	7 26,12	96,36	84,41		1,63	72,14	69,28	86,04			
32		· · · · · · · · · · · · · · · · · · ·	93,55			,								1,64						
64			96,35	,	45,49	85,40	1,92			87,75	99,55	85,52	2	1,78	73,94					
128		3 2,43	96,78	26,83	35,30	88,23	2,53	2,43	67,60	91,09	90,25	88,17	'	2,41	75,87	80,22	88,34	ŕ		
256		· · · · · · · · · · · · · · · · · · ·	99,64	59,55	34,41	90,81	2,70				101,17			2,56	80,46	87,47	91,85	98,71		
512		5 2,86	107,64	82,11	110,03	100,77	2,97	2,86	93,53	103,54	112,58	97,99	)	2,84	83,85	94,60	97,54	104,10		
1024	3,52	2 3,41	120,97	98,86	106,42	112,24	3,52	3,41	107,47	118,41	126,83	106,49	)	3,40	97,34	106,20	112,88			
2048	4,54	4,48	113,75	172,84	108,50	146,21	4,55	4,48	144,54	126,49	117,29	141,24	l .	4,44	192,35	153,77	147,66	137,15		
4096	6,58	3 6,57	251,72	256,34	247,65	244,15	6,58	6,58	269,62	230,88	224,56	284,89	)	6,56	282,53	239,24	275,62	274,82		
8192	8,47	7 8,43	250,83	248,67	250,95	249,15	8,47	8,45	248,30	248,97	254,67	247,43	3	8,42	261,81	240,03	251,19	250,45		
16384	11,12	2 11,10	328,66	321,86	334,00	323,64	11,14	11,10	332,36	335,69	328,07	333,04	!	11,12	313,01	340,97	330,24	333,83		
32768	16,44	4 16,17	492,69	483,37	494,25	490,36	16,27	16,16	490,37	497,96	500,31	491,88	3	16,16	484,16	487,69	501,96	492,64		
65536	26,62	2 26,27	362,85	296,98	260,67	376,14	26,47	26,21	353,66	331,07	265,20	329,14	l .	26,21	390,03	284,66	379,37	318,44		
131072	46,24	45,86	488,97	428,50	398,00	460,38	46,22	45,86	445,32	451,03	408,62	420,09	)	45,79	,	-	487,01	408,33		
262144		84,46	555,13	491,73	487,80	545,97	85,67	83,83	551,87	518,01	425,43	514,13	3	84,51	563,26	500,48	551,89	481,68		
524288	164,97	7 161,19	770,21	734,66	662,11	740,81	165,59	161,27	738,98	728,89	666,06	742,23	3	161,10	762,28	661,29	848,54	703,71		
1048576	324,72	2 315,54	1095,23	958,25	996,85	1057,35	324,32	315,51	1053,36	5 1037,02	955,35	944,12	2	315,53	1170,47	998,66	1073,28	1008,58		
2097152	625,85	5 624,34	1874,31	1453,91	1289,10	1763,01	626,02	624,43	1815,92	1769,04	1280,92	1492,41		624,48	2025,38	1390,87	1603,72	1669,82		
4194304	1243,62	2 1243,62	3420,45	2699,88	2327,88	3177,13	1243,86	1243,49	3290,81	2947,66	2329,35	2736,99	)	1243,16	3706,90	2748,61	2925,97	3087,45		

# Summary

- general concepts about MPI
  - characteristics
  - program model
  - startup
- point-to-point communication
- collective communication
- practical example (matrix multiplication)