Homework #2
Muntaha Pasha

## Part 1: Data Model




## Part 2: DDL Scripts

```
-- MySQL Script generated by MySQL Workbench

-- Sat Feb 16 13:52:58 2019

-- Model: New Model    Version: 1.0

-- MySQL Workbench Forward Engineering


SET @OLD_UNIQUE_CHECKS=@@UNIQUE_CHECKS, UNIQUE_CHECKS=0;

SET @OLD_FOREIGN_KEY_CHECKS=@@FOREIGN_KEY_CHECKS, FOREIGN_KEY_CHECKS=0;

SET @OLD_SQL_MODE=@@SQL_MODE,
SQL_MODE='ONLY_FULL_GROUP_BY,STRICT_TRANS_TABLES,NO_ZERO_IN_DATE,NO_ZERO_DATE,ERROR_FOR_DIVISION_
BY_ZERO,NO_ENGINE_SUBSTITUTION';


-- -----------------------------------------------------
```

Homework #2
Muntaha Pasha

```
-- Schema mydb
-- -----------------------------------------------------


-- -----------------------------------------------------
-- Schema mydb
-- -----------------------------------------------------
CREATE SCHEMA IF NOT EXISTS `mydb` DEFAULT CHARACTER SET utf8 ;
USE `mydb` ;


-- -----------------------------------------------------
-- Table `mydb`.`Customer`
-- -----------------------------------------------------
DROP TABLE IF EXISTS `mydb`.`Customer` ;


CREATE TABLE IF NOT EXISTS `mydb`.`Customer` (
  `CustomerId` INT NOT NULL AUTO_INCREMENT,
  `CustomerName` VARCHAR(45) NOT NULL,
  `CustomerAddress1` VARCHAR(45) NOT NULL,
  `CustomerAddress2` VARCHAR(45) NULL,
  `CustomerCity` VARCHAR(45) GENERATED ALWAYS AS () VIRTUAL,
  `CustomerState` CHAR(2) NOT NULL,
  `CustomerZip` VARCHAR(10) NOT NULL,
  `CustomerPhone1` VARCHAR(10) NOT NULL,
  `CustomerPhone2` VARCHAR(10) NULL,
  `ReferredBy` VARCHAR(45) NULL,
  `CustomerSince` DATE NULL,
  `CustomerTypeMowing` VARCHAR(45) NOT NULL,
  `CustomerTypeLandscaping` VARCHAR(45) NOT NULL,
  `CustomerPriorBalance` DECIMAL(9,2) NOT NULL,
  `CustomerTotalNewCharges` DECIMAL(9,2) NOT NULL,
  `CustomerTaxes` DECIMAL(9,2) NOT NULL,
  `CustomerTotalCredits` DECIMAL(9) NOT NULL,
  `CustomerTotalAmountDue` DECIMAL(9,2) NOT NULL,
  `CustomerTypeOther` VARCHAR(45) NULL,
  `Notes` VARCHAR(45) NULL,
  PRIMARY KEY (`CustomerId`))
```

```
ENGINE = InnoDB;



-- -----------------------------------------------------
-- Table `mydb`.`Invoice`
-- -----------------------------------------------------
DROP TABLE IF EXISTS `mydb`.`Invoice` ;

CREATE TABLE IF NOT EXISTS `mydb`.`Invoice` (
  `InvoiceNumber` INT NOT NULL AUTO_INCREMENT,
  `InvoiceDate` DATE NOT NULL,
  `CustomerID` INT NOT NULL,
  `InvoiceTotalAmountDue` DECIMAL(9,2) NOT NULL,
  `InvoiceTotalAmountRemitted` DECIMAL(9,2) NOT NULL,
  `TotalCharges` DECIMAL(9,2) NOT NULL,
  `TotalCredits` INT NOT NULL,
  `Customer_CustomerId` INT NULL,
  PRIMARY KEY (`InvoiceNumber`),
  CONSTRAINT `fk_Invoice_Customer1`
    FOREIGN KEY (`Customer_CustomerId`)
    REFERENCES `mydb`.`Customer` (`CustomerId`)
    ON DELETE NO ACTION
    ON UPDATE NO ACTION)
ENGINE = InnoDB;

CREATE INDEX `fk_Invoice_Customer1_idx` ON `mydb`.`Invoice` (`Customer_CustomerId` ASC) VISIBLE;



-- -----------------------------------------------------
-- Table `mydb`.`InvoiceDetail`
-- -----------------------------------------------------
DROP TABLE IF EXISTS `mydb`.`InvoiceDetail` ;

CREATE TABLE IF NOT EXISTS `mydb`.`InvoiceDetail` (
  `InvoiceNumber` INT NOT NULL AUTO_INCREMENT,
  `InvoiceDetailLineNumber` INT NOT NULL,
```

```
  `InvoiceDetailDate` DATE NOT NULL,

  `ServicesRendered_MaterialsDelivered` VARCHAR(45) NULL,

  `Charges` DECIMAL(9,2) NOT NULL,

  `Credits` INT NOT NULL,

  `Invoice_InvoiceNumber` INT NOT NULL,

  PRIMARY KEY (`InvoiceNumber`, `InvoiceDetailLineNumber`, `Invoice_InvoiceNumber`),

  CONSTRAINT `fk_InvoiceDetail_Invoice`

    FOREIGN KEY (`Invoice_InvoiceNumber`)

    REFERENCES `mydb`.`Invoice` (`InvoiceNumber`)

    ON DELETE NO ACTION

    ON UPDATE NO ACTION)

ENGINE = InnoDB;


CREATE INDEX `fk_InvoiceDetail_Invoice_idx` ON `mydb`.`InvoiceDetail` (`Invoice_InvoiceNumber`
ASC) VISIBLE;


SET SQL_MODE=@OLD_SQL_MODE;

SET FOREIGN_KEY_CHECKS=@OLD_FOREIGN_KEY_CHECKS;

SET UNIQUE_CHECKS=@OLD_UNIQUE_CHECKS;
```

## Part 3: Assumptions & Thought Process

1) I had to assume that customers had multiple possible invoices, so I used an independent one to many relationship between Customers and Invoice.
2) Invoices are composed OF invoice details, so I used a dependant one to many.
3) I had to make the assumption that customer ID was inside the invoice table, otherwise making the connection would've been hard.
4) I had to assume that some table values like zip codes could be VARCHAR of 10 instead of ints, because when I researched online it said INT values are mostly used for operations like addition and subtraction.
5) I had to assume a lot of customer information and invoice information was NOT NULL, because it's important to have a good amount of information for each customer.