

DDL – Data Definition Language

Modify Database Structures

Create

Alter

Drop

DML – Data Manipulation Language

Modify the data values within the tables/rows

Insert

Update

Delete

INSERT statement – Two Formats

```
INSERT INTO <table name> (column, column, column)
VALUES (value, value, value)
```

(if no column & value are specified, NULL or default will be assigned)

```
INSERT INTO <table name>
VALUES (value, value, value, value)
```

(must have a value or NULL for every column in the table)

INSERT statement (with auto_increment)

```
INSERT INTO nwEmployees
  (LastName, FirstName, Title, TitleOfCourtesy,
   BirthDate, HireDate, Address, City, Region,
   PostalCode, Country, HomePhone, Extension)

VALUES

('Dunn','Nat','Sales Representative', 'Mr.',
'1970-02-19', '2014-01-15',
'4933 Jamesville Rd.','Jamesville','NY',
'13078','USA','315-555-5555','130');
```

INSERT statement (2nd format missing values)

```
INSERT INTO nwEmployees
VALUES
('20','Thomas','Tammy','Database Administrator',
'Ms.','1990-08-27','2017-06-18',
'5012 Arapahoe St.','Boulder','CO',
'80304','USA');
```

```
INSERT INTO nwEmployees
VALUES
('20','Thomas','Tammy','Database Administrator',
'Ms.','1990-08-27','2017-06-18',
'5012 Arapahoe St.','Boulder','CO',
'80304','USA',NULL,NULL,NULL,NULL,NULL);
```

CREATE statement

```
CREATE TABLE <table name>
    (column    DATATYPE (L) ,
      column    DATATYPE (L) NOT NULL,
      column    DATATYPE (L) NOT NULL Default 0,
      column    DATATYPE (L) CONSTRAINT
        <constraint name> TYPE,
      column    DATATYPE (L) )
```

DESCRIBE statement

shows you what MySQL knows about a table

CREATE statement

```
CREATE TABLE IF NOT EXISTS items (  
    itemID      INT          NOT NULL AUTO_INCREMENT,  
    itemCode    CHAR(3)      ,  
    itemname    VARCHAR(40)  NOT NULL DEFAULT ' ',  
    quantity    INT          NOT NULL DEFAULT 0,  
    price       DECIMAL(9,2) NOT NULL DEFAULT 0,  
    PRIMARY KEY (itemID)  
);
```

```
DROP TABLE IF EXISTS items;
```

```
DESC items;
```

CREATE statement

```
CREATE TABLE items (  
    itemID      INT          NOT NULL ,  
    itemCode    CHAR(3)      ,  
    itemname    VARCHAR(40)  NOT NULL DEFAULT ' ',  
    quantity    INT          NOT NULL DEFAULT 0,  
    price       DECIMAL(9,2) NOT NULL DEFAULT 0,  
    PRIMARY KEY (itemID)  
    );
```

TRUNCATE statement – removes all rows, keeps structure

```
TRUNCATE TABLE <table name>
```

DROP statement -- removes all rows, removes structure

```
DROP TABLE <table name>
```


ALTER statement

```
ALTER TABLE <table name>
    ADD/MODIFY/DROP
        COLUMN <column name>    DATATYPE (L) ,

    RENAME <new table name>

ALTER TABLE <table name>
    DROP COLUMN
```

ALTER statement

```
ALTER TABLE nwemployees  
    MODIFY COLUMN EmployeeID INT(11) PRIMARY KEY  
    AUTO_INCREMENT;
```

```
ALTER TABLE Items  
    ADD PRIMARY KEY (ItemID) ;
```

```
ALTER TABLE Items  
    ADD COLUMN InventoryDate DATE AFTER itemname ;
```

```
ALTER TABLE Items  
    DROP COLUMN InventoryDate;
```

BULK INSERT statement

```
INSERT INTO items
    SELECT ProductID, CategoryID, ProductName,
    CURDATE(), unitsInStock, UnitPrice
    FROM nwProducts
;
```

UPDATE statement

```
UPDATE <table name>  
    SET column = <value>  
    WHERE <condition>
```

DELETE statement

```
DELETE FROM <table name>  
    WHERE <condition>
```

**Note: Without the WHERE clause,
the DELETE will affect ALL rows**

UPDATE statement

```
UPDATE items
  SET price = (price + (price * .05))
  WHERE itemcode = 1;
```

```
UPDATE items
  SET price = ROUND((price + (price * .05)),2)
  WHERE itemcode = 1;
```

Delete statement

```
DELETE FROM items
  WHERE itemcode = 2;
```

The VIEW

- A “VIEW” is an empty shell of a table definition
- The view contains no data until it is queried
- Sometimes considered a “Virtual Table”
- Each time the view is queried, the underlying query that populates the view is re-executed

CREATING a VIEW

```
CREATE VIEW <view name> AS
    SELECT <col1>, <col2>, <col3>
        FROM <table1>
        WHERE <condition>
```

Why VIEWS?

- The base table or specific columns in the base table can be hidden from certain users who are only allowed access to the view
- Very complex SQL to create the view can be hidden from end users

First “why”:

Base Table:

Employees(EmpID, Lastname, Firstname, Salary, HireDate)

View:

Employees(EmpID, Lastname, Firstname, HireDate)

Second “why”:

Base Query:

```
Create VIEW TopEmployeeOrders AS
  Select LastName, Firstname,
    sum(UnitPrice * Quantity) as 'OrderValue'
  from nwEmployees E, nwOrders O,
    nwOrderDetails D
  where E.EmployeeID = O.EmployeeID
    and O.OrderID = D.OrderID
  GROUP BY LastName, FirstName
  Order By 3 desc
```

View

```
Select * from TopEmployeeOrders;
```

```
CREATE OR REPLACE VIEW TopEmployeeOrders AS
  SELECT LastName, Firstname,
         SUM(UnitPrice * Quantity) AS 'OrderValue'
  FROM nwEmployees E, nwOrders O,
       nwOrderDetails D
 WHERE E.EmployeeID = O.EmployeeID
       AND O.OrderID = D.OrderID
 GROUP BY LastName, FirstName
 ORDER BY 3 DESC;
```

```
SELECT * FROM TopEmployeeOrders;
```