

Pizza Sales SQL Queries

A.KPI's

```
CREATE DATABASE Pizza_DB
SELECT *
FROM
    pizza_sales
```

1. Total revenue :

```
SELECT
    SUM(total_price) AS Total_Revenue
FROM
    pizza_sales
```

Total_Revenue
817860.0499999993

2. Average order value

```
SELECT
    SUM(total_price)/COUNT(DISTINCT(order_id)) AS Average_Order_Value
FROM
    pizza_sales
```

Average_Order_Value
38.307262295081635

3. Total pizzas sold

```
SELECT
    SUM(quantity) AS Total_pizzas_sold
FROM
    pizza_sales
```

Total_pizzas_s...
49574

4. Total orders

```

SELECT
    COUNT(DISTINCT(order_id)) AS Total_Orders
FROM
    pizza_sales

```

Total_Orders	
21350	

5. Average pizzas per order

```

SELECT
    SUM(quantity)/COUNT(DISTINCT(order_id)) AS Average_pizzas_per_order
FROM
    pizza_sales

```

Average_pizzas_per_order	
2.3220	

B. Chart requirement

1. Daily trend for total orders

```

SELECT
    DATE_FORMAT(STR_TO_DATE(order_date, '%c/%e/%Y'), '%W') AS
order_day,
    COUNT(DISTINCT(order_id)) AS total_orders
FROM
    pizza_sales
GROUP BY
    DATE_FORMAT(STR_TO_DATE(order_date, '%c/%e/%Y'), '%W')

```

order_day	total_orders	
Friday	3538	
Thursday	3239	
Saturday	3158	
Wednesday	3024	
Tuesday	2973	
Monday	2794	
Sunday	2624	

2. Monthly and Hourly trend for total orders

```
SELECT
    DATE_FORMAT(STR_TO_DATE(order_date, '%c/%e/%Y'), '%M') AS
order_monthly,
    COUNT(DISTINCT(order_id)) AS total_orders
FROM
    pizza_sales
GROUP BY
    DATE_FORMAT(STR_TO_DATE(order_date, '%c/%e/%Y'), '%M')
```

order_monthly	total_orders
July	1935
May	1853
January	1845
August	1841
March	1840
April	1799
November	1792
June	1773
February	1685
December	1680
September	1661
October	1646

```
SELECT
    DATE_FORMAT(STR_TO_DATE(order_time, '%H:%i:%s'), '%H') AS
order_hourly,
    COUNT(DISTINCT(order_id)) AS total_orders
FROM
    pizza_sales
GROUP BY
    DATE_FORMAT(STR_TO_DATE(order_time, '%H:%i:%s'), '%H')
ORDER BY
    total_orders DESC
```

order_hourly	total_orders
12	2520
13	2455
18	2399
17	2336
19	2009
16	1920
20	1642
14	1472
15	1468
11	1231
21	1198
22	663
23	28
10	8
09	1

3. Percentage of sales by pizza category

```

SELECT
    pizza_category,
    SUM(total_price)*100 / (SELECT SUM(total_price) FROM pizza_sales) AS
PCT
FROM
    pizza_sales
GROUP BY
    pizza_category

```

pizza_category	PCT
Classic	26.9059602556699
Veggie	23.682590927384783
Supreme	25.45631126009884
Chicken	23.955137556847493

4. Percentage of sales by pizza size

```

SELECT
    pizza_size,
    SUM(total_price)*100 / (SELECT SUM(total_price) FROM pizza_sales) AS
PCT
FROM

```

```

    pizza_sales
GROUP BY
    pizza_size

```

pizza_size	PCT	
M	30.492044451859723	
L	45.8903329487743	
S	21.773468455880682	
XL	1.7210768517181052	
XXL	0.12307729176892906	

5. Total pizzas sold by pizza category

```

SELECT
    pizza_category,
    ROUND(SUM(total_price)) AS Total_sold
FROM
    pizza_sales
GROUP BY
    pizza_category

```

pizza_category	Total_sold	
Classic	220053	
Veggie	193690	
Supreme	208197	
Chicken	195920	

6. Top 5 best sellers by total pizzas sold

```

SELECT
    pizza_name,
    SUM(total_price) AS Revenue
FROM
    pizza_sales
GROUP BY
    pizza_name
ORDER BY
    Revenue DESC
LIMIT 5

```

pizza_name	Revenue	
The Thai Chicken Pizza	43434.25	
The Barbecue Chicken Pizza	42768	
The California Chicken Pizza	41409.5	
The Classic Deluxe Pizza	38180.5	
The Spicy Italian Pizza	34831.25	

```

SELECT
    pizza_name,
    SUM(quantity) AS Quantity
FROM
    pizza_sales
GROUP BY
    pizza_name
ORDER BY
    Quantity DESC
LIMIT 5

```

pizza_name	Quantity	
The Classic Deluxe Pizza	2453	
The Barbecue Chicken Pizza	2432	
The Hawaiian Pizza	2422	
The Pepperoni Pizza	2418	
The Thai Chicken Pizza	2371	

```

SELECT
    pizza_name,
    COUNT(DISTINCT(order_id)) AS Total_order
FROM
    pizza_sales
GROUP BY
    pizza_name
ORDER BY
    Total_order desc
LIMIT 5

```

pizza_name	Total_order	
The Classic Deluxe Pizza	2329	
The Hawaiian Pizza	2280	
The Pepperoni Pizza	2278	
The Barbecue Chicken Pizza	2273	
The Thai Chicken Pizza	2225	

7. Bottom 5 worst sellers by Total Pizzas Sold

```
SELECT
    pizza_name,
    SUM(total_price) AS Revenue
FROM
    pizza_sales
GROUP BY
    pizza_name
ORDER BY
    Revenue
LIMIT 5
```

pizza_name	Revenue	
The Brie Carre Pizza	11588.499999999999	
The Green Garden Pizza	13955.75	
The Spinach Supreme Pizza	15277.75	
The Mediterranean Pizza	15360.5	
The Spinach Pesto Pizza	15596	

```
SELECT
    pizza_name,
    SUM(quantity) AS Quantity
FROM
    pizza_sales
GROUP BY
    pizza_name
ORDER BY
    Quantity
LIMIT 5
```

pizza_name	Quantity	
The Brie Carre Pizza	490	
The Mediterranean Pizza	934	
The Calabrese Pizza	937	
The Spinach Supreme Pizza	950	
The Soppresata Pizza	961	

```
SELECT
    pizza_name,
```

```
        COUNT(DISTINCT(order_id)) AS Total_order
FROM
    pizza_sales
GROUP BY
    pizza_name
ORDER BY
    Total_order
LIMIT 5
```

pizza_name	Total_order	
The Brie Carre Pizza	480	
The Mediterranean Pizza	912	
The Spinach Supreme Pizza	918	
The Calabrese Pizza	918	
The Chicken Pesto Pizza	938	