

# CSE 221: Algorithms

## Quicksort

Mumit Khan

Computer Science and Engineering  
BRAC University

### References

- 1 T. H. Cormen, C. E. Leiserson, R. L. Rivest, and C. Stein, *Introduction to Algorithms, Second Edition*. The MIT Press, September 2001.
- 2 Erik Demaine and Charles Leiserson, *6.046J Introduction to Algorithms*. MIT OpenCourseWare, Fall 2005. Available from: [ocw.mit.edu/OcwWeb/Electrical-Engineering-and-Computer-Science/6-046JFall-2005/CourseHome/index.htm](http://ocw.mit.edu/OcwWeb/Electrical-Engineering-and-Computer-Science/6-046JFall-2005/CourseHome/index.htm)

Last modified: June 21, 2009



This work is licensed under the *Creative Commons Attribution-Noncommercial-Share Alike 3.0 Unported License*.

# Contents

- 1 Quicksort
  - Introduction
  - Partitioning
  - Quicksort algorithm
  - Quicksort analysis
  - Randomized Quicksort
  - Conclusion

# Contents

## 1 Quicksort

- Introduction
- Partitioning
- Quicksort algorithm
- Quicksort analysis
- Randomized Quicksort
- Conclusion

# Quicksort

- Proposed by C. A. R. Hoare in 1962.

# Quicksort

- Proposed by C. A. R. Hoare in 1962.
- Divide and Conquer algorithm – like merge sort.

# Quicksort

- Proposed by C. A. R. Hoare in 1962.
- Divide and Conquer algorithm – like merge sort.
- In-place algorithm – like insertion and heap sorts.

# Quicksort

- Proposed by C. A. R. Hoare in 1962.
- Divide and Conquer algorithm – like merge sort.
- In-place algorithm – like insertion and heap sorts.
- Runs very well with tuning.

# Quicksort

- Proposed by C. A. R. Hoare in 1962.
- Divide and Conquer algorithm – like merge sort.
- In-place algorithm – like insertion and heap sorts.
- Runs very well with tuning.
- Worst-case is  $O(n^2)$ , but for all practical purposes runs in  $O(n \lg n)$ .



# Quicksort

- Proposed by C. A. R. Hoare in 1962.
- Divide and Conquer algorithm – like merge sort.
- In-place algorithm – like insertion and heap sorts.
- Runs very well with tuning.
- Worst-case is  $O(n^2)$ , but for all practical purposes runs in  $O(n \lg n)$ .


## Why do we want to study Quicksort?

One of the most widely used, and extensively studied, sorting algorithms.

# Divide and conquer

Quicksort an  $n$ -element array:

- 1 *Divide* Partition the array into subarrays around a *pivot*  $x$  such that the elements in lower subarray  $\leq x \leq$  elements in the upper subarray.



- 2 *Conquer* Recursively sort the two subarrays.
- 3 *Combine* Trivial – just concatenate the lower subarray, *pivot*, and the upper subarray.

# Divide and conquer

Quicksort an  $n$ -element array:

- 1 *Divide* Partition the array into subarrays around a *pivot*  $x$  such that the elements in lower subarray  $\leq x \leq$  elements in the upper subarray.



- 2 *Conquer* Recursively sort the two subarrays.
- 3 *Combine* Trivial – just concatenate the lower subarray, *pivot*, and the upper subarray.

# Divide and conquer

Quicksort an  $n$ -element array:

- 1 *Divide* Partition the array into subarrays around a *pivot*  $x$  such that the elements in lower subarray  $\leq x \leq$  elements in the upper subarray.



- 2 *Conquer* Recursively sort the two subarrays.
- 3 *Combine* Trivial – just concatenate the lower subarray, *pivot*, and the upper subarray.

# Divide and conquer

Quicksort an  $n$ -element array:

- 1 *Divide* Partition the array into subarrays around a *pivot*  $x$  such that the elements in lower subarray  $\leq x \leq$  elements in the upper subarray.



- 2 *Conquer* Recursively sort the two subarrays.
- 3 *Combine* Trivial – just concatenate the lower subarray, *pivot*, and the upper subarray.

# Divide and conquer

Quicksort an  $n$ -element array:

- 1 *Divide* Partition the array into subarrays around a *pivot*  $x$  such that the elements in lower subarray  $\leq x \leq$  elements in the upper subarray.



- 2 *Conquer* Recursively sort the two subarrays.
- 3 *Combine* Trivial – just concatenate the lower subarray, *pivot*, and the upper subarray.

Key

*Linear-time partitioning algorithm.*

# Quicksort in action


1	2	3	4	5	6	7	8
6	10	13	5	8	3	2	11

# Quicksort in action


1	2	3	4	5	6	7	8
6	10	13	5	8	3	2	11




# Quicksort in action




# Quicksort in action




# Quicksort in action




# Quicksort in action




# Quicksort in action




# Quicksort in action



# Quicksort in action



# Quicksort in action





# Contents

## 1 Quicksort

- Introduction
- Partitioning
- Quicksort algorithm
- Quicksort analysis
- Randomized Quicksort
- Conclusion

# Partitioning algorithm

## Algorithm

PARTITION( $A, p, q$ )  $\triangleright A[p..q]$

```
1   $x \leftarrow A[p]$             $\triangleright$  pivot =  $A[p]$ 
2   $i \leftarrow p$ 
3  for  $j \leftarrow p + 1$  to  $q$ 
4      do if  $A[j] \leq x$ 
5          then  $i \leftarrow i + 1$ 
6              exchange  $A[i] \leftrightarrow A[j]$ 
7  exchange  $A[p] \leftrightarrow A[i]$ 
8  return  $i$ 
```


# Partitioning algorithm

## Algorithm

PARTITION( $A, p, q$ )  $\triangleright A[p..q]$

```
1   $x \leftarrow A[p]$             $\triangleright$  pivot =  $A[p]$ 
2   $i \leftarrow p$ 
3  for  $j \leftarrow p + 1$  to  $q$ 
4      do if  $A[j] \leq x$ 
5          then  $i \leftarrow i + 1$ 
6              exchange  $A[i] \leftrightarrow A[j]$ 
7  exchange  $A[p] \leftrightarrow A[i]$ 
8  return  $i$ 
```

## Invariant



# Partitioning in action

6	10	13	5	8	3	2	11
---	----	----	---	---	---	---	----

$i$     $j$

# Partitioning in action




$i \quad \bullet \rightarrow j$

# Partitioning in action





$i$        $\bullet \rightarrow j$

# Partitioning in action




● →  $i$                        $j$

# Partitioning in action



 $i$  $j$



# Partitioning in action

 $i$ 



# Partitioning in action






● →  $i$

$j$

# Partitioning in action




 $i$  $j$

# Partitioning in action





● →  $i$   $j$

# Partitioning in action

 $i$  $\bullet \rightarrow j$

# Partitioning in action

 $p$  $i$  $\bullet \rightarrow j$

# Partitioning in action

6	10	13	5	8	3	2	11
---	----	----	---	---	---	---	----

6	5	13	10	8	3	2	11
---	---	----	----	---	---	---	----

6	5	3	10	8	13	2	11
---	---	---	----	---	----	---	----

6	5	3	2	8	13	10	11
---	---	---	---	---	----	----	----

2	5	3	6	8	13	10	11
---	---	---	---	---	----	----	----

*i*

# Contents

## 1 Quicksort

- Introduction
- Partitioning
- Quicksort algorithm
- Quicksort analysis
- Randomized Quicksort
- Conclusion



# Quicksort algorithm

## Algorithm

QUICKSORT( $A, p, r$ )  $\triangleright A[p..r]$

```
1  if  $p < r$   
2      then  $q \leftarrow \text{PARTITION}(A, p, r)$   
3          QUICKSORT( $A, p, q - 1$ )  
4          QUICKSORT( $A, q + 1, r$ )
```

# Quicksort algorithm

## Algorithm

QUICKSORT( $A, p, r$ )  $\triangleright A[p \dots r]$

```
1  if  $p < r$ 
2      then  $q \leftarrow \text{PARTITION}(A, p, r)$ 
3          QUICKSORT( $A, p, q - 1$ )
4          QUICKSORT( $A, q + 1, r$ )
```

## Initial call

QUICKSORT( $A, 1, n$ )

# Contents

## 1 Quicksort

- Introduction
- Partitioning
- Quicksort algorithm
- Quicksort analysis
- Randomized Quicksort
- Conclusion

# Analyzing Quicksort - worst-case performance

- Worst-case happens when pivot is always the minimum or maximum element.

# Analyzing Quicksort - worst-case performance

- Worst-case happens when pivot is always the minimum or maximum element.
- Result is that one of the partitions is always empty.

# Analyzing Quicksort - worst-case performance

- Worst-case happens when pivot is always the minimum or maximum element.
- Result is that one of the partitions is always empty.
- When?

# Analyzing Quicksort - worst-case performance

- Worst-case happens when pivot is always the minimum or maximum element.
- Result is that one of the partitions is always empty.
- When? **Input sorted (either non-decreasing or non-increasing)**

# Analyzing Quicksort - worst-case performance

- Worst-case happens when pivot is always the minimum or maximum element.
- Result is that one of the partitions is always empty.
- When? **Input sorted (either non-decreasing or non-increasing)**

## Worst-case analysis

(Note: the worst-case running time for partitioning is  $\Theta(n)$ .)

$$\begin{aligned}T(n) &= T(0) + T(n-1) + \Theta(n) \\&= \Theta(1) + T(n-1) + \Theta(n) \\&= T(n-1) + \Theta(n) \\&= \Theta(n^2)\end{aligned}$$




# Worst-case recursion tree

$$T(n) = T(0) + T(n-1) + cn$$
$$T(n)$$


# Worst-case recursion tree

$$T(n) = T(0) + T(n - 1) + cn$$




# Worst-case recursion tree

$$T(n) = T(0) + T(n-1) + cn$$




# Worst-case recursion tree

$$T(n) = T(0) + T(n-1) + cn$$




# Worst-case recursion tree

$$T(n) = T(0) + T(n-1) + cn$$



# Worst-case recursion tree

$$T(n) = T(0) + T(n-1) + cn$$



# Best- and almost-worst case performances

- Best-case happens when pivot is the **median** element, creating equal size partitions.

# Best- and almost-worst case performances

- Best-case happens when pivot is the **median** element, creating equal size partitions.

$$T(n) = 2T(n/2) + \Theta(n) = \Theta(n \lg n)$$



# Best- and almost-worst case performances

- Best-case happens when pivot is the **median** element, creating equal size partitions.

$$T(n) = 2T(n/2) + \Theta(n) = \Theta(n \lg n)$$

- What if the split is always  $\frac{1}{10} : \frac{9}{10}$ ?

# Best- and almost-worst case performances

- Best-case happens when pivot is the **median** element, creating equal size partitions.

$$T(n) = 2T(n/2) + \Theta(n) = \Theta(n \lg n)$$

- What if the split is always  $\frac{1}{10} : \frac{9}{10}$ ?

$$\begin{aligned} T(n) &= T(n/10) + T(9n/10) + \Theta(n) \\ &= \Theta(n \lg n) \quad \triangleright \text{See text for details} \end{aligned}$$

# Best- and almost-worst case performances

- Best-case happens when pivot is the **median** element, creating equal size partitions.

$$T(n) = 2T(n/2) + \Theta(n) = \Theta(n \lg n)$$

- What if the split is always  $\frac{1}{10} : \frac{9}{10}$ ?

$$\begin{aligned} T(n) &= T(n/10) + T(9n/10) + \Theta(n) \\ &= \Theta(n \lg n) \quad \triangleright \text{See text for details} \end{aligned}$$

## Key observation

Very close to worst-case produces  $\Theta(n \lg n)$ , not  $\Theta(n^2)$ .

# Best- and almost-worst case performances

- Best-case happens when pivot is the **median** element, creating equal size partitions.

$$T(n) = 2T(n/2) + \Theta(n) = \Theta(n \lg n)$$

- What if the split is always  $\frac{1}{10} : \frac{9}{10}$ ?

$$\begin{aligned} T(n) &= T(n/10) + T(9n/10) + \Theta(n) \\ &= \Theta(n \lg n) \quad \triangleright \text{See text for details} \end{aligned}$$

## Key observation

Very close to worst-case produces  $\Theta(n \lg n)$ , not  $\Theta(n^2)$ .

How to ensure that we don't *usually* hit the worst-case?

# Contents

- 1 Quicksort
  - Introduction
  - Partitioning
  - Quicksort algorithm
  - Quicksort analysis
  - Randomized Quicksort
  - Conclusion

# Randomized Quicksort

- Pick a **random** pivot and partition around it.

# Randomized Quicksort

- Pick a **random** pivot and partition around it.
- Pivot independent of input order, so no specific input produces worst-case behavior.

# Randomized Quicksort

- Pick a **random** pivot and partition around it.
- Pivot independent of input order, so no specific input produces worst-case behavior.
- The worst-case is determined only by the output of a random number generator.



# Randomized Quicksort

- Pick a **random** pivot and partition around it.
- Pivot independent of input order, so no specific input produces worst-case behavior.
- The worst-case is determined only by the output of a random number generator.

RANDOMIZED-PARTITION( $A, p, r$ )  $\triangleright A[p..r]$

```
1   $i \leftarrow \text{RANDOM}(p, r)$   $\triangleright i = [p..r]$   
2  exchange  $A[p] \leftrightarrow A[i]$   
3  return PARTITION( $A, p, r$ )
```

# Randomized Quicksort

- Pick a **random** pivot and partition around it.
- Pivot independent of input order, so no specific input produces worst-case behavior.
- The worst-case is determined only by the output of a random number generator.

RANDOMIZED-PARTITION( $A, p, r$ )  $\triangleright A[p..r]$

```
1   $i \leftarrow \text{RANDOM}(p, r)$   $\triangleright i = [p..r]$   
2  exchange  $A[p] \leftrightarrow A[i]$   
3  return PARTITION( $A, p, r$ )
```

RANDOMIZED-QUICKSORT( $A, p, r$ )

```
1  if  $p < r$   
2      then  $q \leftarrow \text{RANDOMIZED-PARTITION}(A, p, r)$   
3          RANDOMIZED-QUICKSORT( $A, p, q - 1$ )  
4          RANDOMIZED-QUICKSORT( $A, q + 1, r$ )
```

# Conclusion

- One of the most widely used sorting algorithm.
- While it runs in  $O(n^2)$  time in the worst-case, it runs in  $O(n \lg n)$  time on the average.
- Runs almost twice as fast as merge-sort.
- Can be *tuned* substantially.
- Almost all program language runtime library provide some variant of Quicksort (`java.util.Arrays.sort()` in Java, `qsort()` in C, `std::sort()` in C++, etc).

# Conclusion

- One of the most widely used sorting algorithm.
- While it runs in  $O(n^2)$  time in the worst-case, it runs in  $O(n \lg n)$  time on the average.
- Runs almost twice as fast as merge-sort.
- Can be *tuned* substantially.
- Almost all program language runtime library provide some variant of Quicksort (`java.util.Arrays.sort()` in Java, `qsort()` in C, `std::sort()` in C++, etc).

Questions to ask (and remember)

# Conclusion

- One of the most widely used sorting algorithm.
- While it runs in  $O(n^2)$  time in the worst-case, it runs in  $O(n \lg n)$  time on the average.
- Runs almost twice as fast as merge-sort.
- Can be *tuned* substantially.
- Almost all program language runtime library provide some variant of Quicksort (`java.util.Arrays.sort()` in Java, `qsort()` in C, `std::sort()` in C++, etc).

## Questions to ask (and remember)

- What are the worst, best and average case performances?

# Conclusion

- One of the most widely used sorting algorithm.
- While it runs in  $O(n^2)$  time in the worst-case, it runs in  $O(n \lg n)$  time on the average.
- Runs almost twice as fast as merge-sort.
- Can be *tuned* substantially.
- Almost all program language runtime library provide some variant of Quicksort (`java.util.Arrays.sort()` in Java, `qsort()` in C, `std::sort()` in C++, etc).

## Questions to ask (and remember)

- What are the worst, best and average case performances?
- Is it in-place?

# Conclusion

- One of the most widely used sorting algorithm.
- While it runs in  $O(n^2)$  time in the worst-case, it runs in  $O(n \lg n)$  time on the average.
- Runs almost twice as fast as merge-sort.
- Can be *tuned* substantially.
- Almost all program language runtime library provide some variant of Quicksort (`java.util.Arrays.sort()` in Java, `qsort()` in C, `std::sort()` in C++, etc).

## Questions to ask (and remember)

- What are the worst, best and average case performances?
- Is it in-place?
- Is it stable?