

Contents

DP

D&C DP optimization	1
SOS	1

DS

2DSPARSE TABLE	1
Alien Trick	1
BIT	1
Centroid Decom	1
HASHING	2
HLD and Merge sort tree	2
HLD	3
LINE EQ	3
MOs	3
Persistence trie	3
Trie	3
persistentSegment	4
randomnumber	4
xor_basis	4

Flow

Dinic	5
edmondskarp	5
mcmf	6

General

formulas	6
generate_codebook	6
sublime build	7
template	7

Geometry

Convex hull	7
Geo 2	8
Nearest point	8
geo_2d	8

Graph

Articulation Bridges	13
Bell	13
Block Cut Tree	14
DSU ON Tree	14
DSU	14

LCA	15
euler_path_directed	15
kosaraju	15
mos on trees	15
roll_dsu	15
scc	16

Number Theory Math

CRT	16
Diophantile	16
FFT	16
LSieveBigModTernaryS	17
Miller Rabin	17
NTT	17
ballot	18
matexpo	18
mobius	18
ncr	18
stirling_number	18
totient	19

String

AhoCorasick	19
Manacher	19
Suffix Automata	19
palindromitree	20
suffixArray	20
z kmp	20

DP

D&C DP optimization

```
1 /**
2  Let opt(i, j) be the value of k that minimizes the above
   expression. Assuming that the cost function satisfies
   the quadrangle inequality, we can show that opt(i, j)
   <= opt(i, j + 1) for all
3  i, j. This is known as the monotonicity condition. Then, we
   can apply divide and conquer DP. The optimal "
   splitting point" for a fixed i increases as j
   increases.
4  */
5  int const N = 3e5 + 5, inf = 1e16;
6  int m, n, R = 0, L = 1, res = 0;
7  int ar[N], cnt[N];
8  vector<long long> dp_before, dp_cur;
9  void add(int id) {
10     res += cnt[ar[id]]; cnt[ar[id]]++;
```

```
11 }
12 void Remove(int id) {
13     cnt[ar[id]]--; res -= cnt[ar[id]];
14 }
15 long long C(int l, int r) {
16     while(R < r) add(++R);
17     while(L > l) add(--L);
18     while(L < l) Remove(L++);
19     while(R > r) Remove(R--);
20     return res;
21 }
22 void compute(int l, int r, int optl, int optpr) {
23     if (l > r) return;
24     int mid = (l + r) >> 1;
25     pair<long long, int> best = {LLONG_MAX, -1};
26     for (int k = optl; k <= min(mid, optpr); k++) best = min(
27         best, {(k ? dp_before[k - 1] : 0) + C(k, mid), k});
28     dp_cur[mid] = best.first;
29     int opt = best.second;
30     compute(l, mid - 1, optl, opt); compute(mid + 1, r, opt,
31         optpr);
32 }
33 void solve() {
34     cin >> n >> m;
35     for (int i = 1; i <= n; i++) cin >> ar[i];
36     dp_before.assign(n + 1, 0); dp_cur.assign(n + 1, 0);
37     for (int i = 1; i <= n; i++) dp_before[i] = C(1, i);
38     for (int i = 1; i < m; i++) {
39         compute(1, n, 1, n); dp_before = dp_cur;
40     }
41     cout << dp_before[n] << endl;
```

SOS

```
1  const int B = 20;
2  int a[1 << B], f[1 << B], g[1 << B];
3  void solve() {
4      int n; cin >> n;
5      for (int i = 1; i <= n; i++) {
6          cin >> a[i];
7          f[a[i]]++;
8          g[a[i]]++;
9      }
10     // sum over subsets
11     for (int i = 0; i < B; i++) {
12         for (int mask = 0; mask < (1 << B); mask++) {
13             if ((mask & (1 << i)) != 0) {
14                 f[mask] += f[mask ^ (1 << i)];
15             }
16         }
17     }
18     // sum over supersets
19     for (int i = 0; i < B; i++) {
20         for (int mask = (1 << B) - 1; mask >= 0; mask--) {
21             if ((mask & (1 << i)) == 0) g[mask] += g[mask ^ (1 <<
22                 i)];
23         }
24     }
25     for (int i = 1; i <= n; i++) {
26         cout << f[a[i]] << ' ' << g[a[i]] << ' ' << n - f[(1 <<
27             B) - 1 - a[i]] << '\n';
28     }
```

DS

2DSPARSE TABLE

```

1 const ll N=1000; const ll M=10; ll tab[M+1][M+1][N+1][N
+1]; ll L[N+1]; ll a[N+1][N+1]; ll s[N+1][N+1];
2 struct st2{ ll n,m; void init(ll _n,ll _m){ n=_n; m=_m; for
(ll i=2;i<=N;i++){ L[i]=L[i/2]+1; } } ll g(ll x,ll y,
ll z=0,ll w=0){ return max(x,y,z,w); } void build(){
for(ll i=0;i<n;i++){ for(ll j=0;j<m;j++){ tab[0][0][i
][j]=a[i][j]; } } for(ll y=1;y<=M;y++){ for(ll i=0;i<n
;i++){ for(ll j=0;j<m;j++){ if(j+(1<<y)-1<m) tab[0][y
][i][j]=g(tab[0][y-1][i][j],tab[0][y-1][i][j+(1<<(y-1
))]); } } } for(ll x=1;x<=M;x++){ for(ll i=0;i<n;i++){
for(ll j=0;j<m;j++){ if(i+(1<<x)-1<n) tab[x][0][i][j]=
g(tab[x-1][0][i][j],tab[x-1][0][i+(1<<(x-1))][j]); } }
for(ll x=1;x<=M;x++){ for(ll y=1;y<=M;y++){ for(ll i=0;i<n;i++){
for(ll j=0;j<m;j++){ if(i+(1<<x)-1<n &&
j+(1<<y)-1<m) { tab[x][y][i][j]=g( tab[x-1][y-1][i][j],
tab[x-1][y-1][i+(1<<(x-1))][j], tab[x-1][y-1][i][j
+(1<<(y-1))], tab[x-1][y-1][i+(1<<(x-1))][j+(1<<(y-1))
]); } } } } } ll qry_i(ll x,ll y,ll _x,ll _y){ ll
lx=L[_x-x+1]; ll ly=L[_y-y+1]; return g( tab[lx][ly][x
][y], tab[lx][ly][_x-(1<<lx)+1][y], tab[lx][ly][x][_y
-(1<<(ly))+1], tab[lx][ly][_x-(1<<lx)+1][_y-(1<<(ly))
+1]); } } };

```

Alien Trick

```

1 // Aliens trick on Tree
2 // Maximizes total value using <= K selections
3 struct State {
4     long long val; // best value
5     int cnt; // number of selections
6 };
7 vector<pair<int,int>> g[N]; // {to, weight}
8 int K;
9 // merge two states
10 State merge(State a, State b) {
11     return {a.val + b.val, a.cnt + b.cnt};
12 }
13 State dfs(int u, int p, long long penalty) {
14     State res = {0, 0};
15     for (auto [v, w] : g[u]) {
16         if (v == p) continue;
17         State cur = dfs(v, u, penalty);
18         // choose edge
19         State take = {cur.val + w - penalty, cur.cnt + 1};
20         // choose better
21         if (take.val > cur.val) res = merge(res, take);
22         else res = merge(res, cur);
23     }
24     return res;
25 }
26 // check if we can do with <= K selections
27 bool check(long long penalty) {
28     State res = dfs(1, 0, penalty);
29     return res.cnt <= K;
30 }
31 // binary search on penalty
32 long long solve() {
33     long long lo = -1e12, hi = 1e12;
34     while (lo < hi) {
35         long long mid = (lo + hi + 1) / 2;

```

```

36         if (check(mid)) lo = mid;
37         else hi = mid - 1;
38     }
39     return dfs(1, 0, lo).val + lo * K;
40 }

```

BIT

```

1 struct FenwickTree {
2     vector<int> bit; int n;
3     FenwickTree(int n) {
4         this->n = n; bit.assign(n, 0);
5     }
6     FenwickTree(vector<int> const& a) : FenwickTree(a.size())
7     {
8         for (size_t i = 0; i < a.size(); i++)
9             add(i, a[i]);
10    }
11    int sum(int r) {
12        int ret = 0;
13        for (; r >= 0; r = (r & (r + 1)) - 1)
14            ret += bit[r];
15        return ret;
16    }
17    int sum(int l, int r) {
18        return sum(r) - sum(l - 1);
19    }
20    void add(int idx, int delta) {
21        for (; idx < n; idx = idx | (idx + 1))
22            bit[idx] += delta;
23    }
24 }

```

Centroid Decom

```

1 struct node {
2     vector<int> adj; int sub = 1; int p = -1; // centroid
3     int dep = 0; int vis = 0; // removed (centroid)
4 };
5 node tree[N]; int n; ll ans = 0; int root;
6 /* ----- SUBTREE SIZE ----- */
7 void dfs(int u, int p) {
8     tree[u].sub = 1;
9     for (int v : tree[u].adj) {
10        if (v != p && tree[v].vis == 0) {
11            dfs(v, u);
12            tree[u].sub += tree[v].sub;
13        }
14    }
15 }
16 /* ----- FIND CENTROID ----- */
17 int dfs2(int u, int p, int tot) {
18     for (int v : tree[u].adj) {
19         if (v != p && tree[v].vis == 0 && tree[v].sub > tot /
20             2) {
21             return dfs2(v, u, tot);
22         }
23     }
24     return u;
25 }
26 /* ----- COLLECT LEVEL INFO (OPTIONAL) ----- */
27 /* Keep this if you need depth / distance info */

```

```

27 void nextlev(int u, int p, int d) {
28     tree[u].dep = d;
29     for (int v : tree[u].adj) {
30         if (v != p && tree[v].vis == 0) {
31             nextlev(v, u, d + 1);
32         }
33     }
34 }
35 /* ----- SOLVE FOR A CENTROID ----- */
36 /*
37 // void solve(int c) {
38 // // example placeholder // do calculations using centroid
39 // c
40 // }
41 /* ----- BUILD DECOMPOSITION ----- */
42 void build(int u, int p) {
43     dfs(u, -1);
44     int c = dfs2(u, -1, tree[u].sub);
45     tree[c].p = p;
46     if (p == -1) root = c;
47     // optional: gather depth info from centroid
48     nextlev(c, -1, 0);
49     solve(c);
50     tree[c].vis = 1;
51     for (int v : tree[c].adj) {
52         if (tree[v].vis == 0) {
53             build(v, c);
54         }
55     }
56 }
57 // Build the tree inside main and call build(1, -1);

```

HASHING

```

1 int power(long long n, long long k, const int mod) { int
ans = 1 % mod; n %= mod; if (n < 0) n += mod; while (k
) { if (k & 1) ans = (long long) ans * n % mod; n = (
long long) n * n % mod; k >>= 1; } return ans; } const
int MOD1 = 127657753, MOD2 = 987654319; const int p1
= 137, p2 = 277; int ip1, ip2; pair<int, int> pw[N];
ipw[N]; void prec() { pw[0] = {1, 1}; for (int i = 1;
i < N; i++) { pw[i].first = 1LL * pw[i - 1].first * p1
% MOD1; pw[i].second = 1LL * pw[i - 1].second * p2 %
MOD2; } ip1 = power(p1, MOD1 - 2, MOD1); ip2 = power(
p2, MOD2 - 2, MOD2); ipw[0] = {1, 1}; for (int i = 1;
i < N; i++) { ipw[i].first = 1LL * ipw[i - 1].first *
ip1 % MOD1; ipw[i].second = 1LL * ipw[i - 1].second *
ip2 % MOD2; } } struct Hashing { int n; string s; // 0
- indexed vector<pair<int, int>> hs; // 1 - indexed
// Hashing() {} void init(string _s) { n = _s.size();
s = _s; hs.emplace_back(0, 0); for (int i = 0; i < n;
i++) { pair<int, int> p; p.first = (hs[i].first + 1LL
* pw[i].first * s[i] % MOD1 % MOD1; p.second = (hs[i
].second + 1LL * pw[i].second * s[i] % MOD2 % MOD2;
hs.push_back(p); } } pair<int, int> get_hash(int l,
int r) { // 1 - indexed assert(1 <= l && l <= r && r
<= n); pair<int, int> ans; ans.first = (hs[r].first -
hs[l - 1].first + MOD1) * 1LL * ipw[l - 1].first %
MOD1; ans.second = (hs[r].second - hs[l - 1].second +
MOD2) * 1LL * ipw[l - 1].second % MOD2; return ans; }
pair<int, int> get_hash() { return get_hash(1, n); }
};

```

HLD and Merge sort tree

```

1 typedef struct node {
2     int p;
3     vector<int> adj;
4     int mxchild; int chain; int ind_in_chain; int subtree;
5     int koto; int price;
6 } node;
7 node tree[200010];
8 vector<int> chain(200010);
9 vector<int> start_c(200010);
10 vector<vector<int>> seg(800010);
11 vector<vector<ll>> sum(800010);
12 vector<int> dfs_array(200010);
13 // vector<vector<seg>> segtree(500010);
14 int c;
15 int ind=-1;
16 void dfs(int u, int p) {
17     tree[u].p = p;
18     int mx=0;
19     f(i, tree[u].adj.size()) {
20         int v = tree[u].adj[i];
21         if(p==v) continue;
22         dfs(v,u);
23         tree[u].subtree += tree[v].subtree;
24         if(mx < tree[v].subtree) {mx = tree[v].subtree; tree[u].mxchild = v;}
25     }
26 void hld(int u) {
27     dfs_array[++ind] = u;
28     chain[c]++;
29     // chain[c].push_back(u);
30     tree[u].chain = c;
31     tree[u].ind_in_chain = chain[c] - 1;
32     if(tree[u].mxchild) hld(tree[u].mxchild);
33     f(i, tree[u].adj.size()) {
34         int v = tree[u].adj[i];
35         if(v == tree[u].p || v == tree[u].mxchild) continue;
36         c++;
37         start_c[c] = ind+1;
38         hld(v);
39     }
40 }
41
42 void merge(int ind) {
43     int lsize = seg[2*ind+1].size();
44     int rsize = seg[2*ind+2].size();
45     seg[ind].clear();
46     sum[ind].clear();
47     seg[ind].resize(lsize+rsize);
48     sum[ind].resize(lsize+rsize);
49     int l = 0, r = 0, i=0;
50     while(l < lsize || r < rsize) {
51         if(l==lsize) {
52             seg[ind][i] = (seg[2*ind+2][r]);r++;
53         }
54         else if(r==rsize) {
55             seg[ind][i] = (seg[2*ind+1][l]);l++;
56         }
57         else if(seg[2*ind+1][l] < seg[2*ind+2][r]) {
58             seg[ind][i] = (seg[2*ind+1][l]);l++;
59         }
60         else {
61             seg[ind][i] = (seg[2*ind+2][r]);r++;
62         }

```

```

63         sum[ind][i] = ((l==0 ? 0 : sum[ind*2+1][l-1]) + (r==0
64             ? 0 : sum[ind*2+2][r-1]));
65         i++;
66         // return narr;
67     }
68 void build(vector<int>& arr, int l, int r, int ind) {
69     if(l==r) {
70         l = arr[l];
71         seg[ind].resize(1);
72         sum[ind].resize(1);
73         seg[ind][0] = (tree[l].price);
74         sum[ind][0] = ((ll)tree[l].koto);
75     } else {
76         int m = (l+r)/2;
77         build(arr,l,m,2*ind+1); build(arr,m+1,r,2*ind+2);
78         merge(ind);
79     }
80 }
81
82 ll query(int s, int e, int l, int r, int ind, int tar) {
83     if(s>e) return 0;
84     if(s==l && e==r) {
85         int ans = -1;
86         l = 0, r = seg[ind].size()-1;
87         while(l <= r) {
88             int m = (l+r)/2;
89             if(seg[ind][m] <= tar)
90                 ans = m, l = m+1;
91             else r = m-1;
92         }
93         return ans==-1?0:sum[ind][ans];
94     } else {
95         int m = (l+r)/2;
96         return query(s,min(e,m),l,m,2*ind+1,tar) + query(max(
97             s,m+1),e,m+1,r,2*ind+2,tar);
98     }

```

HLD

```

1 vector<int> parent, depth, heavy, head, pos;
2 int cur_pos;
3 int dfs(int v, vector<vector<int>> const& adj) {
4     int size = 1; int max_c_size = 0;
5     for (int c : adj[v]) {
6         if (c != parent[v]) {
7             parent[c] = v, depth[c] = depth[v] + 1;
8             int c_size = dfs(c, adj); size += c_size;
9             if (c_size > max_c_size)
10                 max_c_size = c_size, heavy[v] = c;
11         }
12     }
13     return size;
14 }
15 void decompose(int v, int h, vector<vector<int>> const& adj) {
16     head[v] = h, pos[v] = cur_pos++;
17     if (heavy[v] != -1) decompose(heavy[v], h, adj);
18     for (int c : adj[v]) {
19         if (c != parent[v] && c != heavy[v]) decompose(c, c,
20             adj);
21     }
22 void init(vector<vector<int>> const& adj) {

```

```

23 int n = adj.size(); parent = vector<int>(n); depth =
24     vector<int>(n);
25 heavy = vector<int>(n, -1); head = vector<int>(n);
26 pos = vector<int>(n); cur_pos = 0;
27 dfs(0, adj);
28 decompose(0, 0, adj);
29 }

```

LINE EQ

```

1 //all solution of ax+by=c in [minx,maxx], [miny,maxy]
2 int gcd(int a, int b, int &x, int &y) { if (b == 0) { x =
3     1; y = 0; return a; } int x1, y1; int d = gcd(b, a % b
4     , x1, y1); x = x1; y = x1 - y1 * (a / b); return d; }
5 bool solve_any(int a, int b, int c, int &x, int &y,
6     int &g) { if (a == 0 && b == 0) { g = x = y = 0;
7     return true; } g = gcd(abs(a), abs(b), x, y); if (c %
8     g != 0) { return false; } x *= (c / g); y *= (c / g);
9     if (a < 0) x = -x; if (b < 0) y = -y; return true; }
10 void shift(int &x, int &y, int a, int b, int cnt) { x
11     += cnt * b; y -= cnt * a; } int solve_all(int a, int b
12     , int c, int minx, int maxx, int miny, int maxy) { int
13     x, y, g; if (!solve_any(a, b, c, x, y, g)) return 0;
14     a /= g; b /= g; int sign_a = a > 0 ? +1 : -1; int
15     sign_b = b > 0 ? +1 : -1; shift(x, y, a, b, (minx - x)
16     / b); if (x < minx) { shift(x, y, a, b, sign_b); } if
17     (x > maxx) return 0; int lx1 = x; shift(x, y, a, b,
18     (maxx - x) / b); if (x > maxx) { shift(x, y, a, b, -
19     sign_b); } int rx1 = x; shift(x, y, a, b, (y - miny) /
20     a); if (y < miny) { shift(x, y, a, b, -sign_a); } if
21     (y > maxy) return 0; int lx2 = x; shift(x, y, a, b,
22     (y - maxy) / a); if (y > maxy) { shift(x, y, a, b,
23     sign_a); } int rx2 = x; if (lx2 > rx2) swap(lx2, rx2);
24     int lx = max(lx1, lx2); int rx = min(rx1, rx2); if (
25     lx > rx) return 0; return (rx - lx) / abs(b) + 1; }
26 void solve() { int a, b, c; cin >> a >> b >> c; int
27     minx, miny, maxx, maxy; cin >> minx >> maxx >> miny >>
28     maxy; if (maxx < minx || maxy < miny) { cout << 0 <<
29     endl; exit(0); } if (a == 0 && b == 0) { if (c == 0) {
30     cout << (maxy - miny + 1) * (maxx - minx + 1) << endl
31     ; } else { cout << 0 << endl; } } else if (a == 0 || b
32     == 0) { if (a == 0) { if (c % b == 0 && (c / b) >=
33     miny && (c / b) <= maxy) { cout << maxx - minx + 1 <<
34     endl; } else { cout << 0 << endl; } } else { if (c % a
35     == 0 && (c / a) >= minx && (c / a) <= maxx) { cout <<
36     maxy - miny + 1 << endl; } else { cout << 0 << endl;
37     } } } else cout << solve_all(a, b, c, minx, maxx, miny
38     , maxy) << endl; }

```

MOs

```

1 const int BLOCK_SIZE = 350;
2 int n, q, ar[N], freq[N], res = 0, ans[10*N];
3 struct Query {
4     int l, r, id;
5     bool operator<(const Query &y) const {
6         int x_block = l / BLOCK_SIZE;
7         int y_block = y.l / BLOCK_SIZE;
8         if(x_block == y_block)
9             return r < y.r;
10        return x_block < y_block;
11    }
12 };

```

```

13 void add(int i) {
14     int x = ar[i]; res -= freq[x] / 2; freq[x]++; res +=
        freq[x] / 2;
15 }
16 void Remove(int i) {
17     int x = ar[i]; res -= freq[x] / 2; freq[x]--; res +=
        freq[x] / 2;
18 }
19 void solve() { // need to reset freq if needed
20     cin >> n;
21     for (int i = 1; i <= n; i++) cin >> ar[i];
22     cin >> q;
23     vector<Query> qr;
24     res = 0; int ii = 0;
25     while(q--) {
26         int l, r; cin >> l >> r; qr.push_back(Query({l, r, ii
            ++}));
27     }
28     sort(qr.begin(), qr.end());
29     int left = 1, right = 0;
30     for (Query q : qr) {
31         int l = q.l, r = q.r;
32         while(right < r) add(++right);
33         while(left > l) add(--left);
34         while(left < l) Remove(left++);
35
36         while(right > r) Remove(right--);
37         ans[q.id] = res;
38     }
39     for (int i = 0; i < ii; i++) cout << ans[i] << "\n";
40 }

```

Persistence trie

```

1 map<ll,ll>root; struct node { ll left = 0, right = 0; ll
    cnt = 0; }; node a[9000001]; ll ptr=2; struct p_trie{
    p_trie() { root[0] = 1; } void insert(ll par_id,ll
    curr_id,ll k){ root[curr_id]=ptr++; ll par_node=root[
    par_id]; ll curr_node=root[curr_id]; for(ll i=30;i>=0;
    i--){ if((k&(1ll<<i))) { a[curr_node].left = a[
    par_node].left; a[curr_node].right = ptr++; curr_node
    = a[curr_node].right; par_node = a[par_node].right; }
    else{ a[curr_node].right=a[par_node].right; a[
    curr_node].left=ptr++; curr_node=a[curr_node].left;
    par_node=a[par_node].left; } a[curr_node].cnt=a[
    par_node].cnt+1; } } ll max_xor(ll id,ll k){ ll curr=
    root[id]; ll ans=0; for(ll i=30;i>=0;i--){ if((k&(1ll
    <<i))){ if(a[curr].left){ ans|=(1ll<<i); curr=a[curr].
    left; }else{ curr=a[curr].right; } }else{ if(a[curr].
    right){ ans|=(1ll<<i); curr=a[curr].right; }else{ curr
    =a[curr].left; } } } return ans; } ll min_xor(ll id,ll
    k){ ll curr=root[id]; ll ans=0; for(ll i=30;i>=0;i--
    ){ if((k&(1ll<<i))){ if(a[curr].right){ curr=a[curr].
    right; }else{ ans|=(1ll<<i); curr=a[curr].left; } }
    else{ if(a[curr].left){ curr=a[curr].left; }else{ ans
    |= (1ll<<i); curr=a[curr].right; } } } return ans; } }

```

Trie

```

1 const int N = 3e5 + 9;
2
3 struct Trie {
4     static const int B = 31;

```

```

5
6 struct node {
7     node* nxt[2];
8     int sz;
9
10    node() {
11        nxt[0] = nxt[1] = NULL;
12        sz = 0;
13    }
14 } *root;
15 Trie() {
16     root = new node();
17 }
18 void insert(int val) {
19     node* cur = root;
20     cur->sz++;
21     for (int i = B - 1; i >= 0; i--) {
22         int b = (val >> i) & 1;
23         if (cur->nxt[b] == NULL)
24             cur->nxt[b] = new node();
25         cur = cur->nxt[b];
26         cur->sz++;
27     }
28 }
29 void remove(int val) {
30     node* cur = root;
31     cur->sz--;
32
33     for (int i = B - 1; i >= 0; i--) {
34         int b = (val >> i) & 1;
35
36         cur = cur->nxt[b];
37         cur->sz--;
38     }
39 }
40 int get_min(int x) {
41     node* cur = root;
42     int ans = 0;
43
44     for (int i = B - 1; i >= 0; i--) {
45         int b = (x >> i) & 1;
46         if (cur->nxt[b] && cur->nxt[b]->sz > 0) {
47             cur = cur->nxt[b];
48         }
49         else {
50             cur = cur->nxt[!b];
51             ans |= (1LL << i);
52         }
53     }
54     return ans;
55 }
56
57 int get_max(int x) {
58     node* cur = root;
59     int ans = 0;
60
61     for (int i = B - 1; i >= 0; i--) {
62         int b = (x >> i) & 1;
63         if (cur->nxt[!b] && cur->nxt[!b]->sz > 0) {
64             cur = cur->nxt[!b];
65             ans |= (1LL << i);
66         }
67         else {
68             cur = cur->nxt[b];
69         }

```

```

70     }
71 }
72 return ans;
73 }
74 int query(int x, int k) {
75     node* cur = root;
76     int ans = 0;
77
78     for (int i = B - 1; i >= 0; i--) {
79         if (cur == NULL) break;
80
81         int b1 = (x >> i) & 1;
82         int b2 = (k >> i) & 1;
83
84         if (b2 == 1) {
85             if (cur->nxt[b1])
86                 ans += cur->nxt[b1]->sz;
87
88             cur = cur->nxt[!b1];
89         }
90         else {
91             cur = cur->nxt[b1];
92         }
93     }
94     return ans;
95 }
96 void del(node* cur) {
97     for (int i = 0; i < 2; i++) {
98         if (cur->nxt[i])
99             del(cur->nxt[i]);
100     }
101     delete cur;
102 }
103 ~Trie() {
104     del(root);
105 }
106 } t;

```

persistentSegment

```

1 struct node {
2     ll sum; node *left, *right;
3     node(ll val = 0) {
4         sum = val; left = right = NULL;
5     }
6     node(node *l, node *r) {
7         left = l; right = r; sum = (l ? l->sum : 0) + (r ? r
            ->sum : 0);
8     }
9 };
10 int n; vector<int> v;
11 node* build(int start, int end) {
12     if (start == end)
13         return new node(v[start]);
14     int mid = (start + end) >> 1;
15     return new node(build(start, mid), build(mid + 1, end));
16 }
17 node* update(node* prev, int pos, ll val, int start, int
    end) {
18     if (start == end) return new node(val);
19     int mid = (start + end) >> 1;
20     if (pos <= mid) return new node(update(prev->left, pos,
        val, start, mid), prev->right);
21     else return new node(prev->left, update(prev->right, pos
        , val, mid + 1, end));

```

```

22 }
23 ll query(node* cur, int l, int r, int start, int end) {
24     if (cur == NULL || start > r || end < l) return 0;
25     if (l <= start && end <= r) return cur->sum;
26     int mid = (start + end) >> 1;
27     return query(cur->left, l, r, start, mid) + query(cur->
        right, l, r, mid + 1, end);
28 }
29 void solve() {
30     cin >> n; v.resize(n);
31     for (int &x : v) cin >> x;
32     vector<node*> roots; roots.push_back(build(0, n - 1));
33     int q; cin >> q;
34     while (q--) {
35         int id; cin >> id;
36         if (id == 1) {
37             int ver, pos; ll val; cin >> ver >> pos >> val;
38             roots.push_back(update(roots[ver], pos - 1, val,
                0, n - 1));
39         } else {
40             int ver, l, r; cin >> ver >> l >> r;
41             cout << query(roots[ver], l - 1, r - 1, 0, n - 1)
                << "\n";
42         }
43     }
44 }

```

randomnumber

```

1 struct custom_hash {
2     static uint64_t splitmix64(uint64_t x) {
3         x += 0x9e3779b97f4a7c15;
4         x = (x ^ (x >> 30)) * 0xbf58476d1ce4e5b9;
5         x = (x ^ (x >> 27)) * 0x94d049bb133111eb;
6         return x ^ (x >> 31);
7     }
8     size_t operator()(uint64_t x) const {
9         static const uint64_t FIXED_RANDOM = chrono::
10             steady_clock::now().time_since_epoch().count();
11         return splitmix64(x + FIXED_RANDOM);}; //For long long int
            to long long int

```

xor_basis

```

1 struct XorBasis {
2     vector<ll> basis;
3     ll N = 0, tmp = 0;
4     void add(ll x) {
5         N++;
6         tmp ^= x;
7         for (ll b : basis) x = min(x, x ^ b);
8         if (!x) return;
9         for (ll &b : basis) if ((b ^ x) < b) b ^= x;
10        basis.push_back(x);
11        sort(basis.rbegin(), basis.rend());
12    }
13    // number of basis vectors (rank)
14    ll size() { return (ll) basis.size(); }
15    // clear everything
16    void clear() { N = 0; tmp = 0; basis.clear(); }
17    // returns true if x can be formed
18    bool possible(ll x) {
19        for (ll b : basis) x = min(x, x ^ b);

```

```

20        return x == 0;
21    }
22    // returns maximum xor value
23    ll maxxor(ll x = 0) {
24        for (ll b : basis) x = max(x, x ^ b);
25        return x;
26    }
27    // returns minimum xor value
28    ll minxor(ll x = 0) {
29        for (ll b : basis) x = min(x, x ^ b);
30        return x;
31    }
32    // returns count of subsets which xor to x (modded)
33    ll cntxor(ll x) {
34        if (!possible(x)) return 0LL;
35        ll freebits = N - size();
36        ll res = 1;
37        while (freebits--) res = (res * 2) % MOD;
38        return res;
39    }
40    // returns sum of xor of all subsets
41    ll sumOfAll() {
42        return tmp * (1LL << (N - 1));
43    }
44 }
45
46 // Ret: #subsets with XOR sum S where (S & x) == x (mod)
47 // O(B^2), B = basis.size()
48 ll cntSuperset(ll x) {
49     vector<ll> tb;
50     for (ll b : basis) {
51         ll v = b & x;
52         for (ll t : tb) v = min(v, v ^ t);
53         if (v) { tb.push_back(v); sort(tb.rbegin(), tb.rend()); }
54     }
55     ll t = x;
56     for (ll b : tb) t = min(t, t ^ b);
57     if (t) return 0;
58     ll f = N - tb.size(), r = 1;
59     while (f--) r = r * 2 % mod;
60     return r;
61 }
62 // Ret: #subsets with XOR sum S where (S & ~x) == 0 (mod) /
63 // O(B^2), B = basis.size()
64 ll cntSubmask(ll x) {
65     vector<ll> tb;
66     for (ll b : basis) {
67         ll v = b & ~x;
68         for (ll t : tb) v = min(v, v ^ t);
69         if (v) { tb.push_back(v); sort(tb.rbegin(), tb.rend()); }
70     }
71     ll f = N - tb.size(), r = 1;
72     while (f--) r = r * 2 % mod;
73     return r;
74 }
75 // returns k-th smallest xor value (1-indexed)
76 ll kth(ll k) {
77     ll sz = size();
78     if (k > (1LL << sz)) return -1;
79     k--;
80     ll ans = 0;

```

```

81     for (ll i = 0; i < sz; i++)
82         if (k >> (sz - 1 - i) & 1) ans ^= basis[i];
83     return ans;
84 }
85 } xb;

```

Flow

Dinic

```

1 #include<bits/stdc++.h>
2 using namespace std;
3
4 const int N = 5010;
5
6 const long long inf = 1LL << 61;
7 struct Dinic {
8     struct edge {
9         int to, rev;
10        long long flow, w;
11        int id;
12    };
13    int n, s, t, mxid;
14    vector<int> d, flow_through;
15    vector<int> done;
16    vector<vector<edge>> g;
17    Dinic() {}
18    Dinic(int _n) {
19        n = _n + 10;
20        mxid = 0;
21        g.resize(n);
22    }
23    void add_edge(int u, int v, long long w, int id = -1) {
24        edge a = {v, (int)g[v].size(), 0, w, id};
25        edge b = {u, (int)g[u].size(), 0, 0, -2}; //for
            bidirectional edges cap(b) = w
26        g[u].emplace_back(a);
27        g[v].emplace_back(b);
28        mxid = max(mxid, id);
29    }
30    bool bfs() {
31        d.assign(n, -1);
32        d[s] = 0;
33        queue<int> q;
34        q.push(s);
35        while (!q.empty()) {
36            int u = q.front();
37            q.pop();
38            for (auto &e : g[u]) {
39                int v = e.to;
40                if (d[v] == -1 && e.flow < e.w) d[v] = d[u] + 1, q.
                    push(v);
41            }
42        }
43        return d[t] != -1;
44    }
45    long long dfs(int u, long long flow) {
46        if (u == t) return flow;
47        for (int &i = done[u]; i < (int)g[u].size(); i++) {
48            edge &e = g[u][i];
49            if (e.w <= e.flow) continue;
50            int v = e.to;
51            if (d[v] == d[u] + 1) {
52                long long nw = dfs(v, min(flow, e.w - e.flow));

```

```

53     if (nw > 0) {
54         e.flow += nw;
55         g[v][e.rev].flow -= nw;
56         return nw;
57     }
58 }
59 }
60 return 0;
61 }
62 long long max_flow(int _s, int _t) {
63     s = _s;
64     t = _t;
65     long long flow = 0;
66     while (bfs()) {
67         done.assign(n, 0);
68         while (long long nw = dfs(s, inf)) flow += nw;
69     }
70     flow_through.assign(mxid + 10, 0);
71     for(int i = 0; i < n; i++) for(auto e : g[i]) if(e.id >=
72         0) flow_through[e.id] = e.flow;
73     return flow;
74 };
75 int main() {
76     int n, m;
77     cin >> n >> m;
78     Dinic F(n + 1);
79     for (int i = 1; i <= m; i++) {
80         int u, v, w;
81         cin >> u >> v >> w;
82         F.add_edge(u, v, w);
83     }
84     cout << F.max_flow(1, n) << '\n';
85     return 0;
86 }

```

edmondskarp

```

1 // edmonds karp ve^2 call while(bfs(n) != 0)
2 typedef struct node {
3     int vis; int p; vector<int> adj; vector<ll> cap;
4 } node;
5 node graph[519];
6 ll bfs(int n) {
7     queue<int> qu;
8     vector<bool> vis(510, 0);
9     vis[1] = 1;
10    qu.push(1);
11    while (!qu.empty()) {
12        int cur = qu.front();
13        // printf("cur-- %d\n", cur);
14        qu.pop();
15        f(i, graph[cur].adj.size()) {
16            int nex = graph[cur].adj[i];
17            if (vis[nex] == 0 && graph[cur].cap[nex] > 0) {
18                graph[nex].p = cur; vis[nex] = 1;
19                if (nex == n) break;
20                qu.push(nex);
21            }
22        }
23    }
24    if (vis[n] == 0) return 0;
25    ll maxflow = LLONG_MAX;
26    int cur = n;
27    while (cur != 1) {

```

```

28        maxflow = min(maxflow, graph[graph[cur].p].cap[cur]);
29        ;
30        cur = graph[cur].p;
31        // printf("%d ", cur);
32    }
33    // printf("max %d\n", maxflow);
34    cur = n;
35    while (cur != 1) {
36        graph[graph[cur].p].cap[cur] -= maxflow;
37        graph[cur].cap[graph[cur].p] += maxflow;
38        cur = graph[cur].p;
39    }
40    return maxflow;
41 }
42 // call after getting max flow
43 vector<int> getCut(int n) {
44     vector<int> vis(510, 0);
45     queue<int> q;
46     q.push(1);
47     vis[1] = 1;
48     while (!q.empty()) {
49         int u = q.front(); q.pop();
50         for (int v : graph[u].adj) {
51             if (!vis[v] && graph[u].cap[v] > 0) { // residual
52                 capacity
53                 vis[v] = 1;
54                 q.push(v);
55             }
56         }
57     }
58     return vis; // vis[v] = 1 -> reachable -> S-side

```

mcmf

```

1 struct Edge
2 {
3     int from, to, capacity, cost;
4 };
5 vector<vector<int>> adj, cost, capacity;
6 const int INF = 1e9;
7 void shortest_paths(int n, int v0, vector<int>& d, vector<
8     int>& p) {
9     d.assign(n, INF);
10    d[v0] = 0;
11    vector<bool> inq(n, false);
12    queue<int> q;
13    q.push(v0);
14    p.assign(n, -1);
15    while (!q.empty()) {
16        int u = q.front();
17        q.pop();
18        inq[u] = false;
19        for (int v : adj[u]) {
20            if (capacity[u][v] > 0 && d[v] > d[u] + cost[u][v]) {
21                d[v] = d[u] + cost[u][v];
22                p[v] = u;
23                if (!inq[v]) {
24                    inq[v] = true;
25                    q.push(v);
26                }
27            }
28        }
29    }

```

```

28    }
29 }
30 int min_cost_flow(int N, vector<Edge> edges, int K, int s,
31     int t) {
32     adj.assign(N, vector<int>());
33     cost.assign(N, vector<int>(N, 0));
34     capacity.assign(N, vector<int>(N, 0));
35     for (Edge e : edges) {
36         adj[e.from].push_back(e.to);
37         adj[e.to].push_back(e.from);
38         cost[e.from][e.to] = e.cost;
39         cost[e.to][e.from] = -e.cost;
40         capacity[e.from][e.to] = e.capacity;
41     }
42     int flow = 0;
43     int cost = 0;
44     vector<int> d, p;
45     while (flow < K) {
46         shortest_paths(N, s, d, p);
47         if (d[t] == INF)
48             break;
49         // find max flow on that path
50         int f = K - flow;
51         int cur = t;
52         while (cur != s) {
53             f = min(f, capacity[p[cur]][cur]);
54             cur = p[cur];
55         }
56         // apply flow
57         flow += f;
58         cost += f * d[t];
59         cur = t;
60         while (cur != s) {
61             capacity[p[cur]][cur] -= f;
62             capacity[cur][p[cur]] += f;
63             cur = p[cur];
64         }
65         if (flow < K)
66             return -1;
67         else
68             return cost;
69     }

```

General formulas

```

1 /* ----- POLYGON -----
2 Area of polygon (shoelace):
3 Area = 0.5 * |sum(x[i]*y[i+1] - x[i+1]*y[i])|
4 Centroid of polygon:
5 Cx = sum((xi + xi+1) * cross(i, i+1)) / (6*Area)
6 Cy = sum((yi + yi+1) * cross(i, i+1)) / (6*Area)
7 Point inside polygon (ray casting):
8 Count intersections of ray to +x
9 Odd = inside, Even = outside
10 Convex polygon point inside:
11 For all edges (Pi, Pi+1):
12 cross(Pi+1-Pi, X-Pi) >= 0 (or <=0 consistently)
13 */
14 /* ----- TRIANGLE -----
15 Area using cross:
16 Area = |cross(B-A, C-A)| / 2

```

```

17 Circumcenter:
18 Intersection of perpendicular bisectors
19 (Omitted formula compute via lines)
20 Incenter:
21  $I = (a*A + b*B + c*C) / (a+b+c)$ 
22 where:
23 Centroid:
24  $G = (A+B+C)/3$ 
25 Orthocenter:
26  $H = A + B + C - 2*O$  ( $O$  = circumcenter)
27 Radius:
28 Inradius  $r = \text{Area} / s$ 
29 Circumradius  $R = (a*b*c) / (4*\text{Area})$ 
30 Angle between vectors:
31  $\cos(\theta) = \text{dot}(u,v) / (|u||v|)$ 
32 */
33 /* ----- COMBINATORICS & MATH -----
34 Stirling Numbers of the Second Kind  $S(n,k)$  Parity:
35 Odd =  $((n - k) \& ((k - 1) / 2)) == 0$ 
36 Even = otherwise
37
38 Sum of Powers (Faulhaber's Formula):
39 // Based on image_362f5e.png
40  $\text{sum}(k^p \text{ for } k=1..n = (1 / (p + 1)) * \text{sum}_{r=0 \text{ to } p} [ C(p$ 
41  $+1, r) * B_r * n^{(p+1-r)} ]$ 
42 * Note:  $B_r$  represents the  $r$ -th Bernoulli number (using  $B_1$ 
43  $\hat{+} = +1/2$ ).
44
45 Bracket Arrangements:
46 // DP[i][j]: ways to arrange  $i$  pairs of brackets into  $j$ 
47 valid non-empty blocks
48  $\text{DP}[i][j] = (j * C(2i - j, i - j) * \text{inv}(2i - j)) \% M$ 
49 */

```

generate_codebook

```

1 import os
2 import subprocess
3 import sys
4
5 ALLOWED_EXTENSIONS = {
6     ".cpp": "C++",
7     ".cc": "C++",
8     ".h": "C++",
9     ".hpp": "C++",
10    ".py": "Python",
11    ".java": "Java",
12 }
13
14 IGNORE_DIRS = {".git", ".github", "build", "__pycache__"}
15
16 def escape_latex(text: str) -> str:
17     replacements = {
18         "\\": r"\textbackslash{}",
19         "_": r"\_",
20         "%": r"\%",
21         "$": r"\$",
22         "#": r"\#",
23         "&": r"\&",
24         "{": r"\{",
25         "}": r"\}",
26         "~": r"\textasciitilde{}",
27         "^": r"\textasciicircum{}",
28     }
29

```

```

30 for char, rep in replacements.items():
31     text = text.replace(char, rep)
32     return text
33
34 def collect_files():
35     tree = {}
36     for root, dirs, files in os.walk("."):
37         dirs[:] = [d for d in dirs if d not in IGNORE_DIRS
38                     and not d.startswith(".")]
39         rel_dir = os.path.relpath(root, ".")
40         valid_files = [
41             f for f in sorted(files) if os.path.splitext(f)[1]
42             in ALLOWED_EXTENSIONS
43         ]
44         if valid_files:
45             section_name = "General" if rel_dir == "." else
46                 rel_dir
47             tree[section_name] = [
48                 os.path.join(root, f).replace("\\", "/") for f
49                 in valid_files
50             ]
51     return tree
52
53 def build_latex_document(tree, is_color: bool) -> str:
54     color_definitions = (
55         r"""
56         \definecolor{kwcolor}{rgb}{0.0, 0.2, 0.8}
57         \definecolor{cmtcolor}{rgb}{0.0, 0.5, 0.0}
58         \definecolor{strcolor}{rgb}{0.7, 0.1, 0.1}
59         \definecolor{numcolor}{rgb}{0.4, 0.4, 0.4}
60         \definecolor{framecolor}{rgb}{0.7, 0.7, 0.7}
61         """
62         if is_color
63         else r"""
64         \definecolor{kwcolor}{rgb}{0.0, 0.0, 0.0}
65         \definecolor{cmtcolor}{rgb}{0.2, 0.2, 0.2}
66         \definecolor{strcolor}{rgb}{0.0, 0.0, 0.0}
67         \definecolor{numcolor}{rgb}{0.3, 0.3, 0.3}
68         \definecolor{framecolor}{rgb}{0.0, 0.0, 0.0}
69         """
70     )
71     doc = [
72         r"\documentclass[9pt,landscape,a4paper]{article}",
73         r"\usepackage[left=0.8cm,right=0.8cm,top=1.2cm,bottom=1.2cm]{geometry}",
74         r"\usepackage{multicol}",
75         r"\usepackage{listings}",
76         r"\usepackage{xcolor}",
77         r"\usepackage{fancyhdr}",
78         r"\usepackage{titlesec}",
79         r"\usepackage{tocloft}",
80         r"\usepackage{courier}",
81         color_definitions,
82         r"\lstset{",
83         r"  basicstyle=\ttfamily\scriptsize,",
84         r"  keywordstyle=\bfseries\color{kwcolor},",
85         r"  commentstyle=\itshape\color{cmtcolor},",
86         r"  stringstyle=\color{strcolor},",
87         r"  numberstyle=\tiny\color{numcolor},",
88         r"  numbers=left,",
89         r"  stepnumber=1,",
90         r"  numbersep=4pt,",

```

```

91     r"  frame=single,",
92     r"  rulecolor=\color{framecolor},",
93     r"  tabsize=2,",
94     r"  breaklines=true,",
95     r"  breakatwhitespace=false,",
96     r"  showstringspaces=false,",
97     r"  columns=fullflexible,",
98     r"  xleftmargin=12pt",
99     r"}",
100     r"\pagestyle{fancy}",
101     r"\fancyhf{}",
102     r"\fancyhead[L]{\textbf{Algorithmic Code Library}}",
103     (
104         r"\fancyhead[C]{\textit{Color Edition}}"
105         if is_color
106         else r"\fancyhead[C]{\textit{B\&W Edition}}"
107     ),
108     r"\fancyhead[R]{\thepage}",
109     r"\renewcommand{\headrulewidth}{0.4pt}",
110     r"\titlespacing*{\section}{0pt}{4pt}{2pt}",
111     r"\titlespacing*{\subsection}{0pt}{3pt}{1pt}",
112     r"\begin{document}",
113     r"\begin{multicols*}{3}",
114     r"\tableofcontents",
115     r"\vspace{10pt}",
116     r"\hrule",
117     r"\vspace{10pt}",
118 ]
119
120 for section, files in sorted(tree.items()):
121     doc.append(f"\section*{{{escape_latex(section)}}}")
122     doc.append(f"\addcontentsline{{toc}}{{section}}{{{escape_latex(section)}}}")
123
124 for file_path in files:
125     file_name = os.path.basename(file_path)
126     title = os.path.splitext(file_name)[0]
127     ext = os.path.splitext(file_name)[1]
128     lang = ALLOWED_EXTENSIONS.get(ext, "C++")
129
130     doc.append(f"\subsection*{{{escape_latex(title)}}}")
131     doc.append(
132         f"\addcontentsline{{toc}}{{subsection}}{{{escape_latex(title)}}}"
133     )
134     doc.append(
135         f"\lstinputlisting[language={lang}]{{{file_path}}}"
136     )
137     doc.append(r"\end{multicols*}")
138     doc.append(r"\end{document}")
139     return "\n".join(doc)
140
141 def compile_latex(tex_name: str):
142     # Run twice so table of contents page numbers compute correctly
143     for _ in range(2):
144         cmd = ["pdflatex", "-interaction=nonstopmode", tex_name]
145         # We capture the output but don't immediately crash on a non-zero return code
146         subprocess.run(cmd, stdout=subprocess.PIPE, stderr=subprocess.PIPE)

```

```

147 # Instead of checking the strict return code, check if
148 the PDF actually generated
149 pdf_name = tex_name.replace(".tex", ".pdf")
150 if not os.path.exists(pdf_name):
151     print(f"Error: {pdf_name} was not generated!")
152     sys.exit(1)
153
154 def main():
155     tree = collect_files()
156     if not tree:
157         print("No source code files found to compile.")
158         sys.exit(1)
159
160 # 1. Color Edition
161 with open("codebook_color.tex", "w", encoding="utf-8")
162     as f:
163         f.write(build_latex_document(tree, is_color=True))
164     compile_latex("codebook_color.tex")
165
166 # 2. Black & White Edition
167 with open("codebook_bw.tex", "w", encoding="utf-8") as f:
168     :
169     f.write(build_latex_document(tree, is_color=False))
170     compile_latex("codebook_bw.tex")
171
172 print("Successfully built codebook_color.pdf and
173 codebook_bw.pdf")
174
175 if __name__ == "__main__":
176     main()

```

sublime build

```

1 {
2     "cmd" : ["g++ -std=c++20 $file_name -o $file_base_name &&
3         timeout 5s ./ $file_base_name<input.txt>output.txt"
4     ],
5     "selector" : "source.cpp",
6     "shell": true
7     // "working_dir" : "$file_path"
8 }

```

template

```

1 #include<bits/stdc++.h>
2 using namespace std;
3 #define endl '\n'
4 #include <ext/pb_ds/assoc_container.hpp>
5 #include <ext/pb_ds/tree_policy.hpp>
6 using namespace __gnu_pbds;
7 #define int long long
8 typedef tree<int, null_type, less<int>, rb_tree_tag,
9     tree_order_statistics_node_update> o_set;
10 typedef tree<int, null_type, less_equal<int>, rb_tree_tag,
11     tree_order_statistics_node_update> o_multiset;
12 mt19937 rng(chrono::steady_clock::now().time_since_epoch().
13     count());
14 void solve() { //order_of_key, find_by_order }
15 int32_t main() {
16     ios::sync_with_stdio(false); cin.tie(nullptr);
17     int tc = 1; cin >> tc;

```

```

15 for(int i = 1; i <= tc; i++) { solve(); } return 0;
16 }

```

Geometry

Convex hull

```

1 vector<PT> convex_hull(vector<PT> &p) {
2     if (p.size() <= 1) return p;
3     vector<PT> v = p;
4     sort(v.begin(), v.end());
5     vector<PT> up, dn;
6     for (auto& p : v) {
7         while (up.size() > 1 && orientation(up[up.size() -
8             2], up.back(), p) >= 0) {
9             up.pop_back();
10        }
11        while (dn.size() > 1 && orientation(dn[dn.size() -
12            2], dn.back(), p) <= 0) {
13            dn.pop_back();
14        }
15        up.push_back(p);
16        dn.push_back(p);
17    }
18    v = dn;
19    if (v.size() > 1) v.pop_back();
20    reverse(up.begin(), up.end());
21    up.pop_back();
22    for (auto& p : up) {
23        v.push_back(p);
24    }
25    if (v.size() == 2 && v[0] == v[1]) v.pop_back();
26    return v;
27 }
28 //checks if convex or not
29 bool is_convex(vector<PT> &p) {
30     bool s[3]; s[0] = s[1] = s[2] = 0;
31     int n = p.size();
32     for (int i = 0; i < n; i++) {
33         int j = (i + 1) % n;
34         int k = (j + 1) % n;
35         s[(sign(cross(p[j] - p[i], p[k] - p[i])) + 1) = 1;
36         if (s[0] && s[2]) return 0;
37     }
38     return 1;
39 }

```

Geo 2

```

1 struct point { int x, y, idx; }; //Finds squared euclidean
2 distance between two points int dist(point &a, point &b) {
3     return (a.x-b.x)*(a.x-b.x) + (a.y-b.y)*(a.y-b.y);
4 } //Checks if angle ABC is a right angle int
5 isOrthogonal(point &a, point &b, point &c) { return (b
6     .x-a.x) * (b.x-c.x) + (b.y-a.y) * (b.y-c.y) == 0; } //
7 Checks if ABCD form a rectangle (in that order) int
8 isRectangle(point &a, point &b, point &c, point &d) {
9     return isOrthogonal(a, b, c) && isOrthogonal(b, c, d)
10    && isOrthogonal(c, d, a); } //Checks if ABCD form a
11 rectangle, in any orientation int isRectangleAnyOrder(
12 point &a, point &b, point &c, point &d) { return
13 isRectangle(a, b, c, d) || isRectangle(b, c, a, d) |

```

```

isRectangle(c, a, b, d); } //Checks if ABCD form a
square (in that order) int isSquare(point &a, point &b
, point &c, point &d) { return isRectangle(a, b, c, d)
&& dist(a, b) == dist(b, c); } //Checks if ABCD form
a square, in any orientation int isSquareAnyOrder(
point &a, point &b, point &c, point &d) { return
isSquare(a, b, c, d) || isSquare(b, c, a, d) |
isSquare(c, a, b, d); }

```

Nearest point

```

1 const int N = 1<<17; const long long INF =
2 2000000000000000000; struct vp_node { long long
3 threshold; pair < int, int > center; vp_node *left, *
4 right; }; typedef vp_node *node_ptr; int tests, n; pair
5 < int, int > pts[N], arr[N]; long long ans; node_ptr
6 root; long long squared_distance(pair < int, int > a,
7 pair < int, int > b) { return (a.first-b.first)*1ll*(a
8 .first-b.first) + (a.second-b.second)*1ll*(a.second-b
9 .second); } struct cmp_points { pair < int, int > a;
10 cmp_points(){} cmp_points(pair < int, int > p): a(p)
11 {} bool operator () (const pair < int, int > &x, const
12 pair < int, int > &y) const { return squared_distance
13 (a,x)<squared_distance(a,y); } }; void build(node_ptr
14 &node, int a, int b) { if(a>b) { node=NULL; return; }
15 node=new vp_node(); if(a==b) { node->threshold=0; node
16 ->center=arr[a]; node->left=NULL; node->right=NULL;
17 return; } int pos=a+rand()% (b-a+1); swap(arr[a], arr[
18 pos]); node->center=arr[pos]; sort(arr+pos, arr+b+1,
19 cmp_points(arr[pos])); node->threshold=squared_distance(
20 arr[pos], arr[(a+b)>>1]); build(node->left, a, (a+b)>>1);
21 build(node->right, ((a+b)>>1)+1, b); } void query(
22 node_ptr &node, pair < int, int > q, long long &ans) {
23 if(node==NULL) return; if(node->center!=q) ans=min(
24 ans, squared_distance(node->center, q)); if(node->left==
25 NULL && node->right==NULL) { return; } if(
26 squared_distance(q, node->center) <= node->threshold) {
27 query(node->left, q, ans); if(sqrt(squared_distance(node
28 ->center, q))+sqrt(ans)>sqrt(node->threshold)) query(
29 node->right, q, ans); } else { query(node->right, q, ans);
30 if(sqrt(squared_distance(node->center, q))-sqrt(ans)<
31 sqrt(node->threshold)) query(node->left, q, ans); } }
32 int main() { int i; scanf("%d", &tests); while(tests
33 --) { scanf("%d", &n); for(i=1; i<=n; i++) { scanf("%d %
34 d", &arr[i].first, &arr[i].second); pts[i]=arr[i]; }
35 build(root, 1, n); for(i=1; i<=n; i++) { ans=INF; query(
36 root, pts[i], ans); printf("%lld\n", ans); } } return 0;
37 }

```

geo_2d

```

1 const double PI = acos((-1.0)); int sign(double x) {
2     return (x > eps) - (x < -eps); } struct PT { double x,
3     y; PT() { x = 0, y = 0; } PT(double x, double y) : x(
4     x), y(y) {} PT(const PT &p) : x(p.x), y(p.y) {} PT
5     operator + (const PT &a) const { return PT(x + a.x, y
6     + a.y); } PT operator - (const PT &a) const { return
7     PT(x - a.x, y - a.y); } PT operator * (const double a)
8     const { return PT(x * a, y * a); } friend PT operator
9     * (const double &a, const PT &b) { return PT(a * b.x,
10     a * b.y); } PT operator / (const double a) const {
11     return PT(x / a, y / a); } bool operator == (PT a)
12     const { return sign(a.x - x) == 0 && sign(a.y - y) ==

```

```

0; } bool operator != (PT a) const { return !(*this ==
a); } bool operator < (PT a) const { return sign(a.x
- x) == 0 ? y < a.y : x < a.x; } bool operator > (PT a
) const { return sign(a.x - x) == 0 ? y > a.y : x > a
.x; } double norm() { return sqrt(x * x + y * y); }
double norm2() { return x * x + y * y; } PT perp() {
return PT(-y, x); } double arg() { return atan2(y, x);
} PT truncate(double r) { // returns a vector with
norm r and having same direction double k = norm(); if
(!sign(k)) return *this; r /= k; return PT(x * r, y *
r); } };
2 istream &operator >> (istream &in, PT &p) { return in >> p.
x >> p.y; }
3 ostream &operator << (ostream &out, PT &p) { return out <<
"(" << p.x << ", " << p.y << ")"; }
4 inline double dot(PT a, PT b) { return a.x * b.x + a.y * b.
y; }
5 inline double dist2(PT a, PT b) { return dot(a - b, a - b);
}
6 inline double dist(PT a, PT b) { return sqrt(dot(a - b, a -
b)); }
7 inline double cross(PT a, PT b) { return a.x * b.y - a.y *
b.x; }
8 inline double cross2(PT a, PT b, PT c) { return cross(b - a
, c - a); }
9 inline int orientation(PT a, PT b, PT c) { return sign(
cross(b - a, c - a)); }
10 PT perp(PT a) { return PT(-a.y, a.x); }
11 PT rotateccw90(PT a) { return PT(-a.y, a.x); }
12 PT rotatecw90(PT a) { return PT(a.y, -a.x); }
13 PT rotateccw(PT a, double t) { return PT(a.x * cos(t) - a.y
* sin(t), a.x * sin(t) + a.y * cos(t)); }
14 PT rotatecw(PT a, double t) { return PT(a.x * cos(t) + a.y
* sin(t), -a.x * sin(t) + a.y * cos(t)); }
15 double SQ(double x) { return x * x; }
16 double rad_to_deg(double r) { return (r * 180.0 / PI); }
17 double deg_to_rad(double d) { return (d * PI / 180.0); }
18 double get_angle(PT a, PT b) {
19     double costheta = dot(a, b) / a.norm() / b.norm();
20     return acos(max((double)-1.0, min((double)1.0, costheta)
)); }
21 }
22 bool is_point_in_angle(PT b, PT a, PT c, PT p) { // does
point p lie in angle <bac
23     assert(orientation(a, b, c) != 0);
24     if (orientation(a, c, b) < 0) swap(b, c);
25     return orientation(a, c, p) >= 0 && orientation(a, b, p)
<= 0;
26 }
27 bool half(PT p) {
28     return p.y > 0.0 || (p.y == 0.0 && p.x < 0.0);
29 }
30 void polar_sort(vector<PT> &v) { // sort points in
counterclockwise
31     sort(v.begin(), v.end(), [](PT a, PT b) {
32         return make_tuple(half(a), 0.0, a.norm2()) <
make_tuple(half(b), cross(a, b), b.norm2());
33     });
34 }
35 void polar_sort(vector<PT> &v, PT o) { // sort points in
counterclockwise with respect to point o
36     sort(v.begin(), v.end(), [&](PT a, PT b) {
37         return make_tuple(half(a - o), 0.0, (a - o).norm2())
< make_tuple(half(b - o), cross(a - o, b - o), (
b - o).norm2());
38     });
39 }
40 struct line {
41     PT a, b; // goes through points a and b
42     PT v; double c; //line form: direction vec [cross] (x, y
) = c
43     line() {}
44     //direction vector v and offset c
45     line(PT v, double c) : v(v), c(c) {
46         auto p = get_points();
47         a = p.first; b = p.second;
48     }
49     // equation ax + by + c = 0
50     line(double _a, double _b, double _c) : v((_b, -_a)), c(-
_c) {
51         auto p = get_points();
52         a = p.first; b = p.second;
53     }
54     // goes through points p and q
55     line(PT p, PT q) : v(q - p), c(cross(v, p)), a(p), b(q)
{}
56     pair<PT, PT> get_points() { //extract any two points
from this line
57         PT p, q; double a = -v.y, b = v.x; // ax + by = c
58         if (sign(a) == 0) {
59             p = PT(0, c / b); q = PT(1, c / b);
60         }
61         else if (sign(b) == 0) {
62             p = PT(c / a, 0); q = PT(c / a, 1);
63         }
64         else {
65             p = PT(0, c / b); q = PT(1, (c - a) / b);
66         }
67         return {p, q};
68     }
69     // ax + by + c = 0
70     array<double, 3> get_abc() {
71         double a = -v.y, b = v.x; return {a, b, -c};
72     }
73     // 1 if on the left, -1 if on the right, 0 if on the
line
74     int side(PT p) { return sign(cross(v, p) - c); }
75     // line that is perpendicular to this and goes through
point p
76     line perpendicular_through(PT p) { return {p, p + perp(v
)}; }
77     // translate the line by vector t i.e. shifting it by
vector t
78     line translate(PT t) { return {v, c + cross(v, t)}; }
79     // compare two points by their orthogonal projection on
this line
80     // a projection point comes before another if it comes
first according to vector v
81     bool cmp_by_projection(PT p, PT q) { return dot(v, p) <
dot(v, q); }
82     line shift_left(double d) {
83         PT z = v.perp().truncate(d);
84         return line(a + z, b + z);
85     }
86 };
87 // find a point from a through b with distance d
88 PT point_along_line(PT a, PT b, double d) {
89     assert(a != b);
90     return a + ((b - a) / (b - a).norm()) * d;
91 }
92 // projection point c onto line through a and b assuming a
!= b
93 PT project_from_point_to_line(PT a, PT b, PT c) {
94     return a + (b - a) * dot(c - a, b - a) / (b - a).norm2()
;
95 }
96 // reflection point c onto line through a and b assuming a
!= b
97 PT reflection_from_point_to_line(PT a, PT b, PT c) {
98     PT p = project_from_point_to_line(a, b, c);
99     return p + p - c;
100 }
101 // minimum distance from point c to line through a and b
102 double dist_from_point_to_line(PT a, PT b, PT c) {
103     return fabs(cross(b - a, c - a) / (b - a).norm());
104 }
105 // returns true if point p is on line segment ab
106 bool is_point_on_seg(PT a, PT b, PT p) {
107     if (fabs(cross(p - b, a - b)) < eps) {
108         if (p.x < min(a.x, b.x) - eps || p.x > max(a.x, b.x)
+ eps) return false;
109         if (p.y < min(a.y, b.y) - eps || p.y > max(a.y, b.y)
+ eps) return false;
110         return true;
111     }
112     return false;
113 }
114 // minimum distance point from point c to segment ab that
lies on segment ab
115 PT project_from_point_to_seg(PT a, PT b, PT c) {
116     double r = dist2(a, b);
117     if (sign(r) == 0) return a;
118     r = dot(c - a, b - a) / r;
119     if (r < 0) return a;
120     if (r > 1) return b;
121     return a + (b - a) * r;
122 }
123 // minimum distance from point c to segment ab
124 double dist_from_point_to_seg(PT a, PT b, PT c) {
125     return dist(c, project_from_point_to_seg(a, b, c));
126 }
127 // 0 if not parallel, 1 if parallel, 2 if collinear
128 int is_parallel(PT a, PT b, PT c, PT d) {
129     double k = fabs(cross(b - a, d - c));
130     if (k < eps) {
131         if (fabs(cross(a - b, a - c)) < eps && fabs(cross(c -
d, c - a)) < eps) return 2;
132         else return 1;
133     }
134     else return 0;
135 }
136 // check if two lines are same
137 bool are_lines_same(PT a, PT b, PT c, PT d) {
138     if (fabs(cross(a - c, c - d)) < eps && fabs(cross(b - c,
c - d)) < eps) return true;
139     return false;
140 }
141 // bisector vector of <abc
142 PT angle_bisector(PT &a, PT &b, PT &c) {
143     PT p = a - b, q = c - b;
144     return p + q * sqrt(dot(p, p) / dot(q, q));
145 }
146 // 1 if point is ccw to the line, 2 if point is cw to the
line, 3 if point is on the line
147 int point_line_relation(PT a, PT b, PT p) {

```

```

148 int c = sign(cross(p - a, b - a));
149 if (c < 0) return 1;
150 if (c > 0) return 2;
151 return 3;
152 }
153 // intersection point between ab and cd assuming unique
    intersection exists
154 bool line_line_intersection(PT a, PT b, PT c, PT d, PT &ans
    ) {
155     double a1 = a.y - b.y, b1 = b.x - a.x, c1 = cross(a, b);
156     double a2 = c.y - d.y, b2 = d.x - c.x, c2 = cross(c, d);
157     double det = a1 * b2 - a2 * b1;
158     if (det == 0) return 0;
159     ans = PT((b1 * c2 - b2 * c1) / det, (c1 * a2 - a1 * c2)
        / det);
160     return 1;
161 }
162 // intersection point between segment ab and segment cd
    assuming unique intersection exists
163 bool seg_seg_intersection(PT a, PT b, PT c, PT d, PT &ans)
    {
164     double oa = cross2(c, d, a), ob = cross2(c, d, b);
165     double oc = cross2(a, b, c), od = cross2(a, b, d);
166     if (oa * ob < 0 && oc * od < 0) {
167         ans = (a * ob - b * oa) / (ob - oa);
168         return 1;
169     }
170     else return 0;
171 }
172 // intersection point between segment ab and segment cd
    assuming unique intersection may not exists
173 // se.size()==0 means no intersection
174 // se.size()==1 means one intersection
175 // se.size()==2 means range intersection
176 set<PT> seg_seg_intersection_inside(PT a, PT b, PT c, PT d)
    {
177     PT ans;
178     if (seg_seg_intersection(a, b, c, d, ans)) return {ans};
179     set<PT> se;
180     if (is_point_on_seg(c, d, a)) se.insert(a);
181     if (is_point_on_seg(c, d, b)) se.insert(b);
182     if (is_point_on_seg(a, b, c)) se.insert(c);
183     if (is_point_on_seg(a, b, d)) se.insert(d);
184     return se;
185 }
186 // intersection between segment ab and line cd
187 // 0 if do not intersect, 1 if proper intersect, 2 if
    segment intersect
188 int seg_line_relation(PT a, PT b, PT c, PT d) {
189     double p = cross2(c, d, a);
190     double q = cross2(c, d, b);
191     if (sign(p) == 0 && sign(q) == 0) return 2;
192     else if (p * q < 0) return 1;
193     else return 0;
194 }
195 // intersection between segment ab and line cd assuming
    unique intersection exists
196 bool seg_line_intersection(PT a, PT b, PT c, PT d, PT &ans)
    {
197     bool k = seg_line_relation(a, b, c, d);
198     assert(k != 2);
199     if (k) line_line_intersection(a, b, c, d, ans);
200     return k;
201 }
202 // minimum distance from segment ab to segment cd

```

```

203 double dist_from_seg_to_seg(PT a, PT b, PT c, PT d) {
204     PT dummy;
205     if (seg_seg_intersection(a, b, c, d, dummy)) return 0.0;
206     else return min({dist_from_point_to_seg(a, b, c),
        dist_from_point_to_seg(a, b, d),
        dist_from_point_to_seg(c, d, a),
        dist_from_point_to_seg(c, d, b)});
207 }
208 // minimum distance from point c to ray (starting point a
    and direction vector b)
209 double dist_from_point_to_ray(PT a, PT b, PT c) {
210     b = a + b;
211     double r = dot(c - a, b - a);
212     if (r < 0.0) return dist(c, a);
213     return dist_from_point_to_line(a, b, c);
214 }
215 // starting point as and direction vector ad
216 bool ray_ray_intersection(PT as, PT ad, PT bs, PT bd) {
217     double dx = bs.x - as.x, dy = bs.y - as.y;
218     double det = bd.x * ad.y - bd.y * ad.x;
219     if (fabs(det) < eps) return 0;
220     double u = (dy * bd.x - dx * bd.y) / det;
221     double v = (dy * ad.x - dx * ad.y) / det;
222     if (sign(u) >= 0 && sign(v) >= 0) return 1;
223     else return 0;
224 }
225 double ray_ray_distance(PT as, PT ad, PT bs, PT bd) {
226     if (ray_ray_intersection(as, ad, bs, bd)) return 0.0;
227     double ans = dist_from_point_to_ray(as, ad, bs);
228     ans = min(ans, dist_from_point_to_ray(bs, bd, as));
229     return ans;
230 }
231 struct circle {
232     PT p; double r;
233     circle() {}
234     circle(PT p, double r): p(p), r(r) {};
235     // center (x, y) and radius r
236     circle(double x, double y, double r): p(PT(x, y)), r(r)
        {} {};
237     // circumcircle of a triangle
238     // the three points must be unique
239     circle(PT a, PT b, PT c) {
240         b = (a + b) * 0.5;
241         c = (a + c) * 0.5;
242         line_line_intersection(b, b + rotatecw90(a - b), c, c
            + rotatecw90(a - c), p);
243         r = dist(a, p);
244     }
245     // inscribed circle of a triangle
246     // pass a bool just to differentiate from circumcircle
247     circle(PT a, PT b, PT c, bool t) {
248         line u, v;
249         double m = atan2(b.y - a.y, b.x - a.x), n = atan2(c.y
            - a.y, c.x - a.x);
250         u.a = a;
251         u.b = u.a + (PT(cos((n + m)/2.0), sin((n + m)/2.0)));
252         v.a = b;
253         m = atan2(a.y - b.y, a.x - b.x), n = atan2(c.y - b.y,
            c.x - b.x);
254         v.b = v.a + (PT(cos((n + m)/2.0), sin((n + m)/2.0)));
255         line_line_intersection(u.a, u.b, v.a, v.b, p);
256         r = dist_from_point_to_seg(a, b, p);
257     }
258     bool operator == (circle v) { return p == v.p && sign(r
        - v.r) == 0; }
259 }

```

```

260 double area() { return PI * r * r; }
261 double circumference() { return 2.0 * PI * r; }
262 };
263 // 0 if outside, 1 if on circumference, 2 if inside circle
264 int circle_point_relation(PT p, double r, PT b) {
265     double d = dist(p, b);
266     if (sign(d - r) < 0) return 2;
267     if (sign(d - r) == 0) return 1;
268     return 0;
269 }
270 // 0 if outside, 1 if on circumference, 2 if inside circle
271 int circle_line_relation(PT p, double r, PT a, PT b) {
272     double d = dist_from_point_to_line(a, b, p);
273     if (sign(d - r) < 0) return 2;
274     if (sign(d - r) == 0) return 1;
275     return 0;
276 }
277 // compute intersection of line through points a and b with
    // circle centered at c with radius r > 0
278 vector<PT> circle_line_intersection(PT c, double r, PT a,
    PT b) {
279     vector<PT> ret;
280     b = b - a; a = a - c;
281     double A = dot(b, b), B = dot(a, b);
282     double C = dot(a, a) - r * r, D = B * B - A * C;
283     if (D < -eps) return ret;
284     ret.push_back(c + a + b * (-B + sqrt(D + eps)) / A);
285     if (D > eps) ret.push_back(c + a + b * (-B - sqrt(D)) /
        A);
286     return ret;
287 }
288 // 5 - outside and do not intersect
289 // 4 - intersect outside in one point
290 // 3 - intersect in 2 points
291 // 2 - intersect inside in one point
292 // 1 - inside and do not intersect
293 int circle_circle_relation(PT a, double r, PT b, double R)
    {
294     double d = dist(a, b);
295     if (sign(d - r - R) > 0) return 5;
296     if (sign(d - r - R) == 0) return 4;
297     double l = fabs(r - R);
298     if (sign(d - r - R) < 0 && sign(d - l) > 0) return 3;
299     if (sign(d - l) == 0) return 2;
300     if (sign(d - l) < 0) return 1;
301     assert(0); return -1;
302 }
303 vector<PT> circle_circle_intersection(PT a, double r, PT b,
    double R) {
304     if (a == b && sign(r - R) == 0) return {PT(1e18, 1e18)};
305     vector<PT> ret;
306     double d = sqrt(dist2(a, b));
307     if (d > r + R || d + min(r, R) < max(r, R)) return ret;
308     double x = (d * d - R * R + r * r) / (2 * d);
309     double y = sqrt(r * r - x * x);
310     PT v = (b - a) / d;
311     ret.push_back(a + v * x + rotateccw90(v) * y);
312     if (y > 0) ret.push_back(a + v * x - rotateccw90(v) * y)
        ;
313     return ret;
314 }
315 // returns two circle c1, c2 through points a, b and of
    radius r
316 // 0 if there is no such circle, 1 if one circle, 2 if two
    circle

```

```

318 int get_circle(PT a, PT b, double r, circle &c1, circle &c2
319 ) {
320     vector<PT> v = circle_circle_intersection(a, r, b, r);
321     int t = v.size();
322     if (!t) return 0;
323     c1.p = v[0], c1.r = r;
324     if (t == 2) c2.p = v[1], c2.r = r;
325     return t;
326 }
327 // returns two circle c1, c2 which is tangent to line u,
328 // goes through
329 // point q and has radius r1; 0 for no circle, 1 if c1 = c2
330 // , 2 if c1 != c2
331 int get_circle(line u, PT q, double r1, circle &c1, circle
332 &c2) {
333     double d = dist_from_point_to_line(u.a, u.b, q);
334     if (sign(d - r1 * 2.0) > 0) return 0;
335     if (sign(d) == 0) {
336         cout << u.v.x << ' ' << u.v.y << '\n';
337         c1.p = q + rotateccw90(u.v).truncate(r1);
338         c2.p = q + rotatecw90(u.v).truncate(r1);
339         c1.r = c2.r = r1;
340         return 2;
341     }
342     line u1 = line(u.a + rotateccw90(u.v).truncate(r1), u.b
343 + rotateccw90(u.v).truncate(r1));
344     line u2 = line(u.a + rotatecw90(u.v).truncate(r1), u.b +
345 rotatecw90(u.v).truncate(r1));
346     circle cc = circle(q, r1);
347     PT p1, p2; vector<PT> v;
348     v = circle_line_intersection(q, r1, u1.a, u1.b);
349     if (!v.size()) v = circle_line_intersection(q, r1, u2.a,
350 u2.b);
351     v.push_back(v[0]);
352     p1 = v[0], p2 = v[1];
353     c1 = circle(p1, r1);
354     if (p1 == p2) {
355         c2 = c1;
356         return 1;
357     }
358     c2 = circle(p2, r1);
359     return 2;
360 }
361 // returns area of intersection between two circles
362 double circle_circle_area(PT a, double r1, PT b, double r2)
363 {
364     double d = (a - b).norm();
365     if (r1 + r2 < d + eps) return 0;
366     if (r1 + d < r2 + eps) return PI * r1 * r1;
367     if (r2 + d < r1 + eps) return PI * r2 * r2;
368     double theta_1 = acos((r1 * r1 + d * d - r2 * r2) / (2 *
369 r1 * d));
370     theta_2 = acos((r2 * r2 + d * d - r1 * r1) / (2 * r2 * d
371 ));
372     return r1 * r1 * (theta_1 - sin(2 * theta_1) / 2.) + r2 *
373 r2 * (theta_2 - sin(2 * theta_2) / 2.);
374 }
375 // tangent lines from point q to the circle
376 int tangent_lines_from_point(PT p, double r, PT q, line &u,
377 line &v) {
378     int x = sign(dist2(p, q) - r * r);
379     if (x < 0) return 0; // point in circle
380     if (x == 0) { // point on circle
381         u = line(q, q + rotateccw90(q - p));
382         v = u;
383         return 1;
384     }
385     double d = dist(p, q);
386     double l = r * r / d;
387     double h = sqrt(r * r - l * l);
388     u = line(q, p + ((q - p).truncate(l) + (rotateccw90(q -
389 p).truncate(h))));
390     v = line(q, p + ((q - p).truncate(l) + (rotatecw90(q - p
391 ).truncate(h))));
392     return 2;
393 }
394 // returns outer tangents line of two circles
395 // if inner == 1 it returns inner tangent lines
396 int tangents_lines_from_circle(PT c1, double r1, PT c2,
397 double r2, bool inner, line &u, line &v) {
398     if (inner) r2 = -r2;
399     PT d = c2 - c1;
400     double dr = r1 - r2, d2 = d.norm2(), h2 = d2 - dr * dr;
401     if (d2 == 0 || h2 < 0) {
402         assert(h2 != 0);
403         return 0;
404     }
405     vector<pair<PT, PT>> out;
406     for (int tmp: {-1, 1}) {
407         PT v = (d * dr + rotateccw90(d) * sqrt(h2) * tmp) /
408 d2;
409         out.push_back({c1 + v * r1, c2 + v * r2});
410     }
411     u = line(out[0].first, out[0].second);
412     if (out.size() == 2) v = line(out[1].first, out[1].
413 second);
414     return 1 + (h2 > 0);
415 }
416 double area_of_triangle(PT a, PT b, PT c) {
417     return fabs(cross(b - a, c - a) * 0.5);
418 }
419 // -1 if strictly inside, 0 if on the polygon, 1 if
420 // strictly outside
421 int is_point_in_triangle(PT a, PT b, PT c, PT p) {
422     if (sign(cross(b - a, c - a)) < 0) swap(b, c);
423     int c1 = sign(cross(b - a, p - a));
424     int c2 = sign(cross(c - b, p - b));
425     int c3 = sign(cross(a - c, p - c));
426     if (c1 < 0 || c2 < 0 || c3 < 0) return 1;
427     if (c1 + c2 + c3 != 3) return 0;
428     return -1;
429 }
430 double perimeter(vector<PT> &p) {
431     double ans = 0; int n = p.size();
432     for (int i = 0; i < n; i++) ans += dist(p[i], p[(i + 1)
433 % n]);
434     return ans;
435 }
436 double area(vector<PT> &p) {
437     double ans = 0; int n = p.size();
438     for (int i = 0; i < n; i++) ans += cross(p[i], p[(i + 1)
439 % n]);
440     return fabs(ans) * 0.5;
441 }
442 // centroid of a (possibly non-convex) polygon,
443 // assuming that the coordinates are listed in a clockwise
444 // or
445 // counterclockwise fashion. Note that the centroid is
446 // often known as
447 // the "center of gravity" or "center of mass".
448 PT centroid(vector<PT> &p) {
449     int n = p.size(); PT c(0, 0);
450     double sum = 0;
451     for (int i = 0; i < n; i++) sum += cross(p[i], p[(i + 1)
452 % n]);
453     double scale = 3.0 * sum;
454     for (int i = 0; i < n; i++) {
455         int j = (i + 1) % n;
456         c = c + (p[i] + p[j]) * cross(p[i], p[j]);
457     }
458     return c / scale;
459 }
460 // 0 if cw, 1 if ccw
461 bool get_direction(vector<PT> &p) {
462     double ans = 0; int n = p.size();
463     for (int i = 0; i < n; i++) ans += cross(p[i], p[(i + 1)
464 % n]);
465     if (sign(ans) > 0) return 1;
466     return 0;
467 }
468 // it returns a point such that the sum of distances
469 // from that point to all points in p is minimum
470 // O(n log^2 MX)
471 PT geometric_median(vector<PT> p) {
472     auto tot_dist = [&](PT z) {
473         double res = 0;
474         for (int i = 0; i < p.size(); i++) res += dist(p[i], z
475 );
476         return res;
477     };
478     auto findY = [&](double x) {
479         double yl = -1e5, yr = 1e5;
480         for (int i = 0; i < 60; i++) {
481             double yml = yl + (yr - yl) / 3;
482             double ym2 = yr - (yr - yl) / 3;
483             double d1 = tot_dist(PT(x, yml));
484             double d2 = tot_dist(PT(x, ym2));
485             if (d1 < d2) yr = ym2;
486             else yl = yml;
487         }
488         return pair<double, double> (yl, tot_dist(PT(x, yl)));
489     };
490     double xl = -1e5, xr = 1e5;
491     for (int i = 0; i < 60; i++) {
492         double xml = xl + (xr - xl) / 3;
493         double xm2 = xr - (xr - xl) / 3;
494         double yl, dl, y2, d2;
495         auto z = findY(xml); yl = z.first; dl = z.second;
496         z = findY(xm2); y2 = z.first; d2 = z.second;
497         if (dl < d2) xr = xm2;
498         else xl = xml;
499     }
500     return {xl, findY(xl).first};
501 }
502 // -1 if strictly inside, 0 if on the polygon, 1 if
503 // strictly outside
504 // it must be strictly convex, otherwise make it strictly
505 // convex first
506 int is_point_in_convex(vector<PT> &p, const PT& x) { // O(
507 log n)
508     int n = p.size(); assert(n >= 3);

```

```

484 int a = orientation(p[0], p[l], x), b = orientation(p
    [0], p[n - 1], x);
485 if (a < 0 || b > 0) return 1;
486 int l = 1, r = n - 1;
487 while (l + 1 < r) {
488     int mid = l + r >> 1;
489     if (orientation(p[0], p[mid], x) >= 0) l = mid;
490     else r = mid;
491 }
492 int k = orientation(p[l], p[r], x);
493 if (k <= 0) return -k;
494 if (l == 1 && a == 0) return 0;
495 if (r == n - 1 && b == 0) return 0;
496 return -1;
497 }
498 bool is_point_on_polygon(vector<PT> &p, const PT& z) {
499     int n = p.size();
500     for (int i = 0; i < n; i++) {
501         if (is_point_on_seg(p[i], p[(i + 1) % n], z)) return
            1;
502     }
503     return 0;
504 }
505 // returns 1e9 if the point is on the polygon
506 int winding_number(vector<PT> &p, const PT& z) { // O(n)
507     if (is_point_on_polygon(p, z)) return 1e9;
508     int n = p.size(), ans = 0;
509     for (int i = 0; i < n; i++) {
510         int j = (i + 1) % n;
511         bool below = p[i].y < z.y;
512         if (below != (p[j].y < z.y)) {
513             auto orient = orientation(z, p[j], p[i]);
514             if (orient == 0) return 0;
515             if (below == (orient > 0)) ans += below ? 1 : -1;
516         }
517     }
518     return ans;
519 }
520 // -1 if strictly inside, 0 if on the polygon, 1 if
    strictly outside
521 int is_point_in_polygon(vector<PT> &p, const PT& z) { // O(
    n)
522     int k = winding_number(p, z);
523     return k == 1e9 ? 0 : k == 0 ? 1 : -1;
524 }
525
526 double diameter(vector<PT> &p) {
527     int n = (int)p.size();
528     if (n == 1) return 0;
529     if (n == 2) return dist(p[0], p[1]);
530     double ans = 0;
531     int i = 0, j = 1;
532     while (i < n) {
533         while (cross(p[(i + 1) % n] - p[i], p[(j + 1) % n] -
            p[j]) >= 0) {
534             ans = max(ans, dist2(p[i], p[j]));
535             j = (j + 1) % n;
536         }
537         ans = max(ans, dist2(p[i], p[j]));
538         i++;
539     }
540     return sqrt(ans);
541 }
542 // minimum distance between two parallel lines (non
    necessarily axis parallel)
543 // such that the polygon can be put between the lines
544 double width(vector<PT> &p) {
545     int n = (int)p.size();
546     if (n <= 2) return 0;
547     double ans = inf;
548     int i = 0, j = 1;
549     while (i < n) {
550         while (cross(p[(i + 1) % n] - p[i], p[(j + 1) % n] -
            p[j]) >= 0) j = (j + 1) % n;
551         ans = min(ans, dist_from_point_to_line(p[i], p[(i +
            1) % n], p[j]));
552         i++;
553     }
554     return ans;
555 }
556 // minimum perimeter
557 double minimum_enclosing_rectangle(vector<PT> &p) {
558     int n = p.size();
559     if (n <= 2) return perimeter(p);
560     int mndot = 0; double tmp = dot(p[1] - p[0], p[0]);
561     for (int i = 1; i < n; i++) {
562         if (dot(p[1] - p[0], p[i]) <= tmp) {
563             tmp = dot(p[1] - p[0], p[i]);
564             mndot = i;
565         }
566     }
567     double ans = inf;
568     int i = 0, j = 1, mxdot = 1;
569     while (i < n) {
570         PT cur = p[(i + 1) % n] - p[i];
571         while (cross(cur, p[(j + 1) % n] - p[j]) >= 0) j = (j
            + 1) % n;
572         while (dot(p[(mxdot + 1) % n], cur) >= dot(p[mxdot],
            cur)) mxdot = (mxdot + 1) % n;
573         while (dot(p[(mndot + 1) % n], cur) <= dot(p[mndot],
            cur)) mndot = (mndot + 1) % n;
574         ans = min(ans, 2.0 * ((dot(p[mxdot], cur) / cur.norm
            ()) - dot(p[mndot], cur) / cur.norm()) +
            dist_from_point_to_line(p[i], p[(i + 1) % n], p[
            j]));
575         i++;
576     }
577     return ans;
578 }
579 // given n points, find the minimum enclosing circle of the
    points
580 // call convex_hull() before this for faster solution
581 // expected O(n)
582 circle minimum_enclosing_circle(vector<PT> &p) {
583     random_shuffle(p.begin(), p.end());
584     int n = p.size();
585     circle c(p[0], 0);
586     for (int i = 1; i < n; i++) {
587         if (sign(dist(c.p, p[i]) - c.r) > 0) {
588             c = circle(p[i], 0);
589             for (int j = 0; j < i; j++) {
590                 if (sign(dist(c.p, p[j]) - c.r) > 0) {
591                     c = circle((p[i] + p[j]) / 2, dist(p[i], p[j]
                        ) / 2);
592                     for (int k = 0; k < j; k++) {
593                         if (sign(dist(c.p, p[k]) - c.r) > 0) {
594                             c = circle(p[i], p[j], p[k]);
595                         }
596                     }
597                 }
598             }
599         }
600     }
601     return c;
602 }
603
604 pair<PT, int> point_poly_tangent(vector<PT> &p, PT Q, int
    dir, int l, int r) {
605     while (r - l > 1) {
606         int mid = (l + r) >> 1;
607         bool pvs = orientation(Q, p[mid], p[mid - 1]) != -dir;
608         bool nxt = orientation(Q, p[mid], p[mid + 1]) != -dir;
609         if (pvs && nxt) return {p[mid], mid};
610         if (!pvs || !nxt) {
611             auto p1 = point_poly_tangent(p, Q, dir, mid + 1, r);
612             auto p2 = point_poly_tangent(p, Q, dir, l, mid -
                1);
613             return orientation(Q, p1.first, p2.first) == dir ?
                p1 : p2;
614         }
615         if (!pvs) {
616             if (orientation(Q, p[mid], p[l]) == dir) r = mid -
                1;
617             else if (orientation(Q, p[l], p[r]) == dir) r =
                mid - 1;
618             else l = mid + 1;
619         }
620         if (!nxt) {
621             if (orientation(Q, p[mid], p[l]) == dir) l = mid +
                1;
622             else if (orientation(Q, p[l], p[r]) == dir) r =
                mid - 1;
623             else l = mid + 1;
624         }
625     }
626     pair<PT, int> ret = {p[l], l};
627     for (int i = l + 1; i <= r; i++) ret = orientation(Q,
        ret.first, p[i]) != dir ? make_pair(p[i], i) : ret;
628     return ret;
629 }
630
631 // (ccw, cw) tangents from a point that is outside this
    convex polygon
632 // returns indexes of the points
633 // ccw means the tangent from Q to that point is in the
    same direction as the polygon ccw direction
634 pair<int, int> tangents_from_point_to_polygon(vector<PT> &p
    , PT Q) {
635     int ccw = point_poly_tangent(p, Q, 1, 0, (int)p.size() -
        1).second;
636     int cw = point_poly_tangent(p, Q, -1, 0, (int)p.size() -
        1).second;
637     return make_pair(ccw, cw);
638 }
639
640 // minimum distance from a point to a convex polygon
641 // it assumes point lie strictly outside the polygon
642 double dist_from_point_to_polygon(vector<PT> &p, PT z) {
643     double ans = inf;
644     int n = p.size();
645     if (n <= 3) {

```

```

646     for(int i = 0; i < n; i++) ans = min(ans,
        dist_from_point_to_seg(p[i], p[(i + 1) % n], z))
        ;
647     return ans;
648 }
649 auto [r, l] = tangents_from_point_to_polygon(p, z);
650 if(l > r) r += n;
651 while(l < r) {
652     int mid = (l + r) >> 1;
653     double left = dist2(p[mid % n], z), right = dist2(p[(
        mid + 1) % n], z);
654     ans = min({ans, left, right});
655     if(left < right) r = mid;
656     else l = mid + 1;
657 }
658 ans = sqrt(ans);
659 ans = min(ans, dist_from_point_to_seg(p[l % n], p[(l +
        1) % n], z));
660 ans = min(ans, dist_from_point_to_seg(p[l % n], p[(l - 1
        + n) % n], z));
661 return ans;
662 }
663 // minimum distance from convex polygon p to line ab
664 // returns 0 is it intersects with the polygon
665 // top - upper right vertex
666 double dist_from_polygon_to_line(vector<PT> &p, PT a, PT b,
        int top) { //O(log n)
667     PT orth = (b - a).perp();
668     if(orientation(a, b, p[0]) > 0) orth = (a - b).perp();
669     int id = extreme_vertex(p, orth, top);
670     if(dot(p[id] - a, orth) > 0) return 0.0; //if orth and a
        are in the same half of the line, then poly and
        line intersects
671     return dist_from_point_to_line(a, b, p[id]); //does not
        intersect
672 }
673 // minimum distance from a convex polygon to another convex
        polygon
674 // the polygon doesnot overlap or touch
675 // tested in https://toph.co/p/the-wall
676 double dist_from_polygon_to_polygon(vector<PT> &p1, vector<
        PT> &p2) { // O(n log n)
677     double ans = inf;
678     for(int i = 0; i < p1.size(); i++) {
679         ans = min(ans, dist_from_point_to_polygon(p2, p1[i]))
        ;
680     }
681     for(int i = 0; i < p2.size(); i++) {
682         ans = min(ans, dist_from_point_to_polygon(p1, p2[i]))
        ;
683     }
684     return ans;
685 }
686 // maximum distance from a convex polygon to another convex
        polygon
687 double maximum_dist_from_polygon_to_polygon(vector<PT> &u,
        vector<PT> &v) { //O(n)
688     int n = (int)u.size(), m = (int)v.size();
689     double ans = 0;
690     if(n < 3 || m < 3) {
691         for(int i = 0; i < n; i++) {
692             for(int j = 0; j < m; j++) ans = max(ans, dist2(u
                [i], v[j]));
693         }
694         return sqrt(ans);
695     }
696     if(u[0].x > v[0].x) swap(n, m), swap(u, v);
697     int i = 0, j = 0, step = n + m + 10;
698     while(j + 1 < m && v[j].x < v[j + 1].x) j++;
699     while(step--) {
700         if(cross(u[(i + 1) % n] - u[i], v[(j + 1) % m] - v[j])
            >= 0) j = (j + 1) % m;
701         else i = (i + 1) % n;
702         ans = max(ans, dist2(u[i], v[j]));
703     }
704     return sqrt(ans);
705 }
706 // rotate the polygon such that the (bottom, left)-most
        point is at the first position
707 void reorder_polygon(vector<PT> &p) {
708     int pos = 0;
709     for(int i = 1; i < p.size(); i++) {
710         if(p[i].y < p[pos].y || (sign(p[i].y - p[pos].y) == 0
            && p[i].x < p[pos].x)) pos = i;
711     }
712     rotate(p.begin(), p.begin() + pos, p.end());
713 }
714 // returns the area of the intersection of the circle with
        center c and radius r
715 // and the triangle formed by the points c, a, b
716 double triangle_circle_intersection(PT c, double r, PT a,
        PT b) {
717     double sd1 = dist2(c, a), sd2 = dist2(c, b);
718     if(sd1 > sd2) swap(a, b), swap(sd1, sd2);
719     double sd = dist2(a, b);
720     double d1 = sqrt1(sd1), d2 = sqrt1(sd2), d = sqrt(sd);
721     double x = abs(sd2 - sd - sd1) / (2 * d);
722     double h = sqrt1(sd1 - x * x);
723     if(r >= d2) return h * d / 2;
724     double area = 0;
725     if(sd + sd1 < sd2) {
726         if(r < d1) area = r * r * (acos(h / d2) - acos(h / d1
            )) / 2;
727     }
728     else {
729         area = r * r * (acos(h / d2) - acos(h / r)) / 2;
730         double y = sqrt1(r * r - h * h);
731         area += h * (y - x) / 2;
732     }
733 }
734 }
735 else {
736     if(r < h) area = r * r * (acos(h / d2) + acos(h / d1)
        ) / 2;
737     else {
738         area += r * r * (acos(h / d2) - acos(h / r)) / 2;
739         double y = sqrt1(r * r - h * h);
740         area += h * y / 2;
741         if(r < d1) {
742             area += r * r * (acos(h / d1) - acos(h / r)) /
            2;
743             area += h * y / 2;
744         }
745         else area += h * x / 2;
746     }
747 }
748 return area;
749 // intersection between a simple polygon and a circle
750 double polygon_circle_intersection(vector<PT> &v, PT p,
        double r) {
751     int n = v.size();
752     double ans = 0.00;
753     PT org = {0, 0};
754     for(int i = 0; i < n; i++) {
755         int x = orientation(p, v[i], v[(i + 1) % n]);
756         if(x == 0) continue;
757         double area = _triangle_circle_intersection(org, r, v
            [i] - p, v[(i + 1) % n] - p);
758         if(x < 0) ans -= area;
759         else ans += area;
760     }
761     return abs(ans);
762 }
763 // find a circle of radius r that contains as many points
        as possible
764 // O(n^2 log n);
765 double maximum_circle_cover(vector<PT> p, double r, circle
        &c) {
766     int n = p.size();
767     int ans = 0;
768     int id = 0; double th = 0;
769     for(int i = 0; i < n; ++i) {
770         // maximum circle cover when the circle goes through
            this point
771         vector<pair<double, int>> events = {{-PI, +1}, {PI,
            -1}};
772         for(int j = 0; j < n; ++j) {
773             if(j == i) continue;
774             double d = dist(p[i], p[j]);
775             if(d > r * 2) continue;
776             double dir = (p[j] - p[i]).arg();
777             double ang = acos(d / 2 / r);
778             double st = dir - ang, ed = dir + ang;
779             if(st > PI) st -= PI * 2;
780             if(st <= -PI) st += PI * 2;
781             if(ed > PI) ed -= PI * 2;
782             if(ed <= -PI) ed += PI * 2;
783             events.push_back({st - eps, +1}); // take care of
            precisions!
784             events.push_back({ed, -1});
785             if(st > ed) {
786                 events.push_back({-PI, +1});
787                 events.push_back({+PI, -1});
788             }
789         }
790         sort(events.begin(), events.end());
791         int cnt = 0;
792         for(auto &e: events) {
793             cnt += e.second;
794             if(cnt > ans) {
795                 ans = cnt;
796                 id = i; th = e.first;
797             }
798         }
799     }
800     PT w = PT(p[id].x + r * cos(th), p[id].y + r * sin(th));
801     c = circle(w, r); //best_circle
802     return ans;
803 }
804 // radius of the maximum inscribed circle in a convex
        polygon
805 double maximum_inscribed_circle(vector<PT> p) {
806     int n = p.size();
807     if(n <= 2) return 0;
808     double l = 0, r = 20000;

```

```

809 while (r - l > eps) {
810     double mid = (l + r) * 0.5;
811     vector<HP> h;
812     const int L = 1e9;
813     h.push_back(HP (PT(-L, -L), PT(L, -L)));
814     h.push_back(HP (PT(L, -L), PT(L, L)));
815     h.push_back(HP (PT(L, L), PT(-L, L)));
816     h.push_back(HP (PT(-L, L), PT(-L, -L)));
817     for (int i = 0; i < n; i++) {
818         PT z = (p[(i + 1) % n] - p[i]).perp();
819         z = z.truncate(mid);
820         PT y = p[i] + z, q = p[(i + 1) % n] + z;
821         h.push_back(HP (p[i] + z, p[(i + 1) % n] + z));
822     }
823     vector<PT> nw = half_plane_intersection(h);
824     if (!nw.empty()) l = mid;
825     else r = mid;
826 }
827 return l;
828 }

```

Graph

Articulation Bridges

```

1 struct TECC { // 0 indexed
2     int n, k;
3     vector<vector<pair<int, int>>> g, t;
4     vector<bool> used;
5     vector<int> comp, ord, low;
6     struct edge {
7         int u, v, w;
8     };
9     vector<edge> br;
10    void dfs(int x, int prv, int &c) {
11        used[x] = 1; ord[x] = c++; low[x] = n;
12        bool mul = 0;
13        for (auto [y, w] : g[x]) {
14            if (used[y]) {
15                if (y != prv || mul) low[x] = min(low[x], ord[y]);
16                else mul = 1;
17                continue;
18            }
19            dfs(y, x, c);
20            low[x] = min(low[x], low[y]);
21        }
22    }
23    void dfs2(int x, int num) {
24        comp[x] = num;
25        for (auto [y, w] : g[x]) {
26            if (comp[y] != -1) continue;
27            if (ord[x] < low[y]) {
28                br.push_back({x, y, w});
29                k++;
30                dfs2(y, k);
31            } else dfs2(y, num);
32        }
33    }
34    TECC(const vector<vector<pair<int, int>>> &g): g(g), n(g.size()), used(n), comp(n, -1), ord(n), low(n), k(0) {
35        int c = 0;
36        for (int i = 0; i < n; i++) {
37            if (used[i]) continue;

```

```

38        dfs(i, -1, c);
39        dfs2(i, k);
40        k++;
41    }
42 }
43 void build_tree() {
44     t.resize(k);
45     for (auto e: br) {
46         int x = comp[e.u], y = comp[e.v];
47         t[x].push_back({y, e.w});
48         t[y].push_back({x, e.w});
49     }
50 }
51 };

```

Bell

```

1 void solve()
2 {
3     vector<int> d(n, INF);
4     d[v] = 0;
5     vector<int> p(n, -1);
6     int x;
7     for (int i = 0; i < n; ++i) {
8         x = -1;
9         for (Edge e : edges)
10            if (d[e.a] < INF)
11                if (d[e.b] > d[e.a] + e.cost) {
12                    d[e.b] = max(-INF, d[e.a] + e.cost);
13                    p[e.b] = e.a;
14                    x = e.b;
15                }
16        }
17        if (x == -1)
18            cout << "No negative cycle from " << v;
19        else {
20            int y = x;
21            for (int i = 0; i < n; ++i)
22                y = p[y];
23            vector<int> path;
24            for (int cur = y; cur = p[cur]) {
25                path.push_back(cur);
26                if (cur == y && path.size() > 1)
27                    break;
28            }
29            reverse(path.begin(), path.end());
30            cout << "Negative cycle: ";
31            for (int u : path)
32                cout << u << ' ';
33        }
34    }

```

Block Cut Tree

```

1 #include<bits/stdc++.h>
2 using namespace std;
3
4 const int N = 4e5 + 9;
5
6 int T, low[N], dis[N], art[N], sz;
7 vector<int> g[N], bcc[N], st;
8 void dfs(int u, int pre = 0) {
9     low[u] = dis[u] = ++T;

```

```

10     st.push_back(u);
11     for (auto v: g[u]) {
12         if (!dis[v]) {
13             dfs(v, u);
14             low[u] = min(low[u], low[v]);
15             if (low[v] >= dis[u]) {
16                 sz++;
17                 int x;
18                 do {
19                     x = st.back();
20                     st.pop_back();
21                     bcc[x].push_back(sz);
22                 } while (x ^ v);
23                 bcc[u].push_back(sz);
24             }
25             else if (v != pre) low[u] = min(low[u], dis[v]);
26         }
27     }
28
29     int dep[N], par[N][20], cnt[N], id[N];
30     vector<int> bt[N];
31     void dfs1(int u, int pre = 0) {
32         dep[u] = dep[pre] + 1;
33         cnt[u] = cnt[pre] + art[u];
34         par[u][0] = pre;
35         for (int k = 1; k <= 18; k++) par[u][k] = par[par[u][k - 1]][k - 1];
36         for (auto v: bt[u]) if (v != pre) dfs1(v, u);
37     }
38
39     int lca(int u, int v) {
40         if (dep[u] < dep[v]) swap(u, v);
41         for (int k = 18; k >= 0; k--) if (dep[par[u][k]] >= dep[v])
42             u = par[u][k];
43         if (u == v) return u;
44         for (int k = 18; k >= 0; k--) if (par[u][k] != par[v][k])
45             u = par[u][k], v = par[v][k];
46         return par[u][0];
47     }
48
49     int dist(int u, int v) {
50         int lc = lca(u, v);
51         return cnt[u] + cnt[v] - 2 * cnt[lc] + art[lc];
52     }
53
54     int32_t main() {
55         ios_base::sync_with_stdio(0);
56         cin.tie(0);
57
58         int n, m;
59         cin >> n >> m;
60         while (m--) {
61             int u, v;
62             cin >> u >> v;
63             g[u].push_back(v);
64             g[v].push_back(u);
65         }
66         dfs(1);
67         for (int u = 1; u <= n; u++) {
68             if (bcc[u].size() > 1) { //AP
69                 id[u] = ++sz;
70                 art[id[u]] = 1; //if id in BCT is an AP on real graph
71                 or not
72                 for (auto v: bcc[u]) {
73                     bt[id[u]].push_back(v);
74                 }
75             }
76         }

```

```

71     bt[v].push_back(id[u]);
72 }
73 } else if(bcc[u].size() == 1) id[u] = bcc[u][0];
74 }
75
76 dfs1(1);
77 int q;
78 cin >> q;
79 while(q--) {
80     int u, v;
81     cin >> u >> v;
82     int ans;
83     if(u == v) ans = 0;
84     else ans = dist(id[u], id[v]) - art[id[u]] - art[id[v]];
85     cout << ans << '\n'; //number of articulation points in
86     //the path from u to v except u and v
87     //u and v are in the same bcc if ans == 0
88 }
89 return 0;
90 // https://codeforces.com/gym/102512/problem/A

```

DSU ON Tree

```

1 // DSU on Tree (Sack)
2 // Computes for each node some info about its subtree
3 // efficiently
4 const int N = 200005;
5 vector<int> tree[N];
6 int col[N], sz[N];
7 bool big[N];
8 int cnt[N]; // frequency of colors
9 int cur_ans = 0; // example answer (can be modified)
10 int answer[N]; // answer for each node
11 // compute subtree sizes
12 void dfs_sz(int u, int p) {
13     sz[u] = 1;
14     for (int v : tree[u]) {
15         if (v == p) continue;
16         dfs_sz(v, u);
17         sz[u] += sz[v];
18     }
19 }
20 // add/remove contribution of subtree
21 void add(int u, int p, int val) {
22     cnt[col[u]] += val;
23     // example logic: maintain max frequency
24     cur_ans = max(cur_ans, cnt[col[u]]);
25     for (int v : tree[u]) {
26         if (v == p || big[v]) continue;
27         add(v, u, val);
28     }
29 }
30 // main DSU dfs
31 void dfs(int u, int p, bool keep) {
32     int mx = -1, heavy = -1;
33     for (int v : tree[u]) {
34         if (v != p && sz[v] > mx) {
35             mx = sz[v];
36             heavy = v;
37         }
38     }
39     // process light children
40     for (int v : tree[u]) {
41         if (v != p && v != heavy) dfs(v, u, false);

```

```

41     }
42     // process heavy child
43     if (heavy != -1) {
44         dfs(heavy, u, true); big[heavy] = true;
45     }
46     // add current node and light children
47     add(u, p, +1); answer[u] = cur_ans;
48     if (heavy != -1) big[heavy] = false;
49     // clear data if not keeping
50     if (!keep) {
51         add(u, p, -1); cur_ans = 0;
52     }
53 }

```

DSU

```

1 void make_set(int v) {
2     parent[v] = v;
3 }
4 int find_set(int v) {
5     if (v == parent[v])
6         return v;
7     return parent[v] = find_set(parent[v]);
8 }
9 void union_sets(int a, int b) {
10    a = find_set(a);
11    b = find_set(b);
12    if (a != b)
13        parent[b] = a;
14 }

```

LCA

```

1 void dfs(int u, int p) {
2     tree[u][0] = p;
3     dep[u] = dep[p] + 1;
4
5     for(int i = 1; i < B; i++) {
6         tree[u][i] = tree[tree[u][i - 1]][i - 1];
7     }
8     sz[u] = 1;
9     for(auto v : g[u]) {
10        if(v == p) continue;
11        dfs(v, u);
12        sz[u] += sz[v];
13    }
14 }
15
16 int lca(int u, int v) {
17     if(dep[u] > dep[v]) swap(u, v);
18     for(int i = B - 1; i >= 0; i--) {
19         if(dep[tree[v][i]] >= dep[u]) {
20             v = tree[v][i];
21         }
22     }
23
24     if(u == v) return u;
25     for(int i = B - 1; i >= 0; i--) {
26         if(tree[u][i] != tree[v][i]) {
27             u = tree[u][i];
28             v = tree[v][i];
29         }
30     }

```

```

31     return tree[u][0];
32 }

```

euler_path_directed

```

1 vector<int> adj[200005];
2 int ptrs[200005];
3 int in_deg[200005], out_deg[200005];
4 vector<int> path; // node sequence
5 vector<int> edges; // edge sequence
6 int to[200005];
7 bool used[200005];
8
9 void dfs(int u) {
10     while(ptrs[u] < adj[u].size()) {
11         int e = adj[u][ptrs[u]++];
12         if(used[e]) continue;
13         used[e] = true;
14         dfs(to[e]);
15         edges.push_back(e);
16     }
17     path.push_back(u);
18 }
19
20
21
22
23 for(int i=0;i<m;i++){
24     int u,v;
25     cin >> u >> v;
26     adj[u].push_back(i);
27     to[i] = v;
28     out_deg[u]++;
29     in_deg[v]++;
30     if(i==0) s = u;
31 }
32
33 // degree check for Euler path
34 int start = -1, end = -1;
35 bool ok = true;
36
37 for(int i=0;i<n;i++){
38     int diff = out_deg[i] - in_deg[i];
39     if(diff == 1){
40         if(start != -1) ok = false;
41         start = i;
42     }
43     else if(diff == -1){
44         if(end != -1) ok = false;
45         end = i;
46     }
47     else if(diff != 0){
48         ok = false;
49     }
50 }
51
52 reverse(path.begin(), path.end());
53 reverse(edges.begin(), edges.end());

```

kosaraju

```

1 typedef struct node {
2     int vis;
3     vector<int> adj;

```

```

4   vector<int> ulta;
5   } node;
6   node tree[300010];
7   vector<vector<int>> scc(300010);
8   stack<int> st;
9   int scout = 0;
10  void dfs(int u) {
11      tree[u].vis = 1;
12      f(i, tree[u].adj.size()) {
13          int next = tree[u].adj[i];
14          if (tree[next].vis == 0) dfs(next);
15      }
16      st.push(u);
17  }
18  void dfs2(int u) {
19      // printf("%d %d\n", u, scout);
20      tree[u].vis = 1;
21      scc[scout-1].push_back(u);
22      f(i, tree[u].ulta.size()) {
23          int next = tree[u].ulta[i];
24          if (tree[next].vis == 0) dfs2(next);
25      }
26  }

```

mos on trees

```

1  struct Query { ll id, l, r, bno, k; }; //basic comparator
bool cmp(Query &a, Query &b) { if (a.bno != b.bno) {
    return a.bno < b.bno; } else if (a.bno & 1) { return a
    .r < b.r; } else { return a.r > b.r; } } ll n, q; ll bs
    = 700; // change is depending on problem
Query qry[N]; ll a[N], b[N], st[N], en[N]; ll ans[N]; ll tt = -1; vll g
    [N]; void gg(ll x, ll pr) { //trc(x); tt++; st[x] = tt;
    a[tt] = x; //trc(tt, a[tt]); go(i, g[x]) { if (i == pr)
    cu; gg(i, x); } tt++; en[x] = tt; a[tt] = x; } const ll
    LG = 30; ll tim = 0; ll parent[LG][N]; ll tin[N], tout
    [N], level[N]; void dfs(ll k, ll par, ll lvl) { tin[k]
    ] = ++tim; parent[0][k] = par; level[k] = lvl; for (auto it: g
    [k]) { if (it == par) continue; dfs(it, k, lvl+1); } tout
    [k] = tim; } ll walk(ll u, ll h) { for (ll i = LG-1; i >= 0; i
    --) { if ((h >> i) & 1) u = parent[i][u]; } return u; }
    void precompute() { for (ll i = 1; i < LG; i++) for (ll j = 1; j
    <= n; j++) if (parent[i-1][j]) parent[i][j] = parent[i-1][
    parent[i-1][j]]; } ll lca(ll u, ll v) { if (level[u] <
    level[v]) swap(u, v); ll diff = level[u] - level[v]; for (ll
    i = LG-1; i >= 0; i--) { if ((1 << i) & diff) { u = parent[i][u]
    ]; } } if (u == v) return u; for (ll i = LG-1; i >= 0; i--) { if
    (parent[i][u] & parent[i][v] != parent[i][v]) { u =
    parent[i][u]; v = parent[i][v]; } } return parent[0][u];
    } ll dist(ll u, ll v) { return level[u] + level[v] -
    2 * level[lca(u, v)]; } ll lp, rp, cnt; ll freq
    [1000001]; ll freq2[1000005]; //unordered_map<ll, ll>
    freq; void add(ll val) { freq[val]++; freq2[b[
    val]]++; if (freq2[val] == 2) { freq2[b[val]] -= 2; // if (
    freq2[b[val]] == 0) { // cnt--; // } } else { // if (
    freq2[b[val]] == 1) cnt++; } } void remove(ll val) {
    freq[val]--; freq2[b[val]]--; if (freq2[val] == 1) {
    freq2[b[val]] += 2; // if (freq2[b[val]] == 1) { // cnt++;
    // } } else { // if (freq2[b[val]] == 0) cnt--; } } ll
    get_answer() { return cnt; } void solve() { cin >> n >>
    q; //trc(n, q); mll m; ll dd = 0; for (ll i = 1; i <= n
    ; i++) { cin >> b[i]; if (!m.count(b[i])) { m[b[i]] = dd
    ++; } b[i] = m[b[i]]; } f0(n-1) { ipp(x, y); //trc(x, y);
    g[x].pb(y); g[y].pb(x); } gg(1, 0); dfs(1, 0, 0);
    precompute(); for (ll i = 0; i < q; i++) { ll x, y;

```

```

cin >> x >> y; if (level[x] > level[y]) { swap(x, y); } ll
p = lca(x, y); // trc(x, y, p); ll l, r; if (p == x) { l =
st[x]; r = st[y]; qry[i].k = -1; } else { if (st[x] > st[y]
) swap(x, y); l = en[x]; r = st[y]; qry[i].k = st[p];
// trc(l, r, p, st[p]); // f(j, l, r+1) { // trc(j, a[j]); //
} } qry[i].id = i; qry[i].l = l; qry[i].r = r; qry[i]
}.bno = l / bs; } // sort the queries sort(qry, qry +
q, cmp); // initialise the data-structure lp = 0; rp =
-1; cnt = 0; // add(a[0]); // answer the queries for
(ll i = 0; i < q; i++) { ll l = qry[i].l; ll r = qry[i]
}.r; while (rp < r) { add(a[+rp]); } while (lp > l) {
add(a[--lp]); } while (rp > r) { remove(a[rp--]); }
while (lp < l) { remove(a[lp++]); } ans[qry[i].id] =
get_answer(); if (qry[i].k != -1) { // if (freq2[b[a[qry[i]
].k]]) == 0) { // ans[qry[i].id]++; // } } } for (ll i =
0; i < q; i++) { cout << ans[i] << endl; } } //
this require the element to be added on both side l, r
and removed l, r // but we can also use mo's when data
structure allow the removal from the side where we
added like rollback dsu void fun() { solve(); }
int32_t main() { // tasklist // taskkill /f /im a.exe
depressed(); ll tcl = 1; //cin >> tcl; while (tcl--) {
fun(); } //cer; return 0; }

```

roll_dsu

```

1  struct DSU { int connected; int sz[N]; pair<int, int> par[N]
    }; //stores <parent, parity of distance from parent>
vector<int> changes; void init(int n) { for (int i = 1; i
    <= n; i++) { par[i] = {i, 0}; sz[i] = 1; } connected = n; }
    pair<int, int> getPar(int x) { if (par[x].first == x)
    return par[x]; pair<int, int> p = getPar(par[x].first)
    ; p.second ^= par[x].second; return p; } bool unite(
    int u, int v) { //Returns 1 if the graph is no longer
    bipartite { pair<int, int> x = getPar(u), y = getPar(v);
    if (x.first == y.first) { if (x.second == y.second) return
    1; changes.push_back(-1); return 0; } connected--; if (
    sz[x.first] < sz[y.first]) swap(x, y); par[y.first] = {x
    .first, 1^x.second^y.second}; sz[x.first] += sz[y.first]
    ; changes.push_back(y.first); return 0; } void undo()
    //Reversed the previous performed operation { if (!
    changes.size()) return; if (changes.back() != -1) { int x
    = changes.back(); sz[par[x].first] -= sz[x]; par[x] = {x,
    0}; } changes.pop_back(); } }

```

scc

```

1  vector<int> val, comp, z;
2  int Time, ncomps;
3  vector<vector<int>> sccs;
4
5  void dfs(int j, vector<vector<int>>& g) {
6      int low = val[j] = ++Time, x; z.push_back(j);
7      for (int e : g[j]) if (comp[e] < 0)
8          low = min(low, val[e] ? dfs(e, g));
9
10     if (low == val[j]) {
11         sccs.push_back({});
12         do {
13             x = z.back(); z.pop_back();
14             comp[x] = ncomps;
15             sccs.back().push_back(x);
16         } while (x != j);

```

```

17         ncomps++;
18     }
19     return val[j] = low;
20 }
21
22 void get_sccs(vector<vector<int>>& g) {
23     int n = g.size();
24     val.assign(n, 0); comp.assign(n, -1);
25     z.clear(); sccs.clear();
26     Time = ncomps = 0;
27     for (int i = 0; i < n; i++) if (comp[i] < 0) dfs(i, g);
28 }

```

Number Theory Math CRT

```

1  __int128 ExU(__int128 a, __int128 b, __int128 &x, __int128
    &y) {
2      if (b == 0) {
3          x = 1;
4          y = 0;
5          return a;
6      }
7      __int128 x1, y1;
8      __int128 d = ExU(b, a % b, x1, y1);
9      x = y1;
10     y = x1 - (a/b)*y1;
11     return d;
12 }
13 void solve() {
14     cout << "Case " << ii++ << ": ";
15     int n; cin >> n;
16     vector<int> a(n), m(n);
17     for (int i = 0; i < n; i++) cin >> m[i] >> a[i];
18     int al = a[0], ml = m[0];
19     for (int i = 1; i < n; i++) {
20         __int128 a2 = a[i], m2 = m[i];
21         __int128 x, y;
22         __int128 g = ExU(m1, m2, x, y);
23         if ((al-a2) % g != 0) {
24             cout << "Impossible" << endl;
25             return;
26         }
27         __int128 k = (al-a2) / g, lcm = (m1/g) * m2;
28         __int128 a = al - m1*(k * x);
29         al = (a % lcm);
30         if (al < 0) al += lcm;
31         m1 = lcm;
32     }
33     cout << al << endl;
34 }

```

Diophantile

```

1  int gcd(int a, int b, int& x, int& y) {
2      if (b == 0) { x = 1; y = 0; return a;
3      }
4      int x1, y1;
5      int d = gcd(b, a % b, x1, y1);
6      x = y1; y = x1 - y1 * (a / b);
7      return d;

```

```

8 }
9
10 bool find_any_solution(int a, int b, int c, int &x0, int &
    y0, int &g) {
11     g = gcd(abs(a), abs(b), x0, y0);
12     if (c % g) {
13         return false;
14     }
15     x0 *= c / g; y0 *= c / g;
16     if (a < 0) x0 = -x0;
17     if (b < 0) y0 = -y0;
18     return true;
19 }
20 void shift_solution(int &x, int &y, int a, int b, int cnt
    ) {
21     x += cnt * b; y -= cnt * a;
22 }
23 int find_all_solutions(int a, int b, int c, int minx, int
    maxx, int miny, int maxy) {
24     int x, y, g;
25     if (!find_any_solution(a, b, c, x, y, g)) return 0;
26     a /= g; b /= g;
27     int sign_a = a > 0 ? +1 : -1;
28     int sign_b = b > 0 ? +1 : -1;
29     shift_solution(x, y, a, b, (minx - x) / b);
30     if (x < minx) shift_solution(x, y, a, b, sign_b);
31     if (x > maxx) return 0;
32     int lx1 = x;
33     shift_solution(x, y, a, b, (maxx - x) / b);
34     if (x > maxx) shift_solution(x, y, a, b, -sign_b);
35     int rx1 = x; shift_solution(x, y, a, b, -(miny - y) / a)
    ;
36     if (y < miny) shift_solution(x, y, a, b, -sign_a);
37     if (y > maxy) return 0;
38     int lx2 = x;
39     shift_solution(x, y, a, b, -(maxy - y) / a);
40     if (y > maxy) shift_solution(x, y, a, b, sign_a);
41     int rx2 = x;
42     if (lx2 > rx2) swap(lx2, rx2);
43     int lx = max(lx1, lx2);
44     int rx = min(rx1, rx2);
45     if (lx > rx) return 0;
46     return (rx - lx) / abs(b) + 1;
47 }

```

FFT

```

1 const int N = 3e5 + 9;
2 const double PI = acos(-1);
3 struct base {
4     double a, b;
5     base(double a = 0, double b = 0) : a(a), b(b) {}
6     const base operator + (const base &c) const
7     { return base(a + c.a, b + c.b); }
8     const base operator - (const base &c) const
9     { return base(a - c.a, b - c.b); }
10    const base operator * (const base &c) const
11    { return base(a * c.a - b * c.b, a * c.b + b * c.a); }
12 };
13 void fft(vector<base> &p, bool inv = 0) {
14     int n = p.size(), i = 0;
15     for(int j = 1; j < n - 1; ++j) {
16         for(int k = n >> 1; k > (i ^ k); k >>= 1);
17         if(j < i) swap(p[i], p[j]);
18     }

```

```

19     for(int l = 1, m; (m = l << 1) <= n; l <= 1) {
20         double ang = 2 * PI / m;
21         base wn = base(cos(ang), (inv ? 1. : -1.) * sin(ang)), w
            ;
22         for(int i = 0, j, k; i < n; i += m) {
23             for(w = base(1, 0), j = i, k = i + 1; j < k; ++j, w =
                w * wn) {
24                 base t = w * p[j + 1];
25                 p[j + 1] = p[j] - t;
26                 p[j] = p[j] + t;
27             }
28         }
29     }
30     if(inv) for(int i = 0; i < n; ++i) p[i].a /= n, p[i].b /=
        n;
31 }
32 vector<long long> multiply(vector<int> &a, vector<int> &b)
    {
33     int n = a.size(), m = b.size(), t = n + m - 1, sz = 1;
34     while(sz < t) sz <= 1;
35     vector<base> x(sz), y(sz), z(sz);
36     for(int i = 0; i < sz; ++i) {
37         x[i] = i < (int)a.size() ? base(a[i], 0) : base(0, 0);
38         y[i] = i < (int)b.size() ? base(b[i], 0) : base(0, 0);
39     }
40     fft(x), fft(y);
41     for(int i = 0; i < sz; ++i) z[i] = x[i] * y[i];
42     fft(z, 1);
43     vector<long long> ret(sz);
44     for(int i = 0; i < sz; ++i) ret[i] = (long long) round(z[
        i].a);
45     while((int)ret.size() > 1 && ret.back() == 0) ret.
        pop_back();
46     return ret;
47 }

```

LSieveBigModTernaryS

```

1 int a[], n elements;
2 int mx = 0; int ans = 0;
3 for (int i = 0; i < n; i++) {
4     mx = max(mx+a[i], (int)0);
5     ans = max(ans, mx);
6 }
7 #define sz 1000
8 vector<int> prime;
9 bitset<sz> bs;
10 void sieve() {
11     bs.set(); // all bit = 1..
12     bs[0] = bs[1] = 0;
13     prime.push_back(2);
14     for (int i = 3; i <= sz; i += 2) {
15         if(bs[i]) {
16             for (int j = i*i; j <= sz; j += i)
17                 bs[j] = 0;
18             prime.push_back(i);
19         }
20     }
21 }
22 void solve()
23 {
24     int n = 12;
25     int a[] = {60, 70, 80, 90, 100, 200, 400, 500, 600, 700,
        900, 1000};
26     int r = n-1; int l = 0;

```

```

27     // cout << (r-l) / 2;
28     while(l < r) {
29         int c = (r-l) / 3;
30         int m1 = l + c;
31         int m2 = r - c;
32         // cout << a[m1] << ' ' << a[m2] << endl;
33         if(a[m1] < a[m2]) {
34             r = m2 - 1;
35         } else if(a[m1] > a[m2]) {
36             l = m1 + 1;
37         } else {
38             l = m1 + 1; r = m2 - 1;
39         }
40     }
41     cout << a[l] << endl;
42 }
43 int mod = 1e9 + 7;
44 // linear sieve.
45 vector<int> prime;
46 bool is_composite[MAXN];
47 void sieve (int n) {
48     std::fill (is_composite, is_composite + n, false);
49     for (int i = 2; i < n; ++i) {
50         if (!is_composite[i]) prime.push_back (i);
51         for (int j = 0; j < prime.size () && i * prime[j] < n;
            ++j) {
52             is_composite[i * prime[j]] = true;
53             if (i % prime[j] == 0) break;
54         }
55     }
56 }

```

Miller Rabin

```

1 using u64 = uint64_t;
2 using u128 = __uint128_t;
3 u64 binpower(u64 base, u64 e, u64 mod) {
4     u64 result = 1;
5     base %= mod;
6     while (e) {
7         if (e & 1)
8             result = (u128)result * base % mod;
9         base = (u128)base * base % mod;
10        e >>= 1;
11    }
12    return result;
13 }
14 bool check_composite(u64 n, u64 a, u64 d, int s) {
15     u64 x = binpower(a, d, n);
16     if (x == 1 || x == n - 1)
17         return false;
18     for (int r = 1; r < s; r++) {
19         x = (u128)x * x % n;
20         if (x == n - 1)
21             return false;
22     }
23     return true;
24 };
25 bool MillerRabin(u64 n, int iter=5) { // returns true if n
    is probably prime, else returns false.
26     if (n < 4)
27         return n == 2 || n == 3;
28     int s = 0;
29     u64 d = n - 1;
30     while ((d & 1) == 0) {

```

```

31     d >= 1;
32     s++;
33 }
34 for (int i = 0; i < iter; i++) {
35     int a = 2 + rand() % (n - 3);
36     if (check_composite(n, a, d, s))
37         return false;
38 }
39 return true;
40 }
41 bool MillerRabin(u64 n) { // returns true if n is prime,
42     // else returns false.
43     if (n < 2)
44         return false;
45     int r = 0;
46     u64 d = n - 1;
47     while ((d & 1) == 0) {
48         d >= 1;
49         r++;
50     }
51     for (int a : {2, 3, 5, 7, 11, 13, 17, 19, 23, 29, 31,
52         37}) {
53         if (n == a)
54             return true;
55         if (check_composite(n, a, d, r))
56             return false;
57     }
58     return true;
59 }

```

```

31     }
32 }
33 // Scale results for Inverse NTT
34 if (invert) {
35     long long n_inv = modInverse(n);
36     for (long long x : a)
37         x = (x * n_inv) % MOD;
38 }
39 }
40 // Polynomial Multiplication
41 vector<long long> multiply(vector<long long> const& a,
42     vector<long long> const& b) {
43     vector<long long> fa(a.begin(), a.end()), fb(b.begin(),
44         b.end());
45     int n = 1;
46     while (n < a.size() + b.size())
47         n <= 1;
48     fa.resize(n);
49     fb.resize(n);
50     ntt(fa, false);
51     ntt(fb, false);
52     for (int i = 0; i < n; i++)
53         fa[i] = (fa[i] * fb[i]) % MOD;
54     ntt(fa, true);
55     // Optional: Resize to actual degree (removes trailing
56     // zeros)
57     // while (fa.size() > 1 && fa.back() == 0) fa.pop_back();
58     return fa;
59 }

```

```

6     f(j, b[0].size()) {
7         f(k, b.size()) ans[i][j] = (ans[i][j] + ((a[i][k] *
8             b[k][j]) % mod)) % mod;
9     }
10 }
11 return ans;
12 }
13 vector<vector<ll>> matexpo(vector<vector<ll>>& a, ll exp) {
14     vector<vector<ll>> res(a[0].size(), vector<ll>(a[0].size()
15         (), 0));
16     f(i, a[0].size()) res[i][i] = 1;
17     while (exp > 0) {
18         if (exp & 1) res = matmultiply(res, a);
19         a = matmultiply(a, a);
20         exp /= 2;
21     }
22     return res;
23 }
24 int main() {
25     ll n;
26     scanf("%lld", &n);
27     if (n == 0) printf("0\n");
28     else {
29         vector<vector<ll>> arr(2, vector<ll>(2, 1));
30         arr[1][1] = 0;
31         arr = matexpo(arr, n);
32         printf("%lld\n", arr[0][1]);
33     }
34 }
35 return 0;

```

NTT

```

1 // Common prime for NTT: 998244353 = 119 * 2^23 + 1
2 // Primitive root: 3
3 const int MOD = 998244353;
4 const int G = 3;
5 // Number Theoretic Transform
6 // on: true for Inverse NTT, false for Forward NTT
7 void ntt(vector<long long>& a, bool invert) {
8     int n = a.size();
9
10    // Bit-reversal permutation
11    for (int i = 1, j = 0; i < n; i++) {
12        int bit = n >> 1;
13        for (; j & bit; bit >>= 1)
14            j ^= bit;
15        if (i < j) swap(a[i], a[j]);
16    }
17    // Butterfly operations
18    for (int len = 2; len <= n; len <= 1) {
19        long long wlen = power(G, (MOD - 1) / len);
20        if (invert) wlen = modInverse(wlen);
21
22        for (int i = 0; i < n; i += len) {
23            long long w = 1;
24            for (int j = 0; j < len / 2; j++) {
25                long long u = a[i + j], v = (a[i + j + len / 2]
26                    * w) % MOD;
27                a[i + j] = (u + v) < MOD ? (u + v) : (u + v -
28                    MOD);
29                a[i + j + len / 2] = (u - v) >= 0 ? (u - v) : (-
30                    u - v + MOD);
31                w = (w * wlen) % MOD;
32            }
33        }
34    }
35 }

```

ballot

```

1 // Returns the number of paths from (0,0) to (a,b) staying
2 // at or below y = x + k
3 long long ballot_with_offset(int a, int b, int k) {
4     if (b > a + k) return 0; // Already invalid
5     long long total = nCr(a + b, a);
6     long long invalid = nCr(a + b, a + k + 1);
7     return (total - invalid + mod) % mod;
8 }
9 // Non-strict Ballot Number: A >= B at all prefixes
10 long long ballot_non_strict(int a, int b) {
11     return ballot_with_offset(a, b, 0);
12 }
13 // Strict Ballot Number: A > B at all non-empty prefixes
14 long long ballot_strict(int a, int b) {
15     if (a <= b) return 0;
16     return ballot_non_strict(a - 1, b);
17 }
18 }

```

matexpo

```

1 vector<vector<ll>> matmultiply(vector<vector<ll>>& a,
2     vector<vector<ll>>& b) {
3     if (a[0].size() != b.size()) return vector<vector<ll>>(0);
4     else {
5         vector<vector<ll>> ans(a.size(), vector<ll>(b[0].size()
6             (), 0));
7         f(i, a.size()) {
8             f(j, b[0].size()) {
9                 f(k, b.size()) ans[i][j] = (ans[i][j] + ((a[i][k] *
10                     b[k][j]) % mod)) % mod;
11             }
12         }
13     }
14 }

```

mobius

```

1 int mob[N];
2 void mobius() {
3     mob[1] = 1;
4     for (int i = 2; i < N; i++) {
5         mob[i]--;
6         for (int j = i + i; j < N; j += i) {
7             mob[j] -= mob[i];
8         }
9     }
10 }
11 bool vis[N];
12 vector<int> d[N];
13 int mul[N];
14 void add(int x, int k) {
15     for (auto y: d[x]) {
16         mul[y] += k;
17     }
18 }
19 int query(int x) {
20     int ans = 0;
21     for (auto y: d[x]) {
22         ans += mul[y] * mob[y];
23     }
24     return ans;
25 }

```

ncr

```

1 // nCr: (n,0)=1, (n,1)=n, (n,r)=(n-1,r)+(n-1,r-1)
2 // Circular permutation: nPr/r
3 ll fact[MAX], inv[MAX], invFact[MAX];
4 // nCr_mod_p_by_lucas_for_small_p_O(LogN)
5 ll Lucas(ll n, ll m) {
6     if (n == 0 && m == 0) return 1ll;
7     ll ni = n % MOD;
8     ll mi = m % MOD;
9     if (mi > ni) return 0;
10    return (Lucas(n / MOD, m / MOD) * nCr(ni, mi)) % MOD;
11 }
12 ll nCr_by_lucas(ll n, ll r) { return Lucas(n, r); }
13 // nCr_mod_M, M_is_not_prime
14 const int N = 142858; // need primes <= M (nCr%M)
15 int spf[N];
16 vector<int> primes;
17 void sieve() {
18     for (int i = 2; i < N; i++) {
19         if (spf[i] == 0) spf[i] = i, primes.push_back(i);
20         int sz = primes.size();
21         for (int j = 0; j < sz && i * primes[j] < N && primes[j] <= spf[i]; j++) spf[i * primes[j]] = primes[j];
22     }
23 }
24 // returns n! % mod, mod = multiple of p
25 // O(mod * log(n))
26 int factmod(ll n, int p, const int mod) {
27     vector<int> f(mod + 1);
28     f[0] = 1 % mod;
29     for (int i = 1; i <= mod; i++) {
30         if (i % p) f[i] = 1LL * f[i - 1] * i % mod;
31         else f[i] = f[i - 1];
32     }
33     int ans = 1 % mod;
34     while (n > 1) {
35         ans = 1LL * ans * f[n % mod] % mod;
36         ans = 1LL * ans * BigMod(f[mod], n / mod, mod) % mod;
37         n /= p;
38     }
39     return ans;
40 }
41 ll multiplicity(ll n, int p) {
42     ll ans = 0;
43     while (n) {
44         n /= p;
45         ans += n;
46     }
47     return ans;
48 }
49 // C(n, r) modulo p^k
50 // O(p^k log n)
51 int ncr(ll n, ll r, int p, int k) {
52     if (n < r || r < 0) return 0;
53     int mod = 1;
54     for (int i = 0; i < k; i++) { mod *= p; }
55     ll t = multiplicity(n, p) - multiplicity(r, p) - multiplicity(n - r, p);
56     if (t >= k) return 0;
57     int ans = 1LL * factmod(n, p, mod) * inverse(factmod(r, p, mod), mod) % mod * inverse(factmod(n - r, p, mod), mod) % mod;
58     ans = 1LL * ans * BigMod(p, t, mod) % mod;
59     return ans;
60 }

```

```

61 pair<ll, ll> CRT(ll a1, ll m1, ll a2, ll m2) {
62     ll p, q; ll g = e_gcd(m1, m2, p, q);
63     if (a1 % g != a2 % g) return make_pair(0, -1);
64     ll m = m1 / g * m2;
65     p = (p % m + m) % m;
66     q = (q % m + m) % m;
67     return make_pair((p * a2 % m * (m1 / g) % m + q * a1 % m * (m2 / g) % m) % m, m);
68 }
69 // O(m log(n) log(m))
70 int ncr(ll n, ll r, int m) {
71     if (n < r || r < 0) return 0;
72     pair<ll, ll> ans({0, 1});
73     while (m > 1) {
74         int p = spf[m], k = 0, cur = 1;
75         while (m % p == 0) {
76             m /= p; cur *= p; ++k;
77         }
78         ans = CRT(ans.first, ans.second, ncr(n, r, p, k), cur);
79     }
80     return ans.first;
81 }

```

stirling_number

```

1 // S(n,k) = (1/k!) * sum_{i=0..k} (-1)^i * C(k,i) * (k-i)^n
2 int main() {
3     int n, k; cin >> n >> k;
4     vector<ll> fact(k+1, 1), invfact(k+1, 1);
5     ll ans = 0;
6     for (int i = 0; i <= k; i++) {
7         ll term = fact[k] * invfact[i] % MOD * invfact[k-i] % MOD;
8         term = term * power(k - i, n) % MOD;
9         if (i & 1) ans = (ans - term + MOD) % MOD;
10        else ans = (ans + term) % MOD;
11    }
12    ans = ans * modinv(fact[k]) % MOD;
13    cout << ans << "\n";
14 }

```

totient

```

1 int phi(int n) {
2     int result = n;
3     for (int i = 2; i * i <= n; i++) {
4         if (n % i == 0) {
5             while (n % i == 0) n /= i;
6             result -= result / i;
7         }
8     }
9     if (n > 1) result -= result / n;
10    return result;
11 }
12 void phi_1_to_n(int n) {
13     vector<int> phi(n + 1);
14     for (int i = 0; i <= n; i++) phi[i] = i;
15     for (int i = 2; i <= n; i++) {
16         if (phi[i] == i) {
17             for (int j = i; j <= n; j += i) phi[j] -= phi[j] / i;
18         }
19     }
20 }

```

```

19 }
20 }
21 void phi_1_to_n(int n) {
22     vector<int> phi(n + 1);
23     phi[0] = 0; phi[1] = 1;
24     for (int i = 2; i <= n; i++) phi[i] = i - 1;
25
26     for (int i = 2; i <= n; i++)
27         for (int j = 2 * i; j <= n; j += i) phi[j] -= phi[i];
28 }

```

String

AhoCorasick

```

1 typedef struct AC {
2     static const int K = 26;
3     struct node {
4         int nxt[K], link, leaf, par;
5         vector<int> ind;
6         char pch;
7         node(int par = -1, char pch = '$') : par(par), pch(pch) {
8             fill(begin(nxt), end(nxt), -1);
9             leaf = false;
10            link = -1;
11        }
12    };
13    vector<node> t;
14    vector<vector<int>> ad;
15    vector<int> st, en, mp;
16    vector<int> cnt;
17    int dt = 0;
18    AC() {
19        mp = vector<int> (1<<8, 0);
20        for (char ch = 'a'; ch <= 'z'; ++ch) mp[ch] = ch - 'a';
21    }
22    t.resize(1);
23    cnt.resize(1);
24
25    int add(string str, int i) {
26        int ptr = 0;
27        for (auto ch : str) {
28            if (t[ptr].nxt[mp[ch]] < 0) {
29                t[ptr].nxt[mp[ch]] = t.size();
30                t.push_back(node(ptr, ch));
31                cnt.push_back(0);
32            }
33            ptr = t[ptr].nxt[mp[ch]];
34        }
35        t[ptr].leaf = true;
36        t[ptr].ind.push_back(i);
37        return ptr;
38    }
39    int get_link(int v) {
40        if (t[v].link == -1) {
41            t[v].link = (!v || !t[v].par) ? 0 : go(get_link(t[v].par), t[v].pch);
42        }
43        return t[v].link;
44    }
45    int go(int v, char ch) {
46        if (t[v].nxt[mp[ch]] < 0) {
47            t[v].nxt[mp[ch]] = !v ? 0 : go(get_link(v), ch);
48        }
49    }

```

```

47     }
48     return t[v].nxt[mp[ch]];
49 }
50 void dfs(int v) {
51     st[v] = ++dt;
52     for (int u : ad[v]) {
53         dfs(u);
54         cnt[v] += cnt[u];
55     }
56     en[v] = dt;
57 }
58 void calc() {
59     int k = t.size();
60     st.resize(k);
61     en.resize(k);
62     ad.resize(k);
63     for (int i = 1; i < k; i++)
64         ad[get_link(i)].push_back(i);
65     dfs(0);
66 }
67 } cc;
68 int cs = 1;
69 void solve() {
70     cc bc;
71     int n; cin >> n;
72     vector<int> res(n + 1, 0);
73     string text;
74     cin >> text;
75     string p;
76     for (int i = 1; i <= n; i++) {
77         cin >> p;
78         bc.add(p, i);
79     }
80     int vertex = 0;
81     for (int i = 0; i < text.length(); i++) {
82         vertex = bc.go(vertex, text[i]);
83         bc.cnt[vertex]++;
84     }
85     bc.calc();
86     for (int i = 1; i < bc.t.size(); i++) {
87         for (int &x : bc.t[i].ind) res[x] += bc.cnt[i];
88     }
89     cout << "Case " << cs++ << ":\n";
90     for (int i = 1; i <= n; i++) cout << res[i] << "\n";
91 }

```

Manacher

```

1 struct Manacher {
2     vector<int> p[2];
3     // p[1][i] = (max odd length palindrome centered at i) /
4     // 2 [floor division]
5     // p[0][i] = same for even, it considers the right center
6     // e.g. for s = "abbabba", p[1][3] = 3, p[0][2] = 2
7     Manacher(string s) {
8         int n = s.size();
9         p[0].resize(n + 1);
10        p[1].resize(n);
11        for (int z = 0; z < 2; z++) {
12            for (int i = 0, l = 0, r = 0; i < n; i++) {
13                int t = r - i + !z;
14                if (i < r) p[z][i] = min(t, p[z][l + t]);
15                int L = i - p[z][i], R = i + p[z][i] - !z;
16                while (L >= 1 && R + 1 < n && s[L - 1] == s[R + 1])
17                    p[z][i]++, L--, R++;
18            }
19        }
20    }
21 }

```

```

17     if (R > r) l = L, r = R;
18 }
19 }
20 }
21 bool is_palindrome(int l, int r) {
22     int mid = (l + r + 1) / 2, len = r - l + 1;
23     return 2 * p[len % 2][mid] + len % 2 >= len;
24 }
25 };
26 int32_t main() {
27     string s; cin >> s;
28     Manacher M(s);
29     int n = s.size();
30     for (int i = 0; i < n; i++) {
31         cout << 2 * M.p[1][i] + 1 << ' ';
32         if (i + 1 < n) cout << 2 * M.p[0][i + 1] << ' ';
33     }
34     cout << '\n';
35     return 0;
36 }

```

Suffix Automata

```

1 // Suffix Automaton (SAM)
2 // Handles all substrings of a string in linear time
3 struct State {
4     int next[26];
5     int link, len;
6     State() {
7         memset(next, -1, sizeof next);
8         link = -1;
9         len = 0;
10    }
11 };
12 vector<State> st;
13 int last;
14 // initialize
15 void sa_init() {
16     st.clear(); st.push_back(State()); last = 0;
17 }
18 // extend by character c
19 void sa_extend(char ch) {
20     int c = ch - 'a';
21     int cur = st.size();
22     st.push_back(State());
23     st[cur].len = st[last].len + 1;
24     int p = last;
25     while (p != -1 && st[p].next[c] == -1) {
26         st[p].next[c] = cur;
27         p = st[p].link;
28     }
29     if (p == -1) {
30         st[cur].link = 0;
31     } else {
32         int q = st[p].next[c];
33         if (st[p].len + 1 == st[q].len) {
34             st[cur].link = q;
35         } else {
36             int clone = st.size();
37             st.push_back(st[q]);
38             st[clone].len = st[p].len + 1;
39             while (p != -1 && st[p].next[c] == q) {
40                 st[p].next[c] = clone; p = st[p].link;
41             }
42             st[q].link = st[cur].link = clone;
43         }
44     }
45 }

```

```

43     }
44 }
45 last = cur;
46 }
47 // count distinct substrings
48 long long count_distinct() {
49     long long ans = 0;
50     for (auto &s : st)
51         ans += s.len - (s.link == -1 ? 0 : st[s.link].len);
52     return ans;
53 }

```

palindromitree

```

1 const int MAXN = 105000;
2 struct node {
3     int next[26];
4     int len;
5     int sufflink;
6     int num;
7 };
8 int len;
9 char s[MAXN];
10 node tree[MAXN];
11 int num; // node 1 - root with len -1, node 2 - root with
12 // len 0
13 int suff; // max suffix palindrome
14 long long ans;
15 bool addLetter(int pos) {
16     int cur = suff, curlen = 0;
17     int let = s[pos] - 'a';
18     while (true) {
19         curlen = tree[cur].len;
20         if (pos - 1 - curlen >= 0 && s[pos - 1 - curlen] == s[pos])
21             break;
22         cur = tree[cur].sufflink;
23     }
24     if (tree[cur].next[let]) {
25         suff = tree[cur].next[let];
26         return false;
27     }
28     num++;
29     suff = num;
30     tree[num].len = tree[cur].len + 2;
31     tree[cur].next[let] = num;
32     if (tree[num].len == 1) {
33         tree[num].sufflink = 2;
34         tree[num].num = 1;
35         return true;
36     }
37     while (true) {
38         cur = tree[cur].sufflink;
39         curlen = tree[cur].len;
40         if (pos - 1 - curlen >= 0 && s[pos - 1 - curlen] == s[pos]) {
41             tree[num].sufflink = tree[cur].next[let];
42             break;
43         }
44     }
45     tree[num].num = 1 + tree[tree[num].sufflink].num;
46     return true;
47 }
48 void initTree() {
49     num = 2; suff = 2;
50 }

```

```

49     tree[1].len = -1; tree[1].sufflink = 1;
50     tree[2].len = 0; tree[2].sufflink = 1;
51 }
52 int main() {
53     //assert(freopen("input.txt", "r", stdin));
54     //assert(freopen("output.txt", "w", stdout));
55     gets(s); len = strlen(s);
56     initTree();
57     for (int i = 0; i < len; i++) {
58         addLetter(i);
59         ans += tree[suff].num;
60     }
61 }

```

suffixArray

```

1 struct SuffixArray {
2     int n; string s;
3     vector<int> sa, rankv, tmp, lcp;
4     SuffixArray(const string &str) {
5         s = str; n = s.size(); sa.resize(n); rankv.resize(n);
6         tmp.resize(n); build(); build_lcp();
7     }
8     void counting_sort(int k) {
9         int maxi = max(256ll, (long long)n) + 5;
10        vector<int> cnt(maxi, 0), sa2(n);
11        for (int i = 0; i < n; i++) {
12            int key = (i + k < n) ? rankv[i + k] + 1 : 0;
13            cnt[key]++;
14        }
15        for (int i = 1; i < maxi; i++) cnt[i] += cnt[i - 1];
16        for (int i = n - 1; i >= 0; i--) {
17            int key = (sa[i] + k < n) ? rankv[sa[i] + k] + 1 : 0;
18            sa2[--cnt[key]] = sa[i];
19        }
20        sa.swap(sa2);
21    }
22    void build() {
23        for (int i = 0; i < n; i++) {
24            sa[i] = i; rankv[i] = (unsigned char)s[i];
25        }
26        for (int k = 1; k < n; k <= 1) {
27            counting_sort(k);
28            counting_sort(0);
29            tmp[sa[0]] = 0;
30            int r = 0;
31            for (int i = 1; i < n; i++) {
32                int cur1 = rankv[sa[i]], cur2 = (sa[i] + k < n
33                ? rankv[sa[i] + k] : -1);
34                int prev1 = rankv[sa[i - 1]], prev2 = (sa[i - 1]
35                + k < n ? rankv[sa[i - 1] + k] : -1);
36                if (cur1 != prev1 || cur2 != prev2) r++;
37                tmp[sa[i]] = r;
38            }
39            rankv.swap(tmp);
40            if (r == n - 1) break;
41        }
42    }
43    void build_lcp() {
44        lcp.assign(max(0, n - 1), 0);
45        vector<int> inv(n);
46        for (int i = 0; i < n; ++i) inv[sa[i]] = i;
47        int k = 0;
48        for (int i = 0; i < n; ++i) {

```

```

46         if (inv[i] == n - 1) { k = 0; continue; }
47         int j = sa[inv[i] + 1];
48         while (i + k < n && j + k < n && s[i + k] == s[j + k]) ++k;
49         lcp[inv[i]] = k;
50         if (k) --k;
51     }
52 }
53 };
54 void solve(const string &s, const string &t) {
55     // build local combined string so we don't mutate inputs
56     int n = s.size();
57     string combined = s + '$' + t;
58     int N = combined.size();
59     SuffixArray sa(combined);
60 }

```

z kmp

```

1 vector<int> prefix_function(string s) {
2     int n = (int)s.length();
3     vector<int> pi(n);
4     for (int i = 1; i < n; i++) {
5         int j = pi[i - 1];
6         while (j > 0 && s[i] != s[j])
7             j = pi[j - 1];
8         if (s[i] == s[j])
9             j++;
10        pi[i] = j;
11    }
12    return pi;
13 }
14 vector<int> z_function(string pattern, string text) {
15     string s = pattern + "$" + text;
16     int n = size(s);
17     vector<int> z(n);
18     for (int i = 1, l = 0, r = 0; i < n; ++i) {
19         if (i <= r)
20             z[i] = min(r - i + 1, z[i - l]);
21         while (i + z[i] < n && s[z[i]] == s[i + z[i]])
22             ++z[i];
23         if (i + z[i] - 1 > r)
24             l = i, r = i + z[i] - 1;
25     }
26     return z;
27 }

```