


Environments, Scope, and Lazy Evaluation

Environments and variable scope

R has a special mechanism for allowing you to use the same name in different places in your code and have it refer to different objects.


For example, you want to be able to create new variables in your functions and not worry if there are variables with the same name already in the workspace.

The solution relies on *environments* and the *variable scoping rules*.



Global Environment
Contains objects we
defined/source into
our work space

Global Env



```
x = seq(1, 7, 2)
y = rep(2, 3)
z = 17

lookAt = function(x) {
  y = 3
  print(x)
  print(y)
  print(z)
}
```

Global Env

x is vector: 1 3 5 7
y is vector: 2 2 2
z is vector: 17

lookAt is a function
object

Global Env

x is vector: 1 3 5 7
y is vector: 2 2 2
z is vector: 17

lookAt is a function
object

When we call a
function, a new
workspace,
AKA a frame, is
created

lookAt(x = c(0,100))

Global Env

x is vector: 1 3 5 7
y is vector: 2 2 2
z is vector: 17

lookAt is a function
object

lookAt(x = c(0,100))

This call frame has
Global Env as its
parent environment

Global Env

x is vector: 1 3 5 7
y is vector: 2 2 2
z is vector: 17

lookAt is a function
object

In the frame,
variables are
created for the
arguments in the
function call

lookAt(x = c(0,100))

x = c(0, 100)

Global Env

x is vector: 1 3 5 7
y is vector: 2 2 2
z is vector: 17

lookAt is a function
object

As the code in the
function is
evaluated, new
objects are added
to the call frame

lookAt(x = c(0,100))

x = c(0, 100)

Global Env

x is vector: 1 3 5 7
y is vector: 2 2 2
z is vector: 17

lookAt is a function
object

```
lookAt =  
function(x) {  
  y = 3  
  print(x)  
  print(y)  
  print(z)  
}
```

lookAt(x = c(0,100))

x = c(0, 100)

y is vector 3

Global Env

x is vector: 1 3 5 7
y is vector: 2 2 2
z is vector: 17

lookAt is a function
object

lookAt(x = c(0,100))

```
lookAt =  
function(x) {  
  y = 3  
  print(x)  
  print(y)  
  print(z)  
}
```

x = c(0, 100)

Global Env

x is vector: 1 3 5 7
y is vector: 2 2 2
z is vector: 17

lookAt is a function
object

lookAt(x = c(0,100))


CONSOLE
[1] 0 100

```
lookAt =  
function(x) {  
  y = 3  
  print(x)  
  print(y)  
  print(z)  
}
```

x is vector 0

100

y is vector 3



What is happening is that R is looking for variables with that name in a sequence of environments. An *environment* is just a frame (collection of variables) plus a pointer to the next environment to look in.

In our example, R does not find **z** in the environment defined by `lookAt`, so it went on to the next one. In this case, this is our main workspace, which is the *Global Environment*.

The “next environment to look in” is called the parent environment.

Finding Objects

We can ask R to find objects for us:

```
> find("pi")  
[1] "package:base"
```

```
> find("z")  
[1] ".GlobalEnv"
```

```
> find("ggplot")  
[1] "package:ggplot2"
```

Finding Objects

The package codetools helps us find global variables in our functions:

```
> library(codetools)
> findGlobals(lookAt)
```

```
[1] "-"      ":"      "{"      "="      ">"
[6] "if"     "print"  "z"
```

Global Env

```
x is vector: 1 3 5 7
y is vector: 2 2 2
z is vector: 17
```

```
lookAt is a function
object
```

```
lookAt =
function(x) {
  y = 3
  print(x)
  print(y)
  print(z)
}
```

lookAt(z)

x is copy of z

Global Env

```
x is vector: 1 3 5 7
y is vector: 2 2 2
z is vector: 17
```

```
lookAt is a function
object
```

```
lookAt =
function(x) {
  y = 3
  print(x)
  print(y)
  print(z)
}
```

lookAt(z)

```
x is a copy of z
y is vector 3
```

Global Env

```
x is vector: 1 3 5 7
y is vector: 2 2 2
z is vector: 17
```


```
lookAt is a function
object
```

```
lookAt =
function(x) {
  y = 3
  print(x)
  print(y)
  print(z)
}
```

lookAt(z)

```
CONSOLE
[1] 17
```

```
x is 17
y is vector 3
```



The inputs for a function call are not evaluated until they are needed

Lazy Evaluation

R sets up a call frame for the function with the input arguments as variables BUT these are only associated with an expression. When the variable is references in the code then this expression is evaluated

This is called *lazy evaluation*.

```
funnyMean =
  function(x, y = mean(x))
{
  set.seed(1234)
  return(y)
}
```

```
> set.seed(1234)
> mean(runif(2))
[1] 0.3680014
```

```
> set.seed(6789)
> mean(runif(2))
[1] 0.4268003
```

What does

```
> set.seed(6789)
> funnyMean(runif(2))
```

Return?

- A. 0.3680014
- B. 0.4268003
- C. Some other value

```
funnyMean =
  function(x, y = mean(x))
{
  set.seed(1234)
  return(y)
}
```

```
set.seed(1234)
funnyMean(runif(2))
```

x is runif(2)
y is mean(x)

```
funnyMean =
  function(x, y = mean(x))
{
  set.seed(1234)
  return(y)
}
```

```
set.seed(1234)
funnyMean(runif(2))
```

x is runif(2)
y is mean(x)

seed is 1234

```
funnyMean =
  function(x, y = mean(x))
{
  set.seed(1234)
  return(y)
}
```

```
set.seed(1234)
funnyMean(runif(2))
```

x is [1] 0.1137 0.6222
y is 0.3680014

```
[1] 0.3680014
```

seed is 1234

The parameter **x** has not been specified in the function call so the frame is set up with **x** as a variable with no contents

This doesn't cause a problem.

The first time that **x** is referred to it needs to have a value.

It's not a good idea to set the seed inside a function, unless expressly asked to via an input parameter

```
> set.seed(6789)
> funnyMean2(runif(2))
[1] 0.4268003
```

```
> funnyMean2(runif(2))
[1] 0.3680014
> funnyMean2(runif(2))
[1] 0.3680014
```

CAN you figure out what's happening?

funnyMean2 keeps resetting the seed to 1234.

It's an example of what can go wrong when we set a seed

```
funnyMean2 =
  function(x, y = mean(x))
  {
    if (any(is.na(x)) {
      warning("Founds NA")
    }
    set.seed(1234)
    return(y)
  }
```

What does

```
> set.seed(6789)
> funnyMean2(runif(2))
```

Return?

A. 0.3680014
B. 0.4268003
C. Some other value

```
> set.seed(1234)
> mean(runif(2))
[1] 0.3680014

> set.seed(6789)
> mean(runif(2))
[1] 0.4268003
```

If R reaches the Global Environment and still can't find the variable, it looks in something called the *search path*. This is a list of additional environments, which is used for packages of functions and user attached data. You can see the search path by typing `search()`.

This helps explain why we can write over built-in objects in R. What we're really doing is creating that object in the Global Environment, and then when we refer to it by name, R finds it here before it finds the predefined one.

```
> help(pi)
> pi = 3
> pi
> rm(pi)
> pi
```


Assignment in Parent Environment

Global Env

x is vector: 1 3 5 7
y is vector: 2 2 2
z is vector: 17

lookAt is a function
object

```
lookAt3 =  
function(x) {  
  y <- 17  
  y = 3  
  print(x)  
  print(y)  
}
```

lookAt3(z)

x is a copy of z

Global Env

x is vector: 1 3 5 7
y is vector: 17
z is vector: 17

lookAt is a function
object

```
lookAt3 =  
function(x) {  
  y <- 17  
  y = 3  
  print(x)  
  print(y)  
}
```

lookAt3(z)

x is a copy of z

Global Env

x is vector: 1 3 5 7
y is vector: 17
z is vector: 17

lookAt is a function
object

```
lookAt3 =  
function(x) {  
  y <- 17  
  y = 3  
  print(x)  
  print(y)  
}
```

lookAt3(z)

x is a copy of z
y is vector 3

Global Env

x is vector: 1 3 5 7
y is vector: 17
z is vector: 17

lookAt is a function
object

```
lookAt3 =  
function(x) {  
  y <- 17  
  y = 3  
  print(x)  
  print(y)  
}
```

lookAt3(z)

CONSOLE
[1] 17

x is vector 17
y is vector 3

Call Frames for Function Calls within Function

Global Env

x is vector: 1 3 5 7
y is vector: 17
z is vector: 17

lookAt is a function
object

```
lookAt3 =  
function(x) {  
  y <- 17  
  y = 3  
  print(x)  
  print(y)  
}
```

lookAt3(z)

CONSOLE
[1] 17
[1] 3


x is vector 17
y is vector 3

```
lA = function() {  
  print(x)  
}  
  
lookAt4 = function()  
{  
  x = 3  
  lA()  
  print(x)  
}
```

When the lA function
is defined in the Global
Env, it's parent
environment is Global
Env

```
lookAt4A = function()  
{  
  lA = function() {  
    print(x)  
  }  
  
  x = 3  
  lA()  
  print(x)  
}
```

When the lA function
is defined in the body
of lookAt4E, it's parent
environment is
lookAt4E's frame



```

lA = function() {
  print(x)
}

lookAt4 = function()
{
  x = 3
  lA()
  print(x)
}

```

```

Global env
x is 1 3 5 7
y is 2 2 2
z is 35
lA, lookAt4,
and lookAt4A

```

```

lookAt4A = function()
{
  lA = function() {
    print(x)
  }

  x = 3
  lA()
  print(x)
}

```

```

> lookAt4()
> lookAt4A()

A.Same
B.Different

```

The function definition for lA is in the Global environment.

When lA is called in the code in lookAt4 (), a call frame is set up for lA () .

It's parent environment is Global Env

The function definition for lA is in the Global environment.

When lA is called in the code in lookAt4A (), a call frame is set up for lA () .

It's parent environment is the lookAt4A frame.

Additional Examples

Global Env

x is vector: 1 3 5 7
y is vector: 2 2 2
z is vector: 17

lookAt2 is a function
object

```
lookAt2 =  
function(x) {  
  y = 3  
  if (z > 25) x=-1:-4  
  print(x)  
  print(y)  
  print(z)  
}
```

lookAt2()

x is an object
of some kind

Global Env

x is vector: 1 3 5 7
y is vector: 2 2 2
z is vector: 17

lookAt2 is a function
object

```
lookAt2 =  
function(x) {  
  y = 3  
  if (z > 25) x=-1:-4  
  print(x)  
  print(y)  
  print(z)  
}
```

lookAt2()

x is an object
of some kind
y is vector 3

Global Env

x is vector: 1 3 5 7
y is vector: 2 2 2
z is vector: 17

lookAt2 is a function
object

```
lookAt2 =  
function(x) {  
  y = 3  
  if (z > 25) x=-1:-4  
  print(x)  
  print(y)  
  print(z)  
}
```

lookAt2()

x is an object
of some kind
y is vector 3

Global Env

x is vector: 1 3 5 7
y is vector: 2 2 2
z is vector: 17

lookAt2 is a function
object

```
lookAt2 =  
function(x) {  
  y = 3  
  if (z > 25) x=-1:-4  
  print(x)  
  print(y)  
  print(z)  
}
```

lookAt2()

CONSOLE

Error in print(x) :
argument "x" is
missing, with no
default

x is an object
of some kind
y is vector 3

Global Env

x is vector: 1 3 5 7
y is vector: 2 2 2
z is vector: 17

lookAt2 is a function
object

```
lookAt2 =  
function(x) {  
  y = 3  
  if (z > 25) x=-1:-4  
  print(x)  
  print(y)  
  print(z)  
}
```

z = 35
lookAt2()

x is an object
of some kind
y is vector 3

Global Env

x is vector: 1 3 5 7
y is vector: 2 2 2
z is vector: 35

lookAt2 is a function
object

z = 35
lookAt2()

```
lookAt2 =  
function(x) {  
  y = 3  
  if (z > 25) x=-1:-4  
  print(x)  
  print(y)  
  print(z)  
}
```

x is an object
of some kind

Global Env

x is vector: 1 3 5 7
y is vector: 2 2 2
z is vector: 35

lookAt2 is a function
object

z = 35
lookAt2()

```
lookAt2 =  
function(x) {  
  y = 3  
  if (z > 25) x=-1:-4  
  print(x)  
  print(y)  
  print(z)  
}
```

x is vector -1 -2 -3 -4
y is vector 3

Global Env

x is vector: 1 3 5 7
y is vector: 2 2 2
z is vector: 35

lookAt2 is a function
object

z = 35
lookAt2()

CONSOLE

[1] -1 -2 -3 -4

```
lookAt2 =  
function(x) {  
  y = 3  
  if (z > 25) x=-1:-4  
  print(x)  
  print(y)  
  print(z)  
}
```

x is vector -1 -2 -3 -4
y is vector 3

Global Env

x is vector: 1 3 5 7
y is vector: 2 2 2
z is vector: 35

lookAt2 is a function
object

z = 35
lookAt2()

CONSOLE

[1] -1 -2 -3 -4
[1] 3

```
lookAt2 =  
function(x) {  
  y = 3  
  if (z > 25) x=-1:-4  
  print(x)  
  print(y)  
  print(z)  
}
```

x is vector -1 -2 -3 -4
y is vector 3

Global Env

x is vector: 1 3 5 7
y is vector: 2 2 2
z is vector: 35

lookAt2 is a function
object

z = 35
lookAt2()

CONSOLE

[1] -1 -2 -3 -4
[1] 3
[1] 35

```
lookAt2 = function(x) {  
  y = 3  
  if (z > 25) x=-1:-4  
  print(x)  
  print(y)  
  print(z)  
}
```

x is vector -1 -2 -3 -4
y is vector 3

```
lookAt2 =  
function(x) {  
  y = 3  
  if (z > 25) {  
    x=-1:-4  
  }  
  print(x)  
  print(y)  
  print(z)  
}
```

Global env
x is 1 3 5 7
y is 2 2 2
z is 17

lookAt2(4)

A. [1] -1 -2 -3 -4

[1] 3
[1] 35

B. [1] 4

[1] 3
[1] 35

C. Error in print(x)
: argument "x" is
missing, with no
default

```
lookAt2 =  
  function(x) {  
    y = 3  
    if (z > 25) {  
      x=-1:-4  
    }  
    print(x)  
    print(y)  
    print(z)  
  }
```

```
Global env  
x is 1 3 5 7  
y is 2 2 2  
z is 35
```

```
lookAt2(4)
```

A. [1] -1 -2 -3 -4
[1] 3
[1] 35

B. [1] 4
[1] 3
[1] 35

C. Error in print(x)
: argument "x" is
missing, with no
default