

General Principles:

Naming Conventions: Use snake_case, with lowercase letters and underscores(_) to separate words.

Language: English

Avoid Reserved Words: Do not use SQL reserved words as object names.

Glossary of Categories:

Category	Meaning	Example
dim_	Dimension table	dim_customer, dim_product
fact_	Fact Table	fact_sales
agg_	Aggregated table	agg_customer, agg_sales_monthly
_key	Column is a surrogate key	customer_key
dwh_	Column contains technical information or metadata	dwh_load_date
load_	Stored procedure for loading data	load_bronze

Table Naming Conventions:

Bronze Layer

- Names begin with the source system name and table names must match their original names.
- ie `crm_customer_info`, `erp_az12`

Silver Layer

- Names begin with the source system name, tables match their original names.
- ie `crm_customer_info`, `erp_az12`

Gold Layer

- Names use meaningful business-aligned names for tables, beginning with a category prefix.
- category: Describes the role of the table `dim` (dimension) or `fact` (fact table)
- entity: Descriptive name of table, aligned with business domain (ie customers, products, sales)
- ie `dim_customer`, `fact_sales`

Column Naming Conventions:

Surrogate Keys

- Primary keys in dimension
- `<table_name>_<key>`
- `<table_name>`: refers to the name of the table or the entity the key belongs to
- `_key`: indicates the column is a surrogate key
- ie `customer_key` -> Surrogate key in the `dim_customers` table

Technical Columns

- Technical columns start with prefix dwh_, followed by a descriptive name indicating the column's purpose.
- dwh_<column_name>
- ie dwh_load_date -> system-generated column used to store the date when the record was loaded.

Stored Procedures

- Stored procedures used for loading data follow the naming convention: load_
- ie load_bronze -> stored procedure for loading data into the Silver layer.