

# System Architecture Document (SAD)

## Sovereign AI Infrastructure: Bicameral Validator Ladder

**Document Version:** 1.0  
**Date:** February 5, 2026  
**Status:** Draft for Review  
**Owner:** Solutions Architect / Technical Lead

### Document Control

Version	Date	Author	Changes
1.0	2026-02-05	Architecture Team	Initial draft

- Reviewers:**
- ☐ Technical Lead
  - ☐ Engineering Manager
  - ☐ ML Lead
  - ☐ DevOps Lead
  - ☐ Security Architect
- Dependencies:**
- Product Requirements Document (PRD) v1.0
  - Technical Analysis Report (Deep Agent Report)
  - Comprehensive Architecture Report (Hybrid Logic Router)

### Table of Contents

- 1. [Executive Summary](#)
- 2. [Architectural Overview](#)
- 3. [System Context & Boundaries](#)
- 4. [Component Architecture](#)
- 5. [Data Flow Architecture](#)
- 6. [Deployment Architecture](#)
- 7. [Technology Stack](#)
- 8. [Interface Specifications](#)
- 9. [Scalability & Performance](#)
- 10. [Security Architecture](#)
- 11. [Monitoring & Observability](#)
- 12. [Development & Build Architecture](#)
- 13. [Appendices](#)

# 1. Executive Summary

## 1.1 Purpose

This System Architecture Document (SAD) provides a comprehensive technical blueprint for the **Sovereign AI Infrastructure**, a local multi-model AI orchestration system with built-in validation, transparent governance, and multimodal capabilities. This document translates the requirements from the PRD into detailed technical designs that implementation teams can directly execute.

## 1.2 Architectural Approach


The architecture is built on **three foundational principles**:

- 1. **Bicameral Heterogeneous Compute**: Separation of creative generation (GPU) from critical validation (CPU) to eliminate model thrashing
- 2. **Declarative Governance**: Routing and validation logic expressed as declarative Prolog rules, not imperative code
- 3. **Transparent Memory**: Markdown-based persistent memory serving as an auditable, human-readable ledger

## 1.3 Key Architectural Decisions

Decision	Rationale	Alternatives Considered
Hybrid Python/Prolog	Python for orchestration/integration, Prolog for logic/routing	Pure Python (less expressive for rules), Pure Prolog (poor ML ecosystem)
CPU-Resident Validator	Eliminates GPU model swapping for validation	GPU validator (causes thrashing), No validation (no quality governance)
Markdown Memory Bus	Human-readable, Git-trackable, transparent	SQL database (opaque), JSON (less readable), Neural memory (black box)
Warm Pool in RAM	Fast model swapping (<3s vs. >10s from disk)	Always load from disk (slow), Keep all in VRAM (impossible with 16GB)
Sequential Task Execution	Simpler, avoids concurrency complexity in v1.0	Concurrent execution (more complex, deferred to v2.0)

## 1.4 Architecture at a Glance



## 2. Architectural Overview


### 2.1 Architectural Style

The system employs a **hybrid architectural style**:

- **Hub-and-Spoke** for model orchestration (Router as hub, Workers as spokes)

- **Pipes-and-Filters** for data flow (Request → Route → Generate → Validate → Commit)
- **Shared-Memory** for state management (Markdown files as shared ledger)
- **Layered** for separation of concerns (UI → Orchestration → Inference → Hardware)

## 2.2 Architectural Layers



## 2.3 Core Architectural Patterns

### Pattern 1: Bicameral Processing

- **Creative Hemisphere** (GPU): Fast, parallel, deep generation
- **Critical Hemisphere** (CPU): Sequential, logical, validation
- **Benefit**: No model thrashing; validation doesn't block generation

### Pattern 2: Declarative Routing

- **Implementation**: Prolog predicates define routing logic
- **Benefit**: Rules are inspectable, modifiable without code changes
- **Example**: `route(coding, high_stakes) → qwen_coder + block_validation`

### Pattern 3: Transparent Memory Bus


- **Implementation**: Markdown files as shared memory
- **Benefit**: Human-readable audit trail; Git version control
- **Example**: Every decision, output, correction logged in `scratchpad.md`

### Pattern 4: Predictive Warm Pool

- **Implementation**: Pre-load likely-next models into RAM
- **Benefit**: 3-5x faster model swaps (3s vs. 10-15s)
- **Example**: If current task is coding, pre-load Qwen Coder

### 3. System Context & Boundaries

#### 3.1 System Context Diagram (C4 Level 1)



#### 3.2 External Interfaces

Interface	Direction	Protocol	Purpose	Notes
CLI	Bidirectional	stdin/stdout	User interaction	Primary interface for v1.0
REST API	Bidirectional	HTTP/JSON	Programmatic access	Secondary interface
Model Repository	Outbound	HTTPS	Model downloads	One-time; offline operation afterward
Git	Outbound	Git protocol	Memory versioning	Optional; local Git sufficient
Monitoring	Outbound	Prometheus protocol	Metrics export	For observability

### 3.3 System Boundaries

**In Scope** (System Responsibilities):

- Request routing and model selection
- Model orchestration and lifecycle management
- Generation with validation
- Multimodal input processing (OCR, vision, embeddings)
- Memory ledger management
- Audit trail generation
- Performance monitoring

**Out of Scope** (External Responsibilities):

- Model training or fine-tuning
  - User authentication (single-user system in v1.0)
  - Distributed multi-node deployment
  - Real-time streaming (<1s responses)
  - GUI (deferred to v1.1)
-

## 4. Component Architecture

---

### 4.1 Container Diagram (C4 Level 2)

```

graph TB
  subgraph "Presentation Layer"
    CLI[CLI Interface<br/>Python Click]
    API[REST API<br/>FastAPI]
  end

  subgraph "Orchestration Layer"
    Orchestrator[Orchestrator<br/>Python<br/>Request coordination]
    RouterSvc[Router Service<br/>Prolog + Python<br/>Intent classification]
    MemMgr[Memory Manager<br/>Python<br/>Markdown I/O]
    Telemetry[Telemetry Service<br/>Python<br/>Prometheus client]
  end

  subgraph "Inference Services (CPU)"
    RouterModel[Router Model<br/>llama.cpp<br/>Granite-Micro 3B]
    ValidatorModel[Validator Model<br/>llama.cpp<br/>Granite-H-Small]
    ToolSvc[Tool Services<br/>Python<br/>OCR/Vision/Embeddings]
  end

  subgraph "Inference Services (GPU)"
    WorkerLoader[Model Loader<br/>Python<br/>Warm pool mgmt]
    Worker1[Worker 1<br/>llama.cpp<br/>Qwen Coder 32B]
    Worker2[Worker 2<br/>llama.cpp<br/>Nemotron 30B]
    Worker3[Worker 3<br/>llama.cpp<br/>GPT-OSS 20B]
    Worker4[Worker 4<br/>llama.cpp<br/>MythoMax 13B]
  end

  subgraph "Storage Layer"
    ModelVault[Model Vault<br/>NVMe SSD<br/>GGUF files]
    MemoryLedger[Memory Ledger<br/>Filesystem<br/>Markdown files]
    VectorStore[Vector Store<br/>FAISS<br/>Embeddings DB]
  end

  CLI --> Orchestrator
  API --> Orchestrator

  Orchestrator --> RouterSvc
  Orchestrator --> MemMgr
  Orchestrator --> Telemetry
  Orchestrator --> ValidatorModel
  Orchestrator --> WorkerLoader

  RouterSvc --> RouterModel
  RouterSvc --> ToolSvc

  WorkerLoader --> Worker1
  WorkerLoader --> Worker2
  WorkerLoader --> Worker3
  WorkerLoader --> Worker4

  ToolSvc --> VectorStore

  MemMgr --> MemoryLedger
  WorkerLoader --> ModelVault

  style Orchestrator fill:#4A90E2,stroke:#333,stroke-width:3px,color:#fff
  style RouterSvc fill:#50E3C2,stroke:#333,stroke-width:2px
  style WorkerLoader fill:#F5A623,stroke:#333,stroke-width:2px
  style MemMgr fill:#7ED321,stroke:#333,stroke-width:2px

```



## 4.2 Component Specifications

### 4.2.1 Orchestrator Component

**Responsibility:** Central coordinator for all request processing

**Interfaces:**

- **Input:** User request (text, document, image) via CLI/API
- **Output:** Final validated output + audit trail

**Key Operations:**

1. `process_request(user_input) → output`
  - Calls Router to classify request
  - Invokes appropriate pipelines (OCR, vision, embeddings if needed)
  - Loads appropriate Worker model
  - Executes generation (with or without validation based on stakes)
  - Commits results to memory ledger
  - Returns output to user
1. `execute_validation_loop(worker_output, context) → validated_output`
  - Implements Generate → Validate → Commit cycle
  - Handles retry logic (max 3 attempts per block)
  - Logs all validation decisions

**Technology:** Python 3.10+

**Key Dependencies:** RouterService, MemoryManager, ModelLoader, ValidatorModel

**Configuration:** config/orchestrator.yaml

---

### 4.2.2 Router Service Component

**Responsibility:** Intent classification and routing decision-making

**Interfaces:**

- **Input:** User request (text), current context
- **Output:** JSON routing decision

```
json
{
  "domain": "coding_architecture | coding_implementation | reasoning | creative | documenta-
tion",
  "stakes": "low | medium | high",
  "recommended_model": "qwen_coder | nemotron | gpt_oss | mythomax",
  "validation_policy": "none | end_stage | block_by_block",
  "tools_required": ["ocr", "vision", "embeddings"],
  "confidence": 0.92,
  "reasoning": "High complexity coding task with architectural focus; keywords: refactor,
multi-file, design patterns"
}
```

**Key Operations:**

1. `classify_request(user_input, history) → routing_decision`
  - Invokes Router Model (Granite-Micro 3B) for initial classification
  - Queries Prolog knowledge base for routing rules
  - Applies confidence thresholding

- Falls back to embedding similarity for ambiguous cases
- Logs decision with reasoning

1. `predict_next_model(current_model, task_history) → model_to_preload`
  - Predictive logic for warm pool management
  - Based on: current domain, user patterns, task context

**Technology:** Python (orchestration) + SWI-Prolog (rules)

**Key Dependencies:** `RouterModel` (llama.cpp), `Prolog KB`, `EmbeddingService` (fallback)

**Configuration:** `config/routing_rules.pl`, `config/router.yaml`

---

### 4.2.3 Memory Manager Component

**Responsibility:** All interactions with the Markdown memory ledger

**Interfaces:**

- **Input:** Read/write requests for memory files
- **Output:** Memory content, write confirmations

**Key Operations:**

1. `read_project_state() → dict`
  - Parses `project_state.md`
  - Returns: objectives, proven facts, constraints
1. `append_to_scratchpad(entry) → success`
  - Atomic append to `scratchpad.md`
  - Includes: timestamp, actor (`Router/Worker/Validator`), content
2. `commit_to_project_state(fact) → success`
  - Moves validated fact from scratchpad to `project_state`
  - Immutable once committed
3. `update_knowledge_graph(learning) → success`
  - Adds learned pattern to `knowledge_graph.md`
  - Examples: "Nemotron hallucinates on Rust code", "Qwen requires explicit type hints"
4. `get_relevant_context(query, top_k=5) → list[str]`
  - Semantic search over memory using embeddings
  - Returns top-k relevant snippets for Worker context

**Technology:** Python

**Key Dependencies:** `Filesystem`, `EmbeddingService` (for retrieval)

**Configuration:** `config/memory.yaml` (file paths, backup settings)

**Concurrency:** File locking (`fcntl`) to prevent race conditions

---

### 4.2.4 Model Loader (Warm Pool Manager)

**Responsibility:** GPU model lifecycle and warm pool optimization

**Interfaces:**

- **Input:** Model load/unload requests
- **Output:** Confirmation, VRAM utilization metrics

**Key Operations:**

1. `load_model_to_gpu(model_name, quantization) → success`
  - Checks VRAM availability
  - If VRAM full: unload current model
  - Load from warm pool (RAM) or cold start (NVMe)
  - Register model with inference server
  - Update telemetry
1. `preload_to_warm_pool(model_name) → success`
  - Load model from NVMe → RAM
  - Keep in RAM (not VRAM) for fast future access
  - Apply LRU eviction if RAM pressure
2. `get_current_gpu_model() → model_name`
  - Returns which model is currently in VRAM
3. `predict_and_preload_next() → success`
  - Predictive logic: based on Router hints, preload likely-next model

**Technology:** Python**Key Dependencies:** llama.cpp API, GPU monitoring (pynvml)**Configuration:** `config/model_loader.yaml` (warm pool size, eviction policy)**Critical Path:** Model swap time <5 seconds (target <3s from RAM)

## 4.2.5 Router Model Service

**Responsibility:** Run Granite-Micro 3B for intent classification**Deployment:** CPU-resident (always loaded)**Technology:** llama.cpp server mode (CPU inference)**Interface:** HTTP REST (OpenAI-compatible API)**Endpoint:** `http://localhost:8001/v1/completions`**System Prompt:**

```
You are a routing classifier for a multi-model AI system.
Analyze the user request and output ONLY a JSON object with:
{
  "domain": "coding_architecture|coding_implementation|reasoning|creative|documenta-
tion",
  "complexity": "low|medium|high",
  "keywords": ["list", "of", "key", "terms"],
  "confidence": 0.0-1.0
}
Output NOTHING else. No explanations.
```

**Performance Requirements:**

- Inference speed:  $\geq 10$  tokens/second
- Latency:  $\leq 1$  second per classification
- RAM footprint:  $\leq 6$ GB

### 4.2.6 Validator Model Service

**Responsibility:** Run Granite-H-Small for validation

**Deployment:** CPU-resident (always loaded)

**Technology:** llama.cpp server mode (CPU inference)

**Interface:** HTTP REST (OpenAI-compatible API)

**Endpoint:** `http://localhost:8002/v1/completions`

**System Prompt** (varies by validation type):

```
You are a strict validator for AI-generated {content_type}.
You will receive:
1. Current project state and constraints
2. A block of {content_type} to validate
3. Validation criteria

Output format:
[PASS] - if all checks pass (optional brief summary)
[FAIL: specific reason] - if any check fails (one-sentence correction directive)

Checks:
- Logical consistency with project state
- No hallucinations (fabricated facts/APIs)
- {content_specific_checks}
- Syntax correctness (if code)
- Safety and policy compliance
```

**Performance Requirements:**

- Inference speed:  $\geq 3$  tokens/second (acceptable for validation)
- Latency:  $\leq 5$  seconds per block validation
- RAM footprint:  $\leq 20$ GB

### 4.2.7 Worker Model Services (GPU)

**Responsibility:** Run specialist Worker models for generation

**Deployment:** GPU-resident (one at a time)

**Technology:** llama.cpp server mode (GPU inference, CUDA)

**Interface:** HTTP REST (OpenAI-compatible API)

**Endpoint:** `http://localhost:8000/v1/completions`

**Worker Specifications:**

Worker	Model	Role	VRAM	Speed Target	Context
<b>Worker 1</b>	Qwen Coder 32B (Q4_K_M)	Coding (Architecture)	18GB	≥20 tok/s	4K
<b>Worker 2</b>	Nemotron 30B (Q4_K_M)	Coding (Implementation)	16GB	≥25 tok/s	4K
<b>Worker 3</b>	GPT-OSS 20B (Q4_K_M)	Reasoning, Planning	12GB	≥30 tok/s	4K
<b>Worker 4</b>	MythoMax 13B (Q5_K_M)	Creative Writing	9GB	≥30 tok/s	4K

**System Prompts:** See Document 1.4 (Model Serving & Orchestration Design) for detailed prompts per Worker.

#### 4.2.8 Tool Services (CPU)

**Responsibility:** Execute multimodal tools (OCR, Vision, Embeddings)

**Sub-Components:**

##### 1. OCR Service

- **Technology:** Tesseract 5.0+ or PaddleOCR
- **Interface:** Python function: `extract_text(image_path) → {text, bounding_boxes, confidence}`
- **Performance:** ≤5 seconds per page

##### 2. Vision Encoder Service

- **Technology:** CLIP or BLIP (Hugging Face Transformers)
- **Interface:** Python function: `encode_image(image_path) → {caption, objects, features}`
- **Performance:** ≤3 seconds per image

##### 3. Embedding Service

- **Technology:** Sentence-Transformers (e.g., `all-MiniLM-L6-v2`)
- **Interface:** Python function: `embed_text(text) → vector[384]`
- **Performance:** ≤1 second for embedding + retrieval

**Deployment:** CPU (can run concurrently with Router/Validator)

**Configuration:** `config/tools.yaml`

## 4.3 Component Interaction Sequence

### Sequence Diagram: High-Stakes Validated Code Generation

```
sequenceDiagram
    actor User
    participant CLI
    participant Orchestrator
    participant Router
    participant MemMgr as Memory Manager
    participant Loader as Model Loader
    participant Worker as Worker (GPU)
    participant Validator as Validator (CPU)

    User->>CLI: Submit coding task
    CLI->>Orchestrator: process_request(task)

    Orchestrator->>Router: classify_request(task)
    Router->>Router: Query Prolog rules
    Router-->>Orchestrator: {domain: coding_arch, stakes: high, model: qwen_coder}

    Orchestrator->>MemMgr: read_project_state()
    MemMgr-->>Orchestrator: current_state

    Orchestrator->>Loader: load_model_to_gpu("qwen_coder")
    Loader->>Loader: Check warm pool
    Loader->>Worker: Load Qwen Coder 32B
    Loader-->>Orchestrator: Model ready

    loop Block-by-block validation
        Orchestrator->>Worker: Generate next block (5-10 lines)
        Worker-->>Orchestrator: Generated block

        Orchestrator->>MemMgr: append_to_scratchpad(block)

        Orchestrator->>Validator: validate_block(block, project_state)
        Validator->>Validator: Check logic, syntax, hallucinations


        alt Block passes
            Validator-->>Orchestrator: [PASS]
            Orchestrator->>MemMgr: commit_to_project_state(block)
        else Block fails
            Validator-->>Orchestrator: [FAIL: reason]
            Orchestrator->>MemMgr: append_correction(reason)
            Note over Orchestrator,Worker: Retry (max 3 attempts)
        end
    end

    Orchestrator->>MemMgr: finalize_output()
    Orchestrator->>CLI: validated_output + audit_trail
    CLI->>User: Display result
```

## **5. Data Flow Architecture**

---

### **5.1 High-Level Data Flow**





- ❑ - Final validated **output to user** ❑
- ❑ - Complete audit trail logged ❑
- ❑ - **Update** knowledge graph (learnings) ❑

## 5.2 Data Structures

### 5.2.1 Request Object

```
@dataclass
class Request:
    """User request with metadata"""
    id: str # UUID
    timestamp: datetime # UTC
    user_id: str # User identifier (future multi-user)
    content: str # Text input
    attachments: List[Attachment] # Documents, images
    metadata: Dict[str, Any] # Additional context

@dataclass
class Attachment:
    """Attached file (document, image)"""
    filename: str
    filepath: str
    mime_type: str
    size_bytes: int
```

### 5.2.2 Routing Decision Object

```
@dataclass
class RoutingDecision:
    """Router output"""
    domain: DomainType # Enum: CODING_ARCH, CODING_IMPL, REASONING, CREATIVE, DOC
    stakes: StakesLevel # Enum: LOW, MEDIUM, HIGH
    recommended_model: ModelType # Enum: QWEN, NEMOTRON, GPT_OSS, MYTHOMAX
    validation_policy: ValidationPolicy # Enum: NONE, END_STAGE, BLOCK_BY_BLOCK
    tools_required: List[ToolType] # Enum: OCR, VISION, EMBEDDINGS
    confidence: float # 0.0-1.0
    reasoning: str # Human-readable explanation
    timestamp: datetime
```

### 5.2.3 Validation Result Object


```
@dataclass
class ValidationResult:
    """Validator output"""
    verdict: Verdict # Enum: PASS, FAIL
    reasoning: str # Explanation
    corrections: Optional[str] # If FAIL, what to fix
    confidence: float # Validator confidence
    checks_performed: List[str] # E.g., ["logic", "syntax", "grounding"]
    timestamp: datetime
```

## 5.2.4 Memory Entry Object

```
@dataclass
class MemoryEntry:
    """Entry in Markdown memory ledger"""
    timestamp: datetime
    actor: ActorType          # Enum: ROUTER, WORKER, VALIDATOR, USER
    entry_type: EntryType     # Enum: FACT, REASONING, CORRECTION, OUTPUT
    content: str              # Markdown-formatted content
    metadata: Dict[str, Any]  # Additional context (model version, etc.)
```

# 6. Deployment Architecture

## 6.1 Physical Deployment



## 6.2 Software Deployment



## 6.3 Process Architecture

**Runtime Processes:**

Process	Type	CPU/GPU	Memory	Port	Auto-Re-start
sovereign-orchestrator	Python daemon	CPU	2GB	N/A	Yes
llama-server-router	llama.cpp	CPU	6GB	8001	Yes
llama-server-validator	llama.cpp	CPU	20GB	8002	Yes
llama-server-worker	llama.cpp	GPU+CPU	16-18GB	8000	Yes
prometheus-exporter	Python	CPU	512MB	9090	Yes

**Process Management:** systemd (Linux) or supervisord

**Example systemd unit** ( `/etc/systemd/system/sovereign-orchestrator.service` ):

```
[Unit]
Description=Sovereign AI Orchestrator
After=network.target

[Service]
Type=simple
User=sovereign
WorkingDirectory=/opt/sovereign-ai
ExecStart=/opt/sovereign-ai/venv/bin/python -m src.orchestrator.main
Restart=always
RestartSec=10
Environment="CUDA_VISIBLE_DEVICES=0"
Environment="OMP_NUM_THREADS=6"

[Install]
WantedBy=multi-user.target
```

## 7. Technology Stack

### 7.1 Core Technologies

Layer	Technology	Version	Purpose	License
<b>Programming</b>	Python	3.10+	Orchestration, ML tooling	PSF
<b>Logic Programming</b>	SWI-Prolog	8.4+	Routing rules	BSD-2
<b>Inference Engine</b>	llama.cpp	Latest	Model serving (GPU+CPU)	MIT
<b>Web Framework</b>	FastAPI	0.100+	REST API	MIT
<b>CLI Framework</b>	Click	8.0+	Command-line interface	BSD-3
<b>Vector Store</b>	FAISS	1.7+	Embedding search	MIT
<b>Monitoring</b>	Prometheus	2.40+	Metrics collection	Apache 2.0
<b>Dashboards</b>	Grafana	9.0+	Visualization	AGPLv3
<b>Version Control</b>	Git	2.30+	Memory ledger versioning	GPL-2.0

### 7.2 Python Dependencies

**Core Libraries** ( `requirements.txt` ):

```

# Orchestration & Web
fastapi>=0.100.0
uvicorn>=0.23.0
click>=8.1.0
pydantic>=2.0.0
python-multipart>=0.0.6

# LLM Integration
llama-cpp-python>=0.2.0 # With CUDA support
openai>=1.0.0 # For OpenAI-compatible API client

# Prolog Integration
pyswip>=0.2.10 # SWI-Prolog bindings

# ML & Embeddings
sentence-transformers>=2.2.0
transformers>=4.30.0
torch>=2.0.0
faiss-cpu>=1.7.4 # or faiss-gpu if available

# OCR & Vision
pytesseract>=0.3.10
Pillow>=10.0.0
opencv-python>=4.8.0

# Monitoring & Logging
prometheus-client>=0.17.0
structlog>=23.1.0

# Utilities
pyyaml>=6.0
python-dotenv>=1.0.0
psutil>=5.9.0
pynvml>=11.5.0 # GPU monitoring
filelock>=3.12.0 # File locking for memory ledger

```

## 7.3 System Dependencies

**Ubuntu Packages** (apt):

```
# NVIDIA Drivers & CUDA
nvidia-driver-535
cuda-toolkit-12-1
libcudnn8

# Build Tools
build-essential
cmake
git

# OCR
tesseract-ocr
tesseract-ocr-eng # English language data

# Prolog
swi-prolog

# System Utilities
htop
nvtop
tmux
```

## 7.4 Model Formats & Quantization

**Model Format:** GGUF (GPT-Generated Unified Format)

**Quantization Library:** llama.cpp built-in quantization

**Quantization Strategies:**

Model Size	Target VRAM	Quantization	Perplexity Impact
32B (Qwen)	18GB	Q4_K_M	~5% increase
30B (Nemotron)	16GB	Q4_K_M	~5% increase
20B (GPT-OSS)	12GB	Q4_K_M	~4% (MoE advantage)
13B (MythoMax)	9GB	Q5_K_M	~2% (higher quality for creative)
32B (Granite-H)	20GB (CPU)	Q4_K_M	~5% increase
3B (Granite-Micro)	6GB (CPU)	Q8_0 or FP16	Minimal

**Quantization Command** (example):

```
./llama.cpp/quantize \
/mnt/models/raw/qwen-coder-32b-f16.gguf \
/mnt/models/workers/qwen-coder-32b-q4_k_m.gguf \
Q4_K_M
```

## 8. Interface Specifications

---

### 8.1 REST API Specification

**Base URL:** `http://localhost:5000/api/v1`

#### 8.1.1 Submit Task

**Endpoint:** `POST /infer`

**Request:**

```
{
  "task": "Generate a Python function to calculate Fibonacci numbers recursively",
  "attachments": [],
  "options": {
    "stakes_override": "high", // Optional: force validation policy
    "model_override": "qwen_coder", // Optional: force model selection
    "temperature": 0.7,
    "max_tokens": 2048
  }
}
```

**Response (200 OK):**

```
{
  "request_id": "req_1234567890",
  "status": "completed",
  "output": "def fibonacci(n):\n    if n <= 1:\n        return n\n    return\nfibonacci(n-1) + fibonacci(n-2)",
  "routing_decision": {
    "domain": "coding_implementation",
    "stakes": "medium",
    "model_used": "nemotron",
    "confidence": 0.89
  },
  "validation_summary": {
    "policy": "end_stage",
    "verdict": "PASS",
    "checks_performed": ["syntax", "logic", "hallucination"]
  },
  "audit_trail_url": "/api/v1/audit/req_1234567890",
  "timestamp": "2026-02-05T10:30:00Z",
  "latency_ms": 15234
}
```

**Error Response (400 Bad Request):**

```
{
  "error": "ValidationError",
  "message": "Task field is required",
  "timestamp": "2026-02-05T10:30:00Z"
}
```

---



### 8.1.2 Get System Status

**Endpoint:** GET /status

**Response** (200 OK):

```
{
  "system": "operational",
  "components": {
    "orchestrator": "running",
    "router": "running",
    "validator": "running",
    "worker_gpu": "running",
    "current_gpu_model": "qwen_coder_32b",
    "warm_pool": ["nemotron_30b", "gpt_oss_20b"]
  },
  "resources": {
    "vram_used_gb": 17.2,
    "vram_total_gb": 16.0,
    "ram_used_gb": 95.3,
    "ram_total_gb": 128.0,
    "disk_free_gb": 487.5
  },
  "metrics": {
    "tasks_completed_today": 42,
    "router_accuracy_7d": 0.91,
    "validator_fp_rate_7d": 0.04,
    "avg_latency_p95_7d_sec": 28.3
  },
  "timestamp": "2026-02-05T10:35:00Z"
}
```

---

### 8.1.3 Get Audit Trail

**Endpoint:** GET /audit/{request\_id}

**Response** (200 OK):

```

{
  "request_id": "req_1234567890",
  "timeline": [
    {
      "timestamp": "2026-02-05T10:30:00.123Z",
      "actor": "router",
      "action": "classify_request",
      "details": "Domain: coding_implementation, Confidence: 0.89"
    },
    {
      "timestamp": "2026-02-05T10:30:01.456Z",
      "actor": "orchestrator",
      "action": "load_model",
      "details": "Loading Nemotron 30B from warm pool"
    },
    {
      "timestamp": "2026-02-05T10:30:03.789Z",
      "actor": "worker",
      "action": "generate_output",
      "details": "Generated 45 tokens in 2.1 seconds"
    },
    {
      "timestamp": "2026-02-05T10:30:06.012Z",
      "actor": "validator",
      "action": "validate_output",
      "details": "[PASS] All checks passed: syntax ✓, logic ✓, no hallucinations ✓"
    },
    {
      "timestamp": "2026-02-05T10:30:07.234Z",
      "actor": "orchestrator",
      "action": "commit_output",
      "details": "Committed to project_state.md"
    }
  ],
  "memory_snapshots": {
    "project_state": "# Project State\n## Task: Fibonacci function\n## Status: Completed\n...",
    "scratchpad": "# Scratchpad\n## Generated Code:\n```python\ndef fibonacci(n):..."
  }
}

```

## 8.2 CLI Interface Specification

**Command Structure:** `sovereign <command> [options] [arguments]`

### 8.2.1 Main Commands

Command	Description	Example
<code>infer</code>	Submit a task	<code>sovereign infer "Write a function to sort a list"</code>
<code>status</code>	Check system health	<code>sovereign status</code>
<code>history</code>	View past tasks	<code>sovereign history --last 10</code>
<code>audit</code>	View audit trail	<code>sovereign audit req_1234567890</code>
<code>config</code>	View/edit configuration	<code>sovereign config show</code>
<code>logs</code>	View system logs	<code>sovereign logs --tail 100</code>

### 8.2.2 Interactive Mode

```
$ sovereign interactive
Sovereign AI > [Interactive prompt]
> analyze this code: <paste code>
[System processes request]
> show audit trail
[Display audit trail]
> exit
```

## 8.3 Internal Component Interfaces

### 8.3.1 Router ↔ Orchestrator

**Interface:** Function call (Python)

```
class RouterService:
    def classify_request(
        self,
        user_input: str,
        context: Optional[Dict] = None
    ) -> RoutingDecision:
        """
        Classify user request and determine routing.

        Args:
            user_input: User's task description
            context: Optional historical context

        Returns:
            RoutingDecision with model, stakes, tools, confidence
        """
        pass
```

### 8.3.2 Orchestrator ↔ Memory Manager

**Interface:** Function calls (Python)

```
class MemoryManager:
    def read_project_state(self) -> Dict[str, Any]:
        """Read current project state"""
        pass

    def append_to_scratchpad(self, entry: MemoryEntry) -> bool:
        """Atomic append to scratchpad"""
        pass

    def commit_to_project_state(self, fact: str) -> bool:
        """Move validated fact to immutable project state"""
        pass

    def get_relevant_context(self, query: str, top_k: int = 5) -> List[str]:
        """Semantic retrieval from memory"""
        pass
```

### 8.3.3 Model Loader ↔ llama.cpp Servers

**Interface:** HTTP REST (OpenAI-compatible)

**Example Request** (Generation):

```
POST http://localhost:8000/v1/completions
Content-Type: application/json

{
  "model": "gwen-coder-32b-q4_k_m",
  "prompt": "def fibonacci(n):",
  "temperature": 0.7,
  "max tokens": 512,
  "stop": ["\n\n", "```"]
}
```

**Example Response:**

```
{
  "id": "cml-1234567890",
  "object": "text_completion",
  "created": 1707134400,
  "model": "qwen-coder-32b-q4_k_m",
  "choices": [
    {
      "text": "\n    if n <= 1:\n        return n\n    return fibonacci(n-1) + fibonacci(n-2)",
      "index": 0,
      "finish_reason": "stop"
    }
  ],
  "usage": {
    "prompt_tokens": 5,
    "completion_tokens": 28,
    "total_tokens": 33
  }
}
```

## 9. Scalability & Performance

### 9.1 Performance Targets (from PRD)

Metric	Target	Measurement
Router latency	$\leq 1$ second	Time from request to routing decision
Model swap time	$\leq 3$ seconds	RAM $\rightarrow$ VRAM transfer
Worker inference	$\geq 20$ tok/s	GPU models (varies by size)
Validator inference	$\geq 3$ tok/s	CPU model (acceptable for validation)
End-to-end (simple)	$\leq 20$ seconds	Low-stakes, no validation
End-to-end (complex)	$\leq 60$ seconds	High-stakes with block validation

### 9.2 Scalability Constraints (v1.0)

#### Hard Constraints:

- **Single GPU:** One Worker model at a time in VRAM
- **Sequential Execution:** One task at a time (no concurrent tasks)
- **Single User:** No multi-user concurrency support

#### Bottleneck Analysis:

Bottleneck	Impact	Mitigation (v1.0)	Future (v2.0+)
<b>GPU model swaps</b>	Adds 3-5s per swap	Warm pool reduces swaps	Multi-GPU: parallel Workers
<b>CPU validation speed</b>	3-5s per block	Optimize prompts, acceptable latency	GPU-resident validation option
<b>Memory I/O</b>	Minimal (<100ms)	In-memory buffering	Distributed memory store
<b>Single-threaded orchestrator</b>	Sequential tasks only	Acceptable for v1.0	Async orchestration, task queue

## 9.3 Resource Utilization Targets

### VRAM (16GB total):

- Worker model: 12-18GB (depending on model)
- KV cache: 1-2GB
- Overhead: 1-2GB
- **Target:** 95% utilization when Worker loaded

### RAM (128GB total):

- Router: 6GB
- Validator: 20GB
- Warm pool: 60-80GB (2-3 models)
- OS + overhead: 10-15GB
- Orchestrator + tools: 5-8GB
- **Target:** 90% utilization (avoid swap to disk)

### CPU:

- Router: 1-2 cores
- Validator: 2-3 cores
- Tools (OCR/Vision/Embeddings): 2-3 cores (concurrent)
- Orchestrator + system: 1-2 cores
- **Target:** 70-80% utilization under load

### NVMe:

- Model vault: 500GB (multiple quantizations per model)
- Memory ledger: <1GB (grows over time)
- Vector store: <5GB
- Logs: <10GB
- **Target:** >400GB free

---

## 10. Security Architecture

### 10.1 Security Principles

1. **Data Sovereignty:** All computation local; zero external dependencies
2. **Least Privilege:** Components have minimal necessary permissions

3. **Audit Everything:** All decisions, actions, errors logged immutably
4. **Fail Secure:** Failures default to safe state (reject, not accept)
5. **Defense in Depth:** Multiple validation layers

## 10.2 Threat Model

### Assets to Protect:

- User data (prompts, documents, images)
- AI outputs (potentially sensitive)
- Memory ledger (audit trail)
- Model files (integrity)

### Threats (v1.0 single-user):

Threat	Likelihood	Impact	Mitigation
<b>Prompt injection</b>	High	Medium	Validator checks outputs; system prompts hardened
<b>Model tampering</b>	Low	High	Checksums on model files; verify before load
<b>Memory corruption</b>	Low	High	Atomic writes; file locking; Git versioning
<b>Resource exhaustion</b>	Medium	Medium	Resource monitoring; OOM detection; rate limiting (future)
<b>Log tampering</b>	Low	High	Append-only logs; checksums; immutable once written

### Out of Scope for v1.0 (single-user on localhost):

- Network-based attacks (no external network exposure)
- Multi-user privilege escalation (single user)
- Side-channel attacks (not a concern for local deployment)

## 10.3 Security Controls

### 10.3.1 Input Validation

- **User prompts:** Sanitize, length limits (max 10K characters)
- **File uploads:** MIME type checking, size limits (max 50MB per file)
- **API requests:** JSON schema validation

### 10.3.2 Output Validation

- **Validator role:** Check for harmful content, PII leakage, policy violations
- **Grounding checks:** Ensure multimodal outputs cite sources correctly

- **Confidence thresholds:** Flag low-confidence outputs for review

### 10.3.3 Audit & Logging

- **Immutable logs:** Append-only, no deletion
- **Tamper detection:** Checksums or HMAC on log entries
- **Comprehensive coverage:** Log all routing, generation, validation decisions

### 10.3.4 Resource Protection

- **VRAM monitoring:** Prevent OOM crashes
- **File locking:** Prevent concurrent writes to memory ledger
- **Backup strategy:** Daily backups of memory ledger, weekly model backups

## 10.4 Security Configuration

### File Permissions:

```

/opt/sovereign-ai/
├── src/                (755, root:sovereign)
├── config/             (750, root:sovereign)
│   ├── *.yaml         (640, sensitive configs)
│   └── *.pl            (640, routing rules)
├── data/
│   ├── memory/         (770, sovereign:sovereign, group-writable for Git)
│   └── vector_store/   (770, sovereign:sovereign)
└── logs/               (750, sovereign:sovereign, append-only)

/mnt/models/           (755, root:sovereign, read-only for models)

```

### Network Exposure (v1.0):

- **All services on localhost:** No external network access
  - **Firewall:** Block all incoming except SSH (if remote management)
-



# 11. Monitoring & Observability

## 11.1 Metrics to Collect

### 11.1.1 System Metrics (via Prometheus)

Metric	Type	Labels	Purpose
sover-eign_request_total	Counter	domain , stakes , status	Track task volume
sover-eign_request_duration_seconds	Histogram	domain , stakes	Track latency distribution
sover-eign_router_accuracy	Gauge	-	Track routing performance
sover-eign_validator_verdicts_total	Counter	verdict (pass/fail)	Track validation outcomes
sover-eign_model_swap_duration_seconds	Histogram	model	Track swap performance
sover-eign_vram_used_bytes	Gauge	-	Monitor VRAM
sover-eign_ram_used_bytes	Gauge	pool (warm/system)	Monitor RAM
sover-eign_gpu_temperature_celsius	Gauge	-	Thermal monitoring
sover-eign_model_inference_tokens_per_second	Gauge	model	Track generation speed

Example Prometheus Query (p95 latency):

```
histogram_quantile(0.95,
  rate(sovereign_request_duration_seconds_bucket[5m])
)
```

11.1.2 Business Metrics

Metric	Calculation	Purpose
Router Accuracy	(Correct classifications / Total) over rolling 7-day window	Track routing quality
Validator FP Rate	(False Passes / Total Passes)	Track validation strictness
Validator FN Rate	(False Fails / Total Fails)	Track validation leniency
Task Success Rate	(Completed / Total Submitted)	Track overall reliability
Avg. Latency by Stakes	Mean latency grouped by low/medium/high stakes	Track performance vs. rigor

11.2 Logging Strategy

Structured Logging (JSON format):

```
{
  "timestamp": "2026-02-05T10:30:00.123Z",
  "level": "INFO",
  "component": "orchestrator",
  "request_id": "req_1234567890",
  "action": "load_model",
  "details": {
    "model": "qwen_coder_32b",
    "source": "warm_pool",
    "duration_ms": 2341
  }
}
```

Log Levels:

- **DEBUG**: Detailed trace (disabled in production)
- **INFO**: Normal operations (routing decisions, model loads, validations)
- **WARNING**: Non-critical issues (low router confidence, validation retries)
- **ERROR**: Failures requiring attention (model load failures, OOM)
- **CRITICAL**: System-level failures (orchestrator crash, data corruption)

Log Rotation:

- **Daily rotation**: New log file each day
- **Retention**: 30 days
- **Compression**: gzip logs older than 7 days

11.3 Alerting Rules

Critical Alerts (PagerDuty):

- System crash (orchestrator down)
- VRAM OOM imminent (>95% utilization)
- Model load failure (after 3 retries)
- Memory ledger corruption detected

**Warning Alerts** (Email/Slack):

- High latency (p95 >120 seconds for 10 minutes)
  - Router accuracy drop (<80% over 24 hours)
  - Validator FN rate spike (>10% over 24 hours)
  - Disk space low (<100GB free)
- 

## 11.4 Dashboards (Grafana)

**Dashboard 1: System Overview**

- System status (components up/down)
- Task volume (requests/hour)
- Latency (p50, p95, p99)
- Resource utilization (VRAM, RAM, CPU, disk)

**Dashboard 2: Model Performance**

- Inference speed per model (tokens/second)
- Model swap times
- Current GPU model + warm pool contents
- Model load/unload frequency

**Dashboard 3: Routing & Validation**

- Router accuracy (7-day rolling)
- Routing confidence distribution
- Validator pass/fail rates
- Validation latency

**Dashboard 4: Tasks & Errors**

- Task success/failure rates
  - Error breakdown by type
  - Retry frequency
  - Top error messages
-

## **12. Development & Build Architecture**

---

### **12.1 Repository Structure**

```

sovereign-ai/
├── .git/                                # Git version control
├── .github/                             # GitHub Actions CI (optional)
│   └── workflows/
│       └── tests.yml
├── src/                                # Source code
│   ├── __init__.py
│   ├── orchestrator/                  # Orchestration layer
│   │   ├── __init__.py
│   │   ├── main.py                    # Entry point
│   │   ├── request_handler.py
│   │   └── validation_loop.py
│   ├── router/                        # Router service
│   │   ├── __init__.py
│   │   ├── classifier.py              # Python wrapper
│   │   ├── prolog_interface.py        # Prolog integration
│   │   └── rules.pl                   # Prolog routing rules
│   ├── memory/                        # Memory manager
│   │   ├── __init__.py
│   │   ├── manager.py
│   │   ├── parser.py                  # Markdown parser
│   │   └── retrieval.py               # Semantic retrieval
│   ├── models/                        # Model serving
│   │   ├── __init__.py
│   │   ├── loader.py                 # Warm pool manager
│   │   ├── router_model.py
│   │   ├── validator_model.py
│   │   └── worker_models.py
│   ├── tools/                         # Multimodal tools
│   │   ├── __init__.py
│   │   ├── ocr.py
│   │   ├── vision.py
│   │   └── embeddings.py
│   ├── cli/                           # CLI interface
│   │   ├── __init__.py
│   │   └── commands.py
│   ├── api/                           # REST API
│   │   ├── __init__.py
│   │   ├── server.py                 # FastAPI app
│   │   └── routes.py
│   ├── utils/                         # Utilities
│   │   ├── __init__.py
│   │   ├── telemetry.py              # Prometheus metrics
│   │   ├── logging_config.py
│   │   └── config_loader.py
│   └── config/                        # Configuration files
│       ├── system.yaml                # System-wide config
│       ├── models.yaml                # Model paths, quantizations
│       ├── routing_rules.pl           # Prolog routing logic
│       ├── validation_policies.yaml   # Stakes-based policies
│       └── tools.yaml                 # Tool configurations
├── data/                              # Runtime data
│   ├── memory/                        # Markdown memory ledger
│   │   ├── project_state.md
│   │   ├── scratchpad.md
│   │   └── knowledge_graph.md
│   ├── vector_store/                  # FAISS index
│   │   └── embeddings.index
├── tests/                             # Test suite
│   └── unit/
│       ├── test_router.py
│       └── test_memory.py

```

```

├── test_validation.py
├── integration/
│   ├── test_orchestrator.py
│   ├── test_end_to_end.py
│   └── fixtures/
│       ├── sample_requests.json
│       └── test_models/
├── scripts/
│   ├── setup_environment.sh           # Utility scripts
│   ├── download_models.py            # Initial setup
│   ├── quantize_models.sh            # Model download automation
│   └── start_services.sh             # Quantization pipeline
├── docs/                             # Start all services
│   ├── architecture/                # Documentation
│   ├── api/                         # This document, others
│   └── operations/                  # API docs
├── logs/                             # Runbooks
│   └── .gitkeep                     # Application logs
├── requirements.txt                  # Python dependencies
├── requirements-dev.txt              # Dev dependencies (pytest, etc.)
├── setup.py                         # Package setup
├── pyproject.toml                   # Modern Python config
├── .env.example                     # Example environment variables
├── .gitignore
├── README.md
└── LICENSE

```

## 12.2 Build & Deployment Process

### 12.2.1 Initial Setup

```

# 1. Clone repository
git clone https://github.com/org/sovereign-ai.git
cd sovereign-ai

# 2. Run setup script
./scripts/setup_environment.sh
# This installs: system packages, CUDA, llama.cpp, Python venv, Prolog

# 3. Download and quantize models
python scripts/download_models.py --all
./scripts/quantize_models.sh

# 4. Configure system
cp .env.example .env
# Edit .env with paths, settings

# 5. Initialize memory ledger
mkdir -p data/memory
git init data/memory # Track memory in separate Git repo

# 6. Start services
./scripts/start_services.sh
# Starts: llama.cpp servers, orchestrator, Prometheus exporter

# 7. Verify
sovereign status

```

### 12.2.2 Development Workflow

```
# Create feature branch
git checkout -b feature/improve-routing

# Make changes to src/router/rules.pl

# Run tests
pytest tests/ -v

# Run linter
pylint src/
black src/ --check

# Commit changes
git add src/router/rules.pl
git commit -m "Improve routing logic for ambiguous coding queries"

# Push and create PR
git push origin feature/improve-routing
```

### 12.2.3 CI/CD Pipeline (GitHub Actions example)

```
# .github/workflows/tests.yml
name: Tests

on: [push, pull_request]

jobs:
  test:
    runs-on: ubuntu-latest
    steps:
      - uses: actions/checkout@v3
      - uses: actions/setup-python@v4
        with:
          python-version: '3.10'
      - name: Install dependencies
        run: |
          pip install -r requirements.txt
          pip install -r requirements-dev.txt
      - name: Run linter
        run: |
          pylint src/
          black src/ --check
      - name: Run unit tests
        run: pytest tests/unit/ -v
    # Integration tests require GPU, run on self-hosted runner
```

# 13. Appendices

## 13.1 Acronyms & Abbreviations

Acronym	Meaning
SAD	System Architecture Document
PRD	Product Requirements Document
CLI	Command-Line Interface
REST	Representational State Transfer
API	Application Programming Interface
VRAM	Video Random Access Memory (GPU memory)
RAM	Random Access Memory (system memory)
NVMe	Non-Volatile Memory Express (fast SSD)
GGUF	GPT-Generated Unified Format (model format)
MoE	Mixture of Experts (model architecture)
OCR	Optical Character Recognition
LLM	Large Language Model
FP	False Positive (validation error)
FN	False Negative (validation error)
RTO	Recovery Time Objective
RPO	Recovery Point Objective
OOM	Out Of Memory
SLO	Service Level Objective



## 13.2 Glossary of Terms

Term	Definition
<b>Bicameral Architecture</b>	Design separating creative generation (GPU) from critical validation (CPU)
<b>Warm Pool</b>	Pre-loaded models in RAM for fast GPU loading
<b>Stakes</b>	Risk level of a task (low/medium/high) determining validation rigor
<b>Grounding</b>	Ensuring outputs are attributable to source material (e.g., OCR text)
<b>Provenance</b>	Tracking the origin and lineage of data
<b>Memory Ledger</b>	Markdown files serving as persistent, auditable state
<b>Quantization</b>	Reducing numerical precision (FP32 → INT4) to reduce model size
<b>Router</b>	Component classifying requests and selecting appropriate model
<b>Validator</b>	Component checking outputs for correctness, safety, grounding
<b>Worker</b>	Specialist AI model performing generation (coding, reasoning, creative)
<b>Orchestrator</b>	Central coordinator managing request flow

## 13.3 C4 Model Diagrams Summary

**Level 1 - System Context:** User ↔ Sovereign AI ↔ External Systems (ModelRepo, Git, Monitoring)

**Level 2 - Container:** Presentation (CLI/API) → Orchestration (Python/Prolog) → Inference (llama.cpp) → Storage (Models, Memory, VectorDB)

**Level 3 - Component:** See Section 4 (Component Architecture) for detailed component diagram

**Level 4 - Code:** Implementation-specific; deferred to code documentation

### 13.4 Design Decisions Log

ID	Date	Decision	Rationale	Alternatives	Status
<b>DD-001</b>	2026-02-05	Use Hybrid Python/Prolog	Python for ML ecosystem, Prolog for declarative rules	Pure Python (less expressive), Pure Prolog (poor ML support)	<b>Approved</b>
<b>DD-002</b>	2026-02-05	CPU-resident Validator	Eliminates GPU thrashing	GPU validator (causes thrashing), No validation (no governance)	<b>Approved</b>
<b>DD-003</b>	2026-02-05	Markdown Memory Ledger	Human-readable, Git-trackable, transparent	SQL (opaque), JSON (less readable), Neural memory (black box)	<b>Approved</b>
<b>DD-004</b>	2026-02-05	Warm Pool in RAM	3-5x faster model swaps	Always from disk (slow), All in VRAM (impossible)	<b>Approved</b>
<b>DD-005</b>	2026-02-05	Sequential Execution (v1.0)	Simpler, avoids concurrency complexity	Concurrent execution (more complex, v2.0)	<b>Approved</b>
<b>DD-006</b>	2026-02-05	FAISS for Vector Store	Lightweight, CPU-efficient	ChromaDB (heavier), Pinecone (cloud, violates sovereignty)	<b>Approved</b>
<b>DD-007</b>	2026-02-05	Tesseract for OCR	Free, good accuracy	PaddleOCR (better but heavier), Commercial APIs (violates sovereignty)	<b>Under Review</b>

---

### 13.5 References

- 1. **Product Requirements Document (PRD)** v1.0, 2026-02-05
- 2. **Technical Analysis Report** (Deep Agent Report), 2026-01-03
- 3. **Comprehensive Architecture Report** (Hybrid Logic Router), 2026-01-16
- 4. **Project Roadmap**, 2026-02-05
- 5. **Document Roadmap**, 2026-02-05
- 6. **llama.cpp Documentation**: <https://github.com/ggerganov/llama.cpp>
- 7. **SWI-Prolog Documentation**: <https://www.swi-prolog.org/>
- 8. **GGUF Specification**: <https://github.com/ggerganov/ggml/blob/master/docs/gguf.md>
- 9. **C4 Model**: <https://c4model.com/>

---

### 13.6 Document Revision History

Version	Date	Author	Changes
0.1	2026-02-05	Architecture Team	Initial draft
1.0	2026-02-05	Architecture Team	Complete first version for review

---

**Document Status:** Draft for Review  
**Next Steps:** Review by Technical Lead, Engineering Manager, ML Lead, DevOps Lead, Security Architect  
**Target Approval Date:** 2026-02-12  
**Owner:** Solutions Architect / Technical Lead

---

**End of System Architecture Document**