

Q Ping process from 50.0.0.10 to

50.0.0.20 :-

→ This is use to check Host to destination IP alive or not alive.

→ Open Command Prompt. You are host, IP- 50.0.0.10. And then check destination IP- 50.0.0.20 ^{check} alive and communicate purpose.

→ cmd enters Ping and destination IP

C:\Users\ Ping 50.0.0.20

→ First host machine Request to send 4 packet.

→ destination machine reach this Packet, Reply to 4 packet, It will be one time. Receive any losses. Still destination alive and way to communicate.

① Use of Ping Command in network

- ↳ Ping mean Packet Internet Groper
- ↳ Ping is one of trouble shooting command.
- ↳ Ping command use to check connectivity two (or) more computers in network.
- ↳ This is use to Host to destination computer check connectivity.
 - ↳ First enter ping and destination IP (or) system name.
 - ↳ To send the Requesting Packet, then destination PC Reply 4 Packet.

```
ping - 192.172.91.30 (or) PC002
```

② netbios ⇒ Network ^{Basic} input-output System.

↳ netbios used to allow computer identify and communicate with each other using computer name.

computer name → find computer ⇒ communicate

③ SMB ⇒ server message Block

SMB network Protocol used to share file, folders, other resources between computers over network.