Practical Parallel Computing (実践的並列コンピューティング) 2021 No. 14

Part3: MPI (4)
May 31, 2021



Toshio Endo
School of Computing & GSIC
endo@is.titech.ac.jp



Improving MPI diffusion by Overlapping of Communication

related to [M1], but optional

Overview of MPI “diffusion”

(See MPI (2) Slides)




```
for (t = 0; t < nt; t++) {
  if (rank > 0) Send B to rank-1
  if (rank < size-1) Send D to rank+1
  if (rank > 0) Recv A from rank-1
  if (rank < size-1) Recv E from rank+1
  Computes points in rows B-D
  Switch old and new arrays
}
```

(1) Communication in “old” array

(2) Computation “old” array ⇒ “new” array

Actually this should be fixed to avoid deadlock

Considering Performance of MPI Programs

(Simplified) Execution time of an MPI program =

Computation time ← including memory access

\+ Communication time ← including congestion

\+ Others ← load imbalance, I/O…

Behavior of stencil computations on MPI



Computation Time & Communication Time (1)



How are they determined? (very simplified discussion)

1. Aspect of software

Computation time

- Longer if computation costs are larger
  - O(mnk/p) in matmul,
  - O(NX NY NT/p) in diffusion

per process

Communication time

- Longer if communication costs are larger
  - O(mk) in memory reduced matmul
  - O(NX NT) in diffusion

per process

Computation Time & Communication Time (2)

2. Aspect of hardware

Computation time

- Shorter if processor speed is faster
  - 850GFlops per node on TSUBAME3 (CPU only(

Communication time

- Shorter if network speed is faster
  - 400Gbps per node on TSUBAME3



Speed of actual software is slower than the “peak” performance

Parameters for Network Speed



What parameters describes network speed?

- Bandwidth : Data amounts that network can transport per unit time → Larger is better
  - bps: X bits per second
  - B/s: X Bytes per second
  - On TSUBAME3, 400Gbps = 50GB/s per node
- Network latency : Time to transport minimum data (1bit, for example) → Smaller is better
  - On TSUBAME3, a few us

※ Additionally, communication time may suffer from effects of network topology: how nodes/switches are connected to each other

Bandwidth and Latency

Is “latency” reciprocal of “bandwidth”?
→ No, because data are transported in “pipe-lined” style



$$T = M / B + L$$

T: Communication time

M: Data size

B: Bandwidth

L: Network latency

※ Be aware of difference between “Byte” and “bit”: 1Byte=8bit

※ In some contexts, T, not L, may be called “latency”

Idea of Overlapping

If "some computations" do not require contents of message, we may start them beforehand

Without overlap



$T=T_N+T_P$

With overlap



T_P is divided into

- T_{P1}: can be overlapped
- T_{P2}: cannot be overlapped

$T=\max(T_N,T_{P1})+T_{P2}$

Overlapping in Stencil Computation (related to [M1], but not requied)

When we consider data dependency in detail, we can find computations that do not need data from other processes



Rows C, D, E do not need data from other processes → They can be computed without waiting for finishing communication

On the other hand, rows B, F need received data

For such purposes, non-blocking communications (MPI_Isend, MPI_Irecv…) are helpful again

Implementation without Overlapping (Not Fast!)



```
for (t = 0; t < nt; t++) {
  Start Send B to rank-1, Start Send F to rank+1
   (MPI_Isend)
  Start Recv A from rank-1, Start Recv G from
   rank+1 (MPI_Irecv)
  Waits for finishing all communications
   (MPI_Wait for 4 times)
 Compute rows B--F
 Switch old and new arrays
}
```

T_N

T_P

$$T=T_N+T_P$$

Implementation with Overlapping

```
for (t = 0; t < nt; t++) {
  Start Send B to rank-1, Start Send F to rank+1
   (MPI_Isend)
  Start Recv A from rank-1, Start Recv G from
   rank-1 (MPI_Irecv)
 Compute rows C--E
  Waits for finishing all communications
   (MPI_Wait)
 Compute rows B, F
 Switch old and new arrays
}
```

computations are divided

$$T = \max(T_N, T_{P1}) + T_{P2} < T_N + T_{P1} + T_{P2} = T_N + T_P$$

Another Improvement: Reducing Communication Amounts

Multi-dimensional division may reduce communication



Each process communicate with upper/lower/right/left processes

- Comp: O(NY NX/p)
- Comm: O(NX)

per 1 process, 1 iteration

- Comp: O(NY NX/p)
- Comm: O((NY+NX)/$p^{1/2}$)

per 1 process, 1 iteration

→ Comm is reduced

Multi-dimensional division and Non-contiguous data (1)



- MD division may need communication of non-contiguous data



In Row-major format,
we need send/recv of non-contiguous data for left/right borders

But “fragmented communication” degrades performance! (since Latency > 0)
How do we do?

Multi-dimensional division and Non-contiguous data (2)



Solution (1):

- Before sending, copy non-contiguous data into another contiguous buffer
- After receiving, copy contiguous buffer to non-contiguous area

Solution (2):

- Use MPI_Datatype
  - Skipped in the class; you may use Google



Performance of Collective Communication

also in MPI (3) slides

It is Better to Use Collective Communications if Appropriate

measured on TSUBAME2

- Comparing MPI_Bcast and MPI_Send&Recv
  1 process per node is invoked (to measure network)
  In the latter, rank 0 called MPI_Send for p-1 times to other processes





- In most cases, MPI_Bcast is faster

Why are Collective Communications Fast?

- Since MPI library uses scalable communication algorithms
  - Case of broadcast:

Flat tree algorithm (slow)



Binomial tree algorithm



Scatter&Allgather algorithm



(Again) Model of Communication Time

Illustration of peer-to-peer communication of data size M



$$T = M / B + L$$

T: Communication time

M: Data size

B: Bandwidth

L: Network latency

※ Be aware of difference between "Byte" and "bit": 1Byte=8bit

※ Actually it is more complex for process's place, effects of network topology, congestion, packet size…

Cost Model of Broadcast Algorithms

- Case of “broadcast” of size M data
  - p: number of processes, B: network bandwidth, L: network latency

Flat tree algorithm



p(M/B+L)

→ Slow

Binomial tree algorithm



(log p)(M/B+L)

※difference between p-1 and p is ignored

One of Scalable Broadcast Algorithms

- Scatter&Allgather algorithm
  - Message is divided into p parts
  - Better than “binomial tree” if M is larger

R. Thakur and W. Gropp. Improving the performance of collective operations in mpich. EuroPVM/MPI conference, 2003.



Scatter

$M/B + pL +$

$M/B + (\log p)L$

All-gather

Comparison of Broadcast Algorithms



- Consider two extreme cases
  - If M is sufficiently large: *M/B+L → M/B*
  - If M is close to zero: *M/B+L → L*

	Flat Tree	Binomial Tree	Scatter& All-gather
Cost (General)	p(M/B+L)	(log p) (M/B+L)	2M/B + (p + log p)L
Cost with very large M	p M/B	(log p) M/B	2 M/B → Fastest
Cost with very small M	p L	(log p) L → Fastest	(p + log p) L

Many MPI libraries implement multiple algorithms
They switch them automatically according to message size M ☺

Using Multiple GPUs with MPI+CUDA

A way for peta-scale computing!



Parallel Programming Methods on TSUBAME



Using Multiple GPUs

- Basic idea:

  (1) Start processes on multiple nodes by MPI

  (2) Each process uses its local GPU by CUDA

NOTE: there are other methods



Sample: /gs/hs1/tga-ppcomp/21/mm-mpi-cuda/

Compiling mm-mpi-cuda Sample



```
module load cuda openmpi    [Do once after login]
cd ~/t3workspace            [In web-only route]
cp -r /gs/hs1/tga-ppcomp/21/mm-mpi-cuda  .
cd mm-mpi-cuda
make
[An executable file “mm” is created]
```

In this Makefile,

- nvcc is used as the compiler
- mpic++ is used as the linker, with CUDA libraries

Note: This may not work on other systems or future TSUBAME

Executing mm-mpi-cuda



- Interactive use is only for one node
- → To use multiple nodes, job submission is required

In standard route, Use qsub on the login node

qsub job2q.sh ➔ q_node (1GPU) x 2 are used ➔ 2GPUs in total

qsub job2f.sh ➔ f_node (4GPU) x 2 are used ➔ 8 GPUs in total

job2f.sh

```
#!/bin/sh
#$ -cwd
#$ -l f_node=2
#$ -l h_rt=0:10:00

. /etc/profile.d/modules.sh
module load cuda openmpi

mpiexec -n 8 -npernode 4 -x LD_LIBRARY_PATH ./mm 2048 2048 2048
```

8 processes, 4 processes per node

To avoid scheduler's problem

Issues in Multiple GPUs per node



- f_node or h_node has multiple GPUs (4 or 2)
  - In default, all processes use “GPU 0” on the node → slow ☹

- Each process should use distinct GPUs

➔ In mm.cu, cudaSetDevice(int dev) is called first

  - specifies the GPU to be used
  - dev: GPU number in the node (0, 1, 2…)
    - In this sample, GPU number (rank % num of devices) is used

Data Transfer

- mm sample does not use communication
- If we want to do, the basic method is

  (1) Copy data on GPU memory to CPU (cudaMemcpy)

  (2) Transfer between processes (MPI_Send/MPI_Recv)

  (3) Copy data on CPU memory to GPU (cudaMemcpy)



NOTE:
Recent MPI supports
GPU direct,
to direct communication
on GPU memory

We Have Learned

- Part 1: Shared memory parallel programming with OpenMP
- Part 2: GPU programming with OpenACC and CUDA
- Part 3: Distributed memory parallel programming with MPI

Many common strategies towards faster software:

- To understand source of bottleneck
- Reducing computation and communication
- Overlapping computation and communication
- To understand property of architecture

Assignments in MPI Part (Abstract)



Choose *one of* [M1]—[M3], and submit a report

Due date: June 10 (Thursday)

[M1] Parallelize “diffusion” sample program by MPI.

[M2] Improve mm-mpi sample in order to reduce memory consumption.

[M3] (Freestyle) Parallelize *any* program by MPI.

For more detail, please see May 20 slides



- Thank you for participating in
  practical parallel computing

Let's enjoy high performance computing!