

Part No. CQ0603BRNPOYBN4R8

| 0603 (1608) | NPO | 250 Vdc | 4.8 pF | ±0.1pF |

Surface-Mount Ceramic Multilayer Capacitors (RoHS compliant & Halogen Free)

■ Appearance





■ Dimension (mm)

| L (Length) | 1.60 ±0.10 |
|---------------|------------|
| W (width) | 0.80 ±0.10 |
| T (Thickness) | 0.80 ±0.10 |
| L2/L3 | 0.20~0.60 |
| L4 | 0.4 |

Specification

| Application | HighFrequency |
|-----------------------------|---------------------------|
| Case Size (EIA/JIS) | 0603 (1608) |
| Temperature Characteristic | NPO |
| Operation Temp. Range | -55 to +125°C |
| Capacitance | 4.8 pF |
| Capacitance Tolerance | ±0.1pF |
| Rated Voltage (VDC) | 250 |
| Endurance (% Rated voltage) | 150% |
| Tanδ (max) | 0.20% |
| Insulation Resistance (min) | 10.0 GΩ |
| Packing | Paper/PE Tape Reel 7 inch |
| Standard Packing Qty (pcs) | 0 |
| Test Method | IEC-60384 |

 $The \ data \ are \ for \ reference \ only. \ Electrical \ characteristics \ vary \ depending \ on \ environment \ or \ measurement \ condition.$

YAGEO reserves the right to make change to the data at any time without notice. Before making final selection, please check product specification.

