


Part No. CA0612KPNPO0BN101

| 0612 (1632) | NPO | 100 Vdc | 100 pF | ±10% |

Surface-Mount Ceramic Multilayer Capacitors (RoHS compliant & Halogen Free)

■ Appearance





■ Dimension (mm)

L (Length)	3.20 ±0.15	A	0.40±0.10
W (width)	1.60 ±0.15	В	0.30±0.20
T (Thickness)	0.80 ±0.10	Р	0.80±0.10

Specification

Application	Array	
Case Size (EIA/JIS)	0612 (1632)	
Temperature Characteristic	NPO	
Operation Temp. Range	-55 to +125°C	
Capacitance	100 pF	
Capacitance Tolerance	±10%	
Rated Voltage (VDC)	100	
Endurance (% Rated voltage)	200%	
Tanδ (max)	0.10%	
Insulation Resistance (min)	10.0 GΩ	
Packing	Paper/PE Tape Reel 13 inch	
Standard Packing Qty (pcs)	15,000	
Test Method	IEC-60384	

The data are for reference only. Electrical characteristics vary depending on environment or measurement condition.

YAGEO reserves the right to make change to the data at any time without notice. Before making final selection, please check product specification.








Part No. CA0612KPNPO0BN101


| 0612 (1632) | NPO | 100 Vdc | 100 pF | ±10% |

Surface-Mount Ceramic Multilayer Capacitors (RoHS compliant & Halogen Free)









The data are for reference only. Electrical characteristics vary depending on environment or measurement condition.

YAGEO reserves the right to make change to the data at any time without notice. Before making final selection, please check product specification.





Part No. CA0612KPNPO0BN101

| 0612 (1632) | NPO | 100 Vdc | 100 pF | ±10% |

Surface-Mount Ceramic Multilayer Capacitors (RoHS compliant & Halogen Free)







The data are for reference only. Electrical characteristics vary depending on environment or measurement condition.

YAGEO reserves the right to make change to the data at any time without notice. Before making final selection, please check product specification.