

Part No. CA0612KRNPO9BN121

| 0612 (1632) | NPO | 50 Vdc | 120 pF | ±10% |

Surface-Mount Ceramic Multilayer Capacitors (RoHS compliant & Halogen Free)

■ Appearance





■ Dimension (mm)

L (Length)	3.20 ±0.15	A	0.40±0.10
W (width)	1.60 ±0.15	В	0.30±0.20
T (Thickness)	0.80 ±0.10	Р	0.80±0.10

■ Specification

•	•		
Application	Array		
Case Size (EIA/JIS)	0612 (1632)		
Temperature Characteristic	NPO		
Operation Temp. Range	-55 to +125°C		
Capacitance	120 pF		
Capacitance Tolerance	±10%		
Rated Voltage (VDC)	50		
Endurance (% Rated voltage)	200%		
Tanδ (max)	0.10%		
Insulation Resistance (min)	10.0 GΩ		
Packing	Paper/PE Tape Reel 7 inch		
Standard Packing Qty (pcs)	4,000		
Test Method	IEC-60384		

The data are for reference only. Electrical characteristics vary depending on environment or measurement condition.

YAGEO reserves the right to make change to the data at any time without notice. Before making final selection, please check product specification.





Part No. CA0612KRNPO9BN121

| 0612 (1632) | NPO | 50 Vdc | 120 pF | ±10% |

Surface-Mount Ceramic Multilayer Capacitors (RoHS compliant & Halogen Free)







The data are for reference only. Electrical characteristics vary depending on environment or measurement condition.

YAGEO reserves the right to make change to the data at any time without notice. Before making final selection, please check product specification.