

Course Outline

Course Code : CSE 331L / EEE 332L
Course Name : Microprocessor Interfacing & Embedded System
Faculty : Dr. Sakhawat Hossain
Instructor : Tasmia Rahman Shahidi
Section : 6 (M 8:00 AM - 11:10 AM)
: 7 (M 2:40 PM - 5:50 PM)
Semester : Summer 2021

Course Plan:

Week	Date	Topic
Week 1	21-6-2021	Introduction to Assembly Language and basic instructions
Week 2	28-6-2021	DOS Functions
Week 3	5-7-2021	Variables
Week 4	12-7-2021	Project discussion, Quiz 1
Week 5	26-7-2021	Flow Control Instructions
Week 6	2-8-2021	Library emu8086.inc, Quiz 2
Week 7	9-8-2021	Bit-shift instructions
Week 8	16-8-2021	Stack and Procedures, Quiz 3
Week 9	23-8-2021	Review class, Quiz 4
Week 10	6-9-2021	Project Demonstration
Week 11	13-9-2021	Project Demonstration

Marks Distribution:

Quiz (best 3 out of 4) - 30%

Assignment - 20%

Project - 20%

Viva - 10%

Lab Performance - 15%

Class Performance - 5%

Lab - 1

What is Assembly Language

- A low-level programming language
- Converted to machine code using an **assembler**
- Important to low-level embedded system designs
- Designed for specific processor

Registers of MPU 8086

- Total number of registers: 14
- Each register size: 16 bits

General Purpose Registers

AX	AH	AL	Accumulator
BX	BH	BL	Base
CX	CH	CL	Count
DX	DH	DL	Data

Pointer and Index Registers

SP		Stack Pointer
BP		Base Pointer
SI		Source Index
DI		Destination Index
IP		Instruction Pointer

Segment Registers

CS		Code Segment
DS		Data Segment
SS		Stack Segment
ES		Extra Segment

	Flags
--	-------

General Purpose Registers (4 registers):

- Each GPR has two separate parts: Higher order byte and Lower order byte (each with 8 bits size). Data on each part can be separately manipulated
- Can perform 16 bits and 8 bits data read/write operations

	AH	AL
AX: 0011 0000 0011 1001 b	0011 0000 b	0011 1001 b
AX: 1111 0100 1010 0001 b	1111 0100 b	1010 0001 b
AX: F4A1 h	F4 h	A1 h
AX: 4 h	?	?

AX (Accumulator Register): Used in arithmetic, logic and data transfer operations

BX (Base Register): used as an address register

CX (Count Register): used for program loop count

DX (Data Register): used in arithmetic and I/O operations

Segment Registers (4 registers):

- Program code, data and stack are loaded into different memory segments.
- Stack segment: used for temporary storage of addresses and data
- Code segment: program instructions are loaded in this segment.
- Data segment: variables are declared in this segment
- Extra segment: another data segment in the memory

Pointer and Index Registers (5 registers):

- Points to memory locations
- Unlike segment registers, they can be used for general arithmetic operations
- IP register: contains the offset of the next instruction in the code segment

Flag Register:

- Indicates the status of the microprocessor

Structure of Assembly Language Programming for MPU 8086

Label: OperationToPerform operand1 operand2 ;

Label: OperationToPerform Destination Source ;

Label: - symbolic name for memory location

OperationToPerform - instruction name

Operand - direct data, register, memory address

; - comments

Operands: REG, MEMORY, Immediate

- **REG:** Any valid register
- **Memory:** Referring to a memory location in RAM
- **Immediate:** Using direct values (can never be a destination)

Instruction	Algorithm (= is assignment)
MOV	MOV Destination, Source Algorithm: destination = source
ADD	ADD Destination, Source Algorithm: destination = destination + source
SUB	SUB Destination, Source Algorithm: destination = destination - source
INC	INC Destination Algorithm: destination = destination + 1
DEC	DEC Destination Algorithm: destination = destination - 1
** source remains unchanged	

```
04
05 .model small
06 .stack 100h
07 .code
08
09 mov ah, 2      ; ah=2
10 add ah, 5      ; ah=2+5=7
11 mov al, 3      ; al=3
12 sub ah, al     ; ah=ah-al=7-3=4
13
14 inc bl         ; bl = bl+1=0+1=1
15 dec dh         ; dh=dh-1=0-1=-1=ffh
16
17 mov ah, 4ch
18 int 21h
19
```