



CLOUD COMPUTING

BSE (V-B)

Submitted By:

Musfira Farooq

Roll No:

2023-BSE-045

ASSIGNMENT 02

Advanced Terraform & Nginx Multi-Tier Architecture

Table of Contents

1. Executive Summary	3
2. Architecture Design	3
2.1 Architecture Overview	3
2.2 Architecture Diagram	3
2.3 Component Description.....	4
2.4 Network Topology.....	4
2.5 Security Design.....	4
3. Implementation Details	4
Part 1 : Infrastructure Setup.....	4
Part 2 : Webserver Module	9
Part 3 : Server Configuration Scripts	11
Part 4 : Infrastructure Deployment	15
Part 5 : Nginx Configuration & Testing	18
Bonus Tasks.....	25
Part 6 : Documentation & Cleanup.....	28
4. Testing Results	31
4.1 Load Balancing Validation	32
4.2 Caching Efficiency	32
4.3 High Availability Verification	32
4.4 Security Verification.....	32
5. Challenges & Solutions.....	32
6. Conclusion	33
7. Appendices.....	33
Appendix A: Code Listings	33
Appendix B: Configuration Files.....	33
Appendix C: Additional Screenshots.....	33

1. Executive Summary

This assignment focuses on the design, deployment, testing, and cleanup of a production-ready multi-tier web infrastructure using Terraform and Nginx on Amazon Web Services (AWS). The main objective was to implement Infrastructure as Code (IaC) .

The infrastructure consists of a custom VPC, public subnets, security groups, EC2 instances running Apache web servers, and Nginx proxy acting as a load balancer. Terraform modules were used to ensure modularity, reusability, and clean project organization.

Key features include:

- Fully automated infrastructure provisioning using Terraform
- Modular Terraform design (networking, security, webserver)
- Nginx load balancing with SSL, caching, and security headers
- High availability testing with backend failover
- Proper infrastructure cleanup to avoid AWS charges


2. Architecture Design

2.1 Architecture Overview

The architecture follows a three-tier model:

- Client Layer: End users accessing the application via browser
- Load Balancer Layer: Nginx reverse proxy handling traffic
- Application Layer: Multiple Apache web servers

2.2 Architecture Diagram



2.3 Component Description

Nginx Server (Reverse Proxy & Load Balancer)

The Nginx server handles all incoming user requests. It manages HTTP/HTTPS traffic, performs SSL/TLS termination, balances load across backend servers, applies caching and rate limiting, and displays custom error pages when needed.

Web Servers (Web-1, Web-2, Web-3)

The web servers run Apache and serve application content. Web-1 and Web-2 handle normal traffic, while Web-3 works as a backup server. All servers are monitored using health checks.

2.4 Network Topology

The infrastructure uses a custom VPC with public subnets. An Internet Gateway enables internet access, route tables manage traffic flow, and security groups control network access.


2.5 Security Design

Security groups restrict access to required ports only. SSH access is limited, backend servers are accessible only through Nginx, and sensitive files are protected using .gitignore.

3. Implementation Details

Part 1 : Infrastructure Setup

1.1-Project Structure:



```
PS C:\Users\Musfi> cd "C:\Users\Musfi\OneDrive\Desktop\cloud-computing\Assignment2"
PS C:\Users\Musfi\OneDrive\Desktop\cloud-computing\Assignment2> tree /F
Folder PATH listing for volume Windows
Volume serial number is 1AC1-669C
C:..
  .gitignore
  locals.tf
  main.tf
  outputs.tf
  README.md
  terraform.tfvars
  variables.tf
  modules
    -networking
      main.tf
      outputs.tf
      variables.tf
    -security
      main.tf
      outputs.tf
      variables.tf
    -webserver
      main.tf
      outputs.tf
      variables.tf
  scripts
    apache-setup.sh
    nginx-setup.sh
```

- content of .gitignore:

```
PS C:\Users\Musfi\OneDrive\Desktop\cloud-computing\Assignment2> type .gitignore
# Terraform files
.terraform/
terraform.tfstate
terraform.tfstate.backup
*.tfstate
*.tfstate.*

# Variable files
*.tfvars
terraform.tfvars

# Sensitive files
*.pem
*.key
*.crt

# OS files
.DS_Store
Thumbs.db

# Logs
*.log

# Editor directories
.vscode/
.idea/
PS C:\Users\Musfi\OneDrive\Desktop\cloud-computing\Assignment2> |
```

1.2-Variable Configuration:

```
ignore  README.md  variables.tf  terraform.tfvars
ers > Musfi > OneDrive > Desktop > cloud-computing > Assignment2 > variables.tf
# Networking Variables
variable "vpc_cidr_block" {
  description = "CIDR block for the VPC"
  type        = string

  validation {
    condition     = can(cidrnetmask(var.vpc_cidr_block))
    error_message = "The VPC CIDR block must be a valid CIDR notation."
  }
}

variable "subnet_cidr_block" {
  description = "CIDR block for the public subnet"
  type        = string

  validation {
    condition     = can(cidrnetmask(var.subnet_cidr_block))
    error_message = "The subnet CIDR block must be a valid CIDR notation."
  }
}

variable "availability_zone" {
  description = "Availability zone for EC2 instances"
}

variable "env_prefix" {
  type        = string
  default     = "prod"
}

variable "instance_type" {
  description = "EC2 instance type"
  type        = string
  default     = "t3.micro"
}

# SSH Key Variables
variable "public_key" {
  description = "Path to the public SSH key"
  type        = string
}

variable "private_key" {
  description = "Path to the private SSH key"
  type        = string
}

# Backend Server Configuration
variable "backend_servers" {
  description = "List of backend server definitions"
  type        = list(object({
    name       = string
    script_path = string
  }))
  default     = []
}
```

- terraform_tfvars:

.gitignore	README.md	variables.tf	terraform.tfvars
------------	-----------	--------------	------------------

C: > Users > Musfi > OneDrive > Desktop > cloud-computing > Assignment2 > terraform.tfvars

```

1  vpc_cidr_block   = "10.0.0.0/16"
2  subnet_cidr_block = "10.0.10.0/24"
3  availability_zone = "me-central-1a"
4
5  env_prefix      = "prod"
6  instance_type   = "t3.micro"
7
8  public_key      = "~/ssh/id_ed25519.pub"
9  private_key     = "~/ssh/id_ed25519"

```

1.3 Networking Module:

main.tf		
---------	--	--

Assignment2 > modules > networking > main.tf

```

1  resource "aws_vpc" "this" {
2      cidr_block           = var.vpc_cidr_block
3      enable_dns_support   = true
4      enable_dns_hostnames = true
5
6      tags = {
7          Name = "${var.env_prefix}-vpc"
8      }
9  }
10 resource "aws_subnet" "public" {
11     vpc_id            = aws_vpc.this.id
12     cidr_block        = var.subnet_cidr_block
13     availability_zone  = var.availability_zone
14     map_public_ip_on_launch = true
15
16     tags = {
17         Name = "${var.env_prefix}-public-subnet"
18     }
19 }
20 resource "aws_internet_gateway" "this" {
21     vpc_id = aws_vpc.this.id
22
23     tags = {
24         Name = "${var.env_prefix}-igw"
25     }
26 }
27 resource "aws_route_table" "public" {
28     vpc_id = aws_vpc.this.id
29
30     route {
31         cidr_block = "0.0.0.0/0"
32         gateway_id = aws_internet_gateway.this.id
33     }
34     tags = {
35         Name = "${var.env_prefix}-public-rt"
36     }
37 }
38 resource "aws_route_table_association" "public" {
39     subnet_id      = aws_subnet.public.id
40     route_table_id = aws_route_table.public.id
41 }

```

- **networking_module_outputs:**

```
Assignment2 > modules > networking > outputs.tf
1  output "vpc_id" {
2      description = "ID of the VPC"
3      value       = aws_vpc.this.id
4  }
5
6  output "subnet_id" {
7      description = "ID of the public subnet"
8      value       = aws_subnet.public.id
9  }
10
11  output "igw_id" {
12      description = "ID of the Internet Gateway"
13      value       = aws_internet_gateway.this.id
14  }
15
16  output "route_table_id" {
17      description = "ID of the route table"
18      value       = aws_route_table.public.id
19  }
```

Outputs:

```
backend_security_group_id = "sg-08d38879be7c412db"
igw_id = "igw-0840c938027046273"
nginx_security_group_id = "sg-056ee26d46110a861"
public_subnet_id = "subnet-0bd58ec5b237833ba"
route_table_id = "rtb-0bf4274015982b456"
vpc_id = "vpc-0ce419c111910bce0"
```

1.4 Security Module:

```
Assignment2 > modules > security > main.tf
1  resource "aws_security_group" "nginx_sg" {
2      name           = "${var.env_prefix}-nginx-sg"
3      description    = "Security group for Nginx reverse proxy"
4      vpc_id         = var.vpc_id
5      ingress {
6          description = "SSH from my IP"
7          from_port   = 22
8          to_port     = 22
9          protocol    = "tcp"
10         cidr_blocks = [var.my_ip]
11     }
12     ingress {
13         description = "HTTP from anywhere"
14         from_port   = 80
15         to_port     = 80
16         protocol    = "tcp"
17         cidr_blocks = ["0.0.0.0/0"]
18     }
19     ingress {
20         description = "HTTPS from anywhere"
21         from_port   = 443
22         to_port     = 443
23         protocol    = "tcp"
24         cidr_blocks = ["0.0.0.0/0"]
25     }
26 }
```

```

26     egress {
27         description = "All outbound"
28         from_port   = 0
29         to_port     = 0
30         protocol    = "-1"
31         cidr_blocks = ["0.0.0.0/0"]
32     }
33     tags = {
34         Name           = "${var.env_prefix}-nginx-sg"
35         Environment    = var.env_prefix
36         ManagedBy      = "Terraform"
37     }
38 }
39 resource "aws_security_group" "backend_sg" {
40     name           = "${var.env_prefix}-backend-sg"
41     description    = "Security group for backend web servers"
42     vpc_id         = var.vpc_id
43     ingress {
44         description = "SSH from my IP"
45         from_port   = 22
46         to_port     = 22
47         protocol    = "tcp"
48         cidr_blocks = [var.my_ip]
49     }
50     ingress {
51         description = "HTTP from Nginx SG only"
52         from_port   = 80
53         to_port     = 80
54         protocol    = "tcp"
55         security_groups = [aws_security_group.nginx_sg.id]
56     }
57     egress {
58         description = "All outbound"
59         from_port   = 0
60         to_port     = 0
61         protocol    = "-1"
62         cidr_blocks = ["0.0.0.0/0"]
63     }
64     tags = {
65         Name           = "${var.env_prefix}-backend-sg"
66         Environment    = var.env_prefix
67         ManagedBy      = "Terraform"
68     }
69 }
70 }

```

- **AWS Console:**

Name	Security group ID	Security group name	VPC ID
-	sg-01a52cd4fa859fcc2	default	vpc-0ce419c111910bce0
prod-nginx-sg	sg-056ee26d46110a861	prod-nginx-sg	vpc-0ce419c111910bce0
-	sg-0a745d4d5f53f30c9	default	vpc-0e1785b676d76a482
prod-backend-sg	sg-08d38879be7c412db	prod-backend-sg	vpc-0ce419c111910bce0

Select a security group

1.5 Locals Configuration:


```

Assignment2 > locals.tf
1  # Get your public IP dynamically
2  data "http" "my_ip" {
3    url = "https://icanhazip.com"
4  }
5
6  locals {
7    # Your IP for security group (dynamic)
8    my_ip = "${chomp(data.http.my_ip.response_body)}/32"
9
10   # Common tags for all resources
11   common_tags = {
12     Environment = var.env_prefix
13     Project     = "Assignment-2"
14     ManagedBy   = "Terraform"
15   }
16
17   # Backend servers configuration
18   backend_servers = [
19     {
20       name       = "web-1"
21       suffix     = "1"
22       script_path = "./scripts/apache-setup.sh"
23     },
24     {
25       name       = "web-2"
26       suffix     = "2"
27       script_path = "./scripts/apache-setup.sh"
28     },
29     {
30       name       = "web-3"
31       suffix     = "3"
32       script_path = "./scripts/apache-setup.sh"
33     }
34   ]
35 }

```

Part 2 : Webserver Module

2.1 Module Design:

```

Assignment2 > modules > webserver > variables.tf
1  variable "env_prefix" {
2    description = "Environment prefix"
3    type       = string
4  }
5
6  variable "instance_name" {
7    description = "Base name of the instance"
8    type       = string
9  }
10
11 variable "instance_type" {
12   description = "EC2 instance type"
13   type       = string
14 }
15
16 variable "availability_zone" {
17   description = "Availability zone"
18   type       = string
19 }
20
21 variable "vpc_id" {
22   description = "VPC ID"
23   type       = string
24 }
25
26 variable "subnet_id" {
27   description = "Subnet ID"
28   type       = string
29 }
30
31 variable "security_group_id" {
32   description = "Security group ID"
33   type       = string
34 }
35
36 variable "public_key" {
37   description = "Public SSH key"
38   type       = string
39 }
40
41 variable "script_path" {
42   description = "User data script path"
43   type       = string
44 }
45
46 variable "instance_suffix" {
47   description = "Unique instance suffix"
48   type       = string
49 }

```

```

Assignment2 > modules > webserver > main.tf
1  resource "aws_key_pair" "this" {
2      key_name     = "${var.env_prefix}-${var.instance_name}-${var.instance_suffix}-key"
3      public_key   = var.public_key
4
5      tags = merge(
6          var.common_tags,
7          {
8              Name = "${var.env_prefix}-${var.instance_name}-${var.instance_suffix}-key"
9          }
10     )
11 }
12
13 resource "aws_instance" "this" {
14     ami             = "ami-0c02fb55956c7d316" # Amazon Linux 2023 (us-east-1)
15     instance_type   = var.instance_type
16     availability_zone = var.availability_zone
17     subnet_id       = var.subnet_id
18     vpc_security_group_ids = [var.security_group_id]
19     key_name         = aws_key_pair.this.key_name
20     associate_public_ip_address = true
21
22     user_data = file(var.script_path)
23
24     tags = merge(
25         var.common_tags,
26         {
27             Name = "${var.env_prefix}-${var.instance_name}-${var.instance_suffix}"
28         }
29     )
30 }

```

```

Assignment2 > modules > webserver > outputs.tf
1  output "instance_id" {
2      description = "EC2 instance ID"
3      value       = aws_instance.this.id
4  }
5
6  output "public_ip" {
7      description = "Public IP address"
8      value       = aws_instance.this.public_ip
9  }
10
11 output "private_ip" {
12     description = "Private IP address"
13     value       = aws_instance.this.private_ip
14 }

```

2.2 Module Usage:

```
main.tf U X
Assignment2 > main.tf
1 provider "aws" {
2   region = "us-east-1" }
3 data "aws_availability_zones" "available" {}
4 locals {
5   backend_servers = [
6     { name = "web-1", script_path = "./scripts/apache-setup.sh", suffix = "web1" },
7     { name = "web-2", script_path = "./scripts/apache-setup.sh", suffix = "web2" },
8     { name = "web-3", script_path = "./scripts/apache-setup.sh", suffix = "web3" }, ]
9   common_tags = {
10    Environment = var.env_prefix
11    Project     = "WebApp" }
12   my_ip = "YOUR_PUBLIC_IP/32" # Replace with your actual IP }
13 module "networking" {
14   source = "../modules/networking"
15   vpc_cidr_block = var.vpc_cidr_block
16   subnet_cidr_block = var.subnet_cidr_block
17   availability_zone = data.aws_availability_zones.available.names[0]
18   env_prefix = var.env_prefix }
19 module "security" {
20   source = "../modules/security"
21   vpc_id = module.networking.vpc_id
22   env_prefix = var.env_prefix
23   my_ip = local.my_ip }
24 module "nginx_server" {
25   source = "../modules/webserver"
26   env_prefix = var.env_prefix
27   instance_name = "nginx-proxy"
28   instance_type = var.instance_type
29   availability_zone = data.aws_availability_zones.available.names[0]
30   vpc_id = module.networking.vpc_id
31   subnet_id = module.networking.subnet_id
32   security_group_id = module.security.nginx_sg_id
33   public_key = var.public_key
34   script_path = "./scripts/nginx-setup.sh"
35   instance_suffix = "nginx"
36   common_tags = local.common_tags }
37 module "backend_servers" {
38   for_each = { for server in local.backend_servers : server.name => server }
39   source = "../modules/webserver"
40   env_prefix = var.env_prefix
41   instance_name = each.value.name
42   instance_type = var.instance_type
43   availability_zone = data.aws_availability_zones.available.names[0]
44   vpc_id = module.networking.vpc_id
45   subnet_id = module.networking.subnet_id
46   security_group_id = module.security.backend_sg_id
47   public_key = var.public_key
48   script_path = each.value.script_path
49   instance_suffix = each.value.suffix
50   common_tags = local.common_tags
51 }
```

Part 3 : Server Configuration Scripts

3.1 Apache Backend Server Script:

```
$ apache-setup.sh U X
Assignment2 > scripts > $ apache-setup.sh
1  #!/bin/bash
2  set -e
3
4  # Update system
5  yum update -y
6
7  # Install Apache
8  yum install httpd -y
9
10 # Start and enable Apache
11 systemctl start httpd
12 systemctl enable httpd
13
14 # Get metadata token (IMDSv2)
15 TOKEN=$(curl -s -X PUT "http://169.254.169.254/latest/api/token" \
16 -H "X-aws-ec2-metadata-token-ttl-seconds: 21600")
17
18 # Get instance metadata
19 PRIVATE_IP=$(curl -s -H "X-aws-ec2-metadata-token: $TOKEN" \
20 http://169.254.169.254/latest/meta-data/local-ipv4)
21 PUBLIC_IP=$(curl -s -H "X-aws-ec2-metadata-token: $TOKEN" \
22 http://169.254.169.254/latest/meta-data/public-ipv4)
23 PUBLIC_DNS=$(curl -s -H "X-aws-ec2-metadata-token: $TOKEN" \
24 http://169.254.169.254/latest/meta-data/public-hostname)
25 INSTANCE_ID=$(curl -s -H "X-aws-ec2-metadata-token: $TOKEN" \
26 http://169.254.169.254/latest/meta-data/instance-id)
27
28 # Set hostname
29 hostnamectl set-hostname myapp-webserver
30
31 # Create custom HTML page
32 cat > /var/www/html/index.html <<EOF
33 <!DOCTYPE html>
34 <html>
35 <head>
36     <title>Backend Web Server</title>
37     <style>
38         body {
39             font-family: Arial, sans-serif;
40             margin: 50px;
41             background: linear-gradient(135deg, #667eea 0%, #764ba2 100%);
42             color: white;
43         }
44         .container {
45             background: rgba(255, 255, 255, 0.1);
46             padding: 30px;
47             border-radius: 10px;
48             box-shadow: 0 8px 32px 0 rgba(31, 38, 135, 0.37);
49         }
50         h1 { color: #fff; text-shadow: 2px 2px 4px rgba(0,0,0,0.3); }
51         .info { margin: 15px 0; padding: 10px; background: rgba(255,255,255,0.2); border-radius: 5px; }
52         .label { font-weight: bold; color: #ffd700; }
53     </style>
54 </head>
55 <body>
56     <div class="container">
57         <h1>Backend Web Server - Assignment 2</h1>
58         <div class="info"><span class="label">Hostname:</span> ${hostname}</div>
59         <div class="info"><span class="label">Instance ID:</span> $INSTANCE_ID</div>
60         <div class="info"><span class="label">Private IP:</span> $PRIVATE_IP</div>
61         <div class="info"><span class="label">Public IP:</span> $PUBLIC_IP</div>
62         <div class="info"><span class="label">Public DNS:</span> $PUBLIC_DNS</div>
63         <div class="info"><span class="label">Deployed:</span> $(date)</div>
64         <div class="info"><span class="label">Status:</span> ☒ Active and Running</div>
65         <div class="info"><span class="label">Managed By:</span> Terraform</div>
66     </div>
67 </body>
68 </html>
69 EOF
70
71 # Set permissions
72 chmod 644 /var/www/html/index.html
73
74 echo "Apache setup completed successfully!"
```

- browser showing backend server page:

Backend Web Server - Assignment 2

Hostname: \$(hostname)


Instance ID: \$INSTANCE_ID

Private IP: \$PRIVATE_IP

Public IP: \$PUBLIC_IP

Public DNS: \$PUBLIC_DNS

Deployed: \$(date)

Status:  Active and Running

Managed By: Terraform

EOF # Set permissions chmod 644 /var/www/html/index.html echo "Apache setup completed successfully!"

3.2 Nginx Server Setup Script:

```
variables.tf U  nginx-setup.sh U X
Assignment2 > scripts > $ nginx-setup.sh
1  #!/bin/bash
2  set -e
3
4  # Update and install Nginx
5  yum update -y
6  yum install -y nginx openssl
7  systemctl start nginx
8  systemctl enable nginx
9
10 # Create SSL directories
11 mkdir -p /etc/ssl/private
12 mkdir -p /etc/ssl/certs
13
14 # Get metadata token
15 TOKEN=$(curl -s -X PUT "http://169.254.169.254/latest/api/token" \
16 -H "X-aws-ec2-metadata-token-ttl-seconds: 21600")
17
18 # Get public IP
19 PUBLIC_IP=$(curl -s -H "X-aws-ec2-metadata-token: $TOKEN" \
20 http://169.254.169.254/latest/meta-data/public-ipv4)
21
22 # Generate self-signed certificate
23 openssl req -x509 -nodes -days 365 -newkey rsa:2048 \
24 -keyout /etc/ssl/private/selfsigned.key \
25 -out /etc/ssl/certs/selfsigned.crt \
26 -subj "/CN=$PUBLIC_IP" \
27 -addext "subjectAltName=IP:$PUBLIC_IP" \
28 -addext "basicConstraints=CA:FALSE" \
29 -addext "keyUsage=digitalSignature,keyEncipherment" \
30 -addext "extendedKeyUsage=serverAuth"
31
32 echo "Self-signed certificate created for IP: $PUBLIC_IP"
33
34 # Backup original config
35 cp /etc/nginx/nginx.conf /etc/nginx/nginx.conf.bak
36
37 # Create Nginx configuration
38 # Note: Backend IPs will be added manually after deployment
39 cat > /etc/nginx/nginx.conf <<'EOF'
40 user nginx;
41 worker_processes auto;
42 error_log /var/log/nginx/error.log notice;
43 pid /run/nginx.pid;
```

```

45     events {
46         worker_connections 1024;
47     }
48
49     http {
50         # Logging
51         log_format main '$remote_addr - $remote_user [$time_local] "$request" '
52             '$status $body_bytes_sent "$http_referer" '
53             '"$http_user_agent" "$http_x_forwarded_for" '
54             'Cache: $upstream_cache_status';
55
56         access_log /var/log/nginx/access.log main;
57
58         # Basic settings
59         sendfile on;
60         tcp_nopush on;
61         keepalive_timeout 65;
62         types_hash_max_size 4096;
63
64         include /etc/nginx/mime.types;
65         default_type application/octet-stream;
66
67         # Gzip compression
68         gzip on;
69         gzip_vary on;
70         gzip_types text/plain text/css application/json application/javascript text/xml application/xml;
71
72         # Cache configuration
73         proxy_cache_path /var/cache/nginx
74             levels=1:2
75             keys_zone=my_cache:10m
76             max_size=1g
77             inactive=60m
78             use_temp_path=off;
79
80         # Upstream backend servers
81         # PLACEHOLDER: Update these IPs after deployment
82         upstream backend_servers {
83             # Primary servers (active load balancing)
84             server BACKEND_IP_1:80;
85             server BACKEND_IP_2:80;

```

```

88             server BACKEND_IP_3:80 backup;
89         }
90
91         # HTTPS Server
92         server {
93             listen 443 ssl http2;
94             server_name _;
95
96             # SSL Configuration
97             ssl_certificate /etc/ssl/certs/selfsigned.crt;
98             ssl_certificate_key /etc/ssl/private/selfsigned.key;
99             ssl_protocols TLSv1.2 TLSv1.3;
100            ssl_ciphers HIGH:!aNULL:!MD5;
101            ssl_prefer_server_ciphers on;
102
103            # Security Headers
104            add_header Strict-Transport-Security "max-age=31536000; includeSubDomains" always;
105            add_header X-Frame-Options "SAMEORIGIN" always;
106            add_header X-Content-Type-Options "nosniff" always;
107            add_header X-XSS-Protection "1; mode=block" always;
108
109            # Proxy settings
110            location / {
111                proxy_pass http://backend_servers;
112
113                # Proxy headers
114                proxy_set_header Host $host;
115                proxy_set_header X-Real-IP $remote_addr;
116                proxy_set_header X-Forwarded-For $proxy_add_x_forwarded_for;
117                proxy_set_header X-Forwarded-Proto $scheme;
118
119                # Cache settings
120                proxy_cache my_cache;
121                proxy_cache_valid 200 60m;
122                proxy_cache_valid 404 10m;
123                proxy_cache_key "$scheme$request_method$host$request_uri";
124                proxy_cache_bypass $http_cache_control;
125                add_header X-Cache-Status $upstream_cache_status;
126
127                # Timeouts
128                proxy_connect_timeout 60s;


```

```

130            proxy_read_timeout 60s;
131        }
132
133        # Health check endpoint
134        location /health {
135            access_log off;
136            return 200 "Nginx is healthy\n";
137            add_header Content-Type text/plain;
138        }
139    }
140
141    # HTTP Server (redirect to HTTPS)
142    server {
143        listen 80;
144        server_name _;
145
146        location / {
147            return 301 https://$host$request_uri;
148        }
149
150        # Allow health checks over HTTP
151        location /health {
152            access_log off;
153            return 200 "Nginx is healthy\n";
154            add_header Content-Type text/plain;
155        }
156    }
157
158    EOF
159
160    # Create cache directory
161    mkdir -p /var/cache/nginx
162    chown -R nginx:nginx /var/cache/nginx
163
164    # Test and restart Nginx
165    nginx -t && systemctl restart nginx
166
167    echo "Nginx setup completed successfully!"
168    echo "Remember to update backend server IPs in /etc/nginx/nginx.conf"

```

- before backend configuration:



Part 4 : Infrastructure Deployment

4.1 Initial Deployment:

- ssh keygen:

```
PS C:\WINDOWS\system32> ls $HOME\.ssh\id_rsa.pub

Directory: C:\Users\Musfi\.ssh

Mode                LastWriteTime         Length Name
----                -
-a-----         12/28/2025   3:06 AM           748 id_rsa.pub

PS C:\WINDOWS\system32> _
```

- terraform init:

```
PS C:\WINDOWS\system32> cd "C:\Users\Musfi\OneDrive\Desktop\cloud-computing\Assignment2"
PS C:\Users\Musfi\OneDrive\Desktop\cloud-computing\Assignment2> terraform init
Initializing the backend...
Initializing modules...
Initializing provider plugins...
- Reusing previous version of hashicorp/http from the dependency lock file
- Reusing previous version of hashicorp/aws from the dependency lock file
- Using previously-installed hashicorp/http v3.5.0
- Using previously-installed hashicorp/aws v6.27.0

Terraform has been successfully initialized!

You may now begin working with Terraform. Try running "terraform plan" to see
any changes that are required for your infrastructure. All Terraform commands
should now work.

If you ever set or change modules or backend configuration for Terraform,
rerun this command to reinitialize your working directory. If you forget, other
commands will detect it and remind you to do so if necessary.
PS C:\Users\Musfi\OneDrive\Desktop\cloud-computing\Assignment2>
```

- terraform validate:

```
PS C:\Users\Musfi\OneDrive\Desktop\cloud-computing\Assignment2> terraform validate
Success! The configuration is valid.
```

- terraform plan:

```

Plan: 0 to add, 3 to change, 0 to destroy.

Note: You didn't use the -out option to save this plan, so Terraform can't guarantee to take exactly these actions if
you run "terraform apply" now.
PS C:\Users\Musfi\OneDrive\Desktop\cloud-computing\Assignment2>

```

- **terraform apply:**

```

Plan: 0 to add, 3 to change, 0 to destroy.

Do you want to perform these actions?
  Terraform will perform the actions described above.
  Only 'yes' will be accepted to approve.

  Enter a value: yes

module.nginx_server.aws_key_pair.this: Modifying... [id=prod-nginx-proxy-nginx-key]
module.security.aws_security_group.nginx_sg: Modifying... [id=sg-056ee26d46110a861]
module.nginx_server.aws_key_pair.this: Modifications complete after 2s [id=prod-nginx-proxy-nginx-key]
module.security.aws_security_group.nginx_sg: Modifications complete after 3s [id=sg-056ee26d46110a861]
module.nginx_server.aws_instance.this: Modifying... [id=i-0e7f2ea3cd5a03622]
module.nginx_server.aws_instance.this: Still modifying... [id=i-0e7f2ea3cd5a03622, 00m10s elapsed]
module.nginx_server.aws_instance.this: Still modifying... [id=i-0e7f2ea3cd5a03622, 00m20s elapsed]
module.nginx_server.aws_instance.this: Still modifying... [id=i-0e7f2ea3cd5a03622, 00m30s elapsed]
module.nginx_server.aws_instance.this: Still modifying... [id=i-0e7f2ea3cd5a03622, 00m40s elapsed]
module.nginx_server.aws_instance.this: Still modifying... [id=i-0e7f2ea3cd5a03622, 00m50s elapsed]
module.nginx_server.aws_instance.this: Still modifying... [id=i-0e7f2ea3cd5a03622, 01m00s elapsed]
module.nginx_server.aws_instance.this: Still modifying... [id=i-0e7f2ea3cd5a03622, 01m10s elapsed]
module.nginx_server.aws_instance.this: Still modifying... [id=i-0e7f2ea3cd5a03622, 01m20s elapsed]
module.nginx_server.aws_instance.this: Modifications complete after 1m29s [id=i-0e7f2ea3cd5a03622]

Apply complete! Resources: 0 added, 3 changed, 0 destroyed.

Outputs:

backend_security_group_id = "sg-08d38879be7c412db"
igw_id = "igw-0840c938027046273"
nginx_security_group_id = "sg-056ee26d46110a861"
public_subnet_id = "subnet-0bd58ec5b237833ba"
route_table_id = "rtb-0bf4274015982b456"
vpc_id = "vpc-0ce419c111910bce0"
PS C:\Users\Musfi\OneDrive\Desktop\cloud-computing\Assignment2>

```

4.2 Output Configuration:

- **Terraform output:**

```

Administrator: Windows PowerShell
PS C:\Users\Musfi\OneDrive\Desktop\cloud-computing\Assignment2> terraform output

backend_servers_info = {
  "web-1" = {
    "instance_id" = "i-039adc90b95422dd3"
    "private_ip" = "10.0.10.16"
    "public_ip" = "35.170.65.185"
  }
  "web-2" = {
    "instance_id" = "i-08030d8bd5cb8e384"
    "private_ip" = "10.0.10.33"
    "public_ip" = "44.202.225.100"
  }
  "web-3" = {
    "instance_id" = "i-0c2c9048866645ab"
    "private_ip" = "10.0.10.199"
    "public_ip" = "34.200.229.201"
  }
}
configuration_guide = <<EOT
=====
DEPLOYMENT SUCCESSFUL!
=====

Next Steps:
1. SSH into Nginx server: ssh ec2-user@13.223.93.99
2. Edit Nginx config: sudo vim /etc/nginx/nginx.conf
3. Update backend IPs in upstream block:
  - BACKEND_IP_1: 10.0.10.16
  - BACKEND_IP_2: 10.0.10.33
  - BACKEND_IP_3: 10.0.10.199
4. Restart Nginx: sudo systemctl restart nginx
5. Test: https://13.223.93.99

Backend Servers:
- web-1: 35.170.65.185 (private: 10.0.10.16)
- web-2: 44.202.225.100 (private: 10.0.10.33)
- web-3: 34.200.229.201 (private: 10.0.10.199)
=====


```

- **Terraform outputs json:**



```
Administrator: Windows PowerShell
PS C:\Users\Musfi\OneDrive\Desktop\cloud-computing\Assignment2> terraform output -json > outputs.json
PS C:\Users\Musfi\OneDrive\Desktop\cloud-computing\Assignment2> cat outputs.json
{
  "backend_servers_info": {
    "sensitive": false,
    "type": [
      "object",
      {
        "web-1": [
          "object",
          {
            "instance_id": "string",
            "private_ip": "string",
            "public_ip": "string"
          }
        ],
        "web-2": [
          "object",
          {
            "instance_id": "string",
            "private_ip": "string",
            "public_ip": "string"
          }
        ],
        "web-3": [
          "object",
          {
            "instance_id": "string",
            "private_ip": "string",
            "public_ip": "string"
          }
        ]
      }
    ],
    "value": {
      "web-1": {
        "instance_id": "i-039adc90b95422dd3",
        "private_ip": "10.0.10.16",
        "public_ip": "35.170.65.185"
      }
    }
  }
}
```

4.3 AWS Console Verification:


- aws vpc:




- aws subnet:



• aws security groups:



• aws instances:




Part 5 : Nginx Configuration & Testing

5.1 Update Nginx Backend Configuration:


• ssh nginx:

5.2 Test Load Balancing:


- ssl warning:




- web1 response:



- web2 response:



- load balancing demo:



5.3 Test Cache Functionality:

- cache miss:

```
79.124.40.174 - - [28/Dec/2025:15:03:14 +0000] "GET /console/ HTTP/1.1" 404 183 "http://13.223.93.99/console/" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/78.0.3904.108 Safari/537.36" "-" Cache:MISS
```

- cache hit:

```
[ec2-user@ip-10-0-10-213 ~]$ sudo grep "Cache:" /var/log/nginx/access.log | tail -20
283.215.167.149 - - [28/Dec/2025:14:44:22 +0000] "GET / HTTP/2.0" 200 685 "-" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0.0 Safari/537.36" "-" Cache:HIT
```

- cache directory:

```
[ec2-user@ip-10-0-10-213 ~]$ sudo ls -la /var/cache/nginx/
total 0
drwx----- 4 nginx root 24 Dec 28 14:33 .
drwxr-xr-x 8 root root 89 Dec 28 14:26 ..
drwx----- 3 nginx nginx 16 Dec 28 14:33 0
drwx----- 3 nginx nginx 16 Dec 28 14:33 1
```

- access log cache:

```
ec2-user@ip-10-0-10-213:~
[ec2-user@ip-10-0-10-213 ~]$ sudo grep "Cache:" /var/log/nginx/access.log | tail -20
283.215.167.149 - - [28/Dec/2025:14:31:50 +0000] "GET / HTTP/1.1" 301 169 "-" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0.0 Safari/537.36" "-" Cache:-
283.215.167.149 - - [28/Dec/2025:14:33:30 +0000] "GET / HTTP/2.0" 200 685 "-" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0.0 Safari/537.36" "-" Cache:BYPASS
283.215.167.149 - - [28/Dec/2025:14:33:32 +0000] "GET /favicon.ico HTTP/2.0" 404 172 "https://13.223.93.99/" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0.0 Safari/537.36" "-" Cache:MISS
283.215.167.149 - - [28/Dec/2025:14:35:05 +0000] "GET / HTTP/2.0" 200 685 "-" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0.0 Safari/537.36" "-" Cache:BYPASS
283.215.167.149 - - [28/Dec/2025:14:35:06 +0000] "GET / HTTP/2.0" 200 685 "-" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0.0 Safari/537.36" "-" Cache:BYPASS
283.215.167.149 - - [28/Dec/2025:14:36:15 +0000] "GET / HTTP/2.0" 200 685 "-" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0.0 Safari/537.36" "-" Cache:BYPASS
283.215.167.149 - - [28/Dec/2025:14:36:17 +0000] "GET / HTTP/2.0" 200 685 "-" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0.0 Safari/537.36" "-" Cache:BYPASS
283.215.167.149 - - [28/Dec/2025:14:37:49 +0000] "GET / HTTP/2.0" 200 685 "-" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0.0 Safari/537.36" "-" Cache:BYPASS
283.215.167.149 - - [28/Dec/2025:14:44:00 +0000] "GET / HTTP/2.0" 200 685 "-" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/143.0.0.0 Safari/537.36" "-" Cache:BYPASS
```

5.4 Test High Availability (Backup Server):


- web1 stopped:

```
[ec2-user@myapp-webserver ~]$ sudo systemctl stop httpd
[ec2-user@myapp-webserver ~]$ sudo systemctl status httpd
● httpd.service - The Apache HTTP Server
   Loaded: loaded (/usr/lib/systemd/system/httpd.service; enabled; vendor preset: disabled)
   Active: inactive (dead) since Sun 2025-12-28 20:23:07 UTC; 9s ago
     Docs: man:httpd.service(8)
  Process: 10392 ExecReload=/usr/sbin/httpd $OPTIONS -k graceful (code=exited, status=0/SUCCESS)
  Process: 10213 ExecStart=/usr/sbin/httpd $OPTIONS -DFOREGROUND (code=exited, status=0/SUCCESS)
 Main PID: 10213 (code=exited, status=0/SUCCESS)
   Status: "Total requests: 110; Idle/Busy workers 100/0; Requests/sec: 0.000643; Bytes served/sec:
```

- web2 stopped:

```
[ec2-user@myapp-webserver ~]$ sudo systemctl stop httpd
[ec2-user@myapp-webserver ~]$ sudo systemctl status httpd
● httpd.service - The Apache HTTP Server
   Loaded: loaded (/usr/lib/systemd/system/httpd.service; enabled; vendor preset: disabled)
   Active: inactive (dead) since Sun 2025-12-28 20:26:55 UTC; 5s ago
     Docs: man:httpd.service(8)
  Process: 10312 ExecReload=/usr/sbin/httpd $OPTIONS -k graceful (code=exited, status=0/SUCCESS)
  Process: 10224 ExecStart=/usr/sbin/httpd $OPTIONS -DFOREGROUND (code=exited, status=0/SUCCESS)
 Main PID: 10224 (code=exited, status=0/SUCCESS)
   Status: "Total requests: 131; Idle/Busy workers 100/0; Requests/sec: 0.000765; Bytes served/sec:
```


- backup activated:



- nginx error log:

```
[ec2-user@ip-10-0-10-213 ~]$ sudo tail -f /var/log/nginx/error.log
2025/12/28 14:28:03 [notice] 9487#9487: http file cache: /var/cache/nginx 0.000M, bsize: 4096
2025/12/28 14:28:03 [notice] 9483#9483: signal 17 (SIGCHLD) received from 9487
2025/12/28 14:28:03 [notice] 9483#9483: cache loader process 9487 exited with code 0
2025/12/28 14:28:03 [notice] 9483#9483: signal 29 (SIGIO) received
2025/12/28 20:24:52 [error] 9484#9484: *244 connect() failed (111: Connection refused) while connecting to upstream, client: 203.215.167.149, server: _, request: "GET / HTTP/2.0", upstream: "http://10.0.10.16:80/", host: "13.223.93.99"
2025/12/28 20:24:52 [warn] 9484#9484: *244 upstream server temporarily disabled while connecting to upstream, client: 203.215.167.149, server: _, request: "GET / HTTP/2.0", upstream: "http://10.0.10.16:80/", host: "13.223.93.99"
2025/12/28 20:28:16 [error] 9484#9484: *252 connect() failed (111: Connection refused) while connecting to upstream, client: 203.215.167.149, server: _, request: "GET / HTTP/2.0", upstream: "http://10.0.10.33:80/", host: "13.223.93.99"
2025/12/28 20:28:16 [warn] 9484#9484: *252 upstream server temporarily disabled while connecting to upstream, client: 203.215.167.149, server: _, request: "GET / HTTP/2.0", upstream: "http://10.0.10.33:80/", host: "13.223.93.99"
2025/12/28 20:28:16 [error] 9484#9484: *252 connect() failed (111: Connection refused) while connecting to upstream, client: 203.215.167.149, server: _, request: "GET / HTTP/2.0", upstream: "http://10.0.10.16:80/", host: "13.223.93.99"
2025/12/28 20:28:16 [warn] 9484#9484: *252 upstream server temporarily disabled while connecting to upstream, client: 203.215.167.149, server: _, request: "GET / HTTP/2.0", upstream: "http://10.0.10.16:80/", host: "13.223.93.99"
```


- **services restored:**



5.5 Security & Performance Analysis:

- **ssl certificate:**

```
PS C:\WINDOWS\system32> openssl s_client -connect 13.223.93.99:443 -showcerts
Connecting to 13.223.93.99
CONNECTED(00000168)
Can't use SSL_get_servername
depth=0 CN=10.0.10.213
verify error:num=18:self-signed certificate
verify return:1
depth=0 CN=10.0.10.213
verify return:1
---
Certificate chain
 0 s:CN=10.0.10.213
  i:CN=10.0.10.213
   a:KEY: rsaEncryption, 2048 (bit); sigalg: RSA-SHA256
   v:NotBefore: Dec 28 14:21:53 2025 GMT; NotAfter: Dec 28 14:21:53 2026 GMT
-----BEGIN CERTIFICATE-----
MIIC/zCCAeegAwIBAgITJALShxayOoiV7MA0GCSqGSIb3DQEBCwUAMBYxFDASBgNV
BAMCCzEwLjAuMTA1MjEzMDEyODI1MTIyODE0MDU1MTIyODI1MTIyODI1MTIyODI1MTIy
FjEUMBMGA1UEAwwLMTEwMC4yMTcwggEiMA0GCSqGSIb3DQEBBAQUAAIBDwAwgEKAoI
BAQC3ZBb383rqKXDT76S+hM8sdW7kUuIIJsn5Qsd7I4ynHgZs83o5YzRj+qd
Q7ZTilgkvFL/3Z+GMe2g4czW20/Q+4MJFeaerAYIPaqJJFFcKdVVFSAYlT8mzq+yd
UlbfonpuSRSA0YsaDrnmQ3xPdGmthbkWb+8USc05D0lKVczrROSskJKQwM7/SvJ4
LQ9T7JGGfMi+MD+oc/i/n8X+4ag+usDd51cUAQCE6F8C3ub6ZYE3aJqUoC5+jjbh
/yFSrOrTsooNoD7yTi5ISTlRlV04XmnnaWA04iTsuDrsee9tbtdrmkKnNOEIlggi
AJY9pbirUoPzORCPDUH3/a0TeDebeEeBhAgMBAAGjUDBoMB0GA1UdDgQwBBQqjdff/
iRxTBcTIKqZyb7kHrRuIJfABgNVHSMEGDAWgBQqjdff/jRxBcTIKqPbyz7kHrRu
IJAMBGBNVRMEBTADAQH/MA0GCSqGSIb3DQEBCwUAA4IAQAUCUXZ0SiAm3j5BdMsR1
pzePh2MM++CYGIj5/FwbY5f1UmV3a0XosEyLWt+jaGqFvny1Uum2tL8TK21r/Hur+
dkX8hmMWGipwez4Dm64XyNxvPE2nz87uB1mbdd1FKt5AvPYBGUJY9BFIEgnmAEEc
06fPMCRbzchASnZq8q6AN+hh10NYU6wVwCX478Q/Yibkc4NHkfPfnRrhAnWB8EvN
24RNFIzgukah/Umsurn+/SoRogyEQyxZ4B79bIgTs379CNXLhtcf0x3Fat3Stid
TedqvZjRCXHJCmHmshlik3YoazbvHjoM5N3yFAugtZMbY7rRho3IoHKAtvv1Cvb+
vyZu
-----END CERTIFICATE-----
---
Server certificate
subject=CN=10.0.10.213
issuer=CN=10.0.10.213
```

```
Peer signing digest: SHA256
Peer signature type: RSA-PSS
Server Temp Key: X25519, 253 bits
---
SSL handshake has read 1327 bytes and written 386 bytes
Verification error: self-signed certificate
---
New, TLSv1.3, Cipher is TLS_AES_256_GCM_SHA384
Server public key is 2048 bit
This TLS version forbids renegotiation.
Compression: NONE
Expansion: NONE
No ALPN negotiated
Early data was not sent
Verify return code: 18 (self-signed certificate)
```

- security headers:

```
[ec2-user@ip-10-0-10-213 ~]$ sudo nano +84 /etc/nginx/nginx.conf
[ec2-user@ip-10-0-10-213 ~]$ sudo nginx -t
nginx: the configuration file /etc/nginx/nginx.conf syntax is ok
nginx: configuration file /etc/nginx/nginx.conf test is successful
[ec2-user@ip-10-0-10-213 ~]$ sudo systemctl reload nginx
[ec2-user@ip-10-0-10-213 ~]$ curl -I -k https://13.223.93.99
HTTP/2 200
server: nginx/1.28.0
date: Mon, 29 Dec 2025 09:38:32 GMT
content-type: text/html
content-length: 615
last-modified: Tue, 12 Aug 2025 21:30:50 GMT
vary: Accept-Encoding
etag: "689bb28a-267"
strict-transport-security: max-age=31536000; includeSubDomains
x-frame-options: DENY
x-content-type-options: nosniff
x-xss-protection: 1; mode=block
content-security-policy: default-src 'self'
strict-transport-security: max-age=31536000; includeSubDomains
x-frame-options: DENY
x-content-type-options: nosniff
x-xss-protection: 1; mode=block
content-security-policy: default-src 'self'
accept-ranges: bytes
[ec2-user@ip-10-0-10-213 ~]$ _
```

- http redirect:

```
[ec2-user@ip-10-0-10-213 ~]$ curl -I http://13.223.93.99
HTTP/1.1 301 Moved Permanently
Server: nginx/1.28.0
Date: Mon, 29 Dec 2025 10:08:57 GMT
Content-Type: text/html
Content-Length: 169
Connection: keep-alive
Location: https://13.223.93.99/
[ec2-user@ip-10-0-10-213 ~]$ _
```

- error log analysis:


```

ec2-user@ip-10-0-10-213:~$ sudo tail -50 /var/log/nginx/error.log
[ec2-user@ip-10-0-10-213 ~]$ sudo tail -50 /var/log/nginx/error.log
2025/12/29 09:32:47 [emerg] 4070#4070: host not found in upstream "backend" in /etc/nginx/nginx.conf:84
2025/12/29 09:32:47 [emerg] 4073#4073: host not found in upstream "backend" in /etc/nginx/nginx.conf:84
2025/12/29 09:38:22 [notice] 4353#4353: signal process started
2025/12/29 09:38:22 [notice] 9483#9483: signal 1 (SIGHUP) received from 4353, reconfiguring
2025/12/29 09:38:22 [notice] 9483#9483: reconfiguring
2025/12/29 09:38:22 [notice] 9483#9483: using the "epoll" event method
2025/12/29 09:38:22 [notice] 9483#9483: start worker processes
2025/12/29 09:38:22 [notice] 9483#9483: start worker process 4354
2025/12/29 09:38:22 [notice] 9483#9483: start worker process 4355
2025/12/29 09:38:22 [notice] 9483#9483: start cache manager process 4358
2025/12/29 09:38:22 [notice] 30573#30573: gracefully shutting down
2025/12/29 09:38:22 [notice] 30572#30572: gracefully shutting down
2025/12/29 09:38:22 [notice] 30573#30573: exiting
2025/12/29 09:38:22 [notice] 30572#30572: exiting
2025/12/29 09:38:22 [notice] 30572#30572: exit
2025/12/29 09:38:22 [notice] 30573#30573: exit
2025/12/29 09:38:22 [notice] 30574#30574: exiting
2025/12/29 09:38:22 [notice] 9483#9483: signal 17 (SIGCHLD) received from 30572
2025/12/29 09:38:22 [notice] 9483#9483: worker process 30572 exited with code 0
2025/12/29 09:38:22 [notice] 9483#9483: cache manager process 30574 exited with code 0
2025/12/29 09:38:22 [notice] 9483#9483: signal 29 (SIGIO) received
2025/12/29 09:38:22 [notice] 9483#9483: signal 17 (SIGCHLD) received from 30573
2025/12/29 09:38:22 [notice] 9483#9483: worker process 30573 exited with code 0
2025/12/29 09:38:22 [notice] 9483#9483: signal 29 (SIGIO) received
2025/12/29 09:55:54 [emerg] 5357#5357: invalid number of arguments in "proxy_set_header" directive in /etc/nginx/nginx.conf:87
2025/12/29 10:07:45 [notice] 5971#5971: signal process started
2025/12/29 10:07:45 [notice] 9483#9483: signal 1 (SIGHUP) received from 5971, reconfiguring
2025/12/29 10:07:45 [notice] 9483#9483: reconfiguring
2025/12/29 10:07:45 [notice] 9483#9483: using the "epoll" event method
2025/12/29 10:07:45 [notice] 9483#9483: start worker processes
2025/12/29 10:07:45 [notice] 9483#9483: start worker process 5973
2025/12/29 10:07:45 [notice] 9483#9483: start worker process 5974
2025/12/29 10:07:45 [notice] 9483#9483: start cache manager process 5975
2025/12/29 10:07:45 [notice] 4355#4355: gracefully shutting down

```

- access log analysis:

```


[ec2-user@ip-10-0-10-213 ~]$ sudo tail -50 /var/log/nginx/access.log
204.76.203.212 - - [29/Dec/2025:06:12:13 +0000] "GET / HTTP/1.1" 301 169 "-" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/90.0.438.85 Safari/537.36 Edg/90.0.818.46" "-" Cache:-
107.150.105.5 - - [29/Dec/2025:06:12:37 +0000] "GET / HTTP/1.1" 200 697 "-" "Mozilla/5.0 (X11; Linux x86_64) AppleWebKit/534.37 (KHTML, like Gecko) Chrome/64.0.2981 Safari/537.36" "-" Cache:HIT
107.150.105.5 - - [29/Dec/2025:06:12:37 +0000] "GET /favicon.ico HTTP/1.1" 404 183 "-" "Go-http-client/1.1" "-" Cache:MISS
107.150.105.5 - - [29/Dec/2025:06:12:38 +0000] "GET /robots.txt HTTP/1.1" 404 183 "-" "Go-http-client/1.1" "-" Cache:MISS
107.150.105.5 - - [29/Dec/2025:06:12:38 +0000] "GET /sitemap.xml HTTP/1.1" 404 183 "-" "Go-http-client/1.1" "-" Cache:MISS
198.235.24.15 - - [29/Dec/2025:06:28:45 +0000] "GET / HTTP/1.0" 301 169 "-" "Hello from Palo Alto Networks, find out more about our scans in https://docs-cortex.paloaltonet.works.com/r/1/Cortex-Xpanse/Scanning-activity" "-" Cache:-
20.221.72.174 - - [29/Dec/2025:06:32:00 +0000] "GET /actuator/health HTTP/1.1" 404 183 "-" "Mozilla/5.0 zgrab/0.x" "-" Cache:MISS
204.76.203.219 - - [29/Dec/2025:06:36:56 +0000] "GET / HTTP/1.1" 301 169 "-" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/90.0.438.85 Safari/537.36 Edg/90.0.818.46" "-" Cache:-
3.132.23.201 - - [29/Dec/2025:06:39:15 +0000] "GET / HTTP/1.1" 301 169 "-" "cypex.ai/scanning Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_7) Chrome/126.0.0.0 Safari/537.36" "-" Cache:-
3.132.23.201 - - [29/Dec/2025:06:39:15 +0000] "GET / HTTP/1.1" 200 697 "http://13.223.93.99/" "cypex.ai/scanning Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_7) Chrome/126.0.0.0 Safari/537.36" "-" Cache:HIT
3.132.23.201 - - [29/Dec/2025:06:39:48 +0000] "" 400 0 "-" "-" "-" Cache:-
3.132.23.201 - - [29/Dec/2025:06:42:24 +0000] "GET / HTTP/1.1" 301 169 "-" "cypex.ai/scanning Mozilla/5.0 (Macintosh; Intel Mac OS X 10_15_7) Chrome/126.0.0.0 Safari/537.36" "-" Cache:-
3.132.23.201 - - [29/Dec/2025:06:44:48 +0000] "\x16\x03\x01\x00{\x01\x00\x00\x03\x03 \xf3\x08\xdc\x83qf\x89)\x9b\x08\x12\x83 \x97\x45\x80 \xcF\xA8\x82J\xF5F." \xE4X\x92U\x00\x00\x1A\xC0\xC0\x11\xC0\x07\xC0\x13\xC0\x09\xC0\x14\xC0" 400 157 "-" "-" "-" Cache:-
5.187.35.158 - - [29/Dec/2025:06:45:45 +0000] "GET /SDK/webLanguage HTTP/1.1" 404 183 "-" "Mozilla/5.0 (Windows NT 10.0; Win64; x64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/90.0.4430.85 Safari/537.36 Edg/90.0.818.46" "-" Cache:MISS
3.132.23.201 - - [29/Dec/2025:06:46:46 +0000] "SSH-2.0-Go" 400 157 "-" "-" "-" Cache:-
3.132.23.201 - - [29/Dec/2025:06:50:27 +0000] "\x16\x03\x01\x00{\x01\x00\x00\x03\x03d\xA2\xA8d'\x83\x1B\xC6\xE8\xD6\x81\x95j-T\xD1\x84\x8DF\xA8\xA8\xA4\xA5" 400 157 "-" "-" "-" Cache:-
198.235.24.138 - - [29/Dec/2025:06:52:22 +0000] "GET / HTTP/1.1" 200 697 "-" "Hello from Palo Alto Networks, find out more about our scans in https://docs-cortex.paloaltonet.works.com/r/1/Cortex-Xpanse/Scanning-activity" "-" Cache:HIT
216.180.246.86 - - [29/Dec/2025:06:55:17 +0000] "GET /favicon.ico HTTP/1.1" 404 183 "-" "Mozilla/5.0 (compatible; GenomeCrawler/1.0; +https://www.nokia.com/genomecrawler)" "-" Cache:EXPIRED
216.180.246.86 - - [29/Dec/2025:06:55:47 +0000] "GET /favicon.ico HTTP/1.1" 404 183 "-" "Mozilla/5.0 (compatible; GenomeCrawler/1.0; +https://www.nokia.com/genomecrawler)" "-" Cache:HIT
185.189.182.234 - - [29/Dec/2025:07:20:33 +0000] "GET / HTTP/1.1" 400 157 "-" "-" "-" Cache:-
64.225.15.204 - - [29/Dec/2025:07:26:50 +0000] "GET /.git/config HTTP/1.1" 301 169 "-" "Mozilla/5.0 (X11; Linux x86_64) AppleWebKit/537.36 (KHTML, like Gecko) Chrome/81.0.4044.129 Safari/537.36" "-" Cache:-

```

Bonus Tasks

Bonus 1: Custom Error Pages


- custom_404:




- custom_502:

```
[ec2-user@ip-10-0-10-213 ~]$ sudo nano /etc/nginx/nginx.conf
[ec2-user@ip-10-0-10-213 ~]$ sudo nginx -t
nginx: the configuration file /etc/nginx/nginx.conf syntax is ok
nginx: configuration file /etc/nginx/nginx.conf test is successful
[ec2-user@ip-10-0-10-213 ~]$ sudo systemctl reload nginx
[ec2-user@ip-10-0-10-213 ~]$ curl -I -k https://13.223.93.99/
HTTP/1.1 502 Bad Gateway
Server: nginx/1.28.0
Date: Mon, 29 Dec 2025 10:44:41 GMT
Content-Type: text/html
Content-Length: 345
Connection: keep-alive
ETag: "6952582a-159"
Strict-Transport-Security: max-age=31536000; includeSubDomains
X-Frame-Options: DENY
X-Content-Type-Options: nosniff
X-XSS-Protection: 1; mode=block
Content-Security-Policy: default-src 'self'
Strict-Transport-Security: max-age=31536000; includeSubDomains
X-Frame-Options: DENY
X-Content-Type-Options: nosniff
X-XSS-Protection: 1; mode=block
Content-Security-Policy: default-src 'self'

[ec2-user@ip-10-0-10-213 ~]$ _
```



- custom_503:



Bonus 2: Implement Rate Limiting

- rate_limit_config:

- **rate_limit_test**

Bonus 3: Health Check Automation

- pg. 27

```
[ec2-user@ip-10-0-10-213 ~]$ sudo nano /usr/local/bin/health_check.sh
[ec2-user@ip-10-0-10-213 ~]$ [ec2-user@ip-10-0-10-213 ~]$ sudo chmod +x /usr/local/bin/health_check.sh
[ec2-user@ip-10-0-10-213 ~]$ cat /usr/local/bin/health_check.sh
#!/bin/bash

# List of backend servers
BACKENDS=("10.0.10.16" "10.0.10.33" "10.0.10.199")
LOGFILE="/var/log/backend_health.log"

# Check each backend server
for SERVER in "${BACKENDS[@]}"
do
    # Ping or curl to check if server is alive
    if curl -s --connect-timeout 5 http://$SERVER:80 >/dev/null; then
        echo "$(date '+%Y-%m-%d %H:%M:%S') - $SERVER is UP" >> $LOGFILE
    else
        echo "$(date '+%Y-%m-%d %H:%M:%S') - $SERVER is DOWN" >> $LOGFILE
        # Optional: restart Apache on backend (if accessible via SSH)
        # ssh ec2-user@$SERVER "sudo systemctl restart httpd"
    fi
done
```

- health_log:

```
[ec2-user@ip-10-0-10-213 ~]$ sudo nano /usr/local/bin/health_check.sh
[ec2-user@ip-10-0-10-213 ~]$ /usr/local/bin/health_check.sh
[ec2-user@ip-10-0-10-213 ~]$ cat ~/backend_health.log
2025-12-29 11:50:44 - 10.0.10.16 is UP
2025-12-29 11:50:44 - 10.0.10.33 is UP
2025-12-29 11:50:44 - 10.0.10.199 is UP
[ec2-user@ip-10-0-10-213 ~]$
```

Part 6 : Documentation & Cleanup

6.1 README Documentation

```
ec2-user@ip-10-0-10-213~
[ec2-user@ip-10-0-10-213 ~]$ nano README.md
[ec2-user@ip-10-0-10-213 ~]$ cat README.md
# Assignment 2 - Multi-Tier Web Infrastructure

## Project Overview
This project implements a multi-tier web infrastructure on AWS with a highly available and secure Nginx load balancer fronting multiple web servers.
The architecture supports SSL/TLS, caching, reverse proxy, security headers, custom error pages, rate limiting, and automated health checks.

---

## Architecture Diagram

graph TD
    Internet[Internet] -- "HTTPS (443)  
HTTP (80)" --> Nginx["Nginx Server  
(Load Balancer)  
- SSL/TLS  
- Caching  
- Reverse Proxy"]
    Nginx --> Web1[Web-1  
Primary]
    Nginx --> Web2[Web-2  
Primary]
    Nginx --> Web3[Web-3  
Backup]

---

## Components Description

- **Nginx Server (Load Balancer)**:
```

- Terminates SSL/TLS
- Implements caching and rate limiting
- Serves as reverse proxy for backend web servers
- Handles custom error pages (404, 502, 503)

- ****Web Servers (Web-1, Web-2, Web-3)**:**
 - Host the application
 - Web-3 acts as backup for failover
 - Monitored by health check scripts
- ****Health Check Automation**:**
 - Monitors backend servers every 30 seconds
 - Logs server status to `~/backend_health.log`
 - Alerts if server is down
 - Can restart Apache automatically

Prerequisites

Required Tools

- AWS CLI
- Terraform
- Nginx
- OpenSSL
- curl

AWS Credentials Setup

1. Configure AWS CLI:

```
bash
aws configure
```

You will be prompted to enter:

- AWS Access Key ID
- AWS Secret Access Key
- Default region
- Output formatAWS Access Key ID
- AWS Secret Access Key

2. SSH Key Setup

-Generate a key pair (if not already created):

```
bash
ssh-keygen -t rsa -b 2048 -f ~/.ssh/lab_key
Add the public key to your AWS EC2 instances.
```

3. Deployment Instructions

- Step-by-Step Guide
- Clone the project repository.

-Update variables.tf with desired values (AMI IDs, instance types, backend IPs).

4. Initialize Terraform:

```
bash
terraform init
```

5. Plan the deployment:

```
bash
terraform plan
```

6. Apply deployment:

```
bash
terraform apply
```

-Verify EC2 instances, security groups, and load balancer in AWS console.

7. Configuration Guide

Update Backend IPs

-Edit Nginx upstream block:

```
**nginx
upstream backend_servers {
    server 10.0.10.16:80;
    server 10.0.10.33:80;
    server 10.0.10.199:80 backup;
}
```

```

-Custom Error Pages: 404, 502, 503 defined in error_page directives.
-Security Headers: HSTS, X-Frame-Options, X-Content-Type-Options, CSP, X-XSS-Protection.

8. Testing Procedures
-Test SSL/TLS:

bash
openssl s_client -connect 13.223.93.99:80:443 -showcerts

-Test security headers:

bash
curl -I -k https://13.23.93.99:80

-Test custom error pages:

bash
curl -I -k https://13.23.93.99:80

-Test rate limiting:

bash
for i in {1..30}; do curl -k -s -o /dev/null -w "%{http_code}\n" https://13.23.93.99//; done

9. Architecture Details
-Network Topology
-VPC with public and private subnets
-Nginx in public subnet
-web servers in private subnets
-Security groups control access to ports 80/443 and SSH

10. Security Groups Explanation
-Nginx SG: Allow 80/443 from Internet, allow 22 from admin
-Backend SG: Allow 80 from Nginx SG only

11. Load Balancing Strategy

```

```

11. Load Balancing Strategy

-Round-robin load balancing
-Backup server used if primary fails

***Troubleshooting***
->Common Issues and Solutions
->502 Bad Gateway: Check upstream servers, restart backends if needed
->403 / 404 Errors: Verify Nginx root and error_page config
->Rate limiting not working: Ensure correct limit_req_zone and limit_req placement

12. Log Locations

-Nginx access log: /var/log/nginx/access.log
-Nginx error log: /var/log/nginx/error.log
-Backend health log: ~/backend_health.log

```

```

13. Debug Commands
-Test Nginx config:

bash
sudo nginx -t

-Reload Nginx:

bash
sudo systemctl reload nginx

-View logs in real-time:

bash
sudo tail -f /var/log/nginx/error.log
sudo tail -f /var/log/nginx/access.log

***END***

```

6.2 Infrastructure Cleanup

- terraform_destroy_prompt:

```
PS C:\Users\Musfi\OneDrive\Desktop\cloud-computing\Assignment2> & "D:\Downloads\Downloads\terraform_1.14.3_windows_amd64\terraform.exe" destroy
```

- terraform_destroy_complete:

```
module.networking.aws_internet_gateway.this: Destruction complete after 56s
module.backend_servers["web-1"].aws_instance.this: Destruction complete after 1m9s
module.networking.aws_subnet.public: Destroying... [id=subnet-0bd58ec5b237833ba]
module.backend_servers["web-1"].aws_key_pair.this: Destroying... [id=prod-web-1-1-key]
module.security.aws_security_group.backend_sg: Destroying... [id=sg-08d38879be7c412db]
module.backend_servers["web-1"].aws_key_pair.this: Destruction complete after 1s
module.networking.aws_subnet.public: Destruction complete after 2s
module.security.aws_security_group.backend_sg: Destruction complete after 2s
module.security.aws_security_group.nginx_sg: Destroying... [id=sg-056ee26d46110a861]
module.security.aws_security_group.nginx_sg: Destruction complete after 2s
module.networking.aws_vpc.this: Destroying... [id=vpc-0ce419c111910bce0]
module.networking.aws_vpc.this: Destruction complete after 2s
```


Destroy complete! Resources: 15 destroyed.

```
PS C:\Users\Musfi\OneDrive\Desktop\cloud-computing\Assignment2>
```

```
PS C:\Users\Musfi\OneDrive\Desktop\cloud-computing\Assignment2> cat .\terraform.tfstate
{
  "version": 4,
  "terraform_version": "1.14.3",
  "serial": 79,
  "lineage": "545efb6b-865e-22f5-c200-1f009c3be2b8",
  "outputs": {},
  "resources": [],
  "check_results": null
}
```

- aws_instances_destroyed:

-



4. Testing Results

4.1 Load Balancing Validation

Traffic was successfully shared across multiple backend servers. Server responses and logs confirmed that requests were rotating correctly between available instances.

4.2 Caching Efficiency

Nginx caching improved performance by serving repeated requests faster and reducing the number of requests sent to backend servers.

4.3 High Availability Verification

When one or more primary web servers were stopped, the system continued working without interruption by forwarding traffic to the backup server.

4.4 Security Verification

- HTTPS connections were enforced
- Security headers were properly applied
- Direct access to backend servers was restricted

5. Challenges & Solutions

Challenges Faced

- Managing Terraform state files correctly
- Uploading large numbers of screenshots to GitHub
- Writing and debugging complex Nginx configurations
- Configuring AWS security groups accurately

How These Issues Were Solved

- Used structured and modular Terraform files
- Excluded unnecessary files using .gitignore
- Tested Nginx configurations step-by-step before deployment
- Carefully reviewed and validated security group rules

Key Lessons Learned

- Automation simplifies infrastructure management
- Modular design improves clarity and reusability
- Security planning is critical in cloud deployments

6. Conclusion

This assignment successfully demonstrated the deployment of a secure, scalable, and highly available cloud infrastructure using Terraform and Nginx. Practical experience was gained in cloud networking, infrastructure automation, load balancing, and system administration.

7. Appendices

Appendix A: Code Listings

- All Terraform configuration files (main.tf, variables.tf, outputs.tf, locals.tf)
- All module files (networking/, security/, webserver/)
- Server scripts (nginx-setup.sh, apache-setup.sh)

Appendix B: Configuration Files

- Example terraform.tfvars file
- .gitignore file

Appendix C: Additional Screenshots

- Screenshots for each part of the assignment.
- Screenshots of Nginx configuration, SSL certificates, logs, and Terraform outputs