

# Introduction to Music Processing


**Hierarchical Models** 

Metrical Grid and Rhythm Grammars


Dr Robert Lieck <a href="mailto:robert.lieck@durham.ac.uk">robert.lieck@durham.ac.uk</a>

## **Computational Models of Music**

- Sequential Models (n-gram and (hidden) Markov)
  - Look at music <u>horizontally</u> (left-to-right)
  - Focus on transitions



- Hierarchical Models (context-free grammars)
  - Look at music <u>vertically</u> (bottom-up/top-down)
  - Focus on <u>abstraction</u>





## Music as a Hierarchy

## Prélude No. 1 in C Major

from "Das Wohltemperierte Klavier" Book I BWV 846

Johann Sebastian Bach (1685 - 1750)




University

#### **Metrical Grid**

#### **ᢀ** How is time organised in music?


- Any time interval can be repeatedly split up into two (or more) parts.
- This creates a hierarchical temporal structure: the metrical grid.
- The metrical weight of an event at time t corresponds to the number of possible ways it can be generated.



#### **Metrical Grid**

#### **©** Generating Weights Top-Down


- Start with a time interval T and split it up recursively  $(T \rightarrow T T)$ .
- Count the number of times an interval was split.
- Instead of splitting, we could have created an even.
  - $\rightarrow$  #splits + 1 = #opportunities (to create an event)  $\approx w_{max}$  depth (where event can be first created)



## Metrical Grid: Rhythm versus Meter

#### © How is time organised in music?

- The metrical grid is the "canvas" that rhythms are "painted" on.
- Not every position of the metrical grid is filled and/or the different events have different importance (e.g. when does something new happen?)
- How do we generate the actual events in a rhythm?



#### Metrical Grid: Probabilistic Rules

#### \* This can be modelled with a set of probabilistic rules!

- Three rules that can be applied to a time interval T.
- Probability of generating an even at the beginning of T:


$$ar{p} = p_b + p_s \, ar{p} = rac{p_b}{1 - p_s} = rac{p_b}{p_b + p_r}$$


Probability of generating an event at depth d (or deeper):

$$ar{p}_d = p_s^d \, ar{p} = p_s^d \, rac{p_b}{p_b + p_r}$$

Metrical weight corresponds to neg-log-likelihood:

$$egin{aligned} w_d := w_0 - d & \Rightarrow ar{p}_d = p_s^{w_0 - w_d} \, rac{p_b}{p_b + p_r} \ & \Rightarrow \, \log ar{p}_d \propto w_d + const. \end{aligned}$$






· log p

Play with the interactive desmos visualisation

## Metrical Grid: Empirical Data

Empirical distribution of note onsets in a corpus of 1537 Germanic folksongs in 4/4 meter.



Huron D, Ommen A (2006) An empirical study of syncopation in American popular music, 1890-1939. Music Theory Spectrum 28:211-231



## **Metrical Grid:** Examples

University

#### C Major Prelude (JSB) https://www.youtube.com/watch?v=frxT2qB1POQ



#### Elephant's Foot (Maceo Parker) https://youtu.be/PcW75olJSVM?si=UIX-4DA9rAkbZ9eZ&t=20




#### **Metrical Grid:** Syncopation

(irregular/off-beat events)


- Need to differentiate between real and conceptual (or expected) location of events.
- Three more "time stealing" rules to account for syncopation:
  - shift (←<sub>s</sub>): Shift an existing event to an earlier position with smaller metrical weight (the event keeps its original weight).
  - preparation (←<sub>p</sub>): For an existing event, generate an additional event at an earlier position with smaller metrical weight (the new event has a smaller weight).
  - follow-up (→<sub>F</sub>): For an existing event, generate an additional event at a later position with smaller metrical weight (the new event has a smaller weight).








## **Metrical Grid:** Analysis






## **Metrical Grid:** Analysis





## **Metrical Grid:** Analysis





#### References

- 1) Lerdahl F, Jackendoff R (1983) A generative theory of tonal music. MIT press
- 2) Goodman J (1999) Semiring parsing. Computational Linguistics 25:573–605
- Huron D, Ommen A (2006) An empirical study of syncopation in American popular music, 1890–1939. Music Theory Spectrum 28:211–231
- 4) Grune D, Jacobs CJ (2007) Parsing techniques. Monographs in Computer Science Springer
- 5) Rohrmeier M (2011) Towards a generative syntax of tonal harmony. Journal of Mathematics and Music 5:35–53. https://doi.org/10.1080/17459737.2011.573676
- 6) Rohrmeier M (2020) Towards a formalisation of musical rhythm. In: Proceedings of the 21st Int. Society for Music Information Retrieval Conf
- 7) Rohrmeier M (2020) The Syntax of Jazz Harmony: Diatonic Tonality, Phrase Structure, and Form. Music Theory and Analysis (MTA) 7:1–63. https://doi.org/10.11116/MTA.7.1.1
- 8) Rohrmeier M, Moss FC (2021) A formal model of extended tonal harmony. In: Proceedings of the 22nd International Society for Music Information Retrieval Conference. pp 569–578
- 9) Lieck R, Rohrmeier M (2021) Recursive Bayesian Networks: Generalising and Unifying Probabilistic Context-Free Grammars and Dynamic Bayesian Networks. In: Advances in Neural Information Processing Systems 34 (NeurIPS 2021)

