ARCHON — 100% Project Completion Roadmap

Phase-by-Phase Build Plan + Antigravity Prompts

> **Project:** ARCHON — The Engineering Memory Engine
> **Hackathon:** hackFront India 2026
> **Track:** T1 — AI and Developer Tools
> **Problem:** T1.1 — "Why The Code Is Like This"
> **Goal:** Build a complete, evidence-first repository intelligence product and finish the hackathon prototype in controlled, testable phases.

How to Use This File

Do **not** ask Antigravity to rebuild the whole project from scratch in every phase.

For every phase:

1. Open the existing ARCHON project in Antigravity.
2. Make sure the previous phase works.
3. Copy the **Antigravity Prompt** for the next phase.
4. Let Antigravity inspect the existing repository before editing.
5. Run the commands/tests it provides.
6. Fix failures before moving forward.
7. Commit the completed phase to Git.
8. Mark the phase complete only when its **Definition of Done** is satisfied.

The prompts deliberately tell Antigravity to **continue the existing project**, preserve working features, test its work, and report anything that remains incomplete.

Important: "100% complete" in this roadmap means every agreed project requirement and Definition of Done has been implemented and verified. It does not mean the software is mathematically bug-free or that unsupported capabilities should be claimed.

Final Product Vision

ARCHON should allow a developer to:

```
Select Repository
       ↓
Validate Repository
       ↓
Index Source + Git History + Tests
       ↓
Build Repository Intelligence Model
       ↓
Build / Query Knowledge Graph
       ↓
Ask Engineering Question
       ↓
Retrieve Relevant Evidence
       ↓
Analyze Evidence
       ↓
Generate Evidence-Grounded Explanation
       ↓
Show Facts / Inferences / Unknowns
       ↓
Show Source + Commit + Test Evidence
       ↓
Run Change-Impact Analysis
       ↓
Display Relationships in Interactive Graph
       ↓
Allow Developer to Verify Everything
```

The central rule is:

> **No evidence → no confident claim.**

ARCHON must never invent commits, source references, tests, relationships, confidence values, or reasons for a design decision.

PHASE 0 — Audit, Freeze Baseline, and Project Specification

Objective

Understand exactly what already exists before changing architecture.

What Will Be There

At the end of Phase 0:

```
ARCHON/
├── existing working application
├── README.md
├── PROJECT_SPEC.md
├── ARCHITECTURE.md
├── MIGRATION_PLAN.md
├── LIMITATIONS.md
└── docs/
    └── current-state.md
```

How It Will Work

Antigravity must inspect:

- Current folders and files
- Streamlit application
- Repository validation
- Git search
- Source scanner
- Secret redaction
- Caller/test discovery

- Existing tests
- Dependencies
- Broken/incomplete code
- Demo data versus real data

It must document what is:

- Working
- Partially working
- Missing
- Mock/demo-only
- Planned

Do not delete the Streamlit prototype.

Definition of Done

- Existing application still launches.
- Existing tests are executed.
- Current capabilities are documented honestly.
- `PROJECT_SPEC.md` exists.
- `ARCHITECTURE.md` exists.
- `MIGRATION_PLAN.md` exists.
- Known limitations are documented.
- No working feature has been destroyed.

Antigravity Prompt

```
# PHASE 0 — ARCHON AUDIT AND BASELINE

You are working inside the EXISTING ARCHON repository.

Do not rebuild the project from scratch.
Do not delete the existing Streamlit prototype.
Do not claim anything is implemented until you inspect and verify it.

Your task is to complete Phase 0: Audit, Baseline, and Specification.

1. Inspect the complete repository structure.
2. Identify:
   - working features
   - incomplete features
   - mock/demo-only features
   - dead code
   - security-sensitive areas
   - current tests
   - current dependencies
3. Run the existing tests and record the actual results.
4. Determine how the current Streamlit application starts.
5. Verify the current repository validation, Git search, source
scanning,
   secret redaction, caller detection, and test-reference detection.
6. Create or update:
   - PROJECT_SPEC.md
   - ARCHITECTURE.md
   - MIGRATION_PLAN.md
   - LIMITATIONS.md
   - docs/current-state.md
7. PROJECT_SPEC.md must answer:
   - What problem are we solving?
   - Who is the user?
   - What is the primary workflow?
   - What inputs are supported?
   - What evidence can ARCHON use?
   - What must ARCHON never claim without evidence?
```

```
   - What is explicitly out of scope?
   - What defines a successful hackathon prototype?
8. Preserve all currently working behavior.
9. Fix only small baseline issues needed to make tests/app run.
10. Do not begin the Next.js/Django migration yet.

Before finishing:
- rerun tests
- verify the current app launches
- list every changed file
- list test commands and actual results
- list remaining known problems

Stop only when Phase 0 Definition of Done is satisfied.
```

PHASE 1 — Repository Intelligence Core

Objective

Make ARCHON reliably understand a real local repository before adding AI.

What Will Be There

```
Repository
   ├── Files
   ├── Symbols
   ├── Imports
   ├── Callers
   ├── Tests
   ├── Commits
   ├── Diffs
   └── Evidence Records
```

ARCHON should create normalized evidence objects instead of loose strings.

Example:

```
{
  "type": "source",
  "repository_id": "...",
  "file": "app/services/repository.py",
  "start_line": 41,
  "end_line": 58,
  "symbol": "RepositoryManager",
  "excerpt": "...",
  "provenance": "static_source_scan"
}
```

How It Will Work

- Validate repository path.
- Detect Git root.
- Detect current branch.
- Scan bounded supported source files.
- Parse Python using AST.
- Find symbols/imports/references.
- Search Git commits and diffs.
- Find test references.
- Find likely callers/dependencies.
- Normalize findings into evidence records.
- Clearly distinguish observed relationships from inferred relationships.

Definition of Done

A real repository can be analyzed without executing its code.

ARCHON can return actual:

- Files
- Symbols
- Source line ranges
- Git commits when available
- Test references when available

- Callers/references when detectable
- Evidence records

Missing evidence produces an honest empty/unknown state.

Antigravity Prompt

```
# PHASE 1 — REPOSITORY INTELLIGENCE CORE

Continue the EXISTING ARCHON project after Phase 0.

First read:
- PROJECT_SPEC.md
- ARCHITECTURE.md
- MIGRATION_PLAN.md
- LIMITATIONS.md

Do not remove working features.

Build a production-quality repository intelligence core.

Requirements:

1. Repository validation
   - accept a local repository path
   - resolve canonical path
   - verify directory exists
   - detect Git root
   - detect branch
   - protect against traversal
   - handle symlinks safely
   - never execute repository code

2. Bounded source scanning
   - configurable maximum file size
   - supported extension allowlist
   - exclude .git, node_modules, build output, virtualenvs,
     .env, private keys, generated/vendor folders
   - handle unreadable/binary files safely

3. Python analysis
   - use Python AST
   - extract modules, classes, functions, methods, imports
   - capture file and line information
```

```
   - detect references/callers where statically supportable
   - label uncertain relationships as inferred
   - never claim a complete call graph

4. Git archaeology
   - use safe Git CLI subprocess calls
   - collect relevant commits
   - commit hash
   - author metadata only where needed
   - timestamp
   - subject
   - changed files
   - bounded diff excerpts
   - support symbol/text searches
   - gracefully handle no Git history

5. Test discovery
   - locate likely test files
   - find symbol/module references
   - do not claim a symbol is untested merely because static search
found nothing

6. Evidence model
   Create structured evidence records with stable IDs and provenance.

   Evidence types should include where applicable:
   - source
   - git_commit
   - git_diff
   - test_reference
   - import_relationship
   - caller_relationship
   - documentation

7. Security
   - preserve/improve secret redaction
   - never log secret values
```

```
   - never run repository scripts
   - never install target dependencies

8. Tests
   Add tests for:
   - valid repo
   - invalid repo
   - path traversal
   - existing symbol
   - missing symbol
   - symbol with Git history
   - symbol without matching Git history
   - test reference found
   - no test reference
   - oversized file
   - excluded secret file
   - malformed/unreadable file

9. Real validation
   Use a real local repository available in the development environment.
   Identify at least 3 candidate symbols.
   Select one symbol with the strongest available combination of source,
   history, callers, and/or tests.
   Do not fabricate data if no candidate has all evidence types.

Before finishing:
- run all tests
- show actual test results
- provide one real investigation output
- verify displayed source lines against the file
- verify displayed commit hashes using Git
- update README and LIMITATIONS
- list changed files

Do not start Phase 2 until Phase 1 is verified.
```

PHASE 2 — Django REST Backend

Objective

Turn the repository intelligence engine into a clean backend service.

What Will Be There

```
Frontend / Clients
        ↓
Django REST API
        ↓
Investigation Services
        ↓
Repository Intelligence
```

Planned API groups:

```
/api/v1/health/
/api/v1/repositories/validate/
/api/v1/repositories/index/
/api/v1/repositories/{id}/symbols/
/api/v1/investigations/
/api/v1/investigations/{id}/
/api/v1/investigations/{id}/evidence/
/api/v1/impact/
/api/v1/graph/
```

Only implement endpoints backed by real functionality.

How It Will Work

Django will orchestrate the existing intelligence modules rather than duplicate them.

SQLite can store application metadata such as:

- Repository registrations
- Investigations

- Evidence metadata
- Evaluation runs

Raw repository code should not be unnecessarily copied into the database.

Definition of Done

- Django launches successfully.
- Versioned API exists.
- Input validation exists.
- API errors are structured.
- Real repository analysis works through the API.
- Tests cover endpoints.
- No fake endpoints return fake success.

Antigravity Prompt

```
# PHASE 2 — DJANGO REST BACKEND

Continue ARCHON from the verified Phase 1 state.

Do not rewrite the repository intelligence engine.
Wrap the verified core behind a maintainable Django REST Framework API.

Requirements:

1. Create a clean backend architecture using:
   - Python
   - Django
   - Django REST Framework
   - SQLite for local metadata
   - pytest / pytest-django

2. Keep repository analysis in service/domain modules rather than views.

3. Add versioned API routes under /api/v1/.

Implement only endpoints supported by real functionality:

- GET  /api/v1/health/
- POST /api/v1/repositories/validate/
- POST /api/v1/repositories/index/
- GET  /api/v1/repositories/{id}/symbols/
- POST /api/v1/investigations/
- GET  /api/v1/investigations/{id}/
- GET  /api/v1/investigations/{id}/evidence/
- POST /api/v1/impact/
- GET/POST graph endpoints only if Phase 3 graph functionality exists
later

4. Use serializers/request schemas and strict validation.

5. Return structured errors:
   - invalid path
```

```
   - repository not found
   - unsupported repository
   - Git unavailable
   - evidence not found
   - processing error

6. Add reasonable processing limits and timeouts.

7. Do not expose:
   - arbitrary filesystem contents
   - secrets
   - unrestricted file paths
   - stack traces in production responses

8. Persist only useful metadata.
Do not duplicate entire source repositories into SQLite.

9. Add API tests for success and failure paths.

10. Add API documentation to README.

11. Keep Streamlit working during migration.

Before finishing:
- run backend tests
- start Django development server
- call each implemented endpoint with a real request
- verify returned evidence against the repository
- list any planned endpoint that was intentionally not implemented
- update ARCHITECTURE.md
- list changed files and actual test results

Stop when Phase 2 is fully verified.
```

PHASE 3 — Neo4j Engineering Knowledge Graph

Objective

Create a real graph representing relationships in the repository.

What Will Be There

Node Types


```
Repository
File
Symbol
Commit
Test
Evidence
Investigation
```

Relationship Types

```
CONTAINS
DEFINES
IMPORTS
CALLS
MODIFIES
TESTS
DEPENDS_ON
SUPPORTS
CONTRADICTS
INVESTIGATED
```

How It Will Work

Example:



Every important relationship needs provenance.

Relationships derived directly from parsing can be marked observed/static.

Relationships derived heuristically must be marked inferred.

Definition of Done

- Neo4j connects successfully when configured.
- Constraints/indexes exist.
- Real repository data is ingested.
- Re-indexing does not duplicate everything.
- At least several useful Cypher queries work.
- Graph failure does not destroy basic repository investigation.
- UI/API must not pretend graph data is live when Neo4j is unavailable.

Antigravity Prompt

```
# PHASE 3 — NEO4J ENGINEERING KNOWLEDGE GRAPH

Continue ARCHON from verified Phases 0-2.

Add Neo4j as a REAL repository knowledge graph.
Do not create decorative or fabricated graph data.

Use:
- official Neo4j Python driver
- parameterized Cypher
- environment variables for credentials

Model these nodes where supported:
- Repository
- File
- Symbol
- Commit
- Test
- Evidence
- Investigation

Model these relationships where evidence supports them:
- CONTAINS
- DEFINES
- IMPORTS
- CALLS
- MODIFIES
- TESTS
- DEPENDS_ON
- SUPPORTS
- CONTRADICTS
- INVESTIGATED

Requirements:

1. Define stable IDs.
2. Add uniqueness constraints/indexes.
```

```
3. Store provenance on important nodes/relationships.
4. Label relationship origin:
   - observed
   - static_analysis
   - inferred
5. Never convert a heuristic into a confirmed fact.
6. Implement idempotent repository ingestion.
7. Re-indexing must update/merge rather than blindly duplicate.
8. Cleanup must be scoped to the selected repository.
9. Use bounded graph traversals.
10. Do not interpolate raw user strings into Cypher.
11. Add connection health handling.
12. If Neo4j is unavailable:
    - return an honest degraded-mode state
    - keep non-graph repository analysis usable
13. Add graph service tests where practical.
14. Add integration verification against a real repository.

Implement useful queries such as:
- files defining a symbol
- symbols referenced by a file
- commits modifying a file/symbol
- tests related to a symbol
- callers/dependents of a symbol
- evidence supporting an investigation
- bounded neighborhood around a symbol

Add documentation for:
- local Neo4j setup
- required environment variables
- schema
- reset/reindex behavior

Before finishing:
- ingest a real repository
- run real Cypher queries
- show actual node/relationship counts from that repository
```

```
- manually verify several returned relationships
- rerun tests
- update ARCHITECTURE.md and README
- clearly list unsupported relationship types/languages

Do not invent graph metrics.
Stop only when the graph is genuinely usable.
```

PHASE 4 — Evidence-First Investigation Engine / GraphRAG

Objective

Turn repository evidence into trustworthy engineering explanations.

What Will Be There

```
Question
   ↓
Intent / Symbol Extraction
   ↓
Repository Retrieval
   ↓
Git Retrieval
   ↓
Graph Retrieval
   ↓
Tests / Dependency Retrieval
   ↓
Evidence Ranking
   ↓
Contradiction Check
   ↓
Bounded Context
   ↓
Optional LLM Explanation
   ↓
Citation Validation
   ↓
Final Findings
```

How It Will Work

The LLM is not the source of truth.

The repository is the source of evidence.

ARCHON should classify statements as:

```
FACT
INFERENCE
HYPOTHESIS
UNKNOWN
```

Example output:

```
Finding:
The retry mechanism appears to have been introduced to handle transient
failures.

Classification:
INFERENCE

Supporting evidence:
- services/client.py:L80-L108
- commit a13f9c2
- tests/test_client.py:L31-L65

Limitations:
The commit message does not explicitly state the design rationale.
```

Definition of Done

- Retrieval works without an LLM.
- Optional LLM uses only bounded retrieved context.
- Citations are validated before display.
- Unsupported statements are removed or downgraded.
- Contradictory evidence can be surfaced.
- No fake confidence percentages.

Antigravity Prompt

```
# PHASE 4 — EVIDENCE-FIRST INVESTIGATION / GRAPHRAG

Continue ARCHON from verified Phases 0-3.

Build the central investigation pipeline.

ARCHON is NOT a generic repository chatbot.
Retrieval and evidence validation must happen before explanation
generation.

Pipeline:

Question
→ identify likely symbols/files/terms
→ retrieve source evidence
→ retrieve Git evidence
→ retrieve tests
→ retrieve callers/dependencies
→ retrieve relevant Neo4j neighborhood
→ rank evidence
→ search for contradictory evidence
→ construct bounded context
→ optionally generate structured explanation
→ validate citations
→ classify claims
→ return answer

Requirements:

1. Deterministic retrieval must work without a paid LLM API.

2. Build a provider abstraction for optional AI generation.
External AI must be disabled by default unless configured.

3. If using Neo4j GraphRAG:
   - use the official neo4j-graphrag package only where it adds real
value
```

```
   - keep a deterministic fallback
   - do not add it merely for branding

4. Structured answer model:
   - question
   - summary
   - findings[]
   - classification for each finding
   - supporting_evidence[]
   - contradicting_evidence[]
   - unknowns[]
   - limitations[]
   - suggested_verification_steps[]

5. Allowed classifications:
   - FACT
   - INFERENCE
   - HYPOTHESIS
   - UNKNOWN

6. FACT requires direct supporting evidence.

7. INFERENCE must explain what evidence it is inferred from.

8. HYPOTHESIS must never be presented as established rationale.

9. UNKNOWN must be used when repository evidence is insufficient.

10. Never fabricate:
    - commit hashes
    - line numbers
    - files
    - tests
    - graph relationships
    - authors
    - rationale
    - confidence percentages
```

```
11. Citation validator:
    - source file exists
    - cited line range is valid
    - commit exists
    - test reference exists where claimed
    - evidence belongs to selected repository

12. If citation validation fails, remove/downgrade the claim.

13. Add tests for:
    - strong evidence
    - weak evidence
    - zero evidence
    - conflicting evidence
    - invalid citation
    - missing commit
    - renamed/moved file where supportable
    - LLM disabled
    - Neo4j unavailable

14. Add at least 5 manually verified evaluation questions for the demo repository.

Before finishing:
- run all tests
- run the fixed evaluation questions
- manually inspect citations
- show which answers are FACT/INFERENCE/HYPOTHESIS/UNKNOWN
- update README and LIMITATIONS
- report real failures instead of hiding them

Stop only when evidence-first investigation works end-to-end.
```

PHASE 5 — Change Impact Analysis

Objective

Answer:

> “What might be affected if I change this code?”

without pretending to guarantee safety.

What Will Be There

```
Selected Symbol
      ↓
Direct Callers
      ↓
Imports
      ↓
Dependencies
      ↓
Related Tests
      ↓
Recent History
      ↓
Bounded Graph Traversal
      ↓
Potential Impact Report
```

How It Will Work

ARCHON can show:

- Directly related files
- Callers
- Imports
- Dependent modules
- Relevant tests
- Relevant commits
- Suggested verification steps

It should use wording such as:

> “Potentially affected”

not:

> “Changing this is guaranteed safe.”

Definition of Done

Real symbol → real dependency evidence → bounded impact report → tests/verification suggestions.

Antigravity Prompt

```
# PHASE 5 — CHANGE IMPACT ANALYSIS

Continue the verified ARCHON project.

Implement evidence-backed CHANGE IMPACT ANALYSIS.

This feature is advisory only.
Never guarantee that a change is safe.

Input:
- repository
- file/symbol
- optional proposed change description

Analyze where available:
- direct callers
- imports
- reverse imports
- dependency relationships
- related tests
- files modified together in relevant history
- bounded Neo4j neighborhood
- relevant evidence records

Output structure:
- target
- directly_affected[]
- potentially_affected[]
- relevant_tests[]
- relevant_history[]
- evidence[]
- unknowns[]
- suggested_verification_steps[]
- limitations[]

Every affected component must include the reason it was included.
```

```
Distinguish:
- observed direct relationship
- static-analysis relationship
- heuristic/inferred relationship

Do not:
- execute repository code
- edit the user's repository
- deploy anything
- claim complete dependency coverage
- claim safety guarantees

Add tests for:
- symbol with callers
- isolated symbol
- symbol with tests
- symbol without discovered tests
- graph unavailable
- missing symbol
- unsupported language

Expose this through the existing service/API architecture.

Before finishing:
- demonstrate on a real symbol
- manually verify several relationships
- verify evidence links
- run tests
- document limitations
- update API docs

Stop only when impact analysis produces a useful, evidence-backed
report.
```


PHASE 6 — Next.js Product Interface

Objective

Replace the prototype-style experience with a polished engineering workspace.

What Will Be There

Main interface:



Pages/workspaces:

- Command Center
- Repository Explorer
- Investigation Workspace
- Interactive Graph
- Evidence Inspector
- Evaluation & History

How It Will Work

Next.js communicates with Django.

No fake dashboard statistics.

No button should appear functional if it does nothing.

Definition of Done

A teammate/judge can complete the entire primary workflow from the browser.

Antigravity Prompt

```
# PHASE 6 — NEXT.JS ENGINEERING WORKSPACE

Continue ARCHON after the backend investigation workflow is verified.

Build the product-quality frontend using:
- Next.js App Router
- React
- TypeScript strict mode
- Tailwind CSS
- shadcn/ui
- Lucide icons
- React Flow for graph visualization
- TanStack Query where useful
- Zod for client-side schema validation where useful

Do not build a generic chatbot UI.

Design a premium dark engineering intelligence workspace.

Primary layout:
- top repository/context bar
- left Repository Explorer
- center Investigation Workspace
- right Evidence Inspector
- expandable/bottom Interactive Graph

Required experiences:

1. Command Center
   - repository selection/connection
   - repository validation status
   - branch
   - indexing state
   - recent investigations
   - only real metrics

2. Repository Explorer
```

```
   - files
   - symbols
   - tests where detected
   - search/filter
   - select symbol for investigation

3. Investigation Workspace
   - focused engineering question input
   - findings
   - FACT / INFERENCE / HYPOTHESIS / UNKNOWN labels
   - supporting evidence
   - contradictory evidence
   - limitations
   - change-impact results

4. Evidence Inspector
   - evidence type
   - file
   - line range
   - source excerpt
   - commit metadata
   - test reference
   - provenance
   - verification state

5. Interactive Graph
   - real Neo4j-derived data only
   - nodes for actual repository entities
   - relationship labels
   - click node to inspect
   - bounded neighborhood expansion
   - loading/error/Neo4j unavailable states

6. Evaluation & History
   - real completed investigations
   - actual evaluation results only
   - no fake percentages
```

```
UX requirements:
- responsive enough for laptop demo
- keyboard-accessible important controls
- loading states
- empty states
- error states
- no dead buttons
- no placeholder fake analytics
- clear distinction between evidence and AI interpretation

Integration:
- connect to Django REST API
- typed API layer
- centralized error handling
- environment-based backend URL

Preserve Streamlit until this frontend completes the primary workflow.

Testing:
- component/unit tests where valuable
- at least one end-to-end happy path
- error-state verification

Before finishing:
- run frontend build
- fix TypeScript errors
- run tests
- test against real Django backend
- complete a real investigation from the browser
- verify every visible metric is real
- list incomplete UI controls, if any

Stop only when the browser can perform the full primary workflow.
```

PHASE 7 — Evaluation, Observability, and Reliability

Objective

Prove ARCHON works instead of relying only on presentation.

What Will Be There

Evaluation dataset:

```
Question
Expected Evidence
Expected Classification
Observed Result
Citation Valid?
Supported?
Notes
```

Metrics can include:

- Citation validity
- Evidence retrieval precision
- Answer support rate
- Relevant evidence coverage
- Unsupported claims detected
- Investigation latency
- Failure rate

How It Will Work

Create a small manually verified evaluation set for a real repository.

Do not invent benchmark results.

Definition of Done

The evaluation page and documentation show real test data and actual sample counts.

Antigravity Prompt

```
# PHASE 7 — EVALUATION, OBSERVABILITY, RELIABILITY

Continue the verified ARCHON project.

Create a real evaluation framework for the hackathon demo.

Do NOT invent benchmark values.

1. Create a fixed evaluation dataset for at least 5-10 manually verified
   questions against the selected demo repository.

For each question record:
- question
- target symbol/file
- expected relevant evidence
- expected claim classification where practical
- notes from manual verification

2. Implement evaluation measures with precise definitions:

Citation Validity:
Does every displayed citation resolve to a real artifact?

Evidence Retrieval Precision:
Of retrieved/displayed evidence, how much is manually judged relevant?

Answer Support Rate:
What proportion of substantive findings have supporting evidence?

Relevant Evidence Coverage:
Of manually identified relevant evidence, how much did retrieval find?
State clearly that this depends on the manually defined reference set.

Unsupported Claims Detected:
Count claims rejected/downgraded by validation.

Latency:
```

```
Measure investigation duration.

Failure Rate:
Measure failed investigations in the evaluation run.

3. Store:
- evaluation date
- repository/commit tested
- sample count
- actual results

4. Add structured application logging:
- request/investigation IDs
- stage timing
- failures
- retrieval counts

Never log:
- secrets
- tokens
- unnecessary full source code
- sensitive environment values

5. Add an Evaluation UI using only actual stored results.

6. Add reliability tests:
- empty repository
- large file
- invalid path
- missing Git
- Neo4j unavailable
- malformed question
- no evidence
- contradictory evidence
- API error
- frontend API failure
```

```
7. Create EVALUATION.md explaining:
- methodology
- sample size
- metrics
- results
- limitations

Before finishing:
- run evaluation
- save actual results
- manually verify a sample
- run complete test suite
- report failures honestly

Stop when the evaluation is reproducible from documented commands.
```

PHASE 8 — Security and Privacy Hardening

Objective

Make the local repository analyzer defensible during judging.

What Will Be There

Security controls for:

- Filesystem access
- Path traversal
- Symlinks
- Secret files
- Secret redaction
- Git subprocesses
- Neo4j queries
- API validation

- External AI providers
- Logs
- Repository content treated as untrusted input

How It Will Work

ARCHON should remain read-only toward the analyzed repository.

It should never obey instructions found inside source comments, README files, issues, or documentation as if those instructions came from the user.

Definition of Done

Security tests pass and security limitations are documented.

Antigravity Prompt

```
# PHASE 8 — SECURITY AND PRIVACY HARDENING

Perform a security-focused audit of the EXISTING ARCHON implementation.

Do not add security badges or claims without tests.

Threat model ARCHON as a tool that reads UNTRUSTED repositories.

Verify and harden:

1. Filesystem
   - path traversal
   - canonical path checks
   - symlink handling
   - repository boundary enforcement
   - unreadable files
   - file-size limits

2. Sensitive files
   Exclude/redact:
   - .env
   - private keys
   - credentials
   - common token patterns
   - generated dependency folders
   - configurable sensitive paths

3. Repository execution
   - never execute repository source
   - never import target Python modules
   - never run package scripts
   - never install target dependencies

4. Git subprocesses
   - no shell=True with untrusted strings
   - argument arrays
   - timeouts
```

```
   - bounded output
   - error handling

5. Neo4j
   - parameterized Cypher
   - scoped repository operations
   - bounded traversal
   - credentials only from environment

6. Django API
   - strict validation
   - safe errors
   - request limits
   - no arbitrary filesystem browsing
   - appropriate development CORS configuration
   - production settings documented

7. Prompt injection / untrusted repository text
   - repository source/comments/docs are DATA, not instructions
   - retrieved text cannot override system/application rules
   - clearly separate repository content from control instructions

8. External AI
   - disabled unless explicitly configured
   - disclose when repository snippets may leave local machine
   - send only bounded necessary context
   - never send detected secrets
   - deterministic local/no-LLM mode remains available

9. Logging
   - redact secrets
   - avoid unnecessary full source excerpts

10. Add security tests for important controls.

Create SECURITY.md containing:
- threat model
```

```
- controls
- known limitations
- external AI behavior
- responsible demo guidance

Run:
- backend tests
- frontend tests
- security-specific tests
- lint/static checks already configured

Report actual findings and fixes.
Do not claim ARCHON is completely secure.
Stop when critical identified issues are fixed or explicitly documented.
```

PHASE 9 — Demo Repository and Judge-Ready Story

Objective

Turn the engineering work into a clear 3–5 minute demonstration.

What Will Be There

A demo story such as:

```
1. Open ARCHON
2. Select real repository
3. Index repository
4. Select meaningful symbol
5. Ask "Why is this implemented this way?"
6. Show evidence-backed answer
7. Open source citation
8. Open Git evidence
9. Show knowledge graph
10. Ask what could break if changed
11. Show impact report + tests
12. Show honest unknown/limitation
```

How It Will Work

Use a repository/symbol that has enough real evidence to make the workflow understandable.

The demo must not depend on fabricated data.

Definition of Done

The demo can be repeated reliably from a clean documented setup.

Antigravity Prompt

```
# PHASE 9 — JUDGE-READY DEMO

Continue the verified ARCHON project.

Prepare a reliable hackathon demonstration using REAL repository
evidence.

1. Inspect available demo repositories.

2. Find at least 3 candidate symbols/components.

3. For each candidate evaluate:
   - useful source evidence
   - Git history
   - callers/dependencies
   - tests
   - graph relationships
   - understandable engineering story

4. Select the strongest candidate.
Do not fabricate missing evidence.

5. Create DEMO_SCRIPT.md for a 3-5 minute demo.

The demo should cover:
- open ARCHON
- select repository
- validate/index
- choose symbol/component
- ask a focused "why" question
- show findings and classifications
- inspect source evidence
- inspect Git evidence if available
- show graph relationships
- run change-impact analysis
- show relevant tests/verification steps
- demonstrate one honest limitation/unknown
```

```
6. Add DEMO_SETUP.md:
- prerequisites
- environment variables
- Neo4j setup
- backend start command
- frontend start command
- repository setup
- indexing steps
- expected demo path

7. Make demo startup reliable.
If useful, add safe development scripts that start ARCHON services,
but never execute the analyzed repository.

8. Create a demo fallback plan:
- what happens if Neo4j is unavailable
- what happens if optional LLM is unavailable
- deterministic evidence mode must still demonstrate value

9. Create SCREENSHOT_CHECKLIST.md.

10. Test the entire demo from beginning to end.

Before finishing:
- perform the demo workflow
- time it
- record every failure
- fix blocking failures
- ensure all demo claims are supported

Do not optimize for flashy fake features.
Optimize for a clear, credible engineering story.
```

PHASE 10 — Documentation, GitHub, and Submission Package

Objective

Make ARCHON understandable and reproducible by judges and teammates.

What Will Be There

```
README.md
PROJECT_SPEC.md
ARCHITECTURE.md
MIGRATION_PLAN.md
LIMITATIONS.md
SECURITY.md
EVALUATION.md
DEMO_SCRIPT.md
DEMO_SETUP.md
SCREENSHOT_CHECKLIST.md
LICENSE
.gitignore
.env.example
docs/
tests/
frontend/
backend/
```

How It Will Work

README should explain:

- Problem
- Solution
- Architecture
- Evidence model
- Knowledge graph

- Investigation workflow
- Installation
- Demo
- Evaluation
- Security
- Limitations
- Future roadmap

Definition of Done

A new developer can clone the project and understand how to run ARCHON from the documentation.

Antigravity Prompt

```
# PHASE 10 — DOCUMENTATION AND SUBMISSION READINESS

Perform a documentation and repository-readiness pass.

Do not change core architecture unless needed to fix a blocker.

1. Audit README.md.

Rewrite/update it to include:
- ARCHON overview
- hackathon problem
- problem statement
- target user
- key differentiator
- screenshots section placeholders/real images if present
- architecture
- repository intelligence flow
- evidence model
- Neo4j graph model
- evidence-first investigation
- change-impact analysis
- supported languages/features
- installation
- environment setup
- backend commands
- frontend commands
- Neo4j setup
- deterministic no-LLM mode
- optional AI configuration
- demo instructions
- tests
- evaluation
- security
- limitations
- roadmap

2. Verify these documents exist and match implementation:
```

```
- PROJECT_SPEC.md
- ARCHITECTURE.md
- LIMITATIONS.md
- SECURITY.md
- EVALUATION.md
- DEMO_SCRIPT.md
- DEMO_SETUP.md

3. Add/update:
- .gitignore
- .env.example with placeholders only
- LICENSE if team has selected one
- contribution/development notes if useful

4. Remove:
- secrets
- credentials
- accidental local paths
- temporary junk
- generated files that should not be committed
- obsolete fake/mock data not required for explicit demo fixtures

5. Search repository for potential credentials before submission.

6. Verify all documented commands actually work.

7. Ensure screenshots and README never present planned features as
completed.

8. Create SUBMISSION_CHECKLIST.md covering:
- public GitHub repository
- README
- source archive
- PPT/PDF
- demo video
- track/problem statement
- file-size checks
```

```
- final dashboard verification

9. Do not automatically publish secrets or push without user approval.

Before finishing:
- test setup instructions
- run tests
- run frontend production build
- verify backend startup
- verify demo
- list final documentation gaps

Stop only when repository documentation accurately reflects the product.
```

PHASE 11 — Final QA and 100% Requirement Closure

Objective

Do a complete project-wide verification and close remaining gaps.

What Will Be There

A requirement matrix:

```
Requirement | Status | Evidence | Test | Demo Step | Remaining Issue
```

Nothing should be marked complete merely because code exists.

How It Will Work

Antigravity audits the project against all previous phases.

Any incomplete requirement becomes a concrete fix task.

After fixing, tests are rerun.

Definition of Done

Every required hackathon feature is either:

- `VERIFIED COMPLETE`, or
- explicitly removed from scope/documented as unsupported.

There must be no hidden “TODO = complete” logic.

Antigravity Prompt

```
# PHASE 11 — FINAL QA AND REQUIREMENT CLOSURE

This is the final engineering verification pass for ARCHON.

Do NOT redesign the project.
Do NOT add random new features.
Do NOT mark requirements complete without evidence.

Read all project documents and inspect the actual implementation.

Create FINAL_QA.md.

Build a requirement matrix with:

Requirement
Implementation Status
Files/Components
Verification Method
Test
Demo Step
Known Limitation
Final Status

Audit every major requirement from Phases 0-10:

A. Existing prototype preservation/migration
B. Repository path validation
C. Bounded source scanning
D. Python AST analysis
E. Git archaeology
F. Test/reference discovery
G. Structured evidence records
H. Secret redaction
I. Django REST API
J. SQLite metadata
K. Neo4j graph
L. Stable graph IDs/constraints
```

```
M. Real graph queries
N. Evidence-first retrieval
O. FACT/INFERENCE/HYPOTHESIS/UNKNOWN
P. Citation validation
Q. Contradictory evidence handling
R. No-evidence behavior
S. Optional AI provider behavior
T. Deterministic no-paid-API mode
U. Change-impact analysis
V. Next.js frontend
W. Repository Explorer
X. Investigation Workspace
Y. Evidence Inspector
Z. Interactive real-data graph
AA. Evaluation framework
AB. Structured safe logging
AC. Security controls
AD. Demo workflow
AE. Documentation
AF. Tests
AG. Production frontend build
AH. Clean public GitHub readiness
AI. Submission checklist

For every item:
- inspect code
- run the relevant test
- manually verify where necessary
- mark one of:
  VERIFIED COMPLETE
  PARTIAL
  NOT IMPLEMENTED
  BLOCKED
  OUT OF SCOPE

Then:
```

```
1. Fix every realistic PARTIAL or NOT IMPLEMENTED item required for the
   agreed hackathon prototype.

2. Do not fake blocked external infrastructure.

3. If something cannot be completed, document exactly why and make the
UI
   honest about its state.

4. Run the COMPLETE test suite.

5. Run frontend production build.

6. Start backend.

7. Verify Neo4j integration if configured.

8. Perform the complete demo.

9. Test:
   - strong evidence
   - no evidence
   - invalid repository
   - missing symbol
   - Neo4j unavailable
   - optional LLM unavailable

10. Search for:
    - TODO
    - FIXME
    - placeholder
    - mock
    - fake
    - hardcoded demo values
    - secrets
    - dead buttons
    - unhandled errors
```

```
Do not blindly delete legitimate test fixtures.

11. Update FINAL_QA.md with actual final results.

12. Produce a final console summary:

ARCHON FINAL STATUS
-------------------
Backend:
Frontend:
Repository Intelligence:
Git Analysis:
Evidence Validation:
Neo4j:
Investigation Engine:
Impact Analysis:
Evaluation:
Security:
Documentation:
Demo:
Tests:
Production Build:
Known Limitations:

Only say "Hackathon Prototype Complete" if all REQUIRED items are
VERIFIED COMPLETE and the primary demo workflow succeeds.

Otherwise list exactly what remains and continue fixing required items
until no fixable required gaps remain.
```

PHASE 12 — Presentation, Demo Video, and Final Submission

Objective

Package the verified product into the hackathon submission.

What Will Be There

Presentation structure:

```
1. Problem
2. Developer pain
3. ARCHON
4. How it works
5. Evidence-first architecture
6. Live/demo workflow
7. Knowledge graph
8. Change-impact analysis
9. Evaluation
10. Security/privacy
11. Differentiation
12. Future potential
13. Team
```

How It Will Work

Only use metrics and features verified in `FINAL_QA.md`.

Definition of Done

All required submission artifacts are ready, within size limits, and manually checked against the current hackathon dashboard.

Antigravity Prompt

```
# PHASE 12 — FINAL HACKATHON PACKAGE

Use the VERIFIED ARCHON implementation and FINAL_QA.md as the source of truth.

Do not invent features, metrics, users, benchmarks, citations, or results.

Prepare the content/material needed for final submission.

Create:

1. PITCH_DECK_CONTENT.md

Recommended structure:
- Title: ARCHON — The Engineering Memory Engine
- Problem
- Why current workflow is painful
- Our solution
- Product workflow
- Architecture
- Repository intelligence
- Evidence-first reasoning
- Neo4j engineering knowledge graph
- Change-impact analysis
- Evaluation results
- Security/privacy
- Differentiation
- Demo
- Roadmap
- Team

2. VIDEO_SCRIPT.md
Create a concise demo-video script based on the verified demo.

3. FINAL_PROJECT_DESCRIPTION.md
Create:
```

- one-line description
- short description
- detailed description
- problem
- solution
- innovation
- technical architecture
- impact
- limitations
- future scope

4. JUDGE_QA.md
Prepare concise answers for likely questions:
- Why is this different from GitHub Copilot/chatbots?
- How do you prevent hallucinations?
- Where does evidence come from?
- Why Neo4j?
- What happens without an LLM?
- How is change impact calculated?
- What languages are supported?
- How do you protect private repositories?
- What are the current limitations?
- What did the team actually build during the hackathon?

5. FINAL_SUBMISSION_CHECKLIST.md

Include known submission requirements:
- selected track/problem
- PPT/PDF
- source archive
- demo video
- public GitHub repository
- README
- optional instructions
- cohort assessment archive where applicable

Clearly tell the team to recheck the CURRENT official dashboard for:

```
- deadline
- accepted formats
- size limits
- required fields

6. Create commands/instructions for producing a clean source archive
while
excluding:
- node_modules
- virtualenvs
- caches
- .git if not required
- secrets
- local databases if not needed
- generated junk

Do not submit or push anything automatically without user approval.

Cross-check every presentation claim against:
- FINAL_QA.md
- EVALUATION.md
- actual application

Flag any unsupported claim before finalizing.
```

Master Phase Order

Use this exact sequence:

```
PHASE 0
Audit + Baseline
      ↓
PHASE 1
Repository Intelligence
      ↓
PHASE 2
Django REST Backend
      ↓
PHASE 3
Neo4j Knowledge Graph
      ↓
PHASE 4
Evidence-First Investigation / GraphRAG
      ↓
PHASE 5
Change Impact Analysis
      ↓
PHASE 6
Next.js Product Interface
      ↓
PHASE 7
Evaluation + Observability
      ↓
PHASE 8
Security Hardening
      ↓
PHASE 9
Judge-Ready Demo
      ↓
PHASE 10
Documentation + Submission Readiness
      ↓
PHASE 11
Final QA + Requirement Closure
      ↓
```

```
PHASE 12
Pitch + Video + Final Package
```

Overall Completion Tracker

Phase	Deliverable	Status
0	Audit + specification	⬜
1	Repository intelligence	⬜
2	Django REST backend	⬜
3	Neo4j knowledge graph	⬜
4	Evidence-first investigation	⬜
5	Change-impact analysis	⬜
6	Next.js interface	⬜
7	Evaluation + observability	⬜
8	Security hardening	⬜
9	Judge-ready demo	⬜
10	Documentation + repository readiness	⬜
11	Final QA / requirement closure	⬜
12	Presentation + submission package	⬜

Non-Negotiable ARCHON Rules

```
1. Never fabricate evidence.

2. Never fabricate Git commits.

3. Never fabricate source citations.

4. Never call an inference a fact.

5. Never claim that "not found" means "does not exist."

6. Never claim static analysis is a complete call graph.

7. Never execute analyzed repository code.

8. Never expose secrets.

9. Never use fake dashboard metrics.

10. Never claim Neo4j/GraphRAG is working unless real queries work.

11. Never claim AI is required if deterministic evidence retrieval can
    answer the question.

12. Never claim change-impact analysis guarantees safety.

13. Every major claim shown to a judge should be verifiable.

14. Prefer one complete end-to-end workflow over ten half-built
features.

15. Do not proceed to the next phase while the current phase has
blocking
    test failures.
```

Final Definition of Project Complete

ARCHON's hackathon prototype can be considered complete when:

```
[ ] Real local repository can be selected safely
[ ] Repository can be indexed
[ ] Real source symbols can be extracted
[ ] Real Git evidence can be retrieved where it exists
[ ] Test references can be discovered where statically visible
[ ] Evidence records contain provenance
[ ] Neo4j stores real repository relationships
[ ] Real graph queries work
[ ] Engineering questions trigger evidence retrieval
[ ] Findings distinguish facts/inferences/hypotheses/unknowns
[ ] Citations are validated
[ ] Zero-evidence cases are handled honestly
[ ] Change-impact analysis returns evidence-backed potential impacts
[ ] Django API works
[ ] Next.js frontend completes the main workflow
[ ] Interactive graph uses real data
[ ] Evaluation uses manually verified questions
[ ] Security controls are tested
[ ] Optional AI failure does not destroy core evidence workflow
[ ] No fake metrics are displayed
[ ] Tests pass for required functionality
[ ] Production frontend build succeeds
[ ] Demo works from beginning to end
[ ] README accurately documents setup
[ ] Security and limitations are documented
[ ] FINAL_QA.md verifies required features
[ ] Pitch claims match actual implementation
[ ] Submission artifacts are within current official limits
```

Final Instruction to the Team

Build evidence first. Build AI second. Build presentation last.

ARCHON will stand out if a judge can click a finding, inspect the exact source or commit that supports it, see the engineering relationships around it, and watch the system openly say **“insufficient evidence”** when the repository cannot prove something.

That trustworthiness is the product.