Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 1.

Subsection 1.1: Technical Diagnostics for Module ZX-1017.
The primary telemetry carrier frequency for subsystem 1 is calibrated to 120.45 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 11.5 liters per minute. The safety interlock threshold for voltage regulator VREG-1 is set at 24.1 V.

Subsection 1.2: Standard Operating Procedure.
Inspect pressure seal GASKET-1 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1017-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 2.

Subsection 2.1: Technical Diagnostics for Module ZX-1034.
The primary telemetry carrier frequency for subsystem 2 is calibrated to 120.90 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 13.0 liters per minute. The safety interlock threshold for voltage regulator VREG-2 is set at 24.2 V.

Subsection 2.2: Standard Operating Procedure.
Inspect pressure seal GASKET-2 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1034-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 3.

Subsection 3.1: Technical Diagnostics for Module ZX-1051.
The primary telemetry carrier frequency for subsystem 3 is calibrated to 121.35 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 14.5 liters per minute. The safety interlock threshold for voltage regulator VREG-3 is set at 24.3 V.

Subsection 3.2: Standard Operating Procedure.
Inspect pressure seal GASKET-3 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1051-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 4.

Subsection 4.1: Technical Diagnostics for Module ZX-1068.
The primary telemetry carrier frequency for subsystem 4 is calibrated to 121.80 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 16.0 liters per minute. The safety interlock threshold for voltage regulator VREG-4 is set at 24.4 V.

Subsection 4.2: Standard Operating Procedure.
Inspect pressure seal GASKET-4 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1068-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 5.

Subsection 5.1: Technical Diagnostics for Module ZX-1085.
The primary telemetry carrier frequency for subsystem 5 is calibrated to 122.25 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 17.5 liters per minute. The safety interlock threshold for voltage regulator VREG-5 is set at 24.5 V.

Subsection 5.2: Standard Operating Procedure.
Inspect pressure seal GASKET-5 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1085-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 6.

Subsection 6.1: Technical Diagnostics for Module ZX-1102.
The primary telemetry carrier frequency for subsystem 6 is calibrated to 122.70 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 19.0 liters per minute. The safety interlock threshold for voltage regulator VREG-6 is set at 24.6 V.

Subsection 6.2: Standard Operating Procedure.
Inspect pressure seal GASKET-6 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1102-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 7.

Subsection 7.1: Technical Diagnostics for Module ZX-1119.
The primary telemetry carrier frequency for subsystem 7 is calibrated to 123.15 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 20.5 liters per minute. The safety interlock threshold for voltage regulator VREG-7 is set at 24.7 V.

Subsection 7.2: Standard Operating Procedure.
Inspect pressure seal GASKET-7 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1119-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 8.

Subsection 8.1: Technical Diagnostics for Module ZX-1136.
The primary telemetry carrier frequency for subsystem 8 is calibrated to 123.60 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 22.0 liters per minute. The safety interlock threshold for voltage regulator VREG-8 is set at 24.8 V.

Subsection 8.2: Standard Operating Procedure.
Inspect pressure seal GASKET-8 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1136-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 9.

Subsection 9.1: Technical Diagnostics for Module ZX-1153.
The primary telemetry carrier frequency for subsystem 9 is calibrated to 124.05 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 23.5 liters per minute. The safety interlock threshold for voltage regulator VREG-9 is set at 24.9 V.

Subsection 9.2: Standard Operating Procedure.
Inspect pressure seal GASKET-9 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1153-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 10.

Subsection 10.1: Technical Diagnostics for Module ZX-1170.
The primary telemetry carrier frequency for subsystem 10 is calibrated to 124.50 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 25.0 liters per minute. The safety interlock threshold for voltage regulator VREG-10 is set at 25.0 V.

Subsection 10.2: Standard Operating Procedure.
Inspect pressure seal GASKET-10 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1170-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 11.

Subsection 11.1: Technical Diagnostics for Module ZX-1187.
The primary telemetry carrier frequency for subsystem 11 is calibrated to 124.95 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 26.5 liters per minute. The safety interlock threshold for voltage regulator VREG-11 is set at 25.1 V.

Subsection 11.2: Standard Operating Procedure.
Inspect pressure seal GASKET-11 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1187-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 12.

Subsection 12.1: Technical Diagnostics for Module ZX-1204.
The primary telemetry carrier frequency for subsystem 12 is calibrated to 125.40 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 28.0 liters per minute. The safety interlock threshold for voltage regulator VREG-12 is set at 25.2 V.

Subsection 12.2: Standard Operating Procedure.
Inspect pressure seal GASKET-12 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1204-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 13.

Subsection 13.1: Technical Diagnostics for Module ZX-1221.
The primary telemetry carrier frequency for subsystem 13 is calibrated to 125.85 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 29.5 liters per minute. The safety interlock threshold for voltage regulator VREG-13 is set at 25.3 V.

Subsection 13.2: Standard Operating Procedure.
Inspect pressure seal GASKET-13 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1221-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 14.

Subsection 14.1: Technical Diagnostics for Module ZX-1238.
The primary telemetry carrier frequency for subsystem 14 is calibrated to 126.30 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 31.0 liters per minute. The safety interlock threshold for voltage regulator VREG-14 is set at 25.4 V.

Subsection 14.2: Standard Operating Procedure.
Inspect pressure seal GASKET-14 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1238-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 15.

Subsection 15.1: Technical Diagnostics for Module ZX-1255.
The primary telemetry carrier frequency for subsystem 15 is calibrated to 126.75 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 32.5 liters per minute. The safety interlock threshold for voltage regulator VREG-15 is set at 25.5 V.

Subsection 15.2: Standard Operating Procedure.
Inspect pressure seal GASKET-15 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1255-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 16.

Subsection 16.1: Technical Diagnostics for Module ZX-1272.
The primary telemetry carrier frequency for subsystem 16 is calibrated to 127.20 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 34.0 liters per minute. The safety interlock threshold for voltage regulator VREG-16 is set at 25.6 V.

Subsection 16.2: Standard Operating Procedure.
Inspect pressure seal GASKET-16 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1272-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 17.

Subsection 17.1: Technical Diagnostics for Module ZX-1289.
The primary telemetry carrier frequency for subsystem 17 is calibrated to 127.65 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 35.5 liters per minute. The safety interlock threshold for voltage regulator VREG-17 is set at 25.7 V.

Subsection 17.2: Standard Operating Procedure.
Inspect pressure seal GASKET-17 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1289-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 18.

Subsection 18.1: Technical Diagnostics for Module ZX-1306.
The primary telemetry carrier frequency for subsystem 18 is calibrated to 128.10 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 37.0 liters per minute. The safety interlock threshold for voltage regulator VREG-18 is set at 25.8 V.

Subsection 18.2: Standard Operating Procedure.
Inspect pressure seal GASKET-18 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1306-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 19.

Subsection 19.1: Technical Diagnostics for Module ZX-1323.
The primary telemetry carrier frequency for subsystem 19 is calibrated to 128.55 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 38.5 liters per minute. The safety interlock threshold for voltage regulator VREG-19 is set at 25.9 V.

Subsection 19.2: Standard Operating Procedure.
Inspect pressure seal GASKET-19 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1323-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 20.

Subsection 20.1: Technical Diagnostics for Module ZX-1340.
The primary telemetry carrier frequency for subsystem 20 is calibrated to 129.00 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 40.0 liters per minute. The safety interlock threshold for voltage regulator VREG-20 is set at 26.0 V.

Subsection 20.2: Standard Operating Procedure.
Inspect pressure seal GASKET-20 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1340-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 21.

Subsection 21.1: Technical Diagnostics for Module ZX-1357.
The primary telemetry carrier frequency for subsystem 21 is calibrated to 129.45 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 41.5 liters per minute. The safety interlock threshold for voltage regulator VREG-21 is set at 26.1 V.

Subsection 21.2: Standard Operating Procedure.
Inspect pressure seal GASKET-21 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1357-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 22.

Subsection 22.1: Technical Diagnostics for Module ZX-1374.
The primary telemetry carrier frequency for subsystem 22 is calibrated to 129.90 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 43.0 liters per minute. The safety interlock threshold for voltage regulator VREG-22 is set at 26.2 V.

Subsection 22.2: Standard Operating Procedure.
Inspect pressure seal GASKET-22 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1374-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 23.

Subsection 23.1: Technical Diagnostics for Module ZX-1391.
The primary telemetry carrier frequency for subsystem 23 is calibrated to 130.35 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 44.5 liters per minute. The safety interlock threshold for voltage regulator VREG-23 is set at 26.3 V.

Subsection 23.2: Standard Operating Procedure.
Inspect pressure seal GASKET-23 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1391-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 24.

Subsection 24.1: Technical Diagnostics for Module ZX-1408.
The primary telemetry carrier frequency for subsystem 24 is calibrated to 130.80 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 46.0 liters per minute. The safety interlock threshold for voltage regulator VREG-24 is set at 26.4 V.

Subsection 24.2: Standard Operating Procedure.
Inspect pressure seal GASKET-24 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1408-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 25.

Subsection 25.1: Technical Diagnostics for Module ZX-1425.
The primary telemetry carrier frequency for subsystem 25 is calibrated to 131.25 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 47.5 liters per minute. The safety interlock threshold for voltage regulator VREG-25 is set at 26.5 V.

Subsection 25.2: Standard Operating Procedure.
Inspect pressure seal GASKET-25 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1425-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 26.

Subsection 26.1: Technical Diagnostics for Module ZX-1442.
The primary telemetry carrier frequency for subsystem 26 is calibrated to 131.70 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 49.0 liters per minute. The safety interlock threshold for voltage regulator VREG-26 is set at 26.6 V.

Subsection 26.2: Standard Operating Procedure.
Inspect pressure seal GASKET-26 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1442-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 27.

Subsection 27.1: Technical Diagnostics for Module ZX-1459.
The primary telemetry carrier frequency for subsystem 27 is calibrated to 132.15 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 50.5 liters per minute. The safety interlock threshold for voltage regulator VREG-27 is set at 26.7 V.

Subsection 27.2: Standard Operating Procedure.
Inspect pressure seal GASKET-27 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1459-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 28.

Subsection 28.1: Technical Diagnostics for Module ZX-1476.
The primary telemetry carrier frequency for subsystem 28 is calibrated to 132.60 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 52.0 liters per minute. The safety interlock threshold for voltage regulator VREG-28 is set at 26.8 V.

Subsection 28.2: Standard Operating Procedure.
Inspect pressure seal GASKET-28 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1476-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 29.

Subsection 29.1: Technical Diagnostics for Module ZX-1493.
The primary telemetry carrier frequency for subsystem 29 is calibrated to 133.05 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 53.5 liters per minute. The safety interlock threshold for voltage regulator VREG-29 is set at 26.9 V.

Subsection 29.2: Standard Operating Procedure.
Inspect pressure seal GASKET-29 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1493-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 30.

Subsection 30.1: Technical Diagnostics for Module ZX-1510.
The primary telemetry carrier frequency for subsystem 30 is calibrated to 133.50 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 55.0 liters per minute. The safety interlock threshold for voltage regulator VREG-30 is set at 27.0 V.

Subsection 30.2: Standard Operating Procedure.
Inspect pressure seal GASKET-30 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1510-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 31.

Subsection 31.1: Technical Diagnostics for Module ZX-1527.
The primary telemetry carrier frequency for subsystem 31 is calibrated to 133.95 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 56.5 liters per minute. The safety interlock threshold for voltage regulator VREG-31 is set at 27.1 V.

Subsection 31.2: Standard Operating Procedure.
Inspect pressure seal GASKET-31 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1527-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 32.

Subsection 32.1: Technical Diagnostics for Module ZX-1544.
The primary telemetry carrier frequency for subsystem 32 is calibrated to 134.40 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 58.0 liters per minute. The safety interlock threshold for voltage regulator VREG-32 is set at 27.2 V.

Subsection 32.2: Standard Operating Procedure.
Inspect pressure seal GASKET-32 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1544-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 33.

Subsection 33.1: Technical Diagnostics for Module ZX-1561.
The primary telemetry carrier frequency for subsystem 33 is calibrated to 134.85 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 59.5 liters per minute. The safety interlock threshold for voltage regulator VREG-33 is set at 27.3 V.

Subsection 33.2: Standard Operating Procedure.
Inspect pressure seal GASKET-33 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1561-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 34.

Subsection 34.1: Technical Diagnostics for Module ZX-1578.
The primary telemetry carrier frequency for subsystem 34 is calibrated to 135.30 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 61.0 liters per minute. The safety interlock threshold for voltage regulator VREG-34 is set at 27.4 V.

Subsection 34.2: Standard Operating Procedure.
Inspect pressure seal GASKET-34 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1578-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 35.

Subsection 35.1: Technical Diagnostics for Module ZX-1595.
The primary telemetry carrier frequency for subsystem 35 is calibrated to 135.75 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 62.5 liters per minute. The safety interlock threshold for voltage regulator VREG-35 is set at 27.5 V.

Subsection 35.2: Standard Operating Procedure.
Inspect pressure seal GASKET-35 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1595-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 36.

Subsection 36.1: Technical Diagnostics for Module ZX-1612.
The primary telemetry carrier frequency for subsystem 36 is calibrated to 136.20 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 64.0 liters per minute. The safety interlock threshold for voltage regulator VREG-36 is set at 27.6 V.

Subsection 36.2: Standard Operating Procedure.
Inspect pressure seal GASKET-36 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1612-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 37.

Subsection 37.1: Technical Diagnostics for Module ZX-1629.
The primary telemetry carrier frequency for subsystem 37 is calibrated to 136.65 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 65.5 liters per minute. The safety interlock threshold for voltage regulator VREG-37 is set at 27.7 V.

Subsection 37.2: Standard Operating Procedure.
Inspect pressure seal GASKET-37 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1629-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 38.

Subsection 38.1: Technical Diagnostics for Module ZX-1646.
The primary telemetry carrier frequency for subsystem 38 is calibrated to 137.10 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 67.0 liters per minute. The safety interlock threshold for voltage regulator VREG-38 is set at 27.8 V.

Subsection 38.2: Standard Operating Procedure.
Inspect pressure seal GASKET-38 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1646-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 39.

Subsection 39.1: Technical Diagnostics for Module ZX-1663.
The primary telemetry carrier frequency for subsystem 39 is calibrated to 137.55 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 68.5 liters per minute. The safety interlock threshold for voltage regulator VREG-39 is set at 27.9 V.

Subsection 39.2: Standard Operating Procedure.
Inspect pressure seal GASKET-39 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1663-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 40.

Subsection 40.1: Technical Diagnostics for Module ZX-1680.
The primary telemetry carrier frequency for subsystem 40 is calibrated to 138.00 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 70.0 liters per minute. The safety interlock threshold for voltage regulator VREG-40 is set at 28.0 V.

Subsection 40.2: Standard Operating Procedure.
Inspect pressure seal GASKET-40 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1680-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 41.

Subsection 41.1: Technical Diagnostics for Module ZX-1697.
The primary telemetry carrier frequency for subsystem 41 is calibrated to 138.45 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 71.5 liters per minute. The safety interlock threshold for voltage regulator VREG-41 is set at 28.1 V.

Subsection 41.2: Standard Operating Procedure.
Inspect pressure seal GASKET-41 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1697-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 42.

Subsection 42.1: Technical Diagnostics for Module ZX-1714.
The primary telemetry carrier frequency for subsystem 42 is calibrated to 138.90 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 73.0 liters per minute. The safety interlock threshold for voltage regulator VREG-42 is set at 28.2 V.

Subsection 42.2: Standard Operating Procedure.
Inspect pressure seal GASKET-42 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1714-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 43.

Subsection 43.1: Technical Diagnostics for Module ZX-1731.
The primary telemetry carrier frequency for subsystem 43 is calibrated to 139.35 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 74.5 liters per minute. The safety interlock threshold for voltage regulator VREG-43 is set at 28.3 V.

Subsection 43.2: Standard Operating Procedure.
Inspect pressure seal GASKET-43 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1731-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 44.

Subsection 44.1: Technical Diagnostics for Module ZX-1748.
The primary telemetry carrier frequency for subsystem 44 is calibrated to 139.80 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 76.0 liters per minute. The safety interlock threshold for voltage regulator VREG-44 is set at 28.4 V.

Subsection 44.2: Standard Operating Procedure.
Inspect pressure seal GASKET-44 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1748-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 45.

Subsection 45.1: Technical Diagnostics for Module ZX-1765.
The primary telemetry carrier frequency for subsystem 45 is calibrated to 140.25 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 77.5 liters per minute. The safety interlock threshold for voltage regulator VREG-45 is set at 28.5 V.

Subsection 45.2: Standard Operating Procedure.
Inspect pressure seal GASKET-45 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1765-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 46.

Subsection 46.1: Technical Diagnostics for Module ZX-1782.
The primary telemetry carrier frequency for subsystem 46 is calibrated to 140.70 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 79.0 liters per minute. The safety interlock threshold for voltage regulator VREG-46 is set at 28.6 V.

Subsection 46.2: Standard Operating Procedure.
Inspect pressure seal GASKET-46 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1782-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 47.

Subsection 47.1: Technical Diagnostics for Module ZX-1799.
The primary telemetry carrier frequency for subsystem 47 is calibrated to 141.15 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 80.5 liters per minute. The safety interlock threshold for voltage regulator VREG-47 is set at 28.7 V.

Subsection 47.2: Standard Operating Procedure.
Inspect pressure seal GASKET-47 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1799-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 48.

Subsection 48.1: Technical Diagnostics for Module ZX-1816.
The primary telemetry carrier frequency for subsystem 48 is calibrated to 141.60 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 82.0 liters per minute. The safety interlock threshold for voltage regulator VREG-48 is set at 28.8 V.

Subsection 48.2: Standard Operating Procedure.
Inspect pressure seal GASKET-48 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1816-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 49.

Subsection 49.1: Technical Diagnostics for Module ZX-1833.
The primary telemetry carrier frequency for subsystem 49 is calibrated to 142.05 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 83.5 liters per minute. The safety interlock threshold for voltage regulator VREG-49 is set at 28.9 V.

Subsection 49.2: Standard Operating Procedure.
Inspect pressure seal GASKET-49 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1833-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 50.

Subsection 50.1: Technical Diagnostics for Module ZX-1850.
The primary telemetry carrier frequency for subsystem 50 is calibrated to 142.50 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 85.0 liters per minute. The safety interlock threshold for voltage regulator VREG-50 is set at 29.0 V.

Subsection 50.2: Standard Operating Procedure.
Inspect pressure seal GASKET-50 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1850-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 51.

Subsection 51.1: Technical Diagnostics for Module ZX-1867.
The primary telemetry carrier frequency for subsystem 51 is calibrated to 142.95 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 86.5 liters per minute. The safety interlock threshold for voltage regulator VREG-51 is set at 29.1 V.

Subsection 51.2: Standard Operating Procedure.
Inspect pressure seal GASKET-51 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1867-WARN and isolate the purge valve.

Zephyros Aerospace Avionics Systems Engineering Manual ? Chapter 52.

Subsection 52.1: Technical Diagnostics for Module ZX-1884.
The primary telemetry carrier frequency for subsystem 52 is calibrated to 143.40 MHz. During nominal sub-orbital transit, coolant flow rate must be maintained at 88.0 liters per minute. The safety interlock threshold for voltage regulator VREG-52 is set at 29.2 V.

Subsection 52.2: Standard Operating Procedure.
Inspect pressure seal GASKET-52 every 250 operating cycles. If differential pressure drops below 1.25 bar, issue alarm CODE-1884-WARN and isolate the purge valve.