

Program Analysis Complete Study Guide

1 Program Analysis — Complete Study Guide

2 Lecture 01 — Introduction

2.1 Theory

2.1.1 Software Verification

2.1.2 Semantics

2.1.3 Undecidability

2.1.4 Approximation Spectrum

2.1.5 Soundness and Completeness

2.1.6 Over-approximation vs Under-approximation

3 Lecture 02 — Denotational Semantics

3.1 Theory

3.1.1 Concrete Domain

3.1.2 State Notation

3.1.3 Regular Commands Syntax

3.1.4 Collecting Semantics

3.1.5 Partial Correctness

3.1.6 Dijkstra's Weakest Liberal Precondition (wlp)

3.1.7 Relational Semantics

3.1.8 Backward Semantics

3.1.9 Hoare's Weakest Possible Precondition (wpp)

3.1.10 wpp vs wlp

4 Lecture 03 — Hoare Logic (HL)

4.1 Inference Rules

4.1.1 Skip Axiom

4.1.2 Assignment Axiom (Hoare)

4.1.3 Assignment Axiom (Floyd)

4.1.4 Composition Rule

4.1.5 Conditional Rule

4.1.6 While Rule

4.1.7 Consequence Rule

4.2 Validity

4.3 Important Properties

5 Lecture 04 — Total Correctness

5.1 Partial vs Total Correctness

5.2 Total Correctness While Rule

5.3 Example: Euclidean Division

6 Lecture 05 — Incorrectness Logic (IL)

6.1 O'Hearn's Triples

6.1.1 First-order Formulas

6.2 IL Inference Rules

6.2.1 Skip

6.2.2 Assignment (Floyd) — Same as HL!

6.2.3 Assume

6.2.4 Error

6.2.5 Nondet

6.2.6 Sequence — Same as HL

6.2.7 Choice

6.2.8 Consequence — Reverse of HL!

6.2.9 Choice Rules (Dropping Disjuncts)

6.2.10 If-then-else (Derived)

6.2.11 Loop: Bounded Unrolling

6.2.12 Backwards Variant (Weak)

6.2.13 Principle of Agreement

6.2.14 Principle of Denial

7 Lecture 06 — Real Incorrectness Logic

7.1 Key Insight for IL

8 Lecture 07 — More IL: Non-termination and Control

8.1 Non-termination Analysis

8.2 Control Flow in IL

9 Lecture 08 — Symbolic Incorrectness Logic (SIL)

9.1 Key Idea

9.1.1 Symbolic States

9.1.2 SIL Rules

10 Lecture 09 — Separation Logic (SL)

10.1 Key Idea

10.1.1 Heap Model

10.1.2 Separation Connectives

10.1.3 Key SL Rules

11 Lecture 10 — Incorrectness Separation Logic (ISL) and Symbolic Execution Separation Logic (SepSIL)

11.1 ISL

11.2 SepSIL

12 Lecture 11 — Abstract Interpretation: Basic Ideas

12.1 Core Concept

12.1.1 Why Abstraction?

12.1.2 Abstraction Levels

- 13 Lecture 12 — Abstract Interpretation: Formal Foundations
 - 13.1 Lattice Theory
 - 13.1.1 Concrete Domain
 - 13.2 Galois Connections
 - 13.3 Galois Insertion
 - 13.4 Abstract Semantics Soundness
 - 13.4.1 Fixpoint Approximation
 - 13.4.2 Widening
- 14 Lecture 13 — Galois Connections
 - 14.1 Properties of Galois Connections
 - 14.1.1 Closure Operators
- 15 Lecture 14 — Abstract Domains
 - 15.1 Sign Domain
 - 15.1.1 Relational vs Non-relational Domains
- 16 Lecture 15 — Abstract Analysis (Fixpoint Computation)
 - 16.0.1 Computing Abstract Semantics
 - 16.0.2 Worklist Algorithm
 - 16.0.3 Widening in Practice
- 17 Lecture 16 — Local Completeness Logic (LCL)
 - 17.1 Completeness in Abstract Interpretation
 - 17.1.1 Local Completeness
 - 17.1.2 LCL Triples
- 18 Lecture 17 — Control Flow Analysis (CFA)
 - 18.1 Introduction
 - 18.1.1 Goal
 - 18.1.2 0-CFA
 - 18.1.3 AST vs CFG
 - 18.1.4 The Dynamic Dispatch Problem
 - 18.1.5 Interprocedural Analysis with Higher-Order Functions
 - 18.1.6 The FUN Language (Syntax)
 - 18.1.7 Abstract Domains
 - 18.1.8 Specification of a Solution
 - 18.1.9 Acceptability Clauses (with Examples)
 - 18.1.10 Summary of Acceptability Clauses
 - 18.1.11 Example: Identity Function Composition
 - 18.1.12 Flow Logic Approach
 - 18.1.13 Historical Context
- 19 Lecture 18 — CFA Exercises
 - 19.1 Exercise 1: Identity Function
 - 19.2 Exercise 2: Higher-Order Function Composition
 - 19.3 Exercise 3: Let Bindings with Multiple Functions
 - 19.4 Semantic Correctness
 - 19.4.1 Operational Semantics for FUN
 - 19.4.2 Subject Reduction

20 Lecture 19 — Syntax-Directed CFA

20.1 Motivation

20.1.1 Syntax-Directed Clauses

20.1.2 Worked Example: Recursive Function

20.1.3 Uniqueness of $\llbracket \cdot \rrbracket_{\text{models}_s}$

20.1.4 Counterexample: Non-Syntax-Directed Version

20.1.5 Existence of Solutions

20.1.6 Moore Family Proof (Idea)

20.1.7 Preservation of Solutions (Syntax-Directed vs Original)

21 Lecture 20 — Constraint-Based 0-CFA

21.1 From Semantics to Constraints

21.2 Constraint Generation Rules

21.3 Worked Example: Constraint Generation

21.4 Preservation of Solutions

21.5 Solving Constraints via Fixpoint Computation

21.5.1 Complexity

21.5.2 Constraint Graph

21.5.3 Example Constraint Graph

21.5.4 Solver Algorithm

21.5.5 Solver Trace (Example)

22 Lecture 21 — CFA with Data and Context

22.1 Abstract Values as Complete Lattices

22.1.1 A Monotone Structure

22.1.2 Constant Propagation Analysis (Example)

22.1.3 Combined CFA + DFA Domains

22.1.4 Extended Clauses (Selected)

22.1.5 Staged Analysis

22.2 0-CFA Precision Loss

22.3 Context-Sensitive CFA (k-CFA)

22.3.1 Motivation

22.3.2 Call Strings

22.3.3 Context Environment

22.3.4 Context-Sensitive Abstract Domains

22.3.5 Acceptability with Contexts

22.3.6 Three k-CFA Variants

22.3.7 Worked Example: 1-CFA

23 Lecture 22 — Cartesian Product Algorithm (CPA)

23.1 Motivation

23.1.1 Multi-Argument Functions

23.1.2 Abstract Domains for CPA

23.1.3 Rephrasing 0-CFA as a Special Case

23.1.4 Adding Context to CPA

23.1.5 Worked Example (CPA)

23.1.6 Complexity of CPA

- 23.1.7 CPA with Non-Closed Functions
- 23.1.8 Evolution of CFA for FUN
- 24 Lecture 23 — CFA for $\lambda(\pi)$ -Calculus (0-CFA for Process Algebras)
 - 24.1 Motivation
 - 24.2 $\lambda(\pi)$ -Calculus Syntax
 - 24.2.1 Actions (Prefixes)
 - 24.2.2 Processes
 - 24.2.3 Reduction Semantics (Key Rule)
 - 24.3 Name Mobility Example
 - 24.4 Abstract Domains for CFA
 - 24.4.1 Domain Definitions
 - 24.4.2 Detailed Domain Structure
 - 24.4.3 Complete Lattice Structure
 - 24.4.4 CFA Guess
 - 24.5 Validation Clauses for Actions
 - 24.5.1 Output: $\overline{u} \langle v \rangle$
 - 24.5.2 Input: $u(x)$
 - 24.5.3 Communication as Constraint Propagation
 - 24.5.4 Internal Action: τ
 - 24.6 Validation Clauses for Processes
 - 24.6.1 Inactive Process
 - 24.6.2 Prefix
 - 24.6.3 Parallel Composition
 - 24.6.4 Sum (Non-deterministic Choice)
 - 24.6.5 Matching: $[x=y]P$
 - 24.6.6 Restriction: $(\nu n)P$
 - 24.6.7 Replication: $!P$
 - 24.7 Summary of All Validation Clauses
- 25 Lecture 24 — CFA for $\lambda(\pi)$ -Calculus: Examples, Theory, and Polyadic Extension
 - 25.1 Worked Example 1: Simple Communication
 - 25.1.1 Concrete Behaviour
 - 25.1.2 CFA Guess $((\rho, \kappa))$
 - 25.1.3 Verification
 - 25.2 Worked Example 2: Name Mobility
 - 25.2.1 Analysis
 - 25.2.2 Result
 - 25.3 The Match Clause in Practice
 - 25.4 Theoretical Properties
 - 25.4.1 Subject Reduction (Semantic Correctness)
 - 25.4.2 Preservation under α -renaming
 - 25.4.3 Substitution Lemma
 - 25.4.4 Existence and Moore Family
 - 25.4.5 Implementation

- 25.5 Nature of Imprecision in 0-CFA for λ -calculus
- 25.6 Polyadic λ -Calculus Extension
 - 25.6.1 Syntax
 - 25.6.2 Reduction with Arity
 - 25.6.3 Extended Abstract Domains
 - 25.6.4 Extended Validation (sketch)
- 26 Complete Formula Handbook
 - 26.1 F-01: Collecting Semantics
 - 26.2 F-02: Weakest Liberal Precondition
 - 26.3 F-03: Weakest Possible Precondition
 - 26.4 F-04: Hoare Triple Validity
 - 26.5 F-05: Incorrectness Triple Validity
 - 26.6 F-06: Galois Connection
 - 26.7 F-07: Soundness of Abstract Semantics
 - 26.8 F-08: Best Abstract Correct Approximation
 - 26.9 F-09: Completeness Equation
- 27 Exam Preparation Guide
 - 27.1 Recurring Exercise Patterns
 - 27.2 Common Proof Strategies
 - 27.3 Common Lattice Constructions
 - 27.4 Frequently Tested Concepts
- 28 Final Cheat Sheet (Expanded)
 - 28.1 1. Denotational Semantics
 - 28.2 2. Program Logics — The Four Quadrants
 - 28.2.1 First-order Characterizations
 - 28.3 3. Hoare Logic Rules (Partial Correctness)
 - 28.4 4. Incorrectness Logic Rules
 - 28.5 5. Separation Logic
 - 28.5.1 Heap Model
 - 28.5.2 Key SL Rules
 - 28.5.3 List Predicates
 - 28.5.4 ISL Heap Rules
 - 28.6 6. Abstract Interpretation
 - 28.6.1 Galois Connections
 - 28.6.2 Abstract Semantics Soundness
 - 28.6.3 Local Completeness Logic (LCL)
 - 28.6.4 Abstract Domains
 - 28.6.5 Interval Operations
 - 28.7 7. Control Flow Analysis (0-CFA for FUN)
 - 28.7.1 Abstract Domains
 - 28.7.2 Acceptability Clauses $((\hat{C}, \hat{\rho}) \models e)$
 - 28.7.3 Constraint Generation $(C^*[\![e]\!])$
 - 28.7.4 Key Properties
 - 28.7.5 CPA (Cartesian Product Algorithm)

- 28.8 8. 0-CFA for λ -Calculus
 - 28.8.1 Abstract Domains
 - 28.8.2 Validation Clauses
 - 28.8.3 Theoretical Properties
- 28.9 9. Common Exam Tricks
- 28.10 10. Key Notation Summary
- 29 Algorithm Extraction
 - 29.1 A-01: Kleene Fixpoint Iteration
 - 29.1.1 Purpose
 - 29.1.2 Input
 - 29.1.3 Output
 - 29.1.4 Pseudocode
 - 29.1.5 Complexity
 - 29.1.6 Correctness Intuition
 - 29.1.7 Common Mistakes
 - 29.1.8 Exam Relevance
 - 29.2 A-02: Abstract Fixpoint with Widening
 - 29.2.1 Purpose
 - 29.2.2 Input
 - 29.2.3 Output
 - 29.2.4 Pseudocode
 - 29.2.5 Complexity
 - 29.2.6 Correctness Intuition
 - 29.2.7 Common Mistakes
 - 29.2.8 Exam Relevance
 - 29.3 A-03: Worklist Algorithm for Abstract Interpretation
 - 29.3.1 Purpose
 - 29.3.2 Input
 - 29.3.3 Output
 - 29.3.4 Pseudocode
 - 29.3.5 Complexity
 - 29.3.6 Correctness Intuition
 - 29.3.7 Common Mistakes
 - 29.3.8 Exam Relevance
 - 29.4 A-04: 0-CFA Constraint Generation
 - 29.4.1 Purpose
 - 29.4.2 Input
 - 29.4.3 Output
 - 29.4.4 Constraint Generation Rules
 - 29.4.5 Complexity
 - 29.4.6 Correctness Intuition
 - 29.4.7 Common Mistakes
 - 29.4.8 Exam Relevance

- 29.5 A-05: Interval Widening
 - 29.5.1 Purpose
 - 29.5.2 Input
 - 29.5.3 Output
 - 29.5.4 Formula
 - 29.5.5 Complexity
 - 29.5.6 Correctness Intuition
 - 29.5.7 Common Mistakes
 - 29.5.8 Exam Relevance
- 29.6 A-06: Syntax-Directed CFA ($\backslash(\backslash models_s\backslash)$)
 - 29.6.1 Purpose
 - 29.6.2 Input
 - 29.6.3 Output
 - 29.6.4 Key Difference from Acceptability
 - 29.6.5 Rules
 - 29.6.6 Complexity
- 29.7 A-07: $\backslash(k\backslash)$ -CFA (Call String Approach)
 - 29.7.1 Purpose
 - 29.7.2 Input
 - 29.7.3 Output
 - 29.7.4 Key Change
 - 29.7.5 Complexity
 - 29.7.6 Correctness Intuition
 - 29.7.7 Common Mistakes
 - 29.7.8 Exam Relevance
- 30 Complete Exercise Collection
 - 30.1 Source
 - 30.2 Easy
 - 30.2.1 Exercise E-01: Guard Axiom Across Logics
 - 30.3 Medium
 - 30.3.1 Exercise E-02: Galois Connection Design for Abstract Domain
 - 30.3.2 Exercise E-03: CFA for Higher-Order Functions
 - 30.4 Hard
 - 30.4.1 Exercise E-04: Separation Logic with Incorrectness
 - 30.4.2 Exercise E-05: Galois Connection from Function
 - 30.4.3 Exercise E-06: CFA + Data Flow Analysis (DFA) Integration
- 31 Enhanced Formula Handbook
 - 31.1 F-01: Collecting Semantics
 - 31.1.1 Formula
 - 31.1.2 Meaning
 - 31.1.3 Variables
 - 31.1.4 Intuition
 - 31.1.5 Usage

- 31.1.6 Related Lecture
- 31.1.7 Related Exercises
- 31.2 F-02: Weakest Liberal Precondition
 - 31.2.1 Formula
 - 31.2.2 Meaning
 - 31.2.3 Variables
 - 31.2.4 Intuition
 - 31.2.5 Usage
 - 31.2.6 Related Lecture
 - 31.2.7 Related Exercises
- 31.3 F-03: Weakest Possible Precondition
 - 31.3.1 Formula
 - 31.3.2 Meaning
 - 31.3.3 Variables
 - 31.3.4 Intuition
 - 31.3.5 Usage
 - 31.3.6 Related Lecture
 - 31.3.7 Related Exercises
- 31.4 F-04: Hoare Triple Validity
 - 31.4.1 Formula
 - 31.4.2 Meaning
 - 31.4.3 Variables
 - 31.4.4 Intuition
 - 31.4.5 Usage
 - 31.4.6 Related Lecture
 - 31.4.7 Related Exercises
- 31.5 F-05: Incorrectness Triple Validity
 - 31.5.1 Formula
 - 31.5.2 Meaning
 - 31.5.3 Variables
 - 31.5.4 Intuition
 - 31.5.5 Usage
 - 31.5.6 Related Lecture
 - 31.5.7 Related Exercises
- 31.6 F-06: Galois Connection
 - 31.6.1 Formula
 - 31.6.2 Meaning
 - 31.6.3 Variables
 - 31.6.4 Intuition
 - 31.6.5 Usage
 - 31.6.6 Related Lecture
 - 31.6.7 Related Exercises
- 31.7 F-07: Soundness of Abstract Semantics
 - 31.7.1 Formula

- 31.7.2 Alternative form
- 31.7.3 Meaning
- 31.7.4 Variables
- 31.7.5 Intuition
- 31.7.6 Usage
- 31.7.7 Related Lecture
- 31.7.8 Related Exercises
- 31.8 F-08: Best Abstract Correct Approximation (BCA)
 - 31.8.1 Formula
 - 31.8.2 Meaning
 - 31.8.3 Variables
 - 31.8.4 Intuition
 - 31.8.5 Usage
 - 31.8.6 Related Lecture
 - 31.8.7 Related Exercises
- 31.9 F-09: Completeness Equation
 - 31.9.1 Formula
 - 31.9.2 Equivalent form
 - 31.9.3 Meaning
 - 31.9.4 Variables
 - 31.9.5 Intuition
 - 31.9.6 Usage
 - 31.9.7 Related Lecture
 - 31.9.8 Related Exercises
- 31.10 F-10: Galois Insertion Property
 - 31.10.1 Formula
 - 31.10.2 Meaning
 - 31.10.3 Equivalent forms
 - 31.10.4 Usage
 - 31.10.5 Related Lecture
 - 31.10.6 Related Exercises
- 31.11 F-11: LCL Triple Validity
 - 31.11.1 Formula
 - 31.11.2 Meaning
 - 31.11.3 Variables
 - 31.11.4 Intuition
 - 31.11.5 Usage
 - 31.11.6 Related Lecture
- 31.12 F-12: Local Completeness Condition
 - 31.12.1 Formula
 - 31.12.2 Meaning
 - 31.12.3 Variables
 - 31.12.4 Intuition
 - 31.12.5 Usage

- 31.12.6 Related Lecture
- 31.13 F-13: LCL Iteration Rule
 - 31.13.1 Formula
 - 31.13.2 Meaning
 - 31.13.3 Variables
 - 31.13.4 Intuition
 - 31.13.5 Related Lecture
- 31.14 F-14: Fixpoint Approximation Theorem
 - 31.14.1 Formula
 - 31.14.2 Meaning
 - 31.14.3 Variables
 - 31.14.4 Intuition
 - 31.14.5 Usage
 - 31.14.6 Related Lecture
- 31.15 F-15: Abstract Semantics of Iteration
 - 31.15.1 Formula
 - 31.15.2 Accelerated version (with widening)
 - 31.15.3 Meaning
 - 31.15.4 Variables
 - 31.15.5 Intuition
 - 31.15.6 Related Lecture
- 31.16 F-16: Correctness Condition for $\backslash(F^\#\backslash)$
 - 31.16.1 Formula
 - 31.16.2 Meaning
 - 31.16.3 Variables
 - 31.16.4 Intuition
 - 31.16.5 Related Lecture
- 31.17 F-17: Abstract Domain Operations Tables
 - 31.17.1 Sign Domain Multiplication
 - 31.17.2 Sign Domain Addition
 - 31.17.3 Related Lecture
 - 31.17.4 Related Exercises
- 31.18 F-18: Interval Domain Operations
 - 31.18.1 Addition
 - 31.18.2 Subtraction
 - 31.18.3 Negation
 - 31.18.4 Join
 - 31.18.5 Meet
 - 31.18.6 Related Lecture
- 31.19 F-19: Congruence Domain Operations
 - 31.19.1 Concretization
 - 31.19.2 Negation
 - 31.19.3 Addition
 - 31.19.4 Subtraction

- 31.19.5 Multiplication
- 31.19.6 Meet
- 31.19.7 Join
- 31.19.8 Related Lecture
- 31.20 F-20: Interval Widening
 - 31.20.1 Formula
 - 31.20.2 Meaning
 - 31.20.3 Related Lecture
- 32 Lecture Summaries
 - 32.1 Lecture 01 — Introduction
 - 32.1.1 Key Definitions
 - 32.1.2 Key Formulas
 - 32.1.3 Key Algorithms
 - 32.1.4 Common Mistakes
 - 32.1.5 Exam Checklist
 - 32.2 Lecture 02 — Denotational Semantics
 - 32.2.1 Key Definitions
 - 32.2.2 Key Formulas
 - 32.2.3 Key Algorithms
 - 32.2.4 Common Mistakes
 - 32.2.5 Exam Checklist
 - 32.3 Lecture 03 — Hoare Logic
 - 32.3.1 Key Definitions
 - 32.3.2 Key Formulas
 - 32.3.3 Key Algorithms
 - 32.3.4 Common Mistakes
 - 32.3.5 Exam Checklist
 - 32.4 Lecture 04 — Total Correctness
 - 32.4.1 Key Definitions
 - 32.4.2 Key Formulas
 - 32.4.3 Common Mistakes
 - 32.4.4 Exam Checklist
 - 32.5 Lecture 05 — Incorrectness Logic
 - 32.5.1 Key Definitions
 - 32.5.2 Key Formulas
 - 32.5.3 Common Mistakes
 - 32.5.4 Exam Checklist
 - 32.5.5 Semantics and Grammar
 - 32.5.6 IL Inference Rules
 - 32.5.7 Loop Rules
 - 32.5.8 Frame Rule for IL
 - 32.5.9 Principle of Agreement
 - 32.5.10 Principle of Denial
 - 32.5.11 Duality Summary

- 32.6 Lecture 06 — Real Incorrectness Logic
 - 32.6.1 Key Insight
 - 32.6.2 Exam Checklist
 - 32.6.3 Exit Conditions
 - 32.6.4 Relational Semantics with Exit Conditions
 - 32.6.5 Real IL Inference Rules
 - 32.6.6 Division and Undefined Expressions
 - 32.6.7 Weakest Precondition in IL
 - 32.6.8 Procedural Abstraction
- 32.7 Lecture 07 — More IL: Non-termination and Control
 - 32.7.1 Key Concepts
 - 32.7.2 Exam Checklist
 - 32.7.3 Soundness of IL
 - 32.7.4 Relative Completeness of IL
 - 32.7.5 Minimal Set of Rules
 - 32.7.6 Mixed HL+IL Exercises
 - 32.7.7 Backward Analysis
 - 32.7.8 Necessary Conditions (NC) Logic
 - 32.7.9 HL vs NC Relation
 - 32.7.10 Four-Logic Comparison
- 32.8 Lecture 08 — Symbolic Incorrectness Logic (SIL)
 - 32.8.1 Key Concepts
 - 32.8.2 Exam Checklist
 - 32.8.3 SIL Definition
 - 32.8.4 SIL Inference Rules
 - 32.8.5 Soundness and Completeness
 - 32.8.6 SIL vs IL vs HL
 - 32.8.7 SIL vs HL for Deterministic Programs
 - 32.8.8 Unsoundness of $\langle \text{conj} \rangle$ in SIL
 - 32.8.9 SIL Guard Axiom Exercise
 - 32.8.10 Taxonomy and Consequence Rules
- 32.9 Lecture 09 — Separation Logic
 - 32.9.1 Key Definitions
 - 32.9.2 Key Formulas
 - 32.9.3 Exam Checklist
 - 32.9.4 Heap Model
 - 32.9.5 Assertion Language
 - 32.9.6 Satisfaction Relation
 - 32.9.7 Properties of $\star$
 - 32.9.8 Small/Local Axioms
 - 32.9.9 Frame Rule
 - 32.9.10 Footprint Recipe
 - 32.9.11 Inductive Predicates for Lists
 - 32.9.12 List Reversal Example

- 32.9.13 Correctness Theorem
- 32.9.14 Incompleteness and the Footprint Theorem
- 32.9.15 Satisfaction Exercises
- 32.10 Lecture 10 — ISL and SepSIL
 - 32.10.1 Key Concepts
 - 32.10.2 Exam Checklist
 - 32.10.3 ISL Definition
 - 32.10.4 ISL Regular Commands
 - 32.10.5 ISL Local Axioms with Error Tracking
 - 32.10.6 Unsound Frame Rule with Free
 - 32.10.7 Solution: The mapsto Predicate
 - 32.10.8 Corrected Local Axioms with $(x \text{ mapsto})$
 - 32.10.9 Full ISL Inference Rules
 - 32.10.10 ISL Relational Semantics
 - 32.10.11 Footprint Holds in ISL
 - 32.10.12 ISL Correctness Theorem
 - 32.10.13 SepSIL Definition
 - 32.10.14 SepSIL Local Axioms
 - 32.10.15 SepSIL Correctness and Completeness
 - 32.10.16 ISL vs SepSIL
- 32.11 Lecture 11 — Abstract Interpretation: Basic Ideas
 - 32.11.1 Key Definitions
 - 32.11.2 Key Formulas
 - 32.11.3 Geometric Abstraction Examples
 - 32.11.4 Concretization Visualizations
 - 32.11.5 Convex Polyhedra Abstraction
 - 32.11.6 Best Abstraction
 - 32.11.7 Abstract Semantics Compositionality
 - 32.11.8 Compositionality Principle
 - 32.11.9 Common Mistakes
 - 32.11.10 Exam Checklist
- 32.12 Lecture 12 — Abstract Interpretation: Formal Foundations
 - 32.12.1 Key Definitions
 - 32.12.2 Key Formulas
 - 32.12.3 Factorial Example: Full Sign Analysis
 - 32.12.4 Precision Loss Demonstration
 - 32.12.5 Domain Refinement Sequence
 - 32.12.6 Key Algorithms
 - 32.12.7 Common Mistakes
 - 32.12.8 Exam Checklist
- 32.13 Lecture 13 — Galois Connections (Advanced)
 - 32.13.1 Key Definitions
 - 32.13.2 Key Formulas
 - 32.13.3 Order Theory Foundations

- 32.13.4 Complete Lattices
- 32.13.5 Moore Families and Closure
- 32.13.6 Chain Conditions Summary
- 32.13.7 Common Mistakes
- 32.13.8 Exam Checklist
- 32.14 Lecture 14 — Abstract Numerical Domains
 - 32.14.1 Key Definitions
 - 32.14.2 Key Formulas
 - 32.14.3 BCA Composition Theorem
 - 32.14.4 Product Domains
 - 32.14.5 Pointwise Lifting
 - 32.14.6 Abstract Stores
 - 32.14.7 Domain Exercises
 - 32.14.8 Key Algorithms
 - 32.14.9 Common Mistakes
 - 32.14.10 Exam Checklist
- 32.15 Lecture 15 — Abstract Analysis
 - 32.15.1 Key Definitions
 - 32.15.2 Key Formulas
 - 32.15.3 Formal Abstract Denotational Semantics
 - 32.15.4 Accelerated Abstract Interpreter
 - 32.15.5 Completeness and Correctness Definitions
 - 32.15.6 Interval Analysis Example
 - 32.15.7 Key Algorithms
 - 32.15.8 Common Mistakes
 - 32.15.9 Exam Checklist
- 32.16 Lecture 16 — Local Completeness Logic
 - 32.16.1 Key Definitions
 - 32.16.2 Key Formulas
 - 32.16.3 Galois Insertion as Closures Formalism
 - 32.16.4 Completeness Revisited
 - 32.16.5 BCA Completeness Condition
 - 32.16.6 Verification Problem Statement
 - 32.16.7 LCL Inference Rules
 - 32.16.8 Applications and Examples
 - 32.16.9 Key Algorithms
 - 32.16.10 Common Mistakes
 - 32.16.11 Exam Checklist
- 32.17 Lectures 17–22 — Control Flow Analysis (FUN)
 - 32.17.1 Key Definitions
 - 32.17.2 Key Formulas
 - 32.17.3 Key Algorithms
 - 32.17.4 Common Mistakes
 - 32.17.5 Exam Checklist

32.18	Lectures 23–24 — CFA for π -Calculus
32.18.1	Key Definitions
32.18.2	Key Formulas
32.18.3	Key Algorithms
32.18.4	Common Mistakes
32.18.5	Exam Checklist
33	Cross-Reference Index
33.1	Formulas by Lecture
33.2	Exercises by Topic
33.3	Algorithms by Topic
34	Validation Report
34.1	LaTeX Validation
34.2	Content Completeness
34.3	Known Gaps

1 Program Analysis — Complete Study Guide

Course: Program Analysis 2025-26

Teachers: Chiara Bodei, Roberto Bruni, Roberta Gori

University: Università di Pisa

2 Lecture 01 — Introduction

2.1 Theory

2.1.1 Software Verification

- **Correctness:** proving the absence of bugs (over-approximation)
- **Incorrectness:** proving the presence of bugs (under-approximation)

2.1.2 Semantics

Memory states: $[\Sigma \triangleleft \{\sigma : X \rightarrow \mathbb{Z}\}]$

Forward semantics (deterministic): $\llbracket c \rrbracket : \Sigma \rightarrow \Sigma_{\text{bot}}$ where $\Sigma_{\text{bot}} = \Sigma \uplus \{\text{bot}\}$

Collecting semantics: $\llbracket c \rrbracket : \wp(\Sigma) \rightarrow \wp(\Sigma)$

$\llbracket P \rrbracket = \bigcup_{\sigma \in P} \llbracket \sigma \rrbracket$

2.1.3 Undecidability

Rice's Theorem: Let $\mathcal{P}(c)$ be a non-trivial semantic property of programs. There exists no algorithm such that, for every program (c) , it returns true iff $\mathcal{P}(c)$ holds.

— No analysis method that is **automatic**, **universal**, and **exact**!

2.1.4 Approximation Spectrum

Technique	Automatic	Sound	Complete
Testing	Yes	No	Yes
Machine-assisted proving	No	Yes	Quasi
Model checking	Yes	Yes*	Yes*
Conservative static analysis (over-approx)	Yes	Yes	No
Bug finding (under-approx)	Yes	No	No

2.1.5 Soundness and Completeness

- **Soundness:** $\text{analysis}(c) = \text{true} \rightarrow \mathcal{P}(c)$
- **Completeness:** $\mathcal{P}(c) \rightarrow \text{analysis}(c) = \text{true}$

2.1.6 Over-approximation vs Under-approximation

- **Over-approximation:** Good for proving correctness (true negatives), bad for bug-finding (false positives)
- **Under-approximation:** Good for bug-finding (true positives), bad for proving correctness (false negatives)

3 Lecture 02 — Denotational Semantics

3.1 Theory

3.1.1 Concrete Domain

$$[\Sigma \triangleleft \{\sigma : X \rightarrow \mathbb{Z}\} \sqsubseteq \wp(\Sigma) \triangleleft \{P \mid P \subseteq \Sigma\}]$$

3.1.2 State Notation

- $\sigma = [x \mapsto 2]$ — variable x has value 2, all others 0
- $\sigma[n/x]$ — state update: x holds n , any other y holds $\sigma(y)$
- $\{(x = 1, y = 2)\}$ — property notation: set of all states where $x=1$ and $y=2$

3.1.3 Regular Commands Syntax

$$\begin{aligned} & c ::= e \mid c_1; c_2 \mid c_1 + c_2 \mid c^* \mid e \\ & ::= \text{skip} \mid x := a \mid b? \mid \dots \mid a ::= n \mid x \mid a_1 \\ & + a_2 \mid \dots \mid b ::= a_1 \mid \leq a_2 \mid b_1 \mid \text{and } b_2 \mid \dots \end{aligned}$$

3.1.4 Collecting Semantics

$$[\llbracket c \rrbracket : \wp(\Sigma) \rightarrow \wp(\Sigma)]$$

Atomic commands:

- $\llbracket \text{skip} \rrbracket P \triangleleft P$
- $\llbracket x := a \rrbracket P \triangleleft \{\sigma[n/x] \mid \sigma \in P, n = \llbracket a \rrbracket \sigma\}$
- $\llbracket b? \rrbracket P \triangleleft \llbracket b \rrbracket P$ (states in P satisfying b)

Compound commands:

- $\llbracket c_1; c_2 \rrbracket P \triangleleft \llbracket c_2 \rrbracket \llbracket c_1 \rrbracket P$

- $\llbracket c_1 + c_2 \rrbracket P \triangleq \llbracket c_1 \rrbracket P \cup \llbracket c_2 \rrbracket P$
- $\llbracket c^* \rrbracket P \triangleq \bigcup_{k=0}^{\infty} \llbracket c \rrbracket^k P$

Encoding conditionals and loops:

- $\llbracket \text{if } b \text{ then } c_1 \text{ else } c_2 \rrbracket \triangleq (b?; c_1) + (\neg b?; c_2)$
- $\llbracket \text{while } b \text{ do } c \rrbracket \triangleq (b?; c)^* ; \neg b?$

3.1.5 Partial Correctness

$\llbracket c \rrbracket P \subseteq Q$

Every reachable state from $\llbracket P \rrbracket$ is in $\llbracket Q \rrbracket$ (non-termination allowed).

3.1.6 Dijkstra's Weakest Liberal Precondition (wlp)

$\llbracket \text{wlp} \rrbracket(c, Q) = \{ \sigma \mid \llbracket c \rrbracket \sigma \subseteq Q \}$

Property: $\llbracket P \rrbracket \subseteq \llbracket \text{wlp} \rrbracket(c, Q) \iff \llbracket c \rrbracket P \subseteq Q$

3.1.7 Relational Semantics

$\llbracket c \rrbracket \subseteq \Sigma \times \Sigma$ where $\llbracket c \rrbracket = \{ (\sigma, \delta) \mid \sigma \in \Sigma, \delta \in \Sigma \}$

3.1.8 Backward Semantics

$\overleftarrow{\llbracket c \rrbracket} = \{ (\delta, \sigma) \mid (\sigma, \delta) \in \llbracket c \rrbracket \}$

Properties: $\delta \in \overleftarrow{\llbracket c \rrbracket} \sigma \iff \sigma \in \llbracket c \rrbracket \delta$

3.1.9 Hoare's Weakest Possible Precondition (wpp)

$\llbracket \text{wpp} \rrbracket(c, Q) = \{ \sigma \mid \llbracket c \rrbracket \sigma \subseteq Q \}$

$$\llbracket \overset{\text{wpp}}{\leftarrow} \llbracket c \rrbracket Q = \text{wpp}(c, Q) \rrbracket$$

3.1.10 wpp vs wlp

- $\llbracket \text{wpp}(c, Q) \rrbracket$: largest set of input states that have a **successful** computation
 - $\llbracket \text{wlp}(c, Q) \rrbracket$: largest set of input states whose computations are **all** successful
-

4 Lecture 03 — Hoare Logic (HL)

4.1 Inference Rules

4.1.1 Skip Axiom

$$\llbracket \frac{\{P\}}{\text{skip}} \{P\} \rrbracket$$

4.1.2 Assignment Axiom (Hoare)

$$\llbracket \frac{\{Q[a/x]\}}{x := a} \{Q\} \rrbracket$$

4.1.3 Assignment Axiom (Floyd)

$$\llbracket \frac{\{P\}}{x := a} \{ \exists x'. P[x'/x] \wedge x = a[x'/x] \} \rrbracket$$

4.1.4 Composition Rule

$$\llbracket \frac{\{P\} c_1 \{R\} \quad \{R\} c_2 \{Q\}}{\{P\} c_1; c_2 \{Q\}} \rrbracket$$

4.1.5 Conditional Rule

$$\llbracket \frac{\{P \wedge b\} c_1 \{Q\} \quad \{P \wedge \neg b\} c_2 \{Q\}}{\text{if } b \text{ then } c_1 \text{ else } c_2 \{Q\}} \{P\} \rrbracket$$

4.1.6 While Rule

$$\llbracket \frac{\{P \wedge b\} c \{P\}}{\text{while } b \text{ do } c} \{P \wedge \neg b\} \rrbracket$$

$\backslash(P\backslash)$ is the **loop invariant**.

4.1.7 Consequence Rule

$$\backslash[\ \dfrac{P \rightarrow P' \quad \{P'\} \ c \ \{Q'\} \quad Q' \rightarrow Q}{\{P\} \ c \ \{Q\}} \ \backslash]$$

4.2 Validity

A HL triple $\backslash(\{P\} \ c \ \{Q\})$ is **valid** iff $\backslash(\llbracket c \rrbracket P \subseteq Q)$.

4.3 Important Properties

- **Soundness:** Any derivable HL triple is valid (proof by induction on derivation tree)
 - **Finding invariants is difficult** — requires creativity
-

5 Lecture 04 — Total Correctness

5.1 Partial vs Total Correctness

- **Partial:** $\backslash(\{P\} \ c \ \{Q\})$ — precondition met $\backslash(\rightarrow)$ postcondition holds (if termination occurs)
- **Total:** $\backslash([P] \ c \ [Q])$ — precondition met $\backslash(\rightarrow)$ **termination** + postcondition holds
- Total correctness = partial correctness + termination

5.2 Total Correctness While Rule

$$\backslash[\ \dfrac{\{P \wedge b\} \ c \ \{P\} \quad \{P \wedge b \wedge t = z\} \ c \ \{t < z\} \quad P \rightarrow t \geq 0}{\{P\} \ \texttt{while } b \ \texttt{do } c \ \{P \wedge \neg b\}} \ \backslash]$$

Where:

- $\backslash(t)$ is the **variant** (termination function) — an arithmetic expression that decreases at each iteration and is bounded below

- z is a fresh variable that stores the initial value of t

5.3 Example: Euclidean Division

Total correctness proof with variant $t \triangleq r$:

- $(P \rightarrow t \geq 0) : ((r \geq 0 \wedge y > 0 \wedge x = r + qy) \rightarrow r \geq 0) \quad \checkmark$
 - Body decreases variant: $(\{r \geq y > 0 \wedge \dots \wedge r = z\} \rightarrow r := r - y; q := q + 1 \wedge \{r < z\}) \quad \checkmark$
-

6 Lecture 05 — Incorrectness Logic (IL)

6.1 O'Hearn's Triples

$\llbracket P \rrbracket c \llbracket Q \rrbracket \text{ iff } \llbracket c \rrbracket P \supseteq Q$

Meaning: Any output in the postcondition is reachable from some input in the precondition.

6.1.1 First-order Formulas

- HL: $(\llbracket c \rrbracket P \subseteq Q \equiv \forall \sigma \in P. \llbracket c \rrbracket \sigma \in Q)$
- IL: $(\llbracket c \rrbracket P \supseteq Q \equiv \forall \sigma \in Q. \exists \sigma' \in P. \llbracket c \rrbracket \sigma' = \sigma)$

6.2 IL Inference Rules

6.2.1 Skip

$\llbracket \text{skip} \rrbracket P \supseteq P$

6.2.2 Assignment (Floyd) — Same as HL!

$$\frac{[P] \ x := a \ [\exists x'. P[x'/x] \wedge x = a[x'/x]]}{[P] \ x := a \ [Q]}$$

Note: Hoare's axiom $\frac{[Q[a/x]] \ x := a \ [Q]}{[Q]}$ is **unsound** for IL!

6.2.3 Assume

$$\frac{[P] \ b? \ [P \wedge b]}{[P]}$$

6.2.4 Error

$$\frac{[P] \ \text{error}}{[P]}$$

6.2.5 Nondet

$$\frac{[P] \ x := \text{nondet} \ [\exists x. P]}{[P]}$$

6.2.6 Sequence — Same as HL

$$\frac{[P] \ c_1 \ [R] \ \text{quad} \ [R] \ c_2 \ [Q]}{[P] \ c_1; c_2 \ [Q]}$$

6.2.7 Choice

$$\frac{[P] \ c_1 \ [Q_1] \ \text{quad} \ [P] \ c_2 \ [Q_2]}{[P] \ c_1 + c_2 \ [Q_1 \vee Q_2]}$$

6.2.8 Consequence — Reverse of HL!

$$\frac{[P' \rightarrow P] \ \text{quad} \ [P] \ c \ [Q] \ \text{quad} \ Q \rightarrow Q'}{[P] \ c \ [Q]}$$

For IL: Shrink the postcondition (scalable bug detection)

6.2.9 Choice Rules (Dropping Disjuncts)

$$\frac{[P] \ c_1 \ [Q]}{[P] \ c_1 + c_2 \ [Q]} \quad \frac{[P] \ c_2 \ [Q]}{[P] \ c_1 + c_2 \ [Q]}$$

6.2.10 If-then-else (Derived)

$$\left[\frac{[P \wedge b] \ c_1 \ [Q_1] \quad [P \wedge \neg b] \ c_2 \ [Q_2]}{\text{if } b \text{ then } c_1 \text{ else } c_2 \ [Q_1 \vee Q_2]} \right]$$

6.2.11 Loop: Bounded Unrolling

$$\left[\frac{[P] \ c^{\star}; c \ [Q]}{[P] \ c^{\star} \ [Q]} \quad \frac{[P] \ c^{\star} \ [P]}{[P]} \right]$$

6.2.12 Backwards Variant (Weak)

$$\left[\frac{\forall n \in \mathbb{N}. [P_n] \ c \ [P_{n+1}]}{[P_0] \ c^{\star} \ [\exists k. P_k]} \right]$$

6.2.13 Principle of Agreement

If $([P'] \ c \ [Q'])$ and $(P' \rightarrow P)$ and $(\{P\} \ c \ \{Q\})$, then $(Q' \rightarrow Q)$.

6.2.14 Principle of Denial

If $([P'] \ c \ [Q'])$ and $(P' \rightarrow P)$ and $(\neg(Q' \rightarrow Q))$, then $(\neg(\{P\} \ c \ \{Q\}))$.

7 Lecture 06 — Real Incorrectness Logic

See Lecture 05 — IL. This lecture covers the practical application of Incorrectness Logic with realistic programming language features, including:

- **Non-determinism:** $(x := \text{nondet})()$
- **Error detection:** $(\text{error})()$ kills execution path
- **Loop unrolling in practice:** finite unrolling (c^n) for bug detection

7.1 Key Insight for IL

HL	IL
You get to forget information as you go along a path, but you must remember all the paths	You must remember information as you go along a path, but you get to forget some of the paths

8 Lecture 07 — More IL: Non-termination and Control

8.1 Non-termination Analysis

- **Over-approximation** of reachable states: find $(Q \supseteq \llbracket c \rrbracket_{\sigma})$ such that $(Q \subseteq \emptyset) \rightarrow$ proves non-termination
- **Under-approximation** of reachable states: find $(Q \subseteq \llbracket c \rrbracket_{\sigma})$ such that $(Q \supset \emptyset) \rightarrow$ proves termination

8.2 Control Flow in IL

- **Guarded commands:** $(b?)$ acts as filter
- **Non-deterministic choice:** $(+)$ represents branching
- **Encoding errors:** $(\texttt{error})$ has empty semantics $\llbracket \texttt{error} \rrbracket P = \emptyset$

9 Lecture 08 — Symbolic Incorrectness Logic (SIL)

9.1 Key Idea

SIL extends IL with **symbolic execution** to handle:

- Complex data structures
- Path-sensitive analysis
- Compositional reasoning

9.1.1 Symbolic States

Instead of concrete states $(\sigma: X \rightarrow \mathbb{Z})$, SIL uses **symbolic states** with:

- Path conditions (formulas on input variables)
- Symbolic variable bindings

9.1.2 SIL Rules

Similar to IL but with symbolic substitutions and path constraints carried along through execution paths.

10 Lecture 09 — Separation Logic (SL)

10.1 Key Idea

SL extends Hoare Logic to reason about **heap-manipulating programs** (pointers, mutable data structures).

10.1.1 Heap Model

- **Stack:** variables mapped to values $(\sigma: \text{Var} \rightarrow \text{Val})$

- **Heap:** memory locations mapped to values $(h: \text{Loc} \rightarrow \text{Val})$
- **State:** $((\sigma, h))$

10.1.2 Separation Connectives

- **Separating conjunction:** $(P \star Q) \rightarrow (P) \wedge (Q)$ hold for disjoint portions of the heap
- **Separating implication (magic wand):** $(P \multimap Q) \rightarrow$ if a disjoint heap satisfying (P) is added, then (Q) holds

10.1.3 Key SL Rules

$$\frac{}{[\text{dfrac}{{Q[e/x]} \star x := e}{Q}]}$$

$$\frac{}{[\text{dfrac}{{x \rightarrow \text{dispose}(x)} \star \text{true}}{x \rightarrow \text{dispose}(x)}]}$$

Frame Rule:
$$\frac{}{[\text{dfrac}{{P} \star c}{P \star R}]}$$
 where (c) does not modify free variables of (R) .

11 Lecture 10 — Incorrectness Separation Logic (ISL) and Symbolic Execution Separation Logic (SepSIL)

11.1 ISL

ISL combines Incorrectness Logic with Separation Logic for **bug finding in heap-manipulating programs**.

Key idea: Under-approximate reasoning + separation logic for heap.

11.2 SepSIL

Symbolic execution with separation logic for bug finding:

- Tracks symbolic heap configurations
 - Under-approximate: only reachable states are reported
 - Can detect memory errors (dangling pointers, double free, leaks)
-

12 Lecture 11 — Abstract Interpretation: Basic Ideas

12.1 Core Concept

Abstract interpretation provides a **systematic framework** for designing sound static analyses:

1. Start with **concrete semantics** $\llbracket \cdot \rrbracket : \text{wp}(\Sigma) \rightarrow \text{wp}(\Sigma)$
2. Choose an **abstract domain** modeling properties of interest
3. Define **abstract semantics** $\llbracket \cdot \rrbracket^\#$ that executes commands on the abstract domain
4. Prove **correctness**: the abstract semantics soundly approximates the concrete
5. Compute fixpoints for loops

12.1.1 Why Abstraction?

Due to Rice's Theorem, we cannot have exact automatic analysis. We must:

- Trade precision for decidability
- Accept “don't know” answers (sound over-approximation)

12.1.2 Abstraction Levels

Concrete: infinite set of states

↓

Abstract: finite/simple property (e.g., sign of variable)

Soundness principle: If the analysis says YES, the property definitely holds.

13 Lecture 12 — Abstract Interpretation: Formal Foundations

13.1 Lattice Theory

A **complete lattice** $((L, \sqsubseteq, \bot, \top, \sqcup, \sqcap))$:

- $\sqsubseteq$: partial order
- $\bot$: least element
- $\top$: greatest element
- $\sqcup$: least upper bound (join)
- $\sqcap$: greatest lower bound (meet)

13.1.1 Concrete Domain

$((\wp(\Sigma), \subseteq, \emptyset, \Sigma, \cup, \cap))$ is a complete lattice.

13.2 Galois Connections

A **Galois connection** $((C, \alpha, \gamma, A))$ between concrete domain (C) and abstract domain (A) :

$$[\alpha(c) \sqsubseteq_A a \text{ iff } c \sqsubseteq_C \gamma(a)]$$

- $\alpha: C \rightarrow A$ — abstraction function
- $\gamma: A \rightarrow C$ — concretization function

Properties:

- α and γ are monotone
- $\gamma \circ \alpha$ is extensive ($x \sqsubseteq_C \gamma(\alpha(x))$)

- $(\alpha \circ \gamma)$ is reductive ($(\alpha(\gamma(y)) \sqsubseteq y)$)

13.3 Galois Insertion

A Galois insertion adds: $(\alpha \circ \gamma = \text{id}_A)$ (no redundant abstract elements).

13.4 Abstract Semantics Soundness

For each atomic command: $[\alpha \circ \llbracket c \rrbracket \sqsubseteq \llbracket c \rrbracket^{\#} \circ \alpha]$

Or equivalently: $[\llbracket c \rrbracket \circ \gamma \sqsubseteq \gamma \circ \llbracket c \rrbracket^{\#}]$

13.4.1 Fixpoint Approximation

For loops: $(\text{fix}(F) \sqsubseteq \gamma(\text{fix}(F^{\#})))$ where (F) and $(F^{\#})$ are the concrete and abstract transformers.

Kleene fixpoint theorem: $(\text{fix}(F) = \bigsqcup_{n \geq 0} F^n(\bot))$

13.4.2 Widening

To ensure termination of fixpoint computation:

- **Widening operator** (∇) : accelerates convergence
 - $(x \nabla y \sqsupseteq x \sqcup y)$
 - Every ascending chain stabilizes after finitely many widenings
-

14 Lecture 13 — Galois Connections

14.1 Properties of Galois Connections

1. α preserves arbitrary joins: $\alpha(\bigsqcup X) = \bigsqcup \alpha(X)$
2. γ preserves arbitrary meets: $\gamma(\bigsqcap Y) = \bigsqcap \gamma(Y)$
3. α is uniquely determined by γ and vice versa

14.1.1 Closure Operators


$(A \circ \gamma)$ is a **closure operator**:

- Monotone: $(x \sqsubseteq y \Rightarrow \rho(x) \sqsubseteq \rho(y))$
- Extensive: $(x \sqsubseteq \rho(x))$
- Idempotent: $(\rho(\rho(x)) = \rho(x))$

In a Galois insertion, $(\rho = \gamma \circ \alpha)$ is the **closure**.

15 Lecture 14 — Abstract Domains

15.1 Sign Domain



Where:

- $\perp = \emptyset$ (impossible)
- $\top = \mathbb{Z}$ (any value)
- $\mathbb{Z}_{\geq 0} = \{n \mid n \geq 0\}$
- $\mathbb{Z}_{\leq 0} = \{n \mid n \leq 0\}$
- $\mathbb{Z}_{> 0} = \{n \mid n > 0\}$
- $\mathbb{Z}_{< 0} = \{n \mid n < 0\}$
- $\mathbb{Z}_{= 0} = \{0\}$

15.1.1 Relational vs Non-relational Domains

- **Non-relational:** Track each variable independently (e.g., Sign, Interval)
- **Relational:** Track relationships between variables (e.g., Polyhedra, Octagons)

Domain	Expressiveness	Cost
Sign	Signs of variables	$\mathcal{O}(n)$
Interval	$x \in [l, u]$	$\mathcal{O}(n)$
Octagon	$ x - y \leq c$	$\mathcal{O}(n^2)$
Polyhedron	$\sum a_i x_i \leq c$	$\mathcal{O}(2^n)$
Congruence	$x \equiv a \pmod{m}$	$\mathcal{O}(n)$

16 Lecture 15 — Abstract Analysis (Fixpoint Computation)

16.0.1 Computing Abstract Semantics

1. Build **control flow graph** (CFG) with program points
2. Associate **abstract invariant** with each program point
3. Compute **least fixpoint** of the abstract semantic function

16.0.2 Worklist Algorithm

Initialize all program points to $\perp$ (or initial values for entry point).

Iterate:

1. Pick a program point whose abstract value changed
2. Apply abstract transformer to successors
3. Join new values with existing abstract values
4. If any successor's value changed, add to worklist

Until worklist is empty (fixpoint reached).

16.0.3 Widening in Practice

At loop head: merge old and new abstract values using ∇ to ensure termination.

Example (Interval widening): $[\ell_1, u_1] \nabla [\ell_2, u_2] = [\text{if } \ell_2 < \ell_1 \text{ then } -\infty \text{ else } \ell_1, \text{if } u_2 > u_1 \text{ then } +\infty \text{ else } u_1]$

17 Lecture 16 — Local Completeness Logic (LCL)

17.1 Completeness in Abstract Interpretation

Best abstract correct approximation (bca): $[\llbracket c \rrbracket^\alpha]_{\#_A} = \alpha \circ \llbracket c \rrbracket \circ \gamma$

Completeness equation: $[\forall P. \alpha(\llbracket c \rrbracket P) = \alpha(\llbracket c \rrbracket(\gamma(\alpha(P))))]$

Or equivalently: $[\alpha \circ \llbracket c \rrbracket = \alpha \circ \llbracket c \rrbracket \circ \gamma \circ \alpha]$

17.1.1 Local Completeness

A triple $(\{P\} \vdash c \{Q\})$ is **locally complete** if the completeness equation holds when starting from $\{P\}$.

17.1.2 LCL Triples

$\llbracket P \rrbracket^c \llbracket Q \rrbracket$

where $\llbracket \cdot \rrbracket^{\alpha_P}$ is the abstraction relative to property α_P .

18 Lecture 17 — Control Flow Analysis (CFA)

18.1 Introduction

CFA is a **constraint-based** static analysis technique for higher-order programs (functional languages, λ -calculus).

18.1.1 Goal

Given a program, determine **which functions may be called at each call site** and **which values may flow to which variables**.

18.1.2 0-CFA

The simplest CFA — **monovariant** (one abstract value per program point regardless of calling context).

Algorithm:

1. Assign each subexpression a label
2. Generate constraints based on program structure
3. Solve constraints via fixpoint computation

18.1.3 AST vs CFG

The **Abstract Syntax Tree (AST)** captures the syntactic structure of a program — what the program looks like. The **Control Flow Graph (CFG)** captures the possible execution paths — how the program may execute.

For simple imperative languages, building a CFG from an AST is straightforward because procedure calls explicitly name their targets. For higher-order languages, this becomes non-trivial: **functions are values**, so we often do not know at compile time which function is called at a given call site.

18.1.4 The Dynamic Dispatch Problem

Consider:

```
let f = fn x => x + 1;  
    g = fn y => y + 2;  
    h = fn z => z + 3  
in (f g) + (f h)
```

- Variable x in the body of f is a function variable
- At runtime, $x \in \{g, h\}$
- So $x + 1$ may target either g or h (from the two calls $(f\ g)$ and $(f\ h)$)

We cannot know the exact target of a call statically, so we compute a **safe approximation** — an over-approximation of the possible targets of each call. This is **Control Flow Analysis (CFA)**.

18.1.5 Interprocedural Analysis with Higher-Order Functions

In simple imperative languages:

- Construct a CFG for **each function**
- Glue them together via function calls and returns
- Calls have **statically known targets**

In higher-order languages:

- Several functions may be invoked at a call site
- Which functions are called depends on data flow
- But data flow analysis first requires a CFG!
- The boundary between control and data becomes unclear — **everything is both data and control**

CFA solves this circular dependency by approximating the call graph directly from program structure.

18.1.6 The FUN Language (Syntax)

The core functional language used for CFA:

```
\[ \begin{aligned} t &::= c \mid x \mid \texttt{fn } x \rightarrow e_0 \mid \\ &\texttt{fun } f, x \rightarrow e_0 \parallel e ::= t^{\ell} \mid (e_1; e_2)^{\ell} \mid \\ &(\texttt{if } e_0 \texttt{ then } e_1 \texttt{ else } e_2)^{\ell} \parallel \& \mid \\ &(\texttt{let } x = e_1 \texttt{ in } e_2)^{\ell} \mid (e_1 \texttt{ op } e_2)^{\ell} \\ \end{aligned} \]
```

Each subexpression carries a **label** $(\ell \text{ in } \texttt{Lab})$ identifying program points (call sites, expression occurrences).

18.1.7 Abstract Domains

The result of a 0-CFA analysis is a pair $((\hat{C}, \hat{\rho}))$:

- $(\hat{C} \text{ in } \texttt{Cache} = \texttt{Lab} \rightarrow \hat{V})$ — the **cache**, mapping each label to the set of function abstractions the subexpression may evaluate to
- $(\hat{\rho} \text{ in } \texttt{Env} = \texttt{Var} \rightarrow \hat{V})$ — the **abstract environment**, mapping each variable to the set of function abstractions it may be bound to
- $(\hat{v} \text{ in } \hat{V} = \texttt{wp}(\texttt{Term}))$ — **abstract values** as sets of function terms (only functions, no constants in pure CFA)

0-CFA means **monovariant**: no context information is considered; the same function set is used at all call sites.

18.1.8 Specification of a Solution

A guess $((\hat{C}, \hat{\rho}))$ is **acceptable** for expression (e) if it safely over-approximates all runtime behaviour. This is formalised by the **acceptability relation**:

$(\hat{C}, \hat{\rho}) \models e$

The $(\models)$ relation is defined by structural clauses for each syntactic form. It is a coinductively defined relation (to handle recursive function calls).

18.1.9 Acceptability Clauses (with Examples)

18.1.9.1 [con] Constants

$$[(\hat{C}, \hat{\rho}) \text{models } c^{\ell} \text{ iff } \emptyset \subseteq \hat{C}(\ell)]$$

Meaning: Constants do not evaluate to functions, so there are no demands on $(\hat{C}(\ell))$.

Example: $(e = 71^1)$ gives $(\hat{C}(1) = \emptyset)$.

18.1.9.2 [var] Variables

$$[(\hat{C}, \hat{\rho}) \text{models } x^{\ell} \text{ iff } \hat{\rho}(x) \subseteq \hat{C}(\ell)]$$

Meaning: Everything the variable (x) may be bound to must be included in what is observed at program point (ℓ) . Information flows from $(\hat{\rho})$ to $(\hat{C})$.

Example: $(e = x^1)$, and suppose $(\hat{\rho}(x) = \{\text{fn } y \mapsto y^3\})$. Then $(\hat{C}(1) \supseteq \{\text{fn } y \mapsto y^3\})$.

18.1.9.3 [fn] Function Abstraction

$$[(\hat{C}, \hat{\rho}) \text{models } (\text{fn } x \mapsto e_0)^{\ell} \text{ iff } \{\text{fn } x \mapsto e_0\} \subseteq \hat{C}(\ell)]$$

Meaning: The function term itself must be included in $(\hat{C}(\ell))$ as it may be used as a value at that program point. The function body (e_0) is **not** checked here — it will be checked at application time.

Example: $(e = (\text{fn } x \mapsto x^1)^2)$ gives $(\hat{C}(2) \supseteq \{\text{fn } x \mapsto x^1\})$.

18.1.9.4 [fun] Recursive Function

$$[(\hat{C}, \hat{\rho}) \text{models } (\text{fun } f, x \mapsto e_0)^{\ell} \text{ iff } \{\text{fun } f, x \mapsto e_0\} \subseteq \hat{C}(\ell)]$$

Same as [fn], but the function may be self-referential.

18.1.9.5 [if] Conditional

$$\llbracket (\hat{C}, \hat{\rho}) \models \text{if } t_0^{\ell_0} \text{ then } t_1^{\ell_1} \text{ else } t_2^{\ell_2} \rrbracket^{\ell} \text{ iff } \begin{cases} (\hat{C}, \hat{\rho}) \models t_0^{\ell_0} \wedge (\hat{C}, \hat{\rho}) \models t_1^{\ell_1} ; \text{and}; \hat{C}(\ell_1) \subseteq \hat{C}(\ell) \wedge (\hat{C}, \hat{\rho}) \models t_2^{\ell_2} ; \text{and}; \hat{C}(\ell_2) \subseteq \hat{C}(\ell) \end{cases}$$

Meaning: All subexpressions are checked; values from both branches are merged (the condition is ignored — this is an over-approximation).

Example: $\llbracket e = \text{if } (x^1 > 0^2)^3 \text{ then } y \rightarrow y^4)^5 \text{ else } z \rightarrow z^6)^7)^8 \rrbracket$ gives $(\hat{C}(5) \subseteq \hat{C}(8))$ and $(\hat{C}(7) \subseteq \hat{C}(8))$, merging both possible closures.

18.1.9.6 [op] Binary Operation

$$\llbracket (\hat{C}, \hat{\rho}) \models (t_1^{\ell_1} \text{ op } t_2^{\ell_2})^{\ell} \rrbracket \text{ iff } \begin{cases} (\hat{C}, \hat{\rho}) \models t_1^{\ell_1} \wedge (\hat{C}, \hat{\rho}) \models t_2^{\ell_2} \end{cases}$$

Meaning: Sub-expressions are checked; but no data demands on $(\hat{C}(\ell))$ — pure CFA does not track data values.

Example: $\llbracket e = (7^1 + 4^2)^3 \rrbracket$ gives $(\hat{C}(3) = \emptyset)$ (no functions flow here).

18.1.9.7 [let] Let Binding

$$\llbracket (\hat{C}, \hat{\rho}) \models \text{let } x = t_1^{\ell_1} \text{ in } t_2^{\ell_2} \rrbracket^{\ell} \text{ iff } \begin{cases} (\hat{C}, \hat{\rho}) \models t_1^{\ell_1} \wedge (\hat{C}, \hat{\rho}) \models t_2^{\ell_2} \wedge \hat{C}(\ell_1) \subseteq \hat{\rho}(x) \wedge \hat{C}(\ell_2) \subseteq \hat{C}(\ell) \end{cases}$$

Meaning: Two flows are enforced:

1. **Binding:** values produced by (t_1) (at (ℓ_1)) flow to the variable (x)
2. **Evaluation:** values produced by the body (t_2) (at (ℓ_2)) flow to the result of the let-expression (at (ℓ))

Example: $\llbracket e = (\text{let } f = (\text{fn } x \rightarrow x^1)^2 \text{ in } (f^3; 3^4)^5)^6 \rrbracket$ gives $(\hat{C}(2) \subseteq \hat{\rho}(f))$ and $(\hat{C}(5) \subseteq \hat{C}(6))$.

18.1.9.8 [app] Function Application

$$\llbracket (\hat{C}, \hat{\rho}) \models (t_1^{\ell_1}; t_2^{\ell_2})^{\ell} \text{ iff } \begin{cases} (\hat{C}, \hat{\rho}) \models t_1^{\ell_1} \wedge (\hat{C}, \hat{\rho}) \models t_2^{\ell_2} \wedge \forall x \rightarrow t_0^{\ell_0} \text{ in } \hat{C}(\ell_1): \quad (\hat{C}, \hat{\rho}) \models t_0^{\ell_0} \wedge \quad \hat{C}(\ell_2) \subseteq \hat{\rho}(x) \wedge \quad \hat{C}(\ell_0) \subseteq \hat{C}(\ell) \wedge \forall f, x \rightarrow t_0^{\ell_0} \text{ in } \hat{C}(\ell_1): \quad (\hat{C}, \hat{\rho}) \models t_0^{\ell_0} \wedge \quad \hat{C}(\ell_2) \subseteq \hat{\rho}(x) \wedge \quad \hat{C}(\ell_0) \subseteq \hat{C}(\ell) \wedge \quad \{f, x \rightarrow t_0^{\ell_0}\} \subseteq \hat{\rho}(f) \end{cases} \rrbracket$$

Meaning: For each function term that may reach (ℓ_1) (the operator position):

1. The function body (t_0) must be analysed
2. The actual argument (at (ℓ_2)) flows to the formal parameter (x)
3. The result of the body (at (ℓ_0)) flows to the result of the application (at (ℓ))
4. For recursive functions, the function itself also flows to its name (f)

18.1.10 Summary of Acceptability Clauses

Construct	Clause
$\llbracket c^{\ell} \rrbracket$	$(\emptyset \subseteq \hat{C}(\ell))$
$\llbracket x^{\ell} \rrbracket$	$(\hat{\rho}(x) \subseteq \hat{C}(\ell))$
$\llbracket (\text{fn } x \rightarrow e_0)^{\ell} \rrbracket$	$(\{\text{fn } x \rightarrow e_0\} \subseteq \hat{C}(\ell))$
$\llbracket (\text{fun } f, x \rightarrow e_0)^{\ell} \rrbracket$	$(\{\text{fun } f, x \rightarrow e_0\} \subseteq \hat{C}(\ell))$
$\llbracket (\text{if } t_0 \text{ then } t_1 \text{ else } t_2)^{\ell} \rrbracket$	Sub-checks + $(\hat{C}(\ell_1) \subseteq \hat{C}(\ell) \wedge \hat{C}(\ell_2) \subseteq \hat{C}(\ell))$

Construct	Clause
	$\hat{C}(\ell_2) \subseteq \hat{C}(\ell_1)$
$((t_1 \text{ op } t_2)^\ell)$	Sub-checks only
$((\text{let } x = t_1 \text{ in } t_2)^\ell)$	Sub-checks + $\hat{C}(\ell_1) \subseteq \hat{\rho}(x) \wedge \hat{C}(\ell_2) \subseteq \hat{C}(\ell_1)$
$((t_1; t_2)^\ell)$	Sub-checks + $(\forall \text{fn } x \rightarrow t_0^{\ell_0} \text{ in } \hat{C}(\ell_1):) \wedge \hat{C}(\ell_2) \subseteq \hat{\rho}(x) \wedge \hat{C}(\ell_0) \subseteq \hat{C}(\ell_1)$

18.1.11 Example: Identity Function Composition

Expression: $[e = ((\text{fn } x \rightarrow x^1)^2; (\text{fn } y \rightarrow y^3)^4)^5]$

Runtime behaviour: $((\lambda x. x)(\lambda y. y) \text{ to } (\lambda y. y))$ — evaluates to the identity function.

CFA guess $((\hat{C}_e, \hat{\rho}_e))$:

- $(\hat{C}(1) = \{\text{fn } y \rightarrow y^3\}, \hat{C}(4) = \{\text{fn } y \rightarrow y^3\}, \hat{C}(5) = \{\text{fn } y \rightarrow y^3\})$
- $(\hat{C}(2) = \{\text{fn } x \rightarrow x^1\}, \hat{C}(3) = \emptyset)$
- $(\hat{\rho}(x) = \{\text{fn } y \rightarrow y^3\}, \hat{\rho}(y) = \emptyset)$

Verification:

1. [fn] on label 2: $(\{\text{fn } x \rightarrow x^1\} \subseteq \hat{C}(2)) \checkmark$
2. [fn] on label 4: $(\{\text{fn } y \rightarrow y^3\} \subseteq \hat{C}(4)) \checkmark$

3. [app] on label 5: Since $\{\text{fn } x \rightarrow x^1 \in C\}$ (2):
- $(C(4) \subseteq \rho(x))$: $\{\text{fn } y \rightarrow y^3\} \subseteq \rho(x)$ ✓
 - $(C(1) \subseteq C(5))$: $\{\text{fn } y \rightarrow y^3\} \subseteq C(5)$ ✓
4. [var] on label 1: $(\rho(x) \subseteq C(1))$: $\{\text{fn } y \rightarrow y^3\} \subseteq C(1)$ ✓
-

18.1.12 Flow Logic Approach

CFA uses **Flow Logic** — a declarative approach that separates specification from computation:

1. **Specification** (acceptability relation $(models)$): describes when analysis results are acceptable
2. **Computation** (constraint solving): computes the least solution

The approach has four steps:

1. Define acceptability (specification) — what is a correct analysis?
2. Define syntax-directed rules — more computationally oriented
3. Generate constraints — a finite set of set-inclusion constraints
4. Solve constraints — compute the least fixpoint

18.1.13 Historical Context

- **Reynolds**: early analyses of LISP programs
 - **Jones**: first to study lambda expressions, introduced control flow analysis
 - **Shivers**: formalized CFA for Scheme, basis for constraint-based approaches
 - **Nielson, Nielson, Hankin**: Principles of Program Analysis [Chapter 3] — modern constraint-based formulation
-

19 Lecture 18 — CFA Exercises

19.1 Exercise 1: Identity Function

Expression: $\llbracket e \trianglerighteq (\lambda x. x \rightarrow (x^1 + 12^2)^3)^4 \rrbracket; (3)^5)^6 \rrbracket$

CFA guess $((\hat{C}, \hat{\rho}))$:

Label	$(\hat{C}(\ell))$
$(\hat{C}(1))$	$(\emptyset)$
$(\hat{C}(2))$	$(\emptyset) \ ((12))$
$(\hat{C}(3))$	$(\emptyset) \ ((x+12))$
$(\hat{C}(4))$	$(\{\lambda x. x \rightarrow (x^1 + 12^2)^3\})$
$(\hat{C}(5))$	$(\emptyset) \ ((3))$
$(\hat{C}(6))$	$(\emptyset)$

$(\hat{\rho}(x) = \emptyset)$

Verification using $((\hat{C}, \hat{\rho}) \models e)$:

- $((\hat{C}, \hat{\rho}) \models \lambda x. x \rightarrow (x^1 + 12^2)^3)^4$: $(\{\lambda x. x \rightarrow (x^1 + 12^2)^3\} \subseteq \hat{C}(4)) \checkmark$
- $((\hat{C}, \hat{\rho}) \models (3)^5)$: $(\emptyset \subseteq \hat{C}(5)) \checkmark$
- [app] for $((\hat{C}, \hat{\rho}) \models (t_1)^4 (3)^5)^6$:
 - $(\hat{C}(5) \subseteq \hat{\rho}(x)) \checkmark$ (both $\emptyset$)
 - $(\hat{C}(3) \subseteq \hat{C}(6)) \checkmark$ (both $\emptyset$)
- [var] for $(\hat{\rho}(x) \subseteq \hat{C}(1)) \checkmark$ (both $\emptyset$)
- [con] for $((12)^2)$: $(\emptyset \subseteq \hat{C}(2)) \checkmark$

19.2 Exercise 2: Higher-Order Function Composition

Expression: $\lambda e \triangleq ((\text{fn } f \rightarrow (f^1; 76^2)^3 + (f^4; 77^5)^6)^7)^8 \lambda (\text{fn } a \rightarrow a^9)^{10} \lambda$

CFA guess $((\hat{C}, \hat{\rho}))$:

- $(\hat{C}(1) = \{\text{fn } a \rightarrow a^9\}, \hat{C}(4) = \{\text{fn } a \rightarrow a^9\})$
- $(\hat{C}(2) = \text{emptyset}, \hat{C}(3) = \text{emptyset}(76))$
- $(\hat{C}(5) = \text{emptyset}(77), \hat{C}(6) = \text{emptyset}(77))$
- $(\hat{C}(7) = \text{emptyset}(76+77), \hat{C}(8) = \{\text{fn } f \rightarrow (f^1 76^2)^3 + (f^4 77^5)^6\})$
- $(\hat{C}(9) = \text{emptyset}, \hat{C}(10) = \{\text{fn } a \rightarrow a^9\}, \hat{C}(11) = \text{emptyset}, \hat{C}(12) = \{\text{fn } f \rightarrow \dots\})$
- $(\hat{\rho}(f) = \{\text{fn } a \rightarrow a^9\}, \hat{\rho}(a) = \text{emptyset}(76, 77))$

Verification (key steps):

1. [fn] label 8: $(\{\text{fn } f \rightarrow \dots\} \subseteq \hat{C}(8))$
✓
2. [fn] label 10: $(\{\text{fn } a \rightarrow a^9\} \subseteq \hat{C}(10))$ ✓
3. [app] label 12: $(\hat{C}(10) \subseteq \hat{\rho}(f) \wedge \hat{C}(8) \subseteq \hat{C}(12))$ ✓
4. For body $((f^1 76^2)^3)$:
 - [var] $(\hat{\rho}(f) \subseteq \hat{C}(1))$ ✓
 - [con] $(\text{emptyset} \subseteq \hat{C}(2))$ ✓
 - [app] $(\hat{C}(2) \subseteq \hat{\rho}(a) \wedge \hat{C}(9) \subseteq \hat{C}(3))$ ✓
5. For body $((f^4 77^5)^6)$: symmetric ✓

19.3 Exercise 3: Let Bindings with Multiple Functions

Expression:
$$\begin{aligned} & e \triangleq \lambda; \&(\text{let } f = \\ & (\text{fn } x \rightarrow (x^1; 1^2)^3)^4 \& \&(\text{in } (\text{let } g \\ & = (\text{fn } y \rightarrow (y^5 + 2^6)^7)^8 \& \&(\text{in } (\text{let } h = \\ & (\text{fn } z \rightarrow (z^9 + 3^{10})^{11})^{12} \& \&(\text{in } \\ & ((f^{13}; g^{14})^{15} + (f^{16}; h^{17})^{18})^{19})^{20})^{21})^{22} \\ & \end{aligned}$$

This is the earlier dynamic dispatch example. The 0-CFA result will merge:

- $\hat{C}(1) = \{ \text{fn } y \rightarrow (y^5 + 2^6)^7, \text{fn } z \rightarrow (z^9 + 3^{10})^{11} \}$ (both functions flow to (x))
- $\hat{C}(15) = \{ \text{fn } y \rightarrow (y^5 + 2^6)^7, \text{fn } z \rightarrow (z^9 + 3^{10})^{11} \}$ (both results possible)

Key observation: 0-CFA cannot distinguish the two calling contexts for (f) : both g and h flow to parameter (x) .

19.4 Semantic Correctness

19.4.1 Operational Semantics for FUN

To prove that acceptable CFA results are semantically correct, we define a small-step structural operational semantics for FUN.

Values and environments:

- $(v \text{ in } \text{Val})$: values (constants or closures)
- $(\rho \text{ in } \text{Env})$: concrete environments (mapping variables to values)
- $(v ::= c \text{ mid } \langle t, \rho \rangle)$ (closures)
- $(\rho ::= [] \text{ mid } \rho[x \mapsto v])$

Intermediate expressions:

$$[ie ::= it^{\ell} \text{ mid } ie_0; ie_1 \text{ mid } (\text{let } x = ie_1 \text{ in } ie_2 \text{ mid } \rho); ie]$$

Selected transition rules:

- $[var] \ (\rho \vdash x^{\ell} \text{ to } v^{\ell}) \text{ if } (\rho(x) = v)$

- $[\text{fn } \lambda x. e_0] \vdash (\text{fn } x \mapsto e_0) \text{ell} \rightarrow \text{angle}$
 $(\text{fn } x \mapsto e_0, \rho_0 \text{angle}^{\text{ell}})$ where $(\rho_0 = \rho \upharpoonright_{\text{FV}(\text{fn } x \mapsto e_0)})$
- $[\text{let } x = v_1 \text{ in } e_2] \vdash (\text{let } x = v_1 \text{ in } e_2) \text{ell} \rightarrow$
 $(\rho_0[x \mapsto v_1]; e_2) \text{ell}$ where $(\rho_0 = \rho \upharpoonright_{\text{FV}(e_2)})$

19.4.2 Subject Reduction

Theorem (Subject Reduction): If $(\hat{C}, \hat{\rho}) \models ie$ and $\rho \vdash ie \rightarrow ie'$ (with (ρ) agreeing with $(\hat{\rho})$), then $(\hat{C}, \hat{\rho}) \models ie'$.

The analysis information is preserved under computation — it is a sound over-approximation of all reachable states.

20 Lecture 19 — Syntax-Directed CFA

20.1 Motivation

The original $(\models)$ relation has a problem: it is **coinductively defined** because of circular dependencies in recursive functions. This makes it non-constructive — we cannot directly compute from it.

The **syntax-directed** version $(\models_s)$ addresses this:

- It analyses each function body **once**, at its definition site
- It does not wait for applications to trigger body analysis
- It is fully determined by the **structure** of the expression (hence “syntax-directed”)
- It eliminates the need for coinduction (no circular dependencies)

Key property: $(\models_s)$ is a **safe approximation** of $(\models)$:
 $(\hat{C}, \hat{\rho}) \models_s e \Rightarrow (\hat{C}, \hat{\rho}) \models e$
 $(\models e \Rightarrow \text{for program terms})$

20.1.1 Syntax-Directed Clauses

20.1.1.1 [fn] (modified)

$$\llbracket (\hat{C}, \hat{\rho}) \rrbracket_{\text{models}_s} (\text{fn } x \rightarrow e_0)^\ell \text{ iff } \begin{cases} \llbracket \text{fn } x \rightarrow e_0 \rrbracket \subseteq \hat{C}(\ell) \\ (\hat{C}, \hat{\rho}) \rrbracket_{\text{models}_s} e_0 \end{cases}$$

Difference from $\llbracket (\text{models}) \rrbracket$: The function body $\llbracket (e_0) \rrbracket$ is **now analysed at definition time**, even if the function is never applied.

20.1.1.2 [fun] (modified)

$$\llbracket (\hat{C}, \hat{\rho}) \rrbracket_{\text{models}_s} (\text{fun } f, x \rightarrow e_0)^\ell \text{ iff } \begin{cases} \llbracket \text{fun } f, x \rightarrow e_0 \rrbracket \subseteq \hat{C}(\ell) \\ (\hat{C}, \hat{\rho}) \rrbracket_{\text{models}_s} e_0 \llbracket \text{fun } f, x \rightarrow e_0 \rrbracket \subseteq \hat{\rho}(f) \end{cases}$$

Self-binding is enforced immediately.

20.1.1.3 [app] (modified)

$$\llbracket (\hat{C}, \hat{\rho}) \rrbracket_{\text{models}_s} (t_1^\ell; t_2^\ell)^\ell \text{ iff } \begin{cases} (\hat{C}, \hat{\rho}) \rrbracket_{\text{models}_s} t_1^\ell \llbracket (\hat{C}, \hat{\rho}) \rrbracket_{\text{models}_s} t_2^\ell \\ \forall (\text{fn } x \rightarrow t_0^\ell) \text{ in } \hat{C}(\ell_1): \llbracket \hat{C}(\ell_2) \rrbracket \subseteq \hat{\rho}(x) \wedge \llbracket \hat{C}(\ell_0) \rrbracket \subseteq \hat{C}(\ell) \\ \forall (\text{fun } f, x \rightarrow t_0^\ell) \text{ in } \hat{C}(\ell_1): \llbracket \hat{C}(\ell_2) \rrbracket \subseteq \hat{\rho}(x) \wedge \llbracket \hat{C}(\ell_0) \rrbracket \subseteq \hat{C}(\ell) \end{cases}$$

Difference: The body has already been analysed by [fn] at definition time, so there is no $\llbracket (\hat{C}, \hat{\rho}) \rrbracket_{\text{models}_s} t_0^\ell$ here.

All other clauses are unchanged from $\llbracket (\text{models}) \rrbracket$ (just replace $\llbracket (\text{models}) \rrbracket$ with $\llbracket (\text{models}_s) \rrbracket$).

20.1.2 Worked Example: Recursive Function

Consider:
$$\llbracket \text{loop} \rrbracket \triangleq \llbracket \text{let } g = (\text{fun } f, x \rightarrow (f^1; (\text{fn } y \rightarrow y^2)^3)^4)^5 \text{ in } (g^6; (\text{fn } z \rightarrow z^7)^8)^9 \rrbracket^{10}$$

Step-by-step validation with $\backslash(\backslash\text{models_s})$:

1. $\backslash(\backslash\text{hat}\{C\}_{lp}, \backslash\text{hat}\{\rho\}_{lp}) \backslash\text{models_s } \backslash\text{text}\{\text{loop}\}^{\{10\}}$:
 - [let]: check body $\backslash(\backslash\text{texttt}\{\text{fun } f, x \rightarrow \dots\}^5)$ and $\backslash((g^6; (\text{texttt}\{\text{fn } z \rightarrow z^7)^8)^9)$
 - $\backslash(\backslash\text{hat}\{C\}_{lp}(5) \subseteq \backslash\text{hat}\{\rho\}_{lp}(g))$ and $\backslash(\backslash\text{hat}\{C\}_{lp}(9) \subseteq \backslash\text{hat}\{C\}_{lp}(10))$
2. [fun] on label 5: $\backslash(\backslash\text{texttt}\{\text{fun } f, x \rightarrow \dots\} \subseteq \backslash\text{hat}\{C\}_{lp}(5))$ and $\backslash(\backslash\text{texttt}\{\text{fun } f, x \rightarrow \dots\} \subseteq \backslash\text{hat}\{\rho\}_{lp}(f))$, and analyse body $\backslash((f^1; (\text{texttt}\{\text{fn } y \rightarrow y^2)^3)^4)$
3. [app] on label 4 (body): $\backslash(\backslash\text{texttt}\{\text{fun } f, x \rightarrow \dots \text{in } \backslash\text{hat}\{C\}(1))$ triggers:
 - $\backslash(\backslash\text{hat}\{C\}(3) \subseteq \backslash\text{hat}\{\rho\}_{lp}(x))$
 - $\backslash(\backslash\text{hat}\{C\}(4) \subseteq \backslash\text{hat}\{C\}(4))$ (immediate)
4. [fn] on label 3: $\backslash(\backslash\text{texttt}\{\text{fn } y \rightarrow y^2\} \subseteq \backslash\text{hat}\{C\}_{lp}(3))$
5. [app] on label 9: with $\backslash(\backslash\text{hat}\{C\}(6) = \backslash\{g\})$:
 - $\backslash(\backslash\text{hat}\{C\}(8) \subseteq \backslash\text{hat}\{\rho\}_{lp}(x))$
 - $\backslash(\backslash\text{hat}\{C\}(4) \subseteq \backslash\text{hat}\{C\}(9))$

The solution is acceptable under $\backslash(\backslash\text{models_s})$ — no circular dependency, no need for coinduction.

20.1.3 Uniqueness of $\backslash(\backslash\text{models_s})$

The syntax-directed specification is **deterministic**: there is only one relation $\backslash(\backslash\text{models_s})$ satisfying the clauses. Given the structural nature of the definition, any two relations $\backslash(\backslash\text{models}'_s)$ and $\backslash(\backslash\text{models}''_s)$ that satisfy the clauses must be the same.

Proof sketch (structural induction): For any $\backslash(e)$,

- Base case $\backslash(c^{\backslash\text{ell}})$: both relations satisfy $\backslash(\backslash\text{emptyset} \subseteq \backslash\text{hat}\{C\}(\text{ell}))$ — trivially equivalent
- Base case $\backslash(x^{\backslash\text{ell}})$: both require $\backslash(\backslash\text{hat}\{\rho\}(x) \subseteq \backslash\text{hat}\{C\}(\text{ell}))$ — equivalent
- Inductive step $\backslash(\backslash\text{texttt}\{\text{fn } x \rightarrow e_0\}^{\backslash\text{ell}})$: both require $\backslash(\backslash\text{texttt}\{\text{fn } x \rightarrow e_0\} \subseteq \backslash\text{hat}\{C\}(\text{ell}))$ and $\backslash(\text{models_s } e_0)$ — equivalence by IH on $\backslash(e_0)$

- All other cases analogous

Therefore, the least/greatest fixpoint distinction is irrelevant for $\models$.

20.1.4 Counterexample: Non-Syntax-Directed Version

For the original $\models$ (non-syntax-directed), different relations can satisfy the same clauses. Example:

$[a \trianglelefteq 0^1; 0^2)^3, \quad e \trianglelefteq (\text{fn } x \rightarrow a^4)^5]$

Suppose $\hat{C}(1) = \{\text{fn } x \rightarrow a^4\}$, $\hat{C}(2) = \hat{C}(3) = \hat{\rho}(x) = \emptyset$. Then $(\hat{C}, \hat{\rho}) \models a^3$ can be either true or false (because the body (a) has a circular dependency). Both interpretations satisfy the $\models$ clauses, showing that $\models$ is not unique.

20.1.5 Existence of Solutions

Theorem: For all $(e \in \text{Exp})$, the set $\{(\hat{C}, \hat{\rho}) \mid (\hat{C}, \hat{\rho}) \models e\}$ is a **Moore family** (closed under greatest lower bounds).

Corollaries:

1. Every expression (e) admits at least one CFA (take the intersection over the empty set $(Y' = \emptyset)$)
2. Every expression (e) has a **least** (most precise) CFA: intersect all acceptable analyses

20.1.6 Moore Family Proof (Idea)

The proof proceeds by coinduction on (e) :

- Assume $(\forall i \in I; (\hat{C}_i, \hat{\rho}_i) \models e)$
- Show that $(\hat{C}, \hat{\rho}) = \sqcap_i (\hat{C}_i, \hat{\rho}_i)$ satisfies each clause of $\models$
- The pointwise intersection $(\hat{C}(\ell) = \bigcap_i \hat{C}_i(\ell), \hat{\rho}(x) = \bigcap_i \hat{\rho}_i(x))$ preserves all set inclusions

20.1.7 Preservation of Solutions (Syntax-Directed vs Original)

The syntax-directed specification preserves solutions of the original:

$$[(\hat{C}, \hat{\rho}) \models e] \rightarrow (\hat{C}, \hat{\rho}) \models e$$

Proof idea: A simple structural induction on (e) shows that any pair accepted by $(\models_s)$ also satisfies all the clauses of $(\models)$. The only difference is when function bodies are checked: $(\models_s)$ does it upfront, $(\models)$ does it at application time. Since all bodies are checked by $(\models_s)$, they will also be available when $(\models)$ needs them.

21 Lecture 20 — Constraint-Based 0-CFA

21.1 From Semantics to Constraints

The syntax-directed specification $(\models_s)$ can be turned into a **finite set of constraints**. The idea is to replace:

- Occurrences of $(\hat{C})$ with constraint variable $(C(\ell))$
- Occurrences of $(\hat{\rho})$ with constraint variable $(r(x))$

The function $(C^*[!e!])$ maps an expression to a set of constraints of two forms:

1. **Direct constraints:** $(\text{lhs} \subseteq \text{rhs})$
2. **Conditional constraints:** $(\{t\} \subseteq \text{rhs}' \rightarrow \text{lhs} \subseteq \text{rhs})$

Where $(\text{lhs}, \text{rhs}) \in \{C(\ell), r(x), \{t\}\}$.

21.2 Constraint Generation Rules

21.2.0.1 [con] Constants

$$[(\hat{C}, \hat{\rho}) \text{models}_s c^{\ell} \vdash \text{Rightarrow}; C^*[\![c^{\ell}]\!]] = \emptyset$$

Constants generate no constraints.

21.2.0.2 [var] Variables

$$[(\hat{C}, \hat{\rho}) \text{models}_s x^{\ell} \vdash \text{Rightarrow}; C^*[\![x^{\ell}]\!]] = \{ r(x) \subseteq C(\ell) \}$$

21.2.0.3 [fn] Functions

$$[(C^*[\![\text{fn } x \mapsto e_0]^{\ell}]\!]] = \{ \text{fn } x \mapsto e_0 \subseteq C(\ell) \} \cup C^*[\![e_0]^{\ell}]\!]$$

21.2.0.4 [fun] Recursive Functions

$$[(C^*[\![\text{fn } f, x \mapsto e_0]^{\ell}]\!]] = \{ \text{fn } f, x \mapsto e_0 \subseteq C(\ell); \text{fn } f, x \mapsto e_0 \subseteq r(f) \} \cup C^*[\![e_0]^{\ell}]\!]$$

21.2.0.5 [app] Application

$$\begin{aligned} &[(\text{begin{aligned}} C^*[\![t_1^{\ell_1}; t_2^{\ell_2}]^{\ell}]\!]] = & C^*[\![t_1^{\ell_1}]\!] \cup C^*[\![t_2^{\ell_2}]\!] \cup \{ \{t\} \subseteq C(\ell_1) \mapsto C(\ell_2) \subseteq r(x) \mid t = (\text{fn } x \mapsto t_0^{\ell_0}) \\ &\text{in } \text{Term}^* \} \cup \{ \{t\} \subseteq C(\ell_1) \mapsto C(\ell_0) \subseteq C(\ell) \mid t = (\text{fn } x \mapsto t_0^{\ell_0}) \\ &\text{in } \text{Term}^* \} \cup \{ \{t\} \subseteq C(\ell_1) \mapsto C(\ell_2) \subseteq r(x) \mid t = (\text{fn } f, x \mapsto t_0^{\ell_0}) \\ &\text{in } \text{Term}^* \} \cup \{ \{t\} \subseteq C(\ell_1) \mapsto C(\ell_0) \subseteq C(\ell) \mid t = (\text{fn } f, x \mapsto t_0^{\ell_0}) \\ &\text{in } \text{Term}^* \} \end{aligned}$$

21.2.0.6 [let] Let Binding

$$[(C^*[\![\text{let } x = t_1^{\ell_1} \text{ in } t_2^{\ell_2}]^{\ell}]\!]] = C^*[\![t_1^{\ell_1}]\!] \cup C^*[\![t_2^{\ell_2}]\!] \cup \{ C(\ell_1) \subseteq r(x); C(\ell_2) \subseteq C(\ell) \}$$

21.3 Worked Example: Constraint Generation

Expression: $\{ (\text{fn } x \rightarrow x^1)^2 ; (\text{fn } y \rightarrow y^3)^4 \}^5$

Term set: $\{\text{Term}\}^* = \{ (\text{fn } x \rightarrow x^1, ; \text{fn } y \rightarrow y^3) \}$

Generated constraints:

From [fn] on label 2: $\{ (\text{fn } x \rightarrow x^1) \} \subseteq C(2)$
 From [fn] on label 4: $\{ (\text{fn } y \rightarrow y^3) \} \subseteq C(4)$
 From [var] on label 1: $\{ r(x) \} \subseteq C(1)$ From [var] on label 3: $\{ r(y) \} \subseteq C(3)$ From [app] on label 5 (conditional constraints):

- $\{ (\text{fn } x \rightarrow x^1) \} \subseteq C(2) \rightarrow C(4) \subseteq r(x)$
- $\{ (\text{fn } x \rightarrow x^1) \} \subseteq C(2) \rightarrow C(1) \subseteq C(5)$
- $\{ (\text{fn } y \rightarrow y^3) \} \subseteq C(2) \rightarrow C(4) \subseteq r(y)$
- $\{ (\text{fn } y \rightarrow y^3) \} \subseteq C(2) \rightarrow C(3) \subseteq C(5)$

21.4 Preservation of Solutions

Proposition: If $(\hat{C}, \hat{\rho}) \subseteq (\hat{C}_{\text{top}}, \hat{\rho}_{\text{top}})$ and $(\hat{C}, \hat{\rho}) \models_{C^*} \neg[e^*]$, then $(\hat{C}, \hat{\rho}) \models_{e^*}$.

Proof sketch: By structural induction on (e^*) :

- For each sub-expression, the constraints in $(C^*[\neg[e^*]])$ encode the exact conditions required by $(\models_s)$
- The condition $(\hat{C}, \hat{\rho}) \subseteq (\hat{C}_{\text{top}}, \hat{\rho}_{\text{top}})$ ensures $(\hat{C}(\ell_1) \subseteq \text{Term}^*)$ for the application case
- Base cases (constants, variables) follow directly from the constraint definitions
- Inductive cases follow from the inductive hypothesis on sub-expressions

Conversely: If $((\hat{C}, \hat{\rho}) \models_{se} e)$, then $((\hat{C}, \hat{\rho}) \models_{c} C^{\llbracket e^* \rrbracket})$.

21.5 Solving Constraints via Fixpoint Computation

Finding the least solution of the constraints amounts to computing the **least fixed point** of a monotone function:

$[F^* : \text{Cache}^* \times \text{Env}^* \rightarrow \text{Cache}^* \times \text{Env}^*]$

The function (F^*) propagates constraints over (C) and (r) until saturation.

21.5.1 Complexity

Estimate	Direct	Conditional
Naive	$(O(n^2))$	$(O(n^4))$
Refined	$(O(n))$	$(O(n^2))$

Where $(n = |e^*|)$ (size of the expression). Every construct except applications gives one constraint; applications may give $(O(n))$ conditional constraints.

Solving time:

- Least fixpoint via naive iteration: $(O(n^5))$
- With graph formulation: $(O(n^3))$

21.5.2 Constraint Graph

A constraint system can be visualized as a **constraint graph**:

Nodes:

- $(C(\ell))$ for each label $(\ell \in \text{Lab}^*)$
- $(r(x))$ for each variable $(x \in \text{Var}^*)$

Edges:

- Each direct constraint $(p_1 \subseteq p_2)$ adds an edge $((p_1, p_2))$

- Each conditional constraint $\{t\} \subseteq p \rightarrow p_1 \subseteq p_2$ adds:
 - A **candidate edge** $((p_1, p_2))$ with “trigger” $\{t\} \subseteq p$
 - An edge $((p, p_2))$ for trigger propagation

21.5.3 Example Constraint Graph

For our running example:

```

{r(x) ⊆ C(1)}    {r(y) ⊆ C(3)}
{idx} ⊆ C(2)      {idy} ⊆ C(4)
{idx} ⊆ C(2) ⇒ C(4) ⊆ r(x)
{idx} ⊆ C(2) ⇒ C(1) ⊆ C(5)
{id y} ⊆ C(2) ⇒ C(4) ⊆ r(y)
{id y} ⊆ C(2) ⇒ C(3) ⊆ C(5)

```

Graph:

```

{idx} → C(2) → r(x) → C(1)
{id y} → C(4) → r(y) → C(3)
          C(2) → C(5) (conditional, triggered by idx)
          C(2) → C(5) (conditional, triggered by idy)

```

21.5.4 Solver Algorithm

Input: A set of constraints $(C^*[e^*])$ **Output:** The least solution $(\hat{C}, \hat{\rho})$ **Data structures:**

- (W) : worklist (nodes whose data should be propagated)
- $(D[p])$: data array (current abstract value for node (p))
- $(E[p])$: edge array (constraints that node (p) may affect)

21.5.4.1 Step 1: Initialize

```

for q in Vars:
    D[q] := []
    E[q] := []
W := []

```

21.5.4.2 Step 2: Build the Graph

```

for cc in C^*[e^*]:
    match cc:
    | {t} ⊆ p          -> add(p, {t})

```

```

|  $p_1 \subseteq p_2$           ->  $E[p_1] := cc :: E[p_1]$ 
|  $\{t\} \subseteq p \Rightarrow p_1 \subseteq p_2$  ->  $E[p_1] := cc :: E[p_1];$ 
                                    $E[p] := cc :: E[p]$ 

```

Where $\text{add}(q, d)$ inserts (d) into $(D[q])$ and adds (q) to (W) if (d) is new.

21.5.4.3 Step 3: Propagate

```

while  $W \neq \text{nil}$ :
   $q := \text{head}(W); W := \text{tail}(W);$ 
  for  $cc$  in  $E[q]$ :
    case  $cc$  of:
      |  $p_1 \subseteq p_2$ :
         $\text{add}(p_2, D[p_1])$ 
      |  $\{t\} \subseteq p \Rightarrow p_1 \subseteq p_2$ :
        if  $t \in D[p]$ :
           $\text{add}(p_2, D[p_1])$ 

```

21.5.4.4 Step 4: Record Solution

```

for  $\ell$  in  $\text{Lab}^*$ :  $\hat{C}(\ell) := D[C(\ell)]$ 
for  $x$  in  $\text{Var}^*$ :  $\hat{p}(x) := D[r(x)]$ 

```

21.5.5 Solver Trace (Example)

Initialization:

- $(D[C(2)] = \{\texttt{idx}\}, (D[C(4)] = \{\texttt{id}\}),$ all others empty
- $(W = [C(4), C(2)])$ (nodes with initial data)

Iteration 1 (process $(C(4))$):

- $(E[C(4)] = \{\texttt{idx}\} \subseteq C(2) \Rightarrow C(4) \subseteq r(x), \{\texttt{id}\} \subseteq C(2) \Rightarrow C(4) \subseteq r(y))$
- Trigger $(\{\texttt{idx}\} \subseteq C(2))$ is true: $(D[r(x)] \mathrel{+} = \{\texttt{id}\}), (W = [r(x), C(2)])$
- Trigger $(\{\texttt{id}\} \subseteq C(2))$: not yet true (no $(\texttt{id})$ in $(C(2))$ yet)

Iteration 2 (process $C(2)$):

- Propagate $D[C(2)] = \{\texttt{idx}\}$ to all successors via direct edges
- Triggers involving $C(2)$: both $\texttt{idx}$ triggers fire
- $D[r(x)] \mathrel{+} = \{\texttt{idx}\}$, $D[C(5)] \mathrel{+} = \{\texttt{idx}\}$...

Fixed point is reached when W is empty.

22 Lecture 21 — CFA with Data and Context

22.1 Abstract Values as Complete Lattices

So far, $\hat{V} = \wp(\text{Term})$ only tracked function abstractions. We now extend to include **data information**, separating:

- **Term information:** which functions $\wp(\text{Term})$
- **Data information:** abstract data values

The combined abstract domain:

$$[\hat{v} \in \widehat{\text{Val}}_d = \wp(\text{Term}) \cup \text{Data}] \\ \cong \wp(\text{Term}) \times \wp(\text{Data})]$$

We can replace $\wp(\text{Data})$ by a **complete lattice** L , and perform a development closely related to Monotone Frameworks.

22.1.1 A Monotone Structure

A monotone structure consists of:

- A complete lattice L
- A set F of monotone functions $L \times L \rightarrow L$

An instance maps:

- Constants $c \in \text{Const}$ to lattice values $(\iota_c \in L)$
- Binary operators $\text{op} \in \text{Op}$ to functions $(f_{\text{op}} \in F)$

22.1.2 Constant Propagation Analysis (Example)

For constant propagation, $(L = \text{flat}(\mathbb{Z}))$:

$$\begin{array}{c} \top \\ \dots -2 -1 0 1 2 \dots \\ \perp \end{array}$$

- $(\text{iota}_c = (c, \emptyset))$ for numeric constant (c)
- $(f_+(l_1, l_2))$ combines constants: if both are integer values, add them; if one is (bot) , result is (bot) ; otherwise (top)

22.1.3 Combined CFA + DFA Domains

The analysis tracks four components:

CFA part:

- $(\hat{C} \text{ in } \text{Cache}: \text{Lab} \rightarrow \widehat{\text{Val}})$ where $(\widehat{\text{Val}} = \text{wp}(\text{Term}))$
- $(\hat{\rho} \text{ in } \text{Env}: \text{Var} \rightarrow \widehat{\text{Val}})$

DFA part:

- $(\hat{D} \text{ in } \text{DCache}: \text{Lab} \rightarrow L)$ (abstract data values at each label)
- $(\hat{\delta} \text{ in } \text{DEnv}: \text{Var} \rightarrow L)$ (abstract data values for variables)

Acceptability relation: $[(\hat{C}, \hat{D}, \hat{\rho}, \hat{\delta}) \models_D e]$

22.1.4 Extended Clauses (Selected)

22.1.4.1 [con] Constants

$[(\hat{C}, \hat{D}, \hat{\rho}, \hat{\delta}) \models_D c^{\text{ell}} \text{ iff } \text{iota}_c \sqsubseteq \hat{D}(\text{ell})]$

22.1.4.2 [op] Binary Operation

$$\llbracket (\hat{C}, \hat{D}, \hat{\rho}, \hat{\delta}) \rrbracket_{\text{models}_D} (t_1^{\ell_1} \text{ op } t_2^{\ell_2})^{\ell} \text{ iff } \begin{cases} (\hat{C}, \hat{D}, \hat{\rho}, \hat{\delta}) \rrbracket_{\text{models}_D} t_1^{\ell_1} \wedge (\hat{C}, \hat{D}, \hat{\rho}, \hat{\delta}) \rrbracket_{\text{models}_D} t_2^{\ell_2} \wedge f_{\text{op}}(\hat{D}(\ell_1), \hat{D}(\ell_2)) \sqsubseteq \hat{D}(\ell) \end{cases}$$

22.1.4.3 [if] Conditional (refined)

Provides data-dependent analysis: only analyse branches whose guard is data-possible.

22.1.5 Staged Analysis

The combined CFA+DFA can be staged:

1. Solve **control flow** $\llbracket (\hat{C}, \hat{\rho}) \rrbracket$ first
2. Solve **data flow** $\llbracket (\hat{D}, \hat{\delta}) \rrbracket$ afterwards

The analysis still yields the least solution of the combined constraints.

22.2 0-CFA Precision Loss

Consider: $\llbracket e \rrbracket \triangleq \llbracket \text{let } f = (\text{fn } x \rightarrow x^1)^2 \text{ in } ((f^3; f^4)^5; (\text{fn } y \rightarrow y^6)^7)^8 \rrbracket$

0-CFA least solution:

- $\llbracket \hat{C} \rrbracket(1) = \llbracket \text{fn } x \rightarrow x^1; \text{fn } y \rightarrow y^6 \rrbracket$ (both functions merged)
- $\llbracket \hat{C} \rrbracket(8) = \llbracket \text{fn } x \rightarrow x^1; \text{fn } y \rightarrow y^6 \rrbracket$
- $\llbracket \hat{C} \rrbracket(9) = \llbracket \text{fn } x \rightarrow x^1; \text{fn } y \rightarrow y^6 \rrbracket$

Only $\llbracket \text{fn } y \rightarrow y^6 \rrbracket$ is a possible runtime result, but 0-CFA says both are possible — **precision loss** from merging contexts.

22.3 Context-Sensitive CFA (k-CFA)

22.3.1 Motivation

Different calling contexts should produce different analyses of the same function. **k-CFA** distinguishes calling contexts up to depth k using **call strings**.

22.3.2 Call Strings

A **call string** $\hat{\delta} \in \Delta = \text{Lab}^{\leq k}$ is a sequence of labels recording the k most recent call sites. The empty call string is ϵ (or Λ).

Examples:

- $(k = 0)$: $\Delta = \{\epsilon\}$ (monovariant — 0-CFA)
- $(k = 1)$: $\Delta = \{\epsilon\} \cup \text{Lab}$ (call-site sensitivity)
- $(k = 2)$: $\Delta = \{\epsilon\} \cup \text{Lab} \cup \text{Lab}^2$

22.3.3 Context Environment

A **context environment** records for each variable the context in which it was defined:

$$[\text{ce} \in \text{Cenv} = \text{Var} \rightarrow \Delta]$$

22.3.4 Context-Sensitive Abstract Domains

$$\begin{aligned} [\begin{aligned} \hat{v} &\in \widehat{\text{Val}} = \text{wp}(\text{Val} \\ &\times \text{Cenv}) \quad \text{closures paired with context} \\ &\text{environments} \end{aligned}] \quad \hat{\rho} \in \widehat{\text{Cenv}} = (\text{Var} \\ &\times \Delta) \rightarrow \widehat{\text{Val}} \quad \hat{C} \in \\ &\widehat{\text{Cache}} = (\text{Lab} \times \Delta) \rightarrow \widehat{\text{Val}} \end{aligned}]$$

22.3.5 Acceptability with Contexts

The relation becomes context-dependent:

$$[(\hat{C}, \hat{\rho}) \models_{\text{ce}}^{\hat{\delta}} e]$$

Where:

- $\backslash(\text{ce})$: current context environment (tracks where each variable was bound)
- $\backslash(\hat{\delta})$: current calling context (changes when functions are applied)

22.3.5.1 [var] with Context

$$\backslash[(\hat{C}, \hat{\rho}) \backslash \text{models_ce}^{\hat{\delta}} x^{\ell} \text{ iff } \hat{\rho}(x, \text{ce}(x)) \subseteq \hat{C}(\ell, \hat{\delta})]$$

Meaning: The variable $\backslash(x)$ carries the context $\backslash(\text{ce}(x))$ where it was defined; it is used in the current context $\backslash(\hat{\delta})$.

22.3.5.2 [fn] with Context

$$\backslash[(\hat{C}, \hat{\rho}) \backslash \text{models_ce}^{\hat{\delta}} (\text{fn } x \rightarrow e_0)^{\ell} \text{ iff } \{(\text{fn } x \rightarrow e_0, \text{ce}_0)\} \subseteq \hat{C}(\ell, \hat{\delta})]$$

where $\backslash(\text{ce}_0 = \text{ce} \mid \text{FV}(\text{fn } x \rightarrow e_0))$ — the closure captures its definition context environment.

22.3.5.3 [let] with Context

$$\backslash[(\hat{C}, \hat{\rho}) \backslash \text{models_ce}^{\hat{\delta}} (\text{let } x = t_1^{\ell_1} \text{ in } t_2^{\ell_2})^{\ell} \text{ iff } \begin{cases} (\hat{C}, \hat{\rho}) \backslash \text{models_ce}^{\hat{\delta}} t_1^{\ell_1} \subseteq \hat{C}(\ell_1, \hat{\delta}) \\ (\hat{C}, \hat{\rho}) \backslash \text{models_ce'}^{\hat{\delta}} t_2^{\ell_2} \subseteq \hat{C}(\ell_2, \hat{\delta}) \end{cases} \subseteq \hat{C}(\ell, \hat{\delta})]$$

where $\backslash(\text{ce}' = \text{ce}[x \mapsto \hat{\delta}])$ — $\backslash(x)$ is defined in the current context.

22.3.5.4 [app] with Context

$$\backslash[(\hat{C}, \hat{\rho}) \backslash \text{models_ce}^{\hat{\delta}} (t_1^{\ell_1}; t_2^{\ell_2})^{\ell} \text{ iff } \begin{cases} (\hat{C}, \hat{\rho}) \backslash \text{models_ce}^{\hat{\delta}} t_1^{\ell_1} \subseteq \hat{C}(\ell_1, \hat{\delta}) \\ \forall (\text{fn } x \rightarrow e_0)^{\ell_0} \text{ in } \hat{C}(\ell_1, \hat{\delta}): \quad \text{quad } (\hat{C}, \hat{\rho}) \backslash \text{models_ce'}^{\hat{\delta}_0} t_0^{\ell_0} \subseteq \hat{C}(\ell_0, \hat{\delta}_0) \end{cases} \subseteq \hat{C}(\ell, \hat{\delta})]$$

$$\begin{cases} \hat{C}(\ell_2, \hat{\delta}) \subseteq \hat{\rho}(x, \hat{\delta}_0) \\ \hat{C}(\ell_0, \hat{\delta}_0) \subseteq \hat{C}(\ell, \hat{\delta}) \end{cases}$$

where $(\hat{\delta}_0 = \ulcorner \hat{\delta} \urcorner_k)$ (extend call string with the current call site) and $(ce'_0 = ce_0[x \mapsto \hat{\delta}_0])$.

22.3.6 Three k-CFA Variants

Variant	Cache Domain	Complexity	Precision
Uniform k-CFA	$((\text{Lab}) \times \Delta) \rightarrow \widehat{\text{Val}}$	Moderate	Good
Classical k-CFA	$((\text{Lab}) \times \text{Cenv}) \rightarrow \widehat{\text{Val}}$	High	Highest
Polynomial k-CFA	$\widehat{\text{Val}} = \text{wp}(\text{Val}) \times \Delta$	Lowest	Lower

22.3.7 Worked Example: 1-CFA

For the expression: $[e \triangleleft \text{let } f = (\text{fn } x \rightarrow x^1)^2 \text{ in } ((f^3; f^4)^5; (\text{fn } y \rightarrow y^6)^7)^8]^9$

Contexts: $(\Delta = \{\Lambda, 5, 8\})$ (initial (Λ) , two call sites 5 and 8)

Context environments:

- $(ce_0 = [])$ (initial)
- $(ce_1 = ce_0[f \mapsto \Lambda])$ (for let body)
- $(ce_2 = ce_0[x \mapsto 5])$ (for first call)
- $(ce_3 = ce_0[x \mapsto 8])$ (for second call)

1-CFA solution (selected):

- $(\hat{C}'(1, 5) = \{(\text{fn } x \rightarrow x^1, ce_0)\})$ — (x^1) analysed in context 5 (first call)

- $\hat{C}'(1, 8) = \{ \text{fn } y \rightarrow y^6, ce_0 \} - \{x\}$
analysed in context 8 (second call)
- $\hat{C}'(9, \Lambda) = \{ \text{fn } y \rightarrow y^6, ce_0 \}$ —
only $\text{fn } y \rightarrow y^6$ is a result

Precision gain: The two calls are now distinguished: $\{x\}$ gets $\text{fn } y \rightarrow y^6$ only from the second call, restoring precision.

23 Lecture 22 — Cartesian Product Algorithm (CPA)

23.1 Motivation

The Cartesian Product Algorithm (CPA) is another approach to **context-sensitive** CFA. While k-CFA uses call strings as contexts, CPA uses **tuples of argument values** as contexts.

23.1.1 Multi-Argument Functions

CPA assumes a syntax with multi-argument functions:

$$\begin{aligned} t &::= \dots \mid \text{fn } (x_1, \dots, x_m) \\ &\rightarrow e_0 \mid e ::= t^{\ell} \mid e_0(e_1, \dots, e_m)^{\ell} \mid \dots \end{aligned}$$

Well-formedness condition: all function abstractions are closed ($FV = \emptyset$).

23.1.2 Abstract Domains for CPA

$$\begin{aligned} \hat{v} &\in \widehat{\text{Val}} = \wp(\text{Term}) \\ \hat{\rho} &\in \widehat{\text{Cenv}} = (\text{Var} \times \Delta) \rightarrow \widehat{\text{Val}} \\ \hat{C} &\in \widehat{\text{Cache}} = (\text{Lab} \times \Delta) \rightarrow \widehat{\text{Val}} \\ \delta &\in \Delta = \text{Term}^m \end{aligned}$$

Key difference: A context δ is a **tuple of argument values** (sets of terms), not a call string.

23.1.3 Rephrasing 0-CFA as a Special Case

In 0-CFA (no context), the clauses simplify:

23.1.3.1 [fn] (0-CFA, multi-arg)

$$\llbracket (\hat{C}, \hat{\rho}) \models (\text{fn } (x_1, \dots, x_m) \rightarrow e_b)^\ell \text{ iff } \llbracket (\text{fn } (x_1, \dots, x_m) \rightarrow e_b) \rrbracket \subseteq \hat{C}(\ell) \rrbracket$$

23.1.3.2 [app] (0-CFA, multi-arg)

$$\llbracket (\hat{C}, \hat{\rho}) \models (t_0^\ell(t_1^\ell, \dots, t_m^\ell))^\ell \text{ iff } \begin{cases} (\hat{C}, \hat{\rho}) \models t_0^\ell \parallel (\hat{C}, \hat{\rho}) \models t_1^\ell, \dots, (\hat{C}, \hat{\rho}) \models t_m^\ell \parallel \forall (\text{fn } (x_1, \dots, x_m) \rightarrow t_b^\ell) \text{ in } \hat{C}(\ell_0): \parallel \text{quad } \hat{C}(\ell_1) \subseteq \hat{\rho}(x_1) \text{ and } \dots \text{ and } \hat{C}(\ell_m) \subseteq \hat{\rho}(x_m) \parallel \text{quad } \text{and}; (\hat{C}, \hat{\rho}) \models t_b^\ell \text{ and } \hat{C}(\ell_b) \subseteq \hat{C}(\ell) \end{cases} \rrbracket$$

23.1.4 Adding Context to CPA

Now, the acceptability relation is parameterized by a context (δ) :

$$\llbracket (\hat{C}, \hat{\rho}) \models_{\delta}^{\text{CPA}} e \rrbracket$$

23.1.4.1 [var] with CPA Context

$$\llbracket (\hat{C}, \hat{\rho}) \models_{\delta}^{\text{CPA}} x^\ell \text{ iff } \hat{\rho}(x, \delta) \subseteq \hat{C}(\ell, \delta) \rrbracket$$

23.1.4.2 [fn] with CPA Context

$$\llbracket (\hat{C}, \hat{\rho}) \models_{\delta}^{\text{CPA}} (\text{fn } (x_1, \dots, x_m) \rightarrow e_b)^\ell \text{ iff } \llbracket (\text{fn } (x_1, \dots, x_m) \rightarrow e_b) \rrbracket \subseteq \hat{C}(\ell, \delta) \rrbracket$$

23.1.4.3 [app] with CPA Context

$$\llbracket (\hat{C}, \hat{\rho}) \models_{\delta}^{\text{CPA}} (t_0^\ell(t_1^\ell, \dots, t_m^\ell))^\ell \text{ iff } \begin{cases} (\hat{C}, \hat{\rho}) \models_{\delta}^{\text{CPA}} t_0^\ell \parallel (\hat{C}, \hat{\rho}) \models_{\delta}^{\text{CPA}} t_1^\ell, \dots, (\hat{C}, \hat{\rho}) \models_{\delta}^{\text{CPA}} t_m^\ell \parallel \forall (\text{fn } (x_1, \dots, x_m) \rightarrow t_b^\ell) \text{ in } \hat{C}(\ell_0): \parallel \text{quad } \hat{C}(\ell_1) \subseteq \hat{\rho}(x_1, \delta) \text{ and } \dots \text{ and } \hat{C}(\ell_m) \subseteq \hat{\rho}(x_m, \delta) \parallel \text{quad } \text{and}; (\hat{C}, \hat{\rho}) \models_{\delta}^{\text{CPA}} t_b^\ell \text{ and } \hat{C}(\ell_b, \delta) \subseteq \hat{C}(\ell, \delta) \end{cases} \rrbracket$$

$\hat{\rho}) \models_{\{\delta\}^{\text{CPA}}} t_m^{\ell_m} \parallel \forall$
 $(\text{fn } (x_1, \dots, x_m) \rightarrow t_b^{\ell_b}) \in \hat{C}(\ell_0,$
 $\delta): \parallel \quad \forall \delta_b \in \hat{C}(\ell_1, \delta) \times \dots$
 $\times \hat{C}(\ell_m, \delta): \parallel \quad \forall (\text{fn } (x_1, \dots, x_m)$
 $\rightarrow t_b^{\ell_b}) \in \hat{C}(\ell_0, \delta) \parallel \quad \forall \rightarrow$
 $\{\delta_b\} \subseteq \hat{\rho}(x_1) \times \dots \times \hat{\rho}(x_m)$
 $\parallel \quad \forall \quad \text{and}; (\hat{C}, \hat{\rho}) \models_{\{\delta_b\}^{\text{CPA}}}$
 $t_b^{\ell_b} \parallel \quad \forall \quad \text{and}; \hat{C}(\ell_b, \delta_b) \subseteq \hat{C}$
 $(\ell, \delta) \text{endcases} \parallel$

23.1.5 Worked Example (CPA)

Suppose $(\hat{C}(\ell_0) = \{(\text{fn } (x_1, x_2) \rightarrow e_b)\}, \hat{C}(\ell_1, \delta) = \{a, b\}, \hat{C}(\ell_2, \delta) = \{c, d\})$.

The Cartesian product $(\hat{C}(\ell_1, \delta) \times \hat{C}(\ell_2, \delta)) = \{(a, c), (a, d), (b, c), (b, d)\}$. The body (e_b) is analysed **separately** for each of the 4 argument tuples, with no merging across tuples.

23.1.6 Complexity of CPA

- The cartesian product creates **exponential** context explosion in the worst case
- **Memoisation** is essential: bodies are analysed once per template and reused
- In practice, many argument combinations never occur, so the effective number is smaller

23.1.7 CPA with Non-Closed Functions

If function abstractions may have free variables $(FV \neq \emptyset)$, the analysis is extended with:

- $(\delta \in \Delta = \text{Term}^m)$
- $(ce \in \text{CEnv} = \text{Var} \rightarrow \Delta)$
- $(\hat{v} \in \widehat{\text{Val}} = \text{wp}(\text{Val} \times \text{CEnv}))$
(closures with context environments)

The `[app]` clause then uses $(ce'_0 = ce_0[x_1 \mapsto \delta_b! \downarrow_1, \dots, x_n \mapsto \delta_b! \downarrow_n])$
(projecting components of the argument tuple).

23.1.8 Evolution of CFA for FUN

Stage	Context	Precision	Complexity
0-CFA	None (monovariant)	Low	$\mathcal{O}(n^3)$
Syntax-directed	None (body-once)	Medium	$\mathcal{O}(n)$
Constraint-based	None	Same as 0-CFA	$\mathcal{O}(n^3)$ – $\mathcal{O}(n^5)$
k-CFA	Call strings ($\text{Lab}^{\leq k}$)	Medium–High	$\mathcal{O}(n^{k+1})$
CPA	Argument tuples (Term^m)	High	Exponential (with memoisation)

All variants preserve soundness. The choice is a **trade-off** between precision and computational cost.

24 Lecture 23 — CFA for π -Calculus (0-CFA for Process Algebras)

24.1 Motivation

- In CCS, communication is statically defined: channels cannot be transmitted or received
- The π -calculus extends CCS by allowing channels to be treated as ordinary values
- This enables **name mobility**: channels themselves can be communicated, making the communication structure dynamic
- CFA must predict which values may flow over which channels, even when channel names are passed at runtime

24.2 π -Calculus Syntax

24.2.1 Actions (Prefixes)

```
\[ \begin{aligned} \pi ::= & \overline{u} \langle v \rangle \text{ (send } \$v\$ \text{ on } \$u\$)} \mid u(x) \text{ (receive on } \$u\$, \text{ store in } \$x\$)} \mid \\ & \tau \text{ (internal action)} \end{aligned} \]
```

24.2.2 Processes

```
\[ \begin{aligned} P ::= & 0 \text{ (inactive process)} \mid \pi.P \text{ (action prefix)} \mid [x=y]P \text{ (matching: if } \$x=y\$ \text{ then } \$P\$)} \\ & \mid (\nu n)P \text{ (restriction: } \$n\$ \text{ is fresh/local)} \mid \sum_{i \in I} \pi_i.P_i \text{ (non-deterministic guarded choice)} \\ & \mid P_1 \mid P_2 \text{ (parallel composition)} \mid !P \text{ (replication: } \$P \mid P \mid P \mid \dots\$)} \end{aligned} \]
```

24.2.3 Reduction Semantics (Key Rule)

```
\[ [\text{Com}] \quad (\overline{n} \langle m \rangle . P + P') \mid (n(x).Q + Q') \rightarrow P \mid Q[m/x] \]
```

A process can also reduce under restriction, parallel composition, and structural congruence.

24.3 Name Mobility Example

$A = (\nu ab)(\overline{ab} \langle m \rangle . A')$ -- A sends message m on channel ab to B

$B = ab(x).B'$ -- B receives on ab

S -- secure server that establishes channels

System: $(\nu as)(\nu bs)((\nu ab) A \mid B \mid S)$

Channel ab is created by A , used for communication, and can be passed to other processes.

24.4 Abstract Domains for CFA

24.4.1 Domain Definitions

$$\begin{aligned} \text{Val} &= \wp(\text{Const}) \parallel \rho \&: \text{Var} \rightarrow \wp(\text{Const}) \parallel \kappa \&: \text{Var} \rightarrow \wp(\text{Const}) \\ \end{aligned}$$

- **ρ (abstract environment)**: maps each variable to the set of constants it may be bound to
- **κ (abstract channel environment)**: maps each channel constant to the set of constants that may be communicated over it
- Both domains form complete lattices under pointwise subset ordering
- Extension to constants: $\rho(n) = \{n\}$ for any constant n

24.4.2 Detailed Domain Structure

The name space is partitioned into:

- **Constants** $c \in \text{Const}$: channels and values whose identity is statically known (including restricted names)
- **Variables** $x \in \text{Var}$: placeholders for values that will be received

The abstract domain is built on **canonical names**:

- $\lfloor n \rfloor$ denotes the equivalence class of name n under α -renaming
- $\lfloor x \rfloor = x$ for variables
- Substitution preserves equivalence classes

24.4.3 Complete Lattice Structure

The product domain $(\wp(\text{Const}) \times \wp(\text{Const}))^{\text{Var} \times \text{Var}}$ forms a complete lattice with:

- **Order**: $(\rho_1, \kappa_1) \sqsubseteq (\rho_2, \kappa_2)$ iff $(\forall x: \rho_1(x) \subseteq \rho_2(x))$ and $(\forall n: \kappa_1(n) \subseteq \kappa_2(n))$
- **Least element**: $\bot = (\lambda x. \emptyset, \lambda n. \emptyset)$

- **Greatest element:** $\top = (\lambda x. \text{Const}, \lambda n. \text{Const})$
- **Join:** pointwise union: $((\rho_1 \sqcup \rho_2)(x) = \rho_1(x) \cup \rho_2(x))$
- **Meet:** pointwise intersection: $((\rho_1 \sqcap \rho_2)(x) = \rho_1(x) \cap \rho_2(x))$

24.4.4 CFA Guess

A **guess** $((\rho, \kappa))$ is a proposed analysis result. It is **acceptable** if it safely over-approximates all runtime behaviour.

24.5 Validation Clauses for Actions

24.5.1 Output: $(\overline{u} \text{ langle } v \text{ rangle})$

$[\text{out}] \text{ quad } (\rho, \kappa) \models_A \overline{u} \text{ langle } v \text{ rangle}$ iff $\forall n \in \rho(u): \rho(v) \subseteq \kappa(n)$

Meaning: Whatever value (v) may evaluate to must be recorded as possibly communicated on every channel that (u) may denote.

Three subcases: (based on whether (u) and (v) are constants or variables)

1. **Both constants:** $(\overline{n} \text{ langle } m \text{ rangle})$
 - $(\rho(n) = \{n\}), (\rho(m) = \{m\})$
 - Claus: $(m \subseteq \kappa(n))$
 - **Meaning:** The specific constant (m) is recorded as possibly sent on channel (n) .
2. **Constant channel, variable value:** $(\overline{n} \text{ langle } v \text{ rangle})$
 - $(\rho(n) = \{n\})$ (channel is known statically)
 - Claus: $(\rho(v) \subseteq \kappa(n))$
 - **Meaning:** All values that (v) may contain are recorded on channel (n) .
3. **Variable channel, constant value:** $(\overline{u} \text{ langle } m \text{ rangle})$
 - $(\rho(m) = \{m\})$
 - Claus: $(\forall n \in \rho(u): m \subseteq \kappa(n))$
 - **Meaning:** The constant (m) is recorded on all channels that (u) may denote.

Intuition: The output clause ensures that whatever value is sent is included in the abstract channel environment for every possible target channel. This is a **sound over-approximation**: it includes all actual communications, though it may include spurious ones.

24.5.2 Input: $\backslash(u(x)\backslash)$

$$\backslash[\text{in}]\backslash\text{quad}(\rho, \kappa) \backslash\text{models_A } u(x) \backslash\text{iff} \backslash\text{forall } n \backslash\text{in } \rho(u): \kappa(n) \backslash\text{subseq } \rho(x) \backslash]$$

Meaning: Anything that may be communicated over any channel that $\backslash(u)$ denotes (the abstract communication $\backslash(\kappa(n)\backslash)$ for each possible $\backslash(n)\backslash$) may be received and bound to $\backslash(x)\backslash$.

Subcases:

1. Constant channel: $\backslash(n(x)\backslash)$

- $\backslash(\rho(n) = \{n\}\backslash)$
- Clause: $\backslash(\kappa(n) \backslash\text{subseq } \rho(x)\backslash)$
- **Meaning:** All values recorded for channel $\backslash(n)\backslash$ flow to $\backslash(x)\backslash$.

2. Variable channel: $\backslash(u(x)\backslash)$

- Clause: $\backslash(\text{forall } n \backslash\text{in } \rho(u): \kappa(n) \backslash\text{subseq } \rho(x)\backslash)$
- **Meaning:** The union of all $\backslash(\kappa(n)\backslash)$ for every possible $\backslash(n)\backslash$ flows to $\backslash(x)\backslash$.

Intuition: The $\backslash\text{in}\backslash$ clause ensures that the variable $\backslash(x)\backslash$ receives all values that may be communicated on any channel $\backslash(u)\backslash$ denotes. Because $\backslash(u)\backslash$ is a variable that may evaluate to multiple constants, we take the union over all of them — a sound over-approximation.

24.5.3 Communication as Constraint Propagation

Together, $\backslash\text{out}\backslash$ and $\backslash\text{in}\backslash$ model communication:

$$\backslash[\overline{u} \backslash\text{angle } v \backslash\text{angle} \backslash\text{quad} \backslash\text{Longrightarrow} \backslash\text{quad} \rho(v) \backslash\text{subseq } \kappa(\rho(u)) \backslash]$$

$$\backslash[u(x) \backslash\text{quad} \backslash\text{Longrightarrow} \backslash\text{quad} \kappa(\rho(u)) \backslash\text{subseq } \rho(x) \backslash]$$

The channel environment $\backslash(\kappa)\backslash$ acts as an intermediary: outputs **push** values into $\backslash(\kappa)\backslash$, inputs **pull** values from $\backslash(\kappa)\backslash$. When an output and an input agree on a channel ($\backslash(\rho(u)\backslash)$ overlaps), data flows from sender to receiver.

24.5.4 Internal Action: τ

$\llbracket \text{tau} \rrbracket \text{quad } (\rho, \kappa) \models_A \tau \llbracket$

Always satisfied (no communication effect to track).

24.6 Validation Clauses for Processes

24.6.1 Inactive Process

$\llbracket \text{nil} \rrbracket \text{quad } (\rho, \kappa) \models_P 0 \llbracket$

Always satisfied.

24.6.2 Prefix

$\llbracket \text{pref} \rrbracket \text{quad } (\rho, \kappa) \models_P \pi.P \text{ iff } (\rho, \kappa) \models_A \pi \wedge (\rho, \kappa) \models_P P \llbracket$

24.6.3 Parallel Composition

$\llbracket \text{par} \rrbracket \text{quad } (\rho, \kappa) \models_P P_1 \text{ mid } P_2 \text{ iff } (\rho, \kappa) \models_P P_1 \wedge (\rho, \kappa) \models_P P_2 \llbracket$

24.6.4 Sum (Non-deterministic Choice)

$\llbracket \text{sum} \rrbracket \text{quad } (\rho, \kappa) \models_P \Sigma_{i \in I} \pi_i.P_i \text{ iff } \forall i \in I: ((\rho, \kappa) \models_A \pi_i \wedge (\rho, \kappa) \models_P P_i) \llbracket$

24.6.5 Matching: $\llbracket [x=y]P \rrbracket$

$\llbracket \text{match} \rrbracket \text{quad } (\rho, \kappa) \models_P [x=y]P \text{ iff } (\rho, \kappa) \models_P P \llbracket$

Default (oblivious) analysis: The match is over-approximated by assuming it could always succeed. This is sound because it may analyse code that is actually unreachable, but it never misses reachable code.

Refined match clause (more precise): $\llbracket \text{match}^* \rrbracket$

$$\llbracket (\rho, \kappa) \models_P [x=y]P \text{ iff } \rho(x) \cap \rho(y) \neq \emptyset \rrbracket$$

If the two variables' abstract values have **no common elements**, the match can never succeed, and the branch is **unreachable** — we can skip analysing $\llbracket P \rrbracket$.

Practical example: Process: $\llbracket (a(x).c(y).[x=y].P' \mid \overline{a}\langle b \rangle.Q' \mid \overline{c}\langle b \rangle.Q'' \mid \overline{c}\langle b \rangle.R') \rrbracket$

- $\llbracket \rho(x) = \{b, d\}, \rho(y) = \{b\} \rrbracket$
- $\llbracket \rho(x) \cap \rho(y) = \{b\} \neq \emptyset \rrbracket \rightarrow$ match may succeed, analyse $\llbracket P' \rrbracket$

If we had $\llbracket \overline{c}\langle f \rangle.R' \rrbracket$ instead of $\llbracket \overline{c}\langle b \rangle.R' \rrbracket$:

- $\llbracket \rho(x) = \{b, d\}, \rho(y) = \{f\} \rrbracket$
- $\llbracket \rho(x) \cap \rho(y) = \emptyset \rrbracket \rightarrow$ match never succeeds, $\llbracket P' \rrbracket$ is unreachable

24.6.6 Restriction: $\llbracket (\nu n)P \rrbracket$

$$\llbracket \llbracket \text{res} \rrbracket \text{quad } (\rho, \kappa) \models_P (\nu n)P \text{ iff } (\rho, \kappa) \models_P P \rrbracket$$

Meaning: The analysis is **oblivious to scoping** — names are treated as global constants. This is a deliberate over-approximation: it ignores the fact that a restricted name $\llbracket n \rrbracket$ should not be known outside $\llbracket P \rrbracket$, and may therefore predict communications that are impossible in the concrete semantics.

Consequences:

- Restricted names are included in $\llbracket \rho \rrbracket$ and $\llbracket \kappa \rrbracket$ like any other constant
- Spurious flows may result from ignoring scope boundaries
- To refine: one could use **freshness** information to remove impossible flows

Example with scope extrusion:
$$\llbracket (\nu a)(\overline{a}\langle b \rangle.0 \mid a(x).\overline{c}\langle x \rangle.0) \mid \overline{c}\langle d \rangle.0 \rrbracket$$

Although $\langle a \rangle$ is restricted, the analysis treats it as a global constant. The abstract result $\langle \kappa(c) \supseteq \{b, d\} \rangle$ soundly over-approximates the actual behaviour (where $\langle b \rangle$ is indeed forwarded to $\langle c \rangle$ via scope extrusion).

24.6.7 Replication: $\langle !P \rangle$

$\llbracket \text{rep} \rrbracket \quad (\rho, \kappa) \models_P !P \text{ iff } (\rho, \kappa) \models_P P$

Meaning: Replication $\langle !P \equiv P \mid P \mid P \mid \dots \rangle$ represents an unbounded number of parallel copies of $\langle P \rangle$. The analysis treats this as a **single** copy of $\langle P \rangle$, which is sound because the same $\langle (\rho, \kappa) \rangle$ over-approximates all copies.

Correctness intuition: Since all copies of $\langle P \rangle$ share the same abstract values, any communication possible in the replicated process is also possible in the single-copy analysis. The over-approximation is that all copies can communicate with each other (while in reality there is only one copy being analysed).

24.7 Summary of All Validation Clauses

Construct	Clause
$\llbracket \text{nil} \rrbracket$	$\langle (\rho, \kappa) \models_P 0 \rangle$ always
$\llbracket \text{pref} \rrbracket$	$\langle (\rho, \kappa) \models_P \pi.P \text{ iff } (\rho, \kappa) \models_A \pi \text{ and } (\rho, \kappa) \models_P P \rangle$
$\llbracket \text{par} \rrbracket$	$\langle (\rho, \kappa) \models_P P_1 \mid P_2 \text{ iff } (\rho, \kappa) \models_P P_1 \text{ and } (\rho, \kappa) \models_P P_2 \rangle$
$\llbracket \text{sum} \rrbracket$	$\langle (\rho, \kappa) \models_P \sum_i \pi_i.P_i \text{ iff } \forall i: (\rho, \kappa) \models_A \pi_i \text{ and } (\rho, \kappa) \models_P P_i \rangle$
$\llbracket \text{match} \rrbracket$	$\langle (\rho, \kappa) \models_P [x=y]P \text{ iff } (\rho, \kappa) \models_P P \rangle$
$\llbracket \text{res} \rrbracket$	

Construct	Clause
	$\langle (\rho, \kappa) \models_P (\nu n)P \rangle \text{ iff } (\rho, \kappa) \models_P P$
$\langle [\text{rep}] \rangle$	$\langle (\rho, \kappa) \models_P !P \rangle \text{ iff } (\rho, \kappa) \models_P P$
$\langle [\text{out}] \rangle$	$\langle (\rho, \kappa) \models_A \overline{u} \langle v \rangle \rangle \text{ iff } \forall n \in \rho(u): \rho(v) \subseteq \kappa(n)$
$\langle [\text{in}] \rangle$	$\langle (\rho, \kappa) \models_A u(x) \rangle \text{ iff } \forall n \in \rho(u): \kappa(n) \subseteq \rho(x)$
$\langle [\text{tau}] \rangle$	$\langle (\rho, \kappa) \models_A \tau \rangle$ always

25 Lecture 24 — CFA for π -Calculus: Examples, Theory, and Polyadic Extension

25.1 Worked Example 1: Simple Communication

Process: $\langle [\overline{a} \langle b \rangle . P' + \overline{a} \langle d \rangle . P''] \mid a(w) . \langle [\overline{c} \langle w \rangle . Q'] \mid R \rangle \rangle$

25.1.1 Concrete Behaviour

- Output on $\langle a \rangle$: either $\langle b \rangle$ or $\langle d \rangle$ is sent
- Input on $\langle a \rangle$: $\langle w \rangle$ receives the transmitted value
- Forwarding: whatever $\langle w \rangle$ received is output on $\langle c \rangle$

25.1.2 CFA Guess $((\rho, \kappa))$

Variable	(ρ)
(a)	$(\{a\})$
(b)	$(\{b\})$
(c)	$(\{c\})$
(d)	$(\{d\})$
(w)	$(\{b, d\})$

Channel	(κ)
(a)	$(\{b, d\})$
(b)	(emptyset)
(c)	$(\{b, d\})$
(d)	(emptyset)

25.1.3 Verification

1. $(\overline{a} \langle b \rangle)$: $(\rho(b) = \{b\} \subseteq \kappa(a) = \{b, d\}) \checkmark$
2. $(\overline{a} \langle d \rangle)$: $(\rho(d) = \{d\} \subseteq \kappa(a) = \{b, d\}) \checkmark$
3. $(a(w))$: $(\kappa(a) = \{b, d\} \subseteq \rho(w) = \{b, d\}) \checkmark$
4. $(\overline{c} \langle w \rangle)$: $(\rho(w) = \{b, d\} \subseteq \kappa(c) = \{b, d\}) \checkmark$

Analysis predicts both possible executions (sound over-approximation).

25.2 Worked Example 2: Name Mobility

Process: $[(\nu a)(\overline{a} \langle b \rangle.0 \mid a(x).\overline{c} \langle x \rangle.0) \mid \overline{c} \langle d \rangle.0]$

25.2.1 Analysis

- Channel (a) is restricted: $((\nu a))$ creates a fresh name
- Output on (a) : (b) is communicated over (a)
- Input on (a) : (x) receives (b) , then forwards it on (c)
- Parallel output on (c) : (d) is also sent on (c)

25.2.2 Result

$\llbracket \kappa(c) \supseteq \{b, d\}, \text{quad } \rho(x) \supseteq \{b\} \rrbracket$

25.3 The Match Clause in Practice

Consider: $\llbracket a(x).c(y).[x=y].P' \mid \overline{a} \langle d \rangle . Q' \mid \overline{a} \langle b \rangle . Q'' \mid \overline{c} \langle b \rangle . R' \rrbracket$

- $(\rho(x) = \{b, d\}), (\rho(y) = \{b\})$
- $(\rho(x) \cap \rho(y) = \{b\} \neq \emptyset) \rightarrow$ the match can succeed, analyse $\llbracket P' \rrbracket$

Now if $\llbracket \overline{c} \langle f \rangle . R' \rrbracket$ instead of $\llbracket \overline{c} \langle b \rangle . R' \rrbracket$:

- $(\rho(x) = \{b, d\}), (\rho(y) = \{f\})$
- $(\rho(x) \cap \rho(y) = \emptyset) \rightarrow$ match can never succeed, $\llbracket P' \rrbracket$ is unreachable under refined analysis

25.4 Theoretical Properties

25.4.1 Subject Reduction (Semantic Correctness)

If $(\rho, \kappa) \models_P P$ and $(P \rightarrow Q)$ (a reduction step), then $(\rho, \kappa) \models_P Q$.

The analysis result is preserved under computation — it is a **sound over-approximation** of all reachable states.

25.4.2 Preservation under (α) -renaming

Use **canonical names** (equivalence classes):

- $\lfloor n \rfloor$ is the equivalence class of (n)
- $\lfloor x \rfloor = x$ for variables
- Names may only be substituted within the same equivalence class

Lemma: If $(P \equiv_\alpha Q)$ then $(\rho, \kappa) \models_P \lfloor P \rfloor \iff (\rho, \kappa) \models_P \lfloor Q \rfloor$.

25.4.3 Substitution Lemma

If $((\rho, \kappa) \models_P \lfloor P \rfloor)$ then $((\rho, \kappa) \models_P \lfloor P[m/x] \rfloor)$, provided $(\lfloor m \rfloor \subseteq \rho(x))$.

25.4.4 Existence and Moore Family

The set $\{(\rho, \kappa) \mid (\rho, \kappa) \models_P P\}$ is a **Moore family** (closed under greatest lower bounds). Therefore:

- Every process $\langle P \rangle$ has at least one analysis (the trivial one with everything flowing everywhere)
- There exists a **least** (most precise) solution: the intersection of all acceptable pairs

25.4.5 Implementation

- The validation clauses generate a set of logical constraints (set inclusions)
- Constraints can be solved by a specialised constraint solver or by translation to first-order logic
- Complexity is low polynomial

25.5 Nature of Imprecision in 0-CFA for π -calculus

The analysis is **context-insensitive** (0-CFA), leading to imprecision:

$$\begin{aligned} P_1 &\trianglelefteq a(x) \mid \overline{a} \langle b \rangle \\ P_2 &\trianglelefteq a(x) + \overline{a} \langle b \rangle \\ P_3 &\trianglelefteq a(x).\overline{a} \langle b \rangle \end{aligned}$$

In $\langle P_1 \rangle$, $\langle x \rangle$ can be bound to $\langle b \rangle$. In $\langle P_2 \rangle$ and $\langle P_3 \rangle$, it cannot (no communication possible). However, the 0-CFA estimate gives $(\rho(x) \supseteq \langle b \rangle)$ in **all three cases** — a safe over-approximation that does not distinguish between reachable and unreachable communications.

25.6 Polyadic π -Calculus Extension

25.6.1 Syntax

Allow tuples of values:
$$\begin{aligned} \pi ::= & \overline{u} \langle \vec{v} \rangle \mid u(\vec{x}) \mid \tau \end{aligned}$$

25.6.2 Reduction with Arity

$$\begin{aligned} & \text{Com} \quad \overline{n} \langle \vec{m} \rangle . P + P' \mid n(\vec{x}). Q + Q' \rightarrow P \mid Q[\vec{m}/\vec{x}] \text{ provided } (|\vec{m}| \\ & = |\vec{x}|) \text{ (arity must match).} \end{aligned}$$

25.6.3 Extended Abstract Domains

$$\begin{aligned} & \text{Val} \quad \wp(\text{Const}) \mid \rho \&: \text{Var} \rightarrow \wp(\text{Const}) \mid \kappa \&: \text{Var} \rightarrow \wp(\text{Const}^*) \mid \psi \&: \\ & \wp(\text{Const}) \end{aligned}$$

- κ now maps to **sequences of constants** (tuples)
- ψ records the set of channels where an **arity mismatch** may occur

25.6.4 Extended Validation (sketch)

$$(\rho, \kappa) \models_A \overline{u} \langle \vec{v} \rangle \text{ iff } \forall n \in \rho(u): \rho(v_1) \times \dots \times \rho(v_k) \subseteq \kappa(n)$$

$$(\rho, \kappa) \models_A u(\vec{x}) \text{ iff } \forall n \in \rho(u): \kappa(n) \subseteq \rho(x_1) \times \dots \times \rho(x_k)$$

Arity mismatches are recorded in ψ for error detection.

26 Complete Formula Handbook

26.1 F-01: Collecting Semantics

$$\llbracket c \rrbracket P = \bigcup_{\sigma \in P} \llbracket c \rrbracket \sigma$$
Meaning: The collecting semantics maps a set of input states to the union of all reachable output states.

26.2 F-02: Weakest Liberal Precondition

$$\text{wlp}(c, Q) = \{ \sigma \mid \llbracket c \rrbracket \sigma \subseteq Q \}$$

26.3 F-03: Weakest Possible Precondition

$$\text{wpp}(c, Q) = \{ \sigma \mid \llbracket c \rrbracket \sigma \subseteq Q \text{ and } Q \neq \emptyset \}$$

26.4 F-04: Hoare Triple Validity

$$\{P\} c \{Q\} \text{ iff } \llbracket c \rrbracket P \subseteq Q$$

26.5 F-05: Incorrectness Triple Validity

$$\{P\} c [Q] \text{ iff } \llbracket c \rrbracket P \supseteq Q$$

26.6 F-06: Galois Connection

$$\alpha(c) \sqsubseteq_A a \text{ iff } c \sqsubseteq_C \gamma(a)$$

26.7 F-07: Soundness of Abstract Semantics

$$\alpha \circ \llbracket c \rrbracket \sqsubseteq \llbracket c \rrbracket^{\#} \circ \alpha$$

26.8 F-08: Best Abstract Correct Approximation

$$\llbracket c \rrbracket^{\#}_A = \alpha \circ \llbracket c \rrbracket \circ \gamma$$

26.9 F-09: Completeness Equation

$$\alpha \circ \llbracket c \rrbracket = \alpha \circ \llbracket c \rrbracket \circ \gamma \circ \alpha$$

27 Exam Preparation Guide

27.1 Recurring Exercise Patterns

1. **Prove a Hoare triple** using HL inference rules — find the loop invariant
2. **Prove an incorrectness triple** using IL rules — find the right under-approximation
3. **Galois connection** — define α and γ for a given abstraction
4. **Abstract semantics** — define $\llbracket c \rrbracket^{\#}$ for a given abstract domain
5. **Fixpoint computation** — compute the least fixpoint for a loop in an abstract domain
6. **CFA constraints** — generate constraints for a functional program

27.2 Common Proof Strategies

- **Induction on derivation trees** for proving soundness
- **Fixpoint induction** (Kleene) for loop semantics
- **Structural induction** for semantic properties
- **Coinduction** for non-termination/infinite behaviors

27.3 Common Lattice Constructions

1. **Product lattice:** $L_1 \times L_2$ with pointwise order

2. **Flat lattice:** $(L^{\#})$ with $\bot < a < \top$
3. **Interval lattice:** $(\{[l, u] \mid l \leq u, l \in \mathbb{Z} \cup \{-\infty\}, u \in \mathbb{Z} \cup \{+\infty\}\})$
4. **Sign lattice:** $(\{\emptyset, <0, =0, >0, \leq 0, \geq 0, \mathbb{Z}\})$
ordered by subset inclusion

27.4 Frequently Tested Concepts

- wlp vs wpp and their properties
- HL vs IL duality
- Soundness and completeness
- Galois connections and insertions
- Abstract domain design
- Widening for fixpoint termination
- 0-CFA for functional programs
- Flow logic formulation of CFA

28 Final Cheat Sheet (Expanded)

28.1 1. Denotational Semantics

Concept	Definition
State	$\Sigma \triangleq \{\sigma: X \rightarrow \mathbb{Z}\}$
Collecting semantics	$\llbracket c \rrbracket : \text{wp}(\Sigma) \rightarrow \text{wp}(\Sigma), \llbracket c \rrbracket P = \bigcup_{\sigma \in P} \llbracket c \rrbracket \sigma$
Skip	$\llbracket \text{skip} \rrbracket P = P$
Assignment	$\llbracket x := a \rrbracket P = \{\sigma[n/x] \mid \sigma \in P, n = \llbracket a \rrbracket \sigma\}$
Sequence	$\llbracket c_1; c_2 \rrbracket P = \llbracket c_2 \rrbracket (\llbracket c_1 \rrbracket P)$

Concept	Definition
Choice	$\llbracket c_1 + c_2 \rrbracket P = \llbracket c_1 \rrbracket P \cup \llbracket c_2 \rrbracket P$
Iteration	$\llbracket c^* \rrbracket P = \bigcup_{k=0}^{\infty} \llbracket c \rrbracket^k P$
Guard	$\llbracket b? \rrbracket P = P \wedge b$
Encoding if	$\text{if } b \text{ then } c_1 \text{ else } c_2 \equiv (b?; c_1) + (\neg b?; c_2)$
Encoding while	$\text{while } b \text{ do } c \equiv (b?; c)^* \neg b?$
wlp	$\text{wlp}(c, Q) = \{ \sigma \mid \llbracket c \rrbracket \sigma \subseteq Q \}$
wpp	$\text{wpp}(c, Q) = \{ \sigma \mid \llbracket c \rrbracket \sigma \cap Q \neq \emptyset \}$

28.2 2. Program Logics — The Four Quadrants

Logic	Triple	Direction	Approximation	Validity Condition
Hoare Logic (HL)	$\{P\} c \{Q\}$	Forward	Over ($\subseteq$)	$\llbracket c \rrbracket P \subseteq Q$
Incorrectness Logic (IL)	$\{P\} c [Q]$	Forward	Under ($\supseteq$)	$\llbracket c \rrbracket P \supseteq Q$
Necessary Condition (NC)	$\langle P \rangle c \langle Q \rangle$	Backward	Under	$P \subseteq \llbracket c \rrbracket^{\{\text{op}\}} Q$
Sufficient Incorrectness (SIL)	$\langle \langle P \rangle c \langle Q \rangle \rangle$	Backward	Over	$P \supseteq \llbracket c \rrbracket^{\{\text{op}\}} Q$

28.2.1 First-order Characterizations

- HL: $\forall \sigma \in P. \forall \delta \in \llbracket c \rrbracket \sigma. \delta \in Q$
- IL: $\forall \delta \in Q. \exists \sigma \in P. \delta \in \llbracket c \rrbracket \sigma$

28.3 3. Hoare Logic Rules (Partial Correctness)

Rule	Formula
Skip	$\overline{\{P\}} \text{ skip } \{P\}$
Assignment (Hoare)	$\overline{\{Q[a/x]\}} x := a \{Q\}$
Assignment (Floyd)	$\overline{\{P\}} x := a \{ \exists x'. P[x'/x] \wedge x = a[x'/x] \}$
Sequence	$\frac{\{P\} c_1 \{R\} \quad \{R\} c_2 \{Q\}}{\{P\} c_1; c_2 \{Q\}}$
Conditional	$\frac{\{P \wedge b\} c_1 \{Q\} \quad \{P \wedge \neg b\} c_2 \{Q\}}{\{P\} \text{ if } b \text{ then } c_1 \text{ else } c_2 \{Q\}}$
While	$\frac{\{P \wedge b\} c \{P\}}{\{P \wedge b\} \text{ while } b \text{ do } c \{P \wedge \neg b\}}$
Consequence	$\frac{P \rightarrow P' \quad \{P'\} c \{Q'\} \quad Q' \rightarrow Q}{\{P\} c \{Q\}}$
While (total)	$\frac{\{P \wedge b\} c \{P\} \quad \{P \wedge b \wedge t=z\} c \{t < z\} \quad P \rightarrow t \geq 0}{\{P\} \text{ while } b \text{ do } c \{P \wedge \neg b\}}$

28.4 4. Incorrectness Logic Rules

Rule	Formula
Skip	$\overline{[P] \text{ skip } [P]}$
Assignment (Floyd)	$\overline{[P] \ x := a \ [\exists x'. P[x'/x] \wedge x = a[x'/x]]}$
Assume	$\overline{[P] \ b? \ [P \wedge b]}$
Error	$\overline{[P] \ \text{error} \ [\text{false}]}$
Nondet	$\overline{[P] \ x := \text{nondet} \ [\exists x. P]}$
Sequence	$\frac{[P] \ c_1 \ [R] \quad [R] \ c_2 \ [Q]}{[P] \ c_1; c_2 \ [Q]}$
Choice	$\frac{[P] \ c_1 \ [Q_1] \quad [P] \ c_2 \ [Q_2]}{[P] \ c_1 + c_2 \ [Q_1 \vee Q_2]}$
Consequence (IL)	$\frac{P \rightarrow P \quad P \ c \ [Q'] \quad Q \rightarrow Q'}{[P] \ c \ [Q]}$
Disjunction	$\frac{[P_1] \ c \ [Q_1] \quad [P_2] \ c \ [Q_2]}{[P_1 \vee P_2] \ c \ [Q_1 \vee Q_2]}$
Frame (IL)	$\frac{[P] \ c \ [Q]}{[P \wedge R] \ c \ [Q \wedge R]}$ (modifies $\cap$) $FV(R) = \emptyset$
Iteration	$\frac{\forall n \geq 0. \ [P_n] \ c \ [P_{n+1}]}{[P_0] \ c^* \ [\exists k. P_k]}$

28.5 5. Separation Logic

28.5.1 Heap Model

- State: $((s, h))$ where $(s: \text{Var} \rightarrow \text{Val})$, $(h: \text{Loc} \rightarrow \text{Val})$
- $(h_1 \cdot h_2)$: union of disjoint heaps (domains are disjoint)
- $(s, h \models \text{emp})$ iff $(\text{dom}(h) = \emptyset)$
- $(s, h \models x \mapsto v)$ iff $(h = \{s(x) \mapsto v\})$

- $(s, h \models P \star Q) \text{ iff } (\exists h_1, h_2: h = h_1 \cdot h_2), (s, h_1 \models P), (s, h_2 \models Q)$
- $(s, h \models P \mathbin{\text{--}! *} Q) \text{ iff } (\forall h' \text{ bot } h: s, h' \models P \Rightarrow s, h \cdot h' \models Q)$

28.5.2 Key SL Rules

Rule	Formula
Frame	$\frac{(\frac{P}{c} \star Q)}{c \star (Q \star R)}$ (no mod. var in (R))
Alloc	$(\text{emp}) \ x := \text{alloc}() \ [x \mapsto _]$
Read	$(x \mapsto v) \ y := [x] \ [x \mapsto v \ \text{and} \ y = v]$
Write	$(x \mapsto _) \ [x] := y \ [x \mapsto y]$
Free	$(x \mapsto _) \ \text{free}(x) \ [\text{emp}]$

28.5.3 List Predicates

- $(ls(a_1, a_2) \trianglelefteq (a_1 = a_2 \ \text{and} \ \text{emp}) \ \vee (a_1 \neq a_2 \ \text{and} \ \exists \ell. a_1 \mapsto \ell \star ls(\ell, a_2)))$
- $(\text{list}(a) \trianglelefteq ls(a, \text{nil}))$

28.5.4 ISL Heap Rules

Rule	Formula
Read	$([v \mapsto w \star P] \ x := [v] \ [v \mapsto w \star P \ \text{and} \ x = w])$
Write	$([v \mapsto _ \star P] \ [v] := y \ [v \mapsto y \star P])$
Alloc	$(\text{emp}) \ x := \text{alloc}() \ [x \mapsto _]$
Free	$([v \mapsto _] \ \text{free}(v) \ [\text{emp}])$

28.6 6. Abstract Interpretation

28.6.1 Galois Connections

Property	Formula
GC definition	$(\alpha(c) \sqsubseteq_A a \text{ iff } c \sqsubseteq_C \gamma(a))$
(α) preserves	Least upper bounds ($\sqcup$)
(γ) preserves	Greatest lower bounds ($\sqcap$)
GI condition	(α) surjective, (γ) injective, $(\alpha \circ \gamma = \text{id})$
Closure operator	$(\gamma \circ \alpha)$ is extensive, monotone, idempotent
Expressible elements	$(c = \gamma(\alpha(c)))$

28.6.2 Abstract Semantics Soundness

Concept	Formula
Soundness	$(\alpha(\llbracket c \rrbracket P) \sqsubseteq \llbracket \alpha(P) \rrbracket)$
Equivalent	$(\llbracket c \rrbracket \gamma(a) \sqsubseteq \gamma(\llbracket c \rrbracket a))$
BCA	$(\llbracket c \rrbracket_A = \alpha \circ \llbracket c \rrbracket \circ \gamma)$
Completeness	$(\alpha \circ \llbracket c \rrbracket = \llbracket c \rrbracket \circ \alpha)$

28.6.3 Local Completeness Logic (LCL)

Concept	Formula
Closure (A)	$(A = \gamma \circ \alpha)$
Global completeness	

Concept	Formula
	$\forall P. A(\llbracket c \rrbracket P) = \llbracket c \rrbracket^{\#} A(P)$
Local completeness	$\mathbb{C}_P(e): A(\llbracket e \rrbracket P) = A(\llbracket e \rrbracket A(P))$
LCL triple	$\vdash_A [P] \ c \ [Q]$ with $(Q \subseteq \llbracket c \rrbracket P \subseteq A(Q))$
Verification theorem	LCL derivation + local completeness $\rightarrow$ global soundness

28.6.4 Abstract Domains

Domain	Elements	ACC?	Needs Widening?
Sign	$\{\bot, -, 0, +, \top\}$	Yes	No
Constant	$\{\bot, c, \top\}$ for $c \in \mathbb{Z}$	No	Yes
Interval	$[l, h]$ mid $l \leq h$ $\cup \{\bot\}$	No	Yes (∇)
Congruence	$a \mathbb{Z} + b$	Yes	No
Octagon	$\pm x \pm y \leq c$	No	Yes
Polyhedron	$\sum a_i x_i \leq d$	No	Yes

28.6.5 Interval Operations

- $[l_1, h_1] + [l_2, h_2] = [l_1 + l_2, h_1 + h_2]$
- $[l_1, h_1] \times [l_2, h_2] = [\min(l_1 l_2, l_1 h_2, h_1 l_2, h_1 h_2), \max(\dots)]$

- $\llbracket [a,b] \nabla [c,d] = [\text{if } c < a \text{ then } -\infty \text{ else } a, \text{if } d > b \text{ then } +\infty \text{ else } b] \rrbracket$
- $\llbracket [a,b] \Delta [c,d] = [\text{if } a = -\infty \text{ then } c \text{ else } a, \text{if } b = +\infty \text{ then } d \text{ else } b] \rrbracket$

28.7 7. Control Flow Analysis (0-CFA for FUN)

28.7.1 Abstract Domains

- $\llbracket \hat{C} : \text{Lab} \rightarrow \text{wp}(\text{Term}) \rrbracket$ — cache: which function abstractions reach each program point
- $\llbracket \hat{\rho} : \text{Var} \rightarrow \text{wp}(\text{Term}) \rrbracket$ — environment: which abstractions each variable may bind

28.7.2 Acceptability Clauses $\llbracket (\hat{C}, \hat{\rho}) \models e \rrbracket$

Expression	Clause
$\llbracket c^{\ell} \rrbracket$	$\{\emptyset\} \subseteq \hat{C}(\ell)$
$\llbracket x^{\ell} \rrbracket$	$\hat{\rho}(x) \subseteq \hat{C}(\ell)$
$\llbracket (\text{fn } x \rightarrow t)^{\ell} \rrbracket$	$\{\text{fn } x \rightarrow t\} \subseteq \hat{C}(\ell)$
$\llbracket (t_1 \mid t_2)^{\ell} \rrbracket$	$\llbracket (\hat{C}, \hat{\rho}) \models t_1 \rrbracket \wedge \llbracket (\hat{C}, \hat{\rho}) \models t_2 \rrbracket$
$\llbracket (t_1 \mid t_2)^{\ell} \rrbracket$	$\llbracket (\hat{C}, \hat{\rho}) \models t_1 \rrbracket \wedge \llbracket (\hat{C}, \hat{\rho}) \models t_2 \rrbracket$
$\llbracket (\text{let } x = t_1 \text{ in } t_2)^{\ell} \rrbracket$	$\llbracket (\hat{C}, \hat{\rho}) \models t_1 \rrbracket \wedge \llbracket (\hat{C}, \hat{\rho}) \models t_2 \rrbracket$

28.7.3 Constraint Generation $\llbracket C^*[\![e]\!] \rrbracket$

Expression	Constraints
$\llbracket c^{\ell} \rrbracket$	$\{\emptyset\}$

Expression	Constraints
$\backslash(x^{\backslash ell})$	$\backslash(r(x) \backslash subseteq C(\backslash ell))$
$\backslash((\texttt{fn } x \rightarrow t)^{\backslash ell})$	$\backslash(\{\texttt{fn } x \rightarrow t\} \backslash subseteq C(\backslash ell) \cup C^{*[\![t]\!]} \cup (C^{*[\![t_1]\!]} \cup C^{*[\![t_2]\!]}) \cup \{\{\texttt{fn } x \rightarrow t_0\} \backslash subseteq C(\backslash ell_1) \rightarrow C(\backslash ell_2) \backslash subseteq r(x)\} \cup \{\{\texttt{fn } x \rightarrow t_0\} \backslash subseteq C(\backslash ell_1) \rightarrow C(\backslash ell_0) \backslash subseteq C(\backslash ell)\})$

28.7.4 Key Properties

- **Order:** $\backslash((\hat{C}_1, \hat{\rho}_1) \sqsubseteq (\hat{C}_2, \hat{\rho}_2))$ iff $\backslash(\forall \backslash ell. \hat{C}_1(\backslash ell) \backslash subseteq \hat{C}_2(\backslash ell))$ and $\backslash(\forall x. \hat{\rho}_1(x) \backslash subseteq \hat{\rho}_2(x))$
- **Moore family:** the set of acceptable analyses is closed under $\backslash(\sqcap) \rightarrow$ least (most precise) solution exists
- **0-CFA:** monovariant (one value per program point)
- **k-CFA:** context-sensitive with call strings of length $\backslash(k)$

28.7.5 CPA (Cartesian Product Algorithm)

- Contexts: $\backslash(\Delta = \text{Term}^m)$ (tuples of arguments)
- $\backslash(\hat{\rho}: (\text{Var} \times \Delta) \rightarrow \text{wp}(\text{Term}))$
- $\backslash(\hat{C}: (\text{Lab} \times \Delta) \rightarrow \text{wp}(\text{Term}))$

28.8 8. 0-CFA for $\backslash(\pi)$ -Calculus

28.8.1 Abstract Domains

- $\backslash(\rho: \text{Var} \rightarrow \text{wp}(\text{Const}))$ — which constants each variable may bind
- $\backslash(\kappa: \text{Var} \rightarrow \text{wp}(\text{Const}))$ — which constants may be communicated over each channel
- Extension: $\backslash(\rho(n) = \{n\})$ for constants $\backslash(n)$

28.8.2 Validation Clauses

Construct	Clause
$\overline{u} \wedge v$	$\forall n \in \rho(u): \rho(v) \subseteq \kappa(n)$
$u(x)$	$\forall n \in \rho(u): \kappa(n) \subseteq \rho(x)$
τ	Always true
$\pi.P$	$(\rho, \kappa) \models_A \pi \wedge (\rho, \kappa) \models_P P$
$P_1 \mid P_2$	$(\rho, \kappa) \models_P P_1 \wedge (\rho, \kappa) \models_P P_2$
$\sum_i \pi_i.P_i$	$\forall i: (\rho, \kappa) \models_A \pi_i \wedge (\rho, \kappa) \models_P P_i$
$[x=y]P$	$(\rho, \kappa) \models_P P \text{ (or } \rho(x) \cap \rho(y) \neq \emptyset \rightarrow (\rho, \kappa) \models_P P)$
$\nu n.P$	$(\rho, \kappa) \models_P P$
$!P$	$(\rho, \kappa) \models_P P$

28.8.3 Theoretical Properties

- **Subject reduction:** $P \rightarrow Q$ and $(\rho, \kappa) \models_P P \rightarrow (\rho, \kappa) \models_P Q$
- **Substitution lemma:** $\lfloor m \rfloor \subseteq \rho(x) \rightarrow (\rho, \kappa) \models_P \lfloor P[m/x] \rfloor$
- **Moore family:** $\{(\rho, \kappa) \mid (\rho, \kappa) \models_P P\}$ is closed under $\sqcap \rightarrow$ least solution exists

28.9 9. Common Exam Tricks

Pattern	Technique
Prove HL triple	Use consequence to weaken postcondition / strengthen precondition
Prove IL triple	

Pattern	Technique
	Show every poststate has a prestate witness
Find loop invariant	Look for preserved relationship (e.g., $x = n!$ in factorial)
Find loop variant	Decreasing natural-number expression (e.g., $n-i$ in factorial)
Construct Galois connection	Define γ first (most natural), then α as best approximation
Determine completeness	Check if $\alpha \circ F = \alpha \circ F \circ \gamma \circ \alpha$ holds for the given (P)
Generate CFA constraints	Follow syntax-directed rules, track labels carefully
Predict π -calculus communications	Output: $\rho(v) \subseteq \kappa(u)$; Input: $\kappa(u) \subseteq \rho(x)$
Check Moore family	Verify closure under $\sqcap$ (intersection of any set of solutions is a solution)
Design widening	Force unstable bounds to $\perp$

28.10 10. Key Notation Summary

Symbol	Meaning
$\llbracket c \rrbracket$	Denotational semantics of command c
$\{P\} c \{Q\}$	Hoare triple (over, forward)
$[P] c [Q]$	IL triple (under, forward)
$\langle P \rangle c \langle Q \rangle$	NC triple (under, backward)
$(P) c (Q)$	SIL triple (over, backward)
α, γ	Abstraction, concretization
$\sqsubseteq, \sqcup, \sqcap$	Lattice ordering, join, meet
$\bot, \top$	Bottom, top of lattice

Symbol	Meaning
$\backslash(\backslash nabla, \backslash Delta\backslash)$	Widening, narrowing
$\backslash(\backslash hat{C}, \backslash hat{\backslash rho}\backslash)$	CFA cache, CFA environment
$\backslash(\backslash rho, \backslash kappa\backslash)$	$\backslash(\backslash pi\backslash)$ -calculus abstract env, channel env
$\backslash(C\backslash ell), r(x)\backslash)$	CFA constraint variables
$\backslash(A = \backslash gamma\backslash circ\backslash alpha\backslash)$	Closure operator
$\backslash((\backslash hat{C}, \backslash hat{\backslash rho}) \backslash models e\backslash)$	CFA acceptability
$\backslash((\backslash rho, \backslash kappa) \backslash models_P P\backslash)$	$\backslash(\backslash pi\backslash)$ -calculus CFA acceptability

29 Algorithm Extraction

29.1 A-01: Kleene Fixpoint Iteration

29.1.1 Purpose

Compute the least fixpoint of a monotone function $\backslash(F\backslash)$ on a complete lattice, used to compute loop semantics in both concrete and abstract settings.

29.1.2 Input

- A monotone function $\backslash(F: L \rightarrow L\backslash)$ on a complete lattice $\backslash((L, \backslash sqsubseteq, \backslash bot, \backslash top, \backslash sqcup, \backslash sqcap)\backslash)$

29.1.3 Output

- $\backslash(\operatorname{lfp}\{F\}\backslash)$, the least fixpoint of $\backslash(F\backslash)$

29.1.4 Pseudocode

```

x ← ⊥
repeat
  x ← F(x)
until x is a fixpoint (F(x) = x)
return x

```

29.1.5 Complexity

- Termination depends on the height of the lattice (L)
- If (L) has finite height (h) , at most (h) iterations
- If (L) has infinite height (e.g., intervals), may not terminate without widening

29.1.6 Correctness Intuition

Kleene's fixpoint theorem: for a continuous function on a CPO, the least fixpoint equals $(\bigcup_{n \geq 0} F^n(\bot))$.

29.1.7 Common Mistakes

- Assuming termination on infinite-height lattices without widening
- Confusing least fixpoint with greatest fixpoint
- Forgetting monotonicity requirement

29.1.8 Exam Relevance

Fundamental for understanding loop analysis in abstract interpretation. Used in Lectures 12, 15.

29.2 A-02: Abstract Fixpoint with Widening

29.2.1 Purpose

Compute a sound over-approximation of the least fixpoint when the abstract lattice has infinite height (e.g., intervals).

29.2.2 Input

- A monotone function $(F^\# : A \rightarrow A)$ on an abstract domain (A)
- A widening operator $(\nabla : A \times A \rightarrow A)$

29.2.3 Output

- A post-fixpoint (x) such that $(F^\#(x) \sqsubseteq x)$ (sound approximation of $(\text{lfp}(F))$)

29.2.4 Pseudocode

```
x ← ⊥  
repeat  
  x ← x ∇ F#(x)  
until F#(x) ⊆ x  
return x
```

29.2.5 Complexity

Widening guarantees termination in finite time regardless of lattice height.

29.2.6 Correctness Intuition

If $\gamma(x)$ is a post-fixpoint ($F^{\#}(x) \sqsubseteq x$), then $\text{lfp}(F) \sqsubseteq \gamma(x)$ by soundness.

29.2.7 Common Mistakes

- Widening too early, causing precision loss
- Using $\sqcup$ instead of ∇ (no termination guarantee)
- Forgetting that widening must be used at loop heads only

29.2.8 Exam Relevance

Central for interval analysis. Frequently examined in combination with narrowing for precision recovery.

29.3 A-03: Worklist Algorithm for Abstract Interpretation

29.3.1 Purpose

Efficiently compute the least fixpoint of a system of abstract semantic equations over a control flow graph.

29.3.2 Input

- CFG with program points $\ell_1, \dots, \ell_n$

- Initial abstract state $\backslash(a_0\backslash)$ at entry point
- Abstract transfer functions $\backslash(F^{\wedge}_{\#_ell}\backslash)$ for each edge

29.3.3 Output

- Abstract invariant $\backslash(I(\ell)\backslash)$ for each program point $\backslash(\ell\backslash)$

29.3.4 Pseudocode

```

for each  $\ell$ :  $I(\ell) \leftarrow \perp$ 
 $I(\ell_{\text{entry}}) \leftarrow a_0$ 
 $W \leftarrow \{\ell_{\text{entry}}\}$ 
while  $W \neq \emptyset$ :
     $\ell \leftarrow \text{remove from } W$ 
    for each successor  $\ell'$  of  $\ell$ :
         $\text{new} \leftarrow I(\ell) \sqcup F^{\wedge}_{\#\{\ell \rightarrow \ell'\}}(I(\ell))$ 
        if  $\text{new} \neq I(\ell')$ :
             $I(\ell') \leftarrow \text{new}$ 
             $W \leftarrow W \cup \{\ell'\}$ 
return  $I$ 

```

29.3.5 Complexity

- Each edge processed at most $\backslash(h\backslash)$ times where $\backslash(h\backslash)$ is lattice height
- With widening: edges processed at most once per widening point

29.3.6 Correctness Intuition

Join with existing values ensures monotonic increase; termination by lattice ACC or widening.

29.3.7 Common Mistakes

- Forgetting to join new and old values (instead of just assigning)
- Missing widening at loop heads
- Lattice height assumed finite when it's not

29.3.8 Exam Relevance

Standard algorithm for implementing static analyses. Likely asked in exam.

29.4 A-04: 0-CFA Constraint Generation

29.4.1 Purpose

Generate a system of constraints whose least solution gives the 0-CFA of a functional program (monovariant CFA).

29.4.2 Input

- A labeled expression $\langle e \rangle$ with labels $\langle \ell \in \text{Lab} \rangle$
- Abstraction: set of function abstractions $\langle \text{Term} \rangle$

29.4.3 Output

- A set $\langle C^*[\![e]\!] \rangle$ of constraints and conditional constraints over variables $\langle C(\ell) \rangle$ and $\langle r(x) \rangle$
- Least solution $\langle (\hat{C}, \hat{\rho}) \rangle$ is the most precise 0-CFA

29.4.4 Constraint Generation Rules

Constants: $\langle C^*[\![c^{\ell}]\!] \rangle = \emptyset$

Variables: $\langle C^*[\![x^{\ell}]\!] \rangle = \{ r(x) \mid r(x) \subseteq C(\ell) \}$

Functions: $\langle C^*[\![\langle \text{fn } x \mapsto e_0 \rangle^{\ell}]\!] \rangle = \{ \langle \text{fn } x \mapsto e_0 \rangle \mid \langle \text{fn } x \mapsto e_0 \rangle \subseteq C(\ell) \} \cup C^*[\![e_0]\!]$

Application: $\langle C^*[\![e_1^{\ell_1} e_2^{\ell_2}]^{\ell}]\!] \rangle = C^*[\![e_1]\!] \cup C^*[\![e_2]\!] \cup \{ \langle \text{fn } x \mapsto e_0 \rangle \mid \langle \text{fn } x \mapsto e_0 \rangle \subseteq C(\ell_1) \mapsto C(\ell_2) \subseteq r(x) \mid \langle \text{fn } x \mapsto e_0 \rangle \in \text{Term} \} \} \cup \{ \langle \text{fn } x \mapsto e_0 \rangle \mid \langle \text{fn } x \mapsto e_0 \rangle \subseteq C(\ell_1) \mapsto C(\ell_0) \subseteq C(\ell) \mid \langle \text{fn } x \mapsto e_0 \rangle \in \text{Term} \}$

Let: $\langle C^*[\![\langle \text{let } x = t_1^{\ell_1} \text{ in } t_2^{\ell_2} \rangle^{\ell}]\!] \rangle = C^*[\![t_1]\!] \cup C^*[\![t_2]\!] \cup \{ C(\ell_1) \subseteq r(x), C(\ell_2) \subseteq C(\ell) \}$

29.4.5 Complexity

- $\langle O(|e|^2) \rangle$ constraints generated
- Least solution computable via fixpoint in $\langle O(|e|^3) \rangle$

29.4.6 Correctness Intuition

Constraints encode the acceptability relation $((\hat{C}, \hat{\rho}) \models e)$; least solution is most precise analysis.

29.4.7 Common Mistakes

- Forgetting conditional constraints for applications
- Confusing $(\subseteq)$ direction
- Not handling all function abstractions in (Term)

29.4.8 Exam Relevance

High — 0-CFA is a staple exam topic. Exercises require constraint generation and solution.

29.5 A-05: Interval Widening

29.5.1 Purpose

Ensure termination of fixpoint iteration for the interval domain by forcing unstable bounds to $(\pm\infty)$.

29.5.2 Input

- Two intervals $([a, b]), ([c, d])$ with $(a, b, c, d \in \mathbb{Z} \cup \{-\infty, +\infty\})$

29.5.3 Output

- An interval $([a, b] \nabla [c, d])$ that over-approximates both

29.5.4 Formula

$$[a, b] \nabla [c, d] = \begin{cases} [-\infty, b] & \text{if } c < a \\ [a, +\infty] & \text{if } d > b \\ [a, b] & \text{otherwise} \end{cases}$$

29.5.5 Complexity

$(O(1))$

29.5.6 Correctness Intuition

Once a bound moves in a direction, it is pushed to infinity, so it cannot change again. Only finitely many changes per bound.

29.5.7 Common Mistakes

- Widening from $(-\infty)$ gives $([-\infty, +\infty])$ immediately (too imprecise)
- Widening after stabilization is unnecessary
- Forgetting that widening loses precision permanently

29.5.8 Exam Relevance

High — interval widening is a classic exam question. Often combined with narrowing.

29.6 A-06: Syntax-Directed CFA ($\models_s$)

29.6.1 Purpose

Compute CFA using a syntax-directed system that analyzes function bodies once at definition time.

29.6.2 Input

- Labeled expression (e)

29.6.3 Output

- $(C^*[\![e]\!])$, a set of constraints

29.6.4 Key Difference from Acceptability

The syntax-directed relation $\models_s$ analyzes function bodies once regardless of call count. This means:

- Functions are analyzed even if never called
- No “call-context” sensitivity (0-CFA)

- Better for modular analysis

29.6.5 Rules

Same as acceptability but without runtime context: function body constraints are generated at definition time.

29.6.6 Complexity

Linear in program size.

29.7 A-07: (k) -CFA (Call String Approach)

29.7.1 Purpose

Refine 0-CFA by distinguishing calling contexts up to depth (k) .

29.7.2 Input

- Expression (e) , bound (k) on call string length

29.7.3 Output

- Context-sensitive cache $(\hat{C}(\ell, \delta))$ and environment $(\hat{\rho}(x, \delta))$ where (δ) is a call string of length $(\leq k)$

29.7.4 Key Change

- Abstract values replaced by $(\hat{C}, \hat{\rho}, \delta)$ where (δ) tracks the call site history
- $(k=0)$: monovariant (0-CFA)
- $(k=1)$: call-site sensitivity
- $(k=2)$: two-level call stack

29.7.5 Complexity

- $(O(|e|^{k+1}))$ — exponential in (k)
- $(k=1)$ is common practical choice

29.7.6 Correctness Intuition

Different call sites create different instances of formal parameters, removing spurious flows from merged contexts.

29.7.7 Common Mistakes

- Thinking k -CFA is always more precise (it is, but at cost)
- Forgetting that k -CFA still over-approximates

29.7.8 Exam Relevance

Exercise E-03 asks to compare 0-CFA and 1-CFA results.

30 Complete Exercise Collection

30.1 Source

All exercises from the official exercise PDFs and their extracted text versions.

30.2 Easy

30.2.1 Exercise E-01: Guard Axiom Across Logics

Source: ProgramAnalysis_exercises_a.txt (Ex. 1) **Lecture:** Lectures 03–08 (HL, IL, NC, SIL) **Page:** 1 **Difficulty:** Easy **Tags:** hoare logic, incorrectness logic, necessary condition logic, sufficient incorrectness logic, boolean guards

30.2.1.1 Statement

Let us consider the following axiom for atomic boolean guards $\langle b? \rangle$, where the parentheses $\langle \cdot \rangle$ are used to denote a generic program logic triple of either Hoare logic, IL, NC or SIL.

$$\llbracket \langle \text{while } b? \text{ do } P \rangle \rrbracket = \langle P \text{ while } b \rangle$$

Explain for which logics (HL, IL, NC, SIL) the axiom is sound (for any precondition $\langle P \rangle$ and boolean guard $\langle b \rangle$):

- if the axiom is sound, prove its validity;
- if it is not sound, first provide a concrete counterexample and then say under which conditions on $\langle P \rangle$ and $\langle b \rangle$ the axiom would become sound.

30.2.1.2 Official Solution

Hoare Logic. A Hoare triple $\langle \{P\} \text{ c } \{Q\} \rangle$ is sound when every terminating execution from a state satisfying $\langle P \rangle$ ends in a state satisfying $\langle Q \rangle$. Since executing $\langle b? \rangle$ does not modify the state, every reachable state satisfies both $\langle P \rangle$ and $\langle b \rangle$. In fact:

$$\llbracket b? \rrbracket P = (P \wedge b) \subseteq (P \vee b)$$

Hence the axiom is **sound** for Hoare Logic.

Incorrectness Logic. A valid IL triple $\langle [P] \text{ c } [Q] \rangle$ requires $\langle Q \rangle \subseteq \llbracket \text{c} \rrbracket P$. For the proposed axiom we would need:

$$P \vee b \subseteq \llbracket b? \rrbracket P = P \wedge b$$

This is false in general. Counterexample: $\langle P = \text{true} \rangle, \langle b = \text{false} \rangle$. Then $\langle P \vee b = \text{true} \rangle, \langle P \wedge b = \text{false} \rangle$. The axiom becomes sound iff $\langle P \vee b = P \wedge b \rangle$, i.e., iff $\langle P = b \rangle$.

Necessary Condition Logic. NC requires $\llbracket \text{c} \rrbracket^{\text{op}} Q \subseteq P$. Since $\llbracket b? \rrbracket^{\text{op}} Q = Q \wedge b$:

$$\llbracket b? \rrbracket^{\text{op}} (P \vee b) = (P \vee b) \wedge b = b$$

The axiom is sound for NC iff $\langle b \subseteq P \rangle$. Counterexample: $\langle P = \text{false} \rangle, \langle b = \text{true} \rangle$.

Sufficient Incorrectness Logic. SIL requires an under-approximation condition: $\langle P \rangle \subseteq \llbracket \text{c} \rrbracket^{\text{op}} Q$. Thus:

$$P \subseteq \llbracket b? \rrbracket^{\text{op}} (P \vee b) = (P \vee b) \wedge b = b$$

The axiom is sound for SIL iff $(P \sqsubseteq b)$. This is false in general.
Counterexample: $(P = \text{true}, b = \text{false})$.

30.2.1.3 Key Concepts

- HL triple validity: $(\llbracket c \rrbracket P \sqsubseteq Q)$
- IL triple validity: $(\llbracket c \rrbracket P \sqsupseteq Q)$
- NC triple validity: $(\llbracket c \rrbracket^{\{\text{op}\}} Q \sqsubseteq P)$
- SIL triple validity: $(P \sqsubseteq \llbracket c \rrbracket^{\{\text{op}\}} Q)$
- Boolean guard semantics: $(\llbracket b \rrbracket P = P \wedge b)$

30.2.1.4 Typical Exam Insight

Tests understanding of the fundamental difference between over-approximation (HL) and under-approximation (IL/NC/SIL) logics.

30.3 Medium

30.3.1 Exercise E-02: Galois Connection Design for Abstract Domain

Source: ProgramAnalysis_exercises_a.txt (Ex. 2) **Lecture:** Lectures 12–14 (Galois Connections, Abstract Domains) **Page:** 1 **Difficulty:** Medium
Tags: galois connection, abstraction map, concretization map, best correct approximation, completeness, sign domain

30.3.1.1 Statement

Let us consider the usual concrete domain $(\wp(\mathbb{Z}), \sqsubseteq)$ of sets of integers ordered by inclusion and the abstract domain $(A = \{\bot, =0, \leq 0, >0, \top\})$ with the obvious concretization function.

1. Define the GC maps $(\gamma: A \rightarrow \wp(\mathbb{Z}))$ and $(\alpha: \wp(\mathbb{Z}) \rightarrow A)$.
2. Draw the Hasse diagram of (A) .
3. Define the bca $(\cdot \times_A \cdot)$ for the product of integers $(\cdot \times \cdot)$.

4. Show that $(\cdot \times_A \cdot)$ is not complete by exhibiting a counterexample.


30.3.1.2 Official Solution

1. Galois connection maps:

Concretization: $\begin{aligned} \gamma(\bot) &= \emptyset, \quad \gamma(=0) = \{0\}, \\ \gamma(\leq 0) &= \{z \in \mathbb{Z} \mid z \leq 0\}, \quad \gamma(>10) = \{z \in \mathbb{Z} \mid z > 10\}, \\ \gamma(>0) &= \{z \in \mathbb{Z} \mid z > 0\}, \quad \gamma(\top) = \mathbb{Z}. \end{aligned}$

Abstraction: $\begin{aligned} \alpha(X) &= \begin{cases} \bot & \text{if } X = \emptyset \\ =0 & \text{if } X = \{0\} \\ \leq 0 & \text{if } X \subseteq \{z \mid z \leq 0\} \\ >10 & \text{if } X \subseteq \{z \mid z > 10\} \\ >0 & \text{if } X \subseteq \{z \mid z > 0\} \\ \top & \text{otherwise} \end{cases} \end{aligned}$

2. Hasse diagram:



3. Best correct approximation of multiplication:

$\alpha(a \times_A b) = \alpha(\{x \cdot y \mid x \in \gamma(a), y \in \gamma(b)\})$

$(\times_A)$	$(\bot)$	$(=0)$	(≤ 0)	(>10)	(>0)	$(\top)$
$(\bot)$	$(\bot)$	$(\bot)$	$(\bot)$	$(\bot)$	$(\bot)$	$(\bot)$
$(=0)$	$(\bot)$	$(=0)$	$(=0)$	$(=0)$	$(=0)$	$(=0)$
(≤ 0)	$(\bot)$	$(=0)$	$(\top)$	(≤ 0)	(≤ 0)	$(\top)$
(>10)	$(\bot)$	$(=0)$	(≤ 0)	(>10)	(>10)	$(\top)$
(>0)	$(\bot)$	$(=0)$	(≤ 0)	(>10)	(>0)	$(\top)$
$(\top)$	$(\bot)$	$(=0)$	$(\top)$	$(\top)$	$(\top)$	$(\top)$

4. Non-completeness:

Take $(X = \{-1\})$, $(Y = \{-1\})$. Then $(\alpha(X) = \leq 0)$, $(\alpha(Y) = \leq 0)$. Concrete multiplication gives $(X \times Y = \{1\})$, so $(\alpha(X \times Y) = (>0))$. However, $(\leq 0 \times_A \leq 0 = \text{top})$ because the products may be (0) or positive. Therefore $(\alpha(X \times Y) \neq \alpha(X) \times_A \alpha(Y))$, proving incompleteness.

30.3.1.3 Key Concepts

- Galois connection definition: $(\alpha(c) \sqsubseteq_A a \text{ iff } c \sqsubseteq \gamma(a))$
- BCA formula: $(F^A = \alpha \circ F \circ \gamma)$
- Completeness equation: $(\alpha \circ F = F^A \circ \alpha)$
- Formula F-06, F-07, F-08, F-09

30.3.1.4 Typical Exam Insight

Tests understanding of Galois connection construction and the distinction between soundness and completeness.

30.3.2 Exercise E-03: CFA for Higher-Order Functions

Source: ProgramAnalysis_exercises_a.txt (Ex. 3) **Lecture:** Lectures 17–24 (CFA) **Page:** 2 **Difficulty:** Medium **Tags:** CFA, 0-CFA, 1-CFA, constraint generation, flow logic, acceptability

30.3.2.1 Statement

Consider the following expression (e) :

```
let apply = fn f => f 2
in let inc = fn x => x + 4
in let dbl = fn y => y * 2
in (apply inc) - (apply dbl)
```

1. Add labels to all subexpressions and function abstractions.
2. Guess a possible analysis result for Pure 0-CFA and verify it using the corresponding acceptability relation $(\models)$. In particular, comment on the abstract values associated with the two calls to apply.

3. Consider the following additional abstract flow: $(\text{fn } w \rightarrow w \in \hat{C}(\text{Label}(f)))$. Does the acceptability relation (models) still hold? What does this say about the difference between soundness and precision?
4. Discuss how the analysis changes using the syntax-directed version of the acceptability relation (models_s) .
5. Extract the corresponding system of constraints.
6. Explain how the result changes under 1-CFA. Which spurious flows disappear, and why?

30.3.2.2 Official Solution

1. Labeled expression.

$$\begin{aligned} & e \triangleq \& (\text{let } \text{apply} = (\text{fn } f \rightarrow (f^1 \ 2^2)^3)^4 \ \& \ (\text{in } (\text{let } \text{inc} = (\text{fn } x \rightarrow (x^5 + 4^6)^7)^8 \ \& \ (\text{in } (\text{let } \text{dbl} = (\text{fn } y \rightarrow (y^9 * 2^{10})^{11})^{12} \ \& \ (\text{in } ((\text{apply}^{13} \ \text{inc}^{14})^{15} - (\text{apply}^{16} \ \text{dbl}^{17})^{18})^{19})^{20})^{21})^{22} \end{aligned}$$

2. Acceptability relation unfolding.

The relation $(\hat{C}, \hat{\rho}) \models e$ is checked by applying the acceptability rules:

- **[let] rule for outer let:** $(\hat{C}, \hat{\rho}) \models (\text{fn } f \rightarrow (f^1 \ 2^2)^3)^4$ and $(\hat{C}, \hat{\rho}) \models (\text{let inc} = \dots)^{21}$, with $\hat{C}(4) \subseteq \hat{\rho}(\text{apply})$ and $\hat{C}(21) \subseteq \hat{C}(22)$.
- **[fn] rule:** $(\text{fn } f \rightarrow (f^1 \ 2^2)^3) \subseteq \hat{C}(4)$.
- **[let] rule for inc:** $(\hat{C}, \hat{\rho}) \models (\text{fn } x \rightarrow (x^5 + 4^6)^7)^8$ and $(\hat{C}, \hat{\rho}) \models (\text{let dbl} = \dots)^{20}$, with $\hat{C}(8) \subseteq \hat{\rho}(\text{inc})$ and $\hat{C}(20) \subseteq \hat{C}(21)$.
- **[fn] rule:** $(\text{fn } x \rightarrow (x^5 + 4^6)^7) \subseteq \hat{C}(8)$.

- **[let] rule for dbl:** $((\hat{C}, \hat{\rho}) \models \text{ttt}\{fn\} y \rightarrow (y^9 * 2^{10})^{11})^{12})$ and $((\hat{C}, \hat{\rho}) \models (\text{ttt}\{apply\}^{13} \text{ttt}\{inc\}^{14})^{15} - (\text{ttt}\{apply\}^{16} \text{ttt}\{dbl\}^{17})^{18})^{19})$, with $(\hat{C}(12) \subseteq \hat{\rho}(\text{ttt}\{dbl\}))$ and $(\hat{C}(19) \subseteq \hat{C}(20))$.
- **[fn] rule:** $(\text{ttt}\{fn\} y \rightarrow (y^9 * 2^{10})^{11}) \subseteq \hat{C}(12)$.
- **Subtraction rule:** $((\hat{C}, \hat{\rho}) \models \text{ttt}\{apply\}^{13} \text{ttt}\{inc\}^{14})^{15})$ and $((\hat{C}, \hat{\rho}) \models (\text{ttt}\{apply\}^{16} \text{ttt}\{dbl\}^{17})^{18})$, with $(\hat{C}(15) \subseteq \hat{C}(19))$ and $(\hat{C}(18) \subseteq \hat{C}(19))$.
- **[app] rule for $((\text{ttt}\{apply\}^{13} \text{ttt}\{inc\}^{14})^{15})$:** $((\hat{C}, \hat{\rho}) \models \text{ttt}\{apply\}^{13})$ and $((\hat{C}, \hat{\rho}) \models \text{ttt}\{inc\}^{14})$, and for each $(\text{ttt}\{fn\} f \rightarrow (f^1 2^2)^3 \text{ in } \hat{C}(13))$: $(\hat{C}(14) \subseteq \hat{\rho}(f))$ and $(\hat{C}(3) \subseteq \hat{C}(15))$.
- **[app] rule for $((\text{ttt}\{apply\}^{16} \text{ttt}\{dbl\}^{17})^{18})$:** $((\hat{C}, \hat{\rho}) \models \text{ttt}\{apply\}^{16})$ and $((\hat{C}, \hat{\rho}) \models \text{ttt}\{dbl\}^{17})$, and for each $(\text{ttt}\{fn\} f \rightarrow (f^1 2^2)^3 \text{ in } \hat{C}(16))$: $(\hat{C}(17) \subseteq \hat{\rho}(f))$ and $(\hat{C}(3) \subseteq \hat{C}(18))$.

An acceptable solution:

```
[ \begin{aligned} \hat{C}(4) &= \{ \text{ttt}\{fn\} f \rightarrow (f^1 2^2)^3 \} \\ \hat{C}(8) &= \{ \text{ttt}\{fn\} x \rightarrow (x^5 + 4^6)^7 \} \parallel \hat{C}(12) \\ &= \{ \text{ttt}\{fn\} y \rightarrow (y^9 * 2^{10})^{11} \} \parallel \hat{C}(13) &= \\ \hat{C}(16) &= \{ \text{ttt}\{fn\} f \rightarrow (f^1 2^2)^3 \} \parallel \hat{C}(14) &= \{ \\ \text{ttt}\{fn\} x \rightarrow (x^5 + 4^6)^7 \} \parallel \hat{C}(17) &= \{ \text{ttt}\{fn\} y \\ \rightarrow (y^9 * 2^{10})^{11} \} \parallel \hat{C}(1) &= \{ \text{ttt}\{fn\} x \\ \rightarrow (x^5 + 4^6)^7, \text{ttt}\{fn\} y \rightarrow (y^9 * 2^{10})^{11} \} \\ \parallel \hat{C}(i) &= \emptyset \text{ for all remaining labels } i \end{aligned} ]
```

```
[ \begin{aligned} \hat{\rho}(\text{ttt}\{apply\}) &= \{ \text{ttt}\{fn\} f \\ \rightarrow (f^1 2^2)^3 \} \parallel \hat{\rho}(\text{ttt}\{inc\}) &= \{ \text{ttt}\{fn\} x \\ \rightarrow (x^5 + 4^6)^7 \} \parallel \hat{\rho}(\text{ttt}\{dbl\}) &= \{ \text{ttt}\{fn\} y \\ \rightarrow (y^9 * 2^{10})^{11} \} \parallel \hat{\rho}(f) &= \{ \text{ttt}\{fn\} x \\ \rightarrow (x^5 + 4^6)^7, \text{ttt}\{fn\} y \rightarrow (y^9 * 2^{10})^{11} \} \\ \end{aligned} ]
```


Key observation: Because $\hat{C}(14) \subseteq \hat{\rho}(f)$ and $\hat{C}(17) \subseteq \hat{\rho}(f)$, 0-CFA merges the two calling contexts. Both $\texttt{inc}()$ and $\texttt{dbl}()$ flow to f , losing precision.

3. Extra flow. Adding $\texttt{fn } w \rightarrow w \text{ in } \hat{C}(1)$ is still sound (over-approximation) but less precise. This illustrates that acceptability expresses soundness, not optimal precision.

4. Syntax-directed $\texttt{models_s}$. The body of a function is analyzed once at definition time, not at each application. This avoids redundant re-analysis for multiple applications, but also analyzes the body even if the function is never applied. The analysis uses only terms occurring in the expression under investigation.

5. Constraint system. Extracted using syntax-directed rules $C^*[!e] \text{!}$:

For abstractions:
$$\begin{aligned} C^*[!(\texttt{fn } f \rightarrow (f^1 \ 2^2)^3)^4] \! &= \{(\texttt{fn } f \rightarrow (f^1 \ 2^2)^3) \subseteq C(4)\} \cup C^*[!(f^1 \ 2^2)^3] \! \parallel C^*[!(\texttt{fn } x \rightarrow (x^5 + 4^6)^7)^8] \! \\ &= \{(\texttt{fn } x \rightarrow (x^5 + 4^6)^7) \subseteq C(8)\} \cup C^*[!(x^5 + 4^6)^7] \! \parallel C^*[!(\texttt{fn } y \rightarrow (y^9 * 2^{\{10\}})^{11})^{12}] \! \\ &= \{(\texttt{fn } y \rightarrow (y^9 * 2^{\{10\}})^{11}) \subseteq C(12)\} \cup C^*[!(y^9 * 2^{\{10\}})^{11}] \! \end{aligned}$$

For let-bindings:
$$\begin{aligned} C^*[!(\texttt{let apply} = \text{dots})^{22}] \! &= C^*[!(\texttt{fn } f \rightarrow \text{dots})^4] \! \cup C^*[!(\texttt{let inc} = \text{dots})^{21}] \! \cup \{C(4) \subseteq r(\texttt{apply}), \\ &C(21) \subseteq C(22)\} \parallel C^*[!(\texttt{let inc} = \text{dots})^{21}] \! &= C^*[!(\texttt{fn } x \rightarrow \text{dots})^8] \! \cup C^*[!(\texttt{let dbl} = \text{dots})^{20}] \! \\ &\cup \{C(8) \subseteq r(\texttt{inc}), C(20) \subseteq C(21)\} \parallel C^*[!(\texttt{let dbl} = \text{dots})^{20}] \! &= C^*[!(\texttt{fn } y \rightarrow \text{dots})^{12}] \! \\ &\cup C^*[!(\texttt{apply}^{13} \ \texttt{inc}^{14})^{15} - (\texttt{apply}^{16} \ \texttt{dbl}^{17})^{18})^{19}] \! \parallel \\ &\&\text{quad} \cup \{C(12) \subseteq r(\texttt{dbl}), C(19) \subseteq C(20)\} \end{aligned}$$

For variables:
$$\begin{aligned} C^*[![f^1]!] \! &= \{r(f) \subseteq C(1)\} \parallel C^*[![x^5]!] \! = \{r(x) \subseteq C(5)\} \parallel C^*[![y^9]!] \! = \{r(y) \subseteq C(9)\} \\ &\parallel C^*[![\texttt{apply}^{13}]!] \! = \{r(\texttt{apply}) \subseteq C(13)\} \parallel C^*[![\texttt{inc}^{14}]!] \! = \{r(\texttt{inc}) \subseteq C(14)\} \end{aligned}$$

$\text{subseq } C(14) \setminus \setminus C^*[\![\text{apply}^{\{16\}}]\!] \&= \{r(\text{apply})$
 $\text{subseq } C(16) \setminus \setminus C^*[\![\text{dbl}^{\{17\}}]\!] \&= \{r(\text{dbl})$
 $\text{subseq } C(17) \setminus \end{aligned} \setminus$

Arithmetic constants generate no flow: $(C^*[\![2^2]\!] = C^*[\![4^6]\!] = C^*[\![2^{\{10\}}]\!] = \emptyset)$.

For applications, the constraint generation considers all abstractions in $(\text{Term}^* = \{\text{fn } f \mapsto (f^1 \setminus 2^2)^3, \text{fn } x \mapsto (x^5 + 4^6)^7, \text{fn } y \mapsto (y^9 \cdot 2^{\{10\}})^{\{11\}}\})$:

From $((\text{apply}^{\{13\}} \setminus \text{inc}^{\{14\}})^{\{15\}})$: $\begin{aligned} &C^*[\![\text{apply}^{\{13\}} \setminus \text{inc}^{\{14\}}]^{\{15\}}]\!] \&= C^*[\![\\ &[\text{apply}^{\{13\}}]\!] \cup C^*[\![\text{inc}^{\{14\}}]\!] \setminus \&\cup \setminus \\ &\{\text{fn } f \mapsto (f^1 \setminus 2^2)^3 \text{ subseq } C(13) \mapsto C(14) \\ &\text{subseq } r(f)\} \setminus \&\cup \setminus \{\text{fn } f \mapsto (f^1 \setminus 2^2)^3 \\ &\text{subseq } C(13) \mapsto C(3) \text{ subseq } C(15)\} \setminus \&\cup \setminus \{\text{fn } \\ &x \mapsto (x^5 + 4^6)^7 \text{ subseq } C(13) \mapsto C(14) \text{ subseq } \\ &r(x)\} \setminus \&\cup \setminus \{\text{fn } x \mapsto (x^5 + 4^6)^7 \text{ subseq } C(13) \\ &\mapsto C(7) \text{ subseq } C(15)\} \setminus \&\cup \setminus \{\text{fn } y \mapsto (y^9 \cdot 2^{\{10\}})^{\{11\}} \\ &\text{subseq } C(13) \mapsto C(14) \text{ subseq } r(y)\} \setminus \\ &\&\cup \setminus \{\text{fn } y \mapsto (y^9 \cdot 2^{\{10\}})^{\{11\}} \text{ subseq } C(13) \\ &\mapsto C(11) \text{ subseq } C(15)\} \end{aligned}$

Similarly for $((\text{apply}^{\{16\}} \setminus \text{dbl}^{\{17\}})^{\{18\}})$ with $(C(17))$ instead of $(C(14))$.

From $((f^1 \setminus 2^2)^3)$: $\begin{aligned} &C^*[\![f^1 \setminus 2^2]^3]\!] \&= C^*[\![\\ &[f^1]\!] \cup C^*[\![2^2]\!] \setminus \&\cup \setminus \{\text{fn } f \mapsto (f^1 \setminus 2^2)^3 \\ &\text{subseq } C(1) \mapsto C(2) \text{ subseq } r(f)\} \setminus \&\cup \setminus \{\text{fn } x \\ &\mapsto (x^5 + 4^6)^7 \text{ subseq } C(1) \mapsto C(2) \text{ subseq } r(x), \\ &\setminus C(7) \text{ subseq } C(3)\} \setminus \&\cup \setminus \{\text{fn } y \mapsto (y^9 \cdot 2^{\{10\}})^{\{11\}} \\ &\text{subseq } C(1) \mapsto C(2) \text{ subseq } r(y), \setminus C(11) \\ &\text{subseq } C(3)\} \end{aligned}$

Note the key constraints: $(C(14) \text{ subseq } r(f))$ and $(C(17) \text{ subseq } r(f))$, which merge the two call contexts.

6. 1-CFA. Under 1-CFA, each application gets a distinct call string:

- $(\delta_1 = \langle 15 \rangle)$ for $((\text{apply}^{\{13\}} \setminus \text{inc}^{\{14\}})^{\{15\}})$
- $(\delta_2 = \langle 18 \rangle)$ for $((\text{apply}^{\{16\}} \setminus \text{dbl}^{\{17\}})^{\{18\}})$

The acceptability relation becomes context-sensitive:

$\llbracket (\hat{C}, \hat{\rho}) \rrbracket \text{models}^{\{\text{ce}\}}_{\delta} e \llbracket$

where $\llbracket \delta \rrbracket$ is the call string and ce is the context environment mapping variables to call strings.

For the outer binding: $\llbracket \{\text{fn } f \rrbracket \rightarrow (f^1 \setminus 2^2)^3, \text{ce}_0 \rrbracket \subseteq \hat{C}(4, \delta_0) \llbracket \llbracket \hat{C}(4, \delta_0) \rrbracket \subseteq \hat{\rho}(\text{apply}, \delta_0) \llbracket$

The two applications produce:

- $\llbracket \hat{C}(14, \delta_0) \rrbracket \subseteq \hat{\rho}(f, \delta_1) \llbracket$
- $\llbracket \hat{C}(17, \delta_0) \rrbracket \subseteq \hat{\rho}(f, \delta_2) \llbracket$

Hence: $\llbracket \begin{aligned} \hat{\rho}(f, \delta_1) &= \{\text{fn } x \\ &\rightarrow (x^5 + 4^6)^7 \} \llbracket \hat{\rho}(f, \delta_2) &= \{\text{fn } y \\ &\rightarrow (y^9 \cdot 2^{10})^{11} \} \end{aligned} \llbracket$

In the body of $\llbracket \text{apply} \rrbracket$: $\llbracket \begin{aligned} \hat{C}(1, \delta_1) &= \{\text{fn } x \\ &\rightarrow (x^5 + 4^6)^7 \} \llbracket \hat{C}(1, \delta_2) &= \{\text{fn } y \\ &\rightarrow (y^9 \cdot 2^{10})^{11} \} \end{aligned} \llbracket$

Spurious flows disappear: $\llbracket \text{dbl} \rrbracket \not\in \hat{C}(1, \delta_1) \llbracket$ and $\llbracket \text{inc} \rrbracket \not\in \hat{C}(1, \delta_2) \llbracket$. Consequently:

- $\llbracket \hat{C}(15) \rrbracket$ contains only the result of $\llbracket \text{inc} \rrbracket$
- $\llbracket \hat{C}(18) \rrbracket$ contains only the result of $\llbracket \text{dbl} \rrbracket$

In summary: 0-CFA merges the two calls to apply; 1-CFA separates them by call site, so the first call propagates only $\llbracket \text{inc} \rrbracket$ to $\llbracket f \rrbracket$, while the second propagates only $\llbracket \text{dbl} \rrbracket$.

30.3.2.3 Key Concepts

- 0-CFA acceptability relation $\llbracket \text{models} \rrbracket$ (Algorithm A-04)
- Syntax-directed constraint generation $\llbracket C^*[\![e]\!]\rrbracket$
- $\llbracket k \rrbracket$ -CFA call string approach (Algorithm A-07)
- Soundness vs. precision
- Context sensitivity eliminates spurious flows

30.3.2.4 Typical Exam Insight

Tests the entire CFA pipeline: labeling, acceptability, constraint generation, and context sensitivity. The key point is understanding why 0-CFA merges contexts and how 1-CFA separates them.

30.4 Hard

30.4.1 Exercise E-04: Separation Logic with Incorrectness

Source: ProgramAnalysis_exercises_b.txt (Ex. 1) **Lecture:** Lectures 09–10 (SL, ISL) **Difficulty:** Hard **Tags:** separation logic, incorrectness separation logic, heap, postcondition inference

30.4.1.1 Statement

Consider the following code fragment $\langle c \rangle$:

```
x := [y];
if (x != nil) then {
  free(y);
  y := x;
} else {
  x := alloc();
  [y] := x;
}
```

Using Incorrectness Separation Logic, find a suitable (non-trivial) postcondition $\langle Q \rangle$ for the triple $\langle [y \mapsto z \star z \mapsto \texttt{nil}] \rangle c \langle [\texttt{ok}: Q] \rangle$ and inline the intermediate derivation steps that lead to such conclusion.

30.4.1.2 Generated Solution

Preliminary observation. In the precondition $\langle y \mapsto z \star z \mapsto \texttt{nil} \rangle$, the variable $\langle z \rangle$ is a valid heap location (it points to $\langle \texttt{nil} \rangle$). Therefore $\langle z \neq \texttt{nil} \rangle$, and since $\langle x := [y] \rangle$ binds $\langle x \rangle$ to $\langle z \rangle$, we will have $\langle x \neq \texttt{nil} \rangle$ in all reachable states. The $\langle \texttt{else} \rangle$ branch is **unreachable** from this precondition.

Nevertheless, we analyse both branches as required by the ISL conditional rule.

Step 1: Read. Use the ISL read rule: $\frac{[v \mapsto w \star P] \quad x := [v] \quad [v \mapsto w \star P \wedge x = w]}{[y \mapsto z \star z \mapsto \text{ttt}\{\text{nil}\}] \quad x := [y] \quad [y \mapsto z \star z \mapsto \text{ttt}\{\text{nil}\}] \wedge x = z}$ With $(v=y)$, $(w=z)$, $(P=z \mapsto \text{ttt}\{\text{nil}\})$: $\frac{[y \mapsto z \star z \mapsto \text{ttt}\{\text{nil}\}] \quad x := [y] \quad [y \mapsto z \star z \mapsto \text{ttt}\{\text{nil}\}] \wedge x = z}{[y \mapsto z \star z \mapsto \text{ttt}\{\text{nil}\}] \wedge x = z}$

Step 2: Conditional — then branch $(\neg(x = \text{ttt}\{\text{nil}\}))$.

Precondition: $(y \mapsto z \star z \mapsto \text{ttt}\{\text{nil}\}) \wedge x = z \wedge x \neq \text{ttt}\{\text{nil}\})$.

- **free(y):** using the free rule $\frac{[v \mapsto \perp] \quad \text{ttt}\{\text{free}\}(v) \quad [\text{ttt}\{\text{emp}\}]}{[R = z \mapsto \text{ttt}\{\text{nil}\}] \wedge x = z \wedge x \neq \text{ttt}\{\text{nil}\}} : \frac{[y \mapsto z \star z \mapsto \text{ttt}\{\text{nil}\}] \wedge x = z \wedge x \neq \text{ttt}\{\text{nil}\}] \quad \text{ttt}\{\text{free}\}(y) \quad [z \mapsto \text{ttt}\{\text{nil}\}] \wedge x = z \wedge x \neq \text{ttt}\{\text{nil}\}]{[y \mapsto z \star z \mapsto \text{ttt}\{\text{nil}\}] \wedge x = z \wedge x \neq \text{ttt}\{\text{nil}\}]}$
- **y := x:** using the Floyd-style assignment rule: $\frac{[P] \quad y := x \quad [\exists y'. P[y'/y] \wedge y = x[y'/y]]}{[P = (z \mapsto \text{ttt}\{\text{nil}\}) \wedge x = z \wedge x \neq \text{ttt}\{\text{nil}\}]} : \frac{[z \mapsto \text{ttt}\{\text{nil}\}] \wedge x = z \wedge x \neq \text{ttt}\{\text{nil}\}] \quad y := x \quad [z \mapsto \text{ttt}\{\text{nil}\}] \wedge x = z \wedge y = x \wedge x \neq \text{ttt}\{\text{nil}\}]{[z \mapsto \text{ttt}\{\text{nil}\}] \wedge x = z \wedge y = x \wedge x \neq \text{ttt}\{\text{nil}\}]}$

Simplifying $(x = z)$ and $(y = x)$ gives $(y = z)$, and $(z \mapsto \text{ttt}\{\text{nil}\})$ implies $(z \neq \text{ttt}\{\text{nil}\})$: $\frac{Q_{\{\text{then}\}} = z \mapsto \text{ttt}\{\text{nil}\} \wedge x = z \wedge y = z}{Q_{\{\text{then}\}} = z \mapsto \text{ttt}\{\text{nil}\} \wedge x = z \wedge y = z}$

Step 3: Conditional — else branch $(x = \text{ttt}\{\text{nil}\})$.

Precondition: $(y \mapsto z \star z \mapsto \text{ttt}\{\text{nil}\}) \wedge x = z \wedge x = \text{ttt}\{\text{nil}\})$.

From $(x = z)$ and $(x = \text{ttt}\{\text{nil}\})$ we obtain $(z = \text{ttt}\{\text{nil}\})$, but $(z \mapsto \text{ttt}\{\text{nil}\})$ requires (z) to be a valid heap location. This is a contradiction: **no state satisfies** $(P_{\{\text{else}\}})$. Hence the else branch contributes nothing to the postcondition.

$[Q_{\{\text{else}\}} = \text{ttt}\{\text{false}\}]$

Step 4: Conditional rule.

$\frac{[P_{\{\text{then}\}}] \quad c_{\{\text{then}\}} \quad [Q_{\{\text{then}\}}] \quad [P_{\{\text{else}\}}] \quad c_{\{\text{else}\}} \quad [Q_{\{\text{else}\}}] \quad \{[P] \quad \text{ttt}\{\text{if}\} \quad x \neq \text{ttt}\{\text{nil}\} \quad \text{ttt}\{\text{then}\} \quad \dots \quad \text{ttt}\{\text{else}\} \quad \dots \quad [Q_{\{\text{then}\}}] \quad \text{lor} \quad Q_{\{\text{else}\}}\}}{[P_{\{\text{then}\}}] \quad c_{\{\text{then}\}} \quad [Q_{\{\text{then}\}}] \quad [P_{\{\text{else}\}}] \quad c_{\{\text{else}\}} \quad [Q_{\{\text{else}\}}] \quad \{[P] \quad \text{ttt}\{\text{if}\} \quad x \neq \text{ttt}\{\text{nil}\} \quad \text{ttt}\{\text{then}\} \quad \dots \quad \text{ttt}\{\text{else}\} \quad \dots \quad [Q_{\{\text{then}\}}] \quad \text{lor} \quad Q_{\{\text{else}\}}\}]}$

Since $(Q_{\text{else}} = \text{false})$, we have $(Q_{\text{then}} \vee Q_{\text{else}} = Q_{\text{then}})$.

Final postcondition: $[Q = z \mapsto \text{nil} \wedge x = z \wedge y = z]$

The triple is: $[y \mapsto z \star z \mapsto \text{nil}] \ c \ [\text{ok}: z \mapsto \text{nil} \wedge x = z \wedge y = z]$

30.4.1.3 Key Concepts

- ISL triples: $([P] \ c \ [Q])$ with $(Q \subseteq c)$
- Separating conjunction $(\star)$ for disjoint heap portions
- Points-to predicate $(x \mapsto v)$
- `alloc()` creates a fresh cell
- `free(y)` disposes the cell at (y)

30.4.1.4 Typical Exam Insight

Tests ability to reason about heap-manipulating programs using under-approximate logic.

30.4.2 Exercise E-05: Galois Connection from Function

Source: ProgramAnalysis_exercises_b.txt (Ex. 2) **Lecture:** Lectures 12–14 (Galois Connections) **Difficulty:** Medium **Tags:** galois connection, galois insertion, function lifting, inverse image

30.4.2.1 Statement

Given a function $(f: \mathbb{Z} \rightarrow \mathbb{Z})$, let $(L_f: \wp(\mathbb{Z}) \rightarrow \wp(\mathbb{Z}))$ denote its ordinary powerset lifting defined as $(L_f(X) \triangleq \{f(x) \mid x \in X\})$ and let $(I_f: \wp(\mathbb{Z}) \rightarrow \wp(\mathbb{Z}))$ be defined as $(I_f(Y) \triangleq \{x \mid f(x) \in Y\})$ the inverse image function of (f) .

1. Prove that (L_f) and (I_f) form a Galois connection.
2. Under which condition on (f) do they form a Galois insertion?

30.4.2.2 Generated Solution

1. Galois connection.

Let $((\wp(\mathbb{Z}), \subseteq))$ be both the concrete and abstract domain. We set:

- $(\alpha = L_f)$ (abstraction — direct image)
- $(\gamma = I_f)$ (concretization — inverse image)

To form a Galois connection, we must prove: $[L_f(X) \subseteq Y \text{ iff } X \subseteq I_f(Y)]$

Forward direction ($\Rightarrow$): Assume $(L_f(X) \subseteq Y)$, i.e., $(\{f(x) \mid x \in X\} \subseteq Y)$. Take any $(x \in X)$. Then $(f(x) \in L_f(X) \subseteq Y)$, so $(f(x) \in Y)$. By definition of (I_f) , we have $(x \in I_f(Y))$. Since (x) was arbitrary, $(X \subseteq I_f(Y))$.

Backward direction ($\Leftarrow$): Assume $(X \subseteq I_f(Y))$, i.e., for all $(x \in X)$, $(f(x) \in Y)$. Take any $(y \in L_f(X))$. Then $(y = f(x))$ for some $(x \in X)$. Since $(x \in X \subseteq I_f(Y))$, we have $(f(x) \in Y)$, so $(y \in Y)$. Hence $(L_f(X) \subseteq Y)$.

Since the equivalence holds for all (X, Y) , $((L_f, I_f))$ form a Galois connection from $((\wp(\mathbb{Z}), \subseteq))$ to $((\wp(\mathbb{Z}), \subseteq))$.

2. Galois insertion condition.

A Galois connection is a **Galois insertion** if (α) is surjective (equivalently (γ) is injective, or $(\alpha \circ \gamma = \text{id})$).

(L_f) is surjective iff every $(Y \in \wp(\mathbb{Z}))$ can be expressed as $(L_f(X))$ for some $(X \in \wp(\mathbb{Z}))$. This holds iff (f) is **surjective**:

- If (f) is surjective, then for any $(Y \subseteq \mathbb{Z})$, pick $(X = f^{-1}(Y))$. Since for each $(y \in Y)$ there exists (x) with $(f(x)=y)$, we have $(L_f(f^{-1}(Y)) \supseteq Y)$. In fact $(L_f(I_f(Y)) = Y)$ for surjective (f) .
- If (f) is not surjective, let $(y \notin \text{image}(f))$. Then $(\{y\})$ cannot be expressed as $(L_f(X))$ for any (X) , because $(L_f(X) \subseteq \text{image}(f))$ always.

Alternatively, checking $(\alpha \circ \gamma = \text{id})$: $[L_f(I_f(Y)) = \{f(x) \mid f(x) \in Y\} = Y \cap \text{image}(f)]$ This equals (Y) for all $(Y \in \wp(\mathbb{Z}))$ iff $(\text{image}(f) = \mathbb{Z})$, i.e., (f) is surjective.

Answer: $((L_f, I_f))$ form a Galois insertion iff $(f: \mathbb{Z} \rightarrow \mathbb{Z})$ is **surjective**.

30.4.2.3 Key Concepts

- Galois connection: $(L_f(X) \subseteq Y \iff X \subseteq I_f(Y))$
- Galois insertion: $(L_f \circ I_f = \text{id})$, i.e., (f) is surjective
- Formula F-06

30.4.2.4 Typical Exam Insight

Tests understanding of GC beyond the standard $(\alpha)/(\gamma)$ pattern — uses direct and inverse image.

30.4.3 Exercise E-06: CFA + Data Flow Analysis (DFA) Integration

Source: ProgramAnalysis_exercises_b.txt (Ex. 3) **Lecture:** Lectures 17–24 (CFA) + 14–15 (Abstract Domains) **Difficulty:** Hard **Tags:** CFA, DFA, sign analysis, abstract interpretation, product domain

30.4.3.1 Statement

Consider the following expression (e) :

```
let n = 5
in let choose =
  if n > 0
  then (fn x => x + 1)
  else (fn y => y * 2)
in choose 4
```

Assume a sign analysis with $(\text{Data_sign}) = (\text{tt}, \text{ff}, -, 0, +)$.

1. Add labels to all subexpressions and function abstractions.
2. Guess a possible Pure 0-CFA analysis result and verify it using the acceptability relation (models) . In particular, determine the possible closures flowing to `choose` at the application `(choose 4)`.
3. Explain why Pure 0-CFA cannot determine that one branch of the conditional is unreachable.

4. Perform the DFA using abstract values as powersets: $\widehat{\text{Val}}_d = \wp(\text{Data}_{\text{sign}})$. Compute the abstract values associated with 5, $\langle n \rangle$, $\langle n > 0 \rangle$, and the two branches.
5. Explain how the DFA refines the CFA result. Which branch becomes unreachable?
6. Repeat the DFA using the complete lattice formulation of the same sign information and compare.
7. Explain why the refined CFA+DFA result is still sound.

30.4.3.2 Generated Solution

1. Labelling.

```
[ \begin{aligned} e &\triangleq \& (\texttt{let } n = 5^1 \& \texttt{in } \\ &(\texttt{let } \texttt{choose} = \& \& \texttt{if } (n^2 > 0^3)^4 \& \\ &\& \texttt{then } (\texttt{fn } x \& \texttt{Rightarrow } (x^5 + 4^6)^7)^8 \& \\ &\& \texttt{else } (\texttt{fn } y \& \texttt{Rightarrow } (y^9 * \\ &2^{\{10\}})^{\{11\}})^{\{12\}})^{\{13\}} \& \& \texttt{in } (\texttt{choose}^{\{14\}} \\ &4^{\{15\}})^{\{16\}})^{\{17\}})^{\{18\}} \end{aligned} ]
```

2. Pure 0-CFA result.

Environment $\langle \hat{\rho} \rangle$:

- $\langle \hat{\rho} \rangle(n) = \{ 5 \}$ (constant 5)
- $\langle \hat{\rho} \rangle(\texttt{choose}) = \hat{C}(13) = \{ \texttt{fn } x \& \texttt{Rightarrow } x+4, \texttt{fn } y \& \texttt{Rightarrow } y*2 \}$

Cache $\langle \hat{C} \rangle$ (selected labels):

- $\langle \hat{C} \rangle(8) = \{ \texttt{fn } x \& \texttt{Rightarrow } (x^5+4^6)^7 \}$
- $\langle \hat{C} \rangle(12) = \{ \texttt{fn } y \& \texttt{Rightarrow } (y^9*2^{\{10\}})^{\{11\}} \}$
- $\langle \hat{C} \rangle(13) = \{ \texttt{fn } x \& \texttt{Rightarrow } (x^5+4^6)^7, \texttt{fn } y \& \texttt{Rightarrow } (y^9*2^{\{10\}})^{\{11\}} \}$
- $\langle \hat{C} \rangle(14) = \hat{C}(13)$ (identifier choose flows)
- $\langle \hat{C} \rangle(16) = \{ \texttt{fn } x \& \texttt{Rightarrow } (x^5+4^6)^7, \texttt{fn } y \& \texttt{Rightarrow } (y^9*2^{\{10\}})^{\{11\}} \}$ (application of choose to 4)

Both closures flow to choose at the application site.

3. Why CFA cannot determine branch unreachability.

0-CFA only tracks function closure flow; it has no data abstraction. The condition $(n > 0)$ is treated as a syntactic control-flow split, but the CFA acceptability relation requires analysing **both** branches regardless of data values. CFA has no mechanism to evaluate $(5 > 0)$ as true — it simply merges both branches into $\hat{C}(13)$.

4. DFA with powerset abstract values $\hat{\text{Data}}_{\text{sign}} = \wp(\text{Data}_{\text{sign}})$.

Define $\text{Data}_{\text{sign}} = \{\text{tt}, \text{ff}, -, 0, +\}$ with the usual sign semantics.

- $\hat{\text{Val}}_d(1) = \{+\}$ (constant 5 is positive)
- $\hat{\text{Val}}_d(2) = \{+\}$ (n copies the value of 5)
- $\hat{\text{Val}}_d(4) = \{+\}$ (value of $(n > 0)$: positive > 0 is true)
 - This requires an abstract evaluation: $(+ > 0)$ yields $\{\text{tt}\}$ because every positive integer is > 0 .
- $\hat{\text{Val}}_d(5) = \{+\}$ (constant 4 is positive)
- $\hat{\text{Val}}_d(15) = \{+\}$

Branch condition: $\hat{\text{Val}}_d(4) = \{\text{tt}\}$. The else branch $(n \leq 0)$ has empty abstract value: $\hat{\text{Val}}_d(\text{condition for else}) = \{\text{ff}\} \cap \text{flow from } n > 0 = \emptyset$. Therefore the **else branch is unreachable** under the DFA.

5. DFA refines CFA.

The DFA determines that $(n > 0)$ always evaluates to $\{\text{tt}\}$ (since $(n=5)$ is positive). Consequently, only the **then** branch $(\text{fn } x \rightarrow x+4)$ is reachable. The CFA result is refined: at label 14, only one closure flows:

$$\hat{C}(14) = \{\text{fn } x \rightarrow (x^5 + 4^6)^7\}$$

The spurious closure $(\text{fn } y \rightarrow y^2)$ is eliminated.

6. Complete lattice formulation.

Define the sign lattice as:

$$\begin{array}{c} \top \\ / \quad | \quad \backslash \\ + \quad 0 \quad - \end{array}$$

$$\begin{array}{c} \backslash \ / \ / \\ \top \quad \perp? \end{array}$$

Actually, the standard sign lattice:

$$\begin{array}{ccc} & \top & \\ / & | & \backslash \\ + & 0 & - \\ \backslash & | & / \\ & \perp & \end{array}$$

With the correspondence: $\wp(\{\texttt{tt}, \texttt{ff}, -, 0, +\})$ can be mapped to a lattice where each element is a subset. The complete lattice formulation is equivalent to the powerset, but represents the same information more compactly through the ordering:

- $\{\{+\}\}$ corresponds to abstract value “positive”
- $\{\{+, 0\}\}$ corresponds to “non-negative”
- $\{\{-, 0\}\}$ corresponds to “non-positive”

The DFA result is identical: $\{n\}$ is $\{\{+\}\}$, $\{n > 0\}$ is $\{\{\texttt{tt}\}\}$, the else branch is unreachable.

7. Soundness of refined CFA+DFA.

The refined analysis is still **sound** because:

- CFA soundly over-approximates closure flow: every function that may be called at runtime is included.
- DFA soundly over-approximates data values: every runtime value is included in the abstract value.
- The product CFA×DFA removes closures that are inconsistent with the data flow (e.g., closures in a branch whose guard is false).
- Since no runtime execution can take the else branch (the data DFA proves $\{n > 0\}$ always holds), no runtime execution can invoke $\texttt{fn } y \rightarrow y^2$ at the call site. Removing it preserves soundness while improving precision.

Formally: if $(\hat{C}, \hat{\rho}) \models e$ is sound and $\widehat{\text{Val}_d}$ is a sound data abstraction, then $(\hat{C}', \hat{\rho}')$ where $\hat{C}'(\ell) = \hat{C}(\ell) \cap \{t \mid \widehat{\text{Val}_d}(\ell)(t) \text{ is reachable}\}$ is also sound, because data-unreachable branches carry no runtime executions.

30.4.3.3 Key Concepts

- CFA for higher-order functions
- DFA with sign abstract domain
- Product of CFA and DFA for precision
- Soundness preservation under product

30.4.3.4 Typical Exam Insight

Tests integration of CFA (flow information) with DFA (data information) — the two-stage approach from Lecture 21.

31 Enhanced Formula Handbook

31.1 F-01: Collecting Semantics

31.1.1 Formula

$$\llbracket c \rrbracket P = \bigcup_{\sigma \in P} \llbracket c \rrbracket \sigma$$

31.1.2 Meaning

The collecting semantics maps a set of input states to the union of all reachable output states.

31.1.3 Variables

- $\llbracket c \rrbracket$: command
- P : set of input states
- $\llbracket c \rrbracket \sigma$: output state (or $\bot$ for non-termination) when executing c from σ

31.1.4 Intuition

Lifts pointwise semantics to sets. The most concrete semantics used as starting point for abstraction.

31.1.5 Usage

Foundation of all static analyses. Concrete semantics that gets abstracted.

31.1.6 Related Lecture

Lecture 02 — Denotational Semantics

31.1.7 Related Exercises

E-01, E-02

31.2 F-02: Weakest Liberal Precondition

31.2.1 Formula

$$\llbracket \text{wlp} \rrbracket(c, Q) = \{ \sigma \mid \llbracket c \rrbracket \sigma \subseteq Q \}$$

31.2.2 Meaning

The set of input states from which every execution (if it terminates) ends in Q .

31.2.3 Variables

- c : command
- Q : set of output states
- σ : a single state

31.2.4 Intuition

The largest precondition under which all executions are safe. The dual of strongest postcondition.

31.2.5 Usage

Foundation of Hoare Logic: $\llbracket P \rrbracket c \subseteq Q$ iff $P \subseteq \llbracket \text{wlp} \rrbracket(c, Q)$.

31.2.6 Related Lecture

Lecture 02 — Denotational Semantics

31.2.7 Related Exercises

E-01

31.3 F-03: Weakest Possible Precondition

31.3.1 Formula

$$\llbracket \text{wpp} \rrbracket(c, Q) = \{ \sigma \mid \sigma \cap Q \neq \emptyset \}$$

31.3.2 Meaning

The set of input states that have at least one execution ending in Q .

31.3.3 Variables

- c : command
- Q : set of output states

31.3.4 Intuition

The largest precondition for which some execution reaches Q . The under-approximate dual of wlp.

31.3.5 Usage

Foundation of Incorrectness Logic: $\llbracket P \rrbracket c \llbracket Q \rrbracket \text{ iff } P \supseteq \llbracket \text{wpp} \rrbracket(c, Q)$.

31.3.6 Related Lecture

Lecture 02 — Denotational Semantics

31.3.7 Related Exercises

E-01

31.4 F-04: Hoare Triple Validity

31.4.1 Formula

$\llbracket P \rrbracket c \llbracket Q \rrbracket \text{ iff } \llbracket P \rrbracket c \rrbracket \subseteq Q$

31.4.2 Meaning

Every terminating execution from a state in $\llbracket P \rrbracket$ ends in a state in $\llbracket Q \rrbracket$.

31.4.3 Variables

- $\llbracket P \rrbracket$: precondition (set of input states)
- $\llbracket c \rrbracket$: command
- $\llbracket Q \rrbracket$: postcondition (set of output states)

31.4.4 Intuition

Over-approximation of reachable states. Partial correctness — non-termination is allowed.

31.4.5 Usage

The standard correctness logic. Proves absence of bugs.

31.4.6 Related Lecture

Lecture 03 — Hoare Logic

31.4.7 Related Exercises

E-01

31.5 F-05: Incorrectness Triple Validity

31.5.1 Formula

$\llbracket [P] \ c \ [Q] \ \text{iff} \ \llbracket c \rrbracket P \supseteq Q \llbracket$

31.5.2 Meaning

Every state in $\llbracket Q \rrbracket$ is reachable from some state in $\llbracket P \rrbracket$.

31.5.3 Variables

- $\llbracket P \rrbracket$: precondition
- $\llbracket c \rrbracket$: command
- $\llbracket Q \rrbracket$: postcondition

31.5.4 Intuition

Under-approximation of reachable states. Proves presence of bugs.

31.5.5 Usage

Bug finding. Dual of Hoare Logic.

31.5.6 Related Lecture

Lecture 05 — Incorrectness Logic

31.5.7 Related Exercises

E-01

31.6 F-06: Galois Connection

31.6.1 Formula

$\llbracket \alpha(c) \sqsubseteq_A a \ \text{iff} \ c \sqsubseteq_C \gamma(a) \llbracket$

31.6.2 Meaning

Abstraction and concretization are adjoint monotone maps between concrete and abstract domains.

31.6.3 Variables

- $\alpha: C \rightarrow A$: abstraction map
- $\gamma: A \rightarrow C$: concretization map
- $c \in C$: concrete element
- $a \in A$: abstract element
- $(\sqsubseteq_C), (\sqsubseteq_A)$: partial orders on C and A

31.6.4 Intuition

The best abstraction of c is at least as precise as any abstract element a that soundly approximates c .

31.6.5 Usage

Foundation of all abstract interpretation frameworks.

31.6.6 Related Lecture

Lecture 12 — AI Formal Foundations, Lecture 13 — Galois Connections

31.6.7 Related Exercises

E-02, E-05

31.7 F-07: Soundness of Abstract Semantics

31.7.1 Formula

$$[\alpha \circ \llbracket c \rrbracket \sqsubseteq \llbracket a \rrbracket \mid c \rrbracket^\# \circ \alpha]$$

31.7.2 Alternative form

$$\llbracket c \rrbracket^{\gamma} \sqsubseteq \llbracket c \rrbracket^{\alpha}$$

31.7.3 Meaning

Abstract execution of a command soundly over-approximates the concrete execution, when both are applied to an abstracted input.

31.7.4 Variables

- $\llbracket c \rrbracket$: concrete semantics
- $\llbracket c \rrbracket^{\gamma}$: abstract semantics
- α : abstraction
- γ : concretization

31.7.5 Intuition

Abstracting-then-executing is at least as precise as executing-then-abstracting.

31.7.6 Usage

Prove correctness of abstract interpreters.

31.7.7 Related Lecture

Lecture 12 — AI Formal Foundations

31.7.8 Related Exercises

E-02

31.8 F-08: Best Abstract Correct Approximation (BCA)

31.8.1 Formula

$$\llbracket c \rrbracket^{\#_A} = \alpha \circ \llbracket c \rrbracket \circ \gamma$$

31.8.2 Meaning

The most precise sound abstract semantics for a command, obtained by: concretize, execute concretely, then abstract back.

31.8.3 Variables

- $\llbracket c \rrbracket^{\#_A}$: best abstraction of command $\llbracket c \rrbracket$
- α, γ : Galois connection maps

31.8.4 Intuition

Any sound abstract semantics must be at least as imprecise as the BCA. The BCA defines the optimal precision achievable with a given abstraction.

31.8.5 Usage

Benchmark for precision. If a given $\llbracket F \rrbracket^{\#}$ equals BCA, it is complete.

31.8.6 Related Lecture

Lecture 14 — Abstract Domains

31.8.7 Related Exercises

E-02

31.9 F-09: Completeness Equation

31.9.1 Formula

$$\llbracket \alpha \circ \llbracket c \rrbracket \rrbracket = \alpha \circ \llbracket c \rrbracket$$
$$\llbracket \gamma \circ \alpha \rrbracket$$

31.9.2 Equivalent form

$$\llbracket \forall P. A(\llbracket c \rrbracket P) = A(\llbracket c \rrbracket (A(P))) \rrbracket$$

31.9.3 Meaning

Abstraction after concrete execution equals abstraction after executing on abstracted input. No precision loss from abstraction before execution.

31.9.4 Variables

- $(A = \gamma \circ \alpha)$: closure operator
- $(\llbracket c \rrbracket)$: concrete semantics

31.9.5 Intuition

If completeness holds for a command, the abstract semantics can be computed without loss of precision.

31.9.6 Usage

Characterizes when an abstract domain is “precise enough” for a given command.

31.9.7 Related Lecture

Lecture 16 — Local Completeness Logic

31.9.8 Related Exercises

E-02

31.10 F-10: Galois Insertion Property

31.10.1 Formula

$$[\alpha \circ \gamma = \text{id}_A]$$

31.10.2 Meaning

No redundant abstract elements. Every abstract element is the image of some concrete element.

31.10.3 Equivalent forms

- α is surjective
- γ is injective

31.10.4 Usage

Simplifies the abstract domain by removing elements that cannot arise from abstraction.

31.10.5 Related Lecture

Lecture 13 — Galois Connections

31.10.6 Related Exercises

E-05

31.11 F-11: LCL Triple Validity

31.11.1 Formula

$$[\vdash_A [P] \ c \ [Q] \text{ iff } Q \subseteq \llbracket c \rrbracket P \subseteq A(Q)]$$

31.11.2 Meaning

The postcondition $\llbracket Q \rrbracket$ under-approximates reachable states, while $\llbracket A(Q) \rrbracket$ over-approximates them. Both under- and over-approximation combined.

31.11.3 Variables

- $\llbracket A \rrbracket$: abstraction (closure operator)
- $\llbracket P, Q \rrbracket$: sets of states
- $\llbracket \llbracket c \rrbracket P \rrbracket$: reachable states

31.11.4 Intuition

LCL combines the guarantees of HL (over-approximation) and IL (under-approximation) in a single triple.

31.11.5 Usage

Reasoning about programs with abstract interpretation in mind.

31.11.6 Related Lecture

Lecture 16 — LCL

31.12 F-12: Local Completeness Condition

31.12.1 Formula

$$\llbracket \llbracket \mathbb{C} \rrbracket_P(e) \rrbracket \quad \llbracket A(\llbracket e \rrbracket P) \rrbracket = A(\llbracket \llbracket e \rrbracket A(P) \rrbracket)$$

31.12.2 Meaning

The atomic expression $\llbracket e \rrbracket$ is locally complete for input $\llbracket P \rrbracket$ — abstraction after execution equals abstraction after abstracting the input first.

31.12.3 Variables

- $\llbracket e \rrbracket$: expression (command or guard)

- $\backslash(P)$: input set
- $\backslash(A)$: closure operator

31.12.4 Intuition

Local completeness only requires the equation for a specific $\backslash(P)$, not for all inputs. This is a weaker (and more achievable) condition than global completeness.

31.12.5 Usage

Prerequisite for the atomic rules in LCL proof system.

31.12.6 Related Lecture

Lecture 16 — LCL

31.13 F-13: LCL Iteration Rule

31.13.1 Formula

$$\backslash[\frac{\backslashvdash_A[P] \ c \ [Q] \quad Q \implies A(P)}{\backslashvdash_A[P] \ c^{\star} \ [P \ \text{lor} \ Q]} \backslash]$$

31.13.2 Meaning

If the loop body maps $\backslash(P)$ to $\backslash(Q)$, and $\backslash(Q)$ is abstractly equivalent to $\backslash(P)$, then the loop maps $\backslash(P)$ to $\backslash(P \ \text{lor} \ Q)$.

31.13.3 Variables

- $\backslash(c)$: loop body
- $\backslash(c^{\star})$: iteration (Kleene star)
- $\backslash(P, Q)$: sets of states
- $\backslash(A)$: abstraction

31.13.4 Intuition

The condition $\backslash(Q \implies A(P))$ ensures that $\backslash(P)$ is an “abstract invariant” of the loop.

31.13.5 Related Lecture

Lecture 16 — LCL

31.14 F-14: Fixpoint Approximation Theorem

31.14.1 Formula

$$\lfloor \text{lfp}(F) \sqsubseteq \gamma(\text{lfp}(F^\#)) \rfloor$$

31.14.2 Meaning

The concretization of the least fixpoint of the abstract semantic function over-approximates the least fixpoint of the concrete semantic function.

31.14.3 Variables

- F : concrete semantic function
- $F^\#$: abstract semantic function (sound)
- γ : concretization
- lfp : least fixpoint

31.14.4 Intuition

Abstract interpretation of loops is sound: the abstract loop invariant over-approximates the concrete reachable states.

31.14.5 Usage

Core correctness result for loop analysis.

31.14.6 Related Lecture

Lecture 15 — Abstract Analysis

31.15 F-15: Abstract Semantics of Iteration

31.15.1 Formula

$$\llbracket c^* \rrbracket \triangleq \lambda S. \operatorname{lfp} \lambda X. S \sqcup \llbracket c \rrbracket X$$

31.15.2 Accelerated version (with widening)

$$\llbracket c^* \rrbracket \triangleq \lambda S. \operatorname{lfp} \lambda X. S \nabla \llbracket c \rrbracket X$$

31.15.3 Meaning

The abstract semantics of a loop is the least fixpoint of the function $\lambda X. \llbracket c \rrbracket X \sqcup S$, accelerated with widening for non-ACC domains.

31.15.4 Variables

- $\llbracket c^* \rrbracket$: loop (iteration)
- $\llbracket S \rrbracket$: initial abstract state
- $\llbracket \cdot \rrbracket$: abstract join
- ∇ : widening operator

31.15.5 Intuition

Loop analysis requires fixpoint computation; widening ensures termination.

31.15.6 Related Lecture

Lecture 15 — Abstract Analysis

31.16 F-16: Correctness Condition for $(F^{\#})$

31.16.1 Formula

$$F^{\#} \sqsupseteq \alpha \circ F \circ \gamma = F^A$$

31.16.2 Meaning

A sound abstract transfer function must be at least as imprecise as the best correct abstraction. Equivalently, it must over-approximate the BCA.

31.16.3 Variables

- $\backslash(F)$: concrete operator
- $\backslash(F^\#\backslash)$: abstract operator
- $\backslash(F^\#A)$: best correct abstraction

31.16.4 Intuition

The BCA $\backslash(F^\#A)$ defines the precision lower bound. Any $\backslash(F^\#\backslash)$ that is coarser than $\backslash(F^\#A)$ is still sound but less precise.

31.16.5 Related Lecture

Lecture 15 — Abstract Analysis

31.17 F-17: Abstract Domain Operations Tables

31.17.1 Sign Domain Multiplication

$\backslash(\text{times}^\#\backslash)$	$\backslash(\text{mathbb{Z}}_{<0})$	$\backslash(\text{mathbb{Z}}_{=0})$	$\backslash(\text{mathbb{Z}}_{>0})$
$\backslash(\text{mathbb{Z}}_{<0})$	$\backslash(\text{mathbb{Z}}_{>0})$	$\backslash(\text{mathbb{Z}}_{=0})$	$\backslash(\text{mathbb{Z}}_{<0})$
$\backslash(\text{mathbb{Z}}_{=0})$	$\backslash(\text{mathbb{Z}}_{=0})$	$\backslash(\text{mathbb{Z}}_{=0})$	$\backslash(\text{mathbb{Z}}_{=0})$
$\backslash(\text{mathbb{Z}}_{>0})$	$\backslash(\text{mathbb{Z}}_{<0})$	$\backslash(\text{mathbb{Z}}_{=0})$	$\backslash(\text{mathbb{Z}}_{>0})$

31.17.2 Sign Domain Addition

$\backslash (+^\#)$	$\backslash (\mathbb{Z}_{<0})$	$\backslash (\mathbb{Z}_{=0})$	$\backslash (\mathbb{Z}_{>0})$	$\backslash (\mathbb{Z})$
$\backslash (\mathbb{Z}_{<0})$	$\backslash (\mathbb{Z}_{<0})$	$\backslash (\mathbb{Z}_{<0})$	$\backslash (\mathbb{Z})$	$\backslash (\mathbb{Z})$
$\backslash (\mathbb{Z}_{=0})$	$\backslash (\mathbb{Z}_{<0})$	$\backslash (\mathbb{Z}_{=0})$	$\backslash (\mathbb{Z}_{>0})$	$\backslash (\mathbb{Z})$
$\backslash (\mathbb{Z}_{>0})$	$\backslash (\mathbb{Z})$	$\backslash (\mathbb{Z}_{>0})$	$\backslash (\mathbb{Z}_{>0})$	$\backslash (\mathbb{Z})$
$\backslash (\mathbb{Z})$	$\backslash (\mathbb{Z})$	$\backslash (\mathbb{Z})$	$\backslash (\mathbb{Z})$	$\backslash (\mathbb{Z})$

31.17.3 Related Lecture

Lecture 12 — AI Formal Foundations

31.17.4 Related Exercises

E-02

31.18 F-18: Interval Domain Operations

31.18.1 Addition

$$\backslash [a,b] +^\# [c,d] = [a+c, b+d] \backslash$$

31.18.2 Subtraction

$$\backslash [a,b] -^\# [c,d] = [a-d, b-c] \backslash$$

31.18.3 Negation

$$\backslash -^\# [a,b] = [-b, -a] \backslash$$

31.18.4 Join

$$[a, b] \sqcup [c, d] = [\min(a, c), \max(b, d)]$$

31.18.5 Meet

$$[a, b] \sqcap [c, d] = \begin{cases} [\max(a, c), \min(b, d)] & \text{if } \max(a, c) \leq \min(b, d) \\ \bot & \text{otherwise} \end{cases}$$

31.18.6 Related Lecture

Lecture 14 — Abstract Domains

31.19 F-19: Congruence Domain Operations

31.19.1 Concretization

$$\gamma(a\mathbb{Z} + b) = \{ak + b \mid k \in \mathbb{Z}\}$$

31.19.2 Negation

$$-\#(a\mathbb{Z} + b) = a\mathbb{Z} + (-b)$$

31.19.3 Addition

$$(a\mathbb{Z} + b) + \#(c\mathbb{Z} + d) = \gcd(a, c)\mathbb{Z} + (b+d)$$

31.19.4 Subtraction

$$(a\mathbb{Z} + b) - \#(c\mathbb{Z} + d) = \gcd(a, c)\mathbb{Z} + (b-d)$$

31.19.5 Multiplication

$$(a\mathbb{Z} + b) \times \#(c\mathbb{Z} + d) = \gcd(ac, ad, bc)\mathbb{Z} + bd$$

31.19.6 Meet

$$\lfloor (a \mathbb{Z} + b) \sqcap (a' \mathbb{Z} + b') = \begin{cases} \bot & \text{if } b \not\equiv b' \pmod{\gcd(a,a')} \\ \operatorname{lcm}(a,a') \mathbb{Z} + b'' & \text{otherwise} \end{cases} \rfloor$$

31.19.7 Join

$$\lfloor (a \mathbb{Z} + b) \sqcup (a' \mathbb{Z} + b') = d \mathbb{Z} + r \quad \text{where } d = \gcd(a,a', |b-b'|), r \equiv b \pmod{d} \rfloor$$

31.19.8 Related Lecture

Lecture 14 — Abstract Domains

31.20 F-20: Interval Widening

31.20.1 Formula

$$\lfloor [a,b] \nabla [c,d] = \begin{cases} [-\infty, b] & \text{if } c < a \\ [a, +\infty] & \text{if } d > b \\ [a, b] & \text{otherwise} \end{cases} \rfloor$$

31.20.2 Meaning

Forces unstable bounds to $(\pm\infty)$, guaranteeing convergence after finitely many iterations.

31.20.3 Related Lecture

Lecture 14 — Abstract Domains, Lecture 15 — Abstract Analysis

32 Lecture Summaries

32.1 Lecture 01 — Introduction

32.1.1 Key Definitions

- **Correctness:** absence of bugs (over-approximation)
- **Incorrectness:** presence of bugs (under-approximation)
- **Soundness:** if analysis says YES, the property holds
- **Completeness:** if property holds, analysis says YES
- **Rice's Theorem:** no automatic, universal, exact analysis

32.1.2 Key Formulas

- F-01: Collecting semantics
- F-04: HL triple validity
- F-05: IL triple validity

32.1.3 Key Algorithms

None in this lecture.

32.1.4 Common Mistakes

- Confusing soundness and completeness
- Thinking testing can prove correctness
- Expecting exact automatic analysis

32.1.5 Exam Checklist

☐

Can explain Rice's Theorem and its consequences

☐

Can distinguish over- vs under-approximation

☐

Understands the approximation spectrum table

32.2 Lecture 02 — Denotational Semantics

32.2.1 Key Definitions

- **Memory states:** $\Sigma = \{\sigma: X \rightarrow \mathbb{Z}\}$
- **Collecting semantics:** $\llbracket c \rrbracket: \wp(\Sigma) \rightarrow \wp(\Sigma)$
- **wlp:** $\text{wlp}(c, Q) = \{\sigma \mid \llbracket c \rrbracket \sigma \subseteq Q\}$
- **wpp:** $\text{wpp}(c, Q) = \{\sigma \mid \llbracket c \rrbracket \sigma \cap Q \neq \emptyset\}$

32.2.2 Key Formulas

- F-01, F-02, F-03

32.2.3 Key Algorithms

None (foundational definitions).

32.2.4 Common Mistakes

- Forgetting $\llbracket c^* \rrbracket P = \bigcup_{k \geq 0} \llbracket c \rrbracket^k P$
- Not distinguishing wlp and wpp

32.2.5 Exam Checklist

☐

Can compute collecting semantics for simple programs

☐

Understands wlp vs wpp

☐

Can encode conditionals and loops using guarded commands

32.3 Lecture 03 — Hoare Logic

32.3.1 Key Definitions

- **HL triple:** $\{P\} c \{Q\} \text{ iff } \llbracket c \rrbracket P \subseteq Q$

- **Loop invariant:** property that holds before and after each loop iteration

32.3.2 Key Formulas

- F-04
- Inference rules (assignment, composition, conditional, while, consequence)

32.3.3 Key Algorithms

None (proof system).

32.3.4 Common Mistakes

- Misapplying Hoare's assignment axiom (backward substitution)
- Choosing a loop invariant that is too weak/too strong
- Forgetting the consequence rule

32.3.5 Exam Checklist

☐

Can prove simple programs with HL

☐

Can find loop invariants

☐

Knows Hoare vs Floyd assignment axioms

32.4 Lecture 04 — Total Correctness

32.4.1 Key Definitions

- **Partial correctness:** $\{P\} c \{Q\}$ (non-termination allowed)
- **Total correctness:** $[P] c [Q]$ (must terminate)
- **Variant:** $\{t\}$ — expression that decreases each iteration, bounded below

32.4.2 Key Formulas

- Total correctness while rule with variant $\{t\}$

32.4.3 Common Mistakes

- Confusing total correctness notation with IL notation
- Forgetting to prove the variant decreases and is bounded below

32.4.4 Exam Checklist

☐

Can prove termination using a variant

☐

Understands relation between partial and total correctness

32.5 Lecture 05 — Incorrectness Logic

32.5.1 Key Definitions

- **IL triple:** $\langle [P] \rangle c \langle [Q] \rangle$ iff $\llbracket c \rrbracket P \supseteq Q$
- **Principle of Agreement:** IL + HL implies precision
- **Principle of Denial:** IL contradicts HL — bug found

32.5.2 Key Formulas

- F-05
- IL inference rules (skip, assignment, assume, error, nondet, sequence, choice, consequence — reverse!)

32.5.3 Common Mistakes

- Using Hoare's assignment axiom in IL (unsound!)
- Reverse direction of consequence rule

32.5.4 Exam Checklist

☐

Can prove bug-finding triples with IL

☐

Understands the duality between HL and IL

☐

Knows which HL rules are unsound in IL

32.5.5 Semantics and Grammar

Regular commands with atomic commands:

$$\begin{aligned} e & ::= \text{skip} \mid x := a \mid b? \mid c ::= e \mid \\ c_1; c_2 & \mid c_1 + c_2 \mid c^{\star} \end{aligned}$$

Syntactic sugar:

$$\begin{aligned} & b \text{ then } c_1 \text{ else } c_2 \triangleq \\ & (b?; c_1) + (\neg b?; c_2) \quad b \text{ while } c \triangleq \\ & (b?; c)^{\star}; \neg b? \end{aligned}$$

Collecting semantics $(\llbracket c \rrbracket : \wp(\Sigma) \rightarrow \wp(\Sigma))$:

$$\begin{aligned} & \llbracket \text{skip} \rrbracket P \triangleq P \quad \llbracket x := a \rrbracket P \triangleq \{ \sigma[v/x] \mid \sigma \in P, v = \llbracket a \rrbracket \sigma \} \\ & \llbracket b? \rrbracket P \triangleq \{ \sigma \in P \mid \sigma \models b \} \quad \llbracket \text{error}() \rrbracket P \triangleq \emptyset \\ & \llbracket x := \text{nondet}() \rrbracket P \triangleq \{ \sigma[v/x] \mid \sigma \in P, v \in \mathbb{Z} \} \\ & \llbracket c_1; c_2 \rrbracket P \triangleq \llbracket c_1 \rrbracket (\llbracket c_2 \rrbracket P) \quad \llbracket c_1 + c_2 \rrbracket P \triangleq \llbracket c_1 \rrbracket P \cup \llbracket c_2 \rrbracket P \\ & \llbracket c^{\star} \rrbracket P \triangleq \bigcup_{k \geq 0} \llbracket c^k \rrbracket P \quad \text{where } c^k \triangleq c; \dots; c \text{ (} k \text{ times)} \end{aligned}$$

Relational semantics $(\llbracket c \rrbracket \subseteq \Sigma \times \Sigma)$:

$$\begin{aligned} & \llbracket \text{skip} \rrbracket \triangleq \{ (\sigma, \sigma) \} \quad \llbracket b? \rrbracket \triangleq \{ (\sigma, \sigma) \mid \sigma \models b \} \\ & \llbracket x := a \rrbracket \triangleq \{ (\sigma, \sigma[v/x]) \mid \sigma \in \Sigma \} \quad \llbracket \text{error}() \rrbracket \triangleq \emptyset \\ & \llbracket x := \text{nondet}() \rrbracket \triangleq \{ (\sigma, \sigma[v/x]) \mid \sigma \in \Sigma, v \in \mathbb{Z} \} \end{aligned}$$

32.5.6 IL Inference Rules

Skip:
$$\frac{}{\llbracket \text{skip} \rrbracket \subseteq \llbracket P \rrbracket \subseteq \llbracket P \rrbracket}$$

Floyd's assignment axiom (same as HL): $\vdash \text{Floyd} \quad \frac{}{[P] \ x:=a \ [\exists x'. \ P[x'/x] \ \wedge \ x = a[x'/x]]} \ \vdash$

Hoare's assignment axiom (unsound for IL): $\vdash \text{Hoare} \quad \frac{}{[Q[a/x]] \ x:=a \ [Q]} \ \vdash$ Counterexample: $\vdash ([y = 42] \ x:=42 \ [y = x])$ is unsound because $\vdash (\delta = [x \mapsto 3, y \mapsto 3])$ satisfies $\vdash (y = x)$ but is unreachable.

Assume/Guard: $\vdash \text{assume} \quad \frac{}{[P] \ b? \ [P \ \wedge \ b]} \ \vdash$

Error: $\vdash \text{error} \quad \frac{}{[P] \ \text{error}() \ [\text{false}]} \ \vdash$

Nondet: $\vdash \text{nondet} \quad \frac{}{[P] \ x:=\text{nondet}() \ [\exists x. \ P]} \ \vdash$

Sequence: $\vdash \text{seq} \quad \frac{}{[P] \ c_1 \ [R] \quad [R] \ c_2 \ [Q]} \quad \frac{}{[P] \ c_1; c_2 \ [Q]} \ \vdash$

Choice: $\vdash \text{choice} \quad \frac{}{[P] \ c_1 \ [Q_1] \quad [P] \ c_2 \ [Q_2]} \quad \frac{}{[P] \ c_1 + c_2 \ [Q_1 \ \vee \ Q_2]} \ \vdash$

ChoiceL/ChoiceR (dropping disjuncts): $\vdash \text{choiceL} \quad \frac{}{[P] \ c_1 \ [Q]} \quad \frac{}{[P] \ c_1 + c_2 \ [Q]} \quad \frac{}{[P] \ c_2 \ [Q]} \quad \frac{}{[P] \ c_1 + c_2 \ [Q]} \ \vdash$

Consequence (reversed from HL): $\vdash \text{cons} \quad \frac{}{P' \ \rightarrow P \quad P' \ c \ [Q'] \quad Q \ \rightarrow Q'} \quad \frac{}{[P] \ c \ [Q]} \ \vdash$

In IL we weaken the pre and strengthen the post (opposite of HL).

Disjunction: $\vdash \text{disj} \quad \frac{}{[P_1] \ c \ [Q_1] \quad [P_2] \ c \ [Q_2]} \quad \frac{}{[P_1 \ \vee \ P_2] \ c \ [Q_1 \ \vee \ Q_2]} \ \vdash$

Derived if rule: $\vdash \text{if} \quad \frac{}{[P \ \wedge \ b] \ c_1 \ [Q_1] \quad [P \ \wedge \ \neg b] \ c_2 \ [Q_2]} \quad \frac{}{[P] \ \text{if} \ b \ \text{then} \ c_1 \ \text{else} \ c_2 \ [Q_1 \ \vee \ Q_2]} \ \vdash$

32.5.7 Loop Rules

Bounded unrolling: $\vdash \text{unroll} \quad \frac{}{[P] \ c; c^{\star} \ [Q]} \quad \frac{}{[P] \ c^{\star} \ [Q]} \ \vdash$

Iteration zero: $\vdash \text{iter0} \quad \frac{}{[P] \ c^{\star} \ [P]} \ \vdash$

Backwards variant: $\frac{\forall n \in \mathbb{N}. [P_n] \vdash [P_{n+1}]}{[P_0] \vdash c^{\star}} \frac{\exists k. [P_k]}{\vdash}$

32.5.8 Frame Rule for IL

$\frac{\vdash \frac{[P] \vdash [Q]}{[P] \vdash [Q \wedge R]} \quad [P \wedge R] \vdash [Q \wedge R]}{\vdash}$

Side condition: assigned variables in $\vdash(c)$ are disjoint from free variables in $\vdash(R)$.

32.5.9 Principle of Agreement

If $\vdash([P'] \vdash [Q'])$ and $\vdash(P' \rightarrow P)$ and $\vdash(\{P\} \vdash \{Q\})$ then $\vdash(Q' \rightarrow Q)$.

Proof: $\vdash(Q' \subseteq \llbracket c \rrbracket P' \subseteq \llbracket c \rrbracket P \subseteq \llbracket c \rrbracket Q)$.

32.5.10 Principle of Denial

If $\vdash([P'] \vdash [Q'])$ and $\vdash(P' \rightarrow P)$ and $\vdash(\neg(Q' \rightarrow Q))$ then $\vdash(\neg(\{P\} \vdash \{Q\}))$.

32.5.11 Duality Summary

HL	IL
$\vdash(\{P\} \vdash \{Q\})$ with $\vdash(\llbracket c \rrbracket P \subseteq \llbracket c \rrbracket Q)$	$\vdash([P] \vdash [Q])$ with $\vdash(\llbracket c \rrbracket P \supseteq Q)$
Over-approximation	Under-approximation
Proves correctness	Finds bugs
Strengthen pre, weaken post	Weaken pre, strengthen post
Conjunction rule sound	Conjunction rule unsound
$\vdash(\{P\} \vdash \{Q_1 \wedge Q_2\})$ from premises	$\vdash([P] \vdash [Q_1 \vee Q_2])$ from premises
Forget info along path, remember all paths	Remember info along path, forget some paths

32.6 Lecture 06 — Real Incorrectness Logic

32.6.1 Key Insight

- HL: forget info along a path, remember all paths
- IL: remember info along a path, forget some paths

32.6.2 Exam Checklist



Can handle non-determinism in IL



Understands error killing execution

32.6.3 Exit Conditions

The real IL adds exit conditions $(\epsilon \in \{\text{ok}, \text{er}\})$ to triples:

$[P] \ c \ [\epsilon : Q]$

- **ok**: normal (successful) termination
- **er**: erroneous termination

Shorthand: $([P] \ c \ [\text{ok}:Q_1][\text{er}:Q_2])$ stands for $([P] \ c \ [\text{ok}:Q_1])$ and $([P] \ c \ [\text{er}:Q_2])$.

Validity condition: $(Q_1 \subseteq \llbracket c \rrbracket_{\{\text{ok}\}} P)$ and $(Q_2 \subseteq \llbracket c \rrbracket_{\{\text{er}\}} P)$.

32.6.4 Relational Semantics with Exit Conditions

$\llbracket \llbracket c \rrbracket_{\{\epsilon\}} \subseteq \Sigma \times \Sigma \text{quad} \text{for } \epsilon \in \{\text{ok}, \text{er}\} \rrbracket$

Atomic commands:

$\llbracket \llbracket \text{skip} \rrbracket_{\{\text{ok}\}} \triangleq \{(\sigma, \sigma)\} \text{quad} \llbracket \llbracket \text{skip} \rrbracket_{\{\text{er}\}} \triangleq \emptyset \rrbracket$
 $\llbracket \llbracket b? \rrbracket_{\{\text{ok}\}} \triangleq \{(\sigma, \sigma) \mid \sigma \models b\} \text{quad} \llbracket \llbracket b? \rrbracket_{\{\text{er}\}} \triangleq \emptyset \rrbracket$
 $\llbracket \llbracket x:=a \rrbracket_{\{\text{ok}\}} \triangleq \{(\sigma, \sigma[\llbracket a \rrbracket_{\sigma/x}]) \mid \sigma \in \Sigma\} \text{quad} \llbracket \llbracket$

$x := a \text{ } \triangleleft \text{ } \emptyset$
 $\llbracket \text{mathsf{error}}() \rrbracket \triangleleft \llbracket \text{mathsf{ok}} \rrbracket \triangleleft \emptyset$
 $\triangleleft \{(\sigma, \sigma) \mid \sigma \in \Sigma\}$
 $x := \text{mathsf{nondet}}() \rrbracket \triangleleft \{(\sigma, \sigma[x \mapsto v]) \mid \sigma \in \Sigma, v \in \mathbb{Z}\}$
 $\llbracket x := \text{mathsf{nondet}}() \rrbracket \triangleleft \emptyset$

Composition:

$\llbracket c_1; c_2 \rrbracket \triangleleft \llbracket c_2 \rrbracket \circ \llbracket c_1 \rrbracket$
 $\llbracket c_1; c_2 \rrbracket \triangleleft \llbracket c_1 \rrbracket \cup (\llbracket c_2 \rrbracket \circ \llbracket c_1 \rrbracket)$
 $\llbracket c_1 + c_2 \rrbracket \triangleleft \llbracket c_1 \rrbracket \triangleleft \epsilon$
 $\cup \llbracket c_2 \rrbracket \triangleleft \epsilon$
 $\llbracket c^{\star} \rrbracket \triangleleft \bigcup_{k \in \mathbb{N}} \llbracket c^k \rrbracket \triangleleft \epsilon$

where $(T \circ S) \triangleleft \{(\sigma_1, \sigma_2) \mid \exists \sigma. (\sigma_1, \sigma) \in S \wedge (\sigma, \sigma_2) \in T\}$.

Error short-circuiting: if $\llbracket c_1 \rrbracket$ fails, $\llbracket c_2 \rrbracket$ is skipped.

32.6.5 Real IL Inference Rules

Skip: $\llbracket \text{mathsf{skip}} \rrbracket \triangleleft \frac{\llbracket P \rrbracket \triangleleft \text{mathsf{skip}}}{\llbracket \text{mathsf{ok}} \rrbracket : P}$
 $\llbracket \text{mathsf{er}} \rrbracket : \text{mathsf{false}}$

Floyd's assignment: $\llbracket \text{mathsf{Floyd}} \rrbracket \triangleleft \frac{\llbracket P \rrbracket \triangleleft x := a \mid \text{mathsf{ok}} : \exists x'. P[x'/x] \wedge x = a[x'/x]}{\text{mathsf{er}} : \text{mathsf{false}}}$

Assume: $\llbracket \text{mathsf{assume}} \rrbracket \triangleleft \frac{\llbracket P \rrbracket \triangleleft b? \mid \text{mathsf{ok}} : P \wedge b}{\text{mathsf{er}} : \text{mathsf{false}}}$

Error: $\llbracket \text{mathsf{error}} \rrbracket \triangleleft \frac{\llbracket P \rrbracket \triangleleft \text{mathsf{error}}()}{\text{mathsf{ok}} : \text{mathsf{false}} \mid \text{mathsf{er}} : P}$

Nondet: $\llbracket \text{mathsf{nondet}} \rrbracket \triangleleft \frac{\llbracket P \rrbracket \triangleleft x := \text{mathsf{nondet}}()}{\text{mathsf{ok}} : \exists x. P \mid \text{mathsf{er}} : \text{mathsf{false}}}$

Sequence: $\llbracket \text{seq} \rrbracket \text{quad} \frac{[P] \ c_1 \llbracket \text{ok} \rrbracket R}{[R] \ c_2 \llbracket \text{epsilon} \rrbracket Q} \llbracket [P] \ c_1; c_2 \rrbracket \llbracket \text{epsilon} \rrbracket Q \rrbracket \llbracket \text{seq_sc} \rrbracket \text{quad} \frac{[P] \ c_1 \llbracket \text{er} \rrbracket Q}{[P] \ c_1; c_2 \llbracket \text{er} \rrbracket Q} \rrbracket$

Choice: $\llbracket \text{choiceL} \rrbracket \text{quad} \frac{[P] \ c_1 \llbracket \text{epsilon} \rrbracket Q}{[P] \ c_1 + c_2 \llbracket \text{epsilon} \rrbracket Q} \text{qquad} \llbracket \text{choiceR} \rrbracket \text{quad} \frac{[P] \ c_2 \llbracket \text{epsilon} \rrbracket Q}{[P] \ c_1 + c_2 \llbracket \text{epsilon} \rrbracket Q} \rrbracket$

Frame: $\llbracket \text{frame} \rrbracket \text{quad} \frac{[P] \ c \llbracket Q \rrbracket}{[P \ \text{land} \ R] \ c \llbracket Q \ \text{land} \ R \rrbracket} \rrbracket$

32.6.6 Division and Undefined Expressions

Define $\llbracket \text{def} \rrbracket(a)$ for arithmetic expressions:

$\llbracket \text{def}(n) \rrbracket \triangleq \text{true} \text{qquad} \llbracket \text{def}(x) \rrbracket \triangleq \text{true} \text{qquad} \llbracket \text{def}(a_1 + a_2) \rrbracket \triangleq \llbracket \text{def}(a_1) \rrbracket \ \text{land} \ \llbracket \text{def}(a_2) \rrbracket \rrbracket \llbracket \text{def}(a_1 / a_2) \rrbracket \triangleq \llbracket \text{def}(a_1) \rrbracket \ \text{land} \ \llbracket \text{def}(a_2) \rrbracket \ \text{land} \ a_2 \neq 0 \rrbracket$

For boolean expressions:

$\llbracket \text{def}(a_1 \leq a_2) \rrbracket \triangleq \llbracket \text{def}(a_1) \rrbracket \ \text{land} \ \llbracket \text{def}(a_2) \rrbracket \text{qquad} \llbracket \text{def}(b_1 \ \text{land} \ b_2) \rrbracket \triangleq \llbracket \text{def}(b_1) \rrbracket \ \text{land} \ \llbracket \text{def}(b_2) \rrbracket \rrbracket$

Atomic rules with division:

$\llbracket [P] \ x := a \llbracket \text{ok} \rrbracket \text{:} \exists x'. P[x'/x] \ \text{land} \ \llbracket \text{def}(a[x'/x]) \rrbracket \ \text{land} \ x = a[x'/x] \rrbracket \llbracket [P] \ x := a \llbracket \text{er} \rrbracket \text{:} P \ \text{land} \ \text{not} \llbracket \text{def}(a) \rrbracket \rrbracket \llbracket [P] \ b? \llbracket \text{ok} \rrbracket \text{:} P \ \text{land} \ \llbracket \text{def}(b) \rrbracket \ \text{land} \ b \rrbracket \llbracket [P] \ b? \llbracket \text{er} \rrbracket \text{:} P \ \text{land} \ \text{not} \llbracket \text{def}(b) \rrbracket \rrbracket \rrbracket$

32.6.7 Weakest Precondition in IL

In HL, for any $\llbracket c \rrbracket$ and $\llbracket Q \rrbracket$ there exists a weakest precondition $\llbracket P = \text{operatorname{wlp}}(c, Q) \rrbracket$ such that $\llbracket \{P\} \ c \ \{Q\} \rrbracket$.

In IL, a weakest precondition $\llbracket P \rrbracket$ such that $\llbracket ([P] \ c \llbracket Q \rrbracket) \rrbracket$ may **not** exist. Example: there is no $\llbracket P \rrbracket$ such that $\llbracket ([P] \ x := 42 \llbracket \text{true} \rrbracket) \rrbracket$ because $\llbracket \llbracket \text{true} \rrbracket \llbracket \text{true} \rrbracket \llbracket \text{true} \rrbracket \rrbracket$ is valid but a weaker precondition cannot exist (any $\llbracket P \rrbracket$ makes $\llbracket ([P] \ x := 42 \llbracket \text{true} \rrbracket) \rrbracket$ valid trivially, but there is no unique weakest).

32.6.8 Procedural Abstraction

HL over-approximation for procedures:

```
void foo() { // presumes {x >= 0}
    x := x + 1; // achieves {x > 0}
}
```

With HL, client code can use the spec compositionally because $\{x > 0\} \rightarrow \{x \geq 0\}$.

IL under-approximation for procedures:

```
void foo() { // presumes [x >= 0]
    x := x + 1; // achieves [x > 0]
}
```

With IL, client code **cannot** weaken the precondition: $[x > 0] \not\rightarrow [x \geq 0]$. Under-approximations cannot be weakened, so compositional reasoning is more constrained.

32.7 Lecture 07 — More IL: Non-termination and Control

32.7.1 Key Concepts

- Non-termination analysis via over- and under-approximation
- Guarded commands and nondeterministic choice

32.7.2 Exam Checklist



Understands how IL handles loops (bounded unrolling)

32.7.3 Soundness of IL

Theorem. Any derivable IL triple is valid.

Proof by induction on the derivation tree. It suffices to show local soundness of each rule.

Sample case [seq]: Assume premises valid, i.e., $([c_1] P \supseteq R)$ and $([c_2] R \supseteq Q)$. Then:

$$([c_1; c_2] P = [c_2]([c_1] P) \supseteq [c_2] R \supseteq Q)$$

Sample case choice: Assume $([c_1] P \supseteq Q_1)$ and $([c_2] P \supseteq Q_2)$. Then:

$$([c_1 + c_2] P = [c_1] P \cup [c_2] P \supseteq Q_1 \cup Q_2)$$

Sample case [unroll]: Assume $([c; c^*] P \supseteq Q)$. Then:

$$([c^*] P = \bigcup_{k=0}^{\infty} [c^k] P \supseteq \bigcup_{k=1}^{\infty} [c^k] P = [c; c^*] P \supseteq Q)$$

32.7.4 Relative Completeness of IL

Theorem. Any valid IL triple can be derived, assuming an oracle to decide implications.

Proof sketch: Show $([P] c \vdash [c] P)$ is derivable for any (c) and (P) , by structural induction on (c) . Then for any valid triple $([P] c \vdash [Q])$ we have $([c] P \supseteq Q)$, and we derive it using [cons]:

$$(\frac{[P] c \vdash [c] P \quad [c] P \supseteq Q}{[P] c \vdash [Q]})$$

For Kleene star, use $P_n \triangleq [c^n] P$ and instantiate [iter]:

$$(\frac{\forall n. [c^n] P \vdash [c^{n+1}] P \quad [P] c^* \vdash \exists k. [c^k] P}{[P] c^* \vdash [Q]})$$

32.7.5 Minimal Set of Rules

$$(\text{atom}) \quad \frac{}{[P] e \vdash [e] P} \quad \text{seq} \quad \frac{[P] c_1 \vdash [R] \quad [R] c_2 \vdash [Q]}{[P] c_1; c_2 \vdash [Q]} \quad \text{choice} \quad \frac{}{[P] c_i \vdash [Q_i]} \quad \text{iter} \quad \frac{}{[P] c_1 + c_2 \vdash [Q_1 \cup Q_2]}$$

$$\frac{\forall n \geq 0. [P_n] \text{ c } [P_{n+1}]}{[P_0] \text{ c }^{\star} [\exists k. P_k]} \quad \frac{P' \rightarrow P \quad [P] \text{ c } [Q']}{Q \rightarrow Q'} \quad \frac{[P] \text{ c } [Q]}{[P]}$$

Auxiliary rules: $(\text{disj}), (\text{iter0}), (\text{unroll}), (\text{frame}), (\text{stren}), (\text{weak})$.

32.7.6 Mixed HL+IL Exercises

Exercise 1: Is the following mixed rule sound?

$$\frac{[P] \text{ c } [\text{ok}:P \wedge \neg b] \quad \{P \wedge b\} \text{ c } \{P\}}{[P] \text{ c } [\text{while } b \text{ do } P \text{ c } [\text{ok}:P \wedge \neg b]]}$$

Answer: Yes, the conclusion is always valid, because the HL premise ensures correctness while the IL premise ensures reachability.

Exercise 2: Is the following mixed rule sound?

$$\frac{[P \wedge b] \text{ c } [\text{ok}:P] \quad \{P\} \text{ c } [\text{while } b \text{ do } P \text{ c } \{P \wedge \neg b\}]}{[P \wedge b] \text{ c } [\text{while } b \text{ do } P \text{ c } [\text{ok}:P \wedge \neg b]]}$$

Answer: No. Counterexample: $(P = b = (x > 0)), (c = x := x - 1)$. The IL premise $([x > 0] \text{ c } [-1 \text{ ok}:x > 0])$ is valid, but the HL premise $(\{x > 0\} \text{ c } [\text{while } x > 0 \text{ do } x := x - 1 \text{ c } \{x \leq 0\}])$ is not valid because the loop might not terminate (or the post is $(\{x \leq 0\})$ which doesn't hold for all executions).

32.7.7 Backward Analysis

Weakest possible precondition (wpp) , also called backward semantics:

$$[\llbracket c \rrbracket^{\text{op}} \delta \triangleq \{\sigma \mid \delta \in \llbracket c \rrbracket^{\sigma}\} \quad \llbracket c \rrbracket^{\text{op}} Q \triangleq \bigcup_{\delta \in Q} \llbracket c \rrbracket^{\text{op}} \delta]$$

$(\sigma \in \llbracket c \rrbracket^{\text{op}} \delta \text{ iff } \delta \in \llbracket c \rrbracket^{\sigma})$. Hoare called this the “weakest possible precondition,” distinct from (wlp) .

Example: $(c \trianglelefteq (z := x) + (z := y)), (Q \trianglelefteq (z = 0))$.

- $(\text{operatorname{wlp}}(c, Q) = (x = 0 \wedge y = 0))$ (both branches must give $(z = 0)$)
- $(\llbracket c \rrbracket^{\text{mathsf{op}}} Q = (x = 0 \vee y = 0))$ (at least one branch can give $(z = 0)$)

32.7.8 Necessary Conditions (NC) Logic

NC triple: $((P) \ c \ (Q))$ means “any state (σ) that admits at least one non-erroneous execution of (c) ending in (Q) is in (P) .”

$$\llbracket (P) \ c \ (Q) \text{ iff } \llbracket c \rrbracket^{\text{mathsf{op}}} Q \subseteq P \rrbracket$$

NC is an **over-approximation** (backward) logic. It expresses necessary preconditions for correctness: if $(\sigma \notin P)$, then all executions either diverge or reach only bad states.

$$\llbracket G(\sigma) \neq \emptyset \implies \sigma \in P \quad \sigma \notin P \implies (I(\sigma) = \emptyset \implies B(\sigma) \neq \emptyset \wedge G(\sigma) = \emptyset) \rrbracket$$

NC Consequence rule:

$$\llbracket \frac{P' \rightarrow P \quad (P') \ c \ (Q') \quad Q \rightarrow Q'}{(P) \ c \ (Q)} \rrbracket$$

Weaken the pre and strengthen the post (same direction as HL).

32.7.9 HL vs NC Relation

$$\llbracket \{P\} \ c \ \{Q\} \text{ iff } (\neg P) \ c \ (\neg Q) \rrbracket$$

Proof: Assume $(\llbracket c \rrbracket P \subseteq Q)$. Want $(\llbracket c \rrbracket^{\text{mathsf{op}}} (\neg Q) \subseteq \neg P)$. Take $(\sigma \in \llbracket c \rrbracket^{\text{mathsf{op}}} (\neg Q))$. Then $(\exists \delta \in \neg Q)$ with $(\sigma \in \llbracket c \rrbracket^{\text{mathsf{op}}} \delta)$, i.e., $(\delta \in \llbracket c \rrbracket \sigma)$. If $(\sigma \in P)$, then $(\delta \in \llbracket c \rrbracket \sigma \subseteq \llbracket c \rrbracket P \subseteq Q)$, contradicting $(\delta \notin Q)$. Thus $(\sigma \notin P)$, i.e., $(\sigma \in \neg P)$.

32.7.10 Four-Logic Comparison

	Forward	Backward
Over	HL: $\langle P \rangle c \langle Q \rangle, \langle \llbracket c \rrbracket P \subseteq Q \rangle$	NC: $\langle (P) c (Q) \rangle, \langle \llbracket c \rrbracket Q \subseteq P \rangle$
Under	IL: $\langle [P] c [Q] \rangle, \langle \llbracket c \rrbracket P \supseteq Q \rangle$	SIL: $\langle \langle P \rangle c \langle Q \rangle \rangle, \langle \llbracket c \rrbracket Q \supseteq P \rangle$

32.8 Lecture 08 — Symbolic Incorrectness Logic (SIL)

32.8.1 Key Concepts

- SIL extends IL with symbolic execution and path conditions
- Under-approximate reasoning with symbolic states

32.8.2 Exam Checklist



Understands SIL triples as under-approximation



Knows the SIL guard axiom condition: $\langle P \rangle \subseteq b$ for soundness

32.8.3 SIL Definition

SIL (Sufficient Incorrectness Logic) is a **backward under-approximation** logic. SIL triple:

$\langle \langle P \rangle c \langle Q \rangle \rangle$

Validity: $\langle P \rangle \subseteq \llbracket c \rrbracket Q$, i.e., $\langle \forall \sigma \in P. \exists \delta \in Q. \delta \in \llbracket c \rrbracket \sigma \rangle$.

Meaning: any state in $\langle P \rangle$ can lead to an error in $\langle Q \rangle$. This characterizes **sufficient conditions for incorrectness** — it finds initial states that cause errors.

Manifest errors: An error is manifest if it occurs independently of context. $\llbracket \langle \text{true} \rangle \text{ c } \langle Q \rangle \rrbracket \text{ is valid } \iff Q \text{ is a manifest error} \rrbracket$

32.8.4 SIL Inference Rules

Hoare-style assignment (backward): $\llbracket \langle \text{Hoare} \rangle \rrbracket \quad \dfrac{\langle Q[a/x] \rangle \text{ c } \langle Q \rangle}{\langle Q \rangle \text{ c } \langle x := a \rangle}$

Assume/Guard (backward): $\llbracket \langle \text{assume} \rangle \rrbracket \quad \dfrac{\langle Q \land b \rangle \text{ c } \langle Q \rangle}{\langle Q \rangle \text{ c } \langle b? \rangle}$ Note: if $\langle Q \rangle$ contradicts $\langle b \rangle$, the precondition is empty (e.g., $\langle \emptyset \rangle \text{ c } \langle (x > 0)? \rangle \langle x = -42 \rangle$).

Choice (backward): $\llbracket \langle \text{choice} \rangle \rrbracket \quad \dfrac{\langle P_1 \rangle \text{ c } \langle Q \rangle \quad \langle P_2 \rangle \text{ c } \langle Q \rangle}{\langle P_1 \lor P_2 \rangle \text{ c } \langle Q \rangle}$

Iteration (backward): $\llbracket \langle \text{iter} \rangle \rrbracket \quad \dfrac{\text{forall } n \geq 0. \langle Q_{n+1} \rangle \text{ c } \langle Q_n \rangle}{\langle \text{exists } k. \langle Q_k \rangle \text{ c } \langle \text{star} \rangle \langle Q_0 \rangle}$

Empty/Cons' (dropping disjuncts): $\llbracket \langle \text{cons'} \rangle \rrbracket \quad \dfrac{\langle P \rangle \text{ c } \langle Q \rangle}{\langle P \lor R \rangle \text{ c } \langle Q \rangle}$

Note: this is the opposite of dropping in IL: in SIL we can enlarge the pre (since it is backward, a larger pre means more states that can reach the error).

32.8.5 Soundness and Completeness

Soundness: All provable SIL triples are valid. Proof by induction on derivation.

Completeness: All valid SIL triples are provable (using core rules).

32.8.6 SIL vs IL vs HL

Given specification $\langle Q \rangle \trianglelefteq \{z = 42\}$ for the program:

```

if even(x) {
    if odd(y) { z := 42; }
}

```

- **HL:** $\{z = 42\} \vdash \{z = 42\}$ (trivial, doesn't rule out $\{z = 42\}$ already holding)
- **IL:** $\{z = 11\} \vdash [z = 42 \wedge \text{odd}(y) \wedge \text{even}(x)]$ (postcondition is reachable)
- **SIL:** $\langle z = 11 \wedge \text{odd}(y) \wedge \text{even}(x) \rangle \vdash \langle z = 42 \rangle$ (precondition that leads to error)

32.8.7 SIL vs HL for Deterministic Programs

If $\{c\}$ is deterministic and terminating, SIL is equivalent to HL:

$\langle P \rangle \vdash \langle Q \rangle \text{ iff } \{P\} \vdash \{Q\}$

32.8.8 Unsoundness of $\langle \text{conj} \rangle$ in SIL

The rule $\langle P_1 \rangle \vdash \langle Q_1 \rangle, \langle P_2 \rangle \vdash \langle Q_2 \rangle \vdash \langle P_1 \wedge P_2 \rangle \vdash \langle Q_1 \wedge Q_2 \rangle$ is unsound.

Counterexample: $\langle x=0 \rangle \vdash x:=1 \vdash \langle x=0 \rangle$ and $\langle x=0 \rangle \vdash x:=1 \vdash \langle x=1 \rangle$ are both valid, but $\langle x=0 \rangle \vdash x:=1 \vdash \langle x=0 \wedge x=1 \rangle = \langle \text{false} \rangle$ is not valid.

32.8.9 SIL Guard Axiom Exercise

Is $\langle P \rangle \vdash b? \vdash \langle P \wedge b \rangle$ valid?

No. Counterexample: $\langle x \geq 0 \rangle \vdash (x > 1)? \vdash \langle x \geq 2 \rangle$ is not valid because $\{x = 0\}$ cannot reach $\{x \geq 2\}$.

32.8.10 Taxonomy and Consequence Rules

	Forward	Backward
Over	HL: $\{P\} \vdash \{Q\}, \langle P \rangle \vdash \langle Q \rangle$	NC: $\langle P \rangle \vdash \langle Q \rangle, \langle P \supseteq Q \rangle$
Under		

Forward	Backward
IL: $\frac{}{([P] \ c \ [Q])}, \frac{}{(\llbracket c \rrbracket \ P \ \supseteq Q)}$	SIL: $\frac{}{(\langle P \rangle \ c \ \langle Q \rangle)}, \frac{}{(\langle P \rangle \ \supseteq \llbracket c \rrbracket \ Q)}$

Consequence rules per logic:

- **HL:** $\frac{(P \rightarrow P', \{P'\} \ c \ \{Q'\}, Q' \rightarrow Q \vdash \{P\} \ c \ \{Q\})}{(P \rightarrow P', \{P'\} \ c \ \{Q'\}, Q' \rightarrow Q \vdash \{P\} \ c \ \{Q\})}$ (strengthen pre, weaken post)
- **NC:** $\frac{(P' \rightarrow P, (P') \ c \ (Q'), Q \rightarrow Q' \vdash (P) \ c \ (Q))}{(P' \rightarrow P, (P') \ c \ (Q'), Q \rightarrow Q' \vdash (P) \ c \ (Q))}$ (weaken pre, strengthen post)
- **IL:** $\frac{(P' \rightarrow P, [P'] \ c \ [Q'], Q \rightarrow Q' \vdash [P] \ c \ [Q])}{(P' \rightarrow P, [P'] \ c \ [Q'], Q \rightarrow Q' \vdash [P] \ c \ [Q])}$ (weaken pre, strengthen post)
- **SIL:** $\frac{(P \rightarrow P', \langle P' \rangle \ c \ \langle Q' \rangle, Q \rightarrow Q' \vdash \langle P \rangle \ c \ \langle Q \rangle)}{(P \rightarrow P', \langle P' \rangle \ c \ \langle Q' \rangle, Q \rightarrow Q' \vdash \langle P \rangle \ c \ \langle Q \rangle)}$ (strengthen pre, weaken post)

32.9 Lecture 09 — Separation Logic

32.9.1 Key Definitions

- **Heap model:** $\text{stack } (\sigma) + \text{heap } (h)$
- **Separating conjunction:** $(P \star Q)$ — disjoint heap regions
- **Magic wand:** $(P \multimap Q)$ — adjoint of $(\star)$

32.9.2 Key Formulas

- Frame rule: $\frac{(P \ c \ Q) \vdash (P \star R) \ c \ (Q \star R)}{(P \ c \ Q) \vdash (P \star R) \ c \ (Q \star R)}$

32.9.3 Exam Checklist

☐

Can reason about heap-manipulating programs with SL

☐

Understands the frame rule and its soundness condition

32.9.4 Heap Model

Stores: $(s : X \rightarrow \mathbb{Z})$ (variables to values) Heaps: $(h : \mathbb{N} \rightarrow \mathbb{Z}_{\text{bot}})$ (locations to values, $(\text{bot} = \text{null} = -1)$ for deallocated) States: $(\langle s, h \rangle \in \Sigma \rightarrow S \times H)$

Domain of a heap: $(\text{dom}(h))$ is the set of defined locations.

Disjoint heap composition: $(h_1 \# h_2 \text{ iff } \text{dom}(h_1) \cap \text{dom}(h_2) = \emptyset)$ $(h_1 \bullet h_2)$ is the union of functions with disjoint domains (undefined if $(\neg(h_1 \# h_2))$).

Heap update: $(h[x \mapsto n])$ is (h) with (x) mapped to (n) .

32.9.5 Assertion Language

$[P ::= \text{true} \mid \text{false} \mid a_1 < a_2 \mid a_1 = a_2 \mid \dots \text{quad} \text{pure assertions} \mid \neg P \mid P_1 \land P_2 \mid \exists x. P \mid \dots \mid \text{emp} \mid a_1 \mapsto a_2 \mid P_1 \star P_2 \text{quad} \text{structural assertions}]$

Abbreviations: $[a \mapsto _ \triangleq \exists v. a \mapsto v \text{quad} \text{for } \$v \text{ fresh}]$ $a_1 \doteq a_2 \triangleq (a_1 = a_2) \land \text{emp}$ $[a \mapsto \langle a_0, \dots, a_k \rangle \triangleq (a \mapsto a_0) \star \dots \star (a + k \mapsto a_k)]$

32.9.6 Satisfaction Relation

$(\langle s, h \rangle \models P)$ means the assertion holds for state $(\langle s, h \rangle)$.

Classical:

- $(\langle s, h \rangle \models a_1 < a_2) \text{ iff } (s \models a_1 < a_2)$ (heap irrelevant)
- $(\langle s, h \rangle \models P_1 \land P_2) \text{ iff } (\langle s, h \rangle \models P_1) \text{ and } (\langle s, h \rangle \models P_2)$
- $(\langle s, h \rangle \models \forall x. P) \text{ iff } (\forall v \in \mathbb{Z}. \langle s[x \mapsto v], h \rangle \models P)$

Structural:

- $(\langle s, h \rangle \models a_1 \mapsto a_2) \text{ iff } (\text{dom}(h) = \{ \llbracket a_1 \rrbracket s \}) \text{ and } (h(\llbracket a_1 \rrbracket s) = \llbracket a_2 \rrbracket s)$

- $\langle s, h \rangle \models \text{emp}$ iff (h) is the empty map
- $\langle s, h \rangle \models P_1 \star P_2$ iff $\exists h_1, h_2. \langle s, h_1 \rangle \models P_1$ and $\langle s, h_2 \rangle \models P_2$ and $(h = h_1 \bullet h_2)$

32.9.7 Properties of $(\star)$

- $(x \mapsto v \star y \mapsto w \not\Rightarrow x \mapsto v)$ (separating conjunction requires disjoint heaps)
- $(x \mapsto v \wedge y \mapsto w \Rightarrow x \mapsto v)$ (classical conjunction is weaker)
- $(x \mapsto v \star x \mapsto w \equiv \text{false})$ (a cell cannot be split)
- $((x = y) \star (x = y) \equiv (x = y))$ (pure assertions are duplicable)
- $(P \star \text{emp} \equiv P)$ (empty heap is unit of $(\star)$)

32.9.8 Small/Local Axioms

Write: $\llbracket \text{write} \rrbracket \quad \text{dfrac{}{} \{a_1 \mapsto _ \} [a_1] := a_2 \{a_1 \mapsto a_2\}}$

Read: $\llbracket \text{read} \rrbracket \quad \text{dfrac{}{} \{y \mapsto v\} x := [y] \{x = v \wedge y \mapsto v\}}$

Allocation: $\llbracket \text{alloc} \rrbracket \quad \text{dfrac{}{} \{\text{emp}\} x := \text{alloc}() \{x \mapsto _ \}$ $\llbracket \text{cons} \rrbracket \quad \text{dfrac{}{} \{x \text{doteq } x'\} x := \text{cons}(a_1, \dots, a_k) \{x \mapsto \langle s' \mid a_1[x'/x], \dots, a_k[x'/x] \rangle \}$

Dispose: $\llbracket \text{dispose} \rrbracket \quad \text{dfrac{}{} \{a \mapsto _ \} \{\text{free}(a) \text{emp}\}}$

32.9.9 Frame Rule

$\llbracket \text{frame} \rrbracket \quad \text{dfrac{}{} \{P\} c \{Q\} \{P \star R\} c \{Q \star R\}}$

Side condition: $(\text{mod}(c) \cap \text{fv}(R) = \emptyset)$
(variables modified by (c) are disjoint from free variables in (R)).

The frame rule enables **local reasoning**: the specification can concentrate on accessed cells; other cells remain unchanged.

32.9.10 Footprint Recipe

1. Derive the specification of c using local axioms.
2. Apply the frame rule to extend the specification with idle resources.

Example: $\llbracket \text{dfrac}\{\{x \mapsto _\}\} [x] := 1 \backslash \{x \mapsto 1\} \rrbracket \{x \mapsto _\star R\} \backslash [x] := 1 \backslash \{x \mapsto 1 \star R\} \rrbracket$ with $(R \text{equiv } (y \mapsto _\star z \mapsto _))$.

32.9.11 Inductive Predicates for Lists

Precise list segment $\text{ls}(a_1, a_2)$:

$$\llbracket \text{ls}(a_1, a_2) \rrbracket \triangleq (a_1 = a_2 \wedge \text{emp}) \vee (a_1 \neq a_2 \wedge \exists \ell. a_1 \mapsto \ell \star \text{ls}(\ell, a_2))$$

Full list: $\text{list}(a) \triangleq \text{ls}(a, \text{nil})$.

Imprecise list segment $\text{ils}(a_1, a_2)$:

$$\llbracket \text{ils}(a_1, a_2) \rrbracket \triangleq (a_1 = a_2 \wedge \text{emp}) \vee (\exists v. a_1 \mapsto v \star \text{ils}(v, a_2))$$

$\text{ils}(a_1, a_2) \not\equiv \text{ls}(a_1, a_2)$. For example, $\text{ils}(42, 42)$ is satisfied by $\text{dom}(h) = \{42\}, h(42) = 42$, but $\text{ls}(42, 42)$ requires emp for the $(a_1 = a_2)$ case.

32.9.12 List Reversal Example

Full invariant for in-place list reversal:

$$\llbracket \text{inv} \rrbracket \triangleq \exists \alpha, \beta. \text{ls}(\alpha, p) \star \text{ls}(\beta, q) \wedge \alpha_0 = \alpha^{\dagger} \cdot \beta$$

where $\alpha^{\dagger}$ is the reverse of α , and α_0 is the original list. The separating conjunction $\star$ ensures the two list segments are disjoint. The inductive reachability predicate prevents overlap:

$$\llbracket (p, q) \rrbracket \triangleq p = q \vee \exists v, t. p \mapsto \text{angle } v, t \text{rangle} \wedge (t, q)$$

The invariant ensures $\langle p \rangle$ points to the remaining fragment and $\langle q \rangle$ to the already reversed fragment.

32.9.13 Correctness Theorem

Theorem. If $\langle \{P\} \ c \ \{Q\} \rangle$ is provable in SL, then $\llbracket P \rrbracket \subseteq^* Q$.

Proof by induction on the derivation. The key lemma is the frame property: if $\langle \{P\} \ c \ \{Q\} \rangle$ holds for a local specification, extending with $\langle \star R \rangle$ preserves correctness because $\langle c \rangle$ does not touch cells in $\langle R \rangle$.

32.9.14 Incompleteness and the Footprint Theorem

Theorem (Incompleteness). There exist valid SL triples that are not provable.

The issue is the **footprint** — the frame rule can be too weak when allocation produces a location that aliases with the frame. For example:

$$\llbracket \{y \mapsto _ \} \ x := \text{alloc}(); \text{free}(x) \ \{y \mapsto _ \text{ and } y \neq x\} \rrbracket$$

should be valid but cannot be derived in basic SL because the information that $\langle x \rangle$ is fresh is lost after $\langle \text{free}(x) \rangle$.

32.9.15 Satisfaction Exercises

Exercise 1: Find a state satisfying $\langle (x \dot{=} y) \ \star x \mapsto y \rangle$.
 Answer: $\langle x = y \rangle$, $\langle \text{dom}(h) = \{s(x)\} \rangle$, $\langle h(s(x)) = s(y) \rangle$. Since $\langle x \dot{=} y \rangle$ is pure, $\langle \star \rangle$ requires no heap from it.

Exercise 2: Show a state satisfying $\langle (x \mapsto y) \ \star \neg(x \mapsto y) \rangle$. Answer: $\langle \text{dom}(h) = \{11\} \rangle$, $\langle s(x) = 11 \rangle$, $\langle h(11) = 42 \rangle$, $\langle s(y) = 42 \rangle$. Split $\langle h \rangle$ into two parts: $\langle h_1 \rangle$ with $\langle \text{dom}(h_1) = \{11\} \rangle$ gives $\langle x \mapsto y \rangle$, $\langle h_2 \rangle$ empty gives $\langle \neg(x \mapsto y) \rangle$.

32.10 Lecture 10 — ISL and SepSIL

32.10.1 Key Concepts

- ISL: under-approximate reasoning + separation logic

- SepSIL: symbolic execution with separation logic for bug finding

32.10.2 Exam Checklist



Knowledge of ISL triple structure

32.10.3 ISL Definition

ISL (Incorrectness Separation Logic) combines IL (under-approximate bug finding) with SL (local heap reasoning).

$$\llbracket [P] \rrbracket c \llbracket [\epsilon : Q] \rrbracket$$

ISL adds the frame rule for separation logic to IL:

$$\llbracket [\text{frame}] \rrbracket \quad \frac{\llbracket [P] \rrbracket c \llbracket [\epsilon : Q] \rrbracket}{\llbracket [P \star R] \rrbracket c \llbracket [\epsilon : Q \star R] \rrbracket}$$

Side condition: $(\text{mod}(c) \cap \text{fv}(R) = \emptyset)$.

32.10.4 ISL Regular Commands

Atomic commands with heap operations:

$$\llbracket e ::= \text{skip} \rrbracket \mid b? \mid x := a \mid x := [y] \mid \text{read} \mid [x] := y \mid \text{write} \mid x := \text{alloc}() \mid \text{free}(x) \mid \text{error}()$$

32.10.5 ISL Local Axioms with Error Tracking

Write: $\llbracket [x \mapsto v] \rrbracket [x] := y \llbracket [\text{ok}] : x \mapsto y \rrbracket \quad \llbracket [x = \text{nil}] \rrbracket [x] := y \llbracket [\text{er}] : x = \text{nil} \rrbracket$

Read: $\llbracket [y \mapsto v] \rrbracket x := [y] \llbracket [\text{ok}] : x = v \wedge y \mapsto v \rrbracket \quad \llbracket [y = \text{nil}] \rrbracket x := [y] \llbracket [\text{er}] : y = \text{nil} \rrbracket$

Allocation: $\llbracket [x \text{doteq } x'] \rrbracket x := \text{alloc}() \llbracket [\text{ok}] : x \mapsto _ \rrbracket$

Dispose (first try, problematic): $\llbracket [x \mapsto v] \rrbracket \text{free}(x) \llbracket [\text{ok}] : \text{emp} \rrbracket \quad \llbracket [x = \text{nil}] \rrbracket \text{free}(x) \llbracket [\text{er}] : x = \text{nil} \rrbracket$

32.10.6 Unsound Frame Rule with Free

The frame rule with the simple dispose axiom is **unsound**:

$$\frac{[\text{dfrac}\{[x \mapsto v] \backslash \text{free}(x) \backslash [\text{ok} : \text{emp}]]\}]{[x \mapsto v \star x \mapsto v] \backslash \text{free}(x) \backslash [\text{ok} : \text{emp}] \star x \mapsto v}}{}$$

By [cons]: $([\text{false}] \backslash \text{free}(x) \backslash [\text{ok} : x \mapsto v])$. The only sound under-approximation from an inconsistent pre is false.

32.10.7 Solution: The $(x \text{ \textasciitilde\textasciitilde\mapsto})$ Predicate

Add $(x \text{ \textasciitilde\textasciitilde\mapsto})$ to the assertion language to track deallocated locations:

- $(\langle s, h \rangle \models x \text{ \textasciitilde\textasciitilde\mapsto})$ iff $(\text{dom}(h) = \{s(x)\})$ and $(h(s(x)) = \text{bot})$
- $(x \text{ \textasciitilde\textasciitilde\mapsto})$ records that location (x) has been freed

Properties:

- $(x \mapsto v \star x \text{ \textasciitilde\textasciitilde\mapsto} \equiv \text{false})$ (cannot be both allocated and deallocated)
- $(x \text{ \textasciitilde\textasciitilde\mapsto} \star x \text{ \textasciitilde\textasciitilde\mapsto} \equiv \text{false})$ (a cell cannot be doubly deallocated)
- $(y \mapsto v \star x \text{ \textasciitilde\textasciitilde\mapsto} \equiv y \mapsto v \star x \text{ \textasciitilde\textasciitilde\mapsto} \wedge x \neq y)$ (free and alloc on different cells)

32.10.8 Corrected Local Axioms with $(x \text{ \textasciitilde\textasciitilde\mapsto})$

Dispose (corrected): $[[x \mapsto v] \backslash \text{free}(x) \backslash [\text{ok} : x \text{ \textasciitilde\textasciitilde\mapsto}] \quad [x = \text{nil}] \backslash \text{free}(x) \backslash [\text{er} : x = \text{nil}]]$

Now resources cannot shrink: $(x \mapsto v)$ is replaced by $(x \text{ \textasciitilde\textasciitilde\mapsto})$, preserving the footprint.

Additional error axioms (use-after-free, double-free): $[[x \text{ \textasciitilde\textasciitilde\mapsto}] [x := y] \backslash [\text{er} : x \text{ \textasciitilde\textasciitilde\mapsto}] \quad [y \text{ \textasciitilde\textasciitilde\mapsto}] [x := y] \backslash [\text{er} : y \text{ \textasciitilde\textasciitilde\mapsto}]] \quad [[x \text{ \textasciitilde\textasciitilde\mapsto}] \backslash \text{free}(x) \backslash [\text{er} : x \text{ \textasciitilde\textasciitilde\mapsto}] \quad [y \text{ \textasciitilde\textasciitilde\mapsto}] [x := \text{alloc}()] \backslash [\text{ok} : x \mapsto v \wedge x = y]]$

32.10.9 Full ISL Inference Rules

Skip: $\llbracket \text{Skip} \rrbracket \text{quad} \frac{}{\llbracket \text{skip} \rrbracket \text{ : } \llbracket \text{ok} \rrbracket}$

Assign: $\llbracket \text{Assign} \rrbracket \text{quad} \frac{[x = x'] \text{ x} := e \llbracket \text{ok} \rrbracket : x = e[x'/x]]{} \llbracket \text{ok} \rrbracket$

Assume: $\llbracket \text{Assume} \rrbracket \text{quad} \frac{}{\llbracket \text{assume}(B) \rrbracket \text{ : } B}$

Seq1 (error short circuit): $\llbracket \text{Seq1} \rrbracket \text{quad} \frac{[P] \llbracket C_1 \rrbracket \llbracket \text{er}(l) : Q \rrbracket}{[P] \llbracket C_1; C_2 \rrbracket \llbracket \text{er}(l) : Q \rrbracket}$

Seq2: $\llbracket \text{Seq2} \rrbracket \text{quad} \frac{[P] \llbracket C_1 \rrbracket \llbracket \text{ok} \rrbracket : R \llbracket \text{ok} \rrbracket [R] \llbracket C_2 \rrbracket \llbracket \epsilon : Q \rrbracket}{[P] \llbracket C_1; C_2 \rrbracket \llbracket \epsilon : Q \rrbracket}$

Choice: $\llbracket \text{Choice} \rrbracket \text{quad} \frac{[P] \llbracket C_i \rrbracket \llbracket \epsilon : Q \rrbracket}{\text{for some } i \in \{1, 2\} \llbracket P \rrbracket \llbracket C_1 + C_2 \rrbracket \llbracket \epsilon : Q \rrbracket}$

Error: $\llbracket \text{Error} \rrbracket \text{quad} \frac{}{\llbracket \text{error} \rrbracket \llbracket \text{er}(l) : \llbracket \text{ok} \rrbracket \rrbracket}$

Loop1 (zero iterations): $\llbracket \text{Loop1} \rrbracket \text{quad} \frac{[P] \llbracket C^{\star} \rrbracket \llbracket \text{ok} \rrbracket : P \rrbracket{} \llbracket \text{ok} \rrbracket$

Loop2 (unroll): $\llbracket \text{Loop2} \rrbracket \text{quad} \frac{[P] \llbracket C^{\star} \rrbracket \llbracket \epsilon : Q \rrbracket}{[P] \llbracket C^{\star} \rrbracket \llbracket \epsilon : Q \rrbracket}$

Disj: $\llbracket \text{Disj} \rrbracket \text{quad} \frac{[P_1] \llbracket C \rrbracket \llbracket \epsilon : Q_1 \rrbracket \llbracket P_2 \rrbracket \llbracket C \rrbracket \llbracket \epsilon : Q_2 \rrbracket}{[P_1 \vee P_2] \llbracket C \rrbracket \llbracket \epsilon : Q_1 \vee Q_2 \rrbracket}$

Cons (reversed consequence): $\llbracket \text{Cons} \rrbracket \text{quad} \frac{P' \rightarrow P \llbracket P \rrbracket \llbracket C \rrbracket \llbracket \epsilon : Q \rrbracket \llbracket Q \rrbracket \rightarrow Q' \llbracket P' \rrbracket \llbracket C \rrbracket \llbracket \epsilon : Q' \rrbracket}{\llbracket \text{ok} \rrbracket}$

Havoc: $\llbracket \text{Havoc} \rrbracket \text{quad} \frac{[x = x'] \text{ x} := \star \llbracket \text{ok} \rrbracket : x = v \rrbracket{} \llbracket \text{ok} \rrbracket$

Local: $\llbracket \text{Local} \rrbracket \text{quad} \frac{[P] \llbracket C \rrbracket \llbracket \epsilon : Q \rrbracket}{\llbracket \text{local } x \rrbracket \llbracket \text{in} \rrbracket \llbracket C \rrbracket \llbracket \epsilon : \llbracket \text{exists } x \rrbracket Q \rrbracket}$

Exists: $\llbracket \text{Exists} \rrbracket \text{quad} \frac{[P] \llbracket C \rrbracket \llbracket \epsilon : Q \rrbracket}{\llbracket \text{exists } x \rrbracket P \llbracket C \rrbracket \llbracket \epsilon : \llbracket \text{exists } x \rrbracket Q \rrbracket}$

Subst: $\llbracket \text{Subst} \rrbracket \text{quad} \frac{[P] \llbracket C \rrbracket \llbracket \epsilon : Q \rrbracket \llbracket P[y/x] \rrbracket \llbracket C[y/x] \rrbracket \llbracket \epsilon : Q[y/x] \rrbracket}{\llbracket \text{ok} \rrbracket}$

Alloc1: $\llbracket \text{Alloc1} \rrbracket \text{quad} \text{dfrac}\{ \{ [x = x'] \mid x := \text{alloc}() \} \mid \text{ok} : x \mapsto _ \}$

Alloc2: $\llbracket \text{Alloc2} \rrbracket \text{quad} \text{dfrac}\{ \{ [x = x' \star y \text{ \textit{mapsto}}] \mid x := \text{alloc}() \} \mid \text{ok} : x = y \star y \mapsto _ \}$

Free: $\llbracket \text{Free} \rrbracket \text{quad} \text{dfrac}\{ \{ [x \mapsto e] \mid \text{free}(x) \} \mid \text{ok} : x \text{ \textit{mapsto}} \}$

FreeEr: $\llbracket \text{FreeEr} \rrbracket \text{quad} \text{dfrac}\{ \{ [x \text{ \textit{mapsto}}] \mid \text{free}(x) \} \mid \text{er}(l) : x \text{ \textit{mapsto}} \}$

FreeNull: $\llbracket \text{FreeNull} \rrbracket \text{quad} \text{dfrac}\{ \{ [x = \text{null}] \mid \text{free}(x) \} \mid \text{er}(l) : x = \text{null} \}$

Load: $\llbracket \text{Load} \rrbracket \text{quad} \text{dfrac}\{ \{ [x = x' \star y \mapsto e] \mid x := [y] \} \mid \text{ok} : x = e[x'/x] \star y \mapsto e[x'/x] \}$

LoadEr: $\llbracket \text{LoadEr} \rrbracket \text{quad} \text{dfrac}\{ \{ [y \text{ \textit{mapsto}}] \mid x := [y] \} \mid \text{er}(l) : y \text{ \textit{mapsto}} \}$

LoadNull: $\llbracket \text{LoadNull} \rrbracket \text{quad} \text{dfrac}\{ \{ [y = \text{null}] \mid x := [y] \} \mid \text{er}(l) : y = \text{null} \}$

Store: $\llbracket \text{Store} \rrbracket \text{quad} \text{dfrac}\{ \{ [x \mapsto e] \mid [x] := y \} \mid \text{ok} : x \mapsto y \}$

StoreEr: $\llbracket \text{StoreEr} \rrbracket \text{quad} \text{dfrac}\{ \{ [x \text{ \textit{mapsto}}] \mid [x] := y \} \mid \text{er}(l) : x \text{ \textit{mapsto}} \}$

StoreNull: $\llbracket \text{StoreNull} \rrbracket \text{quad} \text{dfrac}\{ \{ [x = \text{null}] \mid [x] := y \} \mid \text{er}(l) : x = \text{null} \}$

Frame: $\llbracket \text{Frame} \rrbracket \text{quad} \text{dfrac}\{ [P] \mid C \mid \text{epsilon} : Q \} \{ [P \star R] \mid C \mid \text{epsilon} : Q \star R \}$

32.10.10 ISL Relational Semantics

$\llbracket \text{skip} \rrbracket_{\text{ok}} \triangleq \{ (\sigma, \sigma) \} \text{quad} \llbracket \text{skip} \rrbracket_{\text{er}} \triangleq \emptyset \mid \llbracket b? \rrbracket_{\text{ok}} \triangleq \{ (\sigma, \sigma) \mid \sigma = \langle s, h \rangle \text{ and } s \models b \} \mid \llbracket \text{error} \rrbracket_{\text{ok}} \triangleq \emptyset \text{quad} \llbracket \text{error} \rrbracket_{\text{er}} \triangleq \{ (\sigma, \sigma) \} \mid \llbracket x := [y] \rrbracket_{\text{ok}} \triangleq \{ (\langle s, h \rangle, \langle s[x \mapsto v], h \rangle) \mid v = h(s(y)) \text{ in } \mathbb{Z} \} \mid \llbracket x :=$

$$\begin{aligned}
& [y] \rrbracket_{\{\text{er}\}} \triangleq \{(\langle s, h \rangle, \langle s, h \rangle) \mid s(y) = \text{nil} \vee h(s(y)) = \text{bot}\} \cup \{ \llbracket x := y \rrbracket_{\{\text{ok}\}} \triangleq \{(\langle s, h \rangle, \langle s, h[s(x) \mapsto s(y)] \rangle) \mid h(s(x)) \in \mathbb{Z}\} \cup \{ \llbracket x := y \rrbracket_{\{\text{er}\}} \triangleq \{(\langle s, h \rangle, \langle s, h \rangle) \mid s(x) = \text{nil} \vee h(s(x)) = \text{bot}\} \cup \{ \llbracket x := \text{alloc}() \rrbracket_{\{\text{ok}\}} \triangleq \{(\langle s, h \rangle, \langle s[x \mapsto n], h[n \mapsto v] \rangle) \mid v \in \mathbb{Z} \land (n \notin \text{dom}(h) \vee h(n) = \text{bot})\} \cup \{ \llbracket \text{free}(x) \rrbracket_{\{\text{ok}\}} \triangleq \{(\langle s, h \rangle, \langle s[x \mapsto v] \rangle, \langle s, h \rangle, \langle s[x \mapsto \text{bot}] \rangle) \mid s(x) \in \mathbb{N} \land v \in \mathbb{Z}\} \cup \{ \llbracket \text{free}(x) \rrbracket_{\{\text{er}\}} \triangleq \{(\langle s, h \rangle, \langle s, h \rangle) \mid s(x) = \text{nil} \vee h(s(x)) = \text{bot}\} \} \}
\end{aligned}$$

32.10.11 Footprint Holds in ISL

The footprint that failed in SL is now derivable in ISL:

$$\begin{aligned}
& \{ \text{dfrac{[]}{[]}} \} x := \text{alloc}() \{ \text{ok} : x \mapsto v \} \text{qquad} [x \mapsto v] \{ \text{free}(x) \} \{ \text{ok} : x \wedge \text{!} \mapsto \} \\
& \{ [y \mapsto _ \star \text{emp}] \} x := \text{alloc}(); \text{free}(x) \{ \text{ok} : y \mapsto _ \star x \wedge \text{!} \mapsto \} \}
\end{aligned}$$

using [seq], [frame], [cons] to obtain $\{ [y \mapsto _] \} x := \text{alloc}(); \text{free}(x) \{ \text{ok} : y \mapsto _ \wedge y \neq x \}$.

32.10.12 ISL Correctness Theorem

Theorem. If $\{ [P] \} c \{ [\epsilon : Q] \}$ is provable, then $\{ Q \} \subseteq \llbracket c \rrbracket_{\{\epsilon\}}(P)$.

Proof by induction on the derivation.

Theorem (Footprint). Any valid ISL triple $\{ [\sigma_P] \} c \{ [\epsilon : \sigma_Q] \}$ can be derived (relative completeness). See CAV 2020 paper for details.

32.10.13 SepSIL Definition

SepSIL (Separation SIL) combines SIL (backward under-approximation) with SL (separation logic):

$$\{ \langle P \rangle \} c \{ \langle Q \rangle \}$$

SepSIL extends SIL with the frame rule for separation logic:

$$\frac{\{ \langle \text{frame} \rangle \quad \frac{\langle P \rangle \quad c \quad \langle Q \rangle}{\langle P \star R \rangle} \quad c \quad \langle Q \star R \rangle}{\langle P \star R \rangle}$$

32.10.14 SepSIL Local Axioms

Write: $\langle \langle x \mapsto _ \rangle \quad [x] := y \rangle \quad \langle x \mapsto y \rangle$

Read: $\langle \langle y \mapsto v \quad \text{land} (v = x') \rangle \quad x := [y] \rangle \quad \langle y \mapsto v \quad \text{land} (x = x') \rangle$

Allocation: $\langle \langle \text{emp} \rangle \quad x := \text{alloc}() \rangle \quad \langle x \mapsto _ \rangle$

Dispose: $\langle \langle x \mapsto _ \rangle \quad \text{free}(x) \rangle \quad \langle x \wedge ! \mapsto \rangle$

32.10.15 SepSIL Correctness and Completeness

Theorem (Correctness). If $\langle \langle P \rangle \quad c \quad \langle Q \rangle \rangle$ is provable, then $\langle P \rangle \subseteq_{\text{eq}} \llbracket c \rrbracket^{\{\text{op}\}} Q \rangle$.

Theorem (Completeness). Any valid SepSIL triple $\langle \langle P \rangle \quad c \quad \langle Q \rangle \rangle$ can be derived. See OOPSLA 2025 paper.

32.10.16 ISL vs SepSIL

ISL	SepSIL
Forward under-approximation	Backward under-approximation
$\langle \langle [P] \rangle \quad c \quad [\epsilon : Q] \rangle, \langle Q \rangle \subseteq_{\text{eq}} \llbracket c \rrbracket_{\epsilon} P \rangle$	$\langle \langle P \rangle \quad c \quad \langle Q \rangle \rangle, \langle P \rangle \subseteq_{\text{eq}} \llbracket c \rrbracket^{\{\text{op}\}} Q \rangle$
Finds reachable error states	Finds initial states leading to errors
Stronger guarantees for postconditions	More succinct postconditions
Frame rule $\langle \langle [P \star R] \rangle \quad c \quad [Q \star R] \rangle$	Frame rule $\langle \langle P \star R \rangle \quad c \quad \langle Q \star R \rangle \rangle$

32.11 Lecture 11 — Abstract Interpretation: Basic Ideas

32.11.1 Key Definitions

- **Abstract interpretation:** framework for designing sound static analyses
- **Abstraction:** selecting a property of interest
- **Concretization:** $\gamma(a)$ — set of states satisfying a
- **Best abstraction:** most precise over-approximation

32.11.2 Key Formulas

- **Compositionality:** $\llbracket c_1; c_2 \rrbracket^\# = \llbracket c_2 \rrbracket^\# \circ \llbracket c_1 \rrbracket^\#$
- **Choice:** $\llbracket c_1 + c_2 \rrbracket^\# = \llbracket c_1 \rrbracket^\# \sqcup \llbracket c_2 \rrbracket^\#$

32.11.3 Geometric Abstraction Examples

The concrete domain for 2D points is $\mathbb{R}^2$. Program commands operate on points (x, y) :

- **init(R):** nondeterministically picks a state in region R
- **translate(u, v):** $(x, y) \mapsto (x+u, y+v)$
- **rotate(u, v, θ):** rotate by angle θ around center (u, v)
- **Sequence:** $p_1; p_2$
- **Choice:** $\{p_1\}$ or $\{p_2\}$
- **Iteration:** $\text{ttt}\{p\}$

32.11.4 Concretization Visualizations

Each abstract element a denotes a set $\gamma(a)$ of concrete states:

Signs abstraction: $\llbracket \gamma([x \leq 0, y \geq 0]) \rrbracket = \{(x, y) \mid x \leq 0, y \geq 0\}$

Intervals abstraction: $\llbracket \gamma([1 \leq x \leq 4, 1 \leq y \leq 3]) \rrbracket = \{(x, y) \mid 1 \leq x \leq 4, 1 \leq y \leq 3\}$

Convex Polyhedra abstraction: $\gamma(c_1 x + c_2 y \leq c) = \{(x, y) \mid c_1 x + c_2 y \leq c\}$

32.11.5 Convex Polyhedra Abstraction

Abstract elements are conjunctions of linear inequality constraints: $[c_1 x + c_2 y \leq c]$

- More expressive than intervals (any interval is also a convex polyhedron)
- Relational: captures dependencies between variables (e.g., $\{x \leq y\}$)
- No best abstraction always exists (e.g., for non-convex shapes like discs)
- Used when intervals are insufficiently precise

32.11.6 Best Abstraction

An abstract element a is the **best abstraction** of a set of points S iff:

1. **Over-approximation:** $S \subseteq \gamma(a)$
2. **Most precise:** $(\forall b. S \subseteq \gamma(b) \implies \gamma(a) \subseteq \gamma(b))$

The best abstraction exists only when the abstract domain is closed under meets (Moore family).

32.11.7 Abstract Semantics Compositionality

Analysis function: $\text{analysis}(p, a)$ maps an abstract pre-state to an abstract post-state.

For atomic commands:

- $\text{analysis}(\text{init}(R), a) = \text{best abstraction of } R$
- $\text{analysis}(\text{translate}(u, v), a) = \text{abstraction containing } \gamma(a) \text{ translated by } (u, v)$
- $\text{analysis}(\text{rotate}(u, v, \theta), a) = \text{abstraction containing } \gamma(a) \text{ rotated}$

For compound commands:

- **Sequence:** $\text{analysis}(p_0; p_1, a) = \text{analysis}(p_1, \text{analysis}(p_0, a))$

- **Choice:** $(\text{analysis}(\{p_0\} \text{ or } \{p_1\}, a) = \text{analysis}(p_0, a) \sqcup \text{analysis}(p_1, a))$
- **Iteration:** fixpoint computation: $(R_0 = a), (R_{k+1} = R_k \sqcup \text{analysis}(p, R_k))$ until stabilization

32.11.8 Compositionality Principle

Compute a sound analysis of a program by computing sound abstract semantics of the program's components: $[[c_1;$

$c_2]] = [c_2] \circ [c_1]$

$\sqcup [c_1 + c_2] = [c_1] \sqcup [c_2]$

$\sqcup [c_1]] = [c_2]$

$\text{star}] = \lambda X. [c]$

32.11.9 Common Mistakes

- Thinking abstraction = omission (it's selection)
- Forgetting that soundness is the opposite for bug-finding

32.11.10 Exam Checklist

☐

Understands the abstraction-concretization paradigm

☐

Knows the soundness diagram

☐

Can explain why Rice's Theorem forces approximation

32.12 Lecture 12 — Abstract Interpretation: Formal Foundations

32.12.1 Key Definitions

- **Galois connection:** (α, γ) with $\alpha(c) \sqsubseteq \gamma(a) \text{ iff } c \sqsubseteq \gamma(a)$
- **Complete lattice:** $(L, \sqsubseteq, \bot, \top, \sqcup, \sqcap)$
- **Soundness:** $\alpha \circ [c] \sqsubseteq c$

32.12.2 Key Formulas

- F-06 (Galois connection), F-07 (soundness)
- Sign domain operations (F-17)

32.12.3 Factorial Example: Full Sign Analysis

Program computing $(k!)$ (factorial of initial (n)):

```
(1) m := 1;
(2) while n > 0 do {
(3)     m := m * n;
(4)     n := n - 1
(5=2) }
(6) // end
```

CFG:

```
(1) m := 1  -->  (2=5)
                |
                [n > 0]? --yes--> (3) m := m*n --> (4) n := n-1 -->
(2=5)                |
                [n <= 0]? --yes--> (6) end
```

Sign analysis with domain $(A = \{\emptyset, \mathbb{Z}_{<0}, \mathbb{Z}_{>0}, \mathbb{Z}\})$:

At each program point, abstract state is a pair $((m, n) \in A \times A)$:

Point	Abstract State
(1)	$(m = \mathbb{Z}, n = \mathbb{Z})$
(2=5)	$(m = \mathbb{Z}_{>0}, n = \mathbb{Z})$
(3)	$(m = \mathbb{Z}_{>0}, n = \mathbb{Z}_{>0})$
(4)	$(m = \mathbb{Z}_{>0}, n = \mathbb{Z}_{>0})$
(5=2)	$(m = \mathbb{Z}_{>0}, n = \mathbb{Z})$
(6)	$(m = \mathbb{Z}_{>0}, n = \mathbb{Z}_{\leq 0})$

Abstract transfer functions:

- $(F_2^{\#}(m, n) = (\mathbb{Z}_{>0}, n))$ (assignment $(m := 1)$)
- $(F_4^{\#}(m, n) = (m \times^{\#} n, n))$ with $(\mathbb{Z}_{>0} \times^{\#} \mathbb{Z}_{>0} = \mathbb{Z}_{>0})$

- $(F_5^{\#}(m,n) = (m, n - 1))$ with $(\mathbb{Z}_{>0} - 1 = \mathbb{Z})$
- $(F_7^{\#}(m,n) = (m,n))$ (guard $(n \leq 0)$)
- $(F_3^{\#}(m,n) = (m,n))$ if $(n = \mathbb{Z}_{>0})$, else $((\text{bot}, \text{bot}))$ (guard $(n > 0)$)

32.12.4 Precision Loss Demonstration

For the variant with guard $(n > 1)$:


```
(1) m := 1;
(2) while n > 1 do {
(3)   m := m * n;
(4)   n := n - 1
(5=2) }
(6) // end
```

With input $(\{n > 0\})$:


- At (6): $(n = \mathbb{Z})$ (precision loss — we cannot infer $(n \leq 1)$ because (n) may enter the loop with value 1)
- The sign domain cannot distinguish $(n = 1)$ from $(n > 1)$ after the loop

32.12.5 Domain Refinement Sequence


Basic sign domain $(A_1 = \{\emptyset, \mathbb{Z}_{<0}, \mathbb{Z}_{>0}, \mathbb{Z}\})$:




Refined sign domain (A_2) adding $(\mathbb{Z}_{\geq 0})$ and $(\mathbb{Z}_{\leq 0})$:



Further refined (A_3) adding $(\mathbb{Z}_{=0})$:



CFG for refined domain (A_2) :



With (A_3) , the loop invariant for the factorial program with guard $(n > 0)$ becomes:

- At (6): $(n = \mathbb{Z}_{=0}, m = \mathbb{Z}_{>0})$ (maximum precision!)

32.12.6 Key Algorithms

- Kleene fixpoint iteration (A-01)

32.12.7 Common Mistakes

- Forgetting monotonicity of (α) and (γ)
- Confusing $(\sqsubseteq)$ direction in soundness condition

32.12.8 Exam Checklist



Can define a Galois connection



Can prove soundness of abstract operations



Knows the Sign domain operations tables

32.13 Lecture 13 — Galois Connections (Advanced)

32.13.1 Key Definitions

- **Galois insertion:** $(\alpha \circ \gamma = \text{id})$ (no redundancy)
- **Closure operator:** monotone, extensive, idempotent
- α preserves joins, γ preserves meets

32.13.2 Key Formulas

- F-06, F-10 (insertion)
- $\alpha(\bigsqcup X) = \bigsqcup \alpha(X)$
- $\gamma(\bigsqcap Y) = \bigsqcap \gamma(Y)$

32.13.3 Order Theory Foundations

Partially ordered set (poset): $((P, \sqsubseteq))$ with reflexive, antisymmetric, transitive $\sqsubseteq$.

Join (lub): $(x \sqcup y)$ is the least upper bound of (x) and (y) (if exists). **Meet (glb):** $(x \sqcap y)$ is the greatest lower bound of (x) and (y) (if exists).

Chain: a totally ordered subset $(x_1 \sqsubseteq x_2 \sqsubseteq \dots)$

Complete partial order (CPO): every chain has a lub.

Ascending Chain Condition (ACC): every ascending chain stabilizes: $(x_1 \sqsubseteq x_2 \sqsubseteq \dots \implies \exists k. x_k = x_{k+1} = \dots)$

Finite height: the longest chain has finite length.

32.13.4 Complete Lattices

A **complete lattice** $((L, \sqsubseteq, \bot, \top, \sqcup, \sqcap))$:

- $(\bot)$: least element
- $(\top)$: greatest element
- Every subset $(X \subseteq L)$ has a lub $(\bigsqcup X)$ and glb $(\bigsqcap X)$

Examples of complete lattices:

1. **Powerset lattice** $((\wp(S), \subseteq, \emptyset, S, \cup, \cap))$ — always complete
2. **Interval lattice** extended: $([a, b])$ with $(a \in \mathbb{Z} \cup \{-\infty\})$, $(b \in \mathbb{Z} \cup \{+\infty\})$, $(a \leq b)$, plus $(\bot)$ — complete
3. **Sign domain** $((\{\emptyset, \mathbb{Z}_{<0}, \mathbb{Z}_{=0}, \mathbb{Z}_{>0}, \mathbb{Z}_{\leq 0}, \mathbb{Z}_{\geq 0}, \mathbb{Z}\}, \subseteq)$ — complete (finite lattice)
4. **Divisibility lattice** $((\mathbb{N}^+, \mid, 1, 0, \gcd, \operatorname{lcm}))$ — complete where $(\gcd)$ is meet and (lcm) is join
5. **Linear inequalities** (convex polyhedra) — complete lattice with $(\subseteq)$ as reverse inclusion

Tarski Fixpoint Theorem: For a monotone function $(F: L \rightarrow L)$ on a complete lattice:

- $(\operatorname{lfp}(F) = \bigsqcap \{x \mid F(x) \subseteq x\})$ (least fixpoint)
- $(\operatorname{gfp}(F) = \bigsqcup \{x \mid x \subseteq F(x)\})$ (greatest fixpoint)
- The set of fixpoints is itself a complete lattice

32.13.5 Moore Families and Closure

A **Moore family** is a set $(M \subseteq \wp(\Sigma))$ closed under arbitrary intersections: $(\bigcap_{X \in M} X \in M)$

- Every Moore family forms a complete lattice (with $(\bigsqcap = \cap)$, $(\bigsqcup)$ as the Moore-closure of $(\cup)$)
- The image of a Galois connection's concretization is always a Moore family

A **closure operator** $(\rho: \wp(\Sigma) \rightarrow \wp(\Sigma))$ satisfies:

1. **Monotone:** $(X \subseteq Y \implies \rho(X) \subseteq \rho(Y))$
2. **Extensive:** $(X \subseteq \rho(X))$
3. **Idempotent:** $(\rho(\rho(X)) = \rho(X))$

The set of closed elements $(\{X \mid \rho(X) = X\})$ forms a Moore family.

32.13.6 Chain Conditions Summary

Domain	ACC?	Finite Height?	Widening Needed?
Sign (finite)	Yes	Yes	No
Intervals (extended)	No	No	Yes
Congruence	No (infinite)	No	Yes
Convex Polyhedra	No	No	Yes
Powerset of finite set	Yes	Yes	No
Constant propagation	Yes ($(\mathbb{Z} \cup \{\top\})$)	No (infinite $(\mathbb{Z})$)	No (but uses $(\top)$)

32.13.7 Common Mistakes

- Thinking every GC is a Galois insertion
- Forgetting that $(\gamma \circ \alpha)$ is a closure operator

32.13.8 Exam Checklist

☐

Can prove GC properties (extensivity, reductivity, monotonicity)

☐

Understands when no best abstraction exists

☐

Can distinguish GC from GI

32.14 Lecture 14 — Abstract Numerical Domains

32.14.1 Key Definitions

- **Sign domain:** $\{\emptyset, <0, =0, >0, \leq 0, \geq 0, \mathbb{Z}\}$
- **Interval domain:** $[a, b]$ with $a \leq b$
- **Congruence domain:** $(a \mathbb{Z} + b)$
- **Widening:** ∇ operator for convergence

32.14.2 Key Formulas

- F-17 (Sign operations), F-18 (Interval operations), F-19 (Congruence operations), F-20 (Interval widening)
- BCA: $(F^A = \alpha \circ F \circ \gamma)$ (F-08)

32.14.3 BCA Composition Theorem

For a sequence $(c = c_1; c_2)$, the BCA of the composition is:

$$[\llbracket c_1; c_2 \rrbracket^A = \alpha \circ \llbracket c_2 \rrbracket \circ \gamma \circ \alpha \circ \llbracket c_1 \rrbracket \circ \gamma = (\alpha \circ \llbracket c_2 \rrbracket \circ \gamma) \circ (\alpha \circ \llbracket c_1 \rrbracket \circ \gamma)]$$

BUT this equals $(\llbracket c_2 \rrbracket^A \circ \llbracket c_1 \rrbracket^A)$ only if $(\gamma \circ \alpha = \text{id})$ (i.e., the abstract domain is a Moore family). In general:

$$[\llbracket c_1; c_2 \rrbracket^A \sqsubseteq \llbracket c_2 \rrbracket^A \circ \llbracket c_1 \rrbracket^A]$$

Counterexample: $(c_1: y := x), (c_2: x := \text{random}())$, with sign domain. The BCA of the sequence loses the relation between (x) and (y) that $(\gamma \circ \alpha)$ discards.

32.14.4 Product Domains

Cartesian product: $((A_1 \times A_2, \sqsubseteq_{\times}))$ where:

- $((a_1, a_2) \sqsubseteq_{\times} (b_1, b_2) \text{ iff } a_1 \sqsubseteq_1 b_1 \text{ and } a_2 \sqsubseteq_2 b_2)$
- $(\text{bot}_{\times} = (\text{bot}_1, \text{bot}_2), (\text{top}_{\times} = (\text{top}_1, \text{top}_2))$

- $((a_1, a_2) \sqcup (b_1, b_2) = (a_1 \sqcup b_1, a_2 \sqcup b_2))$
- $(\alpha \times (S) = (\alpha_1(S), \alpha_2(S)))$
- $(\gamma \times (a_1, a_2) = \gamma_1(a_1) \cap \gamma_2(a_2))$

Reduced product: quotient of the product domain by identifying pairs with identical concretizations. Equivalent to taking the Moore family generated by $(\{\gamma_1(a_1) \cap \gamma_2(a_2)\})$.

Example: Reduced product of intervals and parity yields better precision: interval $([2,4])$ with parity (even) gives $([2,4] \cap \text{even} = \{2,4\})$.

32.14.5 Pointwise Lifting

Given a concrete domain $(C \cong \Sigma \text{ to } \wp(\Sigma))$ (functions), lift an abstract domain (A) for $(\wp(\Sigma))$:

$[A \text{ to } A \text{ text{ (functions ordered pointwise): } } f \sqsubseteq g \text{ iff } \forall a. f(a) \sqsubseteq g(a)]$

Smashed pointwise lifting: functions that map $(\bot)$ to $(\bot)$ (strict). Used for abstract transfer functions.

32.14.6 Abstract Stores

For programs with multiple variables, the abstract domain is a **lifted product**:

$[A_{\text{store}} = \prod_{x \in X} A_{\text{val}}]$

Each variable maps independently to an abstract value. This is **non-relational**: no relation between variables is tracked.

Example: With interval domain (A_{val}) , an abstract store $(\sigma^{\#}(x) = [1,5], \sigma^{\#}(y) = [0,10])$ means $(x \in [1,5])$ and $(y \in [0,10])$, independently.

32.14.7 Domain Exercises

Pirahã domain: $(A = \{\bot, a, b, c, \top\})$ with $(a \sqsubseteq b)$, $(a \sqsubseteq c)$, (b) and (c) incomparable.

- Join table: $(b \sqcup c = \top)$, $(b \sqcup a = b)$, $(c \sqcup a = c)$
- Meet table: $(b \sqcap c = a)$, $(b \sqcap a = a)$, $(c \sqcap a = a)$

- α of concrete set S : map to least abstract element containing S
- Exercise: compute BCA for $c = (x := x+1)$ with different $\sigma^{\#(x)}$

Pirandello domain: Non-lattice poset: $(A = \{\bot, p, q, r, \top\})$ with $(p \sqsubseteq r)$, $(q \sqsubseteq r)$, (p) and (q) incomparable, but $(p \sqcap q)$ does not exist.

- Not a lattice because meets are not defined for all pairs
- Exercise: define γ and α such that soundness holds
- Show that fixpoint computation may fail due to missing meets

Constant domain (simple but useful): $(A = \{\bot\} \cup \mathbb{Z} \cup \{\top\})$, ordered by $(x \sqsubseteq y \text{ iff } x = y \text{ or } x = \bot \text{ or } y = \top)$. Used for constant propagation.

32.14.8 Key Algorithms

- Interval widening (A-05)

32.14.9 Common Mistakes

- Thinking intervals have ACC (they don't — need widening!)
- Forgetting that γ is not injective for congruence domain
- Applying widening too aggressively

32.14.10 Exam Checklist

☐

Can define γ and α for any abstract domain

☐

Can compute BCA for a given domain

☐

Knows which domains have ACC and which need widening

☐

Understands product and reduced product domains

32.15 Lecture 15 — Abstract Analysis

32.15.1 Key Definitions

- **Correctness:** $(F^\# \sqsubseteq \alpha \circ F \circ \gamma = F^A)$
- **Completeness:** $(F^\# \circ \alpha = \alpha \circ F)$

32.15.2 Key Formulas

- F-07 (Soundness), F-08 (BCA), F-14 (Fixpoint approximation), F-15 (Abstract iteration), F-16 (Correctness condition)

32.15.3 Formal Abstract Denotational Semantics

Concrete semantics (collecting semantics): $[\llbracket \cdot \rrbracket : \text{wp}(\Sigma) \rightarrow \text{wp}(\Sigma)]$

Abstract semantics: $[\llbracket \cdot \rrbracket^\# : A \rightarrow A]$

Soundness condition (diagram commuting up to approximation): $[\alpha \circ \llbracket \cdot \rrbracket \sqsubseteq \llbracket \cdot \rrbracket^\# \circ \alpha]$

Equivalently: $[\llbracket \cdot \rrbracket \circ \gamma \sqsubseteq \gamma \circ \llbracket \cdot \rrbracket^\#]$

Monotonicity requirement: $(\llbracket \cdot \rrbracket^\#)$ must be monotone on (A) .

32.15.4 Accelerated Abstract Interpreter

The standard Kleene iteration: $[x_0 = \bot, \quad x_{k+1} = x_k \sqcup F^\#(x_k)]$ terminates only if (A) has ACC.

Widening iteration: $[y_0 = \bot, \quad y_{k+1} = y_k \nabla F^\#(y_k)]$

Properties:

1. $(y_k \sqsubseteq F^\#(y_k) \implies y_{k+1} = y_k \nabla F^\#(y_k) \sqsubseteq y_k)$ (ascending)
2. The sequence stabilizes after finitely many steps
3. The limit $(y_\star)$ is a post-fixpoint: $(F^\#(y_\star) \sqsubseteq y_\star)$

Widening + Narrowing: After widening stabilizes, run narrowing to improve precision: $\lfloor z_0 = y_\star, \quad z_{k+1} = z_k \mathbin{\triangleleft} F^\#(z_k) \rfloor$

A **narrowing operator** $\triangleleft$ satisfies:

1. $(z \mathbin{\triangleleft} w \sqsubseteq z)$ (decreasing)
2. If $(F^\#(z) \sqsubseteq z)$ then $(z \mathbin{\triangleleft} F^\#(z) \sqsubseteq \text{lfp}(F^\#))$ (still sound)

32.15.5 Completeness and Correctness Definitions

Correctness (Soundness): $(F^\#)$ is correct iff: $\lfloor F^\# \sqsubseteq \alpha \circ F \circ \gamma = F^\#A \rfloor$

Completeness: $(F^\#)$ is complete iff: $\lfloor F^\# \circ \alpha = \alpha \circ F \rfloor$

Completeness means no precision loss: abstract analysis gives exactly the abstraction of the concrete result.

Fixpoint Approximation Theorem: If $(F^\#)$ is correct (i.e., $(F^\# \sqsubseteq \alpha \circ F \circ \gamma)$), then: $\lfloor \text{lfp}(F^\#) \sqsubseteq \alpha(\text{lfp}(F)) \rfloor$

Proof: $(\alpha(\text{lfp}(F)))$ is a post-fixpoint of $(F^\#)$ because: $\lfloor F^\#(\alpha(\text{lfp}(F))) \sqsubseteq \alpha(F(\gamma(\alpha(\text{lfp}(F))))) \sqsubseteq \alpha(F(\text{lfp}(F))) = \alpha(\text{lfp}(F)) \rfloor$ The least fixpoint of $(F^\#)$ approximates the abstraction of the concrete least fixpoint.

32.15.6 Interval Analysis Example

Program:

```
(1) x := 0;
(2) while x < 100 do {
(3)     x := x + 1
(4=2) }
(5) // end
```

Abstract domain: $(A = \{[a,b] \mid a \leq b, a \in \mathbb{Z} \} \cup \{-\infty\}, b \in \mathbb{Z} \} \cup \{+\infty\} \} \cup \{\text{bot}\})$

Abstract transfer functions:

- $(F_2^{\#}(x) = [0,0])$ (assignment $(x:=0)$)
- $(F_4^{\#}(x) = [x.\text{lo}+1, x.\text{hi}+1])$ (assignment $(x:=x+1)$)
- $(F_3^{\#}(x) = x \sqcap [-\infty, 99])$ (guard $(x < 100)$)
- $(F_5^{\#}(x) = x \sqcap [100, \infty])$ (guard $(x \geq 100)$)

Kleene iteration without widening:

- $(x_0 = \text{bot})$
- $(x_1 = [0,0])$
- $(x_2 = [0,0] \sqcup ([0,0] \sqcup [-\infty, 99] + [1,1]) = [0,1])$
- $(x_3 = [0,2])$
- $(x_4 = [0,3])$
- ...
- Never stabilizes! (interval domain has no ACC)

With widening (∇) :

- $(x_0 = \text{bot})$
- $(x_1 = [0,0])$
- $(x_2 = [0,0] \nabla ([0,1]) = [0, \infty])$ (upper bound jumps to (∞) because $(0 < 1)$)
- $(x_3 = [0, \infty] \nabla ([1, \infty] \sqcup [-\infty, 99] + [1,1]) = [0, \infty] \nabla [1, 100] = [0, \infty])$
- Stabilized at $([0, \infty])$

Narrowing to improve precision:

- $(z_0 = [0, \infty])$
- $(z_1 = [0, \infty] \triangle ([1, \infty] \sqcup [-\infty, 99] + [1,1]) = [0, \infty] \triangle [1, 100])$ With narrowing: $([0, \infty] \triangle [1, 100] \sqsubseteq [0, \infty])$ but \$ \$ Standard narrowing: $([0, \infty] \triangle [1, 100] = [0, 100])$
- $(z_2 = [0, 100] \triangle ([1, 100] \sqcup [-\infty, 99] + [1,1]) = [0, 100] \triangle [1, 100] = [0, 100])$
- Stabilized at $([0, 100])$

Concrete vs Abstract Equivalence:

Two programs are **concretely equivalent** if they produce the same output for the same input.

Two programs are **abstractly equivalent** if they produce the same abstract result.

Important: concrete equivalence does NOT imply abstract equivalence!

Example:

- $\backslash(P_1: x := x + 1; x := x + 1\backslash)$
- $\backslash(P_2: x := x + 2\backslash)$

Concretely equivalent, but with sign domain $\backslash(x := x+2\backslash)$ gives $\backslash(\mathbb{Z}_{>0} \text{ to } \mathbb{Z}_{>0})\backslash$ (via addition table), while $\backslash(x:=x+1; x:=x+1\backslash)$ gives different intermediate results.

32.15.7 Key Algorithms

- Worklist algorithm (A-03)
- Abstract fixpoint with widening (A-02)

32.15.8 Common Mistakes

- Confusing abstract with concrete equivalence
- Forgetting that concrete equivalence $\backslash(\not\Rightarrow)\backslash$ abstract equivalence

32.15.9 Exam Checklist

☐

Can compute abstract fixpoints

☐

Understands the three-stage approach

☐

Knows when to use widening

32.16 Lecture 16 — Local Completeness Logic

32.16.1 Key Definitions

- **Global completeness:** $\backslash(\forall P. \backslash A(\llbracket c \rrbracket P) = \llbracket c \rrbracket^{\#} A(P)\backslash)$

- **Local completeness:** $\mathbb{C}_P(e): A(\llbracket e \rrbracket P) = A(\llbracket e \rrbracket A(P))$
- **LCL triple:** $\vdash_A [P] \ c \ [Q]$ with $(Q \subseteqq \llbracket c \rrbracket P \subseteqq A(Q))$

32.16.2 Key Formulas

- F-09 (Completeness equation), F-11 (LCL triple), F-12 (Local completeness), F-13 (Iteration rule)

32.16.3 Galois Insertion as Closures Formalism

A **Galois insertion** (α, γ) can be represented equivalently by the **closure operator** $(\rho = \gamma \circ \alpha)$:

$[\rho: \wp(\Sigma) \rightarrow \wp(\Sigma)]$

Properties:

1. (ρ) is monotone, extensive, idempotent
2. The image of (ρ) is $\{Y \mid Y = \rho(Y)\}$ — the set of abstract (closed) sets
3. $(A \cong \{\rho(Y) \mid Y \in \wp(\Sigma)\})$ — abstract elements correspond bijectively to closed sets
4. $(\alpha(S) \cong \rho(S))$ — abstraction is closure

Key insight: In a Galois insertion, (γ) is injective, so abstract elements ARE closed sets. This means:

- $(\gamma \circ \alpha = \rho)$ (closure on concrete)
- $(\alpha \circ \gamma = \text{id}_A)$ (no redundancy in the abstract domain)

32.16.4 Completeness Revisited

Completeness equation: $[\llbracket c \rrbracket^\# \circ A = A \circ \llbracket c \rrbracket]$

This means: analyzing the abstracted input gives the same result as abstracting the concrete output.

Local completeness for atomic command (e) : $[\mathbb{C}_P(e): A(\llbracket e \rrbracket P) = A(\llbracket e \rrbracket A(P))]$

The abstraction of executing $\langle e \rangle$ on $\langle P \rangle$ equals the abstraction of executing $\langle e \rangle$ on the abstraction of $\langle P \rangle$.

Only atomic commands can be incomplete. For compound commands:

- Composition: if $\langle \text{mathbb{C}}_R(c_1) \rangle$ and $\langle \text{mathbb{C}}_{\llbracket c_1 \rrbracket P}(c_2) \rangle$ then $\langle \text{mathbb{C}}_P(c_1; c_2) \rangle$
- Choice: if $\langle \text{mathbb{C}}_P(c_1) \rangle$ and $\langle \text{mathbb{C}}_P(c_2) \rangle$ then $\langle \text{mathbb{C}}_P(c_1 + c_2) \rangle$
- Iteration: if $\langle \text{mathbb{C}}_{\{A(P)\}}(c) \rangle$ and $\langle \text{mathbb{C}}_{\{A(P)\}}(c^{\star}) \rangle$ then $\langle \text{mathbb{C}}_P(c^{\star}) \rangle$

32.16.5 BCA Completeness Condition

The **Best Correct Abstraction** $\langle F^A = \alpha \circ F \circ \gamma \rangle$ is the most precise sound abstraction.

$\langle F^{\#} \rangle$ is **complete** iff $\langle F^{\#} = F^A \rangle$. The difference between $\langle F^{\#} \rangle$ and $\langle F^A \rangle$ measures incompleteness.

Incompleteness sources:

1. **Domain choice:** abstract domain cannot express the needed property
2. **Transfer function design:** $\langle F^{\#} \rangle$ is coarser than $\langle F^A \rangle$
3. **Non-relational loss:** product domains lose correlations between variables

32.16.6 Verification Problem Statement

Given:

- Program $\langle c \rangle$
- Specification: pre/post-condition pair $\langle (\text{Spec}, Q) \rangle$
- Abstract domain $\langle A \rangle$ with abstraction function $\langle A = \gamma \circ \alpha \rangle$

Verification: Check whether $\langle c \rangle$ satisfies the specification with respect to $\langle A \rangle$.

Approach using LCL:

1. Prove $\langle \vdash_A [\text{Spec}] c [Q'] \rangle$ for some $\langle Q' \rangle$ such that $\langle Q' \subseteq \llbracket c \rrbracket (\text{Spec}) \subseteq A(Q') \rangle$

2. Check $(Q' \subseteq Q)$ (under-approximation: all real behaviors reach (Q'))
3. Check $(Q \subseteq \llbracket \text{c} \rrbracket(\text{Spec}))$ (over-approximation: the specification is achievable)

Local completeness proof ensures that inferences about incomplete atomic commands are identified and handled.

32.16.7 LCL Inference Rules

Basic rules: $\llbracket \text{assume} \rrbracket \quad \frac{C_P(b?) \quad P \land b \subseteq A(P)}{A \vdash [P] \ b? \ [P \land b]} \quad \llbracket \text{choice} \rrbracket \quad \frac{A \vdash [P] \ c_1 \ [Q_1] \quad A \vdash [P] \ c_2 \ [Q_2]}{A \vdash [P] \ c_1 + c_2 \ [Q_1 \cup Q_2]} \quad \llbracket$

$\llbracket \text{seq} \rrbracket \quad \frac{A \vdash [P] \ c_1 \ [R] \quad A \vdash [R] \ c_2 \ [Q]}{A \vdash [P] \ c_1; c_2 \ [Q]} \quad \llbracket \text{iter} \rrbracket \quad \frac{}{\frac{\forall n. A \vdash [P_n] \ c \ [P_{n+1}]}{A \vdash [P_0] \ c^{\star}} \ \exists k. P_k} \quad \llbracket$

Relax rule: $\llbracket \text{relax} \rrbracket \quad \frac{A \vdash [P] \ c \ [Q] \quad A(P') = A(P)}{A \vdash [P'] \ c \ [Q]} \quad \llbracket$

Consequence (adjusted for LCL): $\llbracket \text{cons} \rrbracket \quad \frac{Q \subseteq \llbracket \text{c} \rrbracket P \subseteq A(Q) \quad A \vdash [P] \ c \ [Q]}{A \vdash [P] \ c \ [Q'] \ \text{if } Q \subseteq Q' \subseteq A(Q)} \quad \llbracket$

32.16.8 Applications and Examples

Example 1: Sign domain analysis of $(x := x + 1)$:

- $(P = \{x = 5\})$ (concrete singleton)
- $(A(P) = \mathbb{Z}_{>0})$
- $(\llbracket C \rrbracket_P(x := x + 1))$ holds because $(A(\llbracket x:=x+1 \rrbracket \{5\}) = \mathbb{Z}_{>0} = A(\llbracket x:=x+1 \rrbracket \mathbb{Z}_{>0}))$
- Since $(P \subseteq A(P)) \ (\{5\} \subseteq \mathbb{Z}_{>0})$, the assume rule gives $(\vdash_A [\{x=5\}] \ x:=x+1 \ [\{x=6\}])$

Example 2: Interval domain analysis of $(x := x \bmod 2)$:

- $(P = [0,100])$
- $(A(P) = [0,100])$
- $(\llbracket C \rrbracket_P(x := x \bmod 2))$ fails because $(\llbracket x:=x \bmod 2 \rrbracket [0,100] = [0,1])$ but $(A(\llbracket x:=x \bmod 2 \rrbracket [0,100]) = [0,100])$

$2\rrbracket[0,100] = [0,1] \neq [0,1] \cap [0,100] = [0,1]$ — actually this IS locally complete since $A([0,1]) = [0,1]$

- Counterexample: $(P = [1,3])$, $A([1,3]) = [1,3]$, $(\llbracket x := x \bmod 2 \rrbracket[1,3] = \{0,1\})$, $A(\{0,1\}) = [0,1]$, $(\llbracket x := x \bmod 2 \rrbracket[1,3] \cap [1,3] = \{1\})$, $A(\{1\}) = [1,1] \neq [0,1]$
- Therefore $(\mathbb{C}_{[1,3]}(x := x \bmod 2))$ fails — the interval domain loses parity information

32.16.9 Key Algorithms

None new (uses previous fixpoint algorithms).

32.16.10 Common Mistakes

- Thinking LCL is just HL or just IL
- Forgetting the Relax rule condition $(A(P') = A(P))$
- Not understanding that incomplete atomic commands are the only source of incompleteness

32.16.11 Exam Checklist

☐

Can derive LCL triples

☐

Understands local vs global completeness

☐

Knows the verification theorem

☐

Understands sources of incompleteness

32.17 Lectures 17–22 — Control Flow Analysis (FUN)

32.17.1 Key Definitions

- **CFA**: statically approximates which functions may be called at each call site
- **0-CFA**: monovariant (one abstract value per program point)
- **(k)-CFA**: context-sensitive with call strings of length (k)

- **CPA (Cartesian Product Algorithm):** context-sensitive with argument tuples as contexts
- **Acceptability relation:** $((\hat{C}, \hat{\rho}) \models e)$
- **Syntax-directed CFA** ((models_s)): analyses function bodies at definition time
- **Constraint-based CFA** ($(C^*[\![e]\!])$): generates finite set of (conditional) constraints
- **Flow logic:** constraint-based formulation of CFA
- **Moore family:** set of acceptable analyses closed under $(\sqcap)$ (greatest lower bound)
- **Least solution:** most precise CFA exists (intersection of all acceptable analyses)
- **Constraint graph:** nodes $((C(\ell), r(x)))$ + edges (direct and conditional)

32.17.2 Key Formulas

- Constraint generation rules (A-04)
- Order on analyses: $((\hat{C}_1, \hat{\rho}_1) \sqsubseteq (\hat{C}_2, \hat{\rho}_2))$ iff $(\forall \ell. \hat{C}_1(\ell) \subseteq \hat{C}_2(\ell))$ and $(\forall x. \hat{\rho}_1(x) \subseteq \hat{\rho}_2(x))$
- Conditional constraint form: $\{t\} \subseteq \text{rhs}' \Rightarrow \text{lhs} \subseteq \text{rhs}$

32.17.3 Key Algorithms

- 0-CFA constraint generation (A-04)
- Syntax-directed CFA (A-06)
- (k) -CFA call string (A-07)
- Constraint solving via least fixed point

32.17.4 Common Mistakes

- Confusing $(\subseteq)$ direction in constraints (result flows forward, arguments flow into $(\hat{\rho})$)
- Forgetting that 0-CFA loses precision by merging call contexts
- Thinking (k) -CFA is always worth the cost (exponential blowup)
- Not handling the conditional constraint correctly

32.17.5 Exam Checklist



Can label expressions for CFA



Can generate constraints for 0-CFA



Can explain the difference between 0-CFA and (k) -CFA



Understands soundness vs precision in CFA



Can extend CFA with DFA for data properties



Can prove existence of least solution via Moore family

32.18 Lectures 23–24 — CFA for π -Calculus

32.18.1 Key Definitions

- **Name mobility:** channels can be transmitted as values (unlike CCS)
- **Abstract environment** $(\rho: \text{Var} \rightarrow \text{Const})$: maps variables to possible constants
- **Abstract channel environment** $(\kappa: \text{Var} \rightarrow \text{Const})$: maps channels to possible communicated values
- **Acceptable guess:** $(\rho, \kappa) \models_P P$ satisfying all validation clauses
- **Oblivious analysis:** matching, restriction, and replication are treated optimistically (over-approximate)
- **Subject reduction:** if $(\rho, \kappa) \models_P P$ and $(P \rightarrow Q)$, then $(\rho, \kappa) \models_P Q$
- **Canonical names:** $(\lfloor n \rfloor)$ is the equivalence class of (n) (disciplined α -renaming)
- **Polyadic π -calculus:** tuples of values, arity checking, ψ for arity mismatches

32.18.2 Key Formulas

- Output clause: $(\forall n \in \rho(u): \rho(v) \subseteq \kappa(n))$
- Input clause: $(\forall n \in \rho(u): \kappa(n) \subseteq \rho(x))$
- Substitution lemma: $(\rho, \kappa) \models_P \lfloor P[m/x] \rfloor$ provided $(\lfloor m \rfloor \subseteq \rho(x))$
- Prefix clause: $(\rho, \kappa) \models_P \pi.P$ iff $(\rho, \kappa) \models_A \pi$ and $(\rho, \kappa) \models_P P$

- Parallel clause: $((\rho, \kappa) \models_P P_1 \mid P_2 \text{ iff } (\rho, \kappa) \models_P P_1 \text{ and } (\rho, \kappa) \models_P P_2)$
- Match* (refined): $(\rho(x) \cap \rho(y) \neq \emptyset \Rightarrow (\rho, \kappa) \models_P P)$
- Polyadic output: $(\forall n \in \rho(u): \rho(v_1) \times \dots \times \rho(v_k) \subseteq \kappa(n))$
- Polyadic input: $(\forall n \in \rho(u): \kappa(n) \subseteq \rho(x_1) \times \dots \times \rho(x_k))$

32.18.3 Key Algorithms

- Validation clause checking (systematic verification of $((\rho, \kappa) \models_P P)$)
- Constraint generation and solving for (π) -calculus
- Least solution via Moore family intersection (same principle as CFA for FUN)

32.18.4 Common Mistakes

- Forgetting $(\rho(n) = \{n\})$ for constants (extension rule)
- Confusing (ρ) (variable bindings) with (κ) (channel contents)
- Thinking restriction creates fresh names — analysis treats all names as global
- Using the basic match clause when a refined version would give better precision
- Forgetting that 0-CFA for (π) -calculus is context-insensitive (like 0-CFA for FUN)
- Not distinguishing between (π) -calculus with and without arity in polyadic version

32.18.5 Exam Checklist

☐

Can write (π) -calculus processes with actions and prefixes

☐

Can define (ρ) and (κ) for a given process

☐

Can verify $((\rho, \kappa) \models_P P)$ by checking all clauses

☐

Understands why restriction is treated obliviously

☐

Can apply the refined match clause

☐

Understands subject reduction and why it implies soundness

☐

Can explain the role of canonical names

☐

Knows that a least solution always exists (Moore family)

☐

Can describe the polyadic extension with κ and ψ

☐

Understands the limitations of 0-CFA for π -calculus

33 Cross-Reference Index

33.1 Formulas by Lecture

Formula	Lecture	Domain
F-01	02	Semantics
F-02	02	wlp
F-03	02	wpp
F-04	03	HL
F-05	05	IL
F-06	12,13	Galois
F-07	12	Soundness
F-08	14	BCA
F-09	16	Completeness
F-10	13	GI
F-11	16	LCL
F-12	16	LCL
F-13	16	LCL
F-14	15	Fixpoint
F-15	15	Iteration

Formula	Lecture	Domain
F-16	15	Correctness
F-17	12	Sign
F-18	14	Interval
F-19	14	Congruence
F-20	14,15	Widening

33.2 Exercises by Topic

Topic	Exercises
HL / IL / NC / SIL axioms	E-01
Galois Connections	E-02, E-05
Abstract Domains	E-02
BCA / Completeness	E-02
0-CFA / 1-CFA / Constraints	E-03, E-06
CFA + DFA Integration	E-06
Separation Logic (ISL)	E-04

33.3 Algorithms by Topic

Topic	Algorithms
Fixpoint computation	A-01, A-02
Abstract interpretation	A-03
CFA	A-04, A-06, A-07
Interval analysis	A-05

34 Validation Report

34.1 LaTeX Validation

- All formulas use `\(...\)` for inline and `\[...\]` for display mathematics
- Set notation uses `\{` and `\}` throughout
- Semantic brackets use `\llbracket` and `\rrbracket`

- Lattice symbols use `\sqsubseteq`, `\sqcup`, `\sqcap`, `\bot`, `\top`
- Quantifiers use `\forall`, `\exists`
- No LaTeX environment blocks that might break
- No fenced `````latex` blocks
- λ -calculus notation uses standard operators: `\overline{u}`, `\angle v \angle`, `\langle u(x) \rangle`, `\Sigma`, `\mid`, `\langle \nu n \rangle P`, `!P`, `\models_P`, `\models_A`
- Polyadic extension notation uses `\vec{v}`, `\vec{x}`, `\psi`
- All `\kappa` and `\rho` references use consistent `\wp(\text{Const})` notation

34.2 Content Completeness



All 23+ lectures covered



Definitions extracted



Formulas extracted with full metadata (20 formulas)



Theorems and lemmas included



Inference rules for all logics (HL, IL, NC, SIL, SL, ISL, LCL)



Algorithms extracted with structured format (7 algorithms)



Exercises collected with solutions (6 exercises)



Cross-references built



Lecture summaries with exam checklists (per lecture)



Exam preparation guide



Final cheat sheet



Formula handbook (enhanced with meaning, variables, intuition, usage)



Validation report

34.3 Known Gaps

- Exercise E-04 (ISL), E-05 (Galois), E-06 (CFA+DFA) have **generated** solutions (not official) — clearly marked
- Exercise PDFs may contain more exercises beyond text extraction
- NC and SIL full proof systems not detailed beyond guard axioms
- Polyadic λ -calculus CFA with λ (arity mismatch) is sketched but not covered in full depth
- No formal soundness proof for λ -calculus CFA is included (subject reduction theorem stated without proof)