



Assignment 3

Autonomous Learning

June 15, 2020

Upload your video solution and your code to the Team folder on NextCloud until Sunday, the 28th of June until 23:55 pm.

IMPORTANT: Use for **ALL** Tasks a *screen_size* of 16

Task 1 - DDQN

- A. Train your DQN agent with a double deep Q network.
- B. Visualise the training as usual.
- C. The trained DDQN agent shall be started by running the Python file `RunDDQN.py`. The agent shall use the trained weights without further training.
- D. The training of the DDQN agent shall be implemented in `TrainDDQN.py`. Hereby, the agent shall initialise a new network.

Task 2 - Dueling DQN

- A. Train your DQN agent with a dueling deep Q network.
- B. Do this by using a Lambda layer.
- C. Visualise the training as usual.
- D. The trained DDQN agent shall be started by running the Python file `RunDuelDQN.py`. The agent shall use the trained weights without further training.
- E. The training of the DDQN agent shall be implemented in `TrainDuelDQN.py`. Hereby, the agent shall initialise a new network.

Task 3 - CNN Dueling DDQN mit Prioritized experience Replay

- A. Extend your agent with a convolutional neural network consisting of the following layers:
 - (a) 1 Input Layer
 - (b) 1 Hidden Convolution Layer with 16 filters of the size 5x5 and Stride 1 + ReLu
 - (c) 1 Hidden Convolution Layer with 32 filters of the size 3x3 and Stride 1 + ReLu
 - (d) 1 hidden Layer (64 nodes + ReLu)

- (e) 1 Output Layer (8 nodes + Linear)
- B. As input layer we strongly suggest to use an *unity_density*-Layer
 - You can find all layers provided by pyc2 at:
timesteps[0].observation.feature_screen
 - Make sure that your input has the correct format: shape=(x, y, channels)
- C. The agent shall use double Q learning.
- D. Extend your network to a dueling DQN.
- E. Use prioritized experience replay.
 - (a) For this you can use the existing PER by baselines:
<https://github.com/openai/baselines>
 - (b) To install baselines on Windows, follow this guide:
<https://arzt-samuel.github.io/en/blogs/2018/Gym-and-Baselines-on-Windows.html>
- F. Visualise the training as usual.
- G. The trained CNN agent shall be started by running the Python file `RunCNN.py`. The agent shall use the trained weights without further training.
- H. The training of the CNN agent shall be implemented in `TrainCNN.py`. Hereby, the agent shall initialise a new network.