// LAST SEEN: 2025-09-18

General Information

Hostnames	14-178-166-181.**fibertel.com.ar**
Domains	fibertel.com.ar
Country	**Argentina**
City	**Lomas de Zamora**
Organization	**Telecom Argentina S.A.**
ISP	**Telecom Argentina S.A.**
ASN	**AS7303**

Open **Ports**

443 37777

// **443** / TCP -1394619911 | 2025-09-18T19:06:03.290022

Dahua DHI-HCVR4104HS-S3

WEB SERVICE

```
HTTP/1.1 200 OK
CONNECTION: close
Date: Thu, 18 Sep 2025 16:17:23 GMT
Last-Modified: Mon, 06 Jun 2016 07:21:42 GMT
Etag: "1465197702:35a8"
CONTENT-LENGTH: 13736
P3P: CP=CAO PSA OUR
CONTENT-TYPE: text/html


Dahua DHI-HCVR4104HS-S3:
  Web Version: 3.2.7.65490
  Plugin:
    Version: 3.1.0.330019
    Mac Version: 1.0.0.1
    ClassID: CB6C958B-1612-4764-98DF-2757EB82E1E3
    Name: WebActiveX.Plugin.1
  Channel Names:
    CAM 1
    CAM 2
    CAM 3
    CAM 4
```

SSL Certificate

```
Certificate:
    Data:
        Version: 3 (0x2)
        Serial Number:
            39:30:30:32:61:39:38:30:30:33:63:31
        Signature Algorithm: sha1WithRSAEncryption
        Issuer: CN=Product Root CA, C=CN, ST=ZheJiang, L=HangZhou, O=DahuaTech
        Validity
            Not Before: Jun 18 09:16:23 2013 GMT
```

https://www.shodan.io/host/181.166.178.14#37777

WHOIS Domain Lookup

Look up registration details, contacts, and nameservers for any domain name

Enter a domain name... Search

fibertel.com.ar

WHOIS Information

IP Address: 200.45.2.140

Whois RDAP DNS Records Uptime Diagnostics Hide Data Refresh Data

The domain **fibertel.com.ar** is registered. You can still try to buy it here.

Registrar Information

Registrar	WHOIS Server
nicar	whois.nic.ar

Important Dates

Created
6/30/2016

Nameservers

The device I found on Shodan is called a Dahua DHI-HCVR4104HS-S3. It is a DVR used for security cameras. I found it using the domain fibertel.com.ar, and its IP address is 200.45.2.140. These devices can have problems, especially if the software is old. Some have bugs that let hackers get in without logging in or run bad code. Hackers might watch the video, change settings, or put malware on it. Many people don’t change the default username and password,

which makes it easier to hack. Also, these devices are often online without a firewall. The web interface on port 37777 can also be risky.

// TAGS: eol-product honeypot proxy

// LAST SEEN: 2025-09-18

General Information

Hostnames	hn.kd.ny.**adsl**
Domains	adsl
Country	**China**
City	**Shanghai**
Organization	**China Unicom Henan province network**
ISP	**CHINA UNICOM China169 Backbone**
ASN	**AS4837**

Vulnerabilities All ports Latest

Note: the device may not be impacted by all of these issues. The vulnerabilities are implied based on the software and version.

2025 (2)

CVE-2025-32728 4.3 In sshd in OpenSSH before 10.0, the DisableForwarding directive does not adhere to the documentation stating that it disables X11 and agent forwarding.

CVE-2025-26465 6.8 A vulnerability was found in OpenSSH when the VerifyHostKeyDNS option is enabled. A machine-in-the-middle attack can be performed by a malicious machine impersonating a legit server. This issue occurs due to how OpenSSH mishandles error codes in specific conditions when verifying the host key. For an attack to be considered successful, the attacker needs to manage to exhaust the client's memory resource first, turning the attack complexity high.

2024 (1)

Open **Ports**

11	13	15	17	19	23	25	26	37	43	49	53	65
70	79	90	94	102	104	110	111	113	119	143	175	179
180	195	211	221	234	264	311	389	427	444	450	488	502
503	515	541	548	554	556	636	666	685	689	771	785	789
809	873	886	947	990	992	993	995	998	1023	1025	1026	1029
1063	1080	1099	1110	1153	1177	1188	1195	1200	1234	1250	1292	1337
1370	1377	1387	1414	1433	1443	1447	1450	1453	1454	1515	1521	1588
1599	1604	1650	1723	1800	1801	1883	1926	1954	1957	1959	1962	1964
1968	1976	1977	1983	1990	2000	2002	2003	2008	2020	2022	2030	2053
2056	2059	2078	2081	2083	2087	2095	2109	2111	2121	2122	2154	2181
2196	2222	2225	2232	2250	2332	2345	2353	2404	2455	2562	2569	2572
2628	2650	2761	2762	3001	3006	3014	3050	3055	3062	3064	3067	3069
3072	3077	3082	3084	3088	3101	3109	3112	3115	3118	3120	3122	3124
3140	3147	3153	3155	3165	3169	3172	3176	3178	3180	3181	3186	3195
3260	3268	3269	3299	3301	3305	3306	3310	3389	3401	3408	3409	3500

The device I found is in Shanghai, China and is part of the China Unicom network. It is likely a computer or server that allows remote access using SSH. One of the problems with this device is a security issue called CVE-2025-26465. This issue happens when a setting called VerifyHostKeyDNS is turned on in OpenSSH. Hackers can trick the device into thinking they are a safe server. This lets them watch or steal what someone is doing on the connection. The problem is worse if the device runs out of memory. The issue has a danger score of 6.8 out of 10, which means it is a medium risk. To stay safe the system should turn off that setting and install updates. This shows why keeping devices secure and updated is important.

NIST

NVD MENU

Information Technology Laboratory

NATIONAL VULNERABILITY DATABASE

NIST NATIONAL VULNERABILITY DATABASE NVD

VULNERABILITIES

CVE-2025-26465 Detail

MODIFIED

This CVE record has been updated after NVD enrichment efforts were completed. Enrichment data supplied by the NVD may require amendment due to these changes.

Description

A vulnerability was found in OpenSSH when the VerifyHostKeyDNS option is enabled. A machine-in-the-middle attack can be performed by a malicious machine impersonating a legit server. This issue occurs due to how OpenSSH mishandles error codes in specific conditions when verifying the host key. For an attack to be considered successful, the attacker needs to manage to exhaust the client's memory resource first, turning the attack complexity high.

QUICK INFO

CVE Dictionary Entry:
CVE-2025-26465
NVD Published Date:
02/18/2025
NVD Last Modified:
06/02/2025
Source:
Red Hat, Inc.

Metrics

CVSS Version 4.0 | CVSS Version 3.x | CVSS Version 2.0

NVD enrichment efforts reference publicly available information to associate vector strings. CVSS information contributed by other sources is also displayed.

CVSS 3.x Severity and Vector Strings:

CNA: Red Hat, Inc. **Base Score:** 6.8 MEDIUM **Vector:** CVSS:3.1/AV:N/AC:H/PR:N/UI:R/S:U/C:H/I:H/A:N

I picked CVE-2025-26465. This is a problem found in OpenSSH when the VerifyHostKeyDNS setting is turned on. It lets a hacker pretend to be a real server and trick the computer. This is called a "man-in-the-middle" attack. The attacker can steal or change information by getting between two systems talking to each other. This attack is in the MITRE ATT&CK website as Adversary-in-the-Middle (T1557). A way to detect it is to watch network traffic (DS0029), and one way to stop it is by using strong security settings and encryption (M1041).

MITRE | ATT&CK

Matrices Tactics Techniques Defenses CTI Resources Benefactors Blog Se

TECHNIQUES

- Enterprise
  - Reconnaissance
  - Resource Development
  - Initial Access
  - Execution
  - Persistence
  - Privilege Escalation
  - Defense Evasion
  - Credential Access
    - Adversary-in-the-Middle
      - LLMNR/NBT-NS Poisoning and SMB Relay
      - ARP Cache Poisoning

Detection

ID	Data Source	Data Component	Detects
DS0015	Application Log	Application Log Content	Monitor application logs for changes to settings and other events associated with network protocols and other services commonly abused for AiTM.[17]
DS0029	Network Traffic	Network Traffic Content	Monitor network traffic for anomalies associated with known AiTM behavior.
		Network Traffic Flow	Monitor for network traffic originating from unknown/unexpected hardware devices. Local network traffic metadata (such as source MAC addressing) as well as usage of network management protocols such as DHCP may be helpful in identifying hardware.
DS0019	Service	Service Creation	Monitor for newly constructed services/daemons through Windows event logs for event IDs 4697 and 7045. Data and events should not be viewed in isolation, but as part of a chain of behavior that could lead to other activities, such as remote logins or process creation events.
DS0024	Windows Registry	Windows Registry Key Modification	Monitor HKLM\Software\Policies\Microsoft\Windows NT\DNSClient for changes to the "EnableMulticast" DWORD value. A value of "0" indicates LLMNR is disabled.

MITRE | ATT&CK

Matrices Tactics Techniques Defenses CTI Resources Benefactors Blog Search

TECHNIQUES

- Enterprise
  - Reconnaissance
  - Resource Development
  - Initial Access
  - Execution
  - Persistence
  - Privilege Escalation
  - Defense Evasion
  - Credential Access
    - Adversary-in-the-Middle
      - LLMNR/NBT-NS Poisoning and SMB Relay
      - ARP Cache Poisoning
      - DHCP Spoofing
      - Evil Twin
  - Brute Force
  - Credentials from Password Stores

Mitigations

ID	Mitigation	Description
M1042	Disable or Remove Feature or Program	Disable legacy network protocols that may be used to intercept network traffic if applicable, especially those that are not needed within an environment.
M1041	Encrypt Sensitive Information	Ensure that all wired and/or wireless traffic is encrypted appropriately. Use best practices for authentication protocols, such as Kerberos, and ensure web traffic that may contain credentials is protected by SSL/TLS.
M1037	Filter Network Traffic	Use network appliances and host-based security software to block network traffic that is not necessary within the environment, such as legacy protocols that may be leveraged for AiTM conditions.
M1035	Limit Access to Resource Over Network	Limit access to network infrastructure and resources that can be used to reshape traffic or otherwise produce AiTM conditions.
M1031	Network Intrusion Prevention	Network intrusion detection and prevention systems that can identify traffic patterns indicative of AiTM activity can be used to mitigate activity at the network level.
M1030	Network Segmentation	Network segmentation can be used to isolate infrastructure components that do not require broad network access. This may mitigate, or at least alleviate, the scope of AiTM activity.
M1017	User Training	Train users to be suspicious about certificate errors. Adversaries may use their own certificates in an attempt to intercept HTTPS traffic. Certificate errors may arise when the application's certificate does not match the one expected by the host.

Mitigation Method:
ID: M1042
Name: Disable or Remove Feature or Program
Summary: Turn off old or unneeded network features that might let attackers see or mess with network traffic.

Detection Method:
ID: DS0029
Name: Network Traffic
Summary: Watch network traffic closely. Look for strange behavior, like unknown devices or weird traffic patterns that might mean an attacker is in the middle of the connection.