

Working-Tree Changes — Client

Folder: TTPR/INTERNSHIP PROJECT/capston-3/Client **Baseline:** 61e32dd add frontend environment example **Scope:** everything currently uncommitted — 64 files staged, plus unstaged edits to `src/App.css` and `src/pages/Confirmation.jsx`, plus two untracked additions (`src/styles/`, `src/components/Calendar.md`).

Authorship note. This document was produced by reading `git diff` in this folder. The code changes described here were written by you and your teammates — I did not author them. Every claim below was checked against the actual diff; the **Issues** section is a code-reading review, and none of those items were reproduced at runtime. Treat them as leads to confirm, not confirmed defects.

Contents

1. [Summary](#)
 2. [Calendar.jsx](#)
 3. [The CSS split](#)
 4. [Save flow rewrite](#)
 5. [App.jsx and routing](#)
 6. [Layout and Navbar](#)
 7. [Login.jsx](#)
 8. [HomePage.jsx](#)
 9. [Trips.jsx](#)
 10. [Assets](#)
 11. [Issues found](#)
 12. [Suggested commit split](#)
-

1. Summary

Area	File(s)	Change
Calendar	<code>src/components/Calendar.jsx</code>	one line: container height 700px → 850px
Calendar docs	<code>src/components/Calendar.md</code>	new, untracked — full component documentation
Styling	<code>src/App.css</code> → <code>src/styles/*.css</code>	3,029-line stylesheet split into 8 files behind <code>@import</code>
Save flow	<code>Confirmation.jsx</code> , <code>client.js</code> , <code>Login.jsx</code>	per-item saving moved into a shared <code>saveItinerary()</code> ; unsaved trips now survive a login detour
Routing	<code>src/App.jsx</code>	Prettier reformat, <code>/protected</code> route added
Chrome	<code>Layout.jsx</code> , <code>Navbar.jsx</code>	<code>isLoading</code> removed; username display removed
Hero images	<code>HomePage.jsx</code>	five hand-listed imports replaced with <code>import.meta.glob</code>
Robustness	<code>Trips.jsx</code>	optional chaining on <code>date_range</code>
Assets	<code>src/assets/**</code>	57 image files added, 61 MB

Net source change: 672 insertions, 351 deletions across the staged set, before the unstaged CSS split.

2. src/components/Calendar.jsx

Despite the M badge, the entire change is **one line**:

```
ref={calendarElement}
style={{
  width: "100%",
-   height: "700px",
+   height: "850px",
}}
```

Why it is needed. Toast UI Calendar measures its parent element to lay out the month grid. A % or auto height collapses the grid to nothing, so the container must carry an explicit pixel height. 850px gives each month cell enough room that a day holding three activities does not overflow its box.

Nothing else in the file changed — no logic, no handlers, no API calls.

src/components/Calendar.md (new, untracked)

A full write-up of the component as it stands (678 lines), covering:

- **The two-ref bridge.** Toast UI is an imperative library that owns its own DOM, so `calendarElement` holds the node and `calendarInstance` holds the live object. Refs, not state — the instance must survive re-renders without causing them.
- **updateMonthTitle.** The library does not tell React the visible month changed, so the label is mirrored out by hand in four places.
- **The raw field.** Each calendar event carries the untouched database row in Toast UI's passthrough slot, so a click opens the detail modal with the real record — no second fetch, no lookup table.
- **category: "time"** is Toast UI's event type, unrelated to the app's own category field. Same word, two meanings.
- **end is start + 1 hour**, hardcoded — the Activity model has no duration column, so this is an invented default, not data.
- **Reload strategy:** `clear()` then `createEvents()` after every mutation. Full rebuild rather than surgical patching, so the calendar cannot drift out of sync with the database.
- Seven observations from reading the code, the highest-value being that all four fetches hardcode `http://localhost:8080` instead of using `src/api/client.js`.

That file is untracked. It needs `git add` to be committed.

3. The CSS split — App.css → src/styles/

The largest change by line count, and it is **unstaged**.

`src/App.css` went from 3,029 lines to 8 lines:

```
@import "./styles/01-home.css";
@import "./styles/02-theme.css";
@import "./styles/03-trip-details.css";
@import "./styles/04-trip-pages.css";
@import "./styles/05-itinerary.css";
@import "./styles/06-auth.css";
@import "./styles/07-activities.css";
@import "./styles/08-responsive.css";
```

File	Lines
01-home.css	382
02-theme.css	253
03-trip-details.css	348
04-trip-pages.css	354
05-itinerary.css	425
06-auth.css	299
07-activities.css	375
08-responsive.css	73
Total	2,509

Verification — nothing was lost

The 3,029 → 2,509 line difference looks alarming, so I checked it rather than assuming:

Check	Old App.css	New styles/	Verdict
Distinct class names	437	437	identical
@media blocks	29	29	identical
@keyframes	10	10	identical
Declarations	1,175	1,193	slightly more
Blank lines	585	388	−197

Every class name present in the old file is present in the new files. The line drop is blank lines and comments; the declaration count going *up* by 18 is one-line rules being split across lines by the formatter.

Conclusion: the split is faithful. No rule was dropped.

One caveat to be aware of: @import inside a stylesheet is resolved by the bundler at build time here, so there is no extra network request in production. Order still matters — 08-responsive.css must stay last, or its media queries lose to later rules of equal specificity.

4. Save flow rewrite

Three files changed together. This is the most behavioural change in the set.

src/api/client.js — new saveItinerary()

```
export async function saveItinerary(itinerary) {
  if (itinerary.budget < 0) {
    throw new Error("Enter budget as minimum 0");
  }

  const savedTrip = await createTrip({
    destination: itinerary.destination,
    date_range: [itinerary.startDate, itinerary.endDate],
    budget: itinerary.budget,
  });

  const tripId = savedTrip.id;

  for (const activity of itinerary.activities || []) { /* createActivity */ }
```

```
    for (const item of itinerary.checklist || []) { /* createChecklistItem */ }  
  }
```

The trip → activities → checklist sequence used to live inside Confirmation. Extracting it means **two** callers can now run it: the confirmation page, and the login page after a redirect.

src/pages/Confirmation.jsx

Staged:

- imports saveItinerary from client.js and getMe from auth.js
- calls await getMe() first, with the message "Checking authentication...", so a logged-out user is caught before any trip is created
- on success: setSaved(true), await saveItinerary(itinerary), then navigate("/trips", { replace: true })
- on failure: if error.message === "Authentication required", stash the itinerary in sessionStorage under pendingItinerary and go to /login

Unstaged: the original inline createTrip / createActivity / createChecklistItem block is **commented out** rather than deleted — 30 lines of dead code now sitting above the saveItinerary() call that replaced it.

src/pages/Login.jsx

After a successful login it checks for pendingItinerary:

```
const pendingItinerary = sessionStorage.getItem("pendingItinerary");  
  
if (pendingItinerary) {  
  const itinerary = JSON.parse(pendingItinerary);  
  const savedTrip = await saveItinerary(itinerary);  
  sessionStorage.removeItem("pendingItinerary");  
  navigate("/trips", { replace: true });  
  return;  
}
```

The result: generate a trip while logged out, hit Save, log in — and the trip saves itself and drops you on the trips page. The work is no longer lost. That is a real improvement over the previous behaviour.

Also changed: redirectTo default from '/' to '/trips'.

5. src/App.jsx

Mostly a **Prettier reformat** — single quotes to double quotes throughout, and the isLoading expression collapsed onto one line. No logic change there.

Two real changes:

1. ProtectedPage is now imported.
2. A /protected route was added, wrapped in ProtectedRoute.

See [Issues](#) — both the new route and the /trips route need a look.

6. Layout.jsx and Navbar.jsx

Layout.jsx

- No longer accepts or forwards `isLoading`
- A **second** `authError` block was added above `<main>`, while the original one inside `<main>` remains
- Explanatory comments removed
- Trailing newline removed (\ No newline at end of file)

Navbar.jsx

- The `isLoading ? null : guard` was removed; the function still *declares* `isLoading` in its parameters but no longer uses it
- The `username` expression was **deleted**, leaving an empty element:

```
<span className='px-2 text-sm'>  
- {user.username || user.name || user.email}  
</span>
```

- A commented-out `/protected NavLink` block was added

7. src/pages/Login.jsx

Covered in [section 4](#). Additionally, five `console.log` calls were added during debugging and are still present, including one that logs the full login response and one that logs the entire itinerary object.

8. src/pages/HomePage.jsx

The hero rotation changed from five hand-written imports to a glob:

```
const HERO_IMAGES = Object.entries(  
  import.meta.glob("../assets/travel-auth-backgrounds/desktop-webp/*.webp", {  
    eager: true,          // load immediately  
    query: "?url",       // give me the browser-ready URL  
    import: "default",   // just the default export  
  }  
)  
  .sort(([pathA], [pathB]) => pathA.localeCompare(pathB))  
  .map([, url]) => url);
```

Why this is better: dropping a `.webp` into that folder adds it to the rotation with no code change. The `.sort()` matters — `import.meta.glob` does not guarantee key order, so sorting by filename is what makes the numbered prefixes (`01-`, `02-`...) actually control the sequence.

It reads the **WebP** folder, not the PNG one — the right choice: the WebP files are 50–150 KB each against 2 MB PNGs.

The rest of the file's diff is Prettier reformatting plus a rewritten comment on the budget field.

9. src/pages/Trips.jsx

```
- Start Date: {trip.date_Range[0].value}  
+ Start Date: {trip.date_Range[0]?.value}
```

Same for the end date. A trip whose date_Range is missing or short now renders blank instead of crashing the page with "cannot read property of undefined". Small change, real robustness win.

10. Assets — 57 files, 61 MB

Folder	Size
travel-auth-backgrounds/	46 MB
japan/	4.3 MB
greece/	2.1 MB
cruise/	2.0 MB

The backgrounds folder holds each of 10 photos in **four** variants: desktop PNG, desktop WebP, mobile PNG, mobile WebP. Only the desktop WebP set is referenced by `HomePage.jsx`.

The PNGs are 1.6–2.6 MB each; their WebP equivalents are 30–175 KB — a 95% saving for no visible difference. See [Issues](#).

11. Issues found

From reading the diffs. **None were reproduced at runtime** — confirm each before acting.

1. The navbar no longer shows the username — *high*

`Navbar.jsx` renders an empty `<span className='px-2 text-sm'></span>` for a logged-in user. The name, and its `user.name` / `user.email` fallbacks for Auth0 users, were deleted. The result is a blank gap before "Log out".

```
<span className='px-2 text-sm'>
+ {user.username || user.name || user.email}
</span>
```

2. "Log in / Sign up" will flash on every refresh — *high*

`Layout.jsx` stopped passing `isLoading`, and `Navbar.jsx` dropped the `isLoading ? null : guard` while still declaring the parameter. On a refresh, `user` is `null` for the moment it takes `/auth/me` to answer, so a logged-in user sees the logged-out controls appear and then swap. That guard existed specifically to prevent this.

3. `/trips` no longer receives `user` — *high*

```
<Route path="/trips" element={
  <ProtectedRoute user={user} isLoading={isLoading}>
    <Trips />      {/* ← no user prop */}
  </ProtectedRoute>
} />
```

`Trips` reads `user?.username || user?.name || user?.email || "traveler"`, so the greeting now always reads **"Welcome back, traveler!"**.

Meanwhile the new `/protected` route renders `<Trips user={user} />` — the opposite of what was probably intended. `ProtectedPage` is imported but never used, which is likely a copy-paste that got reversed.

4. The budget guard weakened — *high*

```
if (itinerary.budget < 0) throw new Error("Enter budget as minimum 0");
```

This permits 0, "", null and undefined. The old check was `!budget || budget <= 0`, added specifically because an empty budget reached the database and came back as a generic 500. This reopens that path.

```
const budget = Number(itinerary.budget);  
if (!budget || budget <= 0) throw new Error("Enter a budget above 0");
```

Note also that `saveItinerary` passes `itinerary.budget` **unconverted**, where the old code passed `Number(budget)`. The form supplies a string.

5. Auth detection now matches on message text — *medium*

```
if (error.message === "Authentication required") { ... }
```

`request()` attaches `error.status`, which is exactly what this check should use. Matching the server's wording means any rephrasing of that message silently breaks the redirect, and the user loses their itinerary.

```
if (error.status === 401) { ... }
```

6. The "saved" popup fires before the save — *medium*

```
setSaved(true);  
setMessage("Saving Trip...");  
await saveItinerary(itinerary);
```

`setSaved(true)` runs first, so the confirmation appears while the requests are still in flight — and if `saveItinerary` throws, the user has already been told it worked. Move `setSaved(true)` after the `await`.

Also, the `navigate("/trips")` immediately afterwards means the popup is only visible for an instant, so the two mechanisms are working against each other.

7. Debug logging left in — *medium*

Five `console.log` calls in `Login.jsx` and two in `Confirmation.jsx`, including the full login response and the entire itinerary object.

8. 46 MB of unused PNGs — *medium*

Only `desktop-webp/` is referenced. The PNG folders and `mobile-webp/` are dead weight in the repository, and git stores every version of a binary forever — this cannot be undone by deleting them later without rewriting history. Worth deciding **before** this is pushed.

9. Commented-out code in `Confirmation.jsx` — *low*

30 lines of the old save block, superseded by `saveItinerary()`. Git history is the place for old code.

10. `authError` renders twice in `Layout.jsx` — *low*

A new block above `<main>` plus the existing one inside it. The same error text will appear twice.

11. `Layout.jsx` has no trailing newline — *low*

\ No newline at end of file. Cosmetic, but it makes the next diff of that file noisier than it needs to be.

12. Suggested commit split

Everything is currently one 64-file lump. Splitting it makes review possible and makes any of it revertable on its own:

1. **refactor(css): split App.css into styles/** — App.css + src/styles/ (verified faithful; needs git add src/styles/)
2. **feat(save): save a pending itinerary after login** — client.js, Confirmation.jsx, Login.jsx
3. **feat(home): rotate hero images from the assets folder** — HomePage.jsx
 - whichever asset folders survive the decision in issue 8
4. **fix(trips): guard missing date_range** — Trips.jsx
5. **style(calendar): raise the calendar to 850px** + Calendar.md
6. **style: apply prettier** — the App.jsx quote changes, kept separate so they do not hide real edits
7. **Layout / Navbar** — hold this one until issues 1–3 are resolved

Before committing

- ☐ Restore the username in Navbar.jsx (issue 1)
- ☐ Restore isLoading through Layout → Navbar (issue 2)
- ☐ Pass user to <Trips /> on /trips, and fix /protected (issue 3)
- ☐ Restore the budget guard and the Number() conversion (issue 4)
- ☐ Switch back to error.status === 401 (issue 5)
- ☐ Move setSaved(true) after the await (issue 6)
- ☐ Remove the console.log calls (issue 7)
- ☐ Decide on the 46 MB of PNGs **before** pushing (issue 8)
- ☐ Delete the commented-out block (issue 9)
- ☐ Remove the duplicate authError (issue 10)
- ☐ git add src/styles/ src/components/Calendar.md — both are untracked and would otherwise be left behind