

Some pointers on pointers

Salvatore Aiola

Yale University

Analysis Tutorial
ALICE Week
CERN, July 28th, 2017

Outline


- 1 Introduction
 - Disclaimer
 - Pointers and Memory Management
- 2 Why a raw pointer is hard to love
- 3 Smart Pointers
- 4 Conclusions

Introduction

Disclaimer

- Some parts will be too boring for some people, some other parts will be too advanced for others
 - On the other hand, most people might find some parts interesting
- Not a comprehensive lecture on memory management in C++
 - Not even close!
 - Rather some suggestions to write efficient, maintainable and robust code
- Not an IT expert!
 - Experience from writing analysis code in ALICE + some limited readings

What is a Pointer?



A pointer is an object whose value “points to” another value stored somewhere else in memory

- Very powerful tool
- Great power = great responsibility!
- Extensive use of pointers in ROOT/AliRoot/AliPhysics

Using a Pointer

```
/* Defining a pointer */  
int* a; // declares a pointer that can point to an integer value  
//DANGER: the pointer points to a random memory portion!  
  
int* b = nullptr; // OK, pointer is initialized to a null memory address  
  
int* c = new int; // allocate memory for an integer value in the heap  
//and assign its memory address to this pointer  
  
int** d = &a; // this pointer points to a pointer to an integer value  
  
MyObject* e = new MyObject(); // allocate memory for MyObject  
// and assign its memory address to this pointer  
  
/* Using a pointer */  
int f = *c; // dereferencing a pointer and assigning the pointed  
// value to another integer variable  
  
e->DoSomething(); // dereferencing a pointer and calling  
// the method DoSomething() of the instance of MyObject  
// pointed by e
```

Why a raw pointer is hard to love

Array or single value?

- A pointer can point to a single value or to an array, however its declaration does not indicate it
- Different syntax to destroy (= deallocate, free) the pointed object for arrays and single objects

```
void UserExec()
{
    MyTrack *track = new MyTrack(0,0,0,0);
    double *trackPts = new double[100];
    double *returnValue = AnalyzeTracks(trackPts);

    // here use the pointers

    delete track;
    delete[] trackPts;
    delete returnValue; // or should I use delete[] ??
}
```


Memory leaks and double deletes

- Each memory allocation should match a corresponding deallocation
- Difficult to keep track of all memory allocations in a large project
- Ownership of the pointed memory is ambiguous: multiple deletes of the same object may occur

```
void UserExec()  
{  
    AliVTracks* tracks = FilterTracks();  
  
    AnalyzeTracks(tracks);  
  
    delete [] tracks; // should I actually delete it??  
    // or was it already deleted by AnalyzeTracks?  
}
```

Smart Pointers

Conclusions

Final remarks

- When the extra-flexibility of a pointer is not needed, do not use it
- Alternative example: arguments by reference (not covered here)
- Avoid raw pointers whenever possible!
- Smart pointers (`unique_ptr` and `shared_ptr`) should cover most use cases and provide a much more robust and safe memory management