

Practice Problem Set 1

Problem 1:

Using the pseudo-code of *Insertion sort* from class, determine the best-case number of swaps and the worst-case number of swaps when Insertion sort runs on an input array of length n . Repeat for the best-case and worst-case number of comparisons.

Problem 2:

Show that the best-case runtime of insertion sort is $T(n) = an + b$ for constants a and b , and use this result to deduce that the best-case runtime is $O(n)$. Do some research to determine the *average-case* runtime of insertion sort.

Problem 3:

Let A be an array of n numbers. Write the pseudo-code for an algorithm that reverses the elements of A between indices i and j . Call the procedure `Reverse(A, i, j)`. Let $T(n)$ be the worst-case runtime of your algorithm when run on A between indices 1 and n . Find an expression for $T(n)$ and show that this is $O(n)$.

Problem 4:

A sorting algorithm that is similar to Insertion Sort, is **Selection sort**. If you have not seen this algorithm before, I suggest the video

https://www.youtube.com/watch?v=g-PGLbMth_g

Let $T(n)$ be the worst-case runtime of Selection sort. Show that $T(n)$ is of the form $an^2 + bn + c$, and that the runtime is $O(n^2)$. Repeat for the best-case runtime. How does the runtime of Selection sort differ from that of Insertion sort?

Problem 5:

Suppose an array A is indexed from 1 to n . Assuming the RAM model, describe an algorithm that will determine which element in A occurs the *most often*. There are many possible algorithms here. Try to find one that is *fast* (but may use lots of space). Next, try to find one that may be slower but uses *less* space. For each algorithm, describe the worst-case runtime in big-oh notation, and describe how much space is used in big-Oh notation.

Problem 6:

You may have already come across another simple sorting algorithm called *Bubble-sort*. Instead of describing the algorithm here, you are asked to do a bit of online research. One great place to start is here:

<https://www.youtube.com/watch?v=lyZQPjUT5B4>

Write the basic pseudo-code for Bubble sort (the simple version, not the optimal version), using comparisons and swaps. Determine the worst-case number of swaps and the worst-case number of comparisons. Repeat for the best-case. Justify that the worst-case runtime is $O(n^2)$ and the best-case runtime is $O(n)$.

Problem 7:

An optimal version of Bubble sort is such that the inner for loop iterates over fewer and fewer elements. Write the pseudo-code for a version of Bubble-sort that performs fewer comparisons in the worst-case. Nevertheless, justify why this new version is still $O(n^2)$ in the worst-case.

Problem 8:

If you are a python programmer, you are likely familiar with the **list** data structure. The operation `list.remove(x)` removes from the list the *first* item whose value is x . Describe how this operation is implemented, and justify its runtime of $O(n)$.

Repeat for the `list.append(x)` operation.

Problem 9:

For each of the following statements, determine if they are true or false, and justify your answer:

- Suppose algorithm A runs in time $O(n^2)$. Does it also run in time $O(n^3)$?
- Suppose algorithm A runs in time $O(n^2)$. Does it also run in time $O(n)$?
- Suppose algorithm A runs in time $O(n^2)$. Does it also run in time $\Theta(n^2)$?
- Suppose algorithm A runs in time $\Omega(n^2)$. Does it also run in time $\Omega(n)$?
- Suppose algorithm A runs in time $\Omega(n^2)$. Does it also run in time $\Omega(n^3)$?

Problem 10:

Let $f(n) = n^2 + \log n + n$.

Determine which of the below are valid for the function $f(n)$, (there may be more than one).

$$O(n^2), O(n^3), O(n), \Theta(n), \Theta(n^2), \Omega(n^2), \Omega(\log n), \Omega(n)$$

Problem 11:

Determine the big-Theta notation of the following functions. Prove your result.

- $f(n) = \log(n^2) + \log^2(n) + \sqrt{n}$
- $f(n) = n^2 \log(n) + n(\log n)^2$
- $f(n) = n^3 + n^2 \log(n)$
- $f(n) = \sum_{k=1}^n (2k + 1)$

Problem 12: Determine the big-Theta notation of the following functions. Prove your result.

- $f(n) = \log_2 n + \log_3(n)$
- $f(n) = (2^n + n \cdot 2^n)(n^2 + 3^n)$
- $f(n) = \log(n^{0.2}) + \log(n^2)$
- $f(n) = n^{0.2} + \log(n^8)$
- $f(n) = \sum_{k=1}^n kn$

Problem 13:

- Prove that $f(n) = n^2 + n$ is $\Omega(n^2)$ and $\Omega(n)$. Which bound is tighter?
- Prove that $f(n) = n^2 - 3n$ is $O(n^3)$ and $O(2^n)$ and $O(n^2)$. Which bound is tighter?

Problem 14:

Order the following functions by their asymptotic growth (in increasing order):

$$n^n, \quad n \cdot 3^n, \quad 2^n \cdot n^2, \quad 4^n + n, \quad \frac{n^2 + 1}{n + 6}, \quad 6n!, \quad n^2 \log n, \quad n(\log n)^2, \quad \sqrt{n^2 + \log n}, \quad (\log n^3)$$