Mycroft Mark 2 rev 6

SJ201—Raspberry Pi 4 Daughterboard



SJ-201-R6		
Mycroft AI		
Sheet: /		
File: SJ-201-R6.sch		
Title: SJ-201-R6		
Size: A	Date: 2020-12-30	**Rev: Rev6 - v1**
KiCad E.D.A. kicad (5.1.8)-1		Id: 1/8

Power

Typical Application Circuit



Figure4. XL4501 Typical Application Circuit



Reverse Polarity Protection



Reference Diagram

VIN=8V ~ 16V, VOUT=5V/5A

FB Resistor
VOUT=1.25*(1+R2/R1)



3.3v LDO Regulator



LDO to power on PCB stuff,
instead of using Raspberry 3.3v
Enables USB operation

3.3v LDO High Power for Coral TPU



1.8v LDO Regulator



1.0v Buck for XMOS



VFB = 0.6V
VO = 0.6 x (1 + 30/47) = 0.98V

Power Test Points



SJ-201-R6		
Mycroft AI		
Sheet: /Power/		
File: Power.sch		
Title: Power		
Size: A	Date: 2020-12-30	**Rev: Rev5 – v1**
KiCad E.D.A. kicad (5.1.8)-1		Id: 2/8

Audio Amplifier



SJ−201−R6
Mycroft AI
Sheet: /AudioAmp/
File: AudioAmp.sch

Title: Audio Amplifier

Size: A	Date: 2020−12−30	**Rev: Rev5 − v1**
KiCad E.D.A. kicad (5.1.8)−1		Id: 3/8

Monitor & Touch



SJ-201-R6
Mycroft AI
Sheet: /Monitor/
File: monitor.sch

Title: Monitor & Touchscreen

Size: A	Date: 2020-12-30	**Rev: Rev5 – v1**
KiCad E.D.A. kicad (5.1.8)-1		Id: 4/8

Raspberry Pi













SJ-201-R6	
Mycroft AI	
Sheet: /RaspberryPi/	
File: RaspberryPi.sch	
Title: Raspberry Pi	
Size: A	Date: 2020-12-30
KiCad E.D.A. kicad (5.1.8)-1	Id: 5/8

Rev: Rev5 - v1

XMOS Audio Processor



SJ-201-R6		
Mycroft AI		
Sheet: /xmos/		
File: xmos.sch		
Title: XMOS		
Size: A	Date: 2020-12-30	**Rev: Rev5 - v1**
KiCad E.D.A. kicad (5.1.8)-1		Id: 6/8

Coral Processor



SJ-201-R6	
Mycroft AI	
Sheet: /Coral Processor/	
File: Coral.sch	
Title: Coral TPU	
Size: A	Date: 2020-12-30
KiCad E.D.A. kicad (5.1.8)-1	Id: 7/8

Rev: Rev5 – v1

MCU – ATtiny 1614









SJ-201-R6
Mycroft AI
Sheet: /MCU/
File: MCU.sch

Title: MCU & Fan

Size: A	Date: 2020-12-30	**Rev: Rev5 – v1**
KiCad E.D.A. kicad (5.1.8)-1		Id: 8/8