

Contest Duration: 2018-01-14(Sun) 20:00 (<http://www.timeanddate.com/worldclock/fixedtime.html?iso=20180114T2100&p1=248>) ~ 2018-01-14(Sun) 22:10 (<http://www.timeanddate.com/worldclock/fixedtime.html?iso=20180114T2310&p1=248>) (local time) (130 minutes)

iso=20180114T2100&p1=248) ~ 2018-01-14(Sun) 22:10 (<http://www.timeanddate.com/worldclock/fixedtime.html?iso=20180114T2310&p1=248>) (local time) (130 minutes)

[Back to Home \(/home\)](#)

[🏠 Top \(/contests/agc020\)](#)

[☰ Tasks \(/contests/agc020/tasks\)](#)

[❓ Clarifications \(/contests/agc020/clarifications\)](#)

[☰ Results ▾](#)

[⏴ Standings \(/contests/agc020/standings\)](#)

[⏴ Virtual Standings \(/contests/agc020/standings/virtual\)](#)

[📖 Editorial \(/contests/agc020/editorial\)](#)



E - Encoding Subsets

[Editorial \(/contests/agc020/tasks/agc020_e/editorial\)](#)

[🇯🇵 / 🇬🇧](#)

Time Limit: 5 sec / Memory Limit: 512 MB

Score : 1400 points

Problem Statement

Consider the following set of rules for encoding strings consisting of '0' and '1':

- Strings '0' and '1' can be encoded as '0' and '1', respectively.
- If strings A and B can be encoded as P and Q , respectively, then string AB can be encoded as PQ .
- If string A can be encoded as P and $K \geq 2$ is a positive integer, then string $AA \dots A$ (A repeated K times) can be encoded as $(P \times K)$.

For example, string '001001001', among other possibilities, can be encoded as '001001001', '00(1(0x2)x2)1' and '(001x3)'.

Let's call string A a subset of string B if:

- A and B are equal in length and consist of '0' and '1';
- for all indices i such that $A_i = '1'$, it's also true that $B_i = '1'$.

You are given string S consisting of '0' and '1'. Find the total number of distinct encodings of all subsets of S , modulo 998244353.

Constraints

- $1 \leq |S| \leq 100$
- S consists of '0' and '1'.

2020-09-11 (Fri)
08:52:32 +08:00

Input

Input is given from Standard Input in the following format:

S

Output

Print the total number of distinct encodings of all subsets of S modulo 998244353.

Sample Input 1

Copy

011

Copy

Sample Output 1

Copy

9

Copy

There are four subsets of S :

- '011' can be encoded as '011' and '0(1x2)';
- '010' can be encoded as '010';
- '001' can be encoded as '001' and '(0x2)1';
- '000' can be encoded as '000', '0(0x2)', '(0x2)0' and '(0x3)'.

Thus, the total number of encodings of all subsets of S is $2 + 1 + 2 + 4 = 9$.

Sample Input 2

Copy

0000

Copy

Sample Output 2

Copy

10

Copy

This time S has only one subset, but it can be encoded in 10 different ways.

Sample Input 3

Copy

2020-09-11 (Fri)
08:52:32 +08:00

```
101110
```

Copy

Sample Output 3

Copy

```
156
```

Copy

Sample Input 4

Copy

```
001110111010110001100000100111
```

Copy

Sample Output 4

Copy

```
363383189
```

Copy

Don't forget to take the result modulo 998244353.

#telegram)

url=https%3A%2F%2Fatcoder.jp%2Fcontests%2Fagc020%2Ftasks%2Fagc020_e%3Flang%3Den&title=E%20-

[Rule \(/contests/agc020/rules\)](/contests/agc020/rules) [Glossary \(/contests/agc020/glossary\)](/contests/agc020/glossary)

[Terms of service \(/tos\)](/tos) [Privacy Policy \(/privacy\)](/privacy) [Information Protection Policy \(/personal\)](/personal) [Company \(/company\)](/company)

[FAQ \(/faq\)](/faq) [Contact \(/contact\)](/contact)

Copyright Since 2012 ©AtCoder Inc. (<http://atcoder.co.jp>) All rights reserved.