

Search Properties API Contract

Endpoint

POST /api/properties/search

Request Body

```
{
  "property_village": "Madhurawada",
  "property_district": "Visakhapatnam",
  "property_mandal": "Visakhapatnam Urban",
  "property_panchayati": "Madhurawada",

  "listing_type": "Buy",

  "property_group": [
    "Residential",
    "Agricultural"
  ],

  "property_type": [
    "Residential Flats",
    "Villas"
  ],

  "property_price_min": 10000000,
  "property_price_max": 20000000,

  "property_area_min": 200,
  "property_area_max": 420,
  "property_area_unit": "sq.yds",

  "property_bedrooms": 1,
  "property_bathrooms": 2,
  "property_balconies": 3,
  "property_parking": 0,

  "property_age": "1-5 Years",

  "property_furnishing": "Semi-Furnished",

  "property_total_floors": 6,
```

```
"property_floor_number": 2,

"property_facing": [
  "East",
  "North"
],

"property_approval_authority": [
  "GVMC",
  "RERA"
],

"property_amenities": [
  "Lift",
  "Gym"
],

"sort_by": "newest",

"page": 1,
"limit": 6
}
```

Notes

Empty values

Frontend omits:

- empty strings
- null values
- empty arrays

Only active filters are sent.

Multi-select fields

These fields are arrays:

- property_group
- property_type
- property_facing
- property_approval_authority
- property_amenities

Backend may use `$in` queries.

Price Range

```
{
  "property_price_min": 10000000,
  "property_price_max": 20000000
}
```

Area Range

```
{
  "property_area_min": 200,
  "property_area_max": 420,
  "property_area_unit": "sq.yds"
}
```

Sorting

Possible values:

- newest
 - price-asc
 - price-desc
 - area-asc
-

Pagination

Always present:

```
{
  "page": 1,
  "limit": 6
}
```

Data Source

Search is performed against the same property collection used by Post Property submissions.

Field names follow snake_case.