

# Sorelo App Summary

One-page repo-based brief | Generated on 2026-03-10

## What It Is

Sorelo is a Next.js app for building an explainable map of a person with Concepts, Links, the Inspector, and deterministic Scenarios.

It combines a canvas-first interface with workspace tenancy so users can model, inspect, and test reaction paths.

## Who It Is For

- Primary persona: people who need a structured, explainable model of a person instead of fragmented observations.
- Specific profession or industry persona: Not found in repo.

## What It Does

- Supports Google OAuth sign-in via Supabase plus workspace-based access control.
- Creates and manages workspaces and multiple maps per workspace.
- Provides map canvas editing: create concepts, connect links, and drag concept positions.
- Shows Inspector details for selected concepts and links, including editable metadata.
- Runs deterministic scenario simulations and persists step-by-step run results.
- Shows recent scenario runs and map-level activity context inside the product shell.
- Exposes protected internal learning APIs for suggestions, fragments, and resolutions.

## How It Works (Architecture)

- Components: Next.js App Router pages ('app/'), 'ProductShell'/'MarketingShell', 'MapWorkspace', 'GraphCanvasRuntime', 'InspectorPanel', and 'ScenarioPanel'.
- Services: route handlers in 'app/api/maps/\*' and 'app/api/internal/learning/\*' with Zod validation and access checks.
- Domain layer: 'src/features/\*/commands.ts' and 'queries.ts' modules implement map, concept, link, scenario, workspace, and learning behavior.
- Data/auth: Supabase SSR auth plus session sync into Postgres via Drizzle ORM; schema and migrations live in 'src/shared/db/schema.ts' and 'supabase/migrations/'.
- Data flow: browser requests viewport snapshots from '/api/maps/:mapId/graph'; mutation routes update entities and graph revision; scenario runs use a rule-based engine and write 'scenario\_runs' + 'scenario\_run\_steps'.

## How To Run (Minimal)

- Install dependencies: 'npm install' (or 'npm.cmd install' on restricted PowerShell setups).
- Create local env file from '.env.example' to '.env.local' and fill required keys.
- Start the dev server with 'npm run dev'.
- Open 'http://localhost:3000' and sign in with Google.
- First-time local database bootstrap/migration command: Not found in repo (scripts list 'db:generate' and 'db:check').

Evidence source: README.md, docs/product/\*, app/\*, src/features/\*, src/shared/\*, supabase/migrations/\*.