

Contents

Next.js	1
Folder Structure	1
Root	1
User Page	1
Advantages	2
Structure	2
Layout	2
Page	3
Loading	4

Next.js

Folder Structure

To create a page, add a page file inside the app directory and default export a React component. Folders are used to define the route segments that map to URL segments. Files (like page and layout) are used to create UI that is shown for a segment.

Root

- lib and ui have **no framework meaning** for Next (no page.tsx)

path	features
./app	root dir for react
./app/page.tsx	starting point (/ route)
./app/layout.tsx	root layout
./app/not-found.tsx	404 page
./app/lib/	type definitions, REST server client code, server side code
./app/ui/	React components for the user interface
./app/public/	static resources, here: images (png files)
./app/user/	/user page
./app/global-error.tsx	error handling

User Page

path	features
./app/user/layout.tsx	user page layout

path	features
<code>./app/user/loading.tsx</code>	fallback UI (loading screen) upon navigation
<code>./app/user/not-found.tsx</code>	custom 404 page for user
<code>./app/user/error.tsx</code>	error handling
<code>./app/user/[id]</code>	dynamic subpages

Advantages

- SEO improvements through **SSR** (Server Side Rendering) and **SSG** (Static Site Generation)
- Automatic **Code Splitting** (Chunking)
- Simplified *file-based* routing
- Easy full-stack development through API routes
- **Scoped CSS** and **SASS** support
- **TypeScript** support
- Image optimization
- **HMR** (Hot Module Replacement)
- Page pre-fetch
- Minimal configuration on Vercel

Structure

Each route is reflected in the directories and files under “app” and must have at least a “page.tsx” file which defines a Page component creating the content of the (sub)page.

Layout

`layout.tsx` defines an optional **Layout component** creating the layout of page. The result of the Page component is passed to the Layout component through a `children` prop.

- **Partial rendering:** when the user navigates to a certain path, only the Page components are rerendered, not the layouts
- A layout is UI that is shared between multiple pages.
- On navigation, layouts preserve state, remain interactive, and do not rerender
- You can define a layout by default exporting a React component from a layout file.
- The component should accept a `children` prop which can be a page or another layout
- Nesting layouts is possible

```
import '@/app/global.css'; // : import global css file to top level component
```

```

export default function RootLayout({
  children,
}: {
  children: React.ReactNode;
}) {
  return (
    <html lang="en">
      <body className={`${inter.className} antialiased`}>{children}</body>
    </html>
    // The layout above is called a root layout because it's defined at the root of the
    // app directory.
    // The root layout is required and must contain html and body tags.
  );
}

```

Page

- A nested route is a route composed of multiple URL segments.
- For example, the `/details/[id]/edit` route is composed of four segments:
 - `/` - the root segment
 - `/details` - the details segment
 - `/[id]` - the dynamic id segment (slug)
 - `/edit` - the edit segment

```

// 'use server';

interface EditListProps {
  params: {
    id: string;
  };
}

// async component
export default async function EditDetails({ params }: { params: { id: string } }) {
  console.log('invoice id = ' + params.id);
  const id = params.id;
  const friend = JSON.parse(await getFriend(Number(id)));
  console.log('friend = ' + JSON.stringify(friend));

  return (
    <></>
  );
};

// alternative props with interface
function EditDetailsWithInterface({ params }: EditListProps) {

```

```
};
```

Loading

Loading generates code to display while component Page is not finished generating output.

This approach is called **streaming**. We display a **skeleton** of the final layout while data is being loaded. See files `loading.tsx` and `ui/skeletons.ts`

`loading.tsx` defines component Loading:

```
import DashboardSkeleton from "../../ui/skeletons";

export default function Loading() {
  // simple version:
  //return <div>Loading...</div>;

  // more complex version: show dashboard skeleton
  return <DashboardSkeleton />;
}
```

- Has to be in the same folder as the `page.tsx` it is masking