Verification-Gated Model Cascading for Local Coding Inference

Neeraj Pragnya Krishna Vasagiri | Independent Researcher
29 August 2026 | Public GitHub preprint; not peer reviewed

Abstract. Large language model routing is often evaluated as a cost-quality trade-off, but model failures need not be nested: a smaller model can sometimes produce a correct program when a larger model does not. This paper studies whether a deterministic verifier can exploit that complementarity through a local verification-gated cascade. We audit one completed experiment on 542 paired EvalPlus tasks (164 HumanEval+ and 378 MBPP+) using same-family Qwen2.5-Coder FAST, BALANCED, and BEST tiers. Adaptive produced 331 verified Plus successes (61.07%), compared with 297 (54.80%) for Strong-only and 220 (40.59%) for Small-only. Its 34 additional successes over Strong-only came from FAST (22) and BALANCED (12), with no additional BEST successes. The model-size-weighted total-token cost proxy was 899,462.8 versus 893,000.0 (+0.72%), while raw total tokens (+121.04%), CPU time (+14.11%), and wall time (+65.40%) were higher. Successes per weighted total-token proxy were 10.65% higher for Adaptive, but successes per CPU second were slightly lower. These proxies are not FLOPs, measured compute, energy, API usage, or dollar cost. The evidence supports task-level complementarity and verification-gated escalation at this operating point, not a universal efficiency advantage or a strong claim about predictive initial routing.

Keywords: code generation, model cascading, LLM routing, verification, EvalPlus, local inference, reproducibility

1. Introduction

Selecting one language model for every request is simple, but it can waste capacity when tasks vary in difficulty. A smaller model may be adequate for some tasks, while a larger model may be needed for others. More subtly, the sets of tasks solved by two models need not be nested. A routing system can benefit from this complementarity only if it has an authoritative way to decide when an answer is acceptable.

> *Can verification-gated model cascading exploit task-level complementarity among differently sized language models to increase verified coding-task completion efficiently relative to always using the strongest available model?*

The evaluated system is a local benchmark subsystem of Adaptive Workflow. It starts with a local tier, generates one candidate, and runs deterministic EvalPlus tests. A failed verification permits one escalation to the next tier. The historical run did not transfer a failed program or verifier feedback into the next prompt; later tiers received the original frozen task prompt. Thus, the contribution studied here is a verification-gated model cascade, not failure-feedback reasoning or collaborative error correction.

The primary historical result is task-weighted Plus correctness on the same 542 tasks: Adaptive passes 331 tasks (61.07%), Strong-only passes 297 (54.80%), and Small-only passes 220 (40.59%). Adaptive has 34 successes not present in Strong-only. Twenty-two came from FAST and twelve from BALANCED; BEST produced no additional Adaptive-only successes. This is evidence that correctness sets are not nested by model size, not evidence that a small model is stronger on average.

Research questions

RQ1: Can a verification-gated multi-model cascade achieve more verified coding-task successes than always using the strongest available model? RQ2: To what extent are improvements explained by task-level complementarity? RQ3: What additional expenditure occurs under raw tokens, model-size-weighted proxies, CPU, memory, and wall time? RQ4: How much evidence does the completed experiment provide for adaptive initial routing beyond a simpler verification-gated cascade?

2. Related Work

2.1 Model routing and cascades

FrugalGPT describes prompt adaptation, model approximation, and LLM cascades, including settings with improved accuracy at the same reported API cost [4]. RouteLLM learns a preference-data router to select between stronger and weaker models [5]. Early-abstention cascades use correlated errors to avoid some expensive calls [12]. These studies motivate query-dependent model choice, but differ from this work's local same-family models and deterministic code verifier.

Faster Cascades via Speculative Decoding interleaves models through speculative execution [7]; speculative decoding uses a small model to propose tokens and a larger model to verify them [11]. Adaptive Workflow is sequential: each program is accepted or rejected by tests, and no speculative token verification occurs.

2.2 Adaptive inference and test-time computation

Confident Adaptive Language Modeling allocates computation within a model using confidence-calibrated early exits [6]. Snell et al. show that prompt difficulty can make adaptive test-time allocation more effective than uniform scaling [8]. We follow the methodological lesson of separating measured hardware quantities from approximate accounting: parameter-weighted token values are proxies, while CPU, RAM, and time are physical observations.

2.3 Verification for code generation

HumanEval introduced function-level code synthesis tasks scored by executing generated Python [1]. MBPP provides short programming problems for entry-level synthesis [2]. EvalPlus augments original tests to expose test insufficiency [3]. Self-Debugging uses execution feedback to revise programs [9]; our historical cascade deliberately did not pass failure context to later tiers. Self-consistency samples multiple paths [10]; our one deterministic completion per tier does not estimate pass@k.

3. Adaptive Workflow

3.1 System overview

For a task x, the system selects an initial tier, obtains a completion y, and invokes a deterministic verifier V(x,y). If V passes, y is retained. If it fails, the fixed historical policy permits one attempt at the next tier: FAST -> BALANCED -> BEST. Infrastructure failures are recorded and are not retried into a pass.




Figure 1. Historical verification-gated cascade. A pass terminates the cascade; a failure permits escalation. Later tiers received the original frozen task prompt, not the failed program or verifier feedback.

3.2 Tiers, routing, and verification

The manifest maps FAST, BALANCED, and BEST to qwen2.5-coder:1.5b, qwen2.5-coder:3b, and qwen2.5-coder:7b. Frozen parameter values are 1.5, 3.1, and 7.6 billion, all Q4_K_M. Initial Adaptive routing selected FAST for 531 of 542 tasks, BEST for 11, and BALANCED for zero. The audit's chronological online replay has no mismatches; an empty-state replay differs on eight history-dependent HumanEval decisions.

EvalPlus ran in the pinned image ganler/evalplus:v0.3.1 at digest sha256:26b118098bef281fe8dfe999bf05f1d5b45374b4e6c00161ec0f30592aef4740 with network disabled, a read-only root, dropped capabilities, an unprivileged user, task-scoped temporary storage, a PID cap, a 120-second timeout, and one verifier worker.

4. Experimental Method

4.1 Tasks and conditions

The primary set contains 164 HumanEval+ and 378 MBPP+ tasks. HumanEval was pinned to commit 6d43fb980f9fee3c892a914eda09951f772ad10d; MBPP to f46ca8374b4cddef97ca4208ad986049d74d296a; EvalPlus to v0.3.1; HumanEval+ to v0.1.10; and MBPP+ to v0.2.0. The same 542 task IDs and order were used for Small-only, Strong-only, and Adaptive. Base and Plus are two scores of each completion, not 1,084 independent observations.

Item	Frozen value	Size/count	Notes
HumanEval+	v0.1.10	164	EvalPlus augmented tests
MBPP+	v0.2.0	378	EvalPlus augmented tests
Tiers	Qwen2.5-Coder	1.5B / 3.1B / 7.6B	FAST / BALANCED / BEST
Sampling	temperature 0; top_p 1	seed 20260824	one thread; 1024 output cap
Verifier	EvalPlus	v0.3.1	Docker network none; 120 s
Resource	CPU 45% / 50%	RAM 45% / 50%	soft / hard process-tree limits

Table 1. Frozen benchmark configuration.

4.2 Generation, resources, and metrics

Temperature was 0, top-p was 1, the seed was 20260824, the context window was 8,192, the output cap was 1,024, and one model thread was used. The machine reported 25,652,355,072 bytes of physical RAM. Resource controls targeted 45% and hard-limited 50% of total CPU capacity and physical RAM. The CPU equivalent in the manifest is only a readability aid, not a fractional CPU assignment. RAM soft and hard limits were 11,543,559,782 and 12,826,177,536 bytes. No cap violation was recorded.

For a tier with frozen parameter value P in billions, generation_cost_proxy = P times output_tokens and total_token_cost_proxy = P times (input_tokens + output_tokens). These are model-size-weighted token cost proxies, not measured FLOPs, hardware compute, energy, API usage, credits, or dollar cost. Physical evidence is measured CPU time/utilization, wall time, RAM, peak RAM, model-load time, inference time, and verification time.

4.3 Fixed budget, statistics, and reproducibility

Before the run, the frozen total-token baseline was B0 = 4,818,407.6 with cutoffs 1,204,601.9, 2,409,203.8, 3,613,805.7, and 4,818,407.6. Every condition exhausted its task list before the first cutoff, so the stored curve is nondiscriminating; condition-relative curves are post-hoc diagnostics. Paired task-level outcomes are retained. The exact two-sided McNemar test was computed after the run and is labeled post-hoc. The historical run retained exact prompts privately, verifier output, and model metadata, but not exact generated programs or generated-program hashes. The McNemar calculation treats the 542 fixed benchmark task pairs as the observational units; no population sampling frame or out-of-benchmark generalization is claimed.

5. Results

5.1 Overall correctness

Condition	HumanEval+	MBPP+	Overall	Macro average
Small-only	26/164 (15.85%)	194/378 (51.32%)	220/542 (40.59%)	33.59%
Strong-only	34/164 (20.73%)	263/378 (69.58%)	297/542 (54.80%)	45.15%
Adaptive	43/164 (26.22%)	288/378 (76.19%)	331/542 (61.07%)	51.20%

Table 2. Primary verified Plus pass rates. Overall is task-weighted; Base and Plus are not independent samples.




Figure 2. Primary verified Plus pass rates. Overall is task-weighted across HumanEval+ and MBPP+.

Adaptive passes 331 of 542 tasks (61.07%), compared with 297 (54.80%) for Strong-only and 220 (40.59%) for Small-only. Equal-benchmark macro averages are 51.20%, 45.15%, and 33.59%, respectively.

5.2 Adaptive versus Strong-only

Adaptive has 34 additional verified Plus successes, a paired risk difference of 6.27 percentage points and a relative increase of 11.45% in successful tasks. There are 297 tasks passing in both conditions, 34 passing only under Adaptive, none passing only under Strong-only, and 211 failing in both. The exact two-sided McNemar p-value is 1.1641532182693481 x 10^-10; this post-hoc statistic does not establish generalization.

Paired outcome	Count
Both pass	297
Adaptive only	34
Strong-only only	0
Both fail	211
Paired risk difference	6.27%
Exact McNemar p (post-hoc)	1.164e-10

Table 4. Paired Adaptive versus Strong-only outcomes.

5.3 Complementarity and escalation

The 34 Adaptive-only successes comprise 22 FAST outputs and 12 BALANCED outputs; BEST contributes zero additional successes. Among all 331 Adaptive successes, 216 (65.26%) ended at FAST, 69 (20.85%) at BALANCED, and 46 (13.90%) at BEST. Thus 285 of 331 successes (86.10%) avoided BEST. This does not mean FAST or BALANCED is stronger overall: the static FAST-versus-BEST comparison has 22 FAST-only passes, 99 BEST-only passes, 198 in both, and 223 failures in both.




Figure 3. Primary paired task outcomes for Adaptive and Strong-only.




Figure 4. Primary source tier for final verified Adaptive successes.

Observed conditional tier overlaps

Observed comparison	n	Both pass	A only	B only	Both fail
FAST vs BALANCED (conditional)	310	0	0	69	241
BALANCED vs BEST (conditional)	240	0	0	41	199
FAST vs BEST static	542	198	22	99	223
Adaptive vs Strong-only	542	297	34	0	211

Table 5. Observed conditional tier overlaps. These rows are not standalone 542-task Balanced or BEST baselines.

5.4 Initial routing

Observed escalation paths were FAST only for 221 tasks, FAST to BALANCED for 70, FAST to BALANCED to BEST for 240, and BEST only for 11. There were 550 escalations. The initial distribution (FAST 531, BALANCED 0, BEST 11) means the experiment strongly tests verification-gated escalation and complementarity, but provides weaker evidence for sophisticated initial predictive routing.




Figure 6. Primary initial Adaptive routing distribution.

5.5 Resource and usage trade-offs

Metric	Adaptive	Strong-only	Relative difference
Plus successes	331	297	+11.45%
Raw input tokens	166,716	78,993	+111.05%
Raw output tokens	93,006	38,507	+141.53%
Raw total tokens	259,722	117,500	+121.04%
Weighted input proxy	579,460.7	600,346.8	-3.48%
Weighted output proxy	320,002.1	292,653.2	+9.35%
Weighted total proxy	899,462.8	893,000.0	+0.72%
CPU seconds	38,137.61	33,421.46	+14.11%
Wall seconds	78,701.93	47,582.32	+65.40%
Peak CPU	47.1225%	46.8875%	+0.235 pp
Peak RAM bytes	6,897,147,346	6,999,388,192	-1.46%
Model calls	1,092	542	+101.48%
Verifier calls	1,091	542	+101.29%

Table 3. Adaptive versus Strong-only expenditure and physical measurements. Weighted values are cost proxies, not hardware compute.



Figure 5. Primary normalized trade-offs. Each bar is a separate ratio to Strong-only; unlike units are not combined.

5.6 Post-hoc diagnostics

Six MBPP tasks generated shared verifier/infrastructure failures in all three conditions: Mbpp/106, Mbpp/124, Mbpp/252, Mbpp/255, Mbpp/580, and Mbpp/720. The primary result retains them in the denominator. Excluding them post-hoc gives Adaptive 331/536 (61.75%), Strong-only 297/536 (55.41%), and Small-only 220/536 (41.04%). The frozen budget curve is nondiscriminating because the first cutoff is at or above every condition's actual expenditure.

6. Analysis

6.1 Why the cascade gains successes

The paired outcomes show that Adaptive retains 297 tasks also solved by Strong-only and adds 34 tasks that Strong-only misses. Deterministic verification accepts a passing FAST or BALANCED completion immediately, so a correct smaller-model output is not discarded merely because a larger model could be invoked. The result is consistent with a union of non-nested correctness sets, not with making BEST more capable.

6.2 Conditional tiers and verification

The static FAST-versus-BEST comparison measures both endpoints for all 542 tasks, while BALANCED and later BEST outcomes are conditional on earlier failures. Those conditional rows are descriptive, not standalone tier accuracy estimates. Verification is an execution gate, not a learned judge. Because no failure message entered a later prompt, this is not failure-feedback repair.

6.3 Efficiency interpretation

Adaptive's 0.72% increase in weighted total-token proxy accompanies a 10.65% increase in successes per proxy unit. Raw tokens, model calls, CPU time, and wall time favor Strong-only more clearly. The weighted input proxy is slightly lower for Adaptive, but output and tier weights make the total proxy slightly higher. These are different quantities; physical measurements remain the primary evidence for hardware efficiency.

7. Limitations

Threat	Treatment in this study
Conditional tiers	Label tier overlaps as observed conditional outcomes; no standalone Balanced baseline is claimed.
Verifier failures	Keep six shared MBPP infrastructure failures in the primary denominator; exclusion is post-hoc.
Budget curve	Preserve frozen B0 and disclose that every condition exhausted before the first cutoff.
Output retention	State that exact historical generated programs were not persisted.
Public benchmark age	Treat contamination as plausible and avoid general-intelligence claims.
Proxy interpretation	Call weighted token values proxies, never FLOPs or generic compute.

Table 6. Threats to validity and treatment.

This is one deterministic run on one Windows machine and one hardware configuration. HumanEval and MBPP are old public benchmarks, so contamination is plausible. One same-family model set was tested. There was no historical Balanced-only condition or fixed-cascade ablation. The router updated statistics online and was not tested frozen on a held-out set. Exact historical generated programs and hashes were not retained. Six shared verifier failures remain in the primary denominator. Frozen B0 cutoffs exceed actual expenditure. Token proxies are not FLOPs, energy, API price, or generic resource use. One deterministic completion per task does not estimate pass@k or variance. Function-level Python tasks do not measure repository-scale engineering or general intelligence.

8. Future Work

Future work should add a complete Balanced-only baseline, a fixed cascade ablation, a frozen-router held-out evaluation, multiple seeds, multiple model families, newer or private coding tasks, and exact private output hashes. Further studies could test deterministic failure-context extraction, compressed failure memory, context-aware escalation, and provider-specific real-cost measurements. Any feedback-driven repair mechanism should be a new condition.

9. Conclusion

In this completed local experiment, verification-gated cascading produced 331 verified Plus successes versus 297 for Strong-only and 220 for Small-only on the same 542 tasks. The 34 Adaptive-only successes came from FAST and BALANCED outputs, not from making BEST more capable. The result is consistent with non-nested task-level correctness and with verification retaining correct smaller-model outputs before escalation.

The expenditure picture is mixed: weighted total-token proxy +0.72% and success-per-proxy +10.65%, but raw tokens, model calls, CPU time, and wall time increase. The defensible conclusion is bounded: this operating point shows a verification-gated local cascade exploiting model complementarity, not universal superiority, a FLOPs saving, or improved model intelligence.

AI assistance disclosure

AI systems, including ChatGPT and Codex, assisted with transforming the author's ideas and recorded results into academic prose, organization, editing, formatting, and code/audit assistance. They did not originate the architecture, research direction, benchmark result, or scientific conclusions. The author reviewed the manuscript and retains responsibility for the research and final version.

References

[1] Chen, M., Tworek, J., Jun, H., Yuan, Q., Ponde de Oliveira Pinto, H., Kaplan, J., Edwards, H., Burda, Y., Joseph, N., Brockman, G., et al. (2021). Evaluating Large Language Models Trained on Code. arXiv:2107.03374.

[2] Austin, J., Odena, A., Nye, M., Bosma, M., Michalewski, H., Dohan, D., Jiang, E., Cai, C., Terry, M., Le, Q., and Sutton, C. (2021). Program Synthesis with Large Language Models. arXiv:2108.07732.

[3] Liu, J., Xia, C. S., Wang, Y., and Zhang, L. (2023). Is Your Code Generated by ChatGPT Really Correct? Rigorous Evaluation of Large Language Models for Code Generation. NeurIPS 36. arXiv:2305.01210.

[4] Chen, L., Zaharia, M., and Zou, J. (2024). FrugalGPT: How to Use Large Language Models While Reducing Cost and Improving Performance. Transactions on Machine Learning Research. arXiv:2305.05176.

[5] Ong, I., Almahairi, A., Wu, V., Chiang, W.-L., Wu, T., Gonzalez, J. E., Kadous, M. W., and Stoica, I. (2025). RouteLLM: Learning to Route LLMs with Preference Data. ICLR 2025. arXiv:2406.18665.

[6] Schuster, T., Fisch, A., Gupta, J., Dehghani, M., Bahri, D., Tran, V. Q., Tay, Y., and Metzler, D. (2022). Confident Adaptive Language Modeling. NeurIPS 35. DOI: 10.52202/068431-1269.

[7] Narasimhan, H., Jitkrittum, W., Rawat, A. S., Kim, S., Gupta, N., Menon, A. K., and Kumar, S. (2025). Faster Cascades via Speculative Decoding. ICLR 2025. arXiv:2405.19261.

[8] Snell, C., Lee, J., Xu, K., and Kumar, A. (2024). Scaling LLM Test-Time Compute Optimally Can Be More Effective than Scaling Model Parameters. arXiv:2408.03314.

[9] Chen, X., Lin, M., Schärli, N., and Zhou, D. (2023). Teaching Large Language Models to Self-Debug. arXiv:2304.05128.

[10] Wang, X., Wei, J., Schuurmans, D., Le, Q. V., Chi, E. H., Narang, S., Chowdhery, A., and Zhou, D. (2023). Self-Consistency Improves Chain of Thought Reasoning in Language Models. ICLR 2023. arXiv:2203.11171.

[11] Leviathan, Y., Kalman, M., and Matias, Y. (2023). Fast Inference from Transformers via Speculative Decoding. ICML 2023, PMLR 202:19274–19286. arXiv:2211.17192.

[12] Zellinger, M. J., Liu, R., and Thomson, M. (2025). Cost-Saving LLM Cascades with Early Abstention. arXiv:2502.09054.

Appendix: audit details

The audit reports 2,176 attempt records from 1,626 completed condition-task cells and zero duplicate attempt keys. It records raw hashes, source hashes, model digests, sampling settings, verification configuration, resource extrema, and one token-telemetry reconciliation. Private prompts, generated programs, raw logs, databases, and model files are absent from the public bundle.

Failure taxonomy: Adaptive has 331 verified passes, 351 model-incorrect, 98 test-failure, 305 timeout, 6 verifier-infrastructure, and 1 resource-blocked record. Strong-only has 297 passes, 105 model-incorrect, 39 test-failure, 95 timeout, and 6 verifier-infrastructure records. Small-only has 220 passes, 184 model-incorrect, 31 test-failure, 101 timeout, and 6 verifier-infrastructure records.