Binary Search

beOI Training



OLYMPIADE BELGE D'INFORMATIQUE BELGISCHE INFORMATICA-OLYMPIADE

April 15, 2016

Table of Contents

Basic algorithm

Other applications

Why do we need it?

Searching a sorted list:

Given a sorted array A, find the index of an element v in this array.

The algorithm

Look at the middle element and compare it with the number you're looking for.

Is it:

- ▶ The same \rightarrow Congratulations!
- ightharpoonup Smaller ightarrow It can only be after this element
- ightharpoonup Bigger ightarrow It can only be before this element

Repeat!

This is a divide-and-conquer algorithm

$$A = \begin{bmatrix} -5 \end{bmatrix} \begin{bmatrix} -3 \end{bmatrix} \begin{bmatrix} 1 \end{bmatrix} \begin{bmatrix} 5 \end{bmatrix} \begin{bmatrix} 10 \end{bmatrix} \begin{bmatrix} 12 \end{bmatrix} \begin{bmatrix} 15 \end{bmatrix} \begin{bmatrix} 20 \end{bmatrix} \begin{bmatrix} 44 \end{bmatrix} \begin{bmatrix} 45 \end{bmatrix}$$
 $v = 12$

$$low = 0$$

 $high = 9$
 $mid = 4$

$$A = \begin{bmatrix} -5 \end{bmatrix} \begin{bmatrix} -3 \end{bmatrix} \begin{bmatrix} 1 \end{bmatrix} \begin{bmatrix} 5 \end{bmatrix} \begin{bmatrix} 10 \end{bmatrix} \begin{bmatrix} 12 \end{bmatrix} \begin{bmatrix} 15 \end{bmatrix} \begin{bmatrix} 20 \end{bmatrix} \begin{bmatrix} 44 \end{bmatrix} \begin{bmatrix} 45 \end{bmatrix}$$
 $v = 12$

$$low = 0$$

 $high = 9$
 $mid = 4$

$$A = \begin{bmatrix} -5 \end{bmatrix} \begin{bmatrix} -3 \end{bmatrix} \begin{bmatrix} 1 \end{bmatrix} \begin{bmatrix} 5 \end{bmatrix} \begin{bmatrix} 10 \end{bmatrix} \begin{bmatrix} 12 \end{bmatrix} \begin{bmatrix} 15 \end{bmatrix} \begin{bmatrix} 20 \end{bmatrix} \begin{bmatrix} 44 \end{bmatrix} \begin{bmatrix} 45 \end{bmatrix}$$
 $v = 12$

$$low = 5$$

 $high = 9$
 $mid = 7$

$$A = \begin{bmatrix} -5 \end{bmatrix}$$
 $\begin{bmatrix} -3 \end{bmatrix}$ $\begin{bmatrix} 1 \end{bmatrix}$ $\begin{bmatrix} 5 \end{bmatrix}$ $\begin{bmatrix} 10 \end{bmatrix}$ $\begin{bmatrix} 12 \end{bmatrix}$ $\begin{bmatrix} 15 \end{bmatrix}$ $\begin{bmatrix} 20 \end{bmatrix}$ $\begin{bmatrix} 44 \end{bmatrix}$ $\begin{bmatrix} 45 \end{bmatrix}$ $v = 12$

low = 5 high = 6mid = 5



What if it's not there?

We just stop when there's no more items to consider $\rightarrow low > high$

The code

```
int binary_search (vector < int > A, int v) {
     int low = 0;
     int high = A.size() - 1;
     while (low <= high) {
       int mid = (low + high)/2;
5
6
7
8
9
       if(A[mid]==v)
        return mid;
       if(A[mid] < v)
         low = mid + 1;
10
       if(A[mid] > v)
11
         high = mid - 1;
12
     return -1; // Not found
14
```

The code

```
int binary_search (vector < int > A, int v) {
     int low = 0:
     int high = A.size() - 1;
     while (low <= high) {
5
6
7
8
9
       int mid = (low + high)/2;
       if(A[mid]==v)
        return mid;
       if(A[mid] < v)
         low = mid + 1;
10
       if(A[mid] > v)
11
         high = mid - 1;
12
13
     return -1; // Not found
14
```

Complexity? $\mathcal{O}(\log(n))$

The devil's in the details

Beware for off-by-one errors when changing boundaries! How to handle duplicate values? Watch out for overflow when computing indices.



Table of Contents

Basic algorithm

Other applications

So...just searching?

Yep, that's it!

So...just searching?

Yep, that's it! Well, not only in an array.

So...just searching?

Yep, that's it! Well, not only in an array. Only condition: static sorted *sequence*

Bisection method

Find a hard root of a function. Binary search on real numbers. Example: $x^3 - 4x - 9 = 0$

The code: iterative

```
double f(double x) {
     return x*x*x - 4*x - 9;
2
3
4
5
   double bisection (double low, double high, double EPS) {
     while(true) { // depends on your problem
       double mid = (low + high)/2;
8
       double val = f(mid);
       if (abs(val) < EPS)
10
          return mid:
       if(val > 0)
         high = mid;
13
       else if (val < 0)
14
         low = mid:
15
16 }
```

The code: recursive

```
double f(double x) {
     return x*x*x - 4*x - 9;
2
3
4
   double bisection (double low, double high, double EPS) {
     double mid = (low + high)/2;
     double val = f(mid);
     if (abs(val) < EPS)
9
       return mid:
10
     if(val > 0)
11
       return bisection (low, mid, EPS);
12
     else if (val < 0)
13
       return bisection (mid, high, EPS);
14
```

Binary search the answer: possibility 1

You don't know how to find the answer directly. BUT: you do know how to check how close you are.



Binary search the answer: possibility 2

You don't know how to find the answer directly. BUT: you do know how to check if it's possible.



$$A = \boxed{0}$$



Table of Contents

Basic algorithm

Other applications

Exercises

- Code a binary search!
- ▶ UVA 11057
- ▶ UVA 10567
- ▶ (UVA 957)
- ▶ UVA 10341
- ▶ UVA 11413
- ▶ UVA 11935
- ▶ UVA 12190 (very tedious!)