

BACKUP STRATEGY :

PREREQUISITES:

- YOU HAVE TO BE CONNECTED AS ROOT ON THE MACHINE



START DOWN

FIRST STEP:

Once connected as Root on our machine, we will create a folder in which we will put the backups of the site and the database, we will name it "Script".

```
cd /home      <-- To move to the home folder on our machine  
mkdir Script <-- Creation of the Script folder
```

We're then going to create a file using the nano command and we're going to inject it with the script we want it to run for the backup we will name it "sauvegarde.sh".

```
cd /home/Script    <-- To move to the Script folder on our machine  
nano sauveragde.sh <-- Creating the backup file
```

Here is the script to inject

```
#!/bin/bash

# Backup script for GLPI and its database :

# Recording the current date :
dateoftheday=$(date +%d-%m-%y-%H.%M.%S)

# Items to be saved :
glpi="/var/www/html"

# Backup destination :
backupdir="/backup"a

# Variable for storing the message content :
email_body=""

# Backing up the GLPI site :
/bin/tar -cjf $backupdir/glpi-$dateoftheday.tar.bz2 $glpi

# Checking the GLPI site backup return code :
if [ $? -eq 0 ]; then
    echo "Backup of GLPI site successfully completed."
    swaks -t leo.gauthier@formation-technologique.fr -s smtp-mail.outlook.com:587 -tls -au testsrvglpi@outlook.fr -ap Azerty1234! -f testsrvglpi@outlook.fr --h-Subject "backup report" --body "Backup of GLPI site successfully completed."
else
    echo "The GLPI site backup encountered an error."
    swaks -t leo.gauthier@formation-technologique.fr -s smtp-mail.outlook.com:587 -tls -au testsrvglpi@outlook.fr -ap Azerty1234! -f testsrvglpi@outlook.fr --h-Subject "backup report" --body "The GLPI site backup encountered an error."
fi

# GLPI database backup
mysqldump --user=glpiuser --password=password --databases bddglpi | /usr/bin/gzip > $backupdir/sqlglpi-$dateoftheday.sql.gz

# Checking the return code of the GLPI database backup
if [ $? -eq 0 ]; then
    echo "GLPI database backup successfully completed."
    swaks -t leo.gauthier@formation-technologique.fr -s smtp-mail.outlook.com:587 -tls -au testsrvglpi@outlook.fr -ap Azerty1234! -f testsrvglpi@outlook.fr --h-Subject "backup report" --body "GLPI database backup successfully completed successfully."
else
    echo "GLPI database backup encountered an error."
    swaks -t leo.gauthier@formation-technologique.fr -s smtp-mail.outlook.com:587 -tls -au testsrvglpi@outlook.fr -ap Azerty1234! -f testsrvglpi@outlook.fr --h-Subject "backup report" --body "GLPI database backup encountered an error."
fi
```

You need to change the password, the user name, the name of the database and the e-mail address to which you want the backup to send you the report.



SECOND STEP:

PLAN A TASK USING CRON

First, we need to check that cron is installed on the machine, and if not, install it using the command :
apt install cron.

Next, to schedule the task, we're going to use the command :
crontab -e.

Once the command has been executed, we access the cron interface where we'll tell it to run our script every Friday at 8pm. To tell it to execute, you need to do the following implementation :
0 20 * * 5 bash /script/sauvegarde.sh

The GLPI site directory, specified by the glpi variable, is backed up by creating a compressed archive in tar.bz2 format, and the GLPI database is backed up using the mysqldump command, and the backup file is compressed in gzip format.

This backup guarantees the integrity of the data, because it does not disrupt the company's operations when the backup is carried out outside working hours.



START DOWN

☎ 04 90 01 02 03

60 Chem. de Fontanille, 84140 Avignon

Lundi-Vendredi 8:30-17:00