NAME

```
strdup, strndupa, strndupa - duplicate a string
```

SYNOPSIS

_POSIX_C_SOURCE >= 200809L || _XOPEN_SOURCE >= 700

DESCRIPTION

Since glibc 2.10:

Before glibc 2.10:

_GNU_SOURCE strdupa(), strndupa(): _GNU_SOURCE

The **strdup**() function returns a pointer to a new string which is a duplicate of the string s. Memory for the new string is obtained with **malloc**(3), and can be freed with **free**(3).

The **strndup**() function is similar, but copies at most n bytes. If s is longer than n, only n bytes are copied, and a terminating null byte ($\0$) is added.

strdupa() and **strndupa**() are similar, but use **alloca**(3) to allocate the buffer. They are available only when using the GNU GCC suite, and suffer from the same limitations described in **alloca**(3).

RETURN VALUE

On success, the **strdup**() function returns a pointer to the duplicated string. It returns NULL if insufficient memory was available, with *errno* set to indicate the cause of the error.

ERRORS

ENOMEM

Insufficient memory available to allocate duplicate string.

CONFORMING TO

strdup() conforms to SVr4, 4.3BSD, POSIX.1-2001. **strndup**() conforms to POSIX.1-2008. **strdupa**() and **strndupa**() are GNU extensions.

SEE ALSO

```
alloca(3), calloc(3), free(3), malloc(3), realloc(3), string(3), wcsdup(3)
```

COLOPHON

This page is part of release 3.74 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at http://www.kernel.org/doc/man-pages/.