

NAME

`errno` – number of last error

SYNOPSIS

```
#include <errno.h>
```

DESCRIPTION

The `<errno.h>` header file defines the integer variable `errno`, which is set by system calls and some library functions in the event of an error to indicate what went wrong. Its value is significant only when the return value of the call indicated an error (i.e., `-1` from most system calls; `-1` or `NULL` from most library functions); a function that succeeds *is* allowed to change `errno`.

Valid error numbers are all nonzero; `errno` is never set to zero by any system call or library function.

For some system calls and library functions (e.g., `getpriority(2)`), `-1` is a valid return on success. In such cases, a successful return can be distinguished from an error return by setting `errno` to zero before the call, and then, if the call returns a status that indicates that an error may have occurred, checking to see if `errno` has a nonzero value.

`errno` is defined by the ISO C standard to be a modifiable lvalue of type `int`, and must not be explicitly declared; `errno` may be a macro. `errno` is thread-local; setting it in one thread does not affect its value in any other thread.

All the error names specified by POSIX.1 must have distinct values, with the exception of **EAGAIN** and **EWouldBlock**, which may be the same.

Below is a list of the symbolic error names that are defined on Linux. Some of these are marked *POSIX.1*, indicating that the name is defined by POSIX.1-2001, or *C99*, indicating that the name is defined by C99.

E2BIG	Argument list too long (POSIX.1).
EACCES	Permission denied (POSIX.1).
EADDRINUSE	Address already in use (POSIX.1).
EADDRNOTAVAIL	Address not available (POSIX.1).
EAfnosupport	Address family not supported (POSIX.1).
EAGAIN	Resource temporarily unavailable (may be the same value as EWouldBlock) (POSIX.1).
EALREADY	Connection already in progress (POSIX.1).
EBADe	Invalid exchange.
EBADF	Bad file descriptor (POSIX.1).
EBADFD	File descriptor in bad state.
EBADMSG	Bad message (POSIX.1).
EBADR	Invalid request descriptor.
EBADRQC	Invalid request code.
EBADSLT	Invalid slot.
EBUSY	Device or resource busy (POSIX.1).
ECANCELED	Operation canceled (POSIX.1).
ECHILD	No child processes (POSIX.1).

ECHRNG	Channel number out of range.
ECOMM	Communication error on send.
ECONNABORTED	Connection aborted (POSIX.1).
ECONNREFUSED	Connection refused (POSIX.1).
ECONNRESET	Connection reset (POSIX.1).
EDEADLK	Resource deadlock avoided (POSIX.1).
EDEADLOCK	Synonym for EDEADLK .
EDESTADDRREQ	Destination address required (POSIX.1).
EDOM	Mathematics argument out of domain of function (POSIX.1, C99).
EDQUOT	Disk quota exceeded (POSIX.1).
EEXIST	File exists (POSIX.1).
EFAULT	Bad address (POSIX.1).
EFBIG	File too large (POSIX.1).
EHOSTDOWN	Host is down.
EHOSTUNREACH	Host is unreachable (POSIX.1).
EIDRM	Identifier removed (POSIX.1).
EILSEQ	Invalid or incomplete multibyte or wide character (POSIX.1, C99).
	The text shown here is the glibc error description; in POSIX.1, this error is described as "Illegal byte sequence".
EINPROGRESS	Operation in progress (POSIX.1).
EINTR	Interrupted function call (POSIX.1); see signal(7) .
EINVAL	Invalid argument (POSIX.1).
EIO	Input/output error (POSIX.1).
EISCONN	Socket is connected (POSIX.1).
EISDIR	Is a directory (POSIX.1).
EISNAM	Is a named type file.
EKEYEXPIRED	Key has expired.
EKEYREJECTED	Key was rejected by service.
EKEYREVOKED	Key has been revoked.
EL2HLT	Level 2 halted.
EL2NSYNC	Level 2 not synchronized.
EL3HLT	Level 3 halted.
EL3RST	Level 3 halted.
ELIBACC	Cannot access a needed shared library.

ELIBBAD	Accessing a corrupted shared library.
ELIBMAX	Attempting to link in too many shared libraries.
ELIBSCN	.lib section in a.out corrupted
ELIBEXEC	Cannot exec a shared library directly.
ELOOP	Too many levels of symbolic links (POSIX.1).
EMEDIUMTYPE	Wrong medium type.
EMFILE	Too many open files (POSIX.1). Commonly caused by exceeding the RLIMIT_NOFILE resource limit described in getrlimit(2) .
EMLINK	Too many links (POSIX.1).
EMSGSIZE	Message too long (POSIX.1).
EMULTIHOP	Multihop attempted (POSIX.1).
ENAMETOOLONG	Filename too long (POSIX.1).
ENETDOWN	Network is down (POSIX.1).
ENETRESET	Connection aborted by network (POSIX.1).
ENETUNREACH	Network unreachable (POSIX.1).
ENFILE	Too many open files in system (POSIX.1). On Linux, this is probably a result of encountering the <i>/proc/sys/fs/file-max</i> limit (see proc(5)).
ENOBUFS	No buffer space available (POSIX.1 (XSI STREAMS option)).
ENODATA	No message is available on the STREAM head read queue (POSIX.1).
ENODEV	No such device (POSIX.1).
ENOENT	No such file or directory (POSIX.1). Typically, this error results when a specified pathname does not exist, or one of the components in the directory prefix of a pathname does not exist, or the specified pathname is a dangling symbolic link.
ENOEXEC	Exec format error (POSIX.1).
ENOKEY	Required key not available.
ENOLCK	No locks available (POSIX.1).
ENOLINK	Link has been severed (POSIX.1).
ENOMEDIUM	No medium found.
ENOMEM	Not enough space (POSIX.1).
ENOMSG	No message of the desired type (POSIX.1).
ENONET	Machine is not on the network.
ENOPKG	Package not installed.
ENOPROTOPT	Protocol not available (POSIX.1).
ENOSPC	No space left on device (POSIX.1).
ENOSR	No STREAM resources (POSIX.1 (XSI STREAMS option)).

ENOSTR	Not a STREAM (POSIX.1 (XSI STREAMS option)).
ENOSYS	Function not implemented (POSIX.1).
ENOTBLK	Block device required.
ENOTCONN	The socket is not connected (POSIX.1).
ENOTDIR	Not a directory (POSIX.1).
ENOTEMPTY	Directory not empty (POSIX.1).
ENOTSOCK	Not a socket (POSIX.1).
ENOTSUP	Operation not supported (POSIX.1).
ENOTTY	Inappropriate I/O control operation (POSIX.1).
ENOTUNIQ	Name not unique on network.
ENXIO	No such device or address (POSIX.1).
EOPNOTSUPPORT	Operation not supported on socket (POSIX.1).
	(ENOTSUP and EOPNOTSUPPORT have the same value on Linux, but according to POSIX.1 these error values should be distinct.)
EOVERFLOW	Value too large to be stored in data type (POSIX.1).
EPERM	Operation not permitted (POSIX.1).
EPFNOSUPPORT	Protocol family not supported.
EPIPE	Broken pipe (POSIX.1).
EPROTO	Protocol error (POSIX.1).
EPROTONOSUPPORT	Protocol not supported (POSIX.1).
EPROTOTYPE	Protocol wrong type for socket (POSIX.1).
ERANGE	Result too large (POSIX.1, C99).
EREMCHG	Remote address changed.
EREMOTE	Object is remote.
EREMOTEIO	Remote I/O error.
ERESTART	Interrupted system call should be restarted.
EROFS	Read-only filesystem (POSIX.1).
ESHUTDOWN	Cannot send after transport endpoint shutdown.
ESPIPE	Invalid seek (POSIX.1).
ESOCKTNOSUPPORT	Socket type not supported.
ESRCH	No such process (POSIX.1).
ESTALE	Stale file handle (POSIX.1).
	This error can occur for NFS and for other filesystems.
ESTRPIPE	Streams pipe error.
ETIME	Timer expired. (POSIX.1 (XSI STREAMS option))
	(POSIX.1 says "STREAM ioctl (2) timeout")

ETIMEDOUT	Connection timed out (POSIX.1).
ETXTBSY	Text file busy (POSIX.1).
EUCLEAN	Structure needs cleaning.
EUNATCH	Protocol driver not attached.
EUSERS	Too many users.
EWOULDBLOCK	Operation would block (may be same value as EAGAIN) (POSIX.1).
EXDEV	Improper link (POSIX.1).
EXFULL	Exchange full.

NOTES

A common mistake is to do

```
if(somecall() == -1) {
    printf("somecall() failed\n");
    if (errno == ...) { ... }
}
```

where *errno* no longer needs to have the value it had upon return from *somecall()* (i.e., it may have been changed by the **printf(3)**). If the value of *errno* should be preserved across a library call, it must be saved:

```
if(somecall() == -1) {
    int errsv = errno;
    printf("somecall() failed\n");
    if (errsv == ...) { ... }
}
```

It was common in traditional C to declare *errno* manually (i.e., *extern int errno*) instead of including *<errno.h>*. **Do not do this.** It will not work with modern versions of the C library. However, on (very) old UNIX systems, there may be no *<errno.h>* and the declaration is needed.

SEE ALSO

errno(1), **err(3)**, **error(3)**, **perror(3)**, **strerror(3)**

COLOPHON

This page is part of release 4.09 of the Linux *man-pages* project. A description of the project, information about reporting bugs, and the latest version of this page, can be found at <https://www.kernel.org/doc/man-pages/>.